

XAMPP是最流行的PHP开发环境

XAMPP是完全免费且易于安装的Apache发行版，其中包含MariaDB、PHP和Perl。XAMPP开放源码包的设置让安装和使用出奇容易。

网址：[https://www.apachefriends.org/zh\\_cn/index.html](https://www.apachefriends.org/zh_cn/index.html)

首先找到自己需要安装的版本下载地址。

1, root用户登录系统，不是root用户的，用su命令切换下

```
-bash: yangxiaoyi: command not found
[root@iZ23apoleerZ ~]#
```

[http://blog.csdn.net/hong\\_rui](http://blog.csdn.net/hong_rui)

2. 下载安装，linux系统下，可以使用 wget -c 加下载地址，这里是下载的.run格式。

```
[root@iZ23apoleerZ /]# wget -c http://jaist.dl.sourceforge.net/project/xampp/XAMPP%20Linux/1.8.3/xampp-linux-1.8.3-5-installer.run
-bash: wget: command not found
[root@iZ23apoleerZ /]# widget -c http://jaist.dl.sourceforge.net/project/xampp/XAMPP%20Linux/1.8.3/xampp-linux-1.8.3-5-installer.run
-bash: widget: command not found
[root@iZ23apoleerZ /]# wget -c http://jaist.dl.sourceforge.net/project/xampp/XAMPP%20Linux/1.8.3/xampp-linux-1.8.3-5-installer.run
--2014-10-30 15:16:24-- http://jaist.dl.sourceforge.net/project/xampp/XAMPP%20Linux/1.8.3/xampp-linux-1.8.3-5-installer.run
Resolving jaist.dl.sourceforge.net... 150.65.7.130, 2001:df0:2ed:feed::feed
Connecting to jaist.dl.sourceforge.net|150.65.7.130|:80... connected.
HTTP request sent, awaiting response... 200 OK
Length: 125079104 (119M) [application/x-makeself]
Saving to: ? . ampp-linux-1.8.3-5-installer.run?

25% [=====>] 31,760,824 248K/s eta 5m 31s
```

```
[root@iZ23apoleerZ download]# ls
xampp-linux-1.8.3-5-installer.run
[root@iZ23apoleerZ download]#
```

下载完成

[http://blog.csdn.net/hong\\_rui](http://blog.csdn.net/hong_rui)

3. XAMPP文件下载好，切换到文件的存放目录，输入命令:ls查看文件是否存在，接着输入安装命令，如图所示进行安装：

```
[root@iZ23apoleerZ download]# clear
[root@iZ23apoleerZ download]# ls
xampp-linux-1.8.3-5-installer.run
[root@iZ23apoleerZ download]# chmod +x xampp-linux-1.8.3-5-installer.run
[root@iZ23apoleerZ download]# ./xampp-linux-1.8.3-5-installer.run

Welcome to the XAMPP Setup Wizard.

-----
Select the components you want to install; clear the components you do not want
to install. Click Next when you are ready to continue.

XAMPP Core Files : Y (Cannot be edited)
XAMPP Developer Files [Y/n] :y
Is the selection above correct? [Y/n]: y

-----
Installation Directory

XAMPP will be installed to /opt/lampp
Press [Enter] to continue:enter

-----
Setup is now ready to begin installing XAMPP on your computer.
Do you want to continue? [Y/n]: y

-----http://blog.esdn.net/hong_rui
```

4. 直到进度条走完，显示安装完成，进入安装目录，由于上面默认安装，安装目录在/opt/lampp下，然后打开看看情况：

```
XAMPP Developer Files [Y/n]: y

Is the selection above correct? [Y/n]: y

-----
Installation Directory

XAMPP will be installed to /opt/lampp
Press [Enter] to continue:enter

-----
Setup is now ready to begin installing XAMPP on your computer.

Do you want to continue? [Y/n]: y

-----
Please wait while Setup installs XAMPP on your computer.

Installing
0% _____ 50% _____ 100%
#####

cgi-bin      docroot      manager-linux.run  properties.ini  xampp
ctlscript.sh info         manual           RELEASENOTES
docs         lampp        modules          php
errors       lib          mysql            phpmyadmin
etc          libexec      perl             perl
[root@iZ23apoleerZ lampp]#
```

[http://blog.csdn.net/hong\\_rui](http://blog.csdn.net/hong_rui)

5. 运行命令/opt/lampp/lampp start 启动web服务器，从图中可以看到apache、mysql、ftp服务都启动OK了。

```
[root@iZ23apoleerZ ~]# /opt/lampp/lampp start
Starting XAMPP for Linux 1.8.3-5...
XAMPP: Starting Apache...ok.
XAMPP: Starting MySQL...ok.
XAMPP: Starting ProFTPD...ok.
[root@iZ23apoleerZ ~]#
```

[http://blog.csdn.net/hong\\_rui](http://blog.csdn.net/hong_rui)