## HIT — Cryptography — Homework 2

## November 18, 2015

- **Problem 1.** Assuming the existence of a variable output-length pseudorandom generator, present a construction of variable-length encryption scheme, and prove that your construction has indistinguishable encryptions in the presence of an eavesdropper. Hint: the construction of secure fixed-length encryption scheme also holds here.
- **Problem 2.** Assuming the existence of a pseudorandom function, prove that there exists an encryption scheme that has indistinguishable multiple encryptions in the presence of an eavesdropper, but is not CPA-secure. Hint: You will need to use the fact that in a CPA the adversary can choose its queries to the encryption oracle adaptively (i.e., new query may be constructed from previous queries).
- **Problem 3.** Present formulas for decryption of all the different modes of operation for encryption: ECB, CBC, OFB, CTR. For which modes can decryption be parallelized?
- **Problem 4.** Present a construction of a variable output-length pseudorandom generator from any pseudorandom function. Prove that your construction satisfies Definition: 'a variable output-length pseudorandom generator'.
- **Problem 5.** Show that the CBC mode do not yield CPA-secure encryption in the case that the IV is predicable. Hint: The messages presented by the adversary could be constructed from the predicable IV and previous queries.
- **Problem 6.** Show that the CBC, OFB and CTR modes do not yield CCA-secure encryption schemes (regardless of F). Hint: If one bit of Ciphertext is flipped, so does one bit of Plaintext.