## Assignment 3: Database Design (Spring 2019)

Instructor: Zhaonian Zou (znzou@hit.edu.cn)

Name:	Student ID:	Grade:
ranic.	Student 1D.	Grade.

Question	1	2(a)	2(b)	2(c)	2(d)	2(e)	3(a)	3(b)	3(c)	3(d)	3(e)	4	Total
Score													

## Notes

- Print the assignment on A4 paper and answer the questions.
- Assignment due date: April 3, 2019.

## Questions

1. (2 Points) Given the database schema R(A,B,C), and a relation r on the schema R, write an SQL query to test whether the functional dependency  $B \to C$  holds on relation r (the query returns 1 if  $B \to C$  holds on r and 0 otherwise). Hint: the following SQL query returns 1 if its result is non-empty; otherwise, it returns 0.

- 2. (10 Points) Prove or disprove the following inference rules for functional dependencies. A proof can be made by using Armstrong's axioms. A disproof should be performed by demonstrating a relation instance that satisfies the conditions and functional dependencies in the left-hand side of the inference rule but does not satisfy the dependencies in the right-hand side.
  - (a) (2 Points)  $\{W \to Y, X \to Z\} \models \{WX \to Y\}$
  - (b) (2 Points)  $\{X \to Y, X \to W, WY \to Z\} \models \{X \to Z\}$
  - (c) (2 Points)  $\{X \to Z, Y \to Z\} \models \{X \to Y\}$
  - (d) (2 Points)  $\{X \to Y, Z \to W\} \models \{XZ \to YW\}$
  - (e) (2 Points)  $\{X \to Y, Y \to Z\} \models \{X \to YZ\}$
- 3. (15 Points) Consider the following set F of functional dependencies on the relation schema R(A, B, C, D, E):

$$A \rightarrow B$$

$$A \to C$$

$$BC \to A$$

$$CD \to E$$

$$B \to D$$

$$E \to A$$

Answer the following questions:

- (a) (3 Points) Compute  $(BC)_F^+$ .
- (b) (3 Points) List the candidate keys for R. Prove that they are candidate keys using Armstrong's axioms.
- (c) (3 Points) Compute a canonical cover for F; give each step of your derivation with an explanation.
- (d) (3 Points) Suppose that R is decomposed into  $R_1(A, B, C)$  and  $R_2(C, D, E)$ . Show that this decomposition is not a lossless decomposition. Hint: Give an example of a relation r on schema R such that

$$\Pi_{A,B,C}(r) \bowtie \Pi_{C,D,E}(r) \neq r.$$

- (e) (3 Points) Give a 3NF decomposition of R based on the canonical cover for F.
- 4. (3 Points) Let  $R_1(U_1), R_2(U_2), \ldots, R_n(U_n)$  be a decomposition of schema R(U). Let r be a relation on schema R, and let  $r_i = \Pi_{U_i}(r)$ . Show that

$$r \subseteq r_1 \bowtie r_2 \bowtie \cdots \bowtie r_n$$
.

## Answers