



Chapter 5: Reusability-Oriented Software Construction Approaches

5.3 Design Patterns for Reuse

Ming Liu

April 3, 2018

Outline



■ Structural patterns

- **Adapter** allows classes with incompatible interfaces to work together by wrapping its own interface around that of an already existing class.
- **Decorator** dynamically adds/overrides behavior in an existing method of an object.
- **Facade** provides a simplified interface to a large body of code.

■ Behavioral patterns

- **Strategy** allows one of a family of algorithms to be selected on-the-fly at runtime.
- **Template method** defines the skeleton of an algorithm as an abstract class, allowing its subclasses to provide concrete behavior.
- **Iterator** accesses the elements of an object sequentially without exposing its underlying representation.

Recall: Why reusable Designs?



A design...

...enables flexibility to change (reusability)

...minimizes the introduction of new problems when fixing old ones (maintainability)

...allows the delivery of more functionality after an initial delivery (extensibility).



1 Structural patterns






(1) Adapter




Adapter Pattern

- **Intent:** Convert the interface of a class into another interface clients expect.
 - Adapter lets classes work together that couldn't otherwise because of incompatible interfaces.
 - Wrap an existing class with a new interface.
- **Object:** to reuse an old component to a new system (also called “wrapper”)



Example

- A legacy Rectangle component's `display()` method expects to receive "x, y, w, h" parameters.
- But the client wants to pass "upper left x and y" and "lower right x and y".
- This incongruity can be reconciled by adding an additional level of indirection – i.e. an Adapter object.





(2) Decorator



Motivating example of Decorator pattern

- **Suppose you want various extensions of a Stack data structure...**

- UndoStack: A stack that lets you undo previous push or pop operations
- SecureStack: A stack that requires a password
- SynchronizedStack: A stack that serializes concurrent accesses

Inheritance


- **And arbitrarily composable extensions:**

- SecureUndoStack: A stack that requires a password, and also lets you undo previous operations
- SynchronizedUndoStack: A stack that serializes concurrent accesses, and also lets you undo previous operations
- SecureSynchronizedStack: ...
- SecureSynchronizedUndoStack: ...

Inheritance
hierarchies?
Multi-Inheritance?

Decorator

- **Problem:** You need arbitrary or dynamically composable extensions to individual objects.
- **Solution:** Implement a common interface as the object you are extending, add functionality, but delegate primary responsibility to an underlying object.
- **Consequences:**
 - More flexible than static inheritance
 - Customizable, cohesive extensions
- **Decorators use both subtyping and delegation**



The AbstractStackDecorator Class

```
public abstract class AbstractStackDecorator implements Stack {
    private final Stack stack;
    public AbstractStackDecorator(Stack stack) {
        this.stack = stack;
    }
    public void push(Item e) {
        stack.push(e);
    }
    public Item pop() {
        return stack.pop();
    }
    ...
}
```

The concrete decorator classes

```
public class UndoStack
    extends AbstractStackDecorator
    implements Stack {

    private final UndoLog log = new UndoLog();
    public UndoStack(Stack stack) {
        super(stack);
    }
    public void push(Item e) {
        log.append(UndoLog.PUSH, e);
        super.push(e);
    }
    ...
}
```

Using the decorator classes

- To construct a plain stack:
 - `Stack s = new ArrayStack();`
- To construct an undo stack:
 - `UndoStack s = new UndoStack(new ArrayStack());`
- To construct a secure synchronized undo stack:
 - `SecureStack s = new SecureStack(
 new SynchronizedStack(
 new UndoStack(s))`
- **Flexibly Composable!**

Decorator vs. Inheritance

- **Decorator composes features at run time**
 - Inheritance composes features at compile time
- **Decorator consists of multiple collaborating objects**
 - Inheritance produces a single, clearly-typed object
- **Can mix and match multiple decorations**
 - Multiple inheritance is conceptually difficult

Decorators from `java.util.Collections`

- **Turn a mutable list into an immutable list:**

- `static List<T> unmodifiableList(List<T> lst);`
- `static Set<T> unmodifiableSet(Set<T> set);`
- `static Map<K,V> unmodifiableMap(Map<K,V> map);`

- **Similar for synchronization:**

- `static List<T> synchronizedList(List<T> lst);`
- `static Set<T> synchronizedSet(Set<T> set);`
- `static Map<K,V> synchronizedMap(Map<K,V> map);`



(3) Facade



Facade



■ Problem

- A segment of the client community needs a simplified interface to the overall functionality of a complex subsystem.


■ Intent

- Provide a unified interface to a set of interfaces in a subsystem. Facade defines a higher-level interface that makes the subsystem easier to use.
- Wrap a complicated subsystem with a simpler interface.

■ This reduces the learning curve necessary to successfully leverage the subsystem.

■ It also promotes decoupling the subsystem from its potentially many clients.

Facade





2 Behavioral patterns






(1) Strategy




Strategy Pattern

- **Problem:** Different algorithms exist for a specific task, but client can switch between the algorithms at run time in terms of dynamic context.
- **Example:** Sorting a list of customers (Bubble sort, mergesort, quicksort)
- **Solution:** Create an interface for the algorithm, with an implementing class for each variant of the algorithm.
- **Advantage:**
 - Easily extensible for new algorithm implementations
 - Separates algorithm from client context


Strategy Pattern



Code example



Code example






Code example

```
public class ShoppingCart {
    ...
    public void pay(PaymentStrategy paymentMethod){
        int amount = calculateTotal();
        paymentMethod.pay(amount);
    }
}
```

```
public interface PaymentStrategy {
    public void pay(int amount);
}
```

pay(PaymentStrategy):void

~items 0..*



```
public class PaypalStrategy implements PaymentStrategy {
    private String emailId;
    private String password;
    public PaypalStrategy(String email, String pwd){
        this.emailId=email;
        this.password=pwd;
    }
    @Override
    public void pay(int amount) {
        System.out.println(amount + " paid using Paypal.");
    }
}
```

Code example

```
public class ShoppingCart {
    ...
    public void pay(PaymentStrategy paymentMethod){
        int amount = calculateTotal();
        paymentMethod.pay(amount);
    }
}
```

```
public interface PaymentStrategy {
    public void pay(int amount);
}
```

```
interface>>
PaymentStrategy
design.strategy
void
```

```
pay(PaymentStrategy):void
```

```
<<Java Class>>
```

```
<<Java Class>>
```

```
public class ShoppingCartTest {
    public static void main(String[] args) {
        ShoppingCart cart = new ShoppingCart();
        Item item1 = new Item("1234",10);
        Item item2 = new Item("5678",40);
        cart.addItem(item1);
        cart.addItem(item2);
        //pay by paypal
        cart.pay(new PaypalStrategy("myemail@exp.com", "mypwd"));
        //pay by credit card
        cart.pay(new CreditCardStrategy("Alice", "1234", "786", "12/18"));
    }
}
```

```
com.
```

```
U
```

```
p
```

```
Item
```

```
g
```

```
g
```



(2) Template Method



Template Method Motivation


- **Problem:** Several clients share the same algorithm but differ on the specifics, i.e., an algorithm consists of customizable parts and invariant parts. **Common steps should not be duplicated in the subclasses but need to be reused.**
- **Examples:**
 - Executing a test suite of test cases
 - Opening, reading, writing documents of different types
- **Solution:**
 - The common steps of the algorithm are factored out into an abstract class, with abstract (unimplemented) primitive operations representing the customizable parts of the algorithm.
 - Subclasses provide different realizations for each of these steps.

```
step1();  
...  
step2();  
...  
step3();
```

Template Method Pattern Applicability

- **Template method** pattern uses inheritance + overridable methods to **vary part of an algorithm**
 - While strategy pattern uses delegation to vary the entire algorithm (interface and ad-hoc polymorphism).
- **Template Method is widely used in frameworks**
 - The framework implements the invariants of the algorithm
 - The client customizations provide specialized steps for the algorithm
 - Principle: “Don’t call us, we’ll call you”.

Template Method pattern





(3) Iterator




Iterator Pattern

- **Problem:** Clients need uniform strategy to access all elements in a container, independent of the container type
- **Solution:** A strategy pattern for iteration
- **Consequences:**
 - Hides internal implementation of underlying container
 - Support multiple traversal strategies with uniform interface
 - Easy to change container type
 - Facilitates communication between parts of the program

Iterator Pattern

■ Pattern structure

- Abstract Iterator class defines traversal protocol
- Concrete Iterator subclasses for each aggregate class
- Aggregate instance creates instances of Iterator objects
- Aggregate instance keeps reference to Iterator object



Getting an Iterator

```
public interface Collection<E> extends Iterable<E> {  
    boolean add(E e);  
    boolean addAll(Collection<? extends E> c);  
    boolean remove(Object e);  
    boolean removeAll(Collection<?> c);  
    boolean retainAll(Collection<?> c);  
    boolean contains(Object e);  
    boolean containsAll(Collection<?> c);  
    void clear();  
    int size();  
    boolean isEmpty();  
    Iterator<E> iterator();  
    Object[] toArray()  
    <T> T[] toArray(T[] a);  
    ...  
}
```

Defines an interface for creating an Iterator, but allows Collection implementation to decide which Iterator to create.

An example of Iterator pattern

```
public class Pair<E> implements Iterable<E> {
    private final E first, second;
    public Pair(E f, E s) { first = f; second = s; }
    public Iterator<E> iterator() {
        return new PairIterator();
    }

    private class PairIterator implements Iterator<E> {
        private boolean seenFirst = false, seenSecond = false;
        public boolean hasNext() { return !seenSecond; }
        public E next() {
            if (!seenFirst) { seenFirst = true; return first; }
            if (!seenSecond) { seenSecond = true; return second; }
            throw new NoSuchElementException();
        }
        public void remove() {
            throw new UnsupportedOperationException();
        }
    }
}
```

```
Pair<String> pair = new Pair<String>("foo", "bar");
for (String s : pair) { ... }
```



High-level Considerations on Design Patterns for Reusability



Clues for use of Design Patterns (1)

- **Text: “manufacturer independent”, “device independent”, “must support a family of products”**
=> Abstract Factory Pattern
- **Text: “must interface with an existing object”**
=> Adapter Pattern
- **Text: “must interface to several systems, some of them to be developed in the future”, “an early prototype must be demonstrated”**
=> Bridge Pattern
- **Text: “must interface to existing set of objects”**
=> Façade Pattern

Clues for use of Design Patterns (2)

- **Text: “complex structure”, “must have variable depth and width”**
=> Composite Pattern
- **Text: “must be location transparent”**
=> Proxy Pattern
- **Text: “must be extensible”, “must be scalable”**
=> Observer Pattern
- **Text: “must provide a policy independent from the mechanism”**
=> Strategy Pattern

Summary

- **Composite, Adapter, Bridge, Façade, Proxy (Structural Patterns)**
 - Focus: Composing objects to form larger structures
 - Realize new functionality from old functionality,
 - Provide flexibility and extensibility
- **Command, Observer, Strategy, Template (Behavioral Patterns)**
 - Focus: Algorithms and assignment of responsibilities to objects
 - Avoid tight coupling to a particular solution
- **Abstract Factory, Builder (Creational Patterns)**
 - Focus: Creation of complex objects
 - Hide how complex objects are created and put together



Summary





The end

April 3, 2018