

Integrated Modular Avionics – Individual Work – Data description

Dataset: *B(E)3(9)M38IMA_Data_Individual_Semester_Work.mat*

Sampling frequency - IMU - 200 Hz

Sampling frequency - uBlox GPS - 5 Hz

Sampling frequency - Geodetical GNSS - 10 Hz – X91+ GNSS receiver (CHC)

Data structure:

Inertial data + temperature:

- 01 - counter
- 02 - time [ms] from start of the program
- 03 - DMU10 acceleration X – (g) – longitudinal
- 04 - DMU10 delta acceleration X – (g)
- 05 - DMU10 acceleration Y – (g) – lateral
- 06 - DMU10 delta acceleration Y – (g)
- 07 - DMU10 acceleration Z – (g) – vertical
- 08 - DMU10 delta acceleration Z – (g)
- 09,10 - Zeros
- 11 - DMU10 rate X – (°/s) - longitudinal
- 12 - DMU10 delta rate X – (°/s)
- 13 - DMU10 rate Y – (°/s) – lateral
- 14 - DMU10 delta rate Y – (°/s)
- 15 - DMU10 rate Z – (°/s) – vertical
- 16 - DMU10 delta rate Z – (°/s)

uBlox GPS data – absolute position, based only on receiver

- 17 - uBlox GPS time (s)
- 18 - uBlox GPS fix & valid (LSB = fix, MSB = valid)
- 19 - uBlox GPS number of satellites (-)
- 20 - uBlox GPS latitude (°)
- 21 - uBlox GPS longitude (°)
- 22 - uBlox GPS altitude (m)
- 23 - uBlox GPS speed over ground (m/s)
- 24 - uBlox GPS VDOP (-)
- 25 - uBlox GPS HDOP (-)
- 26 - uBlox GPS PDOP (-)
- 27 - uBlox GPS NED velocity down (m/s)
- 28 - uBlox GPS NED velocity north (m/s)
- 29 - uBlox GPS NED velocity east (m/s)
- 30 - uBlox GPS heading (°)
- 31 - uBlox GPS date (may be wrong by one day because of SD parser error) (-)

uBlox NEO-6P GPS receiver – (uBlox NEO-6P receiver 2 Base station Pribram)

- 32 - uBlox RTK GPS time (s)
- 33 - uBlox RTK GPS latitude (°)
- 34 - uBlox RTK GPS longitude (°)
- 35 - uBlox RTK GPS altitude (m)
- 36 - uBlox RTK GPS fix & valid (5 = single, 2 = float, 1 = fix)
- 37 - uBlox RTK GPS number of satellites (-)
- 38 - uBlox RTK standard deviation - north (m)

- 39 - uBlox RTK standard deviation - east (m)
- 40 - uBlox RTK standard deviation - up (m)
- 41 - uBlox RTK standard deviation – north-east (m)
- 42 - uBlox RTK standard deviation – east-up (m)
- 43 - uBlox RTK standard deviation – up-north (m)
- 44 - uBlox RTK age (s)
- 45 - uBlox RTK ratio (-)

Geodetic X91+ GNSS receiver – Results based on RTKLIB (Geodetic receiver 2 Base station Pribram)

- 46 - Reference RTK GPS time (s)
- 47 - Reference RTK GPS latitude (°)
- 48 - Reference RTK GPS longitude (°)
- 49 - Reference RTK GPS altitude (m)
- 50 - Reference RTK GPS fix & valid (5 = single, 2 = float, 1 = fix)
- 51 - Reference RTK GPS number of satellites (-)
- 52 - Reference RTK standard deviation - north (m)
- 53 - Reference RTK standard deviation - east (m)
- 54 - Reference RTK standard deviation - up (m)
- 55 - Reference RTK standard deviation - north-east (m)
- 56 - Reference RTK standard deviation - east-up (m)
- 57 - Reference RTK standard deviation - up-north (m)
- 58 - Reference RTK age (s)
- 59 - Reference RTK ratio (-)