*Assembly Language Lecture Series:*

# Introduction to SASM: Constant

Sensei RL Uy, College of Computer Studies,
De La Salle University, Manila, Philippines

# Copyright Notice

# What is SASM?

**SASM (SimpleASM)** - simple Open Source cross-platform IDE for NASM assembly languages. SASM has syntax highlighting and debugger.

## How to Download?

**SASM software:** http://dman95.github.io/SASM/english.html
**Installing SASM on Windows:**

- Click on the link “Download for Windows” and follow instructions

# SASM Interface



**Instruction:**
Type the code below then type in 10 and 20 in the input window. Click the run icon. Your output should be display in the output window



# SASM Options




SASM
File Edit Build Debug Settings Help
Continue F5
Step over F10
Step into F11
Toggle breakpoint F8
Show registers Ctrl+R
Show memory Ctrl+M
Stop
Debug Menu
Memory
Variable or exp
var1
var2
Add variable...
Address
w64_sasm.asm
5 section .text
6 global CMAIN
7 CMAIN:
8 ;write your code here
9 PRINT_STRING "Hello World"
10 NEWLINE
11 GET_DEC 8, rax
12 GET_DEC 8, rbx
13 add rax, rbx
Input
10
20
Output
Registers
Register Hex
rax 0x7fff0b414d28 1407333822170
rbx 0x1 1
rcx 0x1 1
rdx 0x163f60 1458016
rsi 0x34 52
rdi 0x1622f0 1450736
rbp 0x8 0x8
rsp 0x61fe38 0x61fe38
r8 0x1627c0 1451968
r9 0x7fff0c796950 1407334026714
r10 0x0 0
r11 0x61fc58 6421592
r12 0x163f60 1458016
r13 0x0 0
r14 0x0 0
r15 0x0 0
rip 0x4014e0 0x4014e0 <mai
eflags 0x202 [ IF ]
cs 0x33 51
ss 0x2b 43
ds 0x0 0
es 0x0 0
fs 0x0 0
gs 0x0 0
st0 0 (raw 0x000000
st1 0 (raw 0x000000
st2 0 (raw 0x000000
st3 0 (raw 0x000000
st4 0 (raw 0x000000
st5 0 (raw 0x000000
st6 0 (raw 0x000000
st7 0 (raw 0x000000
fctrl 0x37f 895
fstat 0x0 0
ftag 0x0 0
fiseg 0x0 0
fioff 0x0 0
Build log:
[22:47:30] Build started...
[22:47:30] Built successfully.
[22:47:32] The program is executing...
[22:47:32] The program finished normally. Execution time: 0.045 s
[22:51:39] Build started...
[22:51:39] Built successfully.
GDB command:
Print
Perform

# Debug


SASM
File Edit Build Debug Settings Help
Memory
Variable or expression
Value
Type
var1
0xa
Hex
d
Array size
Address
var2
0xb
Hex
d
Array size
Address
Add variable...
Smart
d
Array size
Address
Contents of Memory
w64_sasm.asm
1 %include "io64.inc"
2 section .data
3 var1 dq 0x0000_0000_0000_000A
4 var2 dq 0x0000_0000_0000_000B
5 section .text
6 global CMAIN
7 CMAIN:
8 ;write your code here
9 PRINT_STRING "Hello World"
Contents of Registers
Input
10
20
Output
Registers
Register
Hex
rax 0x7fff0b414d28 1407333822170
rbx 0x1 1
rcx 0x1 1
rdx 0x163f60 1458016
rsi 0x34 52
rdi 0x1622f0 1450736
rbp 0x8 0x8
rsp 0x61fe38 0x61fe38
r8 0x1627c0 1451968
r9 0x7fff0c796950 1407334026714
r10 0x0 0
r11 0x61fc58 6421592
r12 0x163f60 1458016
r13 0x0 0
r14 0x0 0
r15 0x0 0
rip 0x4014e0 0x4014e0 <mai
eflags 0x202 [ IF ]
cs 0x33 51
ss 0x2b 43
ds 0x0 0
es 0x0 0
fs 0x0 0
gs 0x0 0
st0 0 (raw 0x000000
st1 0 (raw 0x000000
st2 0 (raw 0x000000
st3 0 (raw 0x000000
st4 0 (raw 0x000000
st5 0 (raw 0x000000
st6 0 (raw 0x000000
st7 0 (raw 0x000000
fctrl 0x37f 895
fstat 0x0 0
ftag 0x0 0
fiseg 0x0 0
fioff 0x0 0
Build log:
[22:47:30] Build started...
[22:47:30] Built successfully.
[22:47:32] The program is executing...
[22:47:32] The program finished normally. Execution time: 0.045 s
[22:51:39] Build started...
[22:51:39] Built successfully.
GDB command:
Print
Perform

# Debug


SASM
File Edit Build Debug Settings Help
Memory
Variable or expression
Value
Type
var1
0xa
Hex
d
Array size
Address
var2
0xb
Hex
d
Array size
Address
Add variable...
Smart
d
Array size
Address
Contents of Memory
w64_sasm.asm
1 %include "io64.inc"
2 section .data
3 var1 dq 0x0000_0000_0000_000A
4 var2 dq 0x0000_0000_0000_000B
5 section .text
6 global CMAIN
7 CMAIN:
8 ;write your code here
9 PRINT_STRING "Hello World"
Contents of Registers
Input
10
20
Output
Registers
Register
Hex
rax 0x7fff0b414d28 1407333822170
rbx 0x1 1
rcx 0x1 1
rdx 0x163f60 1458016
rsi 0x34 52
rdi 0x1622f0 1450736
rbp 0x8 0x8
rsp 0x61fe38 0x61fe38
r8 0x1627c0 1451968
r9 0x7fff0c796950 1407334026714
r10 0x0 0
r11 0x61fc58 6421592
r12 0x163f60 1458016
r13 0x0 0
r14 0x0 0
r15 0x0 0
rip 0x4014e0 0x4014e0 <mai
eflags 0x202 [ IF ]
cs 0x33 51
ss 0x2b 43
ds 0x0 0
es 0x0 0
fs 0x0 0
gs 0x0 0
st0 0 (raw 0x000000
st1 0 (raw 0x000000
st2 0 (raw 0x000000
st3 0 (raw 0x000000
st4 0 (raw 0x000000
st5 0 (raw 0x000000
st6 0 (raw 0x000000
st7 0 (raw 0x000000
fctrl 0x37f 895
fstat 0x0 0
ftag 0x0 0
fiseg 0x0 0
fioff 0x0 0
Build log:
[22:47:30] Build started...
[22:47:30] Built successfully.
[22:47:32] The program is executing...
[22:47:32] The program finished normally. Execution time: 0.045 s
[22:51:39] Build started...
[22:51:39] Built successfully.
GDB command:
Print
Perform

# SASM using constant I/O macro (output)

| SASM output macro | Description | Example |
|---|---|---|
| PRINT_STRING *string* | Print null-terminated text *string* | PRINT_STRING “Hello” |
| PRINT_CHAR *ch* | Print symbol *ch* | PRINT_CHAR “A” |
| PRINT_DEC size, *data* | Print number *data* in signed decimal representation | PRINT_DEC 2, -5 |
| PRINT_UDEC size, *data* | Print number *data* in unsigned decimal representation | PRINT_UDEC 2, 10000 |
| PRINT_HEX size, *data* | Print number *data* in hexadecimal representation | PRINT_HEX 4, 0x9ABCDEFO |

- **ch, data** - a constant, variable name, register or address
- **string** – string constant, variable name or address
- **size** – the size of data in bytes (1,2,4,8)
- ***Note: The byte size of “1” is not working correctly in SASM. It is the same as the byte size “2.”***
  - Check: PRINT_DEC 1, 32767 [It printed 32767. But what do you think should be the correct output?]

# Constant Output using SASM macro