


# — LINEAR REGRESSION

Thomas Tiam-Lee, PhD

Norshuhani Zamin, PhD



# Linear Regression

- A **supervised learning algorithm**
  - Contains a target variable (label) that we want to predict
- A model designed for **regression**
  - The label is a **continuous numerical value**
- **Example:** *predict the price of the house given its lot area*



# The Data

Lot area	House Price
50	1148
52	1458
54	1551
56	1513
58	1425
60	1657
62	1457
64	1504
66	1522
68	1594

# The Data

Lot area	House Price
50	1148
52	1458
54	1551
56	1513
58	1425
60	1657
62	1457
64	1504
66	1522
68	1594


**Key idea:** we can visualize **the relationship between the features** (lot area) **and the label** (house price) using a scatterplot.

Lot Area = Independent variable

House Price = Dependent variable (target variable)


# The Data

Lot area	House Price
50	1148
52	1458
54	1551
56	1513
58	1425
60	1657
62	1457
64	1504
66	1522
68	1594



# The Data


Lot area	House Price
50	1148
52	1458
54	1551
56	1513
58	1425
60	1657
62	1457
64	1504
66	1522
68	1594






# The Data

Lot area	House Price
50	1148
52	1458
54	1551
56	1513
58	1425
60	1657
62	1457
64	1504
66	1522
68	1594



# The Data

Lot area	House Price
50	1148
52	1458
54	1551
56	1513
58	1425
60	1657
62	1457
64	1504
66	1522
68	1594



How can we predict the price of a house that we have not seen yet before?




# Modeling: Linear Regression

- In linear regression, the hypothesis function (model) is a **linear equation**.
  - In its most basic form (1 feature), this can be visualized as a **line**.



# The Data

Lot area	House Price
50	1148
52	1458
54	1551
56	1513
58	1425
60	1657
62	1457
64	1504
66	1522
68	1594



# Modeling: Linear Regression

- Equation of a line:
  - $y = mx + b$ 
    - feature (lot area):  $x$
    - label (price):  $y$
- $m$  and  $b$  are the **parameters** of the model
  - $m$  is the **slope** of the line
  - $b$  is the **y-intercept**



# Modeling: Linear Regression

- Rewritten in a different form:
  - $y = w_1x + w_0$ 
    - feature (lot area):  $x$
    - label (price):  $y$
- $w_1$  and  $w_0$  are the **parameters** of the model
  - $w_1$  is the **slope** of the line
  - $w_0$  is the **y-intercept**






# Modeling: Linear Regression

- **Key Idea:** By **changing the parameters** of the model, we can **change how the model behaves** (i.e., the orientation of the line)

$$w_1 = 0.5$$
$$w_0 = 1$$


$$w_1 = -0.25$$
$$w_0 = 2$$

$$w_1 = 1.2$$
$$w_0 = -3$$



# The Data


Lot area	House Price
50	1148
52	1458
54	1551
56	1513
58	1425
60	1657
62	1457
64	1504
66	1522
68	1594



Given the line, we can make a prediction by plugging in the lot area ( $x$ ) and solving the equation!

# The Learning Algorithm

- The “magic” of machine learning lies within:
  - Given a set of training data (points), how can we find the values of the parameters to make a line that best fits the data?
- We’re going to find the best line systematically using a **learning algorithm**.




Which line is the best?





# But First

- Need a **mathematical way** to measure “how good a line is”



\_\_\_\_\_



# Loss Function


- (also known as **objective function, cost function**)
- A function that accepts a model and the training data and returns **a numerical measure of how well the model fits the data.**
- A loss of 0 is the best possible score (the model fits the data perfectly) otherwise keep the function minimum.

<https://www.youtube.com/watch?v=erfeZg27B7A>

# A Linear Regression Loss Function

$$l(\theta) = \frac{1}{2n} \sum (f(x; \theta) - y)^2$$

- Also known as the **Mean Squared Error**
- Measures the average “error” of each prediction of the model on the training data




- **Why squared?**
  - Remove negative values
  - Penalize larger errors more

# Goal of Learning Algorithm

$$l(\theta) = \frac{1}{2n} \sum (f(x; \theta) - y)^2$$


- How do we find the set of parameters  $\theta$  ( $w_0$  and  $w_1$ ) that will **minimize the loss function**?
- Parameters are also known as coefficients.



# Gradient Descent Learning Algorithm

- Gradient Descent is an optimization algorithm to find the minimum of a function.
- To make things simple, let us first assume that our  $w_0$  (y-intercept) is fixed (always 0, no intersection). We can only change  $w_1$  (slope).
- Goal:

**To find the best slope that will make the line best fit the data.**



# Gradient Descent Learning Algorithm

procedure Gradient Descent( $\theta$ ):  
while not converged do:

$\theta$  is the slope

$$\theta_i := \theta_{i-1} - \alpha \frac{\partial y}{\partial x}$$

return  $\theta$

$\alpha$  is the learning rate, determines how large the update will be.  $\alpha$  is usually kept at 0.01

$\frac{\partial y}{\partial x}$  is the gradient of the loss


STEP by STEP:

<https://www.youtube.com/watch?v=Gbz8RIjxIH0>




# Gradient Descent Learning Algorithm

- **Key idea:** start with a random slope, then keep adjusting until the loss function score improves!




# Gradient Descent Learning Algorithm

- **Key idea:** want to try out different slopes until you reach the lowest point!




# Gradient Descent Learning Algorithm

- Start at a random point. Compute the score.




# Gradient Descent Learning Algorithm

- Adjust the point.  
Compute the  
score.




# Gradient Descent Learning Algorithm

- Adjust the point.  
Compute the  
score.




# Gradient Descent Learning Algorithm

- Adjust the point.  
Compute the  
score.



# Gradient Descent Learning Algorithm


- Adjust the point.  
Compute the  
score.






# Gradient Descent Learning Algorithm

- Adjust the point.  
Compute the  
score.




# Gradient Descent Learning Algorithm

- Adjust the point.  
Compute the  
score.
- **Question:** how do  
we know which  
direction to move  
and how much?



# Case of Multiple Parameters

- When we consider both  $w_1$  and  $w_0$ , the graph of the loss function will look like this.
- **Gradient descent concept still applies!**




# Extension to Multiple Features

- **Example:** We are considering not only the lot area, but also the floor space.
- $y = w_1x_1 + w_2x_2 + w_0$ 
  - features (lot area and floor space):  $x_2$
  - label (price):  $y$
- $w_0, w_1, w_2$  are the **parameters** of the model
- Analyzing the relationship between a single dependent variable against multiple independent variables.
- Can be extended to as many features as we want!
- The learning algorithm is called – **Multiple Regression**
- Same principles of linear regression apply

# Evaluating Linear Regression Model

- We can use **Sum of Squared Error** to measure the performance of the model.
- SSE finds the difference between the actual and the predicted values.
- RMSE indicates average model prediction error
- The lower values indicate a better fit.
- It is measured in same units as the target variable.

$$SSE = \sum_{i=1}^n (y_i - f(x_i))^2$$



# Acknowledgments

- Previous STINTSY slides by the following instructors:
  - Courtney Ngo
  - Arren Antioquia