

CSARCH Lecture Series: Integer operation and overflow

Sensei RL Uy
College of Computer Studies
De La Salle University
Manila, Philippines





Copyright Notice

This lecture contains copyrighted materials and is use solely for instructional purposes only, and not for redistribution.

Do not edit, alter, transform, republish or distribute the contents without obtaining express written permission from the author.

Overview


Reflect on the following questions:

- How do you perform addition and subtraction for binary integer?
- How do we know if the result is correct (i.e., not overflow)?

Overview

- This sub-module discusses how to perform addition and subtraction for binary integer and determine if the result of the operation is an overflow.
- The objectives are as follows:
 - ✓ Describe the process of performing integer addition and subtraction
 - ✓ Explain if overflow occurs after performing addition and subtraction

Addition of Integer



```
111 (carry)

1111

+) 1111

-----

1 1110 2= 10_2 \rightarrow 0 \text{ carry 1}

1 1110 3= 11_2 \rightarrow 1 \text{ carry 1}

(carry out)
```

 In order to add multiple-bit numbers, we used a method analogous to that used for manual computation with decimal numbers → Add bit pairs starting from the LSb of the bit vectors, propagating carries toward the MSb

- 4-bit binary addition of unsigned integer:
 - $15 + 15 = ? [1111_2 + 1111_2 = ?]$

```
111 (carry)

1111

+) 1111

----

1 1110

(carry out)
```

- $15 + 15 = 30 [1111_2 + 1111_2 = 1110_2]$
- The result is 1110₂ or 14 but the correct answer is 30
- The result is therefore an overflow.
- There is an overflow because the result needs an additional bit to store the result (i.e., there is a carry-out)
- For unsigned integer, overflow occurs if there is a carry out from the MSb

- 4-bit binary addition of unsigned integer: $7 + 7 = ? [0111_2 + 0111_2 = ?]$ Is the result an overflow?
- $7 + 7 = 14 [0111_2 + 0111_2 = 1110_2]$
- The result is 1110₂ or 14 and the correct answer is 14
- The result is not an overflow (i.e., there is no carry out)

Unsigned integer: overflow occurs if there is a carry-out

Overflow and subtraction of unsigned integer

Subtraction of two *n*-digit unsigned numbers *M-N* in base *r* can be done as follows:

- Add the minuend M to the r's complement of the subtrahend N
- If $M \ge N$, the sum will produce and end carry which can be discarded. What is left is the result of $M \ge N$
- If *M*<*N*, the sum does not produce an end carry and the result is the *r*'s complement of (*M*-*N*). To "view" the answer in a familiar format, take the *r*'s complement of the sum and place a negative sign in front. (Note: since its unsigned, negative should not exist!).

Overflow and subtraction of unsigned integer

```
Using 10's complement, perform 72532-3250
M = 72532
N* = + 96750
         169282
(ignore carry) = 69282
*10's complement; 5 digits (i.e., 03250) since minuend is 5 digits
```

```
Using 10's complement,
perform 3250 - 72532
M = 03250
  = + 27468
       30718
(Overflow)
```

Overflow and subtraction of unsigned integer

```
Using 2's complement,
perform 1010100<sub>2</sub> - 1000011<sub>2</sub>
 M = 1010100
 N* = + 0111101
        10010001
(ignore carry) = 0010001
*2's complement
```

```
Using 2's complement, perform
1000011<sub>2</sub> - 1010100<sub>2</sub>
M = 1000011
N = + 0101100
         1101111
no carry
(overflow)
```

Try

```
Using 10's complement, perform
(1)15-14
(2)14-15
and determine if the result is an
overflow
Using 2's complement, perform
(3) 1111_2 - 1110_2
(4) 1110_2 - 1111_2
and determine if the result is an
overflow
```

Try

```
Using 10's complement, perform
(1)15-14
(2)14-15
```

```
(2)
M = 14
N = + 85
---
99
(no carry)
→Overflow
```

Try

```
Using 2's complement, perform  (3)1111_2 - 1110_2   (4)1110_2 - 1111_2
```

- 4-bit binary addition of signed integer:
 - $7 + 7 = ? [0111_2 + 0111_2 = ?]$

- $7 + 7 = 14 [0111_2 + 0111_2 = 1110_2]$
- The result is 1110₂ or -2 but the correct answer should be 14
- The result is therefore an overflow.
- There is an overflow because adding two positive integers and the result is a negative integer

4-bit binary addition of signed integer:

$$3 + 4 = ? [0011_2 + 0100_2 = ?]$$

- $3 + 4 = 7 [0011_2 + 0100_2 = 0111_2]$
- The result is 0111₂ or 7 and the correct answer is 7
- The result is not an overflow (adding 2 positive integers and the result is a positive integer)

• 4-bit binary addition of signed integer:

$$-7 + -6 = ? [1001_2 + 1010_2 = ?]$$

Is the result an overflow?

•
$$-7 + -6 = -13 [1001_2 + 1010_2 = 0011_2]$$

- The result is 0011₂ or 3 but the correct answer should be -13
- The result is therefore an overflow.
- There is an overflow because adding two negative numbers results in a positive result

- 4-bit binary addition of signed integer:
 - $-3 + -4 = ? [1101_2 + 1100_2 = ?]$

•
$$-3 + -4 = -7 [1101_2 + 1100_2 = 1001_2]$$

- The result is 1001₂ or -7 and the correct answer is -7
- The result is not an overflow (adding 2 negative integers and the result is a negative integer)

- 4-bit binary addition of signed integer:
 - $-3 + 7 = ? [1101_2 + 0111_2 = ?]$

- $-3 + 7 = +4 [1101_2 + 0111_2 = 0100_2]$
- The result is 0100₂ or +4 and the correct answer is +4
- The result is not an overflow (adding a positive with a negative integer is similar to performing subtraction)
- Subtraction operation never cause an overflow result. Why?

- Adding positive integer with negative integer and vice-versa no overflow
- Adding two positive integers
 - Overflow if the result is negative
- Adding two negative integers
 - Overflow if the result is positive



| Is it an overflow (8-bit integer)? | Yes/No |
|-------------------------------------|--------|
| View the result as unsigned integer | |
| View the result as signed integer | |



10111111₂ + 11000001₂ =?

| Is it an overflow (8-bit integer)? | Yes/No |
|-------------------------------------|--------|
| View the result as unsigned integer | Yes |
| View the result as signed integer | No |

| | | 1 | 0 | 1 | 1 | 1 | 1 | 1 | 1 |
|-----|---|---|---|---|---|---|---|---|---|
| +] |) | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 1 |
| | _ | _ | _ | _ | _ | | _ | _ | _ |
| 1 | | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |

| Unsigned: | Signed: |
|-----------|---------|
| 191 | -65 |
| +)193 | +)-63 |
| | |
| 384 | -128 |

Subtraction of Signed Integer

- Subtraction can be viewed as adding the 2's complement of the second operand
 - A B = A + (-B)
 - 2's complement is used to change the sign of the second operand

Subtraction of Signed Integer

• 4-bit binary subtraction using 2's complement addition $^{+)1101}_{----}$ 6 - (+3) = 6 + (-3) = $[0110_2 + 1101_2 = ?]$ 1 0011 (carry out)

•
$$6 - (+3) = 6 + (-3) = [0110_2 + 1101_2 = 0011]$$

- The result is 0011₂ or +3 and the correct answer is 3
- The result is not an overflow since "adding" positive with negative integer will never cause an overflow

(carry)

To recall ...

- What have we learned:
 - ✓ Describe the process of performing integer addition and subtraction
 - ✓ Explain if overflow occurs after performing addition and subtraction