# Annual Review

Michalis Panayides

2021-06-11

# Motivation

Motivation

Hospital queueing model

Hospital queueing model

Hospital queueing model

Hospital queueing model

Hospital queueing model

Hospital queueing model

Hospital queueing model

Performance Measures - Steady state vector

$$Q = \begin{pmatrix} -\lambda_1 - \lambda_2 & \lambda_1 + \lambda_2 & 0 & \cdots & 0 & 0 \\ \mu & -\mu - \lambda_1 - \lambda_2 & \lambda_1 + \lambda_2 & \cdots & 0 & 0 \\ 0 & 2\mu & -2\mu - \lambda_1 - \lambda_2 & \cdots & 0 & 0 \\ \vdots & \vdots & \vdots & \ddots & \vdots & \vdots \\ 0 & 0 & 0 & \cdots & -\lambda_1 - 3\mu & \lambda_1 \\ 0 & 0 & 0 & \cdots & 3\mu & -3\mu \end{pmatrix} \begin{matrix} (0,0) \\ (0,1) \\ (0,2) \\ \\ (2,3) \\ (2,4) \end{matrix}$$

with column labels $(0,0)\quad (0,1)\quad (0,2)\quad \cdots \quad (2,3)\quad (2,4)$

$$\pi Q = 0$$

$$\pi = \left[\pi_{(0,0)}, \pi_{(0,1)}, \pi_{(0,2)}, \cdots, \pi_{(2,3)}, \pi_{(2,4)} \right]$$

Performance Measures - Waiting time

$$W = \frac{\lambda_1 P_{L_1'}}{\lambda_2 P_{L_2'} + \lambda_1 P_{L_1'}} W^{(1)} + \frac{\lambda_2 P_{L_2'}}{\lambda_2 P_{L_2'} + \lambda_1 P_{L_1'}} W^{(2)} \qquad (1)$$

Overall mean waiting time using Markov chain and simulation

Performance Measures - Blocking time

$$B = \frac{\sum_{(u,v) \in S_A^{(2)}} \pi_{(u,v)} \, b(u,v)}{\sum_{(u,v) \in S_A^{(2)}} \pi_{(u,v)}} \qquad (2)$$

Blocking time using Markov chain and simulation

Performance Measures - Proportion within time

$$P(X < t) = \frac{\lambda_1 P_{L_1'}}{\lambda_2 P_{L_2'} + \lambda_1 P_{L_1'}} P(X^{(1)} < t) + \frac{\lambda_2 P_{L_2'}}{\lambda_2 P_{L_2'} + \lambda_1 P_{L_1'}} P(X^{(2)} < t)$$

(3)

Overall proportion individuals within target