TECHNICAL REPORT

ISO/TR 6336-30

Second edition
2022-12

Calculation of load capacity of spur and helical gears —

Part 30: Calculation examples for the application of ISO 6336 parts 1,2,3,5

Calcul de la capacité de charge des engrenages cylindriques à dentures droite et hélicoïdale —

Partie 30: Exemples d'application de l'ISO 6336 parties 1, 2, 3, 5

Reference number
ISO/TR 6336-30:2022(E)

© ISO 2022



COPYRIGHT PROTECTED DOCUMENT

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

© ISO 2022 – All rights reserved

Contents

Page

Foreword ... **iv**

Introduction ... **v**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms, definitions, symbols and units ... **1**
3.1 Terms and definitions ... 1
3.2 Symbols and units ... 1

4 Worked examples ... **6**
4.1 General ... 6
4.2 Qualifying comments ... 6
4.2.1 Calculation of base pitch deviation, f_{pb} ... 6
4.2.2 Calculation of running-in allowance, y_α, for the transverse load factors $K_{H\alpha}$ and $K_{F\alpha}$ ... 7
4.2.3 Calculation of mesh stiffness, c_γ ... 7
4.2.4 Application of lubricant film Z_L, Z_v and Z_R, hardness Z_W and size Z_X influence factors ... 7
4.2.5 Calculation of the permissible contact stress in the limited life range (Z_N and Z_{NT}) ... 7
4.2.6 Application of work hardening factor, Z_W ... 8
4.2.7 Determination of *Rz* ... 8
4.2.8 Facewidth for calculations involving double helical gears ... 8
4.2.9 Calculation of ε_β for double helical gears ... 8
4.2.10 Calculation of $f_{H\beta 5}$ and $f_{H\beta}$ ... 8
4.2.11 Helix tolerance $f_{H\beta 5}$ and $f_{H\beta}$ for double helical gears ... 8
4.2.12 Calculation of root diameter, d_f ... 8
4.2.13 Calculations for internal gears ... 8
4.2.14 Rounding of values ... 8
4.2.15 Deviations of values ... 8
4.2.16 Nominal and generated values ... 9
4.2.17 ISO 1328-1:2013 ... 9
4.2.18 Values for reference only ... 9
4.3 Example 1: Single helical case carburized gear pair ... 9
4.4 Example 2: Single helical through-hardened gear pair ... 14
4.5 Example 3: Spur through-hardened gear pair ... 18
4.6 Example 4: Spur case carburized gear pair ... 22
4.7 Example 5: Spur gear pair with an induction hardened pinion and through-hardened cast gear ... 26
4.8 Example 6: Spur internal through-hardened gear pair ... 30
4.9 Example 7: Double helical through-hardened wrought gear pair ... 34
4.10 Example 8: Single helical case carburized gear pair ... 38

Annex A (informative) **Example 1 detailed calculation** ... **43**

Bibliography ... **63**

© ISO 2022 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 60, *Gears*, Subcommittee SC 2, *Gear capacity calculation*.

This second edition cancels and replaces the first edition (ISO 6336-30:2017), which has been technically revised according to ISO 6336-1:2019, ISO 6336-2:2019, ISO 6336-3:2019.

The main changes are as follows:

— introduction of tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019) f_{ZCa};

— introduction of load distribution influence factor f_{ε};

— modification of the helix angle factor Y_{β};

— calculation of tooth form factor Y_F and stress correction factor Y_S generated with a shaper cutter;

— update to the qualifying comments in 4.2;

— update to the input variables (additional values, modified values).

A list of all parts in the ISO 6336 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2022 – All rights reserved

Introduction

The ISO 6336 series consists of International Standards, Technical Specifications (TS) and Technical Reports (TR) under the general title *Calculation of load capacity of spur and helical gears* (see Table 1).

— International Standards contain calculation methods that are based on widely accepted practices and have been validated.

— TS contain calculation methods that are still subject to further development.

— TR contain data that is informative, such as example calculations.

The procedures specified in ISO 6336-1 to ISO 6336-19 cover fatigue analyses for gear rating. The procedures described in ISO 6336-20 to ISO 6336-29 are predominantly related to the tribological behaviour of the lubricated flank surface contact. ISO 6336-30 to ISO 6336-39 include example calculations. The ISO 6336 series allows the addition of new parts under appropriate numbers to reflect knowledge gained in the future.

Requesting standardized calculations according to ISO 6336 without referring to specific parts requires the use of only those parts that are designated as International Standards (see Table 1 for listing). When requesting further calculations, the relevant part or parts of ISO 6336 need to be specified. Use of a Technical Specification as acceptance criteria for a specific design needs to be agreed in advance between manufacturer and purchaser.

Table 1 — Overview of ISO 6336

Calculation of load capacity of spur and helical gears	International Standard	Technical Specification	Technical Report
Part 1: Basic principles, introduction and general influence factors	X		
Part 2: Calculation of surface durability (pitting)	X		
Part 3: Calculation of tooth bending strength	X		
Part 4: Calculation of tooth flank fracture load capacity		X	
Part 5: Strength and quality of materials	X		
Part 6: Calculation of service life under variable load	X		
Part 20: Calculation of scuffing load capacity — Flash temperature method		X	
Part 21: Calculation of scuffing load capacity — Integral temperature method		X	
Part 22: Calculation of micropitting load capacity (replaces: ISO/TR 15144-1)		X	
Part 30: Calculation examples for the application of ISO 6336-1, ISO 6336-2, ISO 6336-3 and, ISO 6336-5			X
Part 31: Calculation examples of micropitting load capacity (replaces: ISO/TR 15144-2)			X
NOTE At the time of publication of this document, some of the parts listed here were under development. Consult the ISO website.			

This document provides worked examples for the application of the calculation procedures defined in ISO 6336-1, ISO 6336-2, ISO 6336-3 and ISO 6336-5. The example calculations cover the application to spur, helical and double helical, external and internal cylindrical involute gears for both high speed and low speed operating conditions, determining the ISO safety factors against tooth flank pitting and tooth root bending strength for each gear set. The calculation procedures used are consistent with those presented in ISO 6336-1, ISO 6336-2, ISO 6336-3 and ISO 6336-5, unless qualifying comments are provided. Where qualifying comments have been included in this document, they reflect areas of the calculation procedures presented in the current standards where points of clarification are required or editorial errors have been identified. The changes defined within the qualifying comments will be

© ISO 2022 – All rights reserved

implemented in future revisions of ISO 6336-1, ISO 6336-2, ISO 6336-3 and ISO 6336-5. No additional calculations are presented here that are outside of the referenced documents.

Eight worked examples are presented with the necessary input data for each gear set provided at the beginning of the calculation. Calculation details are presented in full for one worked example, with all following examples having summarized results data presented in tabular format.

For all calculations in this document, the flank tolerance classes according to ISO 1328-1:2013 are applied.

© ISO 2022 – All rights reserved

Calculation of load capacity of spur and helical gears —

Part 30:
Calculation examples for the application of ISO 6336 parts 1,2,3,5

1 Scope

This document presents worked examples that apply exclusively the approximation methods for the determination of specific influential factors, such as the dynamic factor, K_v, and the load distributions factors $K_{H\alpha}$, $K_{H\beta}$, etc., where full analytical calculation procedures are provided within the referenced parts of ISO 6336.

Worked examples covering the more advanced analysis techniques and methods are not applicable to this document.

The example calculations presented in this document are provided for guidance on the application of ISO 6336-1:2019, ISO 6336-2:2019, ISO 6336-3:2019 and ISO 6336-5:2016. Any of the values, safety factors or the data presented do not represent recommended criteria for real gearing. Data presented within this document are for the purpose of aiding the application of the calculation procedures of ISO 6336-1, ISO 6336-2, ISO 6336-3 and ISO 6336-5.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 1122-1, *Vocabulary of gear terms — Part 1: Definitions related to geometry*

ISO 6336 (all parts), *Calculation of load capacity of spur and helical gears*

3 Terms, definitions, symbols and units

3.1 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 1122-1 and ISO 6336 (all parts) apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at https://www.electropedia.org/

3.2 Symbols and units

The units of length metre, millimetre and micrometre are chosen in accordance with common practice. The conversions of the units are already included in the given formulae. All symbols used in this document are given in Table 2.

© ISO 2022 – All rights reserved

Table 2 *(continued)*

Symbol	Description	Unit
E	Young's modulus	N/mm^2
$E_{1,2}$	Auxiliary value (for form factor for pinion or wheel)	—
F_m	Mean transverse tangential load	N
F_t	Nominal tangential load at the reference cylinder	N
F_{tH}	Determinant tangential load	N
$F_{\beta x}$	Initial equivalent misalignment	µm
$F_{\beta y}$	Effective equivalent misalignment (after running-in)	µm
$f_{f\alpha eff}$	Effective profile deviation after running-in	µm
$f_{f\alpha}$	Profile form deviation (see ISO 1328-1:2013)	µm
$f_{H\beta}$	Helix slope deviation (see ISO 1328-1:2013)	µm
f_{ma}	Mesh misalignment	µm
f_{pb}	Transverse base pitch deviation (the values of f_{pT} may be used for calculations in accordance with the ISO 6336 series, using tolerances according to ISO 1328-1:2013)	µm
f_{pbeff}	Effective transverse base pitch deviation after running-in	µm
f_{pT}	Single pitch tolerance (see ISO 1328-1:2013, ISO 6336 refers to f_{pT} as f_{pt})	µm
f_{sh}	Equivalent misalignment	µm
f_{sh0}	Shaft deformation under specific load	µm
f_{ZCa}	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—
f_ε	Load distribution influence factor	—
G	Auxiliary value (for form factor)	—
H	Auxiliary value (for form factor)	—
h	Tooth depth	mm
h_{Fe}	Bending moment arm	mm
h_{fP}	Basic rack dedendum	mm
h_K	Tip chamfer	mm
K	Constant	—
K_A	Application factor	—
$K_{F\alpha}$	Transverse load factor	—
$K_{F\beta}$	Face load factor	—
$K_{H\alpha}$	Transverse load factor	—
$K_{H\beta}$	Face load factor	—
K_v	Dynamic factor	—
K_γ	Mesh load factor	—
k	Number of teeth spanned	—
L	Auxiliary notch parameter	—
l	Bearing span	mm
M_{dK}	Dimension between balls	mm
m_n	Normal module	mm
m_{red}	Reduced gear pair mass per unit facewidth	kg/mm
N	Resonance ratio	—
N_F	Exponent	—
N_L	Number of load cycles	—
N_M	Number of meshes	—

© ISO 2022 – All rights reserved

Table 2 *(continued)*

Symbol	Description	Unit
$n_{1,2}$	Rotation speed of pinion (or wheel)	min^{-1}
n_{E1}	Resonance speed	min^{-1}
p_{bn}	Virtual base pitch	mm
pr	As cut basic rack undercut	mm
q	Material allowance for finishing	mm
q_s	Notch parameter	—
q_{sT}	Notch parameter of standard reference test piece	—
q'	Flexibility of pair of meshing teeth	(mm·µm)/N
Ra	Arithmetic mean roughness value, Ra = 1/6 Rz	µm
Rz	Mean peak-to-valley roughness (ISO 4287:1997[a] including ISO 4287:1997/Cor 1:1998, ISO 4287:1997/Cor 2:2005, ISO 4287:1997/Amd 1:2009 and ISO 4288:1996[b])	µm
Rz_{10}	Mean relative peak-to-valley roughness for gear pair	µm
S_F	Safety factor for bending	—
S_H	Safety factor for surface durability	—
s	Bearing span offset	mm
s_{Fn}	Tooth root normal chord	mm
s_{pr}	Residual fillet undercut, $s_{pr} = pr - q$	mm
$T_{1,2}$	Nominal torque at pinion/wheel	Nm
v	Circumferential velocity at the reference cylinder	m/s
v_w	Pitch line velocity	m/s
W_k	Span measurement	mm
x	Nominal profile shift coefficient	—
x_E	Generating profile shift coefficient	—
$x_{E,V}$	Generating profile shift coefficient (pre-finishing)	—
x_0	Pinion cutter profile shift coefficient	—
Y_B	Rim thickness factor	—
Y_{DT}	Deep tooth factor	—
Y_F	Tooth form factor	—
Y_N	Life factor (tooth root stress)	—
Y_{NT}	Life factor for reference test conditions (tooth root stress)	—
Y_{RrelT}	Relative surface factor	—
Y_S	Stress correction factor	—
Y_{ST}	Stress correction factor, relevant to the dimensions of the reference test gears	—
Y_X	Size factor	—
Y_β	Helix angle factor	—
$Y_{\delta relT}$	Relative notch sensitivity factor for reference stress	—
y_f	Running-in allowance	µm
y_α	Running-in allowance	µm
y_β	Running-in allowance	µm
Z_B	Single pair tooth contact factor	—
Z_D	Single pair tooth contact factor	—
Z_E	Elasticity factor	$\sqrt{\mathrm{N/mm^2}}$
Z_H	Zone factor	—

© ISO 2022 – All rights reserved

Table 2 *(continued)*

Symbol	Description	Unit
Z_L	Lubricant factor	—
Z_N	Life factor (contact stress)	—
Z_{NT}	Life factor for reference test conditions (contact stress)	—
Z_R	Roughness factor	—
Z_W	Work hardening factor	—
Z_X	Size factor	—
Z_v	Velocity factor	—
Z_β	Helix angle factor	—
Z_ε	Contact ratio factor	—
z	Number of teeth	—
z_n	Virtual number of teeth	—
z_0	Pinion cutter number of teeth	—
α_n	Normal pressure angle	°
α_{en}	Virtual form factor pressure angle	°
α_{Fen}	Virtual load direction angle	°
α_t	Transverse pressure angle	°
α_{wt}	Transverse working pressure angle	°
β	Helix angle (without subscript, at reference cylinder)	°
γ	Auxiliary angle	°
ε_α	Transverse contact ratio	—
$\varepsilon_{\alpha n}$	Virtual contact ratio	—
ε_β	Overlap ratio	—
ε_γ	Total contact ratio	—
θ	Auxiliary value (for form factor)	rad
ν	Poisson's ratio	—
ν_{40}	Lubrication viscosity	mm^2/s
ρ	Material density	kg/m^3
ρ	Radius of curvature	mm
ρ_{aP0}	Pinion cutter tip radius coefficient	—
ρ_F	Radius of root fillet	mm
ρ_{fP}	Root fillet radius of the basic rack for cylindrical gears	mm
ρ_{red}	Relative radius of curvature	mm
ρ'	Slip layer thickness	mm
σ_{F0}	Nominal tooth root stress	N/mm^2
σ_F	Tooth root stress	N/mm^2
$\sigma_{F\,lim}$	Allowable stress number (bending)	N/mm^2
σ_{FP}	Permissible bending stress	N/mm^2
$\sigma_{FPlonglife}$	Permissible bending stress (long life)	N/mm^2
σ_{FPref}	Permissible bending stress (reference condition)	N/mm^2
σ_H	Contact stress	N/mm^2
$\sigma_{H\,lim}$	Allowable stress number (surface)	N/mm^2
σ_{H0}	Nominal contact stress at pitch point	N/mm^2
σ_{HP}	Permissible contact stress	N/mm^2
$\sigma_{HPlonglife}$	Permissible contact stress (long life)	N/mm^2

© ISO 2022 – All rights reserved

Table 2 *(continued)*

Symbol	Description	Unit
σ_{HPref}	Permissible contact stress (reference)	N/mm^2
σ_s	Yield stress	N/mm^2
$\sigma_{0,2}$	Proof stress	N/mm^2
χ^*	Relative stress gradient in root of a notch	mm^{-1}
χ_P^*	Stress gradient – smooth, polished test piece	mm^{-1}
χ_T^*	*Stress gradient for reference test piece*	mm^{-1}
[a] Cancelled and replaced by ISO 21920-2:2021. [b] Cancelled and replaced by ISO 21920-3:2021.		

4 Worked examples

4.1 General

Clause 4 presents examples for the calculation of the safety factor for surface durability, S_H, and safety factor for tooth breakage, S_F. For all examples, where various calculation methods are presented for the determination of specific influencing factors, the approximate methods detailed in the ISO 6336 series are applied. Where a specific method is used to calculate an influence parameter, the method used is denoted as a subscript to that factor (as defined in ISO 6336-1).

The calculations results in specific aspects of the rating procedure to highlight the influence of specific gear pair geometry, quality or application.

For example 1 in 4.3, the full calculation procedure is presented including the formulae. For all subsequent calculations, only the tabulated input and results data are provided.

In a number of areas, points of clarification of the procedure or specific criteria that differ slightly from the definitions provided in ISO 6336-1, ISO 6336-2 and ISO 6336-3 are incorporated within the example calculations. The points reflect the true intention of the procedures of ISO 6336-1, ISO 6336-2 and ISO 6336-3 and are defined in 4.2.

NOTE 1 The calculations and results presented were performed using computer-based procedures. If the calculations are performed manually, it is possible that small differences between the results appear.

NOTE 2 In the presented results, all values for *K* factors are presented with rounding to two decimal places (X,XX); however, for the actual calculations, the results for each factor have been used with unrounded values.

4.2 Qualifying comments

4.2.1 Calculation of base pitch deviation, f_{pb}

The value calculated for f_{pb} is by means of Formula (1), and is applied without rounding:

$$f_{pb} = f_{pT} \cdot \cos(\alpha_t) \tag{1}$$

where f_{pT} is provided by ISO 1328-1:2013.

© ISO 2022 – All rights reserved

4.2.2 Calculation of running-in allowance, y_α, for the transverse load factors $K_{H\alpha}$ and $K_{F\alpha}$

The following criteria defined in ISO 6336-1:2019, 8.3.1, are applied only for the calculation of $K_{H\alpha}$ and $K_{F\alpha}$:

— The base pitch deviation, f_{pb}, accounts for the total effect of all gear tooth deviations which affect the transverse load factor. If, nevertheless, the profile form deviation, $f_{f\alpha}$, is greater than the base pitch deviation, the profile form deviation $f_{f\alpha}$ is used instead of the base pitch deviation f_{pb}.

— If profile modifications compensate for the deflections of the teeth at the actual load level, 50 % of the base pitch deviation f_{pb} and its corresponding running-in value $y_\alpha(f_{pb})$ respectively the profile form deviation $f_{f\alpha}$ and its corresponding running-in value $y_\alpha(f_{f\alpha})$ is used for the calculation of $K_{H\alpha}$. This reduction applies for examples 1 and 4 of this document.

The criteria listed above do not apply for determining f_{pb} and $f_{f\alpha}$ for the calculation of K_v according to ISO 6336-1:2019, 6.5.4.

4.2.3 Calculation of mesh stiffness, c_γ

The calculation of mesh stiffness, c_γ, in accordance with method B of ISO 6336-1:2019, 9.3.3, is applied for all example calculations. For all c_γ calculations, the use of the nominal profile shift coefficient, x, and nominal basic rack dedendum, h_{fP}, is applied. The generating profile shift coefficient, x_E, is not used, even where x_E is used for other strength calculations associated with the tooth root. Virtual number of teeth of helical gears were calculated with Formula (16) of ISO 6336-3:2019 rather than approximate formula given in Formula (81) of ISO 6336-1:2019.

4.2.4 Application of lubricant film Z_L, Z_v and Z_R, hardness Z_W and size Z_X influence factors

According to the ISO 6336 series, the permissible contact stress numbers for static and reference condition, including all relevant influence factors as defined, will be calculated. For limited life, linear interpolation on a log–log scale, following the procedure of Z_{NT}, between these two values is applied. The linear interpolation on a log-log-scale for limited life leads to a value Z_N, which can be different to the value Z_{NT}.

The displayed values of Z_L, Z_v, Z_R, Z_W and Z_X in the output tables of this document show the interpolated values of each Z-factor.

4.2.5 Calculation of the permissible contact stress in the limited life range (Z_N and Z_{NT})

For the calculation of the permissible contact stress in the limited life range, the following procedure is considered according to ISO 6336-2:2019:

— Calculation of the permissible contact stress for static stress $\sigma_{HP,stat}$ and for reference stress $\sigma_{HP,stat}$ according to ISO 6336-2:2019, 5.4.3 with the use of Z_{NT}.

— Calculation of the permissible contact stress for the limited life range $\sigma_{HP,lim}$ by applying the formulae in ISO 6336-2:2019, 5.4.4.3. The application of the formulae results in the calculation and usage of Z_N (e. g. for case hardened or through hardened material) with no pitting permissible:

$$Z_N = \left(\frac{5 \cdot 10^7}{N_L} \right)^{0{,}3\ 705 \cdot \log \frac{\sigma_{HP,stat}}{\sigma_{HP,ref}}}$$

— The obtained permissible contact stress for the limited life range $\sigma_{HP,lim}$ is equal to the permissible contact stress σ_{HP}, which is subsequently used to calculate the pitting stress limit σ_{HG} according to ISO 6336-2:2019, 5.4.3 and eventually the safety against pitting S_H according to ISO 6336-2:2019, 5.2.

© ISO 2022 – All rights reserved

4.2.6 Application of work hardening factor, Z_W

In example 5 in 4.7, a surface-hardened pinion is used with a through-hardened cast iron wheel. According to ISO 6336-2:2019, 13.3.2, the calculation method is only valid for through-hardened steel, not through-hardened cast iron. To be on the conservative side, the work hardening factor for the wheel is set to Z_{W2} = 1,0. For all other cases where both gears are either through-hardened or surface-hardened, $Z_{W1,2}$ = 1 for both pinion and wheel applies.

4.2.7 Determination of *Rz*

The determination of *Rz* from the specified *Ra* values is determined by the approximation suggested in ISO 6336-2:2019, 12.3.2.3.1, footnote 2, where $Rz = 6 \cdot Ra$.

4.2.8 Facewidth for calculations involving double helical gears

For calculations involving double helical gears (such as example 7), and for the application of ISO 6336-2:2019, Formula (40) b_B is used instead of b.

4.2.9 Calculation of ε_β for double helical gears

For the calculation of ε_β for double helical gears, the value applies for only one helix. For example, the value for facewidth, b, is replaced by b_B.

4.2.10 Calculation of $f_{H\beta 5}$ and $f_{H\beta}$

The calculation of $f_{H\beta 5}$ for use in the determination of the initial equivalent misalignment, $F_{\beta x}$, in ISO 6336-1:2019, 7.5.3.4 is performed in accordance with ISO 1328-1:2013 for flank tolerance class 5 with the as required rounding applied.

4.2.11 Helix tolerance $f_{H\beta 5}$ and $f_{H\beta}$ for double helical gears

When calculating the helix tolerance value $f_{H\beta 5}$ and $f_{H\beta}$ for double helical gears, the facewidth of one helix is used, i.e. b_B.

4.2.12 Calculation of root diameter, d_f

For all calculations presented within this document, the calculation of the root diameter, d_f, is performed with the generating profile shift coefficient, x_E, and not the nominal profile shift coefficient, x (see also 4.2.16).

4.2.13 Calculations for internal gears

For all calculations involving internal gears (example 6), the input data uses negative values for diameters as defined in the ISO 6336 series.

4.2.14 Rounding of values

The calculations within this document have been conducted with unrounded values. The values documented in the table are rounded.

4.2.15 Deviations of values

Numeric calculations and different programming of calculation programs can lead to slight deviations of the values when recalculating. The calculated values documented in this document were achieved by different calculation programs. Deviations were accepted in a defined range, as the basic statement of

© ISO 2022 – All rights reserved

the calculation remains. The range of acceptable deviations for the calculations in this document was defined as the following:

— Absolute deviation: 0,01.

— Relative deviation: 0,5 %.

Values for the calculations were within the absolute and relative deviation range.

4.2.16 Nominal and generated values

The values were calculated with nominal values if not otherwise stated in this document (e.g. in 4.2.12) or the corresponding standard (e.g. bending geometry according to ISO 6336-3:2019).

4.2.17 ISO 1328-1:2013

ISO 1328-1:2013 was used for the calculation of the allowable values of deviations.

4.2.18 Values for reference only

Values in the input table (e.g. nominal profile shift coefficient x) are put in parenthesis when they are calculated and for reference only.

4.3 Example 1: Single helical case carburized gear pair

For example 1, input values and output values are given in Tables 3 and 4, respectively.

A full calculation description is provided in Annex A.

© ISO 2022 – All rights reserved

Table 3 — Example 1 input values

Type	Description	Unit	Symbol	Pinion	Wheel
Geometry	Number of teeth	—	z	17	103
	Normal module	mm	m_n	8,00	
	Normal pressure angle	°	α_n	20,00	
	Helix angle	°	β	15,80	
	Hand of helix	—	—	Left	Right
	Facewidth (total)	mm	b	100,00	100,00
	Gap width	mm	—	0	0
	Edge chamfer	mm	—	0,00	0,00
	Contact facewidth (total)	mm	b_{eff}	100,00	
	Centre distance	mm	a	500,000	
	Span measurement	mm	W_k	38,196	307,943
	Number of teeth spanned	—	k	2	13
	Dimension between balls	mm	M_{dK}	—	—
	Ball diameter	mm	D_M	—	—
	Nominal profile shift coefficient	—	x	(0,145)	0,000
	Tip diameter	mm	d_a	159,66	872,35
	Basic rack dedendum coefficient	—	h_{fP}/m_n	1,400	1,400
	Tip chamfer	mm	h_K	0,00	0,00
	Basic rack fillet root radius coefficient	—	ρ_{fP}/m_n	0,39	0,39
	As cut basic rack undercut	mm	pr	0,00	0,00
	Material allowance for finishing	mm	q	0,00	0,00
	Residual fillet undercut, $s_{pr} = pr - q$	mm	s_{pr}	0,00	0,00
	Pinion cutter number of teeth	—	z_0	—	—
	Pinion cutter profile shift (ref)	—	x_0	—	—
	Flank finishing process	—	—	As cut	As cut
	Root finishing process	—	—	As cut	As cut
	Tip relief	µm	C_a	70	70
	Root relief	µm	C_f	0	0
	Profile modification compensate for the deflections	—	—	Yes	
	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—	f_{ZCa}	based on 3D load distribution program	
Quality	Flank tolerance class	—	A	5	5
	Single pitch tolerance according to ISO 1328-1:2013	µm	f_{pT}	8,5	9,0
	Profile form deviation according to ISO 1328-1:2013	µm	$f_{f\alpha}$	9,5	9,5
	Helix slope deviation according to ISO 1328-1:2013	µm	$f_{H\beta}$	8,0	9,0
	Surface roughness – flank *Ra* (*Rz*)	µm	—	1,0 (6,0)	1,0 (6,0)
	Surface roughness – fillet *Ra* (*Rz*)	µm	—	3,0 (18,0)	3,0 (18,0)

© ISO 2022 – All rights reserved

Table 3 *(continued)*

Type	Description	Unit	Symbol	Pinion	Wheel
Material	Material	—	—	Eh	Eh
	Material quality	—	—	MQ	MQ
	Case hardness	—	—	60 HRC	60 HRC
	Core hardness	—	—	30 HRC	30 HRC
	Young's modulus	N/mm^2	E	206 000	206 000
	Poisson's ratio	—	v	0,3	0,3
	Yield/proof stress	N/mm^2	$\sigma_S/\sigma_{0,2}$	—	—
	Material density	kg/m^3	ρ	7 830	7 830
	Shot peen	—	—	No	No
	Limited pitting allowable	—	—	No	No
Application	Application factor	—	$K_{A\text{-}A}$	1,00	
	Mesh load factor	—	K_γ	1,00	
	Reverse bending	—	—	No	No
	Favourable contact position	—		No	No
	Helix modification (ISO 6336-1:2019, Table 12)	—	—	None (No. 1)	
	Dynamic factor, K_v, calculation method	—	—	Method B	
	Face load distribution factor, $K_{H\beta}$ and $K_{F\beta}$, calculation method	—	—	Method C	
	Number of meshes	—	N_M	1	1
	Gear blank type	—	—	Solid	Solid
	Web thickness	mm	b_s	—	—
	Inside diameter	mm	—	—	—
	Number of webs	—	—	—	—
	Arrangement (ISO 6336-1:2019, Figure 13)	—	—	a	
	Bearing span	mm	l	125,00	—
	Bearing span offset	mm	s	0,00	—
	External shaft diameter	mm	d_{sh}	100,00	—
	Internal shaft diameter	mm	d_{shi}	0,00	—
	Equivalent misalignment	µm	f_{sh}	As Formula (59)	
	Mesh misalignment	µm	f_{ma}	As Formula (66)	
	Minimum safety factor pitting	—	$S_{H\,min}$	1,00	
	Minimum safety factor tooth breakage	—	$S_{F\,min}$	1,00	
	Lubrication viscosity	mm^2/s	ν_{40}	320	
Load	Torque	kNm	T_1	9,000	
	Speed	min^{-1}	n_1	360,0	
	Required life	h	—	50 000	
	Life factor for contact stress, Z_{NT}, at 10^{10} cycles	—	—	0,85	0,85
	Life factor for tooth root stress, Y_{NT}, at 10^{10} cycles	—	—	0,85	0,85

© ISO 2022 – All rights reserved

Table 4 — Example 1 output values

Symbol	Description	Unit	Pinion	Gear
d	Reference diameter	mm	141,34	856,35
d_a	Tip diameter	mm	159,66	872,35
d_b	Base circle diameter	mm	132,20	800,97
x_E	Generating profile shift coefficient	—	0,117 8	- 0,027 5
d_f	Root diameter (based on x_E)	mm	120,82	833,52
d_{Ff}	Root form diameter (based on x_E)	mm	132,25	839,08
d_{Nf}	Start of active profile diameter	mm	132,92	845,23
d_w	Working pitch diameter	mm	141,67	858,33
F_t	Nominal tangential load at the reference cylinder	N	127 352	
$K_{F\alpha\text{-}B}$	Transverse load factor (root stress)	—	1,00	
$K_{F\beta\text{-}C}$	Face load factor (root stress)	—	1,13	
$K_{H\alpha\text{-}B}$	Transverse load factor (contact stress)	—	1,00	
$K_{H\beta\text{-}C}$	Face load factor (contact stress)	—	1,16	
$K_{v\text{-}B}$	Dynamic factor	—	1,00	
S_F	Tooth root breakage safety factor	—	2,09	2,25
S_H	Pitting safety factor	—	1,03	1,09
v_w	Pitch line velocity	m/s	2,67	
Y_B	Rim thickness factor	—	1,00	1,00
Y_{DT}	Deep tooth factor	—	1,00	
Y_F	Tooth form factor	—	1,26	1,07
Y_{NT}	Life factor for reference test conditions (tooth root stress)	—	0,89	0,92
Y_N	Life factor (tooth root stress)	—	0,89	0,92
Y_{RrelT}	Relative surface factor	—	0,96	0,96
Y_S	Stress correction factor	—	1,79	2,05
Y_{ST}	Stress correction factor for reference gears	—	2,00	
Y_X	Size factor	—	0,97	0,97
Y_β	Helix angle factor	—	0,97	
$Y_{\delta relT}$	Relative notch sensitivity factor	—	0,99	1,00
Z_B	Single pair tooth contact factor, pinion	—	1,00	
Z_β	Helix angle factor (pitting)	—	1,02	
Z_D	Single pair tooth contact factor, wheel	—	1,00	
Z_E	Elasticity factor	$\sqrt{N / mm^2}$	189,81	
Z_ε	Contact ratio factor	—	0,80	
Z_H	Zone factor	—	2,40	
Z_L	Lubricant factor	—	1,05	1,05
Z_{NT}	Life factor for reference test conditions (contact stress)	—	0,91	0,96
Z_N	Life factor (contact stress)	—	0,91	0,96
Z_R	Roughness factor	—	0,97	0,97
Z_v	Velocity factor	—	0,97	0,97
Z_W	Work hardening factor	—	1,00	1,00
Z_X	Size factor	—	1,00	1,00
ε_α	Transverse contact ratio	—	1,55	
ε_β	Overlap ratio	—	1,08	

© ISO 2022 – All rights reserved

Table 4 *(continued)*

Symbol	Description	Unit	Pinion	Gear
ε_γ	Total contact ratio	—	2,63	
σ_{F0}	Nominal tooth root stress	N/mm^2	350	339
σ_F	Tooth root stress	N/mm^2	395	382
$\sigma_{F\,lim}$	Limiting tooth root stress	N/mm^2	500	500
σ_{FP}	Permissible tooth root stress	N/mm^2	824	860
σ_H	Contact stress	N/mm^2	1 299	1 299
$\sigma_{H\,lim}$	Limiting contact stress	N/mm^2	1 500	1 500
σ_{H0}	Nominal contact stress	N/mm^2	1 207	
σ_{HP}	Permissible contact stress	N/mm^2	1 338	1 415
Intermediate calculation values				
$K_{v\text{-}B}$ intermediate calculation values				
$c_{\gamma\alpha}$	Mean value of mesh stiffness per unit facewidth (used for $K_{v\text{-}B}$, $K_{H\alpha\text{-}B}$, $K_{F\alpha\text{-}B}$)	N/(mm·µm)	17,5	
c'	Maximum tooth stiffness per unit facewidth (single stiffness) of a tooth pair	N/(mm·µm)	12,4	
m_{red}	Reduced gear pair mass per unit facewidth referenced to the line of action	kg/mm	0,067	
N	Resonance ratio	—	0,04	
$K_{H\beta\text{-}C}$ intermediate calculation values				
$c_{\gamma\beta}$	Mean value of mesh stiffness per unit facewidth (used for $K_{H\beta\text{-}C}$, $K_{F\beta\text{-}C}$)	N/(mm·µm)	14,8	
f_{sh0}	Shaft deformation under specific load	µm	0,012	
$F_{\beta x}$	Initial equivalent misalignment (before running-in)	µm	31,6	
$F_{\beta y}$	Effective equivalent misalignment (after running-in)	µm	26,9	
y_α	Running-in allowance for a gear pair for the calculation of $K_{H\alpha}$ (calculated with 50 % of max(f_{pb}, $f_{f\alpha}$))	µm	0,356	
y_β	Running-in allowance (equivalent misalignment)	µm	4,7	
f_{pb}	Transverse base pitch deviation	µm	8,4	
$f_{H\beta5}$	Tolerance on helix slope deviation for flank tolerance class 5	µm	9,0	
f_{sh}	Component of equivalent misalignment due to deformations of pinion and wheel shafts	µm	14,7	
f_{ma}	Mesh misalignment due to manufacturing deviations	µm	12,0	
Auxiliary values				
f_{ZCa}	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—	1,00	
f_ε	Load distribution influence factor	—	0,78	

© ISO 2022 – All rights reserved

4.4 Example 2: Single helical through-hardened gear pair

For example 2, input values are given in Tables 5 and 6.

Table 5 — Example 2 input values

Type	Description	Unit	Symbol	Pinion	Wheel
Geometry	Number of teeth	—	z	17	103
	Normal module	mm	m_n	8,00	
	Normal pressure angle	°	α_n	20,00	
	Helix angle	°	β	15,80	
	Hand of helix	—	—	Left	Right
	Facewidth (total)	mm	b	100,00	100,00
	Gap width	mm	—	—	—
	Edge chamfer	mm	—	0,00	0,00
	Contact facewidth (total)	mm	b_{eff}	100,00	
	Centre distance	mm	a	500,000	
	Span measurement	mm	W_k	38,196	307,943
	Number of teeth spanned	—	k	2	13
	Dimension between balls	mm	M_{dK}	—	—
	Ball diameter	mm	D_M	—	—
	Nominal profile shift coefficient	—	x	(0,145)	0,000
	Tip diameter	mm	d_a	159,66	872,35
	Basic rack dedendum coefficient	—	h_{fP}/m_n	1,250	1,250
	Tip chamfer	mm	h_K	0,00	0,00
	Basic rack fillet root radius coefficient	—	ρ_{fP}/m_n	0,39	0,39
	As cut basic rack undercut	mm	pr	0,00	0,00
	Material allowance for finishing	mm	q	0,00	0,00
	Residual fillet undercut, $s_{pr} = pr - q$	mm	s_{pr}	0,00	0,00
	Pinion cutter number of teeth	—	z_0	—	—
	Pinion cutter profile shift (ref)	—	x_0	—	—
	Flank finishing process	—	—	As cut	As cut
	Root finishing process	—	—	As cut	As cut
	Tip relief	µm	C_a	70	70
	Root relief	µm	C_f	0	0
	Profile modification compensate for the deflections	—	—	No	
	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—	f_{ZCa}	No modification	
Quality	Flank tolerance class	—	A	8	6
	Single pitch tolerance according to ISO 1328-1:2013	µm	f_{pT}	24,0	13,0
	Profile form deviation according to ISO 1328-1:2013	µm	$f_{f\alpha}$	27,0	13,0
	Helix slope deviation according to ISO 1328-1:2013	µm	$f_{H\beta}$	23,0	13,0
	Surface roughness – flank *Ra* (*Rz*)	µm	—	3,0 (18,0)	3,0 (18,0)
	Surface roughness – fillet *Ra* (*Rz*)	µm	—	3,0 (18,0)	3,0 (18,0)

© ISO 2022 – All rights reserved

Table 5 *(continued)*

Type	Description	Unit	Symbol	Pinion	Wheel
Material	Material	—	—	V (alloy steel)	V (alloy steel)
	Material quality	—	—	MQ	MQ
	Case hardness	—	—	310 HV	260 HV
	Core hardness	—	—	—	—
	Young's modulus	N/mm^2	E	206 000	206 000
	Poisson's ratio	—	v	0,3	0,3
	Yield/proof stress	N/mm^2	$\sigma_S/\sigma_{0,2}$	500,0	500,0
	Material density	kg/m^3	ρ	7 830	7 830
	Shot peen	—	—	No	No
	Limited pitting allowable	—	—	No	No
Application	Application factor	—	$K_{A\text{-}A}$	1,00	
	Mesh load factor	—	K_γ	1,00	
	Reverse bending	—	—	No	No
	Favourable contact position	—	—	No	No
	Helix modification (ISO 6336-1:2019, Table 12)	—	—	None (No. 1)	
	Dynamic factor, K_v, calculation method	—	—	Method B	
	Face load distribution factor, $K_{H\beta}$ and $K_{F\beta}$, calculation method	—	—	Method C	
	Number of meshes	—	N_M	1	1
	Gear blank type	—	—	Solid	Solid
	Web thickness	mm	b_s	—	—
	Inside diameter	mm	—	—	—
	Number of webs	—	—	—	—
	Arrangement (ISO 6336-1:2019, Figure 13)	—	—	a	
	Bearing span	mm	l	125,00	—
	Bearing span offset	mm	s	0,00	—
	External shaft diameter	mm	d_{sh}	100,00	—
	Internal shaft diameter	mm	d_{shi}	0,00	—
	Equivalent misalignment	µm	f_{sh}	15,0	
	Mesh misalignment	µm	f_{ma}	5,0	
	Minimum safety factor pitting	—	$S_{H\,min}$	1,00	
	Minimum safety factor tooth breakage	—	$S_{F\,min}$	1,00	
	Lubrication viscosity	mm^2/s	ν_{40}	320	
Load	Torque	kNm	T_1	1,000	
	Speed	min^{-1}	n_1	360,0	
	Required life	h	—	100 00	
	Life factor for contact stress, Y_{NT}, at 10^{10} cycles	—	—	0,85	0,85
	Life factor for tooth root stress, Y_{NT}, at 10^{10} cycles	—	—	0,85	0,85

© ISO 2022 – All rights reserved

Table 6 — Example 2 output values

Symbol	Description	Unit	Pinion	Gear
d	Reference diameter	mm	141,34	856,35
d_a	Tip diameter	mm	159,66	872,35
d_b	Base circle diameter	mm	132,20	800,97
x_E	Generating profile shift coefficient	—	0,117 8	- 0,027 5
d_f	Root diameter (based on x_E)	mm	123,22	835,92
d_{Ff}	Root form diameter (based on x_E)	mm	132,61	841,13
d_{Nf}	Start of active profile diameter	mm	132,92	845,23
d_w	Working pitch diameter	mm	141,67	858,33
F_t	Nominal tangential load at the reference cylinder	N	14 150	
$K_{F\alpha\text{-}B}$	Transverse load factor (root stress)	—	1,58	
$K_{F\beta\text{-}C}$	Face load factor (root stress)	—	1,61	
$K_{H\alpha\text{-}B}$	Transverse load factor (contact stress)	—	1,58	
$K_{H\beta\text{-}C}$	Face load factor (contact stress)	—	1,78	
$K_{v\text{-}B}$	Dynamic factor	—	1,04	
S_F	Tooth root breakage safety factor	—	5,57	5,42
S_H	Pitting safety factor	—	0,80	0,79
v_w	Pitch line velocity	m/s	2,67	
Y_B	Rim thickness factor	—	1,00	1,00
Y_{DT}	Deep tooth factor	—	1,00	
Y_F	Tooth form factor	—	1,11	1,02
Y_{NT}	Life factor for reference test conditions (tooth root stress)	—	0,92	0,95
Y_N	Life factor (tooth root stress)	—	0,92	0,95
Y_{RrelT}	Relative surface factor	—	0,96	0,96
Y_S	Stress correction factor	—	1,93	2,12
Y_{ST}	Stress correction factor for reference gears	—	2,00	
Y_X	Size factor	—	0,98	0,98
Y_β	Helix angle factor	—	0,97	
$Y_{\delta relT}$	Relative notch sensitivity factor	—	0,98	1,00
Z_B	Single pair tooth contact factor, pinion	—	1,10	
Z_β	Helix angle factor (pitting)	—	1,02	
Z_D	Single pair tooth contact factor, wheel	—	1,10	
Z_E	Elasticity factor	$\sqrt{N / mm^2}$	189,81	
Z_ε	Contact ratio factor	—	0,80	
Z_H	Zone factor	—	2,40	
Z_L	Lubricant factor	—	1,09	1,08
Z_{NT}	Life factor for reference test conditions (contact stress)	—	0,96	1,03
Z_N	Life factor (contact stress)	—	0,96	1,04
Z_R	Roughness factor	—	0,79	0,80
Z_v	Velocity factor	—	0,93	0,94
Z_W	Work hardening factor	—	1,00	1,00
Z_X	Size factor	—	1,00	1,00
ε_α	Transverse contact ratio	—	1,55	
ε_β	Overlap ratio	—	1,08	

© ISO 2022 – All rights reserved

Table 6 *(continued)*

Symbol	Description	Unit	Pinion	Gear
ε_γ	Total contact ratio	—	2,63	
σ_{F0}	Nominal tooth root stress	N/mm^2	37	37
σ_F	Tooth root stress	N/mm^2	98	99
$\sigma_{F\,lim}$	Limiting tooth root stress	N/mm^2	319	298
σ_{FP}	Permissible tooth root stress	N/mm^2	544	535
σ_H	Contact stress	N/mm^2	754	754
$\sigma_{H\,lim}$	Limiting contact stress	N/mm^2	780	714
σ_{H0}	Nominal contact stress	N/mm^2	402	
σ_{HP}	Permissible contact stress	N/mm^2	603	600
Intermediate calculation values				
$K_{v\text{-}B}$ intermediate calculation values				
$c_{\gamma\alpha}$	Mean value of mesh stiffness per unit facewidth (used for $K_{v\text{-}B}$, $K_{H\alpha\text{-}B}$, $K_{F\alpha\text{-}B}$)	N/(mm·µm)	18,9	
c'	Maximum tooth stiffness per unit facewidth (single stiffness) of a tooth pair	N/(mm·µm)	13,4	
m_{red}	Reduced gear pair mass per unit facewidth referenced to the line of action	kg/mm	0,069	
N	Resonance ratio	—	0,04	
$K_{H\beta\text{-}C}$ intermediate calculation values				
$c_{\gamma\beta}$	Mean value of mesh stiffness per unit facewidth (used for $K_{H\beta\text{-}C}$, $K_{F\beta\text{-}C}$)	N/(mm·µm)	16,1	
f_{sh0}	Shaft deformation under specific load	µm	0,102	
$F_{\beta x}$	Initial equivalent misalignment (before running-in)	µm	25,0	
$F_{\beta y}$	Effective equivalent misalignment (after running-in)	µm	14,2	
y_α	Running-in allowance for a gear pair (calculated with max(f_{pb}, $f_{f\alpha}$))	µm	5,793	
y_β	Running-in allowance (equivalent misalignment)	µm	10,7	
f_{pb}	Transverse base pitch deviation	µm	22,4	
$f_{H\beta5}$	Tolerance on helix slope deviation for flank tolerance class 5	µm	9,0	
f_{sh}	Component of equivalent misalignment due to deformations of pinion and wheel shafts	µm	15,0	
f_{ma}	Mesh misalignment due to manufacturing deviations	µm	5,0	
Auxiliary values				
f_{ZCa}	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—	1,20	
f_ε	Load distribution influence factor	—	0,78	

© ISO 2022 – All rights reserved

4.5 Example 3: Spur through-hardened gear pair

For example 3, input values and output values are given in Tables 7 and 8, respectively.

Table 7 — Example 3 input values

Type	Description	Unit	Symbol	Pinion	Wheel
Geometry	Number of teeth	—	z	17	108
	Normal module	mm	m_n	8,00	
	Normal pressure angle	°	α_n	20,00	
	Helix angle	°	β	0,00	
	Hand of helix	—	—	Left	Right
	Facewidth (total)	mm	b	100,00	100,00
	Gap width	mm	—	0,00	0,00
	Edge chamfer	mm	—	0,00	0,00
	Contact facewidth (total)	mm	b_{eff}	100,00	
	Centre distance	mm	a	500,000	
	Span measurement	mm	W_k	37,728	283,000
	Number of teeth spanned	—	k	2	12
	Dimension between balls	mm	M_{dK}	—	—
	Ball diameter	mm	D_M	—	—
	Nominal profile shift coefficient	—	x	0,100	(−0,100)
	Tip diameter	mm	d_a	153,60	878,40
	Basic rack dedendum coefficient	—	h_{fP}/m_n	1,250	1,250
	Tip chamfer	mm	h_K	0,00	0,00
	Basic rack fillet root radius coefficient	—	ρ_{fP}/m_n	0,45	0,40
	As cut basic rack undercut	mm	pr	0,000	0,000
	Material allowance for finishing	mm	q	0,000	0,000
	Residual fillet undercut, $s_{pr} = pr - q$	mm	s_{pr}	0,000	0,000
	Pinion cutter number of teeth	—	z_0	—	—
	Pinion cutter profile shift (ref)	—	x_0	—	—
	Flank finishing process	—	—	As cut	As cut
	Root finishing process	—	—	As cut	As cut
	Tip relief	µm	C_a	70	70
	Root relief	µm	C_f	0	0
	Profile modification compensate for the deflections	—	—	No	
	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—	f_{ZCa}	—	
Quality	Flank tolerance class	—	A	8	6
	Single pitch tolerance according to ISO 1328-1:2013	µm	f_{pT}	24,0	13,0
	Profile form deviation according to ISO 1328-1:2013	µm	$f_{f\alpha}$	27,0	13,0
	Helix slope deviation according to ISO 1328-1:2013	µm	$f_{H\beta}$	23,0	13,0
	Surface roughness – flank *Ra* (*Rz*)	µm	—	3,0 (18,0)	3,0 (18,0)
	Surface roughness – fillet *Ra* (*Rz*)	µm	—	3,0 (18,0)	3,0 (18,0)

© ISO 2022 – All rights reserved

Table 7 *(continued)*

Type	Description	Unit	Symbol	Pinion	Wheel
Material	Material	—	—	V (alloy steel)	V (alloy steel)
	Material quality	—	—	MQ	MQ
	Case hardness	—	—	310 HV	260 HV
	Core hardness	—	—	—	—
	Young's modulus	N/mm^2	E	206 000	206 000
	Poisson's ratio	—	v	0,3	0,3
	Yield/proof stress	N/mm^2	$\sigma_S/\sigma_{0,2}$	500,0	500,0
	Material density	kg/m^3	ρ	7 830	7 830
	Shot peen	—	—	No	No
	Limited pitting allowable	—	—	No	No
Application	Application factor	—	$K_{A\text{-}A}$	1,000	
	Mesh load factor	—	K_γ	1,00	
	Reverse bending	—	—	No	No
	Favourable contact position	—	—	No	No
	Helix modification (ISO 6336-1:2019, Table 12)	—	—	None (No. 1)	
	Dynamic factor, K_v, calculation method	—	—	Method B	
	Face load distribution factor, $K_{H\beta}$ and $K_{F\beta}$, calculation method	—	—	Method C	
	Number of meshes	—	N_M	1	1
	Gear blank type	—	—	Solid	Solid
	Web thickness	mm	b_s	—	—
	Inside diameter	mm	—	—	—
	Number of webs	—	—	—	—
	Arrangement (ISO 6336-1:2019, Figure 13)	—	—	a	
	Bearing span	mm	l	100,0	—
	Bearing span offset	mm	s	0,00	—
	External shaft diameter	mm	d_{sh}	100,00	—
	Internal shaft diameter	mm	d_{shi}	0,00	—
	Equivalent misalignment	µm	f_{sh}	As Formula (59)	
	Mesh misalignment	µm	f_{ma}	As Formula (66)	
	Minimum safety factor pitting	—	$S_{H\,min}$	1,00	
	Minimum safety factor tooth breakage	—	$S_{F\,min}$	1,00	
	Lubrication viscosity	mm^2/s	v_{40}	320	
Load	Torque	kNm	T_1	1,000	
	Speed	min^{-1}	n_1	360,0	
	Required life	h	—	10 000	
	Life factor for contact stress, Z_{NT}, at 10^{10} cycles	—	—	0,85	0,85
	Life factor for tooth root stress, Y_{NT}, at 10^{10} cycles	—	—	0,85	0,85

© ISO 2022 – All rights reserved

Table 8 — Example 3 output values

Symbol	Description	Unit	Pinion	Gear
d	Reference diameter	mm	136,00	864,00
d_a	Tip diameter	mm	153,60	878,40
d_b	Base circle diameter	mm	127,80	811,89
x_E	Generating profile shift coefficient	—	0,072 7	- 0,127 3
d_f	Root diameter (based on x_E)	mm	117,16	841,96
d_{Ff}	Root form diameter (based on x_E)	mm	127,91	847,59
d_{Nf}	Start of active profile diameter	mm	127,98	851,54
d_w	Working pitch diameter	mm	136,00	864,00
F_t	Nominal tangential load at the reference cylinder	N	14 706	
$K_{F\alpha\text{-}B}$	Transverse load factor (root stress)	—	1,23	
$K_{F\beta\text{-}C}$	Face load factor (root stress)	—	1,71	
$K_{H\alpha\text{-}B}$	Transverse load factor (contact stress)	—	1,23	
$K_{H\beta\text{-}C}$	Face load factor (contact stress)	—	1,92	
$K_{v\text{-}B}$	Dynamic factor	—	1,05	
S_F	Tooth root breakage safety factor	—	4,91	4,80
S_H	Pitting safety factor	—	0,75	0,82
v	Pitch line velocity	m/s	2,56	
Y_B	Rim thickness factor	—	1,00	1,00
Y_{DT}	Deep tooth factor	—	1,00	
Y_F	Tooth form factor	—	1,50	1,33
Y_{NT}	Life factor for reference test conditions (tooth root stress)	—	0,92	0,95
Y_N	Life factor (tooth root stress)	—	0,92	0,95
Y_{RrelT}	Relative surface factor	—	0,96	0,96
Y_S	Stress correction factor	—	1,82	2,06
Y_{ST}	Stress correction factor for reference gears	—	2,00	
Y_X	Size factor	—	0,98	0,98
Y_β	Helix angle factor	—	1,00	
$Y_{\delta relT}$	Relative notch sensitivity factor	—	0,98	0,99
Z_B	Single pair tooth contact factor, pinion	—	1,09	
Z_β	Helix angle factor (pitting)	—	1,00	
Z_D	Single pair tooth contact factor, wheel	—	1,00	
Z_E	Elasticity factor	$\sqrt{N / mm^2}$	189,81	
Z_ε	Contact ratio factor	—	0,88	
Z_H	Zone factor	—	2,49	
Z_L	Lubricant factor	—	1,09	1,08
Z_{NT}	Life factor for reference test conditions (contact stress)	—	0,96	1,03
Z_N	Life factor (contact stress)	—	0,96	1,04
Z_R	Roughness factor	—	0,79	0,80
Z_v	Velocity factor	—	0,93	0,94
Z_W	Work hardening factor	—	1,00	1,00
Z_X	Size factor	—	1,00	1,00
ε_α	Transverse contact ratio	—	1,66	
ε_β	Overlap ratio	—	0,00	

© ISO 2022 – All rights reserved

Table 8 *(continued)*

Symbol	Description	Unit	Pinion	Gear
ε_γ	Total contact ratio	—	1,66	
σ_{F0}	Nominal tooth root stress	N/mm^2	50	50
σ_F	Tooth root stress	N/mm^2	110	111
$\sigma_{F\,lim}$	Limiting tooth root stress	N/mm^2	319	298
σ_{FP}	Permissible tooth root stress	N/mm^2	540	533
σ_H	Contact stress	N/mm^2	802	735
$\sigma_{H\,lim}$	Limiting contact stress	N/mm^2	780	714
σ_{H0}	Nominal contact stress	N/mm^2	468	
σ_{HP}	Permissible contact stress	N/mm^2	600	599
Intermediate calculation values				
$K_{v\text{-}B}$ intermediate calculation values				
$c_{\gamma\alpha}$	Mean value of mesh stiffness per unit facewidth (used for $K_{v\text{-}B}$, $K_{H\alpha\text{-}B}$, $K_{F\alpha\text{-}B}$)	N/(mm·µm)	20,1	
c'	Maximum tooth stiffness per unit facewidth (single stiffness) of a tooth pair	N/(mm·µm)	13,5	
m_{red}	Reduced gear pair mass per unit facewidth referenced to the line of action	kg/mm	0,062	
N	Resonance ratio	—	0,04	
$K_{H\beta\text{-}C}$ intermediate calculation values				
$c_{\gamma\beta}$	Mean value of mesh stiffness per unit facewidth (used for $K_{H\beta\text{-}C}$, $K_{F\beta\text{-}C}$)	N/(mm·µm)	17,1	
f_{sh0}	Shaft deformation under specific load	µm	0,012	
$F_{\beta x}$	Initial equivalent misalignment (before running-in)	µm	29,0	
$F_{\beta y}$	Effective equivalent misalignment (after running-in)	µm	16,5	
y_α	Running-in allowance for a gear pair (calculated with max(f_{pb}, $f_{f\alpha}$))	µm	5,793	
y_β	Running-in allowance (equivalent misalignment)	µm	12,4	
f_{pb}	Transverse base pitch deviation	µm	22,6	
$f_{H\beta5}$	Tolerance on helix slope deviation for flank tolerance class 5	µm	9,0	
f_{sh}	Component of equivalent misalignment due to deformations of pinion and wheel shafts	µm	1,9	
f_{ma}	Mesh misalignment due to manufacturing deviations	µm	26,4	
Auxiliary values				
f_{ZCa}	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—	—	
f_ε	Load distribution influence factor	—	1,00	

© ISO 2022 – All rights reserved

4.6 Example 4: Spur case carburized gear pair

For example 4, input values and output values are given in Tables 9 and 10, respectively.

Table 9 — Example 4 input values

Type	Description	Unit	Symbol	Pinion	Wheel
Geometry	Number of teeth	—	z	17	108
	Normal module	mm	m_n	8,00	
	Normal pressure angle	°	α_n	20,00	
	Helix angle	°	β	0,00	
	Hand of helix	—	—	Left	Right
	Facewidth (total)	mm	b	100,00	100,00
	Gap width	mm	—	0,00	0,00
	Edge chamfer	mm	—	0,00	0,00
	Contact facewidth (total)	mm	b_{eff}	100,00	
	Centre distance	mm	a	500,000	
	Span measurement	mm	W_k	37,728	283,000
	Number of teeth spanned	—	k	2	12
	Dimension between balls	mm	M_{dK}	—	—
	Ball diameter	mm	D_M	—	—
	Nominal profile shift coefficient	—	x	0,100	(−0,100)
	Tip diameter	mm	d_a	154,60	878,40
	Basic rack dedendum coefficient	—	h_{fP}/m_n	1,400	1,400
	Tip chamfer	mm	h_K	0,00	0,00
	Basic rack fillet root radius coefficient	—	ρ_{fP}/m_n	0,39	0,39
	As cut basic rack undercut	mm	pr	0,000	0,000
	Material allowance for finishing	mm	q	0,000	0,000
	Residual fillet undercut, $s_{pr} = pr - q$	mm	s_{pr}	0,000	0,000
	Pinion cutter number of teeth	—	z_0	—	—
	Pinion cutter profile shift (ref)	—	x_0	—	—
	Flank finishing process	—	—	As cut	As cut
	Root finishing process	—	—	As cut	As cut
	Tip relief	µm	C_a	70	70
	Root relief	µm	C_f	0	0
	Profile modification compensate for the deflections	—	—	Yes	
	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019	—	f_{ZCa}	—	
Quality	Flank tolerance class	—	A	5	5
	Single pitch tolerance according to ISO 1328-1:2013	µm	f_{pT}	8,5	9,0
	Profile form deviation according to ISO 1328-1:2013	µm	$f_{f\alpha}$	9,5	9,5
	Helix slope deviation according to ISO 1328-1:2013	µm	$f_{H\beta}$	8,0	9,0
	Surface roughness – flank *Ra* (*Rz*)	µm	—	1,0 (6,0)	1,0 (6,0)
	Surface roughness – fillet *Ra* (*Rz*)	µm		3,0 (18,0)	3,0 (18,0)

© ISO 2022 – All rights reserved

Table 9 *(continued)*

Type	Description	Unit	Symbol	Pinion	Wheel
Material	Material	—	—	Eh	Eh
	Material quality	—	—	MQ	MQ
	Case hardness	—	—	60 HRC	60 HRC
	Core hardness	—	—	30 HRC	30 HRC
	Young's modulus	N/mm^2	E	206 000	206 000
	Poisson's ratio	—	v	0,3	0,3
	Yield/proof stress	N/mm^2	$\sigma_S/\sigma_{0,2}$	—	—
	Material density	kg/m^3	ρ	7 830	7 830
	Shot peen	—	—	No	No
	Limited pitting allowable	—	—	No	No
Application	Application factor	—	$K_{A\text{-}A}$	1,000	
	Mesh load factor	—	K_γ	1,00	
	Reverse bending	—	—	No	No
	Favourable contact position	—	—	No	No
	Helix modification (ISO 6336-1:2019, Table 12)	—	—	None (No. 1)	
	Dynamic factor, K_v, calculation method	—	—	Method B	
	Face load distribution factor, $K_{H\beta}$ and $K_{F\beta}$, calculation method	—	—	Method C	
	Number of meshes	—	N_M	1	1
	Gear blank type	—	—	Solid	Solid
	Web thickness	mm	b_s	—	—
	Inside diameter	mm	—	—	—
	Number of webs	—	—	—	—
	Arrangement (ISO 6336-1:2019, Figure 13)	—	—	a	
	Bearing span	mm	l	100,0	—
	Bearing span offset	mm	s	0,00	—
	External shaft diameter	mm	d_{sh}	100,00	—
	Internal shaft diameter	mm	d_{shi}	0,00	—
	Equivalent misalignment	µm	f_{sh}	As Formula (59)	
	Mesh misalignment	µm	f_{ma}	As Formula (66)	
	Minimum safety factor pitting	—	$S_{H\,min}$	1,00	
	Minimum safety factor tooth breakage	—	$S_{F\,min}$	1,00	
	Lubrication viscosity	mm^2/s	ν_{40}	320	
Load	Torque	kNm	T_1	9,000	
	Speed	min^{-1}	n_1	360,0	
	Required life	h	—	50 000	
	Life factor for contact stress, Z_{NT}, at 10^{10} cycles	—	—	0,85	0,85
	Life factor for tooth root stress, Y_{NT}, at 10^{10} cycles	—	—	0,85	0,85

© ISO 2022 – All rights reserved

Table 10 — Example 4 output values

Symbol	Description	Unit	Pinion	Gear
d	Reference diameter	mm	136,00	864,00
d_a	Tip diameter	mm	154,60	878,40
d_b	Base circle diameter	mm	127,80	811,89
x_E	Generating profile shift coefficient	—	0,072 7	- 0,127 3
d_f	Root diameter (based on x_E)	mm	114,76	839,56
d_{Ff}	Root form diameter (based on x_E)	mm	127,81	845,52
d_{Nf}	Start of active profile diameter	mm	127,98	851,00
d_w	Working pitch diameter	mm	136,00	864,00
F_t	Nominal tangential load at the reference cylinder	N	132 353	
$K_{F\alpha\text{-}B}$	Transverse load factor (root stress)	—	1,00	
$K_{F\beta\text{-}C}$	Face load factor (root stress)	—	1,14	
$K_{H\alpha\text{-}B}$	Transverse load factor (contact stress)	—	1,00	
$K_{H\beta\text{-}C}$	Face load factor (contact stress)	—	1,18	
$K_{v\text{-}B}$	Dynamic factor	—	1,00	
S_F	Tooth root breakage safety factor	—	1,43	1,66
S_H	Pitting safety factor	—	0,83	0,93
v_w	Pitch line velocity	m/s	2,56	
Y_B	Rim thickness factor	—	1,00	1,00
Y_{DT}	Deep tooth factor	—	1,00	
Y_F	Tooth form factor	—	1,77	1,36
Y_{NT}	Life factor for reference test conditions (tooth root stress)	—	0,89	0,92
Y_N	Life factor (tooth root stress)	—	0,89	0,92
Y_{RrelT}	Relative surface factor	—	0,96	0,96
Y_S	Stress correction factor	—	1,72	2,01
Y_{ST}	Stress correction factor for reference gears	—	2,00	
Y_X	Size factor	—	0,97	0,97
Y_β	Helix angle factor	—	1,00	
$Y_{\delta relT}$	Relative notch sensitivity factor	—	0,99	1,00
Z_B	Single pair tooth contact factor, pinion	—	1,07	
Z_β	Helix angle factor (pitting)	—	1,00	
Z_D	Single pair tooth contact factor, wheel	—	1,00	
Z_E	Elasticity factor	$\sqrt{N / mm^2}$	189,81	
Z_ε	Contact ratio factor	—	0,88	
Z_H	Zone factor	—	2,49	
Z_L	Lubricant factor	—	1,05	1,05
Z_{NT}	Life factor for test reference conditions (contact stress)	—	0,91	0,96
Z_N	Life factor (contact stress)	—	0,91	0,96
Z_R	Roughness factor	—	0,96	0,96
Z_v	Velocity factor	—	0,97	0,97
Z_W	Work hardening factor	—	1,00	1,00
Z_X	Size factor	—	1,00	1,00
ε_α	Transverse contact ratio	—	1,70	
ε_β	Overlap ratio	—	0,00	

© ISO 2022 – All rights reserved

Table 10 *(continued)*

Symbol	Description	Unit	Pinion	Gear
ε_γ	Total contact ratio	—	1,70	
σ_{F0}	Nominal tooth root stress	N/mm^2	502	452
σ_F	Tooth root stress	N/mm^2	574	518
$\sigma_{F\,lim}$	Limiting tooth root stress	N/mm^2	500	500
σ_{FP}	Permissible tooth root stress	N/mm^2	823	860
σ_H	Contact stress	N/mm^2	1 617	1 512
$\sigma_{H\,lim}$	Limiting contact stress	N/mm^2	1 500	1 500
σ_{H0}	Nominal contact stress	N/mm^2	1 392	
σ_{HP}	Permissible contact stress	N/mm^2	1 335	1 412
Intermediate calculation values				
$K_{v\text{-}B}$ intermediate calculation values				
$c_{\gamma\alpha}$	Mean value of mesh stiffness per unit facewidth (used for $K_{v\text{-}B}$, $K_{H\alpha\text{-}B}$, $K_{F\alpha\text{-}B}$)	N/(mm·µm)	18,9	
c'	Maximum tooth stiffness per unit facewidth (single stiffness) of a tooth pair	N/(mm·µm)	12,4	
m_{red}	Reduced gear pair mass per unit facewidth referenced to the line of action	kg/mm	0,061	
N	Resonance ratio	—	0,04	
$K_{H\beta\text{-}C}$ intermediate calculation values				
$c_{\gamma\beta}$	Mean value of mesh stiffness per unit facewidth (used for $K_{H\beta\text{-}C}$, $K_{F\beta\text{-}C}$)	N/(mm·µm)	16,1	
f_{sh0}	Shaft deformation under specific load	µm	0,012	
$F_{\beta x}$	Initial equivalent misalignment (before running-in)	µm	34,0	
$F_{\beta y}$	Effective equivalent misalignment (after running-in)	µm	28,9	
y_α	Running-in allowance for a gear pair for the calculation of $K_{H\alpha}$ (calculated with 50 % of max(f_{pb}, $f_{f\alpha}$))	µm	0,356	
y_β	Running-in allowance (equivalent misalignment)	µm	5,1	
f_{pb}	Transverse base pitch deviation	µm	8,5	
$f_{H\beta5}$	Tolerance on helix slope deviation for flank tolerance class 5	µm	9,0	
f_{sh}	Component of equivalent misalignment due to deformations of pinion and wheel shafts	µm	16,5	
f_{ma}	Mesh misalignment due to manufacturing deviations	µm	12,0	
Auxiliary values				
f_{ZCa}	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—	—	
f_ε	Load distribution influence factor	—	1,00	

© ISO 2022 – All rights reserved

4.7 Example 5: Spur gear pair with an induction hardened pinion and through-hardened cast gear

For example 5, input values and output values are given in Tables 11 and 12, respectively.

Table 11 — Example 5 input values

Type	Description	Unit	Symbol	Pinion	Wheel
Geometry	Number of teeth	—	z	27	192
	Normal module	mm	m_n	32,00	
	Normal pressure angle	°	α_n	20,00	
	Helix angle	°	β	0,00	
	Hand of helix	—	—	—	—
	Facewidth (total)	mm	b	500,00	500,00
	Gap width	mm	—	0,00	0,00
	Edge chamfer	mm	—	0,00	0,00
	Contact facewidth (total)	mm	b_{eff}	500,00	
	Centre distance	mm	a	3 504,000	
	Span measurement	mm	W_k	247,771	2 022,148
	Number of teeth spanned	—	k	3	21
	Dimension between balls	mm	M_{dK}	—	—
	Ball diameter	mm	D_M	—	—
	Nominal profile shift coefficient	—	x	0,000	(0,000)
	Tip diameter	mm	d_a	928,00	6 208,00
	Basic rack dedendum coefficient	—	h_{fP}/m_n	1,250	1,250
	Tip chamfer	mm	h_K	0,00	0,00
	Basic rack fillet root radius coefficient	—	ρ_{fP}/m_n	0,39	0,39
	As cut basic rack undercut	mm	pr	0,000	0,000
	Material allowance for finishing	mm	q	0,000	0,000
	Residual fillet undercut, $s_{pr} = pr - q$	mm	s_{pr}	0,000	0,000
	Pinion cutter number of teeth	—	z_0	—	—
	Pinion cutter profile shift (ref)	—	x_0	—	—
	Flank finishing process	—	—	As cut	As cut
	Root finishing process	—	—	As cut	As cut
	Tip relief	µm	C_a	0	0
	Root relief	µm	C_f	0	0
	Profile modification compensate for the deflections	—	—	No	
	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—	f_{ZCa}	—	
Quality	Flank tolerance class	—	A	6	9
	Single pitch tolerance according to ISO 1328-1:2013	µm	f_{pT}	26,0	96,0
	Profile form deviation according to ISO 1328-1:2013	µm	$f_{f\alpha}$	32,0	90,0
	Helix slope deviation according to ISO 1328-1:2013	µm	$f_{H\beta}$	19,0	63,0
	Surface roughness – flank *Ra* (*Rz*)	µm	—	2,5 (15,0)	3,0 (18,0)
	Surface roughness – fillet *Ra* (*Rz*)	µm	—	3,0 (18,0)	3,0 (18,0)

© ISO 2022 – All rights reserved

Table 11 *(continued)*

Type	Description	Unit	Symbol	Pinion	Wheel
Material	Material	—	—	IF	St (cast)
	Material quality	—	—	ML	MQ
	Case hardness	—	—	550 HV	200 HBW
	Core hardness	—	—	166 HV	
	Young's modulus	N/mm^2	E	206 000	202 000
	Poisson's ratio	—	ν	0,3	0,3
	Yield/proof stress	N/mm^2	$\sigma_S/\sigma_{0,2}$		400,0
	Material density	kg/m^3	ρ	7 830	7 830
	Shot peen	—	—	No	No
	Limited pitting allowable	—	—	No	No
Application	Application factor	—	$K_{A\text{-}A}$	1,00	
	Mesh load factor	—	K_γ	1,00	
	Reverse bending	—	—	No	No
	Favourable contact position	—	—	No	No
	Helix modification (ISO 6336-1:2019, Table 12)	—	—	None (No. 1)	
	Dynamic factor, K_v, calculation method	—	—	Method B	
	Face load distribution factor, $K_{H\beta}$ and $K_{F\beta}$, calculation method	—	—	Method C	
	Number of meshes	—	N_M	1	1
	Gear blank type	—	—	Solid	Solid
	Web thickness	mm	b_s	—	—
	Inside diameter	mm	—	—	—
	Number of webs	—	—	—	—
	Arrangement (ISO 6336-1:2019, Figure 13)	—	—	a	
	Bearing span	mm	l	1 000,00	—
	Bearing span offset	mm	s	0,00	—
	External shaft diameter	mm	d_{sh}	400,00	—
	Internal shaft diameter	mm	d_{shi}	0,00	—
	Equivalent misalignment	µm	f_{sh}	As Formula (59)	
	Mesh misalignment	µm	f_{ma}	As Formula (66)	
	Minimum safety factor pitting	—	$S_{H\,min}$	1,00	
	Minimum safety factor tooth breakage	—	$S_{F\,min}$	1,00	
	Lubrication viscosity	mm^2/s	ν_{40}	160	
Load	Torque	kNm	T_1	120,000	
	Speed	min^{-1}	n_1	200,0	
	Required life	h	—	25 000	
	Life factor for contact stress, Z_{NT}, at 10^{10} cycles	—	—	0,85	0,85
	Life factor for tooth root stress, Y_{NT}, at 10^{10} cycles	—	—	0,85	0,85

© ISO 2022 – All rights reserved

Table 12 — Example 5 output values

Symbol	Description	Unit	Pinion	Gear
d	Reference diameter	mm	864,00	6 144,00
d_a	Tip diameter	mm	928,00	6 208,00
d_b	Base circle diameter	mm	811,89	5 773,47
x_E	Generating profile shift coefficient	—	- 0,022 9	-0,022 9
d_f	Root diameter (based on x_E)	mm	782,54	6 062,54
d_{Ff}	Root form diameter (based on x_E)	mm	818,70	6 081,59
d_{Nf}	Start of active profile diameter	mm	820,02	6 093,06
d_w	Working pitch diameter	mm	864,00	6 144,00
F_t	Nominal tangential load at the reference cylinder	N	277 778	
$K_{F\alpha\text{-}B}$	Transverse load factor (root stress)	—	1,33	
$K_{F\beta\text{-}C}$	Face load factor (root stress)	—	1,39	
$K_{H\alpha\text{-}B}$	Transverse load factor (contact stress)	—	1,33	
$K_{H\beta\text{-}C}$	Face load factor (contact stress)	—	1,47	
$K_{v\text{-}B}$	Dynamic factor	—	1,26	
S_F	Tooth root breakage safety factor	—	3,27	1,85
S_H	Pitting safety factor	—	1,44	0,53
v_w	Pitch line velocity	m/s	9,05	
Y_B	Rim thickness factor	—	1,00	1,00
Y_{DT}	Deep tooth factor	—	1,00	
Y_F	Tooth form factor	—	1,33	1,15
Y_{NT}	Life factor for reference test conditions (tooth root stress)	—	0,91	0,95
Y_N	Life factor (tooth root stress)	—	0,91	0,95
Y_{RrelT}	Relative surface factor	—	0,96	0,98
Y_S	Stress correction factor	—	1,94	2,30
Y_{ST}	Stress correction factor for reference gears	—	2,00	
Y_X	Size factor	—	0,80	0,85
Y_β	Helix angle factor	—	1,00	
$Y_{\delta relT}$	Relative notch sensitivity factor	—	0,99	1,00
Z_B	Single pair tooth contact factor, pinion	—	1,06	
Z_β	Helix angle factor (pitting)	—	1,00	
Z_D	Single pair tooth contact factor, wheel	—	1,00	
Z_E	Elasticity factor	$\sqrt{N/mm^2}$	188,88	
Z_ε	Contact ratio factor	—	0,86	
Z_H	Zone factor	—	2,49	
Z_L	Lubricant factor	—	0,99	0,99
Z_{NT}	Life factor for reference test conditions (contact stress)	—	0,95	1,01
Z_N	Life factor (contact stress)	—	0,95	1,01
Z_R	Roughness factor	—	0,88	0,88
Z_v	Velocity factor	—	0,99	0,99
Z_W	Work hardening factor (only applicable for through hardened steel, not cast iron)	—	1,00	1,00
Z_X	Size factor	—	1,00	1,00
ε_α	Transverse contact ratio	—	1,77	
ε_β	Overlap ratio	—	0,00	

© ISO 2022 – All rights reserved

Table 12 *(continued)*

Symbol	Description	Unit	Pinion	Gear
ε_γ	Total contact ratio	—	1,77	
σ_{F0}	Nominal tooth root stress	N/mm^2	45	46
σ_F	Tooth root stress	N/mm^2	104	107
$\sigma_{F\,lim}$	Limiting tooth root stress	N/mm^2	244	125
σ_{FP}	Permissible tooth root stress	N/mm^2	340	197
σ_H	Contact stress	N/mm^2	577	546
$\sigma_{H\,lim}$	Limiting contact stress	N/mm^2	1 009	328
σ_{H0}	Nominal contact stress	N/mm^2	348	
σ_{HP}	Permissible contact stress	N/mm^2	830	290
Intermediate calculation values				
$K_{v\text{-}B}$ intermediate calculation values				
$c_{\gamma\alpha}$	Mean value of mesh stiffness per unit facewidth (used for $K_{v\text{-}B}$, $K_{H\alpha\text{-}B}$, $K_{F\alpha\text{-}B}$)	N/(mm·µm)	22,4	
c'	Maximum tooth stiffness per unit facewidth (single stiffness) of a tooth pair	N/(mm·µm)	14,2	
m_{red}	Reduced gear pair mass per unit facewidth referenced to the line of action	kg/mm	2,457	
N	Resonance ratio	—	0,19	
$K_{H\beta\text{-}C}$ intermediate calculation values				
$c_{\gamma\beta}$	Mean value of mesh stiffness per unit facewidth (used for $K_{H\beta\text{-}C}$, $K_{F\beta\text{-}C}$)	N/(mm·µm)	19,1	
f_{sh0}	Shaft deformation under specific load	µm	0,008	
$F_{\beta x}$	Initial equivalent misalignment (before running-in)	µm	73,0	
$F_{\beta y}$	Effective equivalent misalignment (after running-in)	µm	34,4	
y_α	Running-in allowance for a gear pair (calculated with max(f_{pb}, $f_{f\alpha}$))	µm	21,0	
y_β	Running-in allowance (equivalent misalignment)	µm	38,6	
f_{pb}	Transverse base pitch deviation	µm	90,2	
$f_{H\beta5}$	Tolerance on helix slope deviation for flank tolerance class 5	µm	16,0	
f_{sh}	Component of equivalent misalignment due to deformations of pinion and wheel shafts	µm	5,4	
f_{ma}	Mesh misalignment due to manufacturing deviations	µm	65,8	
Auxiliary values				
f_{ZCa}	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—	—	
f_ε	Load distribution influence factor	—	1,00	

© ISO 2022 – All rights reserved

4.8 Example 6: Spur internal through-hardened gear pair

For example 6, input values and output values are given in Tables 13 and 14, respectively.

Table 13 — Example 6 input values

Type	Description	Unit	Symbol	Pinion	Wheel
Geometry	Number of teeth	—	z	15	–99
	Normal module	mm	m_n	12,00	
	Normal pressure angle	°	α_n	20,00	
	Helix angle	°	β	0,00	
	Hand of helix	—	—	—	—
	Facewidth (total)	mm	b	125,00	125,00
	Gap width	mm	—	0,00	0,00
	Edge chamfer	mm	—	0,00	0,00
	Contact facewidth (total)	mm	b_{eff}	125,00	
	Centre distance	mm	a	–500,000	
	Span measurement	mm	W_k	58,161	—
	Number of teeth spanned	—	k	2	—
	Dimension between balls	mm	M_{dK}	—	1 154,900
	Ball diameter	mm	D_M	—	21,60
	Nominal profile shift coefficient	—	x	(0,323)	0,000
	Tip diameter	mm	d_a	211,75	–1 166,00
	Basic rack dedendum coefficient	—	h_{fP}/m_n	1,250	1,250
	Tip chamfer	mm	h_K	0,00	0,00
	Basic rack fillet root radius coefficient	—	ρ_{fP}/m_n	0,39	—
	As cut basic rack undercut	mm	pr	0,000	0,000
	Material allowance for finishing	mm	q	0,000	0,000
	Residual fillet undercut, $s_{pr} = pr - q$	mm	s_{pr}	0,000	0,000
	Pinion cutter number of teeth	—	z_0	—	20
	Pinion cutter profile shift (ref)	—	x_0	—	0,00
	Pinion cutter tip radius coefficient	—	ρ_{aP0}	—	0,001
	Flank finishing process	—	—	As cut	As cut
	Root finishing process	—	—	As cut	As cut
	Tip relief	µm	C_a	70	70
	Root relief	µm	C_f	0	0
	Profile modification compensate for the deflections	—	—	No	
	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—	f_{ZCa}	—	
Quality	Flank tolerance class	—	A	6	8
	Single pitch tolerance according to ISO 1328-1:2013	µm	f_{pT}	14,0	31,0
	Profile form deviation according to ISO 1328-1:2013	µm	$f_{f\alpha}$	16,0	33,0
	Helix slope deviation according to ISO 1328-1:2013	µm	$f_{H\beta}$	12,0	27,0
	Surface roughness – flank *Ra* (*Rz*)	µm	—	1,0 (6,0)	3,0 (18,0)
	Surface roughness – fillet *Ra* (*Rz*)	µm	—	3,0 (18,0)	3,0 (18,0)

© ISO 2022 – All rights reserved

Table 13 *(continued)*

Type	Description	Unit	Symbol	Pinion	Wheel
Material	Material	—	—	V	V
	Material quality	—	—	MQ	MQ
	Case hardness	various	—	310 HV	260 HV
	Core hardness	various	—	—	—
	Young's modulus	N/mm^2	E	206 000	206 000
	Poisson's ratio	—	v	0,3	0,3
	Yield/proof stress	N/mm^2	$\sigma_S/\sigma_{0,2}$	500,0	500,0
	Material density	kg/m^3	ρ	7 830	7 830
	Shot peen	—	—	No	No
	Limited pitting allowable	—	—	No	No
Application	Application factor	—	$K_{A\text{-}A}$	1,300	
	Mesh load factor	—	K_γ	1,00	
	Reverse bending	—	—	No	No
	Favourable contact position	—	—	No	No
	Helix modification (ISO 6336-1:2019, Table 12)	—	—	None (No. 1)	
	Dynamic factor, K_v, calculation method	—	—	Method B	
	Face load distribution factor, $K_{H\beta}$ and $K_{F\beta}$, calculation method	—	—	Method C	
	Number of meshes	—	N_M	1	1
	Gear blank type	—	—	Solid	Solid
	Web thickness	mm	b_s	—	—
	Inside diameter	mm	—	—	—
	Number of webs	—	—	—	—
	Arrangement (ISO 6336-1:2019, Figure 13)	—	—	a	
	Bearing span	mm	l	200,0	—
	Bearing span offset	mm	s	0,00	—
	External shaft diameter	mm	d_{sh}	100,00	—
	Internal shaft diameter	mm	d_{shi}	0,00	—
	Equivalent misalignment	µm	f_{sh}	As Formula (59)	
	Mesh misalignment	µm	f_{ma}	As Formula (66)	
	Minimum safety factor pitting	—	$S_{H\,min}$	1,00	
	Minimum safety factor tooth breakage	—	$S_{F\,min}$	1,00	
	Lubrication viscosity	mm^2/s	ν_{40}	320	
Load	Torque	kNm	T_1	1,000	
	Speed	min^{-1}	n_1	360,0	
	Required life	h	—	10 000	
	Life factor for contact stress, Z_{NT}, at 10^{10} cycles	—	—	0,85	0,85
	Life factor for tooth root stress, Y_{NT}, at 10^{10} cycles	—	—	0,85	0,85

© ISO 2022 – All rights reserved

Table 14 — Example 6 output values

Symbol	Description	Unit	Pinion	Gear
d	Reference diameter	mm	180,00	–1 188,00
d_a	Tip diameter	mm	211,75	–1 166,00
d_b	Base circle diameter	mm	169,14	–1 116,35
x_E	Generating profile shift coefficient	—	0,304 8	-0,018 2
d_f	Root diameter (based on x_E)	mm	157,31	–1 218,44
d_{Ff}	Root form diameter (based on x_E)	mm	169,66	–1 212,79
d_{Nf}	Start of active profile diameter	mm	169,90	–1 202,89
d_w	Working pitch diameter	mm	178,57	–1 178,57
F_t	Nominal tangential load at the reference cylinder	N	11 111	
$K_{F\alpha\text{-}B}$	Transverse load factor (root stress)	—	1,31	
$K_{F\beta\text{-}C}$	Face load factor (root stress)	—	1,89	
$K_{H\alpha\text{-}B}$	Transverse load factor (contact stress)	—	1,24	
$K_{H\beta\text{-}C}$	Face load factor (contact stress)	—	2,24	
$K_{v\text{-}B}$	Dynamic factor	—	1,10	
S_F	Tooth root breakage safety factor	—	7,40	5,66
S_H	Pitting safety factor	—	1,16	1,16
v_w	Pitch line velocity	m/s	3,37	
Y_B	Rim thickness factor	—	1,00	1,00
Y_{DT}	Deep tooth factor	—	1,00	
Y_F	Tooth form factor	—	1,35	1,14
Y_{NT}	Life factor for reference test conditions (tooth root stress)	—	0,92	0,95
Y_N	Life factor (tooth root stress)	—	0,92	0,95
Y_{RrelT}	Relative surface factor	—	0,96	0,96
Y_S	Stress correction factor	—	2,04	3,42
Y_{ST}	Stress correction factor for reference gears	—	2,00	
Y_X	Size factor	—	0,96	0,96
Y_β	Helix angle factor	—	1,00	
$Y_{\delta relT}$	Relative notch sensitivity factor	—	0,99	1,10
Z_B	Single pair tooth contact factor, pinion	—	1,01	
Z_β	Helix angle factor (pitting)	—	1,00	
Z_D	Single pair tooth contact factor, wheel	—	1,00	
Z_E	Elasticity factor	$\sqrt{N / mm^2}$	189,81	
Z_ε	Contact ratio factor	—	0,90	
Z_H	Zone factor	—	2,59	
Z_L	Lubricant factor	—	1,09	1,08
Z_{NT}	Life factor for reference test conditions (contact stress)	—	0,96	1,03
Z_N	Life factor (contact stress)	—	0,96	1,04
Z_R	Roughness factor	—	0,86	0,87
Z_v	Velocity factor	—	0,94	0,95
Z_W	Work hardening factor	—	1,00	1,00
Z_X	Size factor	—	1,00	1,00

© ISO 2022 – All rights reserved

Table 14 *(continued)*

Symbol	Description	Unit	Pinion	Gear
ε_α	Transverse contact ratio	—	1,57	
ε_β	Overlap ratio	—	0,00	
ε_γ	Total contact ratio	—	1,57	
σ_{F0}	Nominal tooth root stress	N/mm^2	20	29
σ_F	Tooth root stress	N/mm^2	72	102
$\sigma_{F\,lim}$	Limiting tooth root stress	N/mm^2	319	298
σ_{FP}	Permissible tooth root stress	N/mm^2	534	578
σ_H	Contact stress	N/mm^2	572	568
$\sigma_{H\,lim}$	Limiting contact stress	N/mm^2	780	714
σ_{H0}	Nominal contact stress	N/mm^2	286	
σ_{HP}	Permissible contact stress	N/mm^2	662	660
Intermediate calculation values				
$K_{v\text{-}B}$ intermediate calculation values				
$c_{\gamma\alpha}$	Mean value of mesh stiffness per unit face-width (used for $K_{v\text{-}B}$, $K_{H\alpha\text{-}B}$, $K_{F\alpha\text{-}B}$)	N/(mm·µm)	20,8	
c'	Maximum tooth stiffness per unit facewidth (single stiffness) of a tooth pair	N/(mm·µm)	14,6	
m_{red}	Reduced gear pair mass per unit facewidth referenced to the line of action	kg/mm	0,123	
N	Resonance ratio	—	0,04	
$K_{H\beta\text{-}C}$ intermediate calculation values				
$c_{\gamma\beta}$	Mean value of mesh stiffness per unit face-width (used for $K_{H\beta\text{-}C}$, $K_{F\beta\text{-}C}$)	N/(mm·µm)	17,7	
f_{sh0}	Shaft deformation under specific load	µm	0,011	
$F_{\beta x}$	Initial equivalent misalignment (before running-in)	µm	31,4	
$F_{\beta y}$	Effective equivalent misalignment (after running-in)	µm	17,9	
y_α	Running-in allowance for a gear pair (calculated with max(f_{pb},$f_{f\alpha}$))	µm	7,080	
y_β	Running-in allowance (equivalent misalignment)	µm	13,5	
f_{pb}	Transverse base pitch deviation	µm	29,1	
$f_{H\beta5}$	Tolerance on helix slope deviation for flank tolerance class 5	µm	9,5	
f_{sh}	Component of equivalent misalignment due to deformations of pinion and wheel shafts	µm	1,4	
f_{ma}	Mesh misalignment due to manufacturing deviations	µm	29,5	
Auxiliary values				
f_{ZCa}	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—	—	
f_ε	Load distribution influence factor	—	1,00	

© ISO 2022 – All rights reserved

4.9 Example 7: Double helical through-hardened wrought gear pair

For example 7, input values and output values are given in Tables 15 and 16, respectively.

Table 15 — Example 7 input values

Type	Description	Unit	Symbol	Pinion	Wheel
Geometry	Number of teeth	—	z	86	429
	Normal module	mm	m_n	1,693 333 3 (15 DP)	
	Normal pressure angle	°	α_n	20,00	
	Helix angle	°	β	18,31	
	Hand of helix	—	—	Double helical	
	Facewidth (total)	mm	b	165,1 (82,55 × 2)	165,1 (82,55 × 2)
	Gap width	mm	—	50,80	50,80
	Edge chamfer	mm	—	0,00	0,00
	Contact facewidth (total)	mm	—	165,1 (82,55 × 2)	
	Centre distance	mm	a	460,375	
	Span measurement	mm	W_k	60,068	289,367
	Number of teeth spanned	—	k	12	56
	Dimension between balls	mm	M_{dK}	—	—
	Ball diameter	mm	D_M	—	—
	Nominal profile shift coefficient	—	x	0,361 5	(0,286 3)
	Tip diameter	mm	d_a	157,99	769,52
	Basic rack dedendum coefficient	—	h_{fP}/m_n	1,250	1,250
	Tip chamfer	mm	h_K	0,00	0,00
	Basic rack fillet root radius coefficient	—	ρ_{fP}/m_n	0,38	0,38
	As cut basic rack undercut	mm	pr	0,000	0,000
	Material allowance for finishing	mm	q	0,000	0,000
	Residual fillet undercut, $s_{pr} = pr - q$	mm	s_{pr}	0,000	0,000
	Pinion cutter number of teeth	—	z_0	—	—
	Pinion cutter profile shift (ref)	—	x_0	—	—
	Flank finishing process	—	—	As cut	As cut
	Root finishing process	—	—	As cut	As cut
	Tip relief	µm	C_a	13	13
	Root relief	µm	C_f	0	0
	Profile modification compensate for the deflections	—	—	No	
	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—	f_{ZCa}	manufacturers experience	
Quality	Flank tolerance class	—	A	5	5
	Single pitch tolerance according to ISO 1328-1:2013	µm	f_{pT}	6,0	6,5
	Profile form deviation according to ISO 1328-1:2013	µm	$f_{f\alpha}$	6,0	6,0
	Helix slope deviation	µm	$f_{H\beta}$	8,0	8,5
	Surface roughness – flank *Ra* (*Rz*)	µm	—	1,0 (6,0)	1,0 (6,0)
	Surface roughness – fillet *Ra* (*Rz*)	µm	—	3,0 (18,0)	3,0 (18,0)

© ISO 2022 – All rights reserved

Table 15 *(continued)*

Type	Description	Unit	Symbol	Pinion	Wheel
Material	Material	—	—	V (alloy steel)	V (alloy steel)
	Material quality	—	—	ML	ML
	Case hardness	—	—	342 HB	300 HB
	Core hardness	—	—	—	—
	Young's modulus	N/mm^2	E	206 000	206 000
	Poisson's ratio	—	ν	0,3	0,3
	Yield/proof stress	N/mm^2	$\sigma_S/\sigma_{0,2}$	1 000,0	1 000,0
	Material density	kg/m^3	ρ	7 830	7 830
	Shot peen	—	—	No	No
	Limited pitting allowable	—	—	Yes	Yes
Application	Application factor	—	$K_{A\text{-}A}$	1,000	
	Mesh load factor	—	K_γ	1,00	
	Reverse bending	—	—	No	No
	Favourable contact position	—	—	Yes	Yes
	Helix modification (ISO 6336-1:2019, Table 12)	—	—	None (No. 1)	
	Dynamic factor, K_v, calculation method	—	—	Method B	
	Face load distribution factor, $K_{H\beta}$ and $K_{F\beta}$, calculation method	—	—	Method C	
	Number of meshes	—	N_M	1	1
	Gear blank type	—	—	Solid	Solid
	Web thickness	mm	b_s	—	—
	Inside diameter	mm	—	—	—
	Number of webs	—	—	—	—
	Arrangement (ISO 6336-1:2019, Figure 13)	—	—	a	
	Bearing span	mm	l	355,600	—
	Bearing span offset	mm	s	0,00	—
	External shaft diameter	mm	d_{sh}	63,50	—
	Internal shaft diameter	mm	d_{shi}	0,00	—
	Equivalent misalignment	µm	f_{sh}	As Formula (59)	
	Mesh misalignment	µm	f_{ma}	As Formula (66)	
	Minimum safety factor pitting	—	$S_{H\,min}$	1,00	
	Minimum safety factor tooth breakage	—	$S_{F\,min}$	1,00	
	Lubrication viscosity	mm^2/s	ν_{40}	25	
Load	Torque	kNm	T_1	0,528	
	Speed	min^{-1}	n_1	5 400,0	
	Required life	h	—	30 000	
	Life factor for contact stress, Z_{NT}, at 10^{10} cycles	—	—	0,85	0,85
	Life factor for tooth root stress, Y_{NT}, at 10^{10} cycles	—	—	0,85	0,85

© ISO 2022 – All rights reserved

Table 16 — Example 7 output values

Symbol	Description	Unit	Pinion	*Gear*
d	Reference diameter	mm	153,39	765,18
d_a	Tip diameter	mm	157,988	769,518
d_b	Base circle diameter	mm	143,23	714,47
x_E	Generating profile shift coefficient	—	0,185 7	0,110 4
d_f	Root diameter (based on x_E)	mm	149,79	761,32
d_{Ff}	Root form diameter (based on x_E)	mm	150,81	762,21
d_{Nf}	Start of active profile diameter	mm	151,39	763,15
d_w	Working pitch diameter	mm	153,76	766,99
F_t	nominal tangential load at the reference cylinder	N	6 884	
$K_{F\alpha\text{-}B}$	Transverse load factor (root stress)	—	1,37	
$K_{F\beta\text{-}C}$	Face load factor (root stress)	—	1,36	
$K_{H\alpha\text{-}B}$	Transverse load factor (contact stress)	—	1,37	
$K_{H\beta\text{-}C}$	Face load factor (contact stress)	—	1,38	
$K_{v\text{-}B}$	Dynamic factor	—	1,68	
S_F	Tooth root breakage safety factor	—	2,79	2,50
S_H	Pitting safety factor	—	1,30	1,33
v_w	Pitch line velocity	m/s	43,47	
Y_B	Rim thickness factor	—	1,00	1,00
Y_{DT}	Deep tooth factor	—	1,00	
Y_F	Tooth form factor	—	0,86	0,89
Y_{NT}	Life factor for reference test conditions (tooth root stress)	—	0,85	0,88
Y_N	Life factor (tooth root stress)	—	0,85	0,88
Y_{RrelT}	Relative surface factor	—	0,96	0,96
Y_S	Stress correction factor	—	2,30	2,36
Y_{ST}	Stress correction factor for reference gears	—	2,00	
Y_X	Size factor	—	1,00	1,00
Y_β	Helix angle factor	—	0,99	
$Y_{\delta relT}$	Relative notch sensitivity factor	—	1,00	1,00
Z_B	Single pair tooth contact factor, pinion	—	1,03	
Z_β	Helix angle factor (pitting)	—	1,03	
Z_D	Single pair tooth contact factor, wheel	—	1,03	
Z_E	Elasticity factor		189,81	
Z_ε	Contact ratio factor	—	0,77	
Z_H	Zone factor	—	2,37	
Z_L	Lubricant factor	—	0,85	0,85
Z_{NT}	Life factor for test reference conditions (contact stress)	—	0,85	0,95
Z_N	Life factor (contact stress)	—	0,85	0,95
Z_R	Roughness factor	—	0,94	0,94
Z_v	Velocity factor	—	1,09	1,09
Z_W	Work hardening factor	—	1,00	1,00
Z_X	Size factor	—	1,00	1,00
ε_α	Transverse contact ratio	—	1,68	
ε_β	Overlap ratio	—	4,87	
ε_γ	Total contact ratio	—	6,56	

© ISO 2022 – All rights reserved

Table 16 *(continued)*

Symbol	Description	Unit	Pinion	*Gear*
σ_{F0}	Nominal tooth root stress	N/mm^2	48	51
σ_F	Tooth root stress	N/mm^2	151	161
$\sigma_{F\,lim}$	Limiting tooth root stress (input data)	N/mm^2	256	238
σ_{FP}	Permissible tooth root stress	N/mm^2	421	404
σ_H	Contact stress	N/mm^2	375	375
$\sigma_{H\,lim}$	Limiting contact stress (input data)	N/mm^2	661	603
σ_{H0}	Nominal contact stress	N/mm^2	203	
σ_{HP}	Permissible contact stress	N/mm^2	489	499
Intermediate calculation values				
$K_{v\text{-}B}$ intermediate calculation values				
$c_{\gamma\alpha}$	Mean value of mesh stiffness per unit facewidth (used for $K_{v\text{-}B}$, $K_{H\alpha\text{-}B}$, $K_{F\alpha\text{-}B}$)	N/(mm·µm)	19,3	
c'	Maximum tooth stiffness per unit facewidth (single stiffness) of a tooth pair	N/(mm·µm)	12,7	
m_{red}	Reduced gear pair mass per unit facewidth referenced to the line of action	kg/mm	0,081	
N	Resonance ratio	—	3,16	
$K_{H\beta\text{-}C}$ intermediate calculation values				
$c_{\gamma\beta}$	Mean value of mesh stiffness per unit facewidth (used for $K_{H\beta\text{-}C}$, $K_{F\beta\text{-}C}$)	N/(mm·µm)	16,4	
f_{sh0}	Shaft deformation under specific load	µm	0,010	
$F_{\beta x}$	Initial equivalent misalignment (before running-in)	µm	6,6	
$F_{\beta y}$	Effective equivalent misalignment (after running-in)	µm	3,3	
y_α	Running-in allowance for a gear pair (calculated with max(f_{pb},$f_{f\alpha}$))	µm	1,540	
y_β	Running-in allowance (equivalent misalignment)	µm	3,4	
f_{pb}	Transverse base pitch deviation	µm	6,1	
$f_{H\beta5}$	Tolerance on helix slope deviation for flank tolerance class 5	µm	8,5	
f_{sh}	Component of equivalent misalignment due to deformations of pinion and wheel shafts	µm	1,4	
f_{ma}	Mesh misalignment due to manufacturing deviations	µm	11,7	
Auxiliary values				
f_{ZCa}	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—	1,07	
f_ε	Load distribution influence factor	—	0,74	

© ISO 2022 – All rights reserved

4.10 Example 8: Single helical case carburized gear pair

NOTE Example 8 is the application of residual protuberance, *pr*.

For example 8, input values and output values are given in Tables 17 and 18, respectively.

Table 17 — Example 8 input values

Type	Description	Unit	Symbol	Pinion	Wheel
Geometry	Number of teeth	—	z	15	63
	Normal module	mm	m_n	4,50	
	Normal pressure angle	°	α_n	20,00	
	Helix angle	°	β	11,00	
	Hand of helix	—	—	Left	Right
	Facewidth (total)	mm	b	78,74	76,20
	Gap width	mm	—	0,00	0,00
	Edge chamfer	mm	—	0,00	0,00
	Contact facewidth (total)	mm	b_{eff}	76,20	
	Centre distance	mm	a	182,880	
	Span measurement	mm	W_k	35,706	118,358
	Number of teeth spanned	—	k	3	9
	Dimension between balls	mm	M_{dK}	—	—
	Ball diameter	mm	D_M	—	—
	Nominal profile shift coefficient	—	x	0,541 3	(0,439 3)
	Tip diameter	mm	d_a	82,19	301,55
	Basic rack dedendum coefficient (pre-finishing)	—	h_{fP}/m_n	1,516	1,516
	Basic rack dedendum coefficient (finishing)	—	h_{fP}/m_n	1,373	1,373
	Tip chamfer	mm	h_K	0,00	0,00
	Basic rack fillet root radius coefficient	—	ρ_{fP}/m_n	0,40	0,40
	As cut (pre-finishing) basic rack undercut	mm	pr	0,267	0,267
	Material allowance for grinding (finishing)	mm	q	0,220	0,220
	Residual fillet undercut, $s_{pr} = pr - q$	mm	s_{pr}	0,047	0,047
	Cutting tool protuberance angle	—	—	10°	10°
	Pinion cutter number of teeth	—	z_0	—	—
	Pinion cutter profile shift (ref)	—	x_0	—	—
	Flank finishing process	—	—	Cut (pre-finishing) and ground (finishing)	Cut (pre-finishing) and ground (finishing)
	Root finishing process	—	—	As cut (pre-finishing)	As cut (pre-finishing)
	Tip relief	µm	C_a	13	13
	Root relief	µm	C_f	0	0
	Profile modification compensate for the deflections	—	—	No	
	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—	f_{ZCa}	manufacturers experience	

© ISO 2022 – All rights reserved

Table 17 *(continued)*

Type	Description	Unit	Symbol	Pinion	Wheel
Quality	Flank tolerance class	—	A	6	6
	Single pitch tolerance according to ISO 1328-1:2013	µm	f_{pT}	9,5	10,0
	Profile form deviation according to ISO 1328-1:2013	µm	$f_{f\alpha}$	11,0	11,0
	Helix slope deviation	µm	$f_{H\beta}$	11,0	11,0
	Surface roughness – flank *Ra* (*Rz*)	µm	—	0,38 (2,3)	0,38 (2,3)
	Surface roughness – fillet *Ra* (*Rz*)	µm	—	3,0 (18,0)	3,0 (18,0)
Material	Material	—	—	Eh	Eh
	Material quality	—	—	MQ	MQ
	Case hardness	—	—	58 HRC	58 HRC
	Core hardness	—	—	30 HRC	30 HRC
	Young's modulus	N/mm^2	E	206 000	206 000
	Poisson's ratio	—	ν	0,3	0,3
	Yield/proof stress	N/mm^2	$\sigma_S/\sigma_{0,2}$	689,5	689,5
	Material density	kg/m^3	ρ	7 830	7 830
	Shot peen	—	—	No	No
	Limited pitting allowable	—	—	No	No
Application	Application factor	—	$K_{A\text{-}A}$	1,000	
	Mesh load factor	—	K_γ	1,00	
	Reverse bending	—	—	No	No
	Favourable contact position	—	—	Yes	Yes
	Helix modification (ISO 6336-1:2019, Table 12)	—	—	Helix + Crowning (No. 5)	
	Dynamic factor, K_v, calculation method	—	—	Method B	
	Face load distribution factor, $K_{H\beta}$ and $K_{F\beta}$, calculation method	—	—	Method C	
	Number of meshes	—	N_M	1	1
	Gear blank type	—	—	Solid	Solid
	Web thickness	mm	b_s	—	—
	Inside diameter	mm	—	—	—
	Number of webs	—	—	—	—
	Arrangement (ISO 6336-1:2019, Figure 13)	—	—	b	
	Bearing span	mm	l	331,724	—
	Bearing span offset	mm	s	67,56	—
	External shaft diameter	mm	d_{sh}	63,50	—
	Internal shaft diameter	mm	d_{shi}	0,00	—
	Equivalent misalignment	µm	f_{sh}	As Formula (59)	
	Mesh misalignment	µm	f_{ma}	As Formula (66)	
	Minimum safety factor pitting	—	$S_{H\,min}$	1,00	
	Minimum safety factor tooth breakage	—	$S_{F\,min}$	1,00	
	Lubrication viscosity	mm^2/s	ν_{40}	220	

© ISO 2022 – All rights reserved

Table 17 *(continued)*

Type	Description	Unit	Symbol	Pinion	Wheel
Load	Torque	kNm	T_1	1,494	
	Speed	min^{-1}	n_1	1 430,0	
	Required life	h	—	10 000	
	Life factor for contact stress, Z_{NT}, at 10^{10} cycles	—	—	1,00	1,00
	Life factor for tooth root stress, Y_{NT}, at 10^{10} cycles	—	—	1,00	1,00

Table 18 — Example 8 output values

Symbol	Description	Unit	Pinion	*Gear*
d	Reference diameter	mm	68,76	288,81
d_a	Tip diameter	mm	82,19	301,55
d_b	Base circle diameter	mm	64,47	270,79
$x_{E,V}$	Generating profile shift coefficient (pre-finishing)	—	0,629 5	0,549 9
x_E	Generating profile shift coefficient	—	0,486 6	0,406 9
d_f	Root diameter (based on $x_{E,V}$ — pre-finishing)	mm	60,79	280,11
d_{Ff}	Root form diameter (based on x_E —finishing)	mm	65,87	284,03
d_{Nf}	Start of active profile diameter	mm	65,88	287,05
d_w	Working pitch diameter	mm	70,34	295,42
F_t	Nominal tangential load at the reference cylinder	N	43 453	
$K_{F\alpha\text{-}B}$	Transverse load factor (root stress)	—	1,03	
$K_{F\beta\text{-}C}$	Face load factor (root stress)	—	1,05	
$K_{H\alpha\text{-}B}$	Transverse load factor (contact stress)	—	1,03	
$K_{H\beta\text{-}C}$	Face load factor (contact stress)	—	1,06	
$K_{v\text{-}B}$	Dynamic factor	—	1,02	
S_F	Tooth root breakage safety factor	—	3,01	2,78
S_H	Pitting safety factor	—	1,20	1,20
v_w	Pitch line velocity	m/s	5,27	
Y_B	Rim thickness factor	—	1,00	1,00
Y_{DT}	Deep tooth factor	—	1,00	
Y_F	Tooth form factor	—	1,25	1,28
Y_{NT}	Life factor for reference test conditions (tooth root stress)	—	1,00	1,00
Y_N	Life factor (tooth root stress)	—	1,00	1,00
Y_{RrelT}	Relative surface factor	—	0,96	0,96
Y_S	Stress correction factor	—	1,98	2,03
Y_{ST}	Stress correction factor for reference gears	—	2,00	
Y_X	Size factor	—	1,00	1,00
Y_β	Helix angle factor	—	0,96	
$Y_{\delta relT}$	Relative notch sensitivity factor	—	1,00	1,00
Z_B	Single pair tooth contact factor, pinion	—	1,03	
Z_β	Helix angle factor (pitting)	—	1,01	
Z_D	Single pair tooth contact factor, wheel	—	1,03	

© ISO 2022 – All rights reserved

Table 18 *(continued)*

Symbol	Description	Unit	Pinion	*Gear*
Z_E	Elasticity factor	$\sqrt{N/mm^2}$	189,81	
Z_ε	Contact ratio factor	—	0,85	
Z_H	Zone factor	—	2,27	
Z_L	Lubricant factor	—	1,02	1,02
Z_{NT}	Life factor for reference test conditions (contact stress)	—	1,00	1,00
Z_N	Life factor (contact stress)	—	1,00	1,00
Z_R	Roughness factor	—	1,02	1,02
Z_v	Velocity factor	—	0,98	0,98
Z_W	Work hardening factor	—	1,00	1,00
Z_X	Size factor	—	1,00	1,00
ε_α	Transverse contact ratio	—	1,39	
ε_β	Overlap ratio	—	1,03	
ε_γ	Total contact ratio	—	2,41	
σ_{F0}	Nominal tooth root stress	N/mm^2	291	317
σ_F	Tooth root stress	N/mm^2	320	347
$\sigma_{F\,lim}$	Limiting tooth root stress	N/mm^2	500	500
σ_{FP}	Permissible tooth root stress	N/mm^2	962	965
σ_H	Contact stress	N/mm^2	1 285	1 285
$\sigma_{H\,lim}$	Limiting contact stress	N/mm^2	1 500	1 500
σ_{H0}	Nominal contact stress	N/mm^2	1 181	
σ_{HP}	Permissible contact stress	N/mm^2	1 541	1 541
Intermediate calculation values				
$K_{v\text{-}B}$ intermediate calculation values				
$c_{\gamma\alpha}$	Mean value of mesh stiffness per unit facewidth (used for $K_{v\text{-}B}$, $K_{H\alpha\text{-}B}$, $K_{F\alpha\text{-}B}$)	N/(mm·µm)	17,5	
c'	Maximum tooth stiffness per unit facewidth (single stiffness) of a tooth pair	N/(mm·µm)	13,5	
m_{red}	Reduced gear pair mass per unit facewidth referenced to the line of action	kg/mm	0,018	
N	Resonance ratio	—	0,07	
$K_{H\beta\text{-}C}$ intermediate calculation values				
$c_{\gamma\beta}$	Mean value of mesh stiffness per unit facewidth (used for $K_{H\beta\text{-}C}$, $K_{F\beta\text{-}C}$)	N/(mm·µm)	14,8	
f_{sh0}	Shaft deformation under specific load	µm	0,136	
$F_{\beta x}$	Initial equivalent misalignment (before running-in)	µm	5,5	
$F_{\beta y}$	Effective equivalent misalignment (after running-in)	µm	4,7	
y_α	Running-in allowance for a gear pair (calculated with $\max(f_{pb}, f_{f\alpha})$)	µm	0,825	
y_β	Running-in allowance (equivalent misalignment)	µm	0,8	
f_{pb}	Transverse base pitch deviation	µm	9,4	
$f_{H\beta 5}$	Tolerance on helix slope deviation for flank tolerance class 5	µm	8,0	
f_{sh}	Component of equivalent misalignment due to deformations of pinion and wheel shafts	µm	78,9	

© ISO 2022 – All rights reserved

Table 18 *(continued)*

Symbol	Description	Unit	Pinion	*Gear*
f_{ma}	Mesh misalignment due to manufacturing deviations	µm	15,6	
Auxiliary values				
f_{ZCa}	Tooth flank correction factor (auxiliary factor, see ISO 6336-2:2019)	—	1,07	
f_{ε}	Load distribution influence factor	—	0,84	

© ISO 2022 – All rights reserved

Annex A
(informative)

Example 1 detailed calculation

A.1 General

This annex contains the detailed calculation example 1. The formulae are numbered according to the respective referenced document.

A.2 Defined data

The defined data are shown in Tables A.1, A.2 and A.3.

Table A.1 — Gear geometry

Description	Pinion	Wheel
Number of teeth	z_1 = 17	z_2 = 103
Normal module	m_n = 8	
Normal pressure angle	α_n = 20,00°	
Helix angle	β = 15,8°	
Hand of helix	Left	Right
Facewidth	b_1 = 100 mm	b_2 = 100 mm
Contact facewidth	b = 100 mm	
Centre distance	a = 500 mm	
Nominal addendum correction factor	x_1 = (0,145 22)	x_2 = 0
Span measurement	W_{k1} = 38,196 mm	W_{k2} = 307,943 mm
Number of teeth spanned	k_1 = 2	k_2 = 13
Tip diameter	d_{a1} = 159,66 mm	d_{a2} = 872,35 mm
Basic rack dedendum	h_{fP1} = 1,4 m_n mm	h_{fP2} = 1,4 m_n = 11,2 mm
Basic rack fillet root radius	ρ_{fP1} = 0,39 m_n mm	ρ_{fP2} = 0,39 m_n = 3,12 mm
residual fillet undercut	s_{pr1} = 0,00 mm	s_{pr2} = 0,00 mm
Material allowance for finishing	q_1 = 0,00 mm	q_2 = 0,00 mm
Tip relief	C_a = 70 µm	
Root relief	C_f = 0 µm	
Profile modification compensate for the deflections	Yes	

Table A.2 — Gear quality

Description	Pinion	Wheel
Flank tolerance class	A = 5	A = 5
Single pitch tolerance	f_{pT1} = 8,5 µm	f_{pT2} = 9,0 µm
Profile form deviation	$f_{f\alpha 1}$ = 9,5 µm	$f_{f\alpha 2}$ = 9,5 µm
Helix slope deviation	$f_{H\beta 1}$ = 8,0 µm	$f_{H\beta 2}$ = 9,0 µm
Surface roughness (Ra)	Ra_{H1} = 1,0 µm	Ra_{H2} = 1,0 µm
Fillet roughness (Ra)	Ra_{F1} = 3,0 µm	Ra_{F2} = 3,0 µm

© ISO 2022 – All rights reserved

Table A.3 — Material data

Description	Pinion	Wheel
Material type	Eh	Eh
Material quality	MQ	MQ
Case hardness (HRC)	60	60
Core hardness (HRC)	30	30
Young's modulus	E_1 = 206 000 N/mm^2	E_2 = 206 000 N/mm^2
Poisson's ratio	ν_1 = 0,3	ν_2 = 0,3
Yield/proof stress	σ_{S1} = 500 N/mm^2	σ_{S2} = 500 N/mm^2
Material density	ρ_1 = 7 830 kg/m^3	ρ_2 = 7 830 kg/m^3
Shot peen	No	No
Limited pitting allowable	No	No

A.3 ISO 6336-5:2016 — Allowable stress values for contact and bending

5.5 Allowable contact stress number, $\sigma_{H\,lim}$

For material Eh with MQ quality (see ISO 6336-5:2016, Table 1),

$$\sigma_{H\,lim} = 1\,500\ N / mm^2$$

Minimum required safety value for contact, $S_{H\,min}$ = 1,00

Allowable stress number (bending), $\sigma_{F\,lim}$

For material Eh, material quality MQ with core hardness ≥ 30 HRC (see ISO 6336-5:2016, Figure 10),

$$\sigma_{F\,lim} = 500\ N / mm^2$$

Minimum safety value for bending, $S_{F\,min}$ = 1,00

A.4 Application data

See Table A.4.

Table A.4 — Application data

Description	Pinion	Wheel
Application factor	K_A = 1,00	
Mesh load factor	K_γ = 1,00	
Reverse bending	No	No
Favourable contact position	No	No
Helix modification	No	No
Profile modifications compensate for the deflections	Yes	Yes
Number of mesh contacts	N_{M1} = 1	N_{M2} = 1
Gear blank type	Solid	Solid
Bearing span offset	s_1 = 0,00 mm	
Equivalent misalignment	f_{sh} = 14,705 µm	
Mesh misalignment	f_{ma} = 12,042 µm	
Lubrication viscosity	ν_{40} = 320 mm^2/s	

© ISO 2022 – All rights reserved

A.5 Load data

See Table A.5.

Table A.5 — Load data

Description	Pinion	Wheel
Pinion torque	T_1 = 9 000 Nm	—
Pinion speed	n_1 = 360 min^{-1}	—
Required life	L_h = 50 000 h	—

A.6 Supplementary calculations

Gear ratio

$$u = \frac{z_2}{z_1} = 6{,}058\ 82$$

Transverse module

$$m_t = \frac{m_n}{\cos(\beta)} = 8{,}314\ 12 \text{ mm}$$

Reference diameter

$$d_1 = z_1 \cdot m_t = 141{,}340 \text{ mm}$$

$$d_2 = z_2 \cdot m_t = 856{,}355 \text{ mm}$$

Involute normal pressure angle

$$\text{inv}\alpha_n = \tan(\alpha_n) - \alpha_n = 0{,}014\ 90 \text{ rad}$$

Transverse pressure angle

$$\alpha_t = a\tan\left[\frac{\tan(\alpha_n)}{\cos(\beta)}\right] = 20{,}720°$$

$$\text{inv}\alpha_t = \tan(\alpha_t) - \alpha_t = 0{,}016\ 63 \text{ rad}$$

Transverse working pressure angle

$$\alpha_{wt} = a\cos\left\{|z_1 + z_2|\left[\frac{m_n \cdot \cos(\alpha_t)}{2a_w \cdot \cos(\beta)}\right]\right\} = 21{,}066°$$

Generating profile shift coefficient

$$x_{E1} = \frac{W_{k1} - \{m_n \cdot \cos(\alpha_n)[\pi(k_1 - 0{,}5) + z_1 \cdot \text{inv}\alpha_t]\}}{2 \cdot m_n \cdot \sin(\alpha_n)} = 0{,}117\ 79$$

$$x_{E2} = \frac{W_{k2} - \{m_n \cdot \cos(\alpha_n)[\pi(k_2 - 0{,}5) + z_2 \cdot \text{inv}\alpha_t]\}}{2 \cdot m_n \cdot \sin(\alpha_n)} = -0{,}027\ 48$$

Root diameter (based on generating profile shift coefficient, x_E)

$$d_{f1} = d_1 - 2[h_{fP1} - (x_{E1} m_n)] = 120{,}825 \text{ mm}$$

$$d_{f2} = d_2 - 2[h_{fP2} - (x_{E2} m_n)] = 833{,}515 \text{ mm}$$

Root form diameter (based on generated profile shift coefficient, x_E; in this case there is no undercut or protuberance, so the following formula can be applied)

$$d_{Ff1} = \sqrt{\left\{d_1 \sin(\alpha_t) - \frac{2[h_{aP0} - x_{E1} m_n - \rho_{aP0}(1 - \sin(\alpha_n))]}{\sin(\alpha_t)}\right\}^2 + d_{b1}^2} = 132{,}248 \text{ mm}$$

$$d_{Ff2} = \sqrt{\left\{d_2 \sin(\alpha_t) - \frac{2[h_{aP0} - x_{E2} m_n - \rho_{aP0}(1 - \sin(\alpha_n))]}{\sin(\alpha_t)}\right\}^2 + d_{b2}^2} = 839{,}084 \text{ mm}$$

Base diameter

$$d_{b1} = d_1 \cos(\alpha_t) = 132{,}199 \text{ mm}$$

$$d_{b2} = d_2 \cos(\alpha_t) = 800{,}968 \text{ mm}$$

Base helix angle

$$\beta_b = \tan^{-1}[\tan(\beta)\cos(\alpha_t)] = 14{,}825°$$

© ISO 2022 – All rights reserved

Working pitch diameter

$$d_{w1} = \frac{d_{b1}}{\cos(\alpha_{wt})} = 141{,}667 \text{ mm}$$

$$d_{w2} = \frac{d_{b2}}{\cos(\alpha_{wt})} = 858{,}333 \text{ mm}$$

Normal pitch $p_n = \pi \cdot m_n = 25{,}133$ mm

Transverse pitch $p_t = \pi \cdot m_t = 26{,}120$ mm

Transverse base pitch $p_{bt} = p_t \cdot \cos(\alpha_t) = 24{,}430$ mm

Transverse base pitch on the path of contact $p_{et} = p_{bt} = 24{,}430$ mm

Length of line of contact

$$g_\alpha = \frac{1}{2}\left[\sqrt{d_{Na1}{}^2 - d_{b1}{}^2} + \frac{z_2}{|z_2|}\left(\sqrt{d_{Na2}{}^2 - d_{b2}{}^2} - 2\,a_w \sin\alpha_{wt}\right)\right] = 37{,}845 \text{ mm}$$

SAP diameter

$$d_{Nf1} = \sqrt{\left(2|a|\sin\alpha_{wt} - \sqrt{d_{Fa2}^2 - d_{b2}^2}\right)^2 + d_{b1}^2} = 132{,}921 \text{ mm}$$

$$d_{Nf2} = \frac{z_2}{|z_2|}\sqrt{\left(2a\sin\alpha_{wt} - \sqrt{d_{Fa1}^2 - d_{b1}^2}\right)^2 + d_{b2}^2} = 845{,}225 \text{ mm}$$

Transverse contact ratio $\varepsilon_\alpha = \frac{g_\alpha}{p_{et}} = 1{,}549\,09$

Overlap ratio $\varepsilon_\beta = \frac{b \cdot \sin(\beta)}{m_n \cdot \pi} = 1{,}083\,37$

Total contact ratio $\varepsilon_\gamma = \varepsilon_\alpha + \varepsilon_\beta = 2{,}632\,46$

Transverse base pitch deviation

$$f_{pb1} = f_{pT1} \cdot \cos(\alpha_t) = 7{,}950\ 24\,\mu\text{m}$$

$$f_{pb2} = f_{pT2} \cdot \cos(\alpha_t) = 8{,}417\ 90\,\mu\text{m}$$

Pitch line velocity $v_w = \frac{d_{w1} \cdot \pi \cdot n_1}{60 \cdot 10^3} = 2{,}670\ 35\ \frac{\text{m}}{\text{s}}$

Circumferential velocity at the reference circle (see ISO 6336-1:2019, 4.2.2) $v = \frac{d_1 \cdot \pi \cdot n_1}{60 \cdot 10^3} = 2{,}664\ 20\ \frac{\text{m}}{\text{s}}$

A.7 ISO 6336-2:2019 — Contact ratio factor

8.2.2 Contact ratio factor, Z_ε

$$Z_\varepsilon = \sqrt{\frac{1}{\varepsilon_\alpha}} = 0{,}803\ 46 \tag{31}$$

© ISO 2022 – All rights reserved

A.8 ISO 6336-1:2019 — Basic principles, introduction and general influence factors

A.8.1 Determination of dynamic factor, K_v

4.2.2 Nominal tangential load, F_t

$$F_t = \frac{2\,000\,T_1}{d_1} = 127\,352{,}381\ \text{N} \tag{1}$$

9.3 Determination of tooth stiffness parameters, c' and c_γ

Virtual number of teeth, z_n

$$z_{n1} = \frac{z_1}{\cos(\beta_b)^2 \cos(\beta)} = 18{,}905$$

$$z_{n2} = \frac{z_2}{\cos(\beta_b)^2 \cos(\beta)} = 114{,}543$$

9.3.2.2 Theoretical single stiffness, c'_{th}

Coefficients: $C_1 = 0{,}047\,23$

$C_2 = 0{,}155\,51$

$C_3 = 0{,}257\,91$

$C_4 = -0{,}006\,35$

$C_5 = -0{,}116\,54$

$C_6 = -0{,}001\,93$

$C_7 = -0{,}241\,88$

$C_8 = 0{,}005\,29$

$C_9 = 0{,}001\,82$

Minimum value for the flexibility of gear pair, q'

$$q' = C_1 + \frac{C_2}{z_{n1}} + \frac{C_3}{z_{n2}} + C_4 x_1 + \frac{C_5 x_1}{z_{n1}} + C_6 x_2 + \frac{C_7 x_2}{z_{n2}} + C_8 {x_1}^2 + C_9 {x_2}^2 = 0{,}056\ 00\ (\text{mm}\cdot\mu\text{m})/\text{N} \tag{84}$$

$$c'_{th} = \frac{1}{q'} = 17{,}857\ \text{N}/(\text{mm}\cdot\mu\text{m}) \tag{83}$$

9.3.2.3 Correction factor, C_M

$$C_M = 0{,}8 \tag{85}$$

9.3.2.4 Gear blank factor, C_R

$$C_R = 1{,}0\,(\text{for solid gears}) \tag{86}$$

© ISO 2022 – All rights reserved

9.3.2.5 Basic rack factor, C_B

Normal pressure angle of basic rack, $\alpha_{Pn} = \alpha_n$

Basic rack dedendum for pinion and gear are the same, therefore,

$$C_{B1} = \left[1{,}0 + 0{,}5\left(1{,}2 - \frac{h_{fP1}}{m_n}\right)\right][1{,}0 - 0{,}02 \cdot (20° - \alpha_{Pn})] = 0{,}900\,00 \tag{88}$$

$$C_{B2} = \left[1{,}0 + 0{,}5\left(1{,}2 - \frac{h_{fP2}}{m_n}\right)\right][1{,}0 - 0{,}02 \cdot (20° - \alpha_{Pn})] = 0{,}900\,00$$

$$C_B = 0{,}5 \cdot (C_{B1} + C_{B2}) = 0{,}900\,00 \tag{89}$$

9.3.2 Single stiffness, c'

$$c' = c'_{th} \cdot C_M \cdot C_R \cdot C_B \cos(\beta) = 12{,}371\,\mathrm{N/(mm \cdot \mu m)} \tag{82}$$

9.3.3.1 Mesh stiffness, $c_{\gamma\alpha}$

$$c_{\gamma\alpha} = c' \cdot (0{,}75\,\varepsilon_\alpha + 0{,}25) = 17{,}466\,\mathrm{N/(mm \cdot \mu m)} \tag{93}$$

9.3.3.2 Mesh stiffness, $c_{\gamma\beta}$

$$c_{\gamma\beta} = 0{,}85\,c_{\gamma\alpha} = 14{,}846\,\mathrm{N/(mm \cdot \mu m)} \tag{94}$$

6.5.3 Calculation of reduced mass of gear pair with external teeth, m_{red}

Mean tooth diameter, d_m

$$d_{m1} = \frac{d_{a1} + d_{f1}}{2} = 140{,}462\ \mathrm{mm} \qquad d_{m2} = \frac{d_{a2} + d_{f2}}{2} = 853{,}152\ \mathrm{mm} \tag{31}$$

Given density ρ_1 = 7 830 kg/m^3 ρ_2 = 7 830 kg/m^3

$$m_1^* = \frac{J_1^*}{r_{b1}^2} = 0{,}068\ 486\ \mathrm{kg/mm} \qquad m_2^* = \frac{J_2^*}{r_{b2}^2} = 2{,}539\ 206\ \mathrm{kg/mm} \tag{8}$$

$$m_{red} = \frac{m_1^* \cdot m_2^*}{m_1^* + m_2^*} = 0{,}066\ 69\ \mathrm{kg/mm} \tag{7}$$

NOTE Quantity $(1 - q_1^4) = (1 - q_2^4) = 1$ for solid pinion and wheel (33)

© ISO 2022 – All rights reserved

6.5.3 Determination of resonance running speed, n_{E1}

$$n_{E1} = \frac{30\ 000}{\pi\, z_1}\sqrt{\frac{c_{\gamma\alpha}}{m_{red}}} = 9\,090{,}605\ \text{min}^{-1} \tag{6}$$

Resonance ratio, N

$$N = \frac{n_1}{n_{E1}} = 0{,}039\,60 \tag{9}$$

Lower limit of resonance ratio, N_S

$$\frac{F_t K_A}{b} > 100, \text{ therefore, } N_S = 0{,}85 \tag{12}$$

6.5.4 Dynamic factor in subcritical range, *($N \le N_S$)*

$\varepsilon_\gamma > 2$ (see ISO 6336-1:2019, Table 8), therefore,

$C_{v1} = 0{,}320\ 00$ $\qquad$ $C_{v4} = \dfrac{0{,}57 - 0{,}05\,\varepsilon_\gamma}{\varepsilon_\gamma - 1{,}44} = 0{,}367\ 62$

$C_{v2} = \dfrac{0{,}57}{\varepsilon_\gamma - 0{,}3} = 0{,}244\ 38$ $\qquad$ $C_{v5} = 0{,}47 = 0{,}470\ 00$

$C_{v3} = \dfrac{0{,}096}{\varepsilon_\gamma - 1{,}56} = 0{,}089\,51$ $\qquad$ $C_{v6} = \dfrac{0{,}12}{\varepsilon_\gamma - 1{,}74} = 0{,}134\,46$

$\varepsilon_\gamma > 2{,}5$ $\qquad$ $C_{v7} = 1$

$$C_{ay} = \frac{1}{18}\left(\frac{\sigma_{H\,lim}}{97} - 18{,}45\right)^2 + 1{,}5 = 1{,}995\,37\ \mu\text{m}$$

Base pitch deviation, $f_{pb} = \max\left(f_{pb1}, f_{pb2}\right) = 8{,}417\,90\ \mu\text{m}$ (see note in ISO 6336-1:2019, 8.3.2)

Profile form deviation, $f_{f\alpha} = \max\left(f_{f\alpha 1}, f_{f\alpha 2}\right) = 9{,}5\ \mu\text{m}$, Running-in allowance (see ISO 6336-1:2019, 8.3.6)

As materials are the same and for Eh material, then,

$$y_\alpha = 0{,}075\, f_{pb} = 0{,}631\,34\ \mu\text{m} \tag{79}$$

NOTE The application of 50 % of the values f_{pb} or $f_{f\alpha}$ (due to profile modification compensation of deflections) is only valid for the calculation of $K_{H\beta}$, but not for the calculation of K_v.

Comparison with the allowable limit for material Eh of 3 µm.

© ISO 2022 – All rights reserved

Estimated running-in allowance (pitch deviation) (see note in ISO 6336-1:2019, 6.54)

$$y_p = y_\alpha = 0{,}631\ 34\ \mu m$$

Estimated running-in allowance (flank deviation) (see ISO 6336-1:2019, 6.5.4)

$$y_f = 0{,}075\, f_{f\alpha} = 0{,}712\ 50\ \mu m$$

Comparison with the allowable limit for material Eh of 3 µm.

$$f_{pbeff} = f_{pb} - y_p = 7{,}786\ 56\ \mu m \quad (18)$$

$$f_{f\alpha eff} = f_{f\alpha} - y_f = 8{,}787\ 50\ \mu m \quad (19)$$

$$B_p = \frac{c' \cdot f_{pb\ eff}}{K_A \cdot K_\gamma \cdot \left(\frac{F_t}{b}\right)} = 0{,}075\ 64 \quad (15)$$

$$B_f = \frac{c' \cdot f_{f\alpha\ eff}}{K_A \cdot K_\gamma \cdot \left(\frac{F_t}{b}\right)} = 0{,}085\ 36 \quad (16)$$

As lowest flank tolerance class ≤ Flank tolerance class 5, then,

$$B_k = \left| 1 - \frac{c' \cdot \min(C_{a1} + C_{f2}, C_{a2} + C_{f1})}{K_A \cdot K_\gamma \cdot \left(\frac{F_t}{b}\right)} \right| = 0{,}320\ 02 \quad (17)$$

$$K = (C_{v1} \cdot B_p) + (C_{v2} \cdot B_f) + (C_{v3} \cdot B_k) = 0{,}073\ 71 \quad (14)$$

As $N \le N_S$, (see ISO 6336-1:2019, 6.5.4), then,

$$K_v = N \cdot K + 1 = 1{,}002\ 92 \quad (13)$$

A.8.2 Determination of face load factors, $K_{H\beta}$ and $K_{F\beta}$

Mean transverse tangential load (see 7.2)

$$F_m = F_t \cdot K_A \cdot K_\gamma \cdot K_v = 127\ 724{,}130\ N$$

7.5.3.5.2 Approximate calculation of equivalent misalignment, f_{sh}

Pinion offset $s_1 = 0$, therefore,

$$f_{sh} = \frac{F_m}{b} 0{,}023[(1 + 0 - 0{,}3) + 0{,}3]\left(\frac{b}{d_1}\right)^2 = 14{,}705\,\mu m \quad (59)$$

7.5.4.4 Mesh misalignment, f_{ma}

$$f_{ma} = \sqrt{{f_{H\beta 1}}^2 + {f_{H\beta 2}}^2} = 12{,}042\,\mu m \quad (66)$$

© ISO 2022 – All rights reserved

7.5.3.4 Initial equivalent misalignment, $F_{\beta x}$

As no helix modification is applied,

$B_1 = 1$ $B_2 = 1$ (see Table 12 of ISO 6336-1:2019)

$$F_{\beta x} = 1{,}33 B_1 f_{sh} + B_2 f_{ma} = 31{,}599\,\mu m \quad (54)$$

7.5.3.2 Running-in allowance, y_β and X_β

As materials are the same and for Eh material,

$$y_\beta = 0{,}15 F_{\beta x} = 4{,}739\,92\,\mu m \quad (50)$$

Comparison with the allowable limit for material Eh of 6 µm.

$$x_{\beta 2} = 0{,}85 \quad (51)$$

7.5.2 Effective equivalent misalignment, $F_{\beta y}$

$$F_{\beta y} = F_{\beta x} - y_\beta = 26{,}860\,\mu m \quad (45)$$

7.5 Face load factor, $K_{H\beta\text{-}C}$

$$\frac{F_{\beta y} c_{\gamma\beta}}{2\frac{F_m}{b}} < 1$$

therefore,

$$K_{H\beta} = \left(1 + \frac{F_{\beta y} c_{\gamma\beta}}{2\frac{F_m}{b}}\right) = 1{,}156\ 10 \quad (43)$$

7.6 Face load factor, $K_{F\beta}$

$$h_1 = \frac{d_{a1} - d_{f1}}{2} = 19{,}198\,mm \qquad \frac{b_1}{h_1} = 5{,}208\,83$$

$$h_2 = \frac{d_{a2} - d_{f2}}{2} = 19{,}198\,mm \qquad \frac{b_2}{h_2} = 5{,}208\,83$$

NOTE The root diameters d_f were calculated with nominal (see 4.2.16).

$$N_F = \frac{(b_1 / h_1)^2}{1 + b_1 / h_1 + (b_1 / h_1)^2} = 0{,}813\ 78 \quad (72)$$

$$K_{F\beta} = K_{H\beta}{}^{N_F} = 1{,}125\,29 \quad (70)$$

A.8.3 Determination of transverse load factors, $K_{H\alpha}$ and $K_{F\alpha}$

Determination tangential load in transverse plane.

© ISO 2022 – All rights reserved

8.3.2 Transverse load factor, $K_{H\alpha}$

$F_{tH} = F_t\ K_A\ K_\gamma\ K_v\ K_{H\beta} = 147\,661{,}660\ \text{N}$ (see definition in ISO 6336-1:2019, 8.3.2)

$\varepsilon_\gamma > 2$ therefore:

NOTE If the profile form deviation $f_{f\alpha}$ is larger than the base pitch deviation f_{pb}, the profile form deviation is taken instead of the base pitch deviation. If the profile modifications compensate for the deflections at the actual load level, 50 % of [max(f_{pb}, $f_{f\alpha}$) - y_α] is used. The value of y_α is calculated by max(f_{pb}, $f_{f\alpha}$).

$$K_{H\alpha-B} = 0{,}9 + 0{,}4\sqrt{\frac{2(\varepsilon_\gamma - 1)}{\varepsilon_\gamma}}\ \frac{c_{\gamma\alpha} \cdot 0{,}5 \cdot \left[\max(f_{pb}, f_{f\alpha}) - y_\alpha\right]}{\frac{F_{tH}}{b}} = 0{,}923\ 15 \tag{74}$$

$$K_{F\alpha-B} = K_{H\alpha-B} = 0{,}923\ 15 \tag{74}$$

8.3.4 Limiting factors, $K_{H\alpha}$

$K_{H\alpha-B} < 1{,}0$, therefore, $K_{H\alpha} = 1{,}0$ (75)

8.3.5 Limiting factors, $K_{F\alpha}$

$K_{F\alpha-B} < 1{,}0$ therefore, $K_{F\alpha} = 1{,}0$ (76)

A.9 ISO 6336-2:2019 — Calculation of surface durability (pitting)

A.9.1 Determination of contact stress, σ_H

6.2 Zone factor, Z_H

$$Z_H = \sqrt{\frac{2\cos(\beta_b)\cos(\alpha_{wt})}{[\cos(\alpha_t)]^2 \sin(\alpha_{wt})}} = 2{,}395\,33 \tag{16}$$

6.3 Single pair tooth contact factors, Z_B and Z_D

As the design of profile modification is based on a 3D load distribution program, see Table 3 – Factor f_{ZCa} in ISO 6336-2:2019, then,

$f_{ZCa} = 1{,}0$

As $\beta > 0$ and $\varepsilon_\alpha > 1$, then, $Z_B = \sqrt{f_{ZCa}} = 1{,}0$ (19)

$Z_D = \sqrt{f_{ZCa}} = 1{,}0$ (19)

7 Elasticity factor, Z_E

$$Z_E = \sqrt{\frac{1}{\pi\left(\frac{1-\nu_1^{\,2}}{E_1} + \frac{1-\nu_2^{\,2}}{E_2}\right)}} = 189{,}812\sqrt{\frac{N}{mm^2}} \tag{24}$$

© ISO 2022 – All rights reserved

8.2 Contact ratio factor, Z_ε

For helical gears with $\varepsilon_\beta \geq 1$, then,

$$Z_\varepsilon = \sqrt{\frac{1}{\varepsilon_\alpha}} = 0{,}803\ 46 \tag{31}$$

9 Helix angle factor, Z_β

$$Z_\beta = \frac{1}{\sqrt{\cos(\beta)}} = 1{,}019\,44 \tag{41}$$

5.3 Contact stress, σ_H

Nominal contact stress at pitch point, σ_{H0}

$$\sigma_{H0} = Z_H \cdot Z_E \cdot Z_\varepsilon \cdot Z_\beta \sqrt{\frac{F_t}{d_1 b} \cdot \frac{u+1}{u}} = 1\,206{,}582\ \mathrm{N/mm^2} \tag{3}$$

$$\sigma_{H1} = Z_B \sigma_{H0} \sqrt{K_A \cdot K_\gamma \cdot K_v \cdot K_{H\beta} \cdot K_{H\alpha}} = 1\,299{,}233\ \mathrm{N/mm^2} \tag{4}$$

$$\sigma_{H2} = Z_D \sigma_{H0} \sqrt{K_A \cdot K_\gamma \cdot K_v \cdot K_{H\beta} \cdot K_{H\alpha}} = 1\,299{,}233\ \mathrm{N/mm^2} \tag{5}$$

A.9.2 Determination of permissible contact stress, σ_{HP}

The number of load cycles for pinion and wheel are greater than the endurance point, therefore the reference values of Z_L, Z_v, Z_R, Z_W and Z_X can be used.

12.3.2.1.3 Lubricant factor, Z_L

As $\sigma_{H\,lim} > 1\,200$, then,

$$C_{ZL} = 0{,}910\,00 \tag{45}$$

$$Z_L = C_{ZL} + \frac{4(1{,}0 - C_{ZL})}{\left(1{,}2 + \frac{134}{v_{40}}\right)^2} = 1{,}047\,39 \tag{42}$$

12.3.2.2.3 Velocity factor, Z_v

$$C_{Zv} = C_{ZL} + 0{,}02 = 0{,}930\,00 \tag{48}$$

$$Z_v = C_{Zv} + \frac{2(1{,}0 - C_{Zv})}{\sqrt{0{,}8 + \frac{32}{v}}} = 0{,}969\,11 \tag{47}$$

12.3.2.3 Roughness factor, Z_R

$Rz = 6\ Ra$, therefore,

$$Rz_{H1} = Ra_{H1} \cdot 6 = 6\,\mu m \qquad Rz_{H2} = Ra_{H2} \cdot 6 = 6\,\mu m$$

Mean surface of peak-to-valley

© ISO 2022 – All rights reserved

Roughness of gear pair

$$Rz_{\mathrm{H}} = \frac{Rz_{\mathrm{H1}} + Rz_{\mathrm{H2}}}{2} = 6{,}000\,00\,\mu\mathrm{m} \tag{49}$$

Radius of curvature

$$\rho_1 = 0{,}5 d_{\mathrm{b1}} \tan(\alpha_{\mathrm{wt}}) = 25{,}461\,\mathrm{mm} \tag{52}$$

$$\rho_2 = 0{,}5 d_{\mathrm{b2}} \tan(\alpha_{\mathrm{wt}}) = 154{,}262\,\mathrm{mm}$$

Relative radius of curvature

$$\rho_{\mathrm{red}} = \frac{\rho_1 \rho_2}{\rho_1 + \rho_2} = 21{,}854\,\mathrm{mm} \tag{51}$$

Mean relative peak-to-valley roughness for the gear pair

$$Rz_{\mathrm{H10}} = Rz_{\mathrm{H}} \sqrt[3]{\frac{10}{\rho_{\mathrm{red}}}} = 4{,}623\,55\,\mu\mathrm{m} \tag{50}$$

As $\sigma_{\mathrm{Hlim}} > 1\,200$, then,

$$C_{\mathrm{ZR}} = 0{,}080\,00 \tag{56}$$

$$Z_{\mathrm{R}} = \left(\frac{3}{Rz_{\mathrm{H10}}} \right)^{C_{\mathrm{ZR}}} = 0{,}965\,99 \tag{53}$$

Work hardening factor, Z_{W}

For Eh pinion and gear, $Z_{\mathrm{W}} = 1{,}000$

Size factor, Z_{X}

$$Z_{\mathrm{X}} = 1{,}000$$

11.3 Life factor for reference test conditions (contact stress), $Z_{\mathrm{NT\text{-}B}}$

Number of load cycles

$$N_{\mathrm{L1}} = n_1 \cdot 60 L_{\mathrm{h}} = 1{,}080 \cdot 10^9$$

$$N_{\mathrm{L2}} = \frac{N_{\mathrm{L1}}}{u} = 1{,}783 \cdot 10^8$$

Number of load cycles, N_{L1}, is greater than endurance point, therefore, interpolation between the endurable point and 10^{10} cycles is required.

$$Z_{\mathrm{NT1ref\,1}} = 1 \qquad Z_{\mathrm{NT1ref2}} = 0{,}85$$

$$N_{\mathrm{L1ref1}} = 5 \cdot 10^7 \qquad N_{\mathrm{L1ref\,2}} = 10^{10}$$

© ISO 2022 – All rights reserved

$$Z_{NT1} = \frac{N_{L1}^{\left[\frac{\log(Z_{NT1ref2})-\log(Z_{NT1ref1})}{\log(N_{L1ref2})-\log(N_{L1ref1})}\right]}}{N_{L1ref1}^{\left[\frac{\log(Z_{NT1ref2})-\log(Z_{NT1ref1})}{\log(N_{L1ref2})-\log(N_{L1ref1})}\right]}} = 0,910\,05$$

Number of load cycles, N_{L2}, is greater than endurance point, therefore, interpolation between the endurable point and 10^{10} cycles is required.

$$Z_{NT2ref1} = 1 \qquad Z_{NT2ref2} = 0,85$$

$$N_{L2ref1} = 5 \cdot 10^7 \qquad N_{L2ref2} = 10^{10}$$

$$Z_{NT2} = \frac{N_{L2}^{\left[\frac{\log(Z_{NT2ref2})-\log(Z_{NT2ref1})}{\log(N_{L2ref2})-\log(N_{L2ref1})}\right]}}{N_{L2ref1}^{\left[\frac{\log(Z_{NT2ref2})-\log(Z_{NT2ref1})}{\log(N_{L2ref2})-\log(N_{L2ref1})}\right]}} = 0,961\,76$$

5.4.2 Permissible contact stress,σ_{HP}

$$\sigma_{HP1} = \frac{\sigma_{H\,lim1} Z_{NT1}}{S_{H\,min}} \cdot Z_L \cdot Z_v \cdot Z_R \cdot Z_W \cdot Z_X = 1\,338,481\,N/mm^2 \quad (6)$$

$$\sigma_{HP2} = \frac{\sigma_{H\,lim2} Z_{NT2}}{S_{H\,min}} \cdot Z_L \cdot Z_v \cdot Z_R \cdot Z_W \cdot Z_X = 1\,414,526\,N/mm^2 \quad (6)$$

5.2 Safety factor for surface durability, S_H

$$S_{H1} = \frac{\sigma_{HP1} \cdot S_{H\,min}}{\sigma_{H1}} = 1,030\,21 \quad (1)$$

$$S_{H2} = \frac{\sigma_{HP2} \cdot S_{H\,min}}{\sigma_{H2}} = 1,088\,74 \quad (2)$$

A.10 ISO 6336-3:2019 — Calculation of tooth bending strength

A.10.1 Determination of tooth root stress, σ_F

6.2 Tooth form factor, Y_F (pinion)

6.2.3 Tooth root normal chord, s_{Fn}, radius of root fillet, ρ_F, and bending moment arm, h_{Fe}

(auxiliary values)

$$E_1 = \frac{\pi}{4} m_n - h_{fP1} \tan(\alpha_n) + \frac{s_{pr1}}{\cos(\alpha_n)} - [1 - \sin(\alpha_n)] \frac{\rho_{fP1}}{\cos(\alpha_n)} = 0,022\,07 \quad (26)$$

$$G_1 = \frac{\rho_{fP1}}{m_n} - \frac{h_{fP1}}{m_n} + x_{E1} = -0,892\,21 \quad (27)$$

$$H_1 = \frac{2}{z_{n1}} \left(\frac{\pi}{2} - \frac{E_1}{m_n} \right) - \frac{\pi}{3} = -0,881\,31 \quad (28)$$

© ISO 2022 – All rights reserved

$\theta_1 = \frac{\pi}{6}$ rad for external gears

$\theta_1 = \frac{2G_1}{z_{n1}} \tan(\theta_1) - H_1 = 0{,}826\,82$ (first iteration) (29)

$\theta_1 = \frac{2G_1}{z_{n1}} \tan(\theta_1) - H_1 = 0{,}778\,76$ (second iteration)

$\theta_1 = \frac{2G_1}{z_{n1}} \tan(\theta_1) - H_1 = 0{,}788\,17$

$\theta_1 = \frac{2G_1}{z_{n1}} \tan(\theta_1) - H_1 = 0{,}786\,40$

$\theta_1 = \frac{2G_1}{z_{n1}} \tan(\theta_1) - H_1 = 0{,}786\,73$

$\theta_1 = \frac{2G_1}{z_{n1}} \tan(\theta_1) - H_1 = 0{,}786\,67$

$\theta_1 = \frac{2G_1}{z_{n1}} \tan(\theta_1) - H_1 = 0{,}786\,68$

$\theta_1 = \frac{2G_1}{z_{n1}} \tan(\theta_1) - H_1 = 0{,}786\,68$ (resolved)

6.2.2 Parameters of virtual tooth

$$\varepsilon_{\alpha n} = \frac{\varepsilon_\alpha}{[\cos(\beta_b)]^2} = 1{,}657\,60 \tag{17}$$

$$d_{n1} = z_{n1} m_n = 151{,}241\,\text{mm} \tag{18}$$

$$p_{bn} = \pi\, m_n \cos(\alpha_n) = 23{,}617\,\text{mm} \tag{19}$$

$$d_{bn1} = d_{n1} \cos(\alpha_n) = 142{,}120\,\text{mm} \tag{20}$$

$$d_{an1} = d_{n1} + d_{a1} - d_1 = 169{,}561\,\text{mm} \tag{21}$$

$$d_{en1} = 2\frac{z_1}{|z_1|}\sqrt{\left[\sqrt{\left(\frac{d_{an1}}{2}\right)^2 - \left(\frac{d_{bn1}}{2}\right)^2} - \frac{\pi\, d_1 \cos(\beta)\cos(\alpha_n)}{|z_1|}(\varepsilon_{\alpha n} - 1)\right]^2 + \left(\frac{d_{bn1}}{2}\right)^2}$$

$$d_{en1} = 154{,}824\,\text{mm} \tag{22}$$

$$\alpha_{en1} = a\cos\left(\frac{d_{bn1}}{d_{en1}}\right) = 23{,}373^\circ \tag{23}$$

$$\text{inv}\alpha_{en1} = \tan(\alpha_{en1}) - \alpha_{en1} = 0{,}024\,24\,\text{rad}$$

© ISO 2022 – All rights reserved

$$\gamma_{e1} = \frac{0{,}5\pi + 2\tan(\alpha_n)x_{E1}}{z_{n1}} + \text{inv}\alpha_n - \text{inv}\alpha_{en1} = 0{,}078\,29 \text{ rad}$$

$$\gamma_{e1} = 4{,}485\,47° \tag{24}$$

$$\alpha_{Fen1} = \alpha_{en1} - \gamma_{e1} = 18{,}887° \tag{25}$$

(a) Tooth root normal chord, s_{Fn}

$$s_{Fn1} = m_n \left\{ z_{n1} \sin\left(\frac{\pi}{3} - \theta_1\right) + \sqrt{3}\left[\frac{G_1}{\cos(\theta_1)} - \frac{\rho_{fP1}}{m_n}\right]\right\} = 16{,}046 \text{ mm} \tag{30}$$

(b) Radius of root fillet, ρ_F

$$\rho_{F1} = m_n \left\{ \frac{\rho_{fP1}}{m_n} + \frac{2{G_1}^2}{\cos(\theta_1)\left\{z_{n1}[\cos(\theta_1)]^2 - 2G_1\right\}}\right\} = 4{,}728\ 50 \text{ mm} \tag{31}$$

(c) Bending moment arm, h_{Fe}

$$h_{Fe1} = m_n \left\{ \frac{1}{2}\left\{[\cos(\gamma_{e1}) - \sin(\gamma_{e1})\tan(\alpha_{Fen1})]\frac{d_{en1}}{m_n} - z_{n1}\cos\left(\frac{\pi}{3} - \theta_1\right) - \left[\frac{G_1}{\cos(\theta_1)} - \frac{\rho_{fP1}}{m_n}\right]\right\}\right\}$$

$$h_{Fe1} = 8{,}648\,49 \text{ mm} \tag{32}$$

Load distribution influence factor

As $\varepsilon_\beta > 1$, then,

$$f_\varepsilon = {\varepsilon_{\alpha n}}^{-0{,}5} = 0{,}776\ 71 \tag{14}$$

Form factor

$$Y_{F1} = \frac{\dfrac{6\,h_{Fe1}}{m_n}\cos(\alpha_{Fen1})}{\left(\dfrac{s_{Fn1}}{m_n}\right)^2 \cos(\alpha_n)} \cdot f_\varepsilon = 1{,}260\,87 \tag{9}$$

6.2 Tooth form factor, Y_F (wheel)

6.2.3 Tooth root normal chord, s_{Fn}**, radius of root fillet,** ρ_F**, and bending moment arm,** h_{Fe} (auxiliary values)

$$E_2 = \frac{\pi}{4}m_n - h_{fP2}\tan(\alpha_n) + \frac{s_{pr2}}{\cos(\alpha_n)} - [1 - \sin(\alpha_n)]\frac{\rho_{fP2}}{\cos(\alpha_n)} = 0{,}022\,07 \text{ mm} \tag{26}$$

$$G_2 = \frac{\rho_{fP2}}{m_n} - \frac{h_{fP2}}{m_n} + x_{E2} = -1{,}037\,48 \tag{27}$$

$$H_2 = \frac{2}{z_{n2}}\left(\frac{\pi}{2} - \frac{E_2}{m_n}\right) - \frac{\pi}{3} = -1{,}019\,82 \tag{28}$$

$$\theta_2 = \frac{\pi}{6} \text{ rad for external gears}$$

© ISO 2022 – All rights reserved

$$\theta_2 = \frac{2G_2}{z_{n2}} \tan(\theta_2) - H_2 = 1{,}009\,36 \text{ (first iteration)} \quad (29)$$

$$\theta_2 = \frac{2G_2}{z_{n2}} \tan(\theta_2) - H_2 = 0{,}991\,02 \text{ (second iteration)}$$

$$\theta_2 = \frac{2G_2}{z_{n2}} \tan(\theta_2) - H_2 = 0{,}992\,16$$

$$\theta_2 = \frac{2G_2}{z_{n2}} \tan(\theta_2) - H_2 = 0{,}992\,09$$

$$\theta_2 = \frac{2G_2}{z_{n2}} \tan(\theta_2) - H_2 = 0{,}992\,09 \text{ (resolved)}$$

6.2.2 Parameters of virtual tooth

$$\varepsilon_{\alpha n} = \frac{\varepsilon_\alpha}{[\cos(\beta_b)]^2} = 1{,}657\,60 \quad (17)$$

$$d_{n2} = z_{n2} m_n = 916{,}342\,\text{mm} \quad (18)$$

$$d_{bn2} = d_{n2} \cos(\alpha_n) = 861{,}080\,\text{mm} \quad (20)$$

$$d_{an2} = d_{n2} + d_{a2} - d_2 = 932{,}338\,\text{mm} \quad (21)$$

$$d_{en2} = 2\frac{z_2}{|z_2|}\sqrt{\left[\sqrt{\left(\frac{d_{an2}}{2}\right)^2 - \left(\frac{d_{bn2}}{2}\right)^2} - \frac{\pi d_2 \cos(\beta)\cos(\alpha_n)}{|z_2|}(\varepsilon_{\alpha n} - 1)\right]^2 + \left(\frac{d_{bn2}}{2}\right)^2}$$

$$d_{en2} = 920{,}875\,\text{mm} \quad (22)$$

$$\alpha_{en2} = a\cos\left(\frac{d_{bn2}}{d_{en2}}\right) = 20{,}761° \quad (23)$$

$$\text{inv}\alpha_{en2} = \tan(\alpha_{en2}) - \alpha_2 = 0{,}016\,74$$

$$\gamma_{e2} = \frac{0{,}5\pi + 2\tan(\alpha_n) x_{E2}}{z_{n2}} + \text{inv}\alpha_n - \text{inv}\alpha_{en2} = 0{,}011\,71\,\text{rad}$$

$$\gamma_{e2} = 0{,}670\ 69° \quad (24)$$

© ISO 2022 – All rights reserved

$$\alpha_{Fen2} = \alpha_{en2} - \gamma_{e2} = 20{,}090° \tag{25}$$

(a) Tooth root normal chord, s_{Fn}

$$s_{Fn2} = m_n \left\{ z_{n2} \sin\left(\frac{\pi}{3} - \theta_2\right) + \sqrt{3}\left[\frac{G_2}{\cos(\theta_2)} - \frac{\rho_{fP2}}{m_n}\right]\right\} = 18{,}783\,\text{mm} \tag{30}$$

(b) Radius of root fillet, ρ_F

$$\rho_{F2} = m_n \left\{ \frac{\rho_{fP2}}{m_n} + \frac{2\,G_2{}^2}{\cos(\theta_2)\left\{z_{n2}\left[\cos(\theta_2)\right]^2 - 2G_2\right\}}\right\} = 3{,}986\,47\,\text{mm} \tag{31}$$

(c) Bending moment arm, h_{Fe}

$$h_{Fe2} = m_n \left\{ \frac{1}{2}\left\{\left[\cos(\gamma_{e2}) - \sin(\gamma_{e2})\tan(\alpha_{Fen2})\right]\frac{d_{en2}}{m_n} - z_{n2}\cos\left(\frac{\pi}{3} - \theta_2\right) - \left[\frac{G_2}{\cos(\theta_2)} - \frac{\rho_{fP2}}{m_n}\right]\right\}\right\}$$

$$h_{Fe2} = 10{,}106\,\text{mm} \tag{32}$$

Load distribution influence factor

As $\varepsilon_\beta > 1$, then,

$$f_\varepsilon = \varepsilon_{\alpha n}{}^{-0,5} = 0{,}776\,71 \tag{14}$$

Form factor

$$Y_{F2} = \frac{\dfrac{6\,h_{Fe2}}{m_n}\cos(\alpha_{Fen2})}{\left(\dfrac{s_{Fn2}}{m_n}\right)^2 \cos(\alpha_n)} \cdot f_\varepsilon = 1{,}067\,34 \tag{9}$$

7.2 Stress concentration factor, Y_S

Notch factor

where

$$q_{s1} = \frac{s_{Fn1}}{2\,\rho_{F1}} = 1{,}696\,77 \qquad q_{s2} = \frac{s_{Fn2}}{2\,\rho_{F2}} = 2{,}355\,88 \tag{64}$$

$$L_1 = \frac{s_{Fn1}}{h_{Fe1}} = 1{,}855\,39 \qquad L_2 = \frac{s_{Fn2}}{h_{Fe2}} = 1{,}858\,56 \tag{63}$$

$1 \le q_s < 8$, therefore,

$$Y_{S1} = (1{,}2 + 0{,}13\,L_1)\,q_{s1}{}^{\left(\frac{1}{1{,}21 + \frac{2{,}3}{L_1}}\right)} = 1{,}788\,39 \tag{62}$$

© ISO 2022 – All rights reserved

$$Y_{S2} = (1,2 + 0,13\,L_2)\,q_{s2}^{\left(\frac{1}{1,21+\frac{2,3}{L_2}}\right)} = 2,045\,98$$

8.3 Helix angle factor, Y_β

$$Y_\beta = \left(1 - \varepsilon_\beta \cdot \frac{\beta}{120°}\right) \cdot \frac{1}{\cos^3(\beta)} = 0,974\,69 \tag{66}$$

9.3 Rim thickness factor, Y_B

For solid gears,

$$Y_{B1} = 1,0 \quad Y_{B2} = 1,0 \tag{68}$$

10.3 Deep tooth factor, Y_{DT}

As $\varepsilon_{\alpha n} < 2,05$, then,

$$Y_{DT} = 1,0 \tag{72}$$

5.3.3 Tooth root stress, σ_F

Nominal tooth root stress, σ_{F0}

$$\sigma_{F01} = \frac{F_t}{b_1\, m_n} Y_{F1}\, Y_{S1}\, Y_\beta\, Y_{B1}\, Y_{DT} = 349,876\,6\ \text{N/mm}^2 \tag{4}$$

$$\sigma_{F02} = \frac{F_t}{b_1\, m_n} Y_{F2}\, Y_{S2}\, Y_\beta\, Y_{B2}\, Y_{DT} = 338,834\,4\ \text{N/mm}^2$$

$$\sigma_{F1} = \sigma_{F01} K_A\, K_\gamma\, K_v\, K_{F\beta}\, K_{F\alpha} = 394,860\ \text{N/mm}^2 \tag{3}$$

$$\sigma_{F2} = \sigma_{F02} K_A\, K_\gamma\, K_v\, K_{F\beta}\, K_{F\alpha} = 382,399\ \text{N/mm}^2$$

A.10.2 Determination of permissible tooth root stress, σ_{FP}

7.4 Stress concentration factor (standard reference test gears), Y_{ST}

$$Y_{ST1} = 2,0 \qquad Y_{ST2} = 2,0$$

13.3.2.1 Relative notch sensitivity factor (for reference stress), $Y_{\delta relT}$

$$\chi_P^* = \frac{1}{5} \tag{77}$$

$$\chi_1^* = \chi_P^* (1 + 2\,q_{s1}) = 0,878\,71 \tag{76}$$

$$\chi_2^* = \chi_P^* (1 + 2\,q_{s2}) = 1,142\,35$$

$$q_{sT} = 2,5$$

© ISO 2022 – All rights reserved

$$\chi_T^* = \chi_P^* (1 + 2 q_{sT}) = 1,200\,00$$

Slip layer thickness (see ISO 6336-3:2019, Table 4).

For material Eh,

$\rho'_1 = 0,003$ $\rho'_2 = 0,003$

$$Y_{\delta relT1} = \frac{1 + \sqrt{\rho'_1 \chi_1^*}}{1 + \sqrt{\rho'_1 \chi_T^*}} = 0,991\,83 \quad (75)$$

$$Y_{\delta relT2} = \frac{1 + \sqrt{\rho'_2 \chi_2^*}}{1 + \sqrt{\rho'_2 \chi_T^*}} = 0,998\,62$$

14.3.2.1 Relative surface factor, Y_{RrelT}

$Rz_{F1} = Ra_{F1}\,6 = 18$ $Rz_{F2} = Ra_{F2}\,6 = 18$

Reference stress in the range 1 µm ≤ Rz ≤ 40 µm for material Eh

$$Y_{RrelT1} = 1,674 - 0,529 \cdot (Rz_{F1} + 1)^{0,1} = 0,963\,88 \quad (87)$$

$$Y_{RrelT2} = 1,674 - 0,529 \cdot (Rz_{F2} + 1)^{0,1} = 0,963\,88$$

15.3.3.1 Size factor, Y_X

See ISO 6336-3:2019, Table 5.

For material Eh and 5 < m_n < 25,

$$Y_{X1} = 1,05 - 0,01\,m_n = 0,970\,00$$

$$Y_{X2} = 1,05 - 0,01\,m_n = 0,970\,00$$

12.3 Life factor for reference test conditions (tooth root stress), $Y_{NT\text{-}B}$

Number of load cycles, N_{L1}, is greater than endurance point, therefore, interpolation between the endurable point and 10^{10} cycles is required.

$Y_{NT1ref1} = 1$ $Y_{NT1ref2} = 0,85$

$N_{L1ref1} = 3 \cdot 10^6$ $N_{L1ref2} = 10^{10}$

$$Y_{NT1} = \frac{N_{L1}^{\left[\frac{\log(Y_{NT1ref2}) - \log(Y_{NT1ref1})}{\log(N_{L1ref2}) - \log(N_{L1ref1})}\right]}}{N_{L1ref1}^{\left[\frac{\log(Y_{NT1ref2}) - \log(Y_{NT1ref1})}{\log(N_{L1ref2}) - \log(N_{L1ref1})}\right]}} = 0,888\,76$$

Number of load cycles, N_{L2}, is greater than endurance point, therefore, interpolation between the endurable point and 10^{10} cycles is required.

$Y_{NT2ref1} = 1$ $Y_{NT2ref2} = 0,85$

© ISO 2022 – All rights reserved

$$N_{\mathrm{L2ref1}} = 3 \cdot 10^6 \qquad N_{\mathrm{L2ref2}} = 10^{10}$$

$$Y_{\mathrm{NT2}} = \frac{N_{L2}^{\left[\frac{\log(Y_{\mathrm{NT2ref2}}) - \log(Y_{\mathrm{NT2ref1}})}{\log(N_{\mathrm{L2ref2}}) - \log(N_{\mathrm{L2ref1}})}\right]}}{N_{\mathrm{L2ref1}}^{\left[\frac{\log(Y_{\mathrm{NT2ref2}}) - \log(Y_{\mathrm{NT2ref1}})}{\log(N_{\mathrm{L2ref2}}) - \log(N_{\mathrm{L2ref1}})}\right]}} = 0{,}921\ 42$$

5.4.3 Permissible bending stress, σ_{FP}

$$\sigma_{\mathrm{FP1}} = \frac{\sigma_{\mathrm{F\,lim1}} \cdot Y_{\mathrm{ST1}} \cdot Y_{\mathrm{NT1}}}{S_{\mathrm{F\,min}}} Y_{\delta\mathrm{relT1}} \cdot Y_{\mathrm{RrelT1}} \cdot Y_{\mathrm{X1}} = 824{,}173\,\mathrm{N/mm^2} \tag{5}$$

$$\sigma_{\mathrm{FP2}} = \frac{\sigma_{\mathrm{F\,lim2}} \cdot Y_{\mathrm{ST2}} \cdot Y_{\mathrm{NT2}}}{S_{\mathrm{F\,min}}} Y_{\delta\mathrm{relT2}} \cdot Y_{\mathrm{RrelT2}} \cdot Y_{\mathrm{X2}} = 860{,}313\,\mathrm{N/mm^2}$$

5.2 Safety factor for bending strength, S_{F}

$$S_{\mathrm{F1}} = \frac{\sigma_{\mathrm{FP1}} \cdot S_{\mathrm{F\,min}}}{\sigma_{\mathrm{F1}}} = 2{,}087\,25 \tag{1}$$

$$S_{\mathrm{F2}} = \frac{\sigma_{\mathrm{FP2}} \cdot S_{\mathrm{F\,min}}}{\sigma_{\mathrm{F2}}} = 2{,}249\ 78 \tag{2}$$

© ISO 2022 – All rights reserved

Bibliography

[1] ISO 53, *Cylindrical gears for general and heavy engineering — Standard basic rack tooth profile*

[2] ISO 1328-1:2013, *Cylindrical gears — ISO system of flank tolerance classification — Part 1: Definitions and allowable values of deviations relevant to flanks of gear teeth*

[3] ISO 4287:1997[1)], *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Terms, definitions and surface texture parameters*

[4] ISO 4288:1996[2)], *Geometrical Product Specifications (GPS) — Surface texture: Profile method — Rules and procedures for the assessment of surface texture*

[5] ISO 21771, *Gears — Cylindrical involute gears and gear pairs — Concepts and geometry*

1) Cancelled and replaced by ISO 21920-2:2021.

2) Cancelled and replaced by ISO 21920-3:2021.

© ISO 2022 – All rights reserved

ICS 21.200

Price based on 63 pages

© ISO 2022 – All rights reserved