



Stored Procedures

.NET CORE

SQL Server creates an execution plan for a stored procedure and stores it in the cache. In following executions, the plan is reused so that the stored procedure can execute fast and with reliable performance.

[HTTPS://WWW.SQLSERVERTUTORIAL.NET/SQL-SERVER-STORED-PROCEDURES/](https://www.sqlservertutorial.net/sql-server-stored-procedures/)

Stored Procedures – Overview

https://www.w3schools.com/sql/sql_stored_procedures.asp

<https://docs.microsoft.com/en-us/sql/relational-databases/stored-procedures/stored-procedures-database-engine?view=sql-server-ver15>

A stored procedure is a SQL query that you have saved as a function so it can be reused. The execution plan is saved so the query runs faster than if it were written new each time it was used.

A commonly used SQL query can be saved as a stored procedure, and then called when needed. Stored procedures can have parameters and act based on the parameter values passed.

SSMS has some built-in Stored Procedures.

1. Use keywords 'CREATE PROCEDURE'
2. Give the procedure a name
3. Use the keyword 'AS'
4. Write the query

```
CREATE PROCEDURE  
procedure_name  
AS  
sql_statement
```

Stored Procedures – Overview

https://www.w3schools.com/sql/sql_stored_procedures.asp

<https://docs.microsoft.com/en-us/sql/relational-databases/stored-procedures/stored-procedures-database-engine?view=sql-server-ver15>

Stored Procedures:

- Accept input parameters
- Can return multiple values in the form of OUTPUT parameters.
- Contain programming statements that perform operations in the database, include calling other procedures.
- Return a status value to a calling program to indicate success, failure, and the reason for failure.
- Allow easy reuse of code maintenance
- Improve performance
- Reduce network traffic.

Stored Procedures – Types

<https://docs.microsoft.com/en-us/sql/relational-databases/stored-procedures/stored-procedures-database-engine?view=sql-server-ver15#types-of-stored-procedures>

There are four types of Stored Procedures

Type	Description
User-Defined	Created in a user-defined database or in any system database except the Resource database. Can be developed in SQL or as a reference to a method.
Temporary	Stored in tempdb . There are two types: local and global. Local temp procedures have # as the first character of their names, are visible only to the current user connection, and they are deleted when the connection is closed. Global temporary procedures have ## as the first two characters of their names, are visible to any user after they are created, and are deleted at the end of the last session using the procedure.
System	Included with SQL Server. They are physically stored in the internal, hidden Resource database and logically appear in the sys schema of every system- and user-defined database.
Extended User-Defined	Extended procedures enable creating external routines in a programming language such as C. These procedures are DLLs that an instance of SQL Server can dynamically load and run.

Stored Procedure – Create, Execute, Delete

<https://www.sqlservertutorial.net/sql-server-stored-procedures/basic-sql-server-stored-procedures/>

<https://docs.microsoft.com/en-us/sql/relational-databases/stored-procedures/create-a-stored-procedure?view=sql-server-ver15>

This Stored Procedure is called
GetAllCustomerNames.

When executed, it will produce a table with two columns,
CustomerId and **FirstName**, from the **Customers** table, where the **addressId** (FK) is 1.

Below the **EXEC** statement you can see how to drop a Stored Procedure.

```
--Simple Stored Procedure
CREATE PROCEDURE GetAllCustomerNames
AS
SELECT CustomerId, FirstName
FROM Customers
WHERE addressID = 1;

EXEC GetAllCustomerNames;
DROP PROCEDURE GetAllCustomerNames;
```


SQL – Scalar Variables

Sometimes we want to store intermediate values.

- We can split queries into several parts
- SQL Server supports *scalar* variables and *table-valued* variables
- They only exist for the duration of that "batch" of commands

```
DECLARE @maxid INT;  
SELECT @maxid = MAX(TypeId) FROM Poke.Type;  
SET @maxid = (SELECT MAX(TypeId) FROM Poke.Type); -- another way to set variable  
INSERT INTO Poke.Type (TypeId, Name) VALUES (@maxid + 1, 'Earth');
```

Declaring Scalar Variables

<https://docs.microsoft.com/en-us/sql/relational-databases/stored-procedures/specify-parameters?view=sql-server-ver15#passing-values-into-parameters>

To declare a variable in SQL:

- Declare the variable(s) by using the **DECLARE** keyword.
- Follow **DECLARE** with **@[variableName] [datatype]**.
- Use the Keyword **SET**.
- Use **@[variableName]**
- Set the variable equal to the value you want.
- Then you can pass the variables as arguments into a Procedure.

```
DECLARE @ProductID int, @CheckDate datetime;  
  
SET @ProductID = 819;  
  
SET @CheckDate = '20050225';  
  
EXEC dbo.uspGetProductID @ProductID,  
@CheckDate;
```


SQL – Table-Valued Variables

<https://docs.microsoft.com/en-us/sql/relational-databases/tables/use-table-valued-parameters-database-engine?view=sql-server-ver15>

Table-valued parameters are declared by using user-defined table types. You can use table-valued parameters to send multiple rows of data to a Transact-SQL statement or a routine, such as a stored procedure or function, without creating a temporary table or many parameters.

A table-valued parameter is scoped to the stored procedure, function, or dynamic Transact-SQL text, exactly like other parameters.

Table-valued parameters must be passed as input READONLY parameters to Transact-SQL routines. You cannot perform DML operations such as UPDATE, DELETE, or INSERT on a table-valued parameter in the body of a routine.

```
/* Create a table type. */
CREATE TYPE LocationTableType
AS TABLE
    ( LocationName VARCHAR(50)
      , CostRate INT );
--Create a procedure to receive data for table-valued parameter.
CREATE PROCEDURE dbo. usp_InsertProductionLocation
    @TVP LocationTableType READONLY
AS    INSERT INTO AdventureWorks2012.Production.Location
    (
        Name
        , CostRate
        , Availability
        , ModifiedDate
    )
    SELECT *, 0, GETDATE()
    FROM @TVP;
/* Declare a variable that references the type. */
DECLARE @LocationTVP AS LocationTableType;
/* Add data to the table variable. */
INSERT INTO @LocationTVP (LocationName, CostRate)
    SELECT Name, 0.00
    FROM AdventureWorks2012.Person.StateProvince;

/* Pass the table variable data to a stored procedure. */
EXEC usp_InsertProductionLocation @LocationTVP;
```

Stored Procedure with Parameters

<https://docs.microsoft.com/en-us/sql/relational-databases/stored-procedures/specify-parameters?view=sql-server-ver15>

The parameter values supplied with a procedure call must be constants or a variable; a function name cannot be used as a parameter value.

When creating a procedure and declaring a parameter name, the parameter name must begin with a single @ character and must be unique in the scope of the procedure.

Parameters must be defined with a data type when they are declared in a CREATE PROCEDURE statement.

```
--Stored Procedure with variables
CREATE PROCEDURE GetCustomerShe
    @LastName nvarchar(50),
    @FirstName nvarchar(50)
AS
    SELECT FirstName, LastName, Remarks
    FROM Customers
    WHERE FirstName = @FirstName
    AND
        LastName = @LastName
    AND
        Remarks LIKE 'S_e%';

EXEC GetCustomerShe
    @LastName = 'Moore',
    @FirstName = 'Maya';

DROP PROCEDURE GetCustomerShe;
```

Stored Procedure – OUT Parameter

<https://docs.microsoft.com/en-us/sql/relational-databases/stored-procedures/specify-parameters?view=sql-server-ver15#specifying-parameter-direction>

The direction of a parameter is either INPUT (default) or OUTPUT, meaning the procedure returns a value to the calling program.

To specify an OUTPUT parameter, the OUTPUT keyword must be specified in the definition of the parameter in the **CREATE PROCEDURE** statement.

The procedure returns the current value of the OUTPUT parameter to the calling program when the procedure exits.

The calling program must also use the OUTPUT keyword when executing the procedure to save the parameter's value in a variable that can be used in the calling program.

```
CREATE PROCEDURE HowManyOrdersByCustomer (  
    @CustomerNumber INT,--customerID  
    @OrderCount INT OUTPUT  
) AS  
BEGIN  
    SELECT  
        CustomerID AS CustomersID  
    FROM Orders  
    WHERE CustomerID = @CustomerNumber;  
    -- @@ROWCOUNT is a system variable that returns  
    -- the number of rows read by the previous statement.  
    SELECT @OrderCount = @@ROWCOUNT;  
END;  
-- declare the OUTPUT variable  
DECLARE @HowMany INT;  
-- call the method with the 2 parameters  
EXEC HowManyOrdersByCustomer 1, @HowMany OUTPUT;  
SELECT @HowMany AS 'Ten times the total';
```

Procedure with Try/Catch

```
GO
CREATE OR ALTER PROCEDURE Poke.UpdateAllDateModified(@param INT, @rowschanged INT OUTPUT)
AS
BEGIN
    BEGIN TRY
        IF (NOT EXISTS (SELECT * FROM Poke.Pokemon))
        BEGIN
            RAISERROR ('No data found in table', 15, 1);
        END
        SET @rowschanged = (SELECT COUNT(*) FROM Poke.Pokemon);
        UPDATE Poke.Pokemon SET DateModified = GETDATE();
    END TRY
    BEGIN CATCH
        PRINT 'Error'
    END CATCH
END
GO
```

This procedure updates all the DateModified values to the current time and returns the number of rows modified

```
DECLARE @result INT;
EXECUTE Poke.UpdateAllDateModified 123, @result OUTPUT;
SELECT @result;
```

Pushpinder Lecture

Lots of stored procedures and her writing them to show that they work. She's using her PPT (that's in the repo) to guide her

The assignment for the Associates is to:

1. Read PDF for Stored Proc Lesson 1-3
2. Perform demos A-C for Module 15
3. Read more pdfs on Conditionals in sql and error handling
4. perform Demos for Module 16 and 17

```
!Query3.sql - RE...MCA\Revature (59))& -> X
exec sp_helptext 'sp_help' --'[sys].[sp_add_agent_profile]'

create procedure sp_GetAllEmployees
as
begin
select * from HR.Employees
end

execute sp_GetAllEmployees

exec sp_helptext 'sp_GetAllEmployees'
```

```
exec sp_helptext 'sp_GetAllEmployees'

create procedure sp_GetEmployeeById
(
    @id int
)
with encryption
as
begin
select empid as Id, (concat(firstname, ' ', lastname)) as Fullname, title as Role, phone
from HR.Employees
where empid=@id
end

exec sp_GetEmployeeById @id=5
```

SQL – Value-Typed Variables

```
DECLARE @@mytable AS TABLE (  
    Id INT,  
    Name NVARCHAR(20)  
);  
INSERT INTO @@mytable  
    SELECT TypeId, Name FROM Poke.Type;
```


Prepared SQL Queries

<https://docs.microsoft.com/en-us/dotnet/api/system.data.sqlclient.sqlcommand.prepare?view=dotnet-plat-ext-5.0>
