



TypeScript Fundamentals

.NET


*TypeScript is a ‘typed’ superset (static typechecker) for JavaScript programs. A Static Typechecker is a tool that runs before code runs to ensure that the **types** of the program are correct.*

[HTTPS://WWW.TYPESCRIPTLANG.ORG/DOCS/HANDBOOK/INTRO.HTML#ABOUT-THIS-HANDBOOK](https://www.typescriptlang.org/docs/handbook/intro.html#about-this-handbook)

TypeScript – Overview

<https://www.typescriptlang.org/docs/handbook/typescript-from-scratch.html#typescript-a-static-type-checker>
<https://angular.io/guide/glossary>

- Detecting errors in code without running it is referred to as **Static Checking**.
- Determining what code is an error (and what's not) based on the kinds(types) of values being operated on is known as **Type Checking**.
- **TypeScript** is a **Static Type Checking*** language. It checks a program for errors before it's run based on the types of the values.
- **TypeScript** is a **Superset** of **JavaScript**. All **JavaScript** syntax is legal withing a **.ts** (**TypeScript**) file. You don't need 'use strict'.
- Remember that all your **JavaScript** questions also apply to **TypeScript**.



*Dynamic Type Checking is when type checking is done at runtime


TypeScript – Compiling vs Transpiling

<https://www.stevefenton.co.uk/2012/11/compiling-vs-transpiling/>
<https://code.visualstudio.com/docs/typescript/typescript-compiling>
<https://www.typescriptlang.org/play>

TypeScript is a typed superset of **JavaScript**. This means that it compiles to plain **JavaScript**. **TypeScript** enforces strict **typing** among other rules. It has classes, modules, **type** checking, and interfaces. **TypeScript** must be **transpiled** into **JavaScript** code.

“Transpiling” vs. “Compiling”:

- **Compiling** is the term for taking source code written in one language and transforming into another.
- **Transpiling** is a specific term for taking source code written in one language and transforming into another language that has a similar level of abstraction.



Click [here](#) to see TS and JS compared.

TypeScript – Types

<https://www.typescriptlang.org/docs/handbook/typescript-from-scratch.html>

TypeScript adds rules about how different value types can be used. *TS* infers value **types** and enforces these **types** throughout the program. *TypeScript's type* system rules are designed to allow correct programs through while catching as many common errors as possible.

If you move code from a *JavaScript* file to a *TypeScript* file, you might see type errors that are legitimate problems with the code or it may be that *TypeScript* is being overly conservative.

```
console.log(4 / []);
```

JS allows division by an empty set while *TS* will not. The below example in *JS* will print **NaN**, but *TS* will give an error.

```
const user = {  
  firstName: "Angela",  
  lastName: "Davis",  
  role: "Professor"  
}
```

```
console.log(user.name)
```

```
Property 'name' does not exist on type '{ firstName: string;  
lastName: string; role: string; }'.
```


TypeScript Type Annotations

<https://www.tutorialsteacher.com/typescript/type-annotation>

<https://www.typescriptlang.org/docs/handbook/basic-types.html#type-assertions>

One of the primary benefits of *TypeScript* over *JavaScript* is that variable types can be explicitly specified. This is done with *Type Annotations* (Type Assertions).

A *Type Annotation* is placed after the name of the variable (or parameter, property, etc).

TypeScript has all the primitive types of *JavaScript* plus adds some new ones.

```
var age: number = 32; // number variable
var name: string = "John"; // string variable
var isUpdated: boolean = true; // Boolean variable
```

```
function display(id:number, name:string)
{
    console.log("Id = " + id + ", Name = " + name);
}
```

```
var employee : {
    id: number;
    name: string;
};
```

```
employee = {
    id: 100,
    name : "John"
}
```

Type assertions have two forms. One is the "angle-bracket" syntax:

```
let someValue: any = "this is a string";
let strLength: number = (<string>someValue).length;
```

And the other is the `as`-syntax:

```
let someValue: any = "this is a string";
let strLength: number = (someValue as string).length;
```

Type Definitions

<https://www.typescriptlang.org/docs/handbook/typescript-in-5-minutes.html#defining-types>

- **TS** infers most *types*, but you can enforce *strict typing* by using an *interface* to declare a class and **TS** will enforce that *typing*.
- **TS** supports classes and OOP, so an *interface* declaration can also be used with classes.
- There are two syntaxes for building types: *Interfaces* and *Types*.
- Usually, you will use *interface*. Use *type* when you need specific features.

```
interface User {  
  name: string;  
  id: number;  
}
```

```
const user: User = {  
  username: "Hayes",
```


Type '{ username: string; id: number; }' is not assignable to type 'User'.

Object literal may only specify known properties, and 'username' does not exist in type 'User'.

```
  id: 0,  
};
```

TypeScript – Erased Types

<https://www.typescriptlang.org/docs/handbook/typescript-from-scratch.html#erased-types>



- Due to *TypeScript*'s *type* annotations there are no browsers that can run *TypeScript* unmodified.
- *TypeScript* has its own compiler in order to strip out (erase) *TypeScript*-specific code so that it can be run.
- There is no persisted *type* information in the resulting *JS* code.
- *TypeScript* preserves the runtime behavior of *JavaScript*.
- *TS* never changes the behavior of your program based on the *types* it inferred, so the *type* system has no influence on how a program works once it's running.
- *TS* uses *JS* libraries so there's no additional *TS-specific* framework to learn.

```
1 // @showEmit
2 function greet(person: string, date: Date) {
3   console.log(`Hello ${person}, today is ${date.toDateString()}!`);
4 }
5
6 greet("Maddison", new Date());
```

TypeScript

JavaScript

```
"use strict";
// @showEmit
function greet(person, date) {
  console.log(`Hello ${person}, today is ${date.toDateString()}!`);
}
greet("Maddison", new Date());
```


TypeScript – Primitive Types

<https://www.typescriptlang.org/docs/handbook/typescript-in-5-minutes.html#defining-types>

<https://www.typescriptlang.org/docs/handbook/basic-types.html>

TypeScript uses all *JS*'s data types. *TS* extends *JS* types with a few of its own.

Type	Purpose
any	Allow any type
unknown	Ensure someone using the type declares what the type is. Unknown is the type-safe counterpart of any.
never	Represents the type of values that never occur. EX. never is the return type for a function expression that always throws an exception or one that never returns.
void	a function which returns undefined or has no return value

TypeScript – Structural Type System

<https://www.typescriptlang.org/docs/handbook/typescript-in-5-minutes.html#structural-type-system>

A core principle of *TypeScript* is that *type* checking focuses on the shape (structure) that objects have. This is called “*Structural Typing*” (or “*Duck Typing*”). The compiler only checks that at least the variable names required are present in args passed and that they match the *types* required.

```
interface Point {  
  x: number;  
  y: number;  
}
```

1. Declare an
interface object.

```
function printPoint(p: Point) {  
  console.log(`${p.x}, ${p.y}`);  
}
```

2. Define a function
that takes
that object.

```
// prints "12, 26"
```

```
const point = { x: 12, y: 26 };  
printPoint(point);
```

3. Instantiate the object.

4. Invoke the function.

```
const point3 = { x: 12, y: 26, z: 89 };  
printPoint(point3); // prints "12, 26"
```

Prints 2 of the
3 parameters

```
const rect = { x: 33, y: 3, width: 30, height: 80 };  
printPoint(rect); // prints "33, 3"
```

Prints 2 of the
4 parameters

```
const color = { hex: "#187ABF" };
```

```
printPoint(color);
```

ERROR Result

Argument of type '{ hex: string; }' is not assignable to parameter of type 'Point'.

Type '{ hex: string; }' is missing the following properties from type 'Point': x, y

TypeScript – Composing Types

<https://www.typescriptlang.org/docs/handbook/typescript-in-5-minutes.html#composing-types>

TypeScript understands how code can change what **type** a variable could be. You can use checks to verify the **type** at runtime and take appropriate action.

Type	Predicate*
string	<code>typeof myString === "string"</code>
number	<code>typeof myNum === "number"</code>
boolean	<code>typeof myBool === "boolean"</code>
undefined	<code>typeof undef === "undefined"</code>
function	<code>typeof myFunc === "function"</code>
array	<code>Array.isArray(a)</code>

A **Union** allows you to declare what the type could be.

```
function wrapInArray(obj: string | string[]) {  
  if (typeof obj === "string") {  
    //      ^ = (parameter) obj: string  
    return [obj];  
  } else {  
    return obj;  
  }  
}
```

*Often used in a if-then comparison.

TypeScript Interfaces and Class Types

<https://www.typescriptlang.org/docs/handbook/interfaces.html#class-types>

Interfaces are a great way to explicitly enforce that a class meets a particular contract for properties and functions.

In **TS**, Interfaces only describe the public side of the class.

```
interface ClockInterface {  
    currentTime: Date;  
    setTime(d: Date): void;  
}  
  
class Clock implements ClockInterface {  
    currentTime: Date = new Date();  
    setTime(d: Date) {  
        this.currentTime = d;  
    }  
    constructor(h: number, m: number) {}  
}
```

TypeScript Classes and Inheritance

<https://www.typescriptlang.org/docs/handbook/classes.html>

TypeScript developers can use OOP techniques and *transpile* them into *JavaScript*. As in *JS*, *Abstract* classes in *TS* may only be inherited.

```
class Greeter {
  greeting: string;
  constructor(message: string) {
    this.greeting = message;
  }
  greet() {
    return "Hello, " + this.greeting;
  }
}

let greeter = new Greeter("world");
```

```
class Animal {
  move(distanceInMeters: number = 0) {
    console.log(`Animal moved ${distanceInMeters}m.`);
  }
}

class Dog extends Animal {
  bark() {
    console.log("Woof! Woof!");
  }
}

const dog = new Dog();
dog.bark();
dog.move(10);
dog.bark();
```

```
abstract class Animal {
  abstract makeSound(): void;
  move(): void {
    console.log("roaming the earth...");
  }
}
```

TypeScript Inheritance with *this*

<https://www.typescriptlang.org/docs/handbook/classes.html#inheritance>

Each *derived* class that contains a constructor function must call *super()* to execute the constructor of the *base* class.

Before a property on *this* is accessed from within a constructor body, *super()* must be called.

This is an important rule that TypeScript will enforce.

```
class Animal {
  name: string;
  constructor(theName: string) {
    this.name = theName;
  }
  move(distanceInMeters: number = 0) {
    console.log(`${this.name} moved ${distanceInMeters}m.`);
  }
}

class Snake extends Animal {
  constructor(name: string) {
    super(name);
  }
  move(distanceInMeters = 5) {
    console.log("Slithering...");
    super.move(distanceInMeters);
  }
}

class Horse extends Animal {
  constructor(name: string) {
    super(name);
  }
  move(distanceInMeters = 45) {
    console.log("Galloping...");
    super.move(distanceInMeters);
  }
}

let sam = new Snake("Sammy the Python");
let tom: Animal = new Horse("Tommy the Palomino");

sam.move();
tom.move(34);
```


TypeScript – Class Property Modifiers

<https://www.typescriptlang.org/docs/handbook/classes.html#public-private-and-protected-modifiers>

- In *TypeScript*, each class member is *public* by default.
- *TS* also has its own way to declare a member as being *private*.
- *TypeScript* also supports the new *JavaScript* syntax for *private* fields.
- *Private* fields cannot be accessed from outside of their containing classes.
- Members declared *protected* can be accessed from within their class and *deriving* classes.
- A constructor may also be marked *protected*. This means that the class cannot be instantiated outside of its containing class but can be *extended*.
- *Readonly* properties must be initialized at their declaration or in the constructor.

```
class Animal {  
  private name: string;  
  constructor(theName: string) {  
    this.name = theName;  
  }  
}
```

```
class Animal {  
  #name: string;  
  constructor(theName: string) { this.#name = theName; }  
}
```

```
class Person {  
  protected name: string;  
  protected constructor(theName: string) {  
    this.name = theName;  
  }  
}  
  
// Employee can extend Person  
class Employee extends Person {  
  private department: string;  
  
  constructor(name: string, department: string) {  
    super(name);  
    this.department = department;  
  }  
  
  public getElevatorPitch() {  
    return `Hello, my name is ${this.name} and I work in ${this.department}.`;  
  }  
}  
  
let howard = new Employee("Howard", "Sales");  
let john = new Person("John"); // Error: The 'Person' constructor is protected
```

TypeScript – Static Class Properties

<https://www.typescriptlang.org/docs/handbook/classes.html#static-properties>

Static members of a class are visible on the class itself rather than on the instances. Each instance accesses this shared value through prepending the name of the containing class.

```
class Grid {  
  static origin = { x: 0, y: 0 };  
  calculateDistanceFromOrigin(point: { x: number; y: number }) {  
    let xDist = point.x - Grid.origin.x;  
    let yDist = point.y - Grid.origin.y;  
    return Math.sqrt(xDist * xDist + yDist * yDist) / this.scale;  
  }  
  constructor(public scale: number) {}  
}  
  
let grid1 = new Grid(1.0); // 1x scale  
let grid2 = new Grid(5.0); // 5x scale  
  
console.log(grid1.calculateDistanceFromOrigin({ x: 10, y: 10 }));  
console.log(grid2.calculateDistanceFromOrigin({ x: 10, y: 10 }));
```

TypeScript Interfaces

<https://www.typescriptlang.org/docs/handbook/interfaces.html>

- Here, **LabeledValue** is an interface with a string property (**label**).
- It is not required to explicitly state that the object passed into a function implements an interface (as in C# and others).
- In **TS**, only the objects' **shape** matters. If the object passed into the function meets the requirements listed (the **shape**), it is allowed.
- **Type** checker does not require that properties come in any specific order.
- The only requirement is that property names required by the interface must be present* AND have the required **type**.

```
interface LabeledValue {  
    label: string;  
}  
  
function printLabel(labeledObj: LabeledValue) {  
    console.log(labeledObj.label);  
}  
  
let myObj = { size: 10, label: "Size 10 Object" };  
printLabel(myObj);
```

*Mark a property **optional** with '?' at the end of the property name.

TypeScript – Extending Interfaces

<https://www.typescriptlang.org/docs/handbook/interfaces.html#extending-interfaces>

Classes and Interfaces can extend Interfaces.

This allows you to copy the members of one interface into another interface or class.

```
interface Shape {  
    color: string;  
}  
  
interface PenStroke {  
    penWidth: number;  
}  
  
interface Square extends Shape, PenStroke {  
    sideLength: number;  
}  
  
let square = {} as Square;  
square.color = "blue";  
square.sideLength = 10;  
square.penWidth = 5.0;
```

TypeScript Functions

<https://www.typescriptlang.org/docs/handbook/functions.html>

In *TypeScript*, there are classes, namespaces, and modules, but functions still play the key role in describing how to complete actions. *TypeScript* adds some new capabilities to JS.

TypeScript functions can be *named* or *anonymous* functions. They can also refer to variables outside of the function body.

You should explicitly **type** the parameters of functions.

A function's **type** has the same two parts: the **type** of the arguments and the return **type**. When writing out the whole function **type**, both parts are required.

```
function add(x: number, y: number): number {  
    return x + y;  
}  
  
let myAdd = function(x: number, y: number): number { return x + y; };
```

```
let myAdd: (x: number, y: number) => number = function(  
    x: number,  
    y: number  
): number {  
    return x + y;  
};
```

TS Function Parameter Types

<https://www.typescriptlang.org/docs/handbook/functions.html#optional-and-default-parameters>

- In *TS*, every function parameter is assumed to be **required** by the function.
- Make a parameter **optional** by placing a '?' behind the parameter name.
- **Optional** parameters must be last.
- Give parameters **default** values with '**paramName** = "value"'.
(paramName and value are highlighted in red in the original image)
- When a **default** parameter comes last, it is treated as **optional**.
- **Rest** Parameters ('...**paramName**') in *TS* are like **args** parameters in *JS*.
(args is highlighted in red in the original image)
- **Rest** parameters are treated as **optional** parameters. The compiler builds an array of the additional arguments passed with the name given after the ellipsis (...).

```
function buildName(firstName: string, lastName?: string) {  
    if (lastName) return firstName + " " + lastName;  
    else return firstName;  
}
```

Optional parameters

```
function buildName(firstName: string, lastName = "Smith")  
    return firstName + " " + lastName;  
}
```

Default parameters

```
function buildName(firstName: string, ...restOfName: string[]) {  
    return firstName + " " + restOfName.join(" ");  
}
```

Rest parameters

TypeScript Modules

<https://www.typescriptlang.org/docs/handbook/modules.html>


TS shares the *JS* concept of **Modules**. **Modules** in *TS* have their own scope. A module must be explicitly exported to make its members visible.

To consume a property **exported** from a different **module**, it must be **imported** using an **import** method.

The relationships between **modules** are specified in terms of **imports** and **exports** at the file level.

In *TS*, any file containing a top-level **import** or **export** is considered a **module**.

A file without any top-level **import** or **export** declarations is treated as a script whose contents are available in the global scope (and therefore in **modules** as well).



TypeScript - Exporting a Declaration

<https://www.typescriptlang.org/docs/handbook/modules.html#export>

Any declaration (variable, function, class, type alias, interface) can be **exported** by adding the **export** keyword before the type keyword.

1. Use the **export** keyword to make a class, function, or variable available to other **modules** from within the **module (component)**.
2. **Import** the class, function, or variable into the **module (component)** where you want to implement it.

```
export interface StringValidator {  
    isAcceptable(s: string): boolean;  
}
```

```
import { StringValidator } from "./StringValidator";  
  
export const numberRegex = /^[0-9]+$/;  
  
export class ZipCodeValidator implements StringValidator {  
    isAcceptable(s: string) {  
        return s.length === 5 && numberRegex.test(s);  
    }  
}
```

TypeScript - Export

<https://www.typescriptlang.org/docs/handbook/modules.html#export-statements>

Export and *Import* statements allow you to rename the module.

Conventionally, import statements are listed at the top of the document while export statements are listed at the bottom.

```
class ZipCodeValidator implements StringValidator {  
    isAcceptable(s: string) {  
        return s.length === 5 && numberRegexp.test(s);  
    }  
}  
  
export { ZipCodeValidator };  
export { ZipCodeValidator as mainValidator };
```

```
import { ZipCodeValidator } from "../ZipCodeValidator";  
  
let myValidator = new ZipCodeValidator();
```

```
import { ZipCodeValidator as ZCV } from "../ZipCodeValidator";  
let myValidator = new ZCV();
```

Create a TS version of GuessingGame Setup

<https://www.valentinog.com/blog/typescript/>

<https://www.typescriptlang.org/docs/handbook/asp-net-core.html>

1. Create a new folder for this project in your repo.
2. Make sure you have Node.js with `node -v` in Command Line. If not, go to nodejs.org to get it.
3. In Command Line, run `npm init -y` to create a *package.json* file.
4. In Command Line run `npm i typescript --save-dev` (dash-dash) (what is [--save-dev](#)?) to install a *TS* dependency via *npm* (this installs for just this program).
5. In the new *package.json* file, configure the node script to compile with *tsc*. Include `"scripts":{ "tsc": "tsc"}`. "scripts" should already be among the key:value pairs.
6. Run `npm run tsc -- --init` (dash-dash, space, dash-dash) in Command Line to create a *tsconfig.json* file for which the TS compiler (*tsc*) will look. You should get `"message TS6071: Successfully created a tsconfig.json file."` in the Command Line.
7. Replace all the original content of the *tsconfig.json* file with:
 - `{ "compilerOptions": { "target": "es5", "strict": true } }`
8. ES5 is the newest JS release. "Strict" enforces *TS*'s highest level of strictness. Visit <https://aka.ms/tsconfig.json> for info on the *tsconfig* file
9. Compile and run with `npm run tsc` in Command Line. This will transpile the TS code to JS code and create a file in the same folder.
10. Complete the [Migrating from JavaScript](#) tutorial.
11. Make sure to use `<script>` to include the new .js file inside your .html.