

Test Report

Number: SZHH01971104

Applicant: GIGACLOUD TECHNOLOGY (USA) INC.
4388 SHIRLEY AVENUE, EL MONTE, CA 91731

Date: Oct 08, 2024

Attn: Jeffery

Sample Description:

One (1) set of submitted sample said to be :

Item Name : **Loft Bed.**
Item No. : **N709P224891+N709P224892**
Labelled Age Group : **6+.**
Applicant Specified Age : **Over 6 years.**
Grading for Testing :
Packaging Provided by Applicant : **No.**
Additional Material and Wet Paint Provided : **No.**
Country of Destination : **USA.**
Date Sample Received : **Sep 05, 2024 & Sep 29, 2024.**
Testing Period : **Sep 05, 2024 – Oct 08, 2024.**

SZHH01971104



Tests conducted:

As requested by the applicant, refer to attached page(s) for details.



Page 1 of 32



Test Report

Number: SZHH01971104

Conclusion:

<u>Tested Sample</u> Submitted Sample	<u>Standard</u> ASTM F1427-21 ^{§1} - Standard Consumer Safety Specification for Bunk Beds -Excluding clause 6.2.3	<u>Result</u> Pass
	<u>Requirement</u> 16 CFR Part 1513 - Requirements for Bunk Beds Intended for Use by Children / 16 CFR Part 1213 -Requirements for Bunk Beds not Intended for Use by Children	<u>Result</u> Pass
	<u>Standard</u> Consumer Product Safety Improvement Act (CPSIA) 2008 Section 103 Tracking Labels for Children Products, 15 U.S.C. §2063(a)(5) (CPSA), Consumer Product Safety Act Section 14(a) (5)	<u>Result</u> See test conducted
	<u>Requirement</u> U.S. CFR Title 16 (CPSC Regulations) Mechanical and physical test	<u>Result</u> Pass
	U.S. CFR Title 16 (CPSC Regulations) Part 1500.3(c)(6)(vi) flammability test on rigid and pliable solids	Pass
<u>Tested Sample</u> Tested components of submitted samples	<u>Standard</u> U.S. CFR Title 16 Part 1303 total Lead content	<u>Result</u> Pass
	U.S. Consumer Product Safety Improvement Act 2008 Title I, Section 101 for total Lead content in surface coating	Pass
	U.S. Consumer Product Safety Improvement Act 2008 Title I, Section 101 for Total Lead content in Non-surface coating materials (substrate)	Pass

Authorized by:
For Intertek Testing Services Shenzhen Ltd
Xiamen Branch



Rachel L. Guo
General Manager



Page 2 of 32



Test Report

Number: SZHH01971104

Tests Conducted

1 Safety Specification for Bunk Beds

Reference standard: ASTM F1427-21^{e1} - Standard Consumer Safety Specification for Bunk Beds.

Number of sample tested: One (1) piece.

Executive summary:

Clause	Testing Items / Requirements	Assessment
1	Scope	
2	Referenced Documents	
3	Terminology	
4	Performance Requirements	
4.1	Vertical Protrusions	
4.1.1	All vertical protrusions along the top inside surfaces of any individual component (including but not limited to bed end structures and guard rails) of the upper bunk shall not extend more than 3/16 in. (4.8 mm) above the upper edge of the adjacent surface. Ladder stiles (uprights) shall not extend more than 3/16 in. (4.8 mm) above the upper edge of the adjacent surface.	P
4.1.2	Any cap used along the top surface of the upper bunk shall not have a vertical protrusion greater than 3/16 in. (4.8 mm) at the edge of the protrusion above the upper edge of the adjacent surface. If the cap is flush with or overhangs the edge of the corner post or other vertical protrusion, the maximum vertical protrusion shall not exceed 3/16 in. (4.8 mm). The cap shall have a maximum height of no more than 20 % of the width or diameter of the cap. At no point shall the cap overhang the post more than 1/16 in. (2 mm). The cap shall fit flush with the top of the corner post.	P
4.2	Fit of Top Bed to Bottom Bed The bed post shall be designed so that the minimum height of lift to allow horizontal disengagement of the top bed from the bottom bed shall be 1 1/4 in. (32 mm), or a fastening mechanism may be used that will prevent the disengagement of the top bed from the bottom bed.	NA




Page 3 of 32



Test Report

Number: SZHH01971104

Tests Conducted

Clause	Testing Items / Requirements	Assessment
4.3	<p>Mattress and Foundation Size and Fit (Top Bed)</p> <p>There shall be no gaps between the interior bed structure and the edges of the mattress and foundation that will permit complete passage of the wedge block when tested in accordance with 5.2.</p> <p>5.2 Mattress and Foundation Size and Fit (see 4.3)—Upper Foundation: 5.2.1 Place the intended mattress and foundation, as specified by the instructions, on the upper foundation support. 5.2.2 Move the mattress and foundation horizontally to obtain the largest gap between the interior bed structure and the edge of the mattress and foundation. 5.2.3 Insert the wedge block shown in Fig. 5, tapered side downwards, and in the most adverse orientation, into any gap and gradually apply a 45 lbf (200 N) vertically downwards force. Sustain the force for a period of 1 min.</p>  <p>FIG. 5 Wedge Block for Tests in Section 5</p>	P



Page 4 of 32



Test Report

Number: SZHH01971104

Tests Conducted

Clause	Testing Items / Requirements	Assessment
4.4	<p>Mattress Size and Fit (Lower Foundation)</p> <p>There shall be no space, between the edge of the manufacturer's recommended mattress and the interior boundary of any component(s) attached to lower bunk (for example, ladders, book shelves, desk), greater than 1.88 in. (48 mm) and smaller than 9 in. (229 mm), when tested in accordance with 5.3.</p> <p>5.3 Mattress Size and Fit (see 4.4)—Lower Foundation: 5.3.1 Place the intended mattress and foundation, as specified by the manufacturer, on the lower mattress support. 5.3.2 For components attached to the side of the lower bed, and for which the mattress height is above the side rail, move the mattress horizontally to obtain the largest gap between the mattress and the interior boundary of any attached component. 5.3.3 Determine if any space between the edge of the manufacturer's recommended mattress and the interior boundary of any attached component is between 1.88 in. (48 mm) and 9 in. (229 mm).</p>	NA
4.5	Upper and Lower Foundation Support Systems	
4.5.1	The foundation support systems shall confine the horizontal position of the mattress and the foundation and shall prohibit the mattress and foundation from falling when the mattress or foundation is manipulated.	P
4.5.2	<p>In the event cross-members are utilized, a minimum of two per bed are required. If more than two cross-members are utilized, they shall be spaced so that the distance between adjacent cross-members or between the cross-members and the bed end structures will not permit complete passage of the wedge block or will allow complete passage of both the wedge block and a 9 in. (229 mm) diameter rigid sphere when tested in accordance with 5.9.</p> <p>5.9 Cross-Member Spacing—Place the wedge block shown in Fig. 5 into any opening tapered side first, and with the 3.5 in. dimension perpendicular to the cross-members. Determine if the wedge block cannot pass freely through the opening. If the wedge block can pass freely through the opening, the 9 in. (229 mm) diameter rigid sphere must pass freely through the opening. This requirement applies to both the upper and lower bunk foundation support systems.</p>	P
4.5.3	The foundation support system shall not be capable of being dislodged without the release of positive fastening devices or the use of hand tools.	P
4.5.4	<p>The foundation support system shall not fail when tested in accordance with 5.4.</p> <p>5.4 Foundation Support System (see 4.5)—Center a sheet of 3/4 in. (19 mm) thick plywood with dimensions 19 in. (483 mm) by 37 in. (940 mm) on the manufacturer's intended foundation (37 in. dimension parallel to the long axis of the bed), and place weights with a total mass of 400 lb (181.4 kg) on the plywood sheet. The weights shall be applied gradually and shall remain in place for a minimum of 5 min.</p>	P
4.6	Side Rails	



Page 5 of 32



Test Report

Number: SZHH01971104

Tests Conducted

Clause	Testing Items / Requirements	Assessment
4.6.1	<i>Bolt-On Side Rails</i> , that attach at their ends or on their side to the bed post, shall be secured at each end by two bolts with a minimum size of 1/4 in. (6.4 mm) diameter or ISO/ANSI size M6. For wood beds, these bolts shall be spaced a minimum of 1 1/2 in. (38 mm) apart on their centers. When the bolts are fully tightened in the assembled bed, no more than 1/4 in. (6.4 mm) of thread shall be exposed.	P
4.6.2	<i>Hook-On Side Rails</i> , securely attached to the bed post. Hook-on attachments shall require an additional action other than an upwards force to disengage.	NA
4.6.3	Side Rail Attachments There shall be no structural failure of bed side rail fastening systems when tested in accordance with 5.5. 5.5 Side Rails (see 4.6)—Apply a downward vertical force of 225 lbf (1000 N) gradually, 10 in. from the bed end structure, and sustain it for 30 s. Apply the force sequentially to each corner of the bed.	P
4.7	Guardrails	
4.7.1	Two guardrails shall accompany any bed in which the underside of the foundation is over 30 in. (762 mm) from the floor. Guardrails may be separate from or integral with the ladder.	P
4.7.2	Guardrails shall be attached in a manner that requires the intentional release of a fastening device or be so designed that they cannot be removed unless forces are applied sequentially in different directions.	P
4.7.3	The upper edge of the guardrails shall be at least 5 in. (127 mm) above the sleeping surface when a mattress of a thickness that is the maximum specified by the manufacturer's instructions is used on the bed.	P
4.7.4	With no mattress on the bed, there shall be no openings in the rigid bed structure below the lower edge of any opening of the guardrail that would permit complete passage of the wedge block when tested in accordance with 5.6. 5.6 Guardrails (see 4.7)—Place the wedge block shown in Fig. 5 into any opening in the rigid bed structure below the level of any opening of the guardrail, tapered side first, and in the most adverse orientation, and gradually apply a 33 lbf (148 N) force in a direction perpendicular to the plane of the opening. Sustain the force for a period of 1 min.	P
4.7.5	A guardrail may terminate before reaching the bed end structure, providing there is no more than 15 in. (381 mm) between either end of the guardrail and the bed end structures in the same plane when measured at a point 5 in. (127 mm) above the sleeping surface as established by the maximum mattress thickness specified by the manufacturer. The second guardrail may terminate before reaching the bed end structure. If this guardrail terminates before reaching the bed end structure, there shall be no more than 0.22 in. (5.6 mm) between either end of the guardrail and the bed end structure when measured horizontally between the bed end structure and the nearest point on the guardrail.	NA
4.8	Bed Structure	



Page 6 of 32



Test Report

Number: SZHH01971104

Tests Conducted

Clause	Testing Items / Requirements	Assessment
4.8.1	The upper edge of the upper bunk end structures for at least 50 % of the distance between the two posts at the head and foot of the upper bunk shall be at least 5 in. (127 mm) above the sleeping surface when a mattress and foundation of the maximum size and thickness specified by the manufacturer's instructional literature is used on the upper bunk.	P
4.8.2	There shall be no openings in the rigid end structures of the upper bunk/bunks that will permit the free passage of the wedge block when tested in accordance with 5.7.1. This requirement shall apply only to those portions of the bed end structure that are above the foundation support system of the upper bunk/bunks. 5.7.1 Place the wedge block shown in Fig. 5 into any opening, tapered side first, and in the most adverse orientation. Determine if the wedge block can pass freely through the opening.	P
4.8.3	When tested in accordance with 5.7.2, there shall be no openings within the entire boundary of the lower bunk that will permit free passage of the wedge block, unless they are large enough to permit the free passage of a 9 in. (229 mm) diameter rigid sphere. This requirement does not apply to openings that are below the level of the lower bunk foundation support system. This requirement shall apply to that portion of the bed structure that is between the level of the lower bunk foundation support system and the level of the upper bunk foundation support system. Such openings include, but are not limited to, bed end structures, foundation, ladders, desks, or bookshelf components, or a combination thereof, as offered with the bed for purchase and designed to be attached to the bed structure. 5.7.2 Lower Bunk Boundaries (see 4.8.3): 5.7.2.1 Without a mattress or foundation on the lower bunk foundation support, place the wedge block shown in Fig. 5 into any opening, tapered side first, in the most adverse orientation. Determine if the wedge block can pass freely through the opening. If the wedge block passes freely through the opening, determine if a 9 in. (229 mm) diameter rigid sphere can pass freely through the opening. 5.7.2.2 With the manufacturer's recommended mattress and foundation size in place, on the lower bunk foundation support, repeat the test in 5.7.2.1.	NA



Page 7 of 32



Test Report

Number: SZHH01971104

Tests Conducted

Clause	Testing Items / Requirements	Assessment
4.8.4	<p>When tested in accordance with 5.7.2.3 and 5.7.2.4, all portions of the boundary of any opening of the entire lower bunk boundary that permits free passage of a 9 in. (229 mm) diameter rigid sphere also must conform to the neck entrapment requirement.</p> <p>5.7.2.3 Insert the A section of the test template shown in Fig. 6 into the portion of the boundary of the opening to be tested, with the plane of the template in the plane of the opening and with the centerline of the top of the template aligned parallel to the centerline of the opening, until motion is stopped by contact between the test template and the boundaries of the opening (see Fig. 7). By visual inspection, determine if there is simultaneous contact between the boundary of the opening and both sides of the A section of the template. If simultaneous contact occurs, mark the contact points on the boundary of the opening and conduct the additional test described in 5.7.2.4.</p> <p>5.7.2.4 Place the neck portion of the B section of the template into the opening, with its plane perpendicular to both the plane of the opening and the centerline of the opening (see Fig. 8). If the neck portion of the B section of the template completely enters the opening (passes 0.75 in. (19 mm) or more beyond the points previously contacted by the A section of the template), the opening fails the test, unless its lower boundary slopes downward at 45° or more for the whole distance from the narrowest part of the opening the neck can reach to the part of the opening that will freely pass a 9 in. (229 mm) diameter sphere.</p>	NA
4.9	Ladders	
4.9.1	A lean-on (slanted) or hang-on (vertical) ladder shall be supplied with each bunk bed set or the ladder may be incorporated as part of the bed structure. The ladder may be separate from or integral with the guardrail. The ladder shall be attached in a manner that prevents inadvertent disengagement, repositioning, or tilting while in use.	P
4.9.2	There shall be no openings between ladder structures that allow complete passage of the wedge block, unless they are large enough to permit the free passage of the 9 in. (229 mm) diameter rigid sphere. The width of the ladder shall be no less than 10 in. (254 mm) measured from the inside of the stiles. Vertical spacing of ladder steps shall be no greater than 12 in. (305 mm) when measured from the floor to the first step or between steps. When bed structures are used as ladders, vertical spacing may be up to 16 in. (407 mm).	P
4.9.3	There shall be no openings between the ladder step and the upper bunk boundary that allow complete passage of the wedge block, unless they are large enough to permit the free passage of the 9 in. (229 mm) diameter rigid sphere.	P



Page 8 of 32



Test Report

Number: SZHH01971104

Tests Conducted

Clause	Testing Items / Requirements	Assessment
4.9.4	<p>For ladders attached to the side of the lower bed and for which mattress height is above the side rail, there shall be no gaps between the edge of the manufacturers recommended mattress and the interior vertical stile between 1.88 in. (48 mm) and 9 in. (229 mm) when tested in accordance with 5.3.</p> <p>5.3 Mattress Size and Fit (see 4.4)—Lower Foundation: 5.3.1 Place the intended mattress and foundation, as specified by the manufacturer, on the lower mattress support. 5.3.2 For components attached to the side of the lower bed, and for which the mattress height is above the side rail, move the mattress horizontally to obtain the largest gap between the mattress and the interior boundary of any attached component. 5.3.3 Determine if any space between the edge of the manufacturer's recommended mattress and the interior boundary of any attached component is between 1.88 in. (48 mm) and 9 in. (229 mm).</p>	NA
4.10	<p>Metal Beds: Frame and Fastenings</p> <p>There shall be no separation of any of the attachments of the foundation support system to the end structures of the bed when tested in accordance with 5.8.1.1 and 5.8.2.</p> <p>5.8 Metal Beds—Frame and Fastenings: 5.8.1 For testing in accordance with 5.8.1.1, the bed shall be prevented from sliding in a manner that does not prevent changes of angle that may take place in the bed structure. 5.8.1.1 Position a test load of 165 lb (75.0 kg) at the center of the upper foundation support system on an area not to exceed 12 in. (305 mm) square (if foundation support systems will not permit the test load to be so positioned, it is permissible to add a platform to support the test load in such a way as to not increase the structural integrity of the bed). Apply an alternate force of 67 lbf (298 N) for 10 000 cycles at each point in the order ABCD or AB followed by CD at a rate not more than 24 loads per minute (see Fig. 9). The points for applying the test forces shall be located as near the center of the vertical bunk bed support as practicable at the height of the upper foundation support system. 5.8.2 After testing in accordance with 5.8.1.1, remove the 165 lb (75.0 kg) load and apply a 67 lbf (298 N) force in directions most likely to cause separation between the end structure and foundation support system. The force shall be applied at each point of attachment of the foundation support system to the end structure (point of applications shall be as close as practical to the point of attachment). The force shall be applied to either the end structure or foundation support system, whichever appears most likely to cause separation.</p>	P



Page 9 of 32



Test Report

Number: SZHH01971104

Tests Conducted

Clause	Testing Items / Requirements	Assessment
5	Test Methods	
6	Marking and Labeling	P (See remark 1)
7	Instructional Literature	P

Abbreviation: P = Pass; F = Fail; NA = Not Applicable

Remark:

- No finalized packaging was provided, hence the warning on the carton required in clause 6.2.3 were not assessed in this report.
- 16 CFR Part 1513-Requirements for Bunk Beds Intended for Use by Children/16 CFR Part 1213-Requirements for Bunk Beds Not Intended for Use by Children

With reference to 16 CFR Part 1513 - Requirements for Bunk Beds & 16 CFR Part 1213 - Safety Standard for Entrapment Hazards in Bunk Beds.

Executive summary:

Clause	Requirements	Assessment
1513.3(a)/1213.3(a)	Guardrails	
(1)	Any bunk bed shall provide at least two guardrails, at least one on each side of the bed, for each bed having the underside of its foundation more than 30 inches (760 mm) from the floor.	P
(2)	One guardrail shall be continuous between each of the bed's end structures. "Continuous" means that any gap between the guardrail and end structure shall not exceed 0.22 inches (5.6 mm) (so as to not cause a finger entrapment hazard for a child).	P
(3)	The other guardrail may terminate before reaching the bed's end structures, providing there is no more than 15 inches (380 mm) between either end of the guardrail and the nearest bed end structures.	NA
(4)	For bunk beds designed to have a ladder attached to one side of the bed, the continuous guardrail shall be on the other side of the bed.	NA
(5)	Guardrails shall be attached so that they cannot be removed without either intentionally releasing a fastening device or applying forces sequentially in different directions.	P
(6)	The upper edge of the guardrails shall be no less than 5 inches (130 mm) above the top surface of the mattress when a mattress of the maximum thickness specified by the bed manufacturer's instructions is on the bed. This requirement does not prohibit a wall-side guardrail that terminates in a quarter-circle bend and attaches to the side rail of the upper bunk foundation.	P
(7)	With no mattress on the bed, there shall be no openings in the structure between the lower edge of the uppermost member of the guardrail and the underside of the upper bunk's foundation that would permit passage of the wedge block shown in Figure 1 of this part when tested in accordance with the procedure at §1513.4(a)/1213.4(a).	P
1513.3(b)/1213.3(b)	Bed end structures	



Page 10 of 32



Test Report

Number: SZHH01971104

Tests Conducted

Clause	Requirements	Assessment
(1)	The upper edge of the upper bunk end structures shall be at least 5 inches (130 mm) above the top surface of the mattress for at least 50 percent of the distance between the two posts at the head and foot of the upper bunk when a mattress and foundation of the maximum thickness specified by the manufacturer's instructions is on the bed.	P
(2)	With no mattress on the bed, there shall be no openings in the end structures above the foundation of the upper bunk that will permit the free passage of the wedge block shown in Figure 1 when tested in accordance with the procedure at §1513.4(b)/1213.4(b).	P
(3)	When tested in accordance with §1513.4(c)/1213.4(c), there shall be no openings in the end structures between the underside of the foundation of the upper bunk and upper side of the foundation of the lower bunk that will permit the free passage of the wedge block shown in Figure 1, unless the openings are also large enough to permit the free passage of a 9-inch (230-mm) diameter rigid sphere.	NA
(4)	All portions of the boundary of any opening required by §1513.4(c)(1) and (2)/1213.4(c)(1) and (2) to be probed by the wedge block of Figure 1, and that permits free passage of a 9-inch diameter sphere, must conform to the neck entrapment requirements of §1513.4(c)(3)/1213.4(c)(3).	NA
1513.5/1213.5	Marking and labeling	P
1513.6/1213.6	Instructions	P

Abbreviation: P = Pass; NA = Not Applicable

3 Tracking Label Assessment

As per consumer product safety Act section 14(a) (5), 15 U.S.C. §2063(a)(5) (CPSA) and Consumer Product Safety Improvement Act (CPSIA) 2008 Section 103 Tracking Labels for Children Products.

Tracking label found on the product:



Test Report

Number: SZHH01971104

Tests Conducted

Name of manufacturer/Distributor/©/®	GIGACLOUD TECHNOLOGY(USA)INC.
Location of production	Zhangzhou, China
Date code	09/2024

Note: The tracking label assessment was based on the submitted sample and the information provided by the applicant. There was no verification on the validity of such information.

Remark: As requested by the applicant, the tracking label information on the packaging was not assessed.

4 **Physical and Mechanical Test**

Test requirement: U.S. Code of Federal Regulations Title 16 Part 1500.50, the hazards of sharp points, sharp edge and small parts are assessed both before and after applicable use and abuse tests.

	No. of Sample Tested	Sharp Point (1500.48)	Sharp Edge (1500.49)	Small Part (1501)
As received	1	P	P	NA
Impact (1500.53(b))	1	P	P	NA
Flexure (1500.53(d))	0	NA	NA	NA
Torque (1500.53(e))	1	P	P	NA
Tension (1500.53(f))	1	P	P	NA
Compression (1500.53(g))	1	P	P	NA

Abbreviation: P = Pass F = Fail NA= Not Applicable NR=Not Requested

5 **Flammability Test**

Test requirement: U.S. Code of Federal Regulations Title 16 Part 1500.44 for rigid and pliable solids.

Result: Did not ignite

6 **Total Lead (Pb) Content in Surface Coating (U.S. 16 CFR Part 1303 and CPSIA Section 101)**

As per Standard Operating Procedure for Determining Lead (Pb) in paint and other similar surface coatings, test method CPSC-CH-E1003-09.1 was used and total Lead content was determined by Inductively Coupled Plasma - Optical Emission Spectrometry.



Page 12 of 32



Test Report

Number: SZHH01971104

Tests Conducted

Element	Result (ppm)		Reporting Limit (ppm)	Limit (ppm)
	Tested Component			
	(1+6)	(8+9)		
Lead (Pb)	ND	17	10	90

The above limit was quoted according to U.S. CFR Title 16 Part 1303 and U.S. Consumer Product Safety Improvement Act 2008 Title I, Section 101 for total Lead content in surface coating.

ppm = parts per million = mg/kg

ND = Not detected (less than reporting limit)

Tested components: See component list in the last section of this report

7 Total Lead (Pb) Content in Non-Surface Coating Materials (Substrate) (U.S. CPSIA Section 101)

As per Standard Operating Procedures for Determining total Lead (Pb) in children's products, test methods CPSC-CH-E1002-08.3 and/or CPSC-CH-E1001-08.3 were used and total Lead content was determined by Inductively Coupled Plasma - Optical Emission Spectrometry and/or Atomic Absorption Spectrometry.

Element	Result (ppm) θ	Reporting Limit (ppm)	Limit (ppm)
	Tested Component		
	(2+3) (4) (5+7)		
Lead (Pb)	ND	10	100

Element	Result (ppm)	Reporting Limit (ppm)	Limit (ppm)
	Tested Component		
	(10+11)		
Lead (Pb)	20	10	100

The above limit was quoted according to U.S. Consumer Product Safety Improvement Act 2008 Title I, Section 101 for total Lead content in Non-surface coating materials.

ppm = parts per million = mg/kg

ND = Not detected (less than reporting limit)

θ = Single result for each test component/group

Tested components: See component list in the last section of this report



Page 13 of 32




Test Report

Number: SZHH01971104

Tests Conducted

Component list:

- (1) Black coating on metal (surface of mesh & sheet & rectangle tube & round tube)
- (2) Silver color metal excluding black coating (mesh & sheet & rectangle tube & round tube)
- (3) Black treated metal (screw)
- (4) Silver color solder excluding black coating (joint of frame)
- (5) Black plastic (stopper & pad of frame)
- (6) Black coating on paper (label of frame)
- (7) White paper label excluding black coating (label of frame)
- (8) Black coating on fiberboard (surface of board)
- (9) Black coating on plastic (surface of edge of board)
- (10) Brown fiberboard excluding black coating (board)
- (11) Black plastic excluding black coating (edge of board)



Page 14 of 32



Test Report

Number: SZHH01971104

Tests Conducted




Page 15 of 32



Test Report

Number: SZHH01971104

Tests Conducted



1



Page 16 of 32



Test Report

Number: SZHH01971104

Tests Conducted

SAFETY WARNINGS AND GENERAL NOTES

1. Follow the information on the warnings appearing on the upper bunk bed end structure and on the carton. Do not remove the warning label from the bed.
2. Always use the recommended size mattress or mattress support, or both, to help prevent the likelihood of entrapment or falls.
3. Do not allow children under 6 years of age to use the upper bunk.
4. Periodically check and ensure the guardrail, ladder and other components are in their proper position, free from damage, and all connectors are tight.
5. Do not allow horseplay on or under beds.
6. Always prohibit jumping on the bed.
7. Prohibit more than one person on upper bunk.
8. Always use the ladder for entering and leaving the upper bunk.
9. Do not use substitute parts. Contact the manufacturer or dealer for replacement parts.
10. Use of a night light may provide added safety precaution for a child using the upper bunk.
11. Always use guardrails on both long sides of the upper bunk.
12. If the bunk bed will be placed next to a wall, the guardrail that runs the full length of the bed should be placed against the wall to prevent entrapment between the bed and the wall. The use of water or sleep flotation mattresses is prohibited.
13. STRANGULATION HAZARD- Never attach or hang items to any part of the bunk bed that are not designed for use with the bed, for example, but not limited to, hooks, belts and jump ropes.
14. Keep these instructions for future reference.
15. We recommend assembling your bunk bed on the shipping carton to protect your floor or carpet.
16. Be certain all staples are out of the box before beginning assembly on the shipping carton.
17. USE ONLY MATTRESSES WHICH ARE AS THE TABLE BELOW ON UPPER BUNKS.

Upper bed (bunk bed and tribed included)

Bed type	Length	Width	Thickness
Full Standard	74" – 75"	53-1/2"	6" max

18. SURFACE OF MATTRESS MUST BE AT LEAST 5" (127MM) BELOW THE UPPER EDGE OF GUARDRAILS.

19. Replacement Parts:

Replacement Parts, including additional guardrails, may be obtained from any of our (GIGACLOUD TECHNOLOGY (USA) INC.) dealers



Test Report

Number: SZHH01971104

Tests Conducted

AVERTISSEMENTS DE SÉCURITÉ ET REMARQUES GÉNÉRALES


1. Suivez les informations figurant sur les avertissements figurant sur la structure d'extrémité du lit superposé supérieur et sur le carton. Ne retirez pas l'étiquette d'avertissement du lit.
 2. Utilisez toujours le matelas ou le support de matelas de taille recommandée, ou les deux, pour éviter tout risque de coincement ou de chute.
 3. Ne laissez pas les enfants de moins de 6 ans utiliser le lit supérieur.
 4. Vérifiez périodiquement et assurez-vous que le garde-corps, l'échelle et les autres composants sont dans leur bonne position, exempts de dommages et que tous les connecteurs sont bien serrés.
 5. Ne laissez pas les chahuts sur ou sous les lits.
 6. Interdisez toujours de sauter sur le lit.
 7. Interdire plus d'une personne sur la couchette supérieure.
 8. Utilisez toujours l'échelle pour entrer et sortir du lit supérieur.
 9. N'utilisez pas de pièces de rechange. Contactez le fabricant ou le revendeur pour obtenir des pièces de rechange.
 10. L'utilisation d'une veilleuse peut fournir une mesure de sécurité supplémentaire pour un enfant utilisant le lit supérieur.
 11. Utilisez toujours des garde-corps sur les deux côtés longs du lit supérieur.
 12. Si le lit superposé doit être placé à côté d'un mur, le garde-corps qui s'étend sur toute la longueur du lit doit être placé contre le mur pour éviter tout coincement entre le lit et le mur. L'utilisation de matelas flottants à eau ou de sommeil est interdite.
 13. RISQUE D'ÉTRANGULATION - N'attachez ou ne suspendez jamais d'objets à une partie du lit superposé qui ne sont pas conçu pour être utilisés avec le lit, par exemple, mais sans s'y limiter, des crochets, des ceintures et des cordes à sauter.
 14. Conservez ces instructions pour référence future.
 15. Nous vous recommandons d'assembler votre lit superposé sur le carton d'expédition pour protéger votre sol ou votre tapis.
 16. Assurez-vous que toutes les agrafes sont sorties de la boîte avant de commencer l'assemblage sur le carton d'expédition.
 17. UTILISER UNIQUEMENT DES MATELAS QUI SONT COMME DANS LE TABLEAU CI-DESSOUS SUR LES SUPERPOSÉS.
- | <u>Lit supérieur (lits superposés et triblés inclus)</u> | | | |
|--|-----------|---------|-----------|
| Type de lit | Longueur | Largeur | Épaisseur |
| Double Standard | 74" – 75" | 38 1/2" | 6" max |
18. LA SURFACE DU MATELAS DOIT ÊTRE AU MOINS 5" (127 MM) EN DESSOUS DU BORD SUPÉRIEUR DES GARDE-CORPS.
 19. Pièces de rechange :
Les pièces de rechange, y compris les garde-corps supplémentaires, peuvent être obtenues auprès de l'un de nos revendeurs (GIGACLOUD TECHNOLOGY (USA) INC.)



Test Report

Number: SZHH01971104













Tests Conducted



Test Report

Number: SZHH01971104

Tests Conducted
















Part List/Liste des pièces (N709P224891)	
<p>1</p>  <p>1pc</p>	<p>2</p>  <p>1pc</p>
<p>3</p>  <p>1pc</p>	<p>4</p>  <p>1pc</p>
<p>5</p>  <p>2pcs</p>	<p>6</p>  <p>1pc</p>
<p>7</p>  <p>1pc</p>	<p>8</p>  <p>4pcs</p>
<p>9</p>  <p>16pcs</p>	<p>10</p>  <p>6pcs</p>
<p>11</p>  <p>1pc</p>	<p>12</p>  <p>5pcs</p>

5

Test Report

Number: SZHH01971104















Tests Conducted

Part List/Liste des pièces (N709P224892)		
13  2pcs	14  1pc	15  1pc
16  2pcs	17  2pcs	18  4pcs
19  3pcs	20  3pcs	21  3pcs
22  1pc	23  1pc	24  1pc
25  1pc	26  3pcs	27  2pcs

Test Report

Number: SZHH01971104

Tests Conducted

Hardware List / Liste du matériel (N709P224891)		
A  M6X20mm 12pcs	B  M6X30mm 27pcs	C  M6X40mm 30pcs
D  M6X40mm 8pcs	E  M6X50mm 14pcs	F  M6X60mm 27 pcs
G  M6X17mm 12pcs	H  M6X40mm 3pcs	I  M4 2pcs
J  M4*14mm 2pcs	K  M4*30mm 2pcs	L  ø6 2pcs
M  4pcs	N  2pcs	


7



Test Report

Number: SZHH01971104


Tests Conducted



Test Report

Number: SZHH01971104

Tests Conducted




9

Test Report

Number: SZHH01971104

Tests Conducted




10

Test Report

Number: SZHH01971104

Tests Conducted




11

Test Report

Number: SZHH01971104


Tests Conducted



Test Report

Number: SZHH01971104


Tests Conducted



Test Report

Number: SZHH01971104


Tests Conducted



Test Report

Number: SZHH01971104


Tests Conducted



Test Report

Number: SZHH01971104

Tests Conducted



16

End of report

Page 31 of 32



Test Report

Number: SZHH01971104

Tests Conducted

The statements of conformity reported have considered the decision rule agreed, namely that Intertek have taken account of measurement uncertainty as calculated by Intertek, and applied according to ILAC-G8/09:2019-(Non-binary acceptance based on guard band $w = U$) except designation from the customer, regulation or test specification. This decision rule only applies to the numeric test results. Full details of our agreed decision rules and the associated risk can be viewed: <https://www.intertek.com.cn/diypage/upload/SZ-AP15-HLS-QA.pdf>.

The sample(s) and sample information hereto are provided by the client who shall be solely responsible for the authenticity and integrity thereof. The results shown in this report relate only to the sample(s) received and tested. It is not intended to be a recommendation for any particular course of action. Intertek does not accept a duty of care or any other responsibility to any person other than the Client in respect of this report and only accepts liability to the Client insofar as is expressly contained in the terms and conditions governing Intertek's provision of services to you. Intertek makes no warranties or representations either express or implied with respect to this report save as provided for in those terms and conditions. We have aimed to conduct the review on a diligent and careful basis and we do not accept any liability to you for any loss arising out of or in connection with this report, in contract, tort, by statute or otherwise, except in the event of our gross negligence or wilful misconduct. This report shall not be reproduced unless with prior written approval from Intertek.



Page 32 of 32

Intertek Testing Services Shenzhen Ltd. Xiamen Branch
深圳天祥质量技术服务有限公司厦门分公司

Unit 1E, 1st floor, Unit 2C, 2nd floor, Unit 4C
、4D、4L、4O, 4th floor, Xinglian
Building, No.2, Chuangxin RD, Huoju Hi-
tech District, Xiamen, Fujian, P.R.C
福建省厦门市湖里区火炬高新区创新路2
号兴联电子大厦一楼1E区, 二楼2C和四楼
4C、4D、4L、4O

Tel: +86592 8063339
Fax: +86592 8060054
www.intertek.com
www.intertek.com.cn

