







Test Report No.: AJFS2303001801FF Date: MAR.27, 2023 Page 1 of 3

ANJI HESHUN SPONGE PRODUCTS CO., LTD.

ANJI COUNTY XIAOFENG TOWN BAMBOO INDUSTRIAL DISTRICT

Sample Description: SPONGE

<u>Color</u>: GRAY <u>Style/Item No.</u>: /

The above sample(s) was / were submitted and identified on behalf of the client. SGS is not responsible for the authenticity, integrity and results of the data and information and / or the validity of the conclusion arising therefrom. Results apply to the sample as received.

Test Requested:

State of California, Department of Consumer Affairs, Bureau Household Goods and Services, Technical Bulletin 117-2013(R2019), Requirement, Test Procedure and Apparatus for Testing the Smolder Resistance of Materials Used in Upholstered Furniture, Section 3 Resilient Filling Material Test.

Test Results: -- See attached sheet -

<u>Conclusion</u>: The tested sample **meets** the Requirements of Section 3 for Resilient Filling Material Test of California Technical Bulletin 117-2013(R2019).

Test Period:

Sample Receiving Date : MAR.21, 2023

Test Performing Date : MAR.21, 2023 TO MAR.24, 2023

Signed for and on behalf of

SGS-CSTC Standards Technical Services Co., Ltd. Anji Branch

Echo Li

Approved Signatory







Test Report No.: AJFS2303001801FF Date: MAR.27, 2023 Page 2 of 3

I. Test Conducted

The test was conducted in accordance with California Technical Bulletin 117-2013(R2019) Testing the Smolder Resistance of Materials Used in Upholstered Furniture, Section 3: Resilient Filling Material Test.

II. Test Specimen

Description	Foam	
Color	Grey	
Density	28.4 kg/m³	
Size of specimen	203 mm × 127 mm × 51mm & 203 mm × 203 mm × 51 mm	

Conditioning

Prior to testing, the specimens were conditioned for a minimum of 24 hours, at $70 \pm 5^{\circ}F$ (21°C \pm 3°C) and less than 55% relative humidity.

III. Test Result

Specimen No.	Duration of smoldering (min:sec)	Open flaming (Yes/No)	Vertical char length (mm)	Comment
1	33min48s	No	17	Pass
2	35min12s	No	16	Pass
3	34min39s	No	16	Pass

Pass / Fail Criteria:

- 1. A single mock-up test specimen fails the requirements of this test procedure if any of the following criteria occurs:
 - a) The mock-up test specimen continues to smolder after the 45 minute test duration;
 - b) A vertical char length (measured as described in step 17.9 of ASTM E1353-08a ε1) of more than 1.5 inches (38 mm) develops on the cover fabric.
 - c) The mock-up test specimen transitions to open flaming.
- 2. The resilient filling material passes the test if three mock-up specimens pass the test.
- 3. If more than one specimen fails, the resilient filling material fails the test.
- 4. If any one of the three initial specimens fails, repeat the test on additional three specimens.
- 5. If all three additional specimens pass the test, the resilient filling material passes the test. If any one of the additional three specimens fails, the resilient filling material fails the test.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printec overleaf, available on request or accessible at http://www.sps.com/en/fems-and-Conditions.apx and, for electronic Pormat documents subject to Terms and Conditions for Electronic Documents at http://www.sps.com/en/Terms-and-Conditions/Terms-e-Document.aspx Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of client's instructions, if any. The Company's sole responsibility is to its Client and his document does not excerted parties to a except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content o appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the xu. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only. Attention:To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 830



Test Report No.: AJFS2303001801FF Date: MAR.27, 2023 Page 3 of 3

Statement:

This declaration of conformity is only based on the result of this laboratory activity, the impact of the uncertainty of the results was not included.

The specimen was supplied by the sponsor and SGS-CSTC ANJI Branch was not involved in any selection or sampling procedure.

Photo Appendix:



SGS authenticate the photo on original report only

End of Report

