Lecture 9

Lecturer: Assoc. Prof. M. Mert Ankarali

9.1 Externall Input-Output Stability

9.1.1 Signal Norms

A continuous time bilateral signal is a mapping defined by $f : \mathbb{R} \mapsto \mathbb{R}^n$ (or for unilateral case $f : \mathbb{R}^{\geq 0} \mapsto \mathbb{R}^n$), whereas discrete time bilateral signal is a mapping defined by $g : \mathbb{Z} \mapsto \mathbb{R}$ (or for unilateral case $g : \mathbb{Z}^{\geq 0} \mapsto \mathbb{R}$). Graphical Examples


Figure 9.1: CT vs DT Signal

∞-norm

In the chacarterization and analysis of input-output stability of linear dynamical systems, most commonly used norm concept is the ∞-norm which is technically e measure of peak magnitude over time. For scalar signals ∞-norm is defined as

$$||f||_\infty \triangleq \sup_k |f(k)| \quad \text{(DT)}$$
$$\triangleq \sup_t |f(t)| \quad \text{(CT)}$$

The "sup" denotes the *supremum* or *least upper bound*, the value that is approached arbitrarily closely but never (i.e., at any finite time) exceeded. Note that this is the natural standard ∞-norm definition for finite-dimensional vectors to the infinite dimensional case, i.e. DT and CtT signals. Let's remember the ∞-norm of an n-dimensional vector,

$$||v||_\infty \triangleq \max_{i \in [1,n]} |v_i| \ , \text{ where } v \in \mathbb{R}^n,$$

A scalar signal, $f(.)$ is called *bounded* if $||f||_\infty = M < \infty$ and that is the fundamental signal measure adopted in BIBO stability.

For multi-variate signals, we add a ned "dimension" in addition to the time dimension, thus in such a case we define ∞-norm as

$$||f||_\infty \triangleq \sup_k ||f(k)||_\infty \quad \text{(DT)}$$

$$\triangleq \sup_t ||f(t)||_\infty \quad \text{(CT)}$$

The space of all signals with finite ∞-norm are generally denoted by ℓ_∞ and $\mathcal{L}_\infty$ for DT and CT signals respectively. For multi-variate case, the dimension of the vector may be explicitly added as ℓ_∞^n and $\mathcal{L}_\infty^n$.

∞-norms of some example CT and DT uni-lateral signals (i.e. $t \geq 0$ and $k \geq 0$)

$$
\begin{aligned}
f(t) = 1\,,\ ||f||_\infty = 1 \quad &- \quad g[k] = 1\,,\ ||g||_\infty = 1 \\
f(t) = t\,,\ ||f||_\infty = \infty \quad &- \quad g[k] = k\,,\ ||g||_\infty = \infty \\
f(t) = e^t\,,\ ||f||_\infty = \infty \quad &- \quad g[k] = 2^k\,,\ ||g||_\infty = \infty \\
f(t) = 1 - e^{-t}\,,\ ||f||_\infty = 1 \quad &- \quad g[k] = 1 - 0.5^k\,,\ ||g||_\infty = 1 \\
f(t) = \delta(t)\,,\ ||f||_\infty = \infty \quad &- \quad g[k] = \delta[k]\,,\ ||g||_\infty = 1
\end{aligned}
$$

2-norm

2-norm of a signal is the most fundamental measure of signal in optimal control theory and it can be considered as the square root of the "energy" of the signal. For scalar signals 2-norm is defined as

$$||f||_2 \triangleq \left[\sum_k (f[k])^2 \right]^{\frac{1}{2}} \quad \text{(DT)}$$

$$\triangleq \left[\int (f(t))^2 dt \right]^{\frac{1}{2}} \quad \text{(CT)}$$

The space of all signals with finite 2-norm are generally denoted by ℓ_2 and $\mathcal{L}_2$ for DT and CT signals respectively. For multivariate signals, we adopt the inner product and obtain

$$||f||_2 \triangleq \left[\sum_k (f[k])^T f[k] \right]^{\frac{1}{2}} = \left[\sum_k ||f[k]||_2^2 \right]^{\frac{1}{2}} \quad \text{(DT)}$$

$$\triangleq \left[\int (f(t))^T f(t) dt \right]^{\frac{1}{2}} = \left[\int ||f(t)||_2^2 \right]^{\frac{1}{2}} \quad \text{(CT)}$$

2-norms of some example CT and DT uni-lateral signals (i.e. $t \geq 0$ and $k \geq 0$)

$$
\begin{aligned}
f(t) = 1\,,\ ||f||_2 = \infty \quad &- \quad g[k] = 1\,,\ ||g||_2 = \infty \\
f(t) = t\,,\ ||f||_2 = \infty \quad &- \quad g[k] = k\,,\ ||g||_2 = \infty \\
f(t) = e^t\,,\ ||f||_2 = \infty \quad &- \quad g[k] = 2^k\,,\ ||g||_2 = \infty \\
f(t) = e^{-t}\,,\ ||f||_2 = 1/\sqrt{2} \quad &- \quad g[k] = 0.5^k\,,\ ||g||_2 = 2/\sqrt{3} \\
f(t) = \delta(t)\,,\ ||f||_2 = 1 \quad &- \quad g[k] = \delta[k]\,,\ ||g||_2 = 1
\end{aligned}
$$

1-norm

1-norm of a signal is refered as the "action" of the signal and for scalar signals 1-norm is defined as

$$||f||_1 \triangleq \left[\sum_k |f[k]| \right] \quad \text{(DT)}$$

$$\triangleq \left[\int |f(t)| dt \right] \quad \text{(CT)}$$

The space of all signals with finite 1-norm are generally denoted by ℓ_1 and $\mathcal{L}_1$ for DT and CT signals respectively. In order to generalize the 1-norm for multi-variate signals, we adopt the 1-norm definition of the vectors

$$||f||_1 \triangleq \left[\sum_k ||f[k]||_1 \right] \quad \text{(DT)}$$

$$\triangleq \left[\int ||f(t)||_1 dt \right] = \quad \text{(CT)}$$

$$||v||_1 \triangleq \sum_{i=1}^n |v_i| \ , \ \text{where } v \in \mathbb{R}^n,$$

1-norms of some example CT and DT uni-lateral signals (i.e. $t \geq 0$ and $k \geq 0$)

$$
\begin{array}{lcl}
f(t) = 1 \, , \, ||f||_1 = \infty & - & g[k] = 1 \, , \, ||g||_1 = \infty \\
f(t) = t \, , \, ||f||_1 = \infty & - & g[k] = k \, , \, ||g||_1 = \infty \\
f(t) = e^t \, , \, ||f||_1 = \infty & - & g[k] = 2^k \, , \, ||g||_1 = \infty \\
f(t) = e^{-t} \, , \, ||f||_1 = 1 & - & g[k] = 0.5^k \, , \, ||g||_1 = 2 \\
f(t) = \delta(t) \, , \, ||f||_1 = 1 & - & g[k] = \delta[k] \, , \, ||g||_1 = 1
\end{array}
$$

p-norm

p-norm is technically generalization of the previous norms define in the Lecture Notes. Let $p > 0$, p-norm for vector valued signals are defined as

$$||f||_p \triangleq \left[\sum_k ||f[k]||_p^p \right]^{1/p} \quad \text{(DT)}$$

$$\triangleq \left[\int ||f(t)||_p^p dt \right]^{1/p} = \quad \text{(CT)}$$

$$||v||_p \triangleq \left[\sum_{i=1}^n |v_i|^p \right]^{1/p} \ , \ \text{where } v \in \mathbb{R}^n,$$

9.1.2   Input-Output Stability

The most important notion of input-output stability in the analysis of dynamical systems is termed ℓ_p (or $\mathcal{L}_p$) stability or p-stability.

Definition: A system with input signal, u, and output signal, y, is ℓ_p stable (or p-stable) if $\exists M \in \mathbb{R}$ such that

$$||y||_p \leq M||u||_p \, , \forall u \in \ell_p \, (\text{or } \mathcal{L}_p)$$

In other words a p-stable system is characterized by the requirement that for every input, u, with finite p-norm, p-norm of the output has also has to be finite.

BIBO Stability & ∞-stability for LTI Systems

If we directly follow the definition of ℓ_p stability or p-stability and signal norm definitions, we can see that BIBO stability definition is indeed a special case of p-stability where $p = \infty$. Lets first remember BIBO stability or ∞-stability for SISO LTI systems.

Theorem: Let, S_h, be a CT-LTI SISO system where $h(t)$ is its impulse response, i.e.

$$y(t) = h(t) * u(t) = \int_{-\infty}^{\infty} h(t - \tau)u(\tau)d\tau = \int_{-\infty}^{\infty} h(\tau)u(t - \tau)d\tau$$

S_h is BIBO stable (or ∞-stable) if and only if $\exists M < \infty$ such that

$$||h||_1 = \int_{-\infty}^{\infty} |h(t)|dt = M$$

Proof: *Sufficiency* - Let $||h||_1 = M < \infty$ and $||u||_\infty = C < \infty$

$$y(t) = \int_{-\infty}^{\infty} h(\tau)u(t - \tau)d\tau$$

$$|y(t)| = \left| \int_{-\infty}^{\infty} h(\tau)u(t - \tau)d\tau \right| \leq \int_{-\infty}^{\infty} |h(\tau)u(t - \tau)|d\tau \leq \int_{-\infty}^{\infty} |h(\tau)||u(t - \tau)|d\tau \leq \left[\int_{-\infty}^{\infty} |h(\tau)|d\tau \right] ||u||_\infty \, , \forall t$$

$$||y||_\infty \leq ||h||_1 ||u||_\infty \leq MC < \infty$$

Neccesity - Let $||h||_1 = \infty$, and for any t we can choose $u(t - \tau) = \text{sign}(h(\tau)$, then

$$y(t) = \int_{-\infty}^{\infty} h(\tau)u(t - \tau)d\tau = \int_{-\infty}^{\infty} h(\tau)\text{sign}(h(\tau)d\tau = \int_{-\infty}^{\infty} |h(\tau)|d\tau = \infty$$

Thus a SISO CT-LTI system is BIBO stable (or ∞-stable) $\iff ||h||_1 = \int_{-\infty}^{\infty} |h(t)|dt < \infty$. Furthermore,

the least upper bound of the infinity norm of the output given that $||u||_\infty$ simply given by

$$\sup_{||u||_\infty=1} ||y||_\infty = ||h||_1 = \int_{-\infty}^{\infty} |h(t)|dt$$

and this constant is is called the $\mathcal{L}_1$-norm (or $\mathcal{L}_{\infty-\text{ind}}$-norm) of the system and showed as

$$||S_h||_1 = \sup_{||u||_\infty=1} ||y||_\infty$$

Theorem: Let, S_g, be a DT-LTI SISO system where $g[k]$ is its impulse response, i.e.

$$y[k] = g[k] * u[k] = \sum_{n=-\infty}^{\infty} g[k-n]u[n] = \sum_{n=-\infty}^{\infty} g[n]u[k-n]$$

S_g is BIBO stable (or ∞-stable) if and only if $\exists M < \infty$ such that

$$||g||_1 = \sum_{n=-\infty}^{\infty} |g[n]| = M$$

Proof: Steps of the proof is very similar to the CT case.

Now let's generalize the BIBO stability for MIMO systems.

Theorem: Let, $S_{\mathcal{H}}$, be a CT-LTI MIMO system where $\mathcal{H}(t)$ is its impulse response matrix with m inputs and p outputs, i.e.

$$y(t) = \mathcal{H}(t) * u(t) = \int_{-\infty}^{\infty} \mathcal{H}(t-\tau)u(\tau)d\tau = \int_{-\infty}^{\infty} \mathcal{H}(\tau)u(t-\tau)d\tau$$

$S_{\mathcal{H}}$ is BIBO stable (or ∞-stable) if and only if $\exists M < \infty$ such that

$$\max_{i\in[1,p]} \sum ||h_{ij}||_1 = M$$

we can see that for multivariate BIBO stability all possible SISO input–output terminals has to be BIBO stability. It is enough to the sufficiency for the multi-variate case, since proof in SISO case covers necessity condition. Let $y_i(t)$ is the i^{th} output terminal then

$$y_i(t) = \sum_{j=1}^{m} \left[\int h_{ij}(\tau)u_j(t-\tau)d\tau \right]$$

$$|y_i(t)| = \left| \sum_{j=1}^{m} \left[\int h_{ij}(\tau)u_j(t-\tau)d\tau \right] \right| \le \sum_{j=1}^{m} \left[\int |h_{ij}(\tau)u_j(t-\tau)| \, d\tau \right] \le \sum_{j=1}^{m} \left[\int |h_{ij}(\tau)| \, |u_j(t-\tau)| \, d\tau \right]$$

$$\le \sum_{j=1}^{m} \left[\int |h_{ij}(\tau)| \, ||u(t-\tau)||_\infty d\tau \right] \le \sum_{j=1}^{m} \left[\int |h_{ij}(\tau)| \, d\tau \right] ||u||_\infty \le \left[\sum_{j=1}^{m} ||h_{ij}||_1 \right] ||u||_\infty$$

Noe let's focus on all output variables

$$||y||_\infty = \sup_t ||y(t)||_\infty = \sup_t \max_{i\in[1,p]} |y_i(t)| \le \max_{i\in[1,p]} \left[\sum_{j=1}^{m} ||h_{ij}||_1 \right] ||u||_\infty$$

thus if $\max\limits_{i\in[1,p]}\left[\sum\limits_{j=1}^{m}||h_{ij}||_1\right] = M < \infty$, then $||y||_\infty$ is finite for all finite $||u||_\infty$. The constant M derived in this proof is called the called the $\mathcal{L}_1$-norm (or $\mathcal{L}_{\infty-\mathrm{ind}}$-norm) of the system and showed as

$$||S_{\mathcal{H}}||_1 = \max\limits_{i\in[1,p]}\left[\sum\limits_{j=1}^{m}||h_{ij}||_1\right]$$

Theorem: Let, $S_{\mathcal{G}}$, be a DT-LTI MIMO system where $\mathcal{G}[k]$ is its impulse response matrix with m inputs and p outputs, i.e.

$$y[k] = \mathcal{G}[k] * u[k] = \sum\limits_{n=-\infty}^{\infty}\mathcal{G}[k-n]u[k]$$

$S_{\mathcal{G}}$ is BIBO stable (or ∞-stable) if and only if $\exists M < \infty$ such that

$$||S_{\mathcal{G}}||_1 = \max\limits_{i\in[1,p]}\sum||h_{ij}||_1 = M$$

Steps of the proof is very similar to the CT case.