

TASK 2

DATABASE INTEGRATION AND MIGRATION





EXPLOLERER

ALFIDO TECH INTERNSHIP TASKS

employeeapi

src

main

java\com\jackie\empl...
EmployeeapiApplicatio...

resources

static

templates

application.properties

test

target

.gitattributes

nitignore

OUTLINE

TIMELINE

JAVA PROJECTS

MAVEN

employeeController.java

ion.java

application.properties

employeeapi > src > main > resources > application.properties

1 spring.application.name=employeeapi

2 spring.datasource.url=jdbc:h2:mem:employeeDB

3 spring.datasource.driverClassName=org.h2.Driver

4 spring.datasource.username=sa

5 spring.datasource.password=

PROBLEMS

OUTPUT

DEBUG CONSOLE

TERMINAL

PORTS

spring.jpa.open-in-view to disable this warning

2025-12-11T19:49:39.716+05:30 INFO 10264 --- [employeeapi] [main] o.s.b.h.a.H2ConsoleAutoConfiguration : H2 console available at '/h2-console'. Database available at 'jdbc:h2:mem:employeeDB'

2025-12-11T19:49:39.823+05:30 INFO 10264 --- [employeeapi] [main] o.s.boot.tomcat.TomcatWebServer : Tomcat started on port 8080 (http) with context path '/'

2025-12-11T19:49:39.837+05:30 INFO 10264 --- [employeeapi] [main] c.j.employeeapi.EmployeeapiApplication : Started EmployeeapiApplication in 4.1 seconds (process running for 4.495)

Run: Emplo...

Run: Emplo...

Java: Ready

Ln 1, Col 36 Spaces: 4 UTF-8 LF { } Java Properties Signed out

EXPLOLER

ALFIDO TECH INTERNSHIP TASKS

employeeapi

.idea

.mvn

src

main

java\com\jackie\empl...

controller

EmployeeController.j...

model

repository

EmployeeapiApplicatio...

resources

OUTLINE

TIMELINE

JAVA PROJECTS

MAVEN

alfido tech internship tasks

EmployeeapiApplication.java

application.p

main > java > com > jackie > employeeapi > EmployeeapiApplication.java > EmployeeapiApplication

```
1 package com.jackie.employeeapi;
2 import org.springframework.boot.SpringApplication;
3 import org.springframework.boot.autoconfigure.SpringBootApplication;
4 @SpringBootApplication
5 public class EmployeeapiApplication {
```

PROBLEMS

TERMINAL

Run: EmployeeapiApplication

j.employeeapi.EmployeeapiApplication : Started EmployeeapiApplication in 4.246 seconds (process running for 4.597)

2025-12-11T20:11:28.255+05:30 INFO 20620 --- [employeeapi] [nio-8080-exec-3] o.a.c.c.C.[Tomcat].[localhost].[/] : Initializing Spring DispatcherServlet 'dispatcherServlet'

2025-12-11T20:11:28.257+05:30 INFO 20620 --- [employeeapi] [nio-8080-exec-3] o.s.web.servlet.DispatcherServlet : Initializing Servlet 'dispatcherServlet'

2025-12-11T20:11:28.261+05:30 INFO 20620 --- [employeeapi] [nio-8080-exec-3] o.s.web.servlet.DispatcherServlet : Completed initialization in 2 ms

2025-12-11T20:11:28.466+05:30 INFO 20620 --- [employeeapi] [nio-8080-exec-3] c.j.e.controller.EmployeeController : fetching all employees...

< 0 0

Java: Ready

Ln 4, Col 1

Tab Size: 4

UTF-8

LF

{ } Java

Signed out

Login

Saved Settings: Generic H2 (Embedded)

Setting Name: Generic H2 (Embedded) Save Remove

Driver Class: org.h2.Driver

JDBC URL: jdbc:h2:mem:employeeDB

User Name: sa

Password:

Connect Test Connection

Spring Initializrlocalhost:8080/employeesH2 Console

localhost:8080/h2-console/login.do?sessionId=9285b3c9b1d70ca1d645bfeddb62fff86

Auto commit

Max rows: 1000

Auto complete Off

Auto select On

jdbc:h2:mem:employeeDB

EMPLOYEE

INFORMATION_SCHEMA

Users

H2 2.4.240 (2025-09-22)

RunRun SelectedAuto completeClear

SQL statement:

Important Commands

?	Displays this Help Page
	Shows the Command History
Ctrl+Enter	Executes the current SQL statement
Shift+Enter	Executes the SQL statement defined by the text selection
Ctrl+Space	Auto complete
	Disconnects from the database

Sample SQL Script

Delete the table if it exists	DROP TABLE IF EXISTS TEST;
Create a new table	CREATE TABLE TEST(ID INT PRIMARY KEY,
with ID and NAME columns	NAME VARCHAR(255));
Add a new row	INSERT INTO TEST VALUES(1, 'Hello');
Add another row	INSERT INTO TEST VALUES(2, 'World');
Query the table	SELECT * FROM TEST ORDER BY ID;
Change data in a row	UPDATE TEST SET NAME='Hi' WHERE ID=1;
Remove a row	DELETE FROM TEST WHERE ID=2;
Help	HELP ...

Adding Database Drivers

Additional database drivers can be registered by adding the Jar file location of the driver to the environment variables H2DRIVERS or CLASSPATH. Example (Windows): to add the database driver library C:/Programs/hsqldb/lib/hsqldb.jar, set the environment variable H2DRIVERS to C:/Programs/hsqldb/lib/hsqldb.jar.