



Notes:

- 1. Adjust dimensions of trolley according to size of your sorting containers
- 2. Grind all surfaces to be welded about 25mm from weld
- 3. Tack weld the whole frame
- 4. Check that everything is square and all measurements are accurate
- 5. Fully weld all seams

8	2	underlayment 15mm	1635	90	90	plywood
7	4	L angle 20 x 20 x 3	545	90	90	mild steel
6	2	flat bar 20 x 3	75	45	45	mild steel
5	8	square tube 30 x 30 x 2	1640	90	90	mild steel
4	2	square tube 30 x 30 x 2	545	90	90	mild steel
3	4	square tube 30 x 30 x 2	700	90	90	mild steel
2	4	square tube 30 x 30 x 2	605	45	45	mild steel
1	2	square tube 30 x 30 x 2	1700	45	45	mild steel
ITEM NO.	QTY.	DESCRIPTION	LENGTH	ANGLE1	ANGLE2	MATERIAL

	Workspace Collection		Description Table				
	Projection method First angle		Release date 07/01/20	Drawing no. COLWS-V1-4000.00		Rev. A	
	General tolerances ISO-2768-m	Doc type Assembly	Units unless specified mm	Sheet size A3	Scale 1:10	Sheet 1/2	

