NAME & SURAT RAWAT ROLLNO \$ 2101234 Sec > B Sem=> Ist course => MCA Jate \$ 15/3/22 Subject > scripting language. (html) < head) (title) customer Information (Hitle) <style) table border-style: Solid, border-width: 3 px', border-color: blue; </style) 2/head) (body) < 9Php \$ con = mysql-Connect ("localhost," root", ""); if (! 5 (on) die ('not connected'. mysql-error());

NAME & SURAT RAWAT ROLLNO \$ 2101234 Sec > B Sem=> Ist course => MCA Jate \$ 15/3/22 Subject > scripting language (html) (head) (title) customer Information (Hitle) <style) table border-style: Solid, border-width: 3 px', border-color: blue; </style) 2/head) (body) < 9Php \$ con = mysql-Connect ("localhost," root", ""); if (! 5 (on) die ("not connected". mysql-error ());

NAME = SURATRAWAT ROLLNO = 26/234 sec=) B sem of JS1 cousse ma Date of 15/3/12 Subject scripting language While (s'row = mysq1-fetch array (fsq1)) Caho "(trs"; echo "<td", frow ['a no']. <Hds"; echo " (tds". frno ['C_name']. </td"); Echo "(td") frow ['tem purchased']. " <td"; echo "¿td>. f' row ['mob-no']," ¿Hd>", echo "Utrs"; Cho" (Hable)"; <1 body > (1html)

sect is NAME & SURAT RAWAT ROIL NO \$ 2101234 Date = 2 15/3/22 Semy Ist course & MCA Subject > language 12 Hide & show the paragraph content <! POCTYPE html> <html lang = "en") (head) (meta charset = "UTF-8"/> <meta name = "viewport"</p> Content = 1) width = device - width, initial - Scale = 1.0"/> Kmeta http-equiv = "x-uA-compatible "content="ie=edge") (title) Hide and show effects (Ititle) <p 15"> </script) 2style). button & background - color: 11408080; border: nong badding: 15P1 32px; text-align: Conter; textde Coration: none; desplay: inline-block; font-size: 14/95 margin: 2 px 3 px; cursor: pointer; (1 Style) (15tyle) (Script)

Sec > B NAME & SURATRAWAT ROHNO > 2101234 Jate \$ 15/3/122 Sem > Ist course > mcA Subject & Scripting language \$ (document). ready (function () ? 1) Showing hidden paragraphs \$ ("# Show"). click (function () { \$ ("hz"). showl); 4); dis played paragraphs 11 Hiding S' ("# hide"). click function () { s' ("h2"). hide (); 3); 4); 4/script) 4/head) (body) (h2) This is a paragraph (1h2) Lbutton class = "button" id = "hide"> Hide 21 button>

NAME = SURAT RAWAT ROLLINO = 2101234 Sec = B

sem = Ist course = mcA pake = 15/3/22

Subject = Scripting language

(button class = "button"

id "Show" > Show < 1 button)

(body)

(1html)

sect B NAME & SURAT RAWAT ROII NO + 210 1234 Date + 15/3/22 sem = Ist course = mcA Subject + R-language CSV data set 3 > Summary (var1) min 1st au. median max. mean 3rd au. 1.0 96.5 195.0 194.8 2925 391.0 Fivenum (vari) 1.0 96.5 195.0 292.5 391.0 JOR (vari) 196 range (vari) 392 Var (vari) 12877.82 Sd (vari) 113.4805 Sart (var (vari))

NAME = SURAT RAWAT ROLL NO = 2101234 Sec= B Sem + Ist (ousse =) mcA Date= 15/3/22 Subject= 1 R- language

dy Piscriptive statistics

Here we take the data of crytocurrency in our data mean of the forther wind in 194.8 and Standerd deviation is 113.4805 and variance is 12877.82

in Frential Statistica

In our data set cryto currency the minimum is 10 and the maximum is 391.0 and the First quartile is 96.5 and the 3rd Quartile W 292.5