Ans1 Program to read info like C_no, _name, Item — purchased & mob_no from Customer table.

Source Calc:

```
<html>
<head>
<title> display data in table format </title>
</head>
<body>
<?php
$con = mysql_connect("localhost", "root", "");
if (!$con)
{
die("not connected". mysql_error());
}
echo "Connection open"."</br>";
$sldb = mysql_select_db("coust", $con);
if(!$sldb)
{
die("not found".mysql_error());
}
echo "Database Selected"."<br/>";
$querry = "Select * from Customer";
```

Kunal

```php
$sql = mysql_query ($query);
echo "<table border ='1'>
<tr>
<th>2345</th>
<th> C_name </th>
<th>item_purchase</th>
<th> mob_no   </th>
</tr>;

while ( $row = mysql_fetch_array ($sql))
{
echo "<tr>";
echo "<td>". $row ['C_no'].". </td>
echo "<td>". $row ['C_name']. "</td>"
echo "<td>". $row ['item_purchased']. "</td>";
echo "<td>". $row ['mob_no']. "</td>";
echo "</tr>";
}
echo "</table>";
?>
</body>
</html>
```

Kunal

Connection open
Database selected

C_No	C_Name	Item_Purchased	Mob_no
1	Kunal Rawat	operating system	90279065
2	Rajat Rawat	Php Book	12345678

Name = Kunal Rawat
Student id = 21711010
Roll no = 01
Section = B
University Roll no = 2101103

Subject Practical = SL & R

Ans2 Program to hide and show the paragraph content on the button click using jQuery.

Source code:

```
<! DOCTYPE html>
<html>
<head>
<script src="https://ajax.googleapis.com/ajax
        /libs/jQuery/3.5.1/jQuery.min.Js">
</script>
<script>
$(document).ready(function(){
$("#hide").click(function(){
$("p").hide();
});

$("#show").click(function(){
$("p").show();
});
});
</script>
```

Kunal

```html
</head>
<body>

<p>If you click on the "Hide" button, I will
    disappear </p>

< button id="hide">Hide </button>
< button id="Show" >Show </button>

</body>
</html>
```

Kunal

If you click on the "Hide" button, I will disappear.

`Hide` `Show`

Hide Show

Name = Kunal Rawat   Stdid = 21711010

Ans3   Analyze anyCSV dataset
                        Summary (TM)
>min (TM)
[1] 48.14652

>max (TM)
[1] 18582700

>mean (TM$TM.open)
[1] 111.0244

>mean (TM$TM.Close)
[1] 111.0025

>mean (TM$TM.High)
[1] 111.6275

>mean (TM$TM.Low)
[1] 110.3195

>mean (TM$TM.Adjusted)
[1] 103.7753

>median (TM$TM.Volume)
[1] 340600

>quartile (TM$TM.open)

  0%   25%   50%   75%   100%
57.390 84.005 115.86 127.74 187.87

>quartile (TM$TM.open)

                                        Kunal

```
>quantile (TM$TM.low)
___

>quartile (TM$TM.High)
___

>quartile (TM$TM.Volume)
___

>sd (TM $TM.Volume)
[1] 558190.8

>sd (TM$TM.open)
[1] 27.21876

>sd (TM$TM.close)
 [1] 27.2189

>sd (TM$TM.High)
[1] 27.23972

>sd (TM $TM.low)
[1] 27.2025

>sd (TM$TM.Adjusted)
[1] 30.75341

>sd (TM $TM.Adjusted)
   [1] 30.75341

>var (TM $TM.open)
```

TM.open

TM.open 740.8606

>Var (TM $TM.close)

TM.close

TM.close 740.8688

>Var (TM $TM.High)

TM.High

TM.High 742.0024

>Var (TM $TM.Low)

TM.low

TM.low 739.955

>Var (TM $ TM.Adjusted)

TM.Adjusted

TM.Adjusted 945.7722

> Var (TM $TM.Volume)

TM.Volume

TM.Volume 311576928916

Kunal

Connection open
Database selected

C_No	C_Name	Item_Purchased	Mob_no
1	Manish	php book	9897563
2	rohit	scripting language	123456

Ans 4   Discriptive statics

Here we take the data of populations and Sample in our data mean of the population $5.94l+07$ and the mean of the data $8.614l+10$ standard deviation of our data population is 217665173 and Variance is $4.735308l+16$.

Infrential statics

In our data set minimum population of a country is $9.12l+04$ & max is $1.206l+09$ our 1st quartile population is $4.698l+06$ & 3rd quartile $3.148l+07$. our last quartile is $5.648l+09$.

Kunal