Name : Lavanya Tiwade

PRN : 24070521130

Batch : B2

```c
#include <stdio.h>
#include <string.h>
#include <stdlib.h>
#include <unistd.h>
#include <arpa/inet.h>
#include <sys/socket.h>
#define PORT 10082
#define BUF_SIZE 1024
int main() {
    int sock;
    struct sockaddr_in server, client;
    char buffer[BUF_SIZE];
    socklen_t client_len = sizeof(client);
    sock = socket(AF_INET, SOCK_DGRAM, 0);
    if (sock < 0) {
        perror("Socket creation failed");
        return 1;
    }
    memset(&server, 0, sizeof(server));
    server.sin_family = AF_INET;
    server.sin_addr.s_addr = INADDR_ANY;
    server.sin_port = htons(PORT);
    if (bind(sock, (struct sockaddr *)&server, sizeof(server)) < 0) {
        perror("Bind failed");
        close(sock);
        return 1;
    }
    printf("UDP Echo Server listening on port %d...\n", PORT);
    while (1) {
        memset(buffer, 0, BUF_SIZE);
        int bytes = recvfrom(
            sock,
            buffer,
            BUF_SIZE - 1,
            0,
            (struct sockaddr *)&client,
            &client_len
        );
        if (bytes < 0) {
            perror("Receive failed");
            break;
        }
        buffer[bytes] = '\0';
        printf("Received: %s", buffer);
        sendto(
            sock,
            buffer,
            bytes,
            0,
            (struct sockaddr *)&client,
            client_len
        );
    }
    close(sock);
    return 0;
}
```

Name : Lavanya Tiwade

PRN : 24070521130

Batch : B2

```c
#include <stdio.h>
#include <string.h>
#include <stdlib.h>
#include <unistd.h>
#include <arpa/inet.h>
#include <sys/socket.h>
#define PORT 10082
#define BUF_SIZE 1024
int main() {
    int sock;
    struct sockaddr_in server;
    char buffer[BUF_SIZE];
    socklen_t server_len = sizeof(server);
    sock = socket(AF_INET, SOCK_DGRAM, 0);
    if (sock < 0) {
        perror("Socket creation failed");
        return 1;
    }
    memset(&server, 0, sizeof(server));
    server.sin_family = AF_INET;
    server.sin_port = htons(PORT);
    server.sin_addr.s_addr = inet_addr("127.0.0.1");
    while (1) {
        printf("Enter message: ");
        fgets(buffer, BUF_SIZE, stdin);
        sendto(
            sock,
            buffer,
            strlen(buffer),
            0,
            (struct sockaddr *)&server,
            sizeof(server)
        );
        memset(buffer, 0, BUF_SIZE);
        int bytes = recvfrom(
            sock,
            buffer,
            BUF_SIZE - 1,
            0,
            (struct sockaddr *)&server,
            &server_len
        );
        if (bytes < 0) {
            perror("Receive failed");
            break;
        }
        buffer[bytes] = '\0';
        printf("Echo from server: %s", buffer);
    }
    close(sock);
    return 0;
}
```