

Test S0246394086U

Online>qm

Management Ethernet Interface:
IP Configuration Method: static
IP address: 172.16.36.85
Subnet mask: 255.255.255.0
Default Gateway: 172.16.36.1
MAC address: 00:d0:fa:06:0b:12
Port speed: 1 Gbps Full-Duplex
payShield Manager connection: Enabled

Online>qh

Message header length: 04
Disable host connections when no LMKs are installed: NO
Protocol: Ethernet
Well-Known-Port: 01500
Well-Known-TLS-Port: 02500
Transport: TCP, 64 connections
TCP Keep_Alive value (minutes): 2 minutes
ACL: Enabled
Number of interfaces : (1)

Interface Number: 1
IP Configuration Method: static
IP address: 172.24.6.186
Subnet mask: 255.255.255.0
Default Gateway: 172.24.6.1
MAC address: 00:d0:fa:06:0b:11
Port speed: 1 Gbps Full-Duplex

Online>qs

PIN length: 06

Encrypted PIN length: 07

Echo: OFF

Atalla ZMK variant support: OFF

Transaction key support: NONE

User storage key length: SINGLE

Display general information on payShield Manager Landing Page: NO

Default LMK identifier: 00

Management LMK identifier: 00

Select clear PINs: NO

Enable ZMK translate command: NO

Enable X9.17 for import: YES

Enable X9.17 for export: YES

Solicitation batch size: 1024

ZMK length: SINGLE

Decimalization tables: ENCRYPTED

Decimalization table checks: ENABLED

PIN encryption algorithm: A

Press "Enter" to view additional security settings...

Authorized State required when importing a key under an RSA key: YES

Minimum HMAC length in bytes: 10

Enable PKCS#11 import and export for HMAC keys: NO

Enable ANSI X9.17 import and export for HMAC keys: NO

Enable ZEK/TEK encryption of ASCII data or Binary data or None: BINARY

Restrict key check values to 6 hex chars: YES

Enable multiple authorized activities: YES

Allow persistent authorized activities: YES

Enable variable length PIN offset: NO

Enable weak PIN checking: NO

Enable PIN block Format 34 as output format for PIN translations to ZPK: NO

Enable translation of account number for LMK encrypted PINs: NO

Use HSM clock for date/time validation: YES

Additional padding to disguise key length: NO

Key export and import in trusted format only: NO

Protect MULTOS cipher data checksums: YES

Enable Key Scheme Tag 'X' (X9.17) for storing keys under LMK: YES

Enable use of Tokens in PIN Translation: YES

Enable use of Tokens in PIN Verification: NO
Ensure LMK Identifier in command corresponds with host port: NO
Ignore LMK ID in Key Block Header: NO
Enable import and export of RSA Private keys: NO
Enable import of a ZMK: NO
Enable export of a ZMK: NO

NOTE: The following settings are not all PCI HSM compliant.
Prevent single-DES keys masquerading as double or triple-length keys: YES
Single-DES: ENABLED
Card/password authorization (local): C
Restrict PIN block usage for PCI HSM Compliance: NO
Enforce key type 002 separation for PCI HSM compliance: YES
Enforce Authorization Time Limit: YES
Enforce Multiple Key Components: YES
Enforce PCI HSMv3 Key Equivalence: NO
Enforce minimum key strength of 1024-bits for RSA signature verification: YES
Enforce minimum key strength of 2048-bits for RSA: YES

Online>vr

Base Release: 1.2a
Revision: 1500-0024
Firmware Version: 1.5.0
Deployment Version: 1.5.0

PCI HSM Compliance:
Some security settings are not PCI HSM compliant

Serial Number: S0246394086U
Model: PS10-S

Power supply #1:
Model number : D1U54P-W-450-12-HA4C
Serial number: XQ2041RJ2621
Power supply #2:
Model number : D1U54P-W-450-12-HA4C
Serial number: XQ2041RJ1436

Fan #1:

Serial number: FM01512020212

Fan #2:

Serial number: FM01512020223

Unit info: Licensed

Host Configuration: Ethernet,(optional) TLS/SSL

License Issue No: 2

Performance: 25 cps

Ship Counter: 1

Crypto: 3DES,AES,RSA

Press "Enter" to view additional information...

Premium Package:

- Premium Key Management
- Magnetic Stripe Issuing
- Magnetic Stripe Transaction Processing
- EMV Chip, Contactless & Mobile Issuing
- EMV Transaction Processing
- User Authentication
- Data Protection

Optional Licenses:

- Legacy Commands
- LMKx5
- Remote payShield Manager

Bootstrap Version: 1.1.40

Sensor Processor Application: 1.1.29

Sensor Processor Boot Version: 1.0.0

CPLD Version: 1.2.3

PCI HW Rev: 01

FIPS validated algorithms:

Algorithm	Name and Version	FIPS Status
-----	-----	-----
DRBG/RNG	TASP-DRBG v1.0	Approved
SHA	TASP-SHA v1.0	Approved
HMAC	TASP-HMAC v1.0	Approved
TDES	TASP-TDES v1.0	Approved

AES	TASP-AES v1.0	Approved
CMAC	TASP-CMAC v1.0	Approved
RSA	TASP-RSA-ACCELERATED v1.0	Approved
AES	TASP-AES-ACCELERATED v1.0	Approved
TDES	TASP-TDES-ACCELERATED v1.0	Approved

Online>vt

LMK table:

ID	Authorized	Scheme	Algorithm	Status	Check	Comments
----	------------	--------	-----------	--------	-------	----------

00	No	Variant	3DES(2key)	Live	142586	
----	----	---------	------------	------	--------	--

Key change storage table:No keys loaded in key change storage

Online>

Online>configcmds

List of enabled Host commands:

A0 A2 A4 A6 A8 AA AC AE AG AI AK AM AO AQ AS
 AU AW AY B0 B2 B8 BA BC BE BG BI BK BM BQ BS
 BU BW BY C0 C2 C4 C6 C8 CA CC CE CG CI CK CM
 CO CQ CS CU CW CY D0 D2 D4 D6 D8 DA DC DE DG
 DI DK DM DO DQ DS DU DW DY E0 E2 E4 E6 E8 EA
 EC EE EG EI EK EM EO EQ ES EU EW EY F0 F2 F4
 F6 F8 FA FC FE FG FI FK FM FO FQ FS FU FW FY
 G0 G2 G4 G6 G8 GA GC GE GG GI GK GM GO GQ GS
 GU GW GY H0 H2 H4 H6 H8 HA HC HE HG HI HK HM
 HO HQ HS HU HW HY I0 I2 I4 I6 I8 IA IC IE IG
 II IK IM IO IQ IU IW IY J0 J2 J4 J6 J8 JA JC
 JE JG JI JK JO JS JU JW JY K0 K2 K8 KA KC KE
 KG KI KK KM KO KQ KS KU KW KY L0 L6 L8 LA LC
 LE LG LI LK LM LO LQ LS LU LW LY M0 M2 M4 M6
 M8 MA MC ME MG MI MK MM MO MQ MS MU MW MY NO
 N6 N8 NC NE NG NI NK NO NY OA OC OE OI OK OU
 OW P0 P2 P4 P6 P8 PA PC PE PG PI PK PM PO PQ

PS PU PW PY Q0 Q2 Q4 Q6 Q8 QA QC QE QI QK QM
QO QQ QS QU QW QY R2 R4 R6 R8 RA RC RE RG RI
RK RM RO RQ RS RU RW RY T0 T2 T4 T6 TA U0 U2
U4 U6 U8 V0 V2 V4 V6 V8 W0 W2 W4 W6 W8 X0 X2
X4 X6 X8 XK XM XO XQ XS XU XW Y0 Y2 Y4 Y6 Y8
Z0 ZA ZE ZK ZM ZU

List of enabled Console commands:

A A5 A6 A7 AUDITLOG AUDITOPTIONS
C CA CH CK CL CLEARERR
CLEARAUDIT CM CO CONFIGACL CONFIGCMDS CONFIGPB
CP CS CV DC DM DO
DT EC ED EJECT ERRLOG FC
FICONTEST FK GC GETCMDS GETTIME GK
GS GT HEALTHENABLE HEALTHSTATS IK IV
KD KE KG KK KM KN
KT LK LO LN MI N
NP NETSTAT PING PV QA QH
QL QM QMAC QP QS R
RC RESET RS SD SE SETTIME
SG SI SK SL SP SNMP
SNMPADD SNMPDEL SS ST SV T
TD TRAP TRAPADD TRAPDEL TRACERT UPLOAD
UTILCFG UTILENABLE UTILSTATS V VA VC
VR VT XA XD XE XH
XI XK XR XT XX XY
XZ \$

Online>