





SECTION A-A

SPECIAL NOTE: ENGRAVE P/N NO WITH 3mm TEX	Ι ,													APPROX WEIGHT(Kg):	INICIA	\sim TTT			
HEAT TREATMENT:,						LIN	LINEAR DIMENSIONS				ANG	ULAR D	R DIMENSIONS			0200-012885		IN2IQH I	
INDUCTION HARDENED, 55 HRC						ABOVE	LIDTO		TOLERANCE		LENGTH OF SHORTER SIDE		TOLERANCE			TITLE:		Shaping Imaginations	
HARDENED LINE:	2				ľ		0110	MACHINE D PARTS			OF ANGLE		MACHINED PARTS		RTS	WS_PIN_OP10_		1 0	
SURFACE COATING:						0.5	6	±0.1	±0.5	ABOVE	UPTO	ON SHORTER	DEGREES OR	ON SHORTER	DEGREES OR	MATERIAL:		DRN.:KIRAN	SCALE:
ENGRAVE DRAWING No. WITH 3mm TEXT					L	6	30	±0.2	±1	. IDO I L		SIDE	MINUTES	JTES SIDE	MINUTES	C45+N Ø21X16.5	A 213/16 5	CHD.:SRINIVAS	6
	1			L	30	120	±0.3	±1.5	0	0 10	±0.1	±1°	±0.3	±3°		1 4	DATE:	Ŭ	
						120	315	±0.5	±2	10	50	±0.2	±30'	±0.8	±2°	1) DE-BURR ALL SHARP EDGES &		FIRST	SHT:
	REV	DESCRIPTION	NAME	DATE A		315	1000	±0.8	±3	50	120	±0.6	±20'	±1.8	±1°	7).5x45 -2) ALL "H7 TOL." HOLES TO HAV		ANGLE	3H1:
					AREA	1000	2000	±1.2	±5	120	-	±0.8	±10'	±2.4	±30'	B) UNSPECIFIED SURFACE FINISH		ANGLE	1/1