







SPECIAL NOTE: ENGRAVE P/N NO WITH 3mm TEXT	2					ALLOWABLE DEVIATIONS FOR											APPROX WEIGHT(Kg)	INICI	СТТТ
HEAT TREATMENT:	3					LIN	EAR DI	MENSIONS		ANG		GULAR DIMENSIONS				0200-012871]	INSIGH I Shaping Imaginations	
THROUGH HARDENED , 50 ~ 60 HRC,		2			,	ABOVE U	LIDTO		TOLERANCE		LENGTH OF SHORTER SIDE		TOLERANCE			TITLE:			
	2						OFIO	MACHINE D PARTS	SHEETMET AL PARTS	OF ANGLE		MACHINED PARTS SHEETMETAL PARTS		METAL TS	LOC_PIN_OP10_AUTOPILOT		1 6 6		
GURDA GE GOATING TO DE DIAGUED	-					0.5	6	±0.1	±0.5	ABOVE	UPTO	ON SHORTER	DEGREES OR MINUTES	ON SHORTER	DEGREES OR	MATERIAL: FINIS		DRN.:KIRAN	SCALE:
SURFACE COATING: TO BE BLACKENED						6	30	±0.2	±1	· ibo · L	01.10	SIDE	MINUTES	SIDE	MINUTES		53761	CHD.:SKINIVAS	1
	1					30	120	±0.3	±1.5	0	10	±0.1	±1°	±0.3	±3°			DATE:	•
						120	315	±0.5	±2	10	50	±0.2	±30'	±0.8	±2°	I) DE-BURR ALL SHARP EDGES & CORN		FIRST	SHT:
	REV	DESCRIPTION	NAME	DATE		315	1000	±0.8	±3	50	120	±0.6	±20'	±1.8	±1°).5x45° 2) ALL "H7 TOL." HOLES TO HAVE ENTF		ANGLE	1/1
					AREA	1000	2000	±1.2	±5	120	-	±0.8	±10'	±2.4	±30'	3) UNSPECIFIED SURFACE FINISH, MAC	HINED: 3.2 Ra	ANGLE	1/1