

# Inf1-OP

## Inheritance

Volker Seeker, adapting earlier version by Perdita Stevens and  
Ewan Klein


School of Informatics

February 22, 2019

# Abstracting Common Stuff


## Inheritance hierarchy:

Subclass (UG, PG) **inherit** from superclass (Student) inherits from superclass (Object)



# Flat vs. Nested Hierarchies

# Flat Animal Hierarchy



# Animals Example, 1

Our base class: Animal

## Animal

```
public class Animal {  
    public void sleep() {  
        System.out.println("Sleeping: Zzzzz");  
    }  
    public void makeNoise() {  
        System.out.println("Noises...");  
    }  
    public void roam() {  
        System.out.println("Roamin' on the plain.");  
    }  
}
```

## Animals Example, 2

1. Lion subclass-of Animal
2. Override the makeNoise() method.

### Lion

```
public class Lion extends Animal {  
    public void makeNoise() {  
        System.out.println("Roaring: Rrrrrr!");  
    }  
}
```

## Animals Example, 3

1. Cat subclass-of Animal
2. Override the makeNoise() method.

### Cat

```
public class Cat extends Animal {  
    public void makeNoise() {  
        System.out.println("Miaowing: Miaooo!");  
    }  
}
```

## Animals Example, 4

1. Wolf subclass-of Animal
2. Override the makeNoise() method.

### Wolf

```
public class Wolf extends Animal {  
    public void makeNoise() {  
        System.out.println("Howling: Ouooooo!");  
    }  
}
```



## Animals Example, 5

1. Dog subclass-of Animal
2. Override the makeNoise() method.

### Dog

```
public class Dog extends Animal {  
    public void makeNoise() {  
        System.out.println("Barking: Woof Woof!");  
    }  
}
```

# Animals Example, 6

## The Launcher

```
public class AnimalLauncher {  
    public static void main(String[] args) {  
        System.out.println("\nWolf\n====");  
        Wolf wolfie = new Wolf();  
        wolfie.makeNoise(); // from Wolf  
        wolfie.roam(); // from Animal  
        wolfie.sleep(); // from Animal  
  
        System.out.println("\nLion\n====");  
        Lion leo = new Lion();  
        leo.makeNoise(); // from Lion  
        leo.roam(); // from Animal  
        leo.sleep(); // from Animal  
    }  
}
```

## Animals Example, 7

### Output

Wolf

=====

Howling: Ouooooo!

Roamin' on the plain.

Sleeping: Zzzzz

Lion

=====

Roaring: Rrrrrr!


Roamin' on the plain.

Sleeping: Zzzzz

# Nested Animal Hierarchy

- ▶ Lions and cats can be grouped together into Felines, with common `roam()` behaviours.
- ▶ Dogs and wolves can be grouped together into Canines, with common `roam()` behaviours.

# Nested Animal Hierarchy



# Animals Example, 1

Same as before.

## Animal

```
public class Animal {  
    public void sleep() {  
        System.out.println("Sleeping: Zzzzz");  
    }  
    public void makeNoise() {  
        System.out.println("Noises...");  
    }  
    public void roam() {  
        System.out.println("Roamin' on the plain.");  
    }  
}
```

## Animals Example, 2

The new class Feline

Feline

```
public class Feline extends Animal {  
    public void roam() {  
        // Override roam()  
        System.out.println("Roaming: I'm roaming alone.");  
    }  
}
```

## Animals Example, 3

The new class Canine

### Canine

```
public class Canine extends Animal {  
    public void roam() {  
        // Override roam()  
        System.out.println("Roaming: I'm with my pack.");  
    }  
}
```



## Animals Example, 4

1. Lion subclass-of Feline
2. Override the makeNoise() method.

### Lion

```
public class Lion extends Feline {  
    public void makeNoise() {  
        System.out.println("Roaring: Rrrrrrr!");  
    }  
}
```

- Similarly for Cat.

## Animals Example, 5

1. Wolf subclass-of Canine
2. Override the makeNoise() method.

### Wolf

```
public class Wolf extends Canine {  
    public void makeNoise() {  
        System.out.println("Howling: Ouoouooo!");  
    }  
}
```

- Similarly for Dog.


# Which method gets called?

1. `Wolf wolfie = new Wolf();`

2. `wolfie.makeNoise();`

3. `wolfie.roam();`

4. `wolfie.sleep();`



# Animals Example, 6

## The Launcher

```
public class AnimalLauncher {  
    public static void main(String[] args) {  
        System.out.println("\nWolf\n=====");  
        Wolf wolfie = new Wolf();  
        wolfie.makeNoise(); // from Wolf  
        wolfie.roam(); // from Canine  
        wolfie.sleep(); // from Animal  
  
        System.out.println("\nLion\n=====");  
        Lion leo = new Lion();  
        leo.makeNoise(); // from Lion  
        leo.roam(); // from Feline  
        leo.sleep(); // from Animal  
    }  
}
```

## Animals Example, 7

### Output

Wolf

=====

Howling: Ouooooo!

Roaming: I'm with my pack.

Sleeping: Zzzzz

Lion

=====

Roaring: Rrrrrr!

Roaming: I'm roaming alone.

Sleeping: Zzzzz

# Polymorphism

The ability of an object to take on many forms.

# Declaring, Initialising and Using a Reference Variable

```
private static void goToBed(Animal tiredAnimal) {  
    tiredAnimal.sleep();  
}  
  
public static void main(String[] args) {  
    Animal myAnimal = new Animal();  
    goToBed(myAnimal);  
}
```

I am working only with the superclass here.

# Declaring, Initialising and Using a Reference Variable

Polymorphism means:

I can use the subtype `Wolf` of the object `Animal` in any context where an object of type `Animal` is expected.



# Declaring, Initialising and Using a Reference Variable

```
private static void goToBed(Animal tiredAnimal) {  
    tiredAnimal.sleep();  
}  
  
public static void main(String[] args) {  
    Animal myAnimal = new Wolf();  
    goToBed(myAnimal);  
}
```

The subclass can do **at least** everything the superclass can do.  
(maybe a bit different though)

Formal Notation: `Wolf <: Animal` (Wolf is a subtype of Animal)

# Polymorphic ArrayList

## The Launcher

```
public class AnimalLauncher2 {  
    public static void main(String[] args) {  
        Wolf wolfie = new Wolf();  
        Lion leo = new Lion();  
        Cat felix = new Cat();  
        Dog rover = new Dog();  
        ArrayList<Animal> animals = new ArrayList<Animal>();  
        animals.add(wolfie);  
        animals.add(leo);  
        animals.add(felix);  
        animals.add(rover);  
        for (Animal a : animals) {  
            a.makeNoise();  
            goToBed(a);  
        }  
    }  
}
```


# Polymorphic Arrays

`ArrayList<Animal>` is polymorphic.

- ▶ `animals.add(wolfie)`  
add an object of type `Wolf`. OK since `Wolf <: Animal`.
- ▶ `for (Animal a : animals)`  
for each object `a` of type `T` such that `T <: Animal` ...
- ▶ `a.makeNoise()`  
if `a` is of type `T`, use `T`'s `makeNoise()` method.
- ▶ `goToBed(a)`  
You get at least an `Animal`, so you can call every method on it an `Animal` has

# Student Hierarchy

Subclass (UG, PG) **inherit** from superclass (Student) inherits from superclass (Object)



# Casting Object Types

Does this work?

```
private static void giveTutorial(Student support) {  
    support.tutor();  
}  
  
public static void main(String[] args) {  
    Student support = new PGStudent();  
    giveTutorial(support);  
}
```

# Casting Object Types

Does this work?

```
private static void giveTutorial(Student support) {  
    support.tutor();  
}  
  
public static void main(String[] args) {  
    Student support = new PGStudent();  
    giveTutorial(support);  
}
```

**Compiler Error!** Student does not have a tutor()  
method

# Casting Object Types

Does this work?

```
private static void giveTutorial(Student support) {  
    PGStudent pgsupport = (PGStudent) support;  
    pgsupport.tutor();  
}  
  
public static void main(String[] args) {  
    Student support = new PGStudent();  
    giveTutorial(support);  
}
```

# Casting Object Types

Does this work?

```
private static void giveTutorial(Student support) {  
    PGStudent pgsupport = (PGStudent) support;  
    pgsupport.tutor();  
}  
  
public static void main(String[] args) {  
    Student support = new PGStudent();  
    giveTutorial(support);  
}
```

Yes, I do actually get a PGStudent as argument.  
But what if not??



# Casting Object Types

## Casting Object Types Should be Protected

```
private static void giveTutorial(Student support) {  
    if (support instanceof PGStudent) {  
        PGStudent pgsupport = (PGStudent) support;  
        pgsupport.tutor();  
    }  
}  
  
public static void main(String[] args) {  
    Student support = new UGStudent();  
    giveTutorial(support);  
}
```

This works and nothing will be printed.

# Overriding vs. Overloading

# Method Overriding

If a class C **overrides** a method **m** of superclass D, ...

## For Example

```
public class Animal {  
    public Animal findPlaymate() {  
        ...  
    }  
}  
  
public class Wolf extends Animal {  
    ???  
}
```

# Method Overriding

If a class C **overrides** a method **m** of superclass D, then:

- ▶ Parameter lists must be the same.

```
public class Animal {  
    public Animal findPlaymate () {  
        ...  
    }  
}
```

```
public class Wolf extends Animal {  
    public Animal findPlaymate (int number) { // This is not overriding  
        ...  
    }  
}
```

```
public class Wolf extends Animal {  
    public Animal findPlaymate () { // This is overriding  
        ...  
    }  
}
```

# Method Overriding

If a class C **overrides** a method **m** of superclass D, then:

- ▶ Parameter lists must be the same.
- ▶ The return type must be the same or a subclass of the original.

```
public class Animal {  
    public Animal findPlaymate() {  
        ...  
    }  
}
```

```
public class Wolf extends Animal {  
    public Student findPlaymate() { // This is not overriding  
        ...  
    }  
}
```

```
public class Wolf extends Animal {  
    public Wolf findPlaymate() { // This is overriding  
        ...  
    }  
}
```

# Method Overriding

If a class C **overrides** a method **m** of superclass D, then:

- ▶ Parameter lists must be the same.
- ▶ The return type must be the same or a subclass of the original.
- ▶ The overridden method must be at least as accessible as the original.

```
public class Animal {  
    protected Animal findPlaymate() {  
        ...  
    }  
}
```

```
public class Wolf extends Animal {  
    private Student findPlaymate() { // This is not overriding  
        ...  
    }  
}
```

```
public class Wolf extends Animal {  
    public Wolf findPlaymate() { // This is overriding  
        ...  
    }  
}
```

# Method Overriding

If a class C **overrides** a method **m** of superclass D, then:

- ▶ Parameter lists must be same and return type must be compatible:
  1. signature of **m** in C must be same as signature of **m** in D; i.e. same name, same parameter list, and
  2. return type S of **m** in C must such that  $S \leq T$ , where T is return type of **m** in D.
- ▶ **m** must be at least as accessible in C as **m** is in D

Most versions I showed that  
did not override, do in fact  
compile.



Most versions I showed that  
did not override, do in fact  
compile.

But they **overload** the method  
rather than **override** it.

# Method Overloading

Overloading: two methods with **same** name but **different** parameter lists.

## Overloaded makeNoise

```
public void makeNoise() {  
    ...  
}  
public void makeNoise(int volume) {  
    ...  
}
```

## Overloaded println

```
System.out.println(3); // int  
System.out.println(3.0); // double  
System.out.println((float) 3.0); // cast to float  
System.out.println("3.0"); // String
```

# Method Overloading

1. Return types can be different.
2. You can't **just** change the return type — gets treated as an invalid override.
3. Access levels can be varied up or down.

## Incorrect override of makeNoise

```
public String makeNoise() {  
    String howl = "0uooooo!";  
    return howl;  
}
```

Exception in thread "main" java.lang.Error:

Unresolved compilation problem:

The return type is incompatible with Animal.makeNoise()

Let's practice that!

# What does it print?

```
1  public class Vehicle {
2      public void drive() {
3          System.out.println("drivedrive");
4      }
5  }
6  public class Car extends Vehicle {
7      public void drive() {
8          System.out.println("rollroll");
9      }
10 }
11 public class Bike extends Vehicle {
12     public void drive() {
13         System.out.println("pedalpedal");
14     }
15 }
16 public class Main {
17     public static void main(String[] args) {
18         Vehicle c = new Car();
19         c.drive();
20         Vehicle b = new Bike();
21         b.drive();
22     }
23 }
```

# What does it print?

```
1  public class Vehicle {
2      public void drive() {
3          System.out.println("drivedrive");
4      }
5  }
6  public class Car extends Vehicle {
7      public void drive() {
8          System.out.println("rollroll");
9      }
10 }
11 public class Bike extends Vehicle {
12     public void drive() {
13         System.out.println("pedalpedal");
14     }
15 }
16 public class Main {
17     public static void main(String[] args) {
18         Vehicle c = new Car();
19         c.drive();
20         Vehicle b = new Bike();
21         b.drive();
22     }
23 }
```

Prints **rollroll** and **pedalpedal**  
because polymorphic references  
c and b contain instances of  
Car and Bike.

# What does it print?

```
1  public class Addition{
2      public int add(int a, int b){
3          int sum = a+b;
4          return sum;
5      }
6      public int add(int a, int b, int c){
7          int sum = a+b+c;
8          return sum;
9      }
10     public double add(double a, double b, double c){
11         double sum = a+b+c;
12         return sum;
13     }
14 }
15 public class Main {
16     public static void main (String[] args) {
17         Addition op = new Addition();
18         System.out.println(op.add(1,2));
19         System.out.println(op.add(1,2,3));
20         System.out.println(op.add(1.0,2.0,3.0));
21     }
22 }
```

# What does it print?

```
1  public class Addition{
2      public int add(int a, int b){
3          int sum = a+b;
4          return sum;
5      }
6      public int add(int a, int b, int c){
7          int sum = a+b+c;
8          return sum;
9      }
10     public double add(double a, double b, double c){
11         double sum = a+b+c;
12         return sum;
13     }
14 }
15 public class Main {
16     public static void main (String[] args) {
17         Addition op = new Addition();
18         System.out.println(op.add(1,2));
19         System.out.println(op.add(1,2,3));
20         System.out.println(op.add(1.0,2.0,3.0));
21     }
22 }
```

Prints **3**, **6** and **6.00000**

because add is overloaded once by using more parameters and once by using different parameter types.



# What does it print?

```
1  public class Birthday {
2      public void greet(String name, int age){
3          System.out.println("Happy " + age + ". birthday, " + name + "!");
4      }
5      public void greet(int age, String name){
6          System.out.println("All the best for your " +
7              age + ". birthday, " + name + "!");
8      }
9  }
10
11 public class Main {
12     public static void main (String[] args) {
13         Birthday b = new Birthday();
14         b.greet("Jack", 5);
15         b.greet(7, "Jill");
16     }
17 }
```

# What does it print?

```
1  public class Birthday {
2      public void greet(String name, int age){
3          System.out.println("Happy " + age + ". birthday, " + name + "!");
4      }
5      public void greet(int age, String name){
6          System.out.println("All the best for your " +
7                          age + ". birthday, " + name + "!");
8      }
9  }
10
11 public class Main {
12     public static void main (String[] args) {
13         Birthday b = new Birthday();
14         b.greet("Jack", 5);
15         b.greet(7, "Jill");
16     }
17 }
```

Prints **Happy 5. birthday, Jack!** and **All the best for your 7. birthday, Jill!** because greet is overloaded by swapping parameter types around.

# What does it print?

```
1  public class Addition{
2      public int add(int a, int b){
3          int sum = a+b;
4          return sum;
5      }
6      public double add(int a, int b){
7          int sum = a+b;
8          return sum;
9      }
10 }
11
12 public class Main {
13     public static void main (String[] args) {
14         Addition ob = new Addition();
15         System.out.println(ob.add(1,2));
16         System.out.println(ob.add(1,2));
17     }
18 }
```

# What does it print?

```
1  public class Addition{
2      public int add(int a, int b){
3          int sum = a+b;
4          return sum;
5      }
6      public double add(int a, int b){
7          int sum = a+b;
8          return sum;
9      }
10 }
11
12 public class Main {
13     public static void main (String[] args) {
14         Addition ob = new Addition();
15         System.out.println(ob.add(1,2));
16         System.out.println(ob.add(1,2));
17     }
18 }
```

Does not compile because changing only the return type when overloading is not enough.

# Summary

- ▶ Inheritance structures can be long and nested.
- ▶ Polymorphism is the ability of objects to take on many forms.
  - ▶ It allows you to collect various subtypes in the same list, if the list has the supertype parameter.
  - ▶ It allows you to use the same client code for different subtypes, if the client code handles the supertype.
- ▶ Overriding needs to follow three rules (parameter list, return type, access).
- ▶ Otherwise it is likely overloading.
- ▶ It is hard to keep an overview if overloading happens accross class hierarchies.

# Reading

## Java Tutorial

Chapter 6 *Interfaces and Inheritance*, from *Inheritance* until *Abstract Methods and Classes*.