
Issue: Lack of Sudo Permissions for User on Cloudways Server

Problem Description:

The user `master_xppjpsnmsw` is unable to execute administrative tasks using `sudo` due to the lack of sudo privileges. When attempting to run a command with `sudo`, the following error is encountered:

```
[sudo] password for master_xppjpsnmsw:  
Sorry, try again.
```

Additionally, using the `groups` command shows that the user is part of the `www-data` group, but not the `sudo` group, which is required for administrative access:

```
[master_xppjpsnmsw]:master$ groups  
www-data
```

Cause:

The `master_xppjpsnmsw` user does not belong to the `sudo` group, and therefore, lacks the necessary permissions to execute commands with `sudo`.

Suggested Solutions:

Solution 1: Request Sudo Privileges from Cloudways Support

Since the user `master_xppjpsnmsw` does not have root access and is not part of the `sudo` group, the most efficient solution is to contact **Cloudways Support** and request them to add the user to the `sudo` group. This would grant the necessary permissions to execute administrative tasks.

Steps to request from Cloudways Support:

1. Contact Cloudways support through their chat or ticketing system.
2. Explain the issue and request them to add the `master_xppjpsnmsw` user to the `sudo` group for administrative privileges.
3. Once the request is processed, re-login to the server and verify the sudo permissions using the `sudo whoami` command.

Solution 2: Adding User to Sudo Group (if Root Access Available)

If **root access** is available, the following command can be used to add the user to the `sudo` group:

```
sudo usermod -aG sudo master_xppjpsnmsw
```

This command will add the user **master_xppjpsnmsw** to the **sudo** group, enabling them to execute administrative commands with **sudo**.

After executing the command, it is necessary to re-login or restart the SSH session for the changes to take effect.

Conclusion:

To resolve this issue, the recommended approach is to request **Cloudways Support** to add the **master_xppjpsnmsw** user to the **sudo** group. If root access is available, the user can be added to the group manually by executing the appropriate command.
