Logo STUDENT REPORT DETAILS G L SRI NIDHI Roll Number 3BR23CD021 **EXPERIMENT** ₃⇔Title CANDIES **Description** Let's consider a scenario where there are K candies to be distributed among N children, each uniquely numbered from 1 to N. The distribution commences with Child A, followed by a sequential allocation to the subsequent children in the order: A, A+1, A+2,..., N. The query at hand is to identify which child will be the last recipient of a candy. In more explicit terms, after Child x (where 1<= x < N) receives a candy, the subsequent candy is granted to Child x+1. Upon Child N receiving a candy, the distribution cycle restarts. and Child 1 becomes the next recipient. The primary objective is to ascertain the identity of the child who will receive the last candy in this cyclic distribution. Note: Each child receives only 1 candy. Input Format: The first line of input contains 3 space seperated integers N, K and A. **Output Format:** Print the friend who will be the final recipient of the candy. Constraints: 1<=N<=K<=10^8 Sample Input: 521 Sample Output: 2 Source Code: def last_candy_recipient(N, K, A): $last_child = (A - 1 + K - 1) \% N + 1$ return last_child # Example usage: N, K, A = map(int, input().strip().split()) print(last_candy_recipient(N, K, A))

RESULT

2027

3878EV

20202