### Depth First Search

1355

DF

- **Graph traversal** refers to the process of visiting (checking and/or updating) each vertex(node) in a graph.
- Two Algorithms of Graph Traversal are:
  - Breadth First Search (BFS)
  - Depth First Search (DFS)
- In DFS, we start with a node and start exploring its connected nodes keeping on suspending the exploration of previous nodes



### **DFS Procedure**


- 1. Start by putting any one of the graph's vertices on top of a stack.
- 2. Take the top item of the stack and add it to the visited list
- Create a list of that vertex's adjacent nodes. Add the ones which aren't in the visited list to the top of the stack.
- 4. Keep repeating steps 2 and 3 until the stack is empty.

(isited: 012345

### **DFS Procedure**

- 1. Start by putting any one of the graph's vertices on top of a stack.
- 2. Take the top item of the stack and add it to the visited list
- 3. Create a list of that vertex's adjacent nodes. Add the ones which aren't in the visited list to the top of the stack.
- 4. Keep repeating steps 2 and 3 until the stack is empty.

Visited: 0123456



### **DFS** Procedure

- 1. Start by putting any one of the graph's vertices on top of a stack.
- 2. Take the top item of the stack and add it to the visited list
- Create a list of that vertex's adjacent nodes. Add the ones which aren't in the visited list to the top of the stack.
- 4. Keep repeating steps 2 and 3 until the stack is empty.




V: 012

### **DFS Procedure**



- 1. Start by putting any one of the graph's vertices on top of a stack.
- 2. Take the top item of the stack and add it to the visited list.
- 3 Create a list of that vertex's adjacent nodes. Add the ones which aren't in the visited list to the top of the stack.
- 4. Keep repeating steps 2 and 3 until the stack is empty.

Visited: 01234562




### DFS Procedure - Step 2


- 1. Start by putting any one of the graph's vertices on top of a stack Lets put 0 into the stack!
- 2. Take the top item of the stack and add it to the visited list 0 is now visited!

Visited: 0





- 1. Start by putting any one of the graph's vertices on top of a stack Lets put 0 into the stack!
- 2. Take the top item of the stack and add it to the visited list
- Create a list of that vertex's adjacent nodes. Add the ones which aren't in the visited list to the top of the stack.






### DFS Procedure - Step 2

1. Take the top item of the stack and add it to the visited list – 1 is now visited!


Visited: 0, 1





1. Take the top item of the stack and add it to the visited list – 1 is now visited!

Visited: 0, 1






# DFS Procedure - Step 2

1. Take the top item of the stack and add it to the visited list – 1 is now visited!


Visited: 0, 1, 2





1. Take the top item of the stack and add it to the visited list – 1 is now visited!

Visited: 0, 1, 2, 4






# DFS Procedure - Step 2

1. Take the top item of the stack and add it to the visited list -1 is now visited!


Visited: 0, 1, 2, 4





1. Take the top item of the stack and add it to the visited list – 1 is now visited!

Visited: 0, 1, 2, 4, 6






# DFS Procedure - Step 2

1. Take the top item of the stack and add it to the visited list – 1 is now visited!


Visited: 0, 1, 2, 4, 6, 5





1. Take the top item of the stack and add it to the visited list – 1 is now visited!

Visited: 0, 1, 2, 4, 6, 5, 3






# DFS Procedure - Step 2

1. Take the top item of the stack and add it to the visited list – 1 is now visited!


Visited: 0, 1, 2, 4, 6, 5, 3





1. Take the top item of the stack and add it to the visited list – 1 is now visited!

Visited:  $0, 1, 2, 4, 6, 5, 3 \rightarrow DF5$ 





### **DFS Pseudocode**

DFS(G, u) u.visited = true for each  $v \in G.Adj[u]$ if v.visited == false DFS(G,v)

init() {

For each  $u \in G$  u.visited = falseFor each  $u \in G$ DFS(G, u)

