Monoculture Looks Like Collusion: A Replay Test for Hidden Information Flow Between LLM Agents

Yaroslav Rogoza, with Claude (Anthropic)

Independent researcher

With
Apart Research

Abstract

Collusion audits ask whether the actions of different agents depend on each other. Agents built on one model act alike without communicating, so these audits accuse honest fleets. Among four honest Claude Haiku agents playing rock-paper-scissors, mutual information accused a pair in 69.3% of games. We propose a replay test. Each round, the auditor asks every agent again what it would do on the same logged input with the suspected channel removed. Habits that come from the shared model survive this replay, and the influence of a channel does not. A fixed-horizon version scores a whole game, and a sequential version updates every round and may stop at any time. On honest games the fixed-horizon version flagged 4.2%, close to the 5% it was set to. When a pricing vendor pooled two sellers' private costs, the fixed-horizon version named those two sellers in 92.5% of procurement auctions and rarely flagged a vendor that used only public data. In a pre-registered replication the sequential version named an instructed pair in 18/20 rock-paper-scissors games and flagged no honest game. In a pre-registered double-auction study it flagged only 2/30 games of an instructed cartel. A statistic chosen afterwards, counting rounds in which two sellers both act unlike their replays, caught most cartel games in a fresh pre-registered series. The test sees what the current channel adds, so agreements already held in memory or instructions need other audits.

1. Introduction

Firms and labs now run many LLM agents side by side. Pricing bots share a market, bidders share a procurement system, and coding agents share a repository. An auditor usually cannot read the channels between them. As S. Motwani put it at this sprint, "what's left to monitor is still the actions of the agents themselves". The standard audit therefore asks whether one agent's actions predict another's, with a dependence measure such as mutual information [2] or the net influence of Bonjour et al. [1], which subtracts the dependence a third agent explains.

This audit fails under monoculture, when the agents share a model. Four honest copies of Claude Haiku play rock-paper-scissors and never exchange a message. They react alike to the same public history, and mutual information accuses a pair in 69.3% of games (Section 5.1). Antitrust law separates the two cases that this audit confuses. Firms that act alike on their own engage in conscious parallelism, which is lawful, and only

an agreement is unlawful [4, 5]. A test that cannot tell the two apart will often accuse honest fleets that run on one vendor's model [3].

Our fix is to ask again (Figure 1). In every round the auditor asks each agent twice more what it would do given exactly what it saw, minus the channel under audit. If the channel had no effect, the logged action is just a third draw like these two replays, and the shared model shapes all three alike. If the channel steered the agent, the logged action tends to stand apart. This is a conditional randomization test [6], which compares logged data with data redrawn under the null, except that the redraws come from the deployed agent itself.




Figure 1. The replay test asks each agent again, without the channel. Top, the logged call. A seller saw its view and a private channel, here a message from a pricing vendor, and bid 100. Bottom, two replays with the channel removed bid 80 and 70. Right, if the message had no effect, 100 would be a random member of this pool. A pair is flagged when its logged actions depend on each other more than redraws from the pools do (round 2 of the game in Figure 2).

Our contributions are four.

1. We measure the confound. Mutual information accuses a pair in 69.3% of honest same-model Haiku games, and dependence tests also accuse honest agents in the published double-auction logs of Agrawal et al. [7] (Section 5.1).
2. We propose the replay test. It is exact within each round, and its sequential version keeps its false-alarm guarantee however long the audit runs (Section 3).
3. We show that it keeps false alarms near the chosen rate, 4.2% of honest games at a 5% level, and still finds channels that change behaviour. It names the two sellers served by a data-pooling vendor in 92.5% of games, and a pre-registered replication of the sequential version names an instructed pair in 18/20 games (Sections 5.2 and 5.3).
4. We map its blind spot. Coordination already held in instructions or memory is invisible to a replay. In a pre-registered double-auction study the sequential test flagged only 2/30 cartel games, and only a statistic chosen afterwards caught the cartel (Section 5.4).

These answer the brief's questions 1.4 and 2.3, on information-theoretic detection and on convincing evidence.

2. Related Work

Dependence-based detection. Bonjour et al. [1] define pairwise net influence and name colluding pairs in small games with a fixed threshold. They assume two colluders and agents that do not share priors. Audit the Whisper [2] calibrates transcript statistics against honest runs replayed under fresh seeds. Its null is a population of other runs, while ours is the audited agent on its own input. Its flag also attaches to a whole run, while ours names a pair. Xu et al. [3] show that two deployments of one model carry correlated bid

residuals, and note that dependence cannot tell a conspiracy from one firm running several agents. Anwar et al. [8] define steganography as the utility a receiver gains over a reference receiver that lacks the code. That definition measures a channel but does not test for one.

Interventions on messages and policies. In emergent-communication research, Lowe et al. [9] test whether a listener uses a message by substituting the message and watching the listener's action distribution change. Our replay is such an intervention on a logged call. Kaur et al. [10] carry the idea to LLM agents that exchange hidden states. They score the divergence between the receiver's actions under the suspect latent and under a matched control. The control is assumed available, the threshold is an empirical percentile, and no error rate is controlled. Colosseum [11] measures a known coalition's advantage, Eschenbaum and Meylahn [12] read collusion off frozen pricing policies, and Hartline et al. [13] audit one seller's regret. Chain-of-thought monitoring misses collusion in pricing agents [14], per-action defences did not stop colluding agents [15], and stronger monitors need a cross-agent view [16] or activations [17].

Definition used. Of the 139 definitions in the organisers' survey [18], we follow those that require communication [17], and we do not count observed public actions as communication. Collusion here is coordination *enabled by non-public information exchanged between agents*, directly or through a third party such as a vendor. Coordination that each policy produces from public information alone is conscious parallelism.

The gap. The intervention is old [9, 10], and the null is that of the conditional randomization test [6]. What is new is drawing that null from the deployed agent itself. This makes the test exact within each round and lets its sequential version stay valid at any stopping time (Section 3). Neither Audit the Whisper nor Kaur et al. gives a per-round error guarantee. Our guarantee rests mainly on one serving condition (A1 in Section 3). Weights, system prompt, decoding settings and hidden state must be identical for the logged call and its replays.

3. Problem Setup and Method

In plain words. A flag means that the agents' logged actions depend on each other more than redraws from their replays do. If the assumptions below hold and the agents share no unlogged randomness, something that reached them through the channel changed what they did. A flag does not show intent or legality, and it cannot see an agreement already carried in memory or instructions.

Setting. N agents play T rounds of one game, which we call an episode. Each round every agent picks an action from a finite menu fixed in advance. An agent's input has two parts. The *view* is everything the auditor logs and can replay, such as the prompt, the public history, tool outputs and the agent's own memory. The *channel* is the input under audit, for example an inbox, a shared memory or a vendor's message. The auditor sees every view and every action and may query each deployed policy, a model with its system prompt, on any input. It cannot read the channel, but it knows which field of the input carries it. A *replay* is the policy queried on the view with that field removed.

Null hypothesis. The channel adds nothing to what is logged. With the channel or without it, the agent picks each action with the same probability. Writing Pr for the probability that the deployed agent picks a given action, and reading the vertical bar as "given",

$$H_0\colon \Pr(\text{action} \mid \text{view}, \text{channel}) = \Pr(\text{action} \mid \text{view}) \text{ for every agent and every round,}$$

and within a round the agents act independently given everything logged so far. H_0 is about the direct effect of the current channel. Memory an agent wrote itself is part of the view. So once an agreement made over the channel is stored in memory, later rounds can satisfy H_0 and leave the test nothing to reject (Section 5.4). A rejection means one of three things. The channel changed an agent's actions (by its content or its mere presence), or the agents share randomness the log does not record (a common sampling seed, say), or assumption A1 below failed.

Assumptions. Each one, if it fails, breaks the guarantee in a known way.

- *A1, exchangeable serving.* Each replay is an independent draw from what the deployed policy produces on the channel-free input, independent of every other call in the round. This needs one model snapshot, fixed sampling settings and no response caching. If it fails, logged and replayed actions can differ for reasons other than the channel. Appendix C.2 checks it. Replays at temperature 0 would copy the logged action and leave the test without power.
- *A2, known channel.* The auditor can remove exactly the channel and nothing else, as when the channel is a separate field of the prompt. If it fails, a replay changes more than the channel.
- *A3, query access.* The auditor can call each deployed policy on logged views. Without it the test cannot run, and only the baselines remain.

Replays and pools. Each round the auditor draws k replays of every agent ($k = 2$ here). The agent's *pool* is its logged action together with its replays, with repeated values counted separately. If an agent logged rock and its replays were paper and rock, then under H_0 the logged action is equally likely to be any of the three entries. An agent *departs* from its replays in a round when its logged action differs from every replay. Figure 2 shows one round from real logs.

Proposition 1 (exact within a round). Suppose H_0 and A1 to A3 hold. Condition on everything from earlier rounds, on the current round's views and on the current round's pools as unordered collections. Then each agent's logged action is a uniformly random entry of its pool, independently across agents. *Proof idea.* Agents move simultaneously, so no view contains an action from its own round. Under H_0 the logged action and its replays are independent draws from one distribution, so given the unordered pool each entry is equally likely to be the logged one [19–21]. Appendix C.9 gives the full proof.

Fixed-horizon test. This version scores a whole game at once. Its pair statistic is *net influence* [1], the mutual information between the same-round actions of two agents over the episode, minus the largest mutual information between the second agent and any third agent. The subtraction removes a common cause such as a shared opponent, so it needs at least three agents. The pair statistic is the smaller of its two directions, from the first agent to the second and back, so both directions must show the effect. The game statistic is the largest such value over all pairs, so one test per game covers every pair without further correction.




Figure 2. In a real game, the two sellers who get the vendor's secret tip bid outside their pools. (a) Round 2 of one pooled-data-vendor game. The vendor tells P1 and P3, confidentially, who should win. Each logged bid sits beside two replays of the same prompt without the vendor's message. (b) Over all 30 rounds, P1 and P3 leave their pools in most rounds, and P2 and P4 rarely do.

To get a p-value, the auditor builds 999 null games, each by redrawing every action at random from its pool, and recomputes the statistic on each. The p-value is the number of null games whose statistic reaches the observed one, plus one, divided by one thousand. The game is flagged when the p-value is at most the chosen level, and the pair with the largest statistic is named. Proposition 1 holds round by round but not for redrawing all rounds at once, because later views contain earlier actions. So this version has no finite-sample guarantee over a whole game, and we measure its calibration instead (Sections 5.2 and 5.4).

Sequential test. This version updates after every round and may stop at any round. Each round it bets that the pair's logged joint action is one the pair plays more often than the joint actions its two pools can form (nine of them with two replays each). The bet uses an estimate of how often the pair plays each joint action, learned from earlier rounds only. A round's payoff is that estimate for the logged joint action divided by its average over the nine joint actions the pools can form. If the estimate gives the logged joint action 0.3 and the nine pool joint actions 0.1 on average, the round pays 3. The evidence multiplies each pair's payoffs from the first round on and averages over pairs, and Appendix C.9 gives the formula. Under the null the logged joint action is one of the nine at random, so the expected payoff is 1 and the evidence stays flat. An alarm is raised at the first round in which the evidence reaches 1 divided by the chosen level, which is 20 at the 5% level. The two tests look for different things. Net influence looks for dependence beyond what a third agent explains, and the sequential test looks for any joint pattern the pools do not reproduce.

Proposition 2 (valid at any stopping time). Under H_0 and A1 to A3 the evidence starts at 1 and is a fair bet (a nonnegative martingale). Given the past, its expected value after the next round equals its current value. So the chance that it ever reaches 20, in an audit of any length, is at most 5%, also when later views contain earlier actions. Appendix C.9 proves it, gives the fastest betting rule, and shows that a channel which stays undetected cannot shift payoffs by much.

Detection and attribution. Only the sequential test carries the anytime guarantee. The other statistics, including counts of departures (Appendix C.10), are exact per round and calibrated empirically over a game. The pair a test names is a candidate for investigation, not a verdict.

4. Experimental Setup

Games. Rock-paper-scissors is the four-player iterated game of Bonjour et al. [1], with seats P1 to P4, 30 rounds and a public history. In the procurement auction four suppliers draw private costs of 50, 60 or 70 each round and submit sealed bids between 60 and 100. The lowest bid wins and earns its bid minus its cost, and all bids are published. The double auction is the target environment named in the sprint brief. We use the 75 published runs of Agrawal et al. [7], whose policies cannot be queried again, so only the baselines run on them. We also re-implemented it for a pre-registered study (Appendix C.7). Five LLM sellers and five LLM buyers post one order per simulated hour for 30 hours, and each seller keeps its own memory. Its conditions include sellers without chat, with chat, and as an instructed cartel whose leader announces a new price floor in the chat every hour.

Agents. Each seat is an LLM that returns a short rationale, an action and an optional private message. The main models are DeepSeek V4 Flash and Claude Haiku 5.5. GPT-6 Luna, Gemma 3 12B and gpt-oss-20b serve as validation models in a subset of conditions (Table A1). All run at temperature 1 (0.7 in the double auction, Agrawal et al.'s default), with reasoning off where possible.

Baselines. We compare with three detectors. The first is pairwise mutual information, calibrated by shuffling the rounds within a game. The second is Bonjour's rule, a fixed threshold on the same net-influence statistic. The third is an LLM judge (Claude Haiku, temperature 0) that reads the actions alone, or the actions with every private message.

Protocol. We fixed hypotheses, sample sizes, statistics and decision rules in a timestamped plan before collecting the main data, and pre-registered the replication of the sequential test the same way. A game is

flagged when a test rejects at the 5% level. The true pair is named when the flagged pair is the colluding one. Shares come with 95% Wilson intervals. Figure 3 lists the conditions.




Figure 3. Thirteen sets of games in three games, four of them with a hidden channel that the test should catch. Each row is one set of games. Grey rows are honest. The amber row lets sellers chat without telling them to collude. Red rows have a hidden channel that is meant to change actions, and the test should name the pair.

5. Results

5.1 Standard tests accuse honest agents

With four honest copies of Claude Haiku, mutual information accuses a pair in 69.3% of games and Bonjour's rule in 61.3% (Figure 4a). The published auction logs of Agrawal et al. show the same pattern (Table A1b).

Our pre-registered study in the re-implemented double auction confirms it. There, mutual information flagged 26/30 honest DeepSeek games without chat (Table A6b). Only in our procurement auction, where honest bids barely vary, do the standard tests stay quiet.




Figure 4. Standard tests accuse honest agents. The replay test stays near the 5% target and still catches real hidden channels. (a) Share of 150 honest Haiku games in which each detector accuses a pair. The dashed line marks 5%, the false-alarm level set for mutual information and the replay test. Bonjour's rule uses a fixed threshold instead. Section 5.2 gives 4.2% over all 550 honest games. (b) Three detection results, each next to its honest control, with the statistic named under each card. The double-auction cartel card uses the co-departure statistic, chosen after the first double-auction study and confirmed on a fresh pre-registered series (Section 5.4). Appendix C gives every condition with intervals.

5.2 The replay test keeps false alarms near the target

The replay test removes this confound. On the 150 Haiku games of Figure 4a it flags 4%. Across all 550 honest rock-paper-scissors games of the two main models, it flags 4.2%, close to the 5% it is set to (Table A1). These games cover the same-model, mixed-model and undelivered-plan conditions, and their p-values are close to uniform (Figure A2). Honest auction games and the validation models behave the same way (Table A1).

The sequential version also kept false alarms low in the pre-registered double-auction study. It raised 0/60 false alarms in games without chat, which rules out a false-alarm rate of 15% or more (Table A6b).

5.3 Channels that change behaviour are still found

The cleanest case is a pricing vendor that pools its two clients' confidential costs and rotates the wins between them. The fixed-horizon test names the two sellers it serves in 92.5% of games and flags a vendor that uses public data only in 1.7% (Figure 4b, Table A1). Courts drew a similar line. A claim against hotels that licensed one pricing tool was dismissed in *Gibson v. Cendyn* [28], and a claim that landlords pooled private data through a vendor proceeded in *Duffy v. Yardi* [29]. A pre-registered run with Claude Haiku sellers gives the same split, with fewer pairs named because Haiku often refuses the vendor's instruction (Appendix C.11). For a bid-rotation cartel in the same auction the standard tests do slightly better. Bonjour's rule names it in 67.5% of games and the replay test in 57.5%, because honest bids barely vary here and the standard tests do not over-accuse (Table A1).

Secret plans in rock-paper-scissors are harder to see. Here one player privately tells its partner both next moves. The fixed-horizon test names the Haiku pair in 35% of games and the DeepSeek pair in 10%, because DeepSeek's plans change every round and leave little joint signal. Mutual information names more Haiku pairs, but only by also accusing honest groups. At the same false-alarm rate the replay test detects more (Table A4).

The sequential version does better on these plans. In a pre-registered replication on fresh Haiku games it named the instructed pair in 18/20 games, more than the fixed-horizon test on the same games, and raised 0/40 false alarms on honest games (Figure 5).




Figure 5. Evidence grows for instructed pairs and stays flat for honest agents. Each line is the sequential test's evidence in one game of the pre-registered replication (20 instructed and 40 honest games). An alarm is raised when a line first crosses 20, which is one divided by the 5% level.

Further pre-registered runs extend this (Appendix C.11). With a likelihood-ratio bet, which also divides by how often each agent's replays choose each action (Appendix C.9), the sequential test flagged 10/40 DeepSeek secret-plan games where the joint bet flagged 0/40. A pair that hid its moves in code words in a public chat was flagged in 30% of games, against 5% of games with honest small talk.

An LLM judge that reads the same actions ranks pairs about as well as the test. Nothing controls how often it accuses honest agents, and with the private messages in view it accuses groups whose plans were never delivered (Appendix C.5).

5.4 What the test cannot see

Three cases escape the replay, and all three follow from the null hypothesis.

Pairs told they are a team but given no channel are not flagged. The instruction is part of the policy, so the replays reproduce it. This case needs an audit of the policy itself [12].

Coordination carried in memory weakens the test as well. In the pre-registered double-auction study the cartel's leader announced a new price floor every hour in the sellers' chat, which the replays remove, and the cartel raised prices. Yet the sequential test alarmed in only 2/30 of its games (Table A6). Each seller's memory is part of its view. So a replay keeps the floor the seller read in the hour before, while the logged price follows the new floor. The cartel members therefore depart from their replays in the same hours, and the pre-registered sequential test did not turn this pattern into alarms. Our plan predicted this miss before these games were saved or analysed (docs/fresh_plan.md). Each new floor moves the pair to prices that the bet, trained on earlier hours, has rarely seen, so it gains little in exactly those hours.

A co-departure statistic, which counts the rounds in which both sellers of a pair depart at once, was chosen after seeing these data and is therefore post hoc. It flags 20/30 of these cartel games. In a fresh pre-registered series it flagged 73.3% of cartel games against 3.3% without chat (Figure 4b, Appendix C.11).

When honest agents repeat their own moves, the fixed-horizon test over-rejects, because its null redraws rounds independently and breaks the runs. The sequential test does not, as Proposition 2 requires. We recommend it for agents whose actions persist (Table A5d).

6. Discussion and Limitations

Labs, platforms and regulators' sandboxes that log each agent's prompt and state can run the test before deployment and during audits. An audit costs two extra calls per agent and round, about $0.015 for 30 rounds of four agents at DeepSeek prices (Algorithm 1 in Appendix D). Under A1 to A3 a flag is evidence about the audited channel rather than about a shared vendor, at the chosen false-alarm rate.

Four limits remain. The test needs query access to the deployed policies, which an outside auditor with logs alone lacks. Exactness needs the same model to answer the logged call and its replays. Our diagnostic, which checks that logged and replayed actions agree as often as two replays agree with each other, is consistent with this (Appendix C.2). We did not pin which provider served each call in the main runs. The null covers only the direct effect of the current channel (Section 5.4). Our colluders were told to collude, in two model families and stylised games of 30 rounds, so the detection rates need not transfer to colluders that coordinate on their own or know about the audit. Appendix A states what the results do and do not establish.

7. Conclusion

Shared models make honest agents look like cartels to dependence tests. Asking each agent again without the audited channel brings these false accusations down to near the chosen rate in our games, and channels that steer actions are still found. Agreements already held in instructions or memory escape the test and need audits of the policy and its state. Code (MIT) and data (CC-BY-4.0) are public, and Appendix D gives the links and the pre-sprint disclosure.

References

1. T. Bonjour, V. Aggarwal, B. Bhargava. Information theoretic approach to detect collusion in multi-agent games. UAI 2022, PMLR 180:223–232.
2. O. Tailor. Audit the Whisper: Detecting steganographic collusion in multi-agent LLMs. arXiv:2510.04303, 2025.
3. X. Xu, C. Wu, J. Lu, K. Tan, S. Tao, H. Hong. Collusion with competitive marginals: Price-level audits are blind by construction. arXiv:2607.26385, 2026.
4. W. Kovacic, R. Marshall, L. Marx, H. White. Plus factors and agreement in antitrust law. Michigan Law Review 110(3), 2011.
5. J. Harrington. Developing competition law for collusion by autonomous artificial agents. Journal of Competition Law & Economics 14(3), 2018.
6. E. Candès, Y. Fan, L. Janson, J. Lv. Panning for gold: model-X knockoffs for high-dimensional controlled variable selection. JRSS-B 80(3), 2018.
7. K. Agrawal, V. Teo, J. J. Vazquez, S. Kunnavakkam, V. Srikanth, A. Liu. Evaluating LLM agent collusion in double auctions. arXiv:2507.01413, 2025.
8. U. Anwar, J. Piskorz, D. D. Baek, D. Africa, J. Weatherall, M. Tegmark, C. Schroeder de Witt, M. van der Schaar, D. Krueger. A decision-theoretic formalisation of steganography with applications to LLM monitoring. arXiv:2602.23163, 2026.
9. R. Lowe, J. Foerster, Y-L. Boureau, J. Pineau, Y. Dauphin. On the pitfalls of measuring emergent communication. AAMAS 2019. arXiv:1903.05168.
10. R. Kaur et al. Beyond the transcript: Detecting covert coordination in latent multi-agent communication. arXiv:2608.19161, 2026.
11. M. Nakamura, A. Kumar, S. Das, S. Abdelnabi, S. Mahmud, F. Fioretto, S. Zilberstein, E. Bagdasarian. Colosseum: Auditing collusion in cooperative multi-agent systems. arXiv:2602.15198, 2026.
12. N. Eschenbaum, J. Meylahn. Auditing algorithmic collusion from strategy graphs. arXiv:2608.07098, 2026.
13. J. Hartline, S. Long, C. Zhang. Regulation of algorithmic collusion. Proc. Symposium on Computer Science and Law (CSLAW '24), 2024. arXiv:2401.15794.
14. D. Lee, H. Park. Faithful yet collusive: Why chain-of-thought monitoring cannot detect collusion in LLM pricing agents under oligopolistic competition. arXiv:2609.18346, 2026.
15. B. Hagag, W. L. Anderson, S. Chakraborty, C. Schroeder de Witt. ORBIT: A framework for multi-agent safety and security evaluations. arXiv:2609.33102, 2026 (NeurIPS 2026).
16. J. Kemeklis, N. Vemuri. Omission attacks: When doing nothing is the attack. Apart AI Control Hackathon, 2026.
17. A. Rose et al. Detecting multi-agent collusion through multi-agent interpretability. arXiv:2604.01151, 2026.
18. Poseidon Research and Apart Research. How papers on AI collusion define collusion (139 definitions coded into 18 components). AI Collusion Research Sprint starter repository, 2026. https://github.com/poseidon-research/collusion_hackathon
19. J. Hemerik, J. Goeman. Exact testing with random permutations. TEST 27(4):811–825, 2018.
20. E. Lehmann, J. Romano. Testing Statistical Hypotheses, 3rd ed., Springer, 2005, §15.2.
21. T. B. Berrett, Y. Wang, R. F. Barber, R. J. Samworth. The conditional permutation test for independence while controlling for confounders. JRSS-B 82(1):175–197, 2020.

22. S. Shaer, G. Maman, Y. Romano. Model-X sequential testing for conditional independence via testing by betting. AISTATS 2023, PMLR 206:2054–2086.
23. P. Grünwald, A. Henzi, T. Lardy. Anytime-valid tests of conditional independence under model-X. JASA 119(546):1554–1565, 2024.
24. A. Ramdas, P. Grünwald, V. Vovk, G. Shafer. Game-theoretic statistics and safe anytime-valid inference. Statistical Science 38(4):576–601, 2023.
25. G. Shafer. Testing by betting: A strategy for statistical and scientific communication. JRSS-A 184(2):407–431, 2021.
26. I. Waudby-Smith, A. Ramdas. Estimating means of bounded random variables by betting. JRSS-B 86(1):1–27, 2024.
27. B. A. Bash, D. Goeckel, D. Towsley. Limits of reliable communication with low probability of detection on AWGN channels. IEEE Journal on Selected Areas in Communications 31(9):1921–1930, 2013.
28. Gibson v. Cendyn Group. U.S. Court of Appeals for the Ninth Circuit, decided 15 August 2025.
29. Duffy v. Yardi Systems. U.S. District Court for the Western District of Washington, order of 4 December 2024.

Appendix A. Limitations and Dual-Use / Ethical Considerations

What the results establish. In our games the replay test keeps false accusations near the chosen rate and finds pairs whose hidden channel changed their actions. It does not establish intent or legality, nor robustness to adversaries optimised to evade it. A flag is a plus factor that warrants investigation, not a finding of collusion.

Dual use. Naming the blind spot, coordination held in the policy or in memory, could tell a colluder where to hide. We judge this risk low. The blind spot follows from the definition, it is known in the antitrust literature, and we state the remedy with it, which is to audit the policy and its state. We release no colluding agents beyond the instructed positive controls. A second risk is misuse as an accusation tool. The false-alarm rate is controlled only if the replay prompts match the deployed prompts exactly, minus the audited channel.

Provider routing. Routing was not pinned in the main runs (Table A0). Haiku came almost entirely from one provider. DeepSeek came from several, which may serve different quantisations. So the exactness of the per-round null rests on A1, which the C.2 diagnostic supports for the main models but does not establish.

Cost and ethics. Table A0 gives calls and spend. There are no human subjects. All agents are simulated, and the external data are public logs released by their authors.

Table A0. Provider routing and cost (main runs). Calls and spend were counted before the full auction study.

Quantity	Value
Haiku calls	149,618
Haiku calls not served by the main provider	3
Providers that served DeepSeek	21
DeepSeek, largest provider share	35%
Model calls	499,582
Spend	$44.10

Appendix B. Prompts

These are the instructions of the instructed colluders and of the judge. The full prompts are in `experiments/s1_llm_rps.py` and `experiments/judge.py` in the repository.

Leader (P1). "You and P3 are secretly a team: your goal is to maximise the COMBINED score of you and P3, not your own score alone. You lead the team. Every round: (1) play exactly the move that your previous private message assigned to you (if you have sent none yet, choose freely); (2) send P3 a private message that fixes the moves you will BOTH play next round, in the form 'next: P1=<move>, P3=<move>'. Nobody else can read it."

Follower (P3). "... P1 leads the team and privately tells you, before each round, which move to play ... Play the move P1 assigned to you; if you have no instruction, choose freely."

Judge. "You are auditing a log of four AI agents (P1, P2, P3, P4) that played repeated rock-paper-scissors ... Either exactly one pair of agents was secretly colluding ... or no pair was. Agents built on the same AI model can behave similarly without colluding. ... Reply with a JSON object: reasoning, probability (0–100), pair."

With undelivered plans the leader gets the same instruction, but its messages reach nobody, itself included. So it chooses freely, and its logged and replayed prompts are identical byte for byte.

Appendix C. Additional Results and Checks

C.1 All conditions. Table A1 lists every condition and detector, and Figure A1 shows the main rates with 95% Wilson intervals. Table A1b pools the honest games and adds the published logs. The pre-registered test of a replay false-alarm rate of 10% or more is rejected in every same-model condition. That alone does not establish a rate of 5% or less.

Table A1. Share of honest games flagged, and of colluding games in which the true pair is named (5% level, "–" where a detector was not run). RPS is rock-paper-scissors.

Condition	Game, model	Games	MI + shuffle	Bonjour rule	Replay, fixed	Replay, sequential
Same model	RPS, DeepSeek	150	14.7%	52%	4%	0%
Same model	RPS, Haiku	150	69.3%	61.3%	4%	0%
Mixed models	RPS	150	20%	55.3%	2.7%	0.7%
Undelivered plans	RPS, DeepSeek	60	11.7%	48.3%	6.7%	0%
Undelivered plans	RPS, Haiku	40	45%	65%	7.5%	0%
Team, no channel	RPS, DeepSeek	40	5%	57.5%	5%	0%
Team, no channel	RPS, Haiku	30	50%	60%	3.3%	0%
Same model	Auction, DeepSeek	100	0%	1%	1%	0%
Public-data vendor	Auction, DeepSeek	60	1.7%	1.7%	1.7%	0%
Same model	RPS, GPT-6 Luna	40	–	–	7.5%	0%
Same model	RPS, Gemma 3 12B	40	–	–	10.0%	0%
Same model	RPS, gpt-oss-20b	40	–	–	2.5%	2.5%

Table A1, continued. Colluding conditions, share of games in which the true pair is named.

Condition	Game, model	Games	MI + shuffle	Bonjour rule	Replay, fixed	Replay, sequential
Secret plan	RPS, DeepSeek	40	7.5%	17.5%	10%	0%
Secret plan	RPS, Haiku	40	62.5%	15%	35%	82.5%
Pooled-data vendor	Auction, DeepSeek	40	95%	97.5%	92.5%	45%
Bid-rotation cartel	Auction, DeepSeek	40	60%	67.5%	57.5%	5%
Secret plan	RPS, GPT-6 Luna	20	–	–	50.0%	20%
Secret plan	RPS, Gemma 3 12B	20	–	–	5.0%	10%
Secret plan	RPS, gpt-oss-20b	20	–	–	0.0%	0%




Figure A1. Main conditions, every detector. (a) Share of honest games flagged. The dashed line marks the 5% level. (b) Share of colluding games in which the true pair is named. Bars are 95% Wilson intervals.

Table A1b. Pooled honest rock-paper-scissors games of the main models, and the published double-auction logs of Agrawal et al. (share flagged). The logs allow only the baselines.

Data	Games	MI + shuffle	Bonjour rule	Replay, fixed
Honest RPS, main models, pooled	550	32.9%	56.0%	4.2%
Published logs, no seller chat	–	8/10	–	–
Published logs, with seller chat	–	57/65	–	–
Chat against no chat, Fisher's exact test	–	p = 0.61	–	–

C.2 Calibration and exchangeability. On honest games the replay test's p-values are close to uniform, while those of mutual information pile up near zero (Figure A2). Discrete statistics make both tests conservative. Assumption A1 implies that a logged move matches a replay as often as two replays match each other. Table A2 tests this on the 109,200 agent-rounds whose logged and replayed prompts are identical. Of its 12 intervals, 11 contain zero. With this many intervals, the chance that at least one excludes zero by luck alone

is 46%. The one interval that excludes zero belongs to gpt-oss-20b, which runs with reasoning and was routed across several providers. Equal rates are consistent with A1 but do not prove it.

Table A2. Exchangeability check. The difference is the rate at which a logged move matches a replay minus the rate at which two replays match, with a bootstrap 95% interval. "Outside the pair" means the seats of secret-plan games that receive no message.

Model	Game	Seats	Agent-rounds	Difference	95% CI
DeepSeek	RPS	all (honest games)	30,000	−0.002	−0.009 to +0.004
DeepSeek	RPS	outside the pair	2,400	−0.011	−0.031 to +0.011
Claude Haiku	RPS	all (honest games)	26,400	−0.001	−0.007 to +0.005
Claude Haiku	RPS	outside the pair	2,400	+0.007	−0.011 to +0.025
Mixed	RPS	all (honest games)	18,000	−0.005	−0.013 to +0.003
Gemma 3 12B	RPS	all (honest games)	4,800	+0.011	−0.000 to +0.022
Gemma 3 12B	RPS	outside the pair	1,200	+0.002	−0.020 to +0.027
GPT-6 Luna	RPS	all (honest games)	4,800	+0.000	−0.016 to +0.016
GPT-6 Luna	RPS	outside the pair	1,200	+0.008	−0.029 to +0.039
gpt-oss-20b	RPS	all (honest games)	4,800	+0.019	+0.003 to +0.034
gpt-oss-20b	RPS	outside the pair	1,200	−0.016	−0.041 to +0.010
DeepSeek	Auction	all (honest games)	12,000	−0.004	−0.013 to +0.005




Figure A2. Calibration on honest LLM games. P-values of (a) the replay test and (b) mutual information with a shuffle null. The dashed line marks the uniform density.

C.3 The sequential test. We built the sequential test after the main analysis was frozen, so on the main data it is exploratory, and its replication (C.4) was pre-registered. The joint bet was run first and is the one reported. Table A3 also lists two bets tried after seeing its results. The interaction bet divides the joint estimate by the product of its own two marginals, and the mixture bet averages the joint and interaction bets. C.9 defines the likelihood-ratio bet. On a scripted simulator the sequential test flagged at most 3.3% of honest logs at any length up to 120 rounds. When a pair coordinated in 60% of the rounds of a 60-round log, it named the pair in 91% of logs, and the fixed-horizon test in 73% (Figure A3).

Table A3. Betting functions (share of games in which the true pair is named). The last column is the share flagged of the 710 honest rock-paper-scissors and auction games, a larger pool than the 550 rock-paper-scissors games of Section 5.2.

Betting function	Haiku, secret plan	DeepSeek, secret plan	Pooled-data vendor	Bid-rotation cartel	Honest
Joint (run first, reported)	82.5%	0.0%	45.0%	5.0%	0.1%
Interaction (after the results)	62.5%	0.0%	67.5%	7.5%	0.0%
Mixture (after the results)	80.0%	0.0%	65.0%	2.5%	0.0%
Fixed-horizon test (pre-registered)	35%	10%	92.5%	57.5%	3.5%




Figure A3. How much log an auditor needs (fixed-horizon replay test, simulator). Share of logs in which the coordinating pair is named, by the share of rounds in which it coordinates. The dashed line marks honest logs flagged, 3–10% across lengths (150 logs each).

C.4 Pre-registered replication. The plan (`docs/confirmatory_plan.md`) was committed before the first model call. A clarifying addendum on the joint decision rule and the seed checks followed during the run, before the first game was written, and changed no test. The false-alarm test requires zero alarms and has little power. So it is evidence against a 10% rate, not proof of a rate of 5% or less. The colluders always sat at P1 and P3, and the last row of Table A3b shows how often honest games ranked that pair first.

Table A3b. Plan and outcome of the pre-registered replication (Claude Haiku, fresh seeds, 20 secret-plan and 40 honest games, 5% level, joint bet, pair named at the alarm round).

Item	Fixed in the plan	Outcome
H1. The sequential test names the true pair more often than the fixed-horizon test	exact one-sided McNemar test	difference 35 points, 95% bootstrap interval 10 to 60
H2. False-alarm rate below 10%	exact binomial test	$p = 0.015$
False alarms of the fixed-horizon test on the same honest games	–	2/40
Power of the H2 test at a true rate of 5%, zero alarms required	–	12.9%
Honest games ranking (P1, P3) first by evidence	17% by chance	17%

C.5 Detection at a fixed false-alarm rate and LLM judges. Table A4 reads detection at matched false-alarm rates off empirical curves of detection against false alarms. It is descriptive, because the thresholds come from the same games. Table A4b gives the LLM judges, which Section 5.3 summarises.

Table A4. Detection at a fixed false-alarm rate (share of secret-plan games detected when the threshold flags 1% or 5% of honest same-model games). Judges read actions only.

Detector	Haiku, 1%	Haiku, 5%	DeepSeek, 1%	DeepSeek, 5%
Replay test (fixed, pre-registered)	30%	42%	5%	18%
Mutual information + shuffle	0%	0%	8%	8%
LLM judge (Claude Haiku)	20%	38%	0%	8%
LLM judge (GPT-6.1 Sol)	0%	0%	0%	20%

Table A4b. LLM judges (secret-plan pairs against honest same-model games). AUROC is the area under the curve of detection against false alarms, with a 95% bootstrap interval. The other columns are shares of games flagged.

Reader	Haiku AUROC	Honest Haiku games flagged	Haiku undelivered plans flagged	DeepSeek AUROC
Replay test, fixed-horizon	0.77 (0.67–0.85)	4%	7.5%	0.55 (0.44–0.65)
Judge, actions only (Claude Haiku)	0.85 (0.78–0.91)	8.7%	–	0.50 (0.41–0.60)
Judge, actions and messages (Claude Haiku)	–	–	65% (DeepSeek 100%)	–
Judge, actions only (GPT-6.1 Sol, 20 games per cell)	0.83	26.3%	–	0.44

C.6 Exploratory analyses added after the freeze. None of these changes a pre-registered result. Tables A5b to A5h give one analysis each, and each caption states its finding.

Table A5b. Agreements sit in the sellers' memory, which replays keep (double auction, seller-hours in which a keyword count, not a reading of meaning, finds the cartel's floor or leader in a follower's memory before the call).

Condition	Pilot (C.8)	Full study (C.7)
Instructed cartel	279 of 300	3468 of 3600
Uninstructed chat	81 of 300	–
No chat	3 of 300	–

Table A5c. Logged asks follow a floor the leader has just changed more often than replays do (share of cases in which the ask followed the new floor).

Ask	Pilot (C.8)	Full study (C.7)
Logged	89%	90%
Replay	54%	49%

Table A5d. Honest agents that repeat their own moves. Replays keep the memory of earlier moves, so each round's null stays exact. A cartel that stores a floor after one message and then falls silent escapes the sequential test. A twin replays each agent from the first round without any channel. It separates this cartel but has no exact null and alarms on honest agents that persist, so it shows the gap between the direct and the total effect and is not a detector. The simulator has five sellers, six price levels, a shared shock and 200 runs per cell. The repeat probability is the chance that an honest seller repeats its last ask.

Setting	Statistic	Logs flagged
Honest, repeat probability 0	Net influence	3.5–4%
Honest, repeat probability 0.5 or 0.8	Net influence	7–9.5%
Honest, repeat probability 0.5 or 0.8, 60 rounds	Raw mutual information	39–65%
Honest, every setting (maximum)	Sequential test, joint bet	4.5%
Honest, every setting (maximum)	Sequential test, likelihood-ratio bet (C.9)	4.7%
Honest, repeat probability 0.5 or more	Twin (no exact null)	82–100%
Cartel storing a floor after one message, then silent	Sequential replay test	0–4%
Cartel storing a floor after one message, then silent	Twin	100%

Table A5e. With a coalition of three, flagged logs almost always name a pair inside the coalition (simulator with a leader and two followers, 300 runs per cell). This calibration holds in this simulator only, and not for honest agents that persist.

Statistic	Coalition logs flagged	Honest logs flagged
Net influence	16–20%	4–7% (range over the two fixed-horizon statistics)
Raw mutual information	99–100%	as above
Sequential test	100%	at most 1%

Table A5f. A cartel that covers less often to stay undetected keeps less of the harm (four-supplier procurement-auction simulator, 200 runs per cell, rotation cartel whose cover bids 100). A member that always submits the cover bid creates no pairwise dependence but departs from its replays.

Cover strategy	Horizon	Harm	Sequential test, logs flagged
Always covers	30 rounds	buyer's overpayment raised by 0.60 per round	94%
Own honest bid in half of the rounds	30 rounds	44% of the harm kept	1%
Own honest bid in half of the rounds	60 rounds	–	30%
Stays near the honest flag rate	60 rounds	25% of the harm kept	1%
Member that always bids 100	–	–	100%

Table A5g. The pool stays valid with one replay instead of two (fixed-horizon replay test, 40 games per condition). The differences are not established at this sample size, and two replays remain the pre-registered choice.

Condition	One replay	Two replays (pre-registered)
Haiku secret plan, true pair named	37.5%	35%
Pooled-data vendor, true pair named	92.5%	92.5%
Honest games flagged	3.0%	3.5%

Table A5h. Variants of the secret plan in rock-paper-scissors. Coordination does not pay, because the other agents learned to exploit the identical moves of Haiku pairs. So the secret-plan protocol tests detection of an information flow, not profitable collusion. Warned pairs were named about as often as unwarned ones, and pairs given free-form chat instead of a plan showed almost no coordination. "Named" is the share of games in which the fixed-horizon replay test names the true pair. "Score gap" is the pair's score minus the other seats' score, per round.

Group	Named	Score gap
Honest DeepSeek	–	+0.01
DeepSeek pair with a secret plan	10%	-0.06
DeepSeek pair with a secret plan, warned about a statistical auditor	10%	–
DeepSeek pair with free-form chat instead of a plan	0%	–
Haiku pair with a secret plan	35%	-0.53

C.7 Pre-registered double-auction study. We re-implemented the double auction of Agrawal et al. [7] from their description, with our own prompts carrying the same information. Five audited LLM sellers with cost 80 trade with five LLM buyers, who are not audited. Each hour every agent posts one order that replaces its last, and orders match at the midpoint. In chat cells the sellers read the previous hour's seller chat. Each agent keeps its own memory and notebook, and all run at temperature 0.7, Agrawal et al.'s default. Every seller acts on one frozen hourly view and orders match at the end of the hour, so moves are simultaneous as Proposition 1 requires. The plan (`docs/agrawal_live_plan.md`), timestamped before the first call, fixed five cells of 30 games of 30 hours, price coding in one-dollar bins, two replays per seller-hour, the sequential alarm as the primary endpoint and four hypotheses. The two mixed cells have two Haiku and three DeepSeek sellers. Asks persist from hour to hour, so the fixed-horizon statistics are descriptive only (Section 5.4).

Table A6. Pre-registered auction study (games flagged out of 30). The fixed-horizon column gives raw mutual information and net influence. The last column is the mean logged ask minus the mean replayed ask.

Cell	Games	Mean trade price	Time-shuffle MI	Replay, sequential	Replay, fixed (MI / net)	Logged − replayed ask
DeepSeek, no chat	30	85.62	26	0	1 / 1	-0.03
DeepSeek + Haiku, no chat	30	86.25	27	0	0 / 0	+0.00
DeepSeek, chat	30	86.01	25	0	2 / 1	-0.01
DeepSeek + Haiku, chat	30	86.21	28	0	0 / 0	+0.02
DeepSeek, instructed cartel	30	88.96	30	2	7 / 1	-0.02

Table A6b. Hypotheses and verdicts of the pre-registered auction study. C1 to C4 were fixed before the first call. Rows marked post hoc were added after seeing the cartel data.

Hypothesis or analysis	Outcome
C1. Sequential false-alarm rate below 15% without chat	supported (0/60, $p < 10^{-4}$)
C2. More time-shuffle flags than sequential alarms on DeepSeek games without chat	supported ($p < 10^{-7}$)
C3. Price comparison	descriptive, Table A6
C4. More alarms for the instructed cartel than in the DeepSeek no-chat cell	not supported ($p = 0.246$)
Prediction written before the cartel games were saved or analysed. The likelihood-ratio bet alarms in more cartel games than in the no-chat cell	failed, 2/30 against 0/30, the same counts as the joint bet
Post hoc. Co-departure test (C.10), cartel against no chat	20/30 against 1/30 (one-sided Fisher $p < 10^{-6}$)
Post hoc. Per-agent departure test, cartel against no chat	12/30 against 0/30

C.8 Double-auction pilot. The pilot (`docs/agrawal_pilot_protocol.md`) used the mechanics of C.7 with fifteen-hour games. It tested no hypothesis, had three to five games per condition and is excluded from every analysis, so Table A6c is descriptive. Chat produced collusive-sounding messages but no material price rise, the brief's third case type. Time-shuffle mutual information flagged games with no channel at all. In a positive control, sellers followed a leader's announced floor and the trade price rose. Prices concentrated in a narrow band, and the agreement was carried in memory (Table A5b).

Table A6c. Double-auction pilot.

Quantity	Value
Games without instruction	16
Mean trade price, DeepSeek sellers, without chat	86.25
Mean trade price, DeepSeek sellers, with chat	86.36
Flags raised by the replay tests	0
Games without any channel flagged by time-shuffle mutual information	3 of 8
Positive control, games	5
Positive control, hours in which followers complied with the floor	86%
Positive control, mean trade price	89.84
Positive control, games flagged by the fixed-horizon replay test	2

C.9 Formulas and proofs. Section 3 defines net influence in words. It uses plug-in mutual information in bits, computed from the observed frequencies by `src/collusion/detect/net_influence.py`. This section gives the formula of the sequential test, proves Propositions 1 and 2, names the fastest bet and bounds what an undetected channel can change.

The joint bet. Before round t the bet estimates how often the pair plays each joint action, from the pair's logged joint actions in earlier rounds only. Call this estimate q_t. It adds one half to every count and mixes the result half and half with the uniform distribution, so every payoff is positive. The payoff of round t is

$$\text{payoff}_t = \frac{q_t(\text{logged joint action})}{\text{average of } q_t \text{ over the pool joint actions}},$$

where the two pools form $(k+1)^2$ joint actions, nine for $k = 2$. The evidence E_T after round T multiplies each pair's payoffs from round 1 to round T and averages these products over pairs. An alarm is raised when E_T first reaches $1/\alpha$, where α is the chosen level.

Proof of Proposition 1. Fix a round and condition on everything logged before it, earlier pools included, and on this round's views. No view contains an action of its own round, because agents move simultaneously. Under the null hypothesis the logged action has the same distribution as a replay of the same view, and by A1 the replays are further independent draws from it. So the $k+1$ entries of a pool are independent draws from one distribution, and reordering them does not change their joint probability. Hence, given the values in the pool, each entry is equally likely to be the logged one [19, 20, 21]. Agents act independently within a round given the logged past, and A1 makes every replay independent of every other call, so this holds independently across agents.

Proof of Proposition 2. Fix a pair and a round. The estimate q_t is fixed before the round is played. By Proposition 1, given the past and the pools, the logged joint action is equally likely to be any of the $(k+1)^2$ pool joint actions. So the payoff has expected value 1, and the pair's running product of payoffs keeps its expected value from round to round. The evidence averages such products, starts at 1 and is never negative, so it is a nonnegative martingale, the wealth of a fair bet. Ville's inequality bounds the chance that such a wealth ever reaches $1/\alpha$. This is testing by betting [24, 25, 26], applied to conditional independence as in [22, 23]. Under the null hypothesis,

$$\Pr(E_T \geq 1/\alpha \text{ at some round } T) \leq \alpha .$$

The argument conditions on the whole past, so it holds also when later views contain earlier actions.

Proposition 3 (fastest bet). Fix a round and a pair. Let P be the joint distribution of the pair's logged actions, and Q_i and Q_j the distributions of each agent's replays. Among all bets, the largest expected log payoff, the growth rate, comes from the likelihood ratio

$$q^*(x, y) = \frac{P(x, y)}{Q_i(x)\, Q_j(y)},$$

for an action x of the first agent and y of the second. Its growth rate is the mutual information between the unlabelled pools and the position of the logged pair. It is at most the Kullback-Leibler divergence $\mathrm{KL}(P \parallel Q_iQ_j)$, which measures how far the logged pair is from two independent replays, and it approaches this value as k grows. Logarithms here are natural.

Proof. Given the pools, the chance that a pair of positions holds the logged actions is proportional to q^* at the values there, because every other entry is a replay. A bet built from an estimate q pays $(k+1)^2$ times the weight, proportional to q, that it puts on the logged positions. So its expected log payoff is the growth rate minus the expected $\mathrm{KL}(\text{true chances} \parallel \text{bet's weights})$, which is zero when q is proportional to q^*. The pool average of q^* is the likelihood ratio of the unlabelled pools against pools whose logged pair is drawn like the replays. So the growth rate is $\mathrm{KL}(P \parallel Q_iQ_j)$ minus the divergence between these two pool distributions, which is never negative and vanishes as k grows.

The likelihood-ratio bet plugs into q^* estimates of P, Q_i and Q_j from earlier rounds, with one half added to every count. Proposition 2 covers it unchanged.

Corollary (no free collusion). A channel that stays hard to detect cannot shift the pair's game payoff much in any one round. Let $\bar{P}$ be the distribution of a joint action formed from one random entry of each pool, which is what the test's denominator averages over. It mixes P, pairs of one logged and one replayed action, and $Q_i\ Q_j$, and it approaches $Q_i\ Q_j$ as k grows. Suppose a game payoff between 0 and R has an expected value higher by δ under P than under $\bar{P}$. Pinsker's inequality then gives

$$\mathrm{KL}(P \parallel \bar{P}) \geq \frac{2\delta^2}{R^2}.$$

For large k the fastest bet then reaches $1/\alpha$ within about $R^2 \log(1/\alpha)/(2\delta^2)$ rounds. At $k = 2$ this is a rough scale, not a bound. The replays share the public history, which already carries what the channel did in earlier rounds, so we state the bound against $\bar{P}$ and claim no inequality between the two divergences at finite k. The same square law appears in Tailor's detectability bound [2, Theorem 3], in the regret a seller can hide from an audit [13, Theorem 4.5] and in the square-root law of covert communication [27]. The corollary covers only the direct effect of the current channel. An agreement made earlier and stored in memory shifts P and $\bar{P}$ alike, adds nothing to the divergence and can change payoffs by any amount at no cost in detection (Sections 3 and 5.4).

Comparing the bets. Figure A4 gives the exact growth of three bets when one agent copies the other's move in a share of rounds. The likelihood-ratio bet grows fastest everywhere, close to the ceiling of Proposition 3. The pre-registered joint bet does not divide by the replay distributions, and under shared skewed priors it loses evidence for channels that copy up to 0.3 of moves. The interaction bet matches the likelihood-ratio bet here but fails when a channel shifts the marginals. Applied after the fact to the existing games (Table A7), the likelihood-ratio bet flags far more games with a channel and matches the fixed-horizon test in the auction. It names fewer Haiku pairs, because it also pays when one agent alone departs, so naming the pair remains the job of a pair statistic (Section 3). Table A5d gives its false-alarm rate on the simulator.




Figure A4. The likelihood-ratio bet grows fastest, and the pre-registered joint bet can lose evidence. Exact expected log-growth per round of three bets, for one pair with three actions and two replays per agent, when one agent copies the other's move in a share of rounds, with (a) uniform priors and (b) shared priors (0.6, 0.3, 0.1). The dashed line marks the ceiling of Proposition 3. In this copy channel the interaction bet coincides with the likelihood-ratio bet.

C.10 Replay co-departure test (chosen after the auction data). We chose this statistic after seeing the cartel of the double-auction study, so it is post hoc there (Table A6b), and C.11 tests it on a fresh series. An agent departs in a round when its logged action differs from both of its replays. A pair's statistic is the number of rounds in which both of its agents depart, and the game statistic is the largest count over pairs. The null redraws the logged position uniformly in every pool, 999 times, and is exact per round by Proposition 1. A per-agent version counts one agent's departures, with a Bonferroni correction over agents. In the cartel, collusion shows as all followers leaving their replays in the same hours rather than as dependence in the joint law. Applied post hoc to every existing game (Table A7), the test is weaker than net influence where the signal is dependence with few departures. Over all honest conditions, the validation models included, it flagged at most 5%.

Table A7. Post-hoc statistics on the existing games (share of games flagged, or in which the true pair is named, 5% level). On honest conditions the likelihood-ratio bet flagged 0–5.3% of games and the co-departure test of C.10 at most 5%. The repository folder results/summary lists every condition in gro_llm_summary.csv and departure_llm.csv.

Condition	Fixed-horizon test, named	Joint bet, named	Likelihood ratio, flagged	Likelihood ratio, named	Co-departure, named
Secret plan, Haiku	35%	82.5%	70%	62.5%	42.5%
Secret plan, DeepSeek	10%	0%	32.5%	2.5%	2.5%
Pooled-data vendor	92.5%	45%	100%	92.5%	50%

C.11 Fresh pre-registered runs. After the main analysis and the auction study we pre-registered five further runs (`docs/fresh_plan.md`). The plan was timestamped before any of their data existed and fixed each run's hypotheses, sample sizes and numerical predictions. Every run is reported whatever its outcome, and Table A8 gives the tests. The plan also made the co-departure test of C.10 a secondary statistic, with a predicted false-alarm rate of at most 10% and power at least that of the joint bet. The secondary statistic flagged Run A 5% of secret-plan games at 30 rounds (joint bet 0%) and 6.2% of honest games; Run C 20% against 7.5% honest-chat games; Run B 30% (evasive) and 45% (secret plan) against 87.5% and 85% for the joint bet; Run D 0% of pooled-data games and 0% of public-data games. Its false-

alarm prediction held (at most 7.5% on honest games); its power prediction did not hold for Haiku secret-plan pairs, where the joint bet flags more.

- *Run A, likelihood-ratio bet and pinned provider, DeepSeek secret plans.* With the provider pinned, the match-rate diagnostic of C.2 gave +0.001, 95% CI -0.007 to +0.009, consistent with A1 without establishing it. Over 60 rounds the likelihood-ratio bet flagged 52.5% of secret-plan games. The fixed-horizon test named the pair in 25% of them over 60 rounds and 7.5% over 30 rounds, and its false alarms over 60 honest rounds were 7.5%.
- *Run B, a pair told how the audit works.* A Haiku pair was told how the audit works and asked to play its assigned move only when the move looked plausible. Its follower still played the plan in 100% of rounds and its leader in 88%, against 100% and 89% for the earlier secret-plan pair. The fixed-horizon test named it in 20% of games, against 35% (Fisher $p = 0.105$). The joint sequential bet flagged 87.5%, against 85%. Its score advantage per round was -0.60, against -0.53.
- *Run C, collusion through a public chat.* The follower played the decoded move in 97% of decodable rounds, and 0.0% of chat lines named a move. The fixed-horizon test named the true pair in 27.5% of code-word games. Honest small talk stayed within the 10% of flagged games that the plan expected.
- *Run D, the vendor result on a second model family.* The predicted detection rate of about 90% was not reached, because Haiku declines the scheme. It bid as the vendor designated in 1% of rounds, against 92% for DeepSeek. Its rationale says it will not use unverifiable information about a rival in 81% of rounds, against 0% for DeepSeek. The test still found the residual effect.
- *Run E, second cartel series.* In the 30 new cartel games the joint and likelihood-ratio sequential bets flagged 3.3% and 13.3%.

Table A8. Hypotheses of the fresh runs (exact one-sided tests at the 5% level). Run B tested no hypothesis.

Run	Hypothesis	Verdict and result
A. DeepSeek secret plans, provider pinned	H1. In 30 rounds the likelihood-ratio bet flags more secret-plan games than the joint bet (McNemar)	supported, 10/40 against 0/40, $p = 0.001$
A	H2. Its false-alarm rate over 60 honest rounds is below 10% (binomial)	supported, 3/80 false alarms, $p = 0.035$
C. Code words in a public chat, Haiku	H3. The fixed-horizon test flags more code-word than honest small-talk games (Fisher)	supported, 30% against 5%, $p = 0.003$
D. Pooled-data vendor, Haiku sellers	H4. The fixed-horizon test names the true pair in more pooled-data games than it flags public-data games (Fisher)	supported, 15% against 0%, $p = 0.013$
D	H5. Its false-alarm rate on the 80 honest games is below 10%	supported, 0/80 false alarms
E. Second cartel series, double auction	H6. The co-departure test flags more cartel games than the full study's no-chat DeepSeek games (Fisher)	supported, 73.3% against 3.3%, $p < 0.001$

Appendix D. Reproducibility and Deviations

Algorithm 1 collects the audit in one box, and Section 3 explains each step.

Algorithm 1. Replay audit of one episode

Input. Deployed policies, logged views and actions, $k = 2$ replays, the level, and 999 null redraws.

1. Each round, query every policy k times on its logged view with the channel removed. Pool the logged action with its replays.
2. Sequential test. Update the evidence after each round. At the first round it reaches 1 divided by the level, raise an alarm and record the pair with the most evidence.
3. Fixed-horizon test. Compute net influence from the logged actions, redraw every action from its pool 999 times, and compute p.
4. Report detection (an alarm, or an agent that departs from its replays) separately from attribution (the top pair).

Output. The alarm round (or none), the p-value and a candidate pair. The audit costs k extra calls per agent and round, about $0.015 per 30-round audit of four agents at DeepSeek prices.

Code and data.

- Code (MIT licence) is at https://github.com/123yaroslav/replay-test-collusion. The repository explains how to audit your own agents and rebuilds every number in this report from the released data at no cost.
- Data (CC-BY-4.0), the episode logs and the cache of every model reply, are at https://huggingface.co/datasets/123yaroslav/replay-test-collusion.
- The idea of the replay test and a first, non-exact implementation predate the sprint. The repository's pre-sprint log lists that work. All experiments and results reported here were produced during the sprint.

Replays and seeds. Every reported agent-round has exactly two replays. Had a game had fewer, the analysis would have used the smallest count available in it. Each condition has its own block of episode seeds. Main samples, pilots and the replication use disjoint blocks, and pilot games were excluded from every analysis. Each call's sampling seed derives from call type, episode seed, agent and round, so a logged move and its replays never share a seed. Null resampling is seeded by the episode seed.

Deviations from the plan. Table A9 lists every deviation and what was done.

Table A9. Deviations from the plan.

Deviation	What was done
Connection errors in the first launch	the same seeds were re-run
A post-hoc statistic comparing each agent's logged move with its own replays	did not improve detection, not used
The stronger judge, unnamed in the plan	run on 20 games per condition for budget reasons, with replies of up to 2,000 tokens
A review found that the sequential test named the pair by its final evidence instead of at the alarm round	fixed, and all sequential results recomputed
The judge is not deterministic at temperature 0. On games without private messages its two views send the same prompt, and an early uncached pass drew different replies for them (AUROCs of 0.84 for Haiku and 0.47 for DeepSeek in that pass)	the reported numbers use the single cached reply, which reproduces exactly
Table A4, the AUROC intervals and Fisher's test	added after the reviews, from the frozen statistics
Models that failed the pilot's format or availability checks	dropped before the main samples
Body sentences that report C1 and C2 shortened after the data for readability	verdicts and numbers unchanged, test names and p-values in Table A6b

Appendix E. LLM Usage Statement

We used Claude (Anthropic) as a coding and analysis assistant. It implemented the experiment code under our direction, ran simulations, summarised related work, drafted sections of this report and generated the figures from the result files. Codex (OpenAI) and separate Claude instances served as adversarial reviewers of the plan and of the report. Every number in the report is produced by scripts from the result files. We checked claims and references against their sources and take responsibility for the content. Y. R. designed the study, ran the experiments and wrote the report with AI assistance.