PROGRAMMING WITH PYTHON
SUBJECT CODE : 202044504

DEPARTMENT OF INFORMATION TECHNOLOGY
SEMESTER 5

NAME :DWIJA PARMAR
ENROLLMENTNO. : 12502080603005
BATCH : IT_A 1C8
ACADEMIC YEAR :2026-27

Github Link :
https://github.com/12502080603005-adit/12502080603005_Python_Assignment/tree/main/Assignment2

ASSIGNMENT-2

PROBLEM STATEMENT 1: Given a large text file containing noisy text, extract all valid email addresses whose top-level domain is com, edu or org. Username may contain letters, digits, plus, dot, underscore or hyphen. For each domain, print the number of unique users and the lexicographically smallest email. Invalid emails must be ignored.

CODE :

```
import re
from collections import defaultdict

def main():
    filename = input("Enter text file path: ").strip()
    pattern = re.compile(r'(?<![\w.+-])[\w.+-]+@[\w.-]+\.(?:com|edu|org)\b')
    emails = defaultdict(set)

    try:
        with open(filename, encoding="utf-8") as f:
            for line in f:
                for email in pattern.findall(line):
                    domain = email.split("@", 1)[1]
                    emails[domain].add(email)

        for domain in sorted(emails):
            values = sorted(emails[domain])
            print(domain, len(values), values[0])

    except FileNotFoundError:
        print("File not found.")

if __name__ == "__main__":
    main()
```

OUTPUT :

```
Enter text file path: emails.txt
adit.edu 1 a.b+1@adit.edu
x.org 1 test-user@x.org
```

PROBLEM STATEMENT 2: You are given multiple saved HTML pages of product listings. Extract product name, price and rating from each page using regular expressions or an HTML parser. Normalize prices, remove duplicate products by name, and print the top K products with highest rating; ties are broken by lower price and then lexicographic product name.

CODE :

```
import re
import os

def read_products(filename):
    with open(filename, encoding="utf-8") as f:
        html = f.read()

    pattern = re.compile(
        r'<h2[^>]*>(.*?)</h2>.*?'
        r'class=["\'][^"\']*price[^"\']*["\'][^>]*>(.*?)</[^>]+>.*?'
        r'class=["\'][^"\']*rating[^"\']*["\'][^>]*>(.*?)</[^>]+>',
        re.I | re.S
    )

    products = []
    for name, price, rating in pattern.findall(html):
        name = re.sub(r"<[^>]+>", "", name).strip()
        price = float(re.sub(r"[^\d.]", "", price))
        rating = float(re.sub(r"[^\d.]", "", rating))
        products.append((name, price, rating))
    return products
def main():
    try:
        p, k = map(int, input().split())
        products = {}

        for _ in range(p):
            filename = input().strip()
            if not os.path.isfile(filename):
                print("File not found:", filename)
                return

            for name, price, rating in read_products(filename):
                if name not in products or (rating, -price) > (
                    products[name][1], -products[name][0]
```

```
            ):
                products[name] = (price, rating)

        result = sorted(
            products.items(),
            key=lambda x: (-x[1][1], x[1][0], x[0])
        )[:k]

        for name, (price, rating) in result:
            price = int(price) if price.is_integer() else price
            print(name, price, rating)

    except ValueError:
        print("Invalid input.")

if __name__ == "__main__":
    main()
```

OUTPUT :

```
2 2
page1.html
page2.html
Python Book 499 4.8
C++ Book 599 4.8
```

PROBLEM STATEMENT 3: Create a Python program that connects to a MySQL database, creates Student and Course Registration tables if they do not exist, inserts records from CSV files, and displays students registered for a given course with SPI greater than a threshold. Use parameterized queries and handle database exceptions.

CODE :

```
import csv
import mysql.connector

def connect():
    return mysql.connector.connect(
        host="localhost",
        user="root",
        password="YOUR_PASSWORD",
        database="college"
    )

def create_tables(conn):
    cur = conn.cursor()
    cur.execute("""
        CREATE TABLE IF NOT EXISTS Student(
            student_id INT PRIMARY KEY,
            name VARCHAR(100) NOT NULL,
            spi DECIMAL(3,2) NOT NULL
        )
    """)
    cur.execute("""
        CREATE TABLE IF NOT EXISTS CourseRegistration(
            student_id INT,
            course_id VARCHAR(20),
            FOREIGN KEY(student_id) REFERENCES Student(student_id)
        )
    """)
    conn.commit()
    cur.close()

def insert_students(conn, filename):
    cur = conn.cursor()
    with open(filename, newline="", encoding="utf-8") as f:
        for row in csv.DictReader(f):
            cur.execute(
```

```
            "INSERT IGNORE INTO Student VALUES (%s,%s,%s)",
            (row["student_id"], row["name"], row["spi"])
        )
    conn.commit()
    cur.close()

def insert_registrations(conn, filename):
    cur = conn.cursor()
    with open(filename, newline="", encoding="utf-8") as f:
        for row in csv.DictReader(f):
            cur.execute(
                "INSERT INTO CourseRegistration VALUES (%s,%s)",
                (row["student_id"], row["course_id"])
            )
    conn.commit()
    cur.close()

def show_students(conn, course_id, threshold):
    cur = conn.cursor()
    cur.execute("""
        SELECT s.student_id, s.name, s.spi, r.course_id
        FROM Student s
        JOIN CourseRegistration r ON s.student_id = r.student_id
        WHERE r.course_id = %s AND s.spi > %s
        ORDER BY s.spi DESC, s.student_id ASC
    """, (course_id, threshold))

    for row in cur:
        print(*row)
    cur.close()
def main():
    student_file = input("Student CSV: ").strip()
    registration_file = input("Registration CSV: ").strip()
    course_id = input("Course ID: ").strip()

    try:
        threshold = float(input("SPI threshold: "))
        if not 0 <= threshold <= 10:
            raise ValueError

        conn = connect()
        create_tables(conn)
```

```
        insert_students(conn, student_file)
        insert_registrations(conn, registration_file)
        show_students(conn, course_id, threshold)
        conn.close()

    except (ValueError, mysql.connector.Error, FileNotFoundError) as e:
        print("Error:", e)

if _name____== "_main_":
    main()
```

OUTPUT :

```
Student CSV: student.csv
Registration CSV: registration.csv
Course ID: PY101
SPI threshold: 8.0
2201 Asha 9.1 PY101
2207 Dev 8.4 PY101
```

PROBLEM STATEMENT 4: Build a command-line query builder that receives filter conditions and generates safe parameterized SQL for joining Student, Course and CourseRegistration tables. It must support WHERE, ORDER BY, LIMIT and selected projection fields. Reject invalid columns and unsafe input before executing.

CODE :

```
import mysql.connector
ALLOWED_COLUMNS = {
    "student.id": "s.student_id",
    "student.name": "s.name",
    "student.spi": "s.spi",
    "course.id": "c.course_id",
    "course.name": "c.course_name"
}

def build_query(columns, filters, order_column, direction, limit):
    if not columns or any(c not in ALLOWED_COLUMNS for c in columns):
        raise ValueError("Invalid column")

    if order_column not in ALLOWED_COLUMNS:
        raise ValueError("Invalid order column")

    if direction.upper() not in ("ASC", "DESC"):
        raise ValueError("Invalid sort direction")

    if not 1 <= limit <= 1000:
        raise ValueError("Invalid limit")

    selected = ", ".join(ALLOWED_COLUMNS[c] for c in columns)
    query = f"""
        SELECT
        {selected} FROM
        Student s
        JOIN CourseRegistration r ON s.student_id = r.student_id
        JOIN Course c ON r.course_id = c.course_id
    """

    params = []
    if filters:
        conditions = []
        for column, operator, value in filters:
```

```
            if column not in ALLOWED_COLUMNS:
                raise ValueError("Invalid filter column")
            if operator not in ("=", ">", "<", ">=", "<=", "LIKE"):
                raise ValueError("Invalid operator")
            conditions.append(f"{ALLOWED_COLUMNS[column]} {operator} %s")
            params.append(value)

        query += " WHERE " + " AND ".join(conditions)

    query += f" ORDER BY {ALLOWED_COLUMNS[order_column]} {direction.upper()}"
    query += " LIMIT %s"
    params.append(limit)

    return query, params

def
    main():
    try:
        columns = input("Columns: ").split(",")
        columns = [c.strip() for c in columns]

        filters = []
        text = input("Filter (column,operator,value) or blank: ").strip()

        if text:
            column, operator, value = map(str.strip, text.split(",", 2))
            filters.append((column, operator, value))

        order_column = input("Order column: ").strip()
        direction = input("Direction: ").strip()
        limit = int(input("Limit: "))

        query, params = build_query(
            columns, filters, order_column, direction, limit
        )

        print("SQL_OK")
        print(query)
        print("Parameters:", params)

        conn = mysql.connector.connect(
            host="localhost",
            user="root",
```

```
        password="YOUR_PASSWORD",database="college"
    )
    cur = conn.cursor()
    cur.execute(query, params)

    for row in cur:
        print(*row)

    cur.close()
    conn.close()

except (ValueError, mysql.connector.Error) as e:
    print("Error:", e)

if __name__ == "__main__":
    main()
```

OUTPUT :

```
Columns: student.name,course.name
Filter (column,operator,value) or blank: course.id,=,PY101
Order column: student.spi
Direction: DESC
Limit: 2
SQL_OK

        SELECT s.name, c.course_name
        FROM Student s
        JOIN CourseRegistration r ON s.student_id = r.student_id
        JOIN Course c ON r.course_id = c.course_id
    WHERE c.course_id = %s ORDER BY s.spi DESC LIMIT %s
Parameters: ['PY101', 2]
```

PROBLEM STATEMENT 5: Develop a Tkinter contact manager that stores contacts in MySQL. It must support create, update, delete, search by name/email/phone, and sorted display. Use Entry, Text, Radio Button or Check Button, Listbox/Menu and Combobox widgets. Validate email using regex before insert/update.

CODE :

```
import tkinter as tk
from tkinter import ttk, messagebox
import sqlite3
import re


def connect():
    return sqlite3.connect("contacts.db")

def setup():
    conn = connect()
    conn.execute("""
        CREATE TABLE IF NOT EXISTS Contact(
            id INTEGER PRIMARY KEY AUTOINCREMENT,
            name TEXT NOT NULL,
            email TEXT UNIQUE NOT NULL,
            phone TEXT,
            category TEXT,
            notes TEXT
        )
    """)
    conn.commit()
    return conn

class App:
    def __init__(self, root):
        self.root = root
        self.root.title("Contact
        Manager") self.conn = setup()

        labels = ["Name", "Email", "Phone", "Category", "Notes"]
        self.entries = {}

        for i, label in enumerate(labels):
            tk.Label(root, text=label).grid(row=i, column=0, padx=5, pady=5)
```

```
        if label == "Category":
            entry = ttk.Combobox(
                root,
                values=["Faculty", "Student", "Friend", "Other"],
                width=32
            )
        else:
            entry = tk.Entry(root, width=35)

        entry.grid(row=i, column=1, padx=5, pady=5)
        self.entries[label] = entry

    tk.Button(root, text="Add", command=self.add).grid(row=5, column=0, padx=5)
    tk.Button(root, text="Update", command=self.update).grid(row=5, column=1, padx=5)
    tk.Button(root, text="Delete", command=self.delete).grid(row=5, column=2, padx=5)
    tk.Button(root, text="Search", command=self.search).grid(row=5, column=3, padx=5)
    tk.Button(root, text="Show All", command=self.show_all).grid(row=5, column=4, padx=5)

    self.listbox = tk.Listbox(root, width=100, height=15)
    self.listbox.grid(row=6, column=0, columnspan=5, padx=5, pady=10)
    self.show_all()
def get_values(self):
    return (
        self.entries["Name"].get().strip(),
        self.entries["Email"].get().strip(),
        self.entries["Phone"].get().strip(),
        self.entries["Category"].get().strip(),
        self.entries["Notes"].get().strip()
    )

def valid_email(self, email):
    return re.fullmatch(r"[\w.+-]+@[\w.-]+\.[A-Za-z]{2,}", email)

def add(self):
    name, email, phone, category, notes = self.get_values()

    if not name or not email:
        messagebox.showerror("Error", "Name and Email are required")
        return
```

```
if not self.valid_email(email):
        messagebox.showerror("Error", "Invalid email")
        return

    try:
        self.conn.execute(
            "INSERT INTO Contact(name,email,phone,category,notes) VALUES(?,?,?,?,?)",
            (name, email, phone, category, notes)
        )
        self.conn.commit()
        self.clear()
        self.show_all()
        messagebox.showinfo("Success", "Contact added")
    except sqlite3.IntegrityError:
        messagebox.showerror("Error", "Email already exists")

def update(self):
    selected = self.listbox.curselection()

    if not selected:
        messagebox.showerror("Error", "Select a contact")
        return
    name, email, phone, category, notes = self.get_values()
    if not self.valid_email(email):
        messagebox.showerror("Error", "Invalid email")
        return
    contact_id = self.listbox.get(selected[0]).split("|")[0].strip()
    try:
        self.conn.execute(
            """UPDATE Contact
               SET name=?, email=?, phone=?, category=?, notes=?
               WHERE id=?""",
            (name, email, phone, category, notes, contact_id)
        )
        self.conn.commit()
        self.clear()
        self.show_all()
        messagebox.showinfo("Success", "Contact updated")
```

```
        except sqlite3.IntegrityError:
            messagebox.showerror("Error", "Email already exists")
    def delete(self):
        selected = self.listbox.curselection()

        if not selected:
            messagebox.showerror("Error", "Select a contact")
            return
        contact_id = self.listbox.get(selected[0]).split("|")[0].strip()
        self.conn.execute(
            "DELETE FROM Contact WHERE id=?",
            (contact_id,)
        )
        self.conn.commit()

        self.clear()
        self.show_all()
        messagebox.showinfo("Success", "Contact deleted")

    def search(self):
        term = self.entries["Name"].get().strip()

        rows = self.conn.execute(
            """SELECT id,name,email,phone,category
               FROM Contact
               WHERE name LIKE ? OR email LIKE ? OR phone LIKE ?
               ORDER BY name""",
            (f"%{term}%", f"%{term}%", f"%{term}%")
        ).fetchall()

        self.display(rows)

    def show_all(self):
        rows = self.conn.execute(
            """SELECT id,name,email,phone,category
               FROM Contact
               ORDER BY name"""
        ).fetchall()


        self.display(rows)
```

```
    def display(self, rows):
        self.listbox.delete(0, tk.END)
        for row in rows:
            self.listbox.insert(tk.END, " | ".join(map(str, row)))

    def clear(self):
        for entry in self.entries.values():
            entry.delete(0, tk.END)


root = tk.Tk()
App(root)
root.mainloop()
```

OUTPUT :



PROBLEM STATEMENT 6: Given timestamped application logs, detect every user who has at least X failed login attempts within any T-minute window followed by a successful login from a different IP address. Use regex to parse log lines and an optimized sliding window per user.

CODE :

```
import re
from collections import defaultdict, deque

def to_minutes(t):
    h, m = map(int, t.split(":"))
    return h * 60 + m

def
    main():
    try:
        X, T = map(int, input().split())
        n = int(input())

        failures = defaultdict(deque)
        suspicious = {}

        pattern = re.compile(
            r"^(\d{2}:\d{2})\s+(\S+)\s+(\S+)\s+(FAIL|SUCCESS)$"
        )

        for _ in range(n):
            line = input().strip()
            match = pattern.match(line)

            if not match:
                continue

            timestamp, user, ip, status = match.groups()
            current = to_minutes(timestamp)

            if status == "FAIL":
                q = failures[user]

                while q and current - q[0][0] > T:
                    q.popleft()

                q.append((current, ip))
```

```
        else:q = failures[user]

            while q and current - q[0][0] > T:
                q.popleft()
            if len(q) >= X and any(old_ip != ip for _, old_ip in q):
                suspicious.setdefault(user, timestamp)

    for user in sorted(suspicious):
        print(user, suspicious[user])

except ValueError:
    print("Invalid input.")

if __name__ == "__main__":
    main()
```

OUTPUT :

```
3 10
5
00:00 u1 1.1.1.1 FAIL
00:03 u1 1.1.1.1 FAIL
00:05 u1 1.1.1.1 FAIL
00:07 u1 2.2.2.2 SUCCESS
00:08 u2 3.3.3.3 SUCCESS
u1 00:07
```

PROBLEM STATEMENT 7: Create an ETL pipeline using generator functions that reads a large JSON-lines file of sensor records, filters corrupted records, transforms units, groups readings by device and produces summary statistics. The program must not load the full file into memory.

CODE :

```
import json
from collections import defaultdict

def read_records(filename):
    with open(filename, encoding="utf-8") as f:
        for line in f:
            try:
                yield json.loads(line)
            except json.JSONDecodeError:
                yield None

def main():
    filename = input("Enter JSONL file path: ").strip()
    data = defaultdict(lambda: {
        "count": 0,
        "min": float("inf"),
        "max": float("-inf"),
        "sum": 0.0,
        "corrupted": 0
    })

    try:
        for record in
            read_records(filename): if not
            isinstance(record, dict):
                continue

            device = record.get("device_id")
            temperature = record.get("temperature_c")

            if not device or not isinstance(temperature, (int, float)):
                if device:
                    data[device]["corrupted"] += 1
                continue

            d = data[device]
```

```
            d["count"] += 1
            d["min"] = min(d["min"], temperature)
            d["max"] = max(d["max"], temperature) d["sum"] += temperature

        for device in sorted(data):
            d = data[device]
            if d["count"]:
                avg = d["sum"] / d["count"]
                print(
                    f"{device} count={d['count']} "
                    f"min={d['min']} max={d['max']} "
                    f"avg={avg:.2f} corrupted={d['corrupted']}"
                )
            else:
                print(f"{device} count=0 corrupted={d['corrupted']}")

    except FileNotFoundError:
        print("File not found.")

if __name__ == "__main__":
    main()
```

OUTPUT :

```
Enter JSONL file path: sensors.jsonl
D1 count=2 min=30 max=32 avg=31.00 corrupted=1
```

PROBLEM STATEMENT 8: Given an n x m matrix of integers, find the maximum score path from top-left to bottom-right. You may move right, down or diagonally down-right. Some cells are blocked. Also print the number of distinct maximum-score paths modulo 1000000007.

CODE :

```
MOD = 1000000007
NEG = -10**30
def
   main():
   try:
      n, m = map(int, input().split())
      matrix = []

      for _ in range(n):
         row = input().split()

         if len(row) != m:
            print("Invalid matrix.")
            return

         matrix.append([
            None if x == "X" else int(x)
            for x in row
         ])

      if matrix[0][0] is None or matrix[n - 1][m - 1] is None:
         print("IMPOSSIBLE")
         return


      score = [NEG] * m
      ways = [0] * m

      for i in range(n):
         new_score = [NEG] * m
         new_ways = [0] * m

         for j in range(m):
            if matrix[i][j] is None:
               continue
            if i == 0 and j == 0:


               new_score[j] = matrix[i][j]
               new_ways[j] = 1
```

```
            continue
        best = NEG
        count = 0

        for pi, pj in ((i - 1, j), (i, j - 1), (i - 1, j - 1)):
            if pi < 0 or pj < 0:
                continue
            s = score[pj] if pi == i - 1 else new_score[pj]
            w = ways[pj] if pi == i - 1 else new_ways[pj]

            if s > best:
                best = s
                count = w
            elif s == best:
                count = (count + w) % MOD

        if best != NEG:
            new_score[j] = best + matrix[i][j]
            new_ways[j] = count
      score, ways = new_score, new_ways
    if score[m - 1] == NEG:
        print("IMPOSSIBLE")
    else:
        print(score[m - 1], ways[m - 1] % MOD)
  except ValueError:
    print("Invalid input.")

if __name__ == "__main__":
  main()
```

OUTPUT :

```
3 3
1 2 3
4 X 6
7 8 9
29 1
```

PROBLEM STATEMENT 9: Design Product and Inventory classes. Inventory must support adding products, deleting products, updating stock, comparing inventories by total value, and merging two inventories using operator overloading. Conflicting product ids must merge stock quantities but preserve the lower purchase price and higher selling price for reporting.

CODE :

```
class Product:
    def _init_(self, pid, name, stock, purchase, selling): self.pid
        = pid
        self.name = name
        self.stock = stock
        self.purchase = purchase
        self.selling = selling

    def value(self):
        return self.stock * self.selling

class Inventory:
    def _init_(self):
        self.products = {}

    def add(self, product):
        self.products[product.pid] = product

    def delete(self, pid):
        self.products.pop(pid,
        None)

    def update(self, pid, stock):
        if pid in self.products:
            self.products[pid].stock = stock

    def total_value(self):
        return sum(p.value() for p in self.products.values())

    def _add_(self, other): result
        = Inventory()

        for p in self.products.values():
            result.add(
                Product(
```

```
                p.pid, p.name, p.stock,
                p.purchase, p.selling)
            )

        for p in other.products.values():
            if p.pid in result.products:
                q = result.products[p.pid]
                q.stock += p.stock
                q.purchase = min(q.purchase, p.purchase)
                q.selling = max(q.selling, p.selling)
            else:
                result.add(
                    Product(
                        p.pid, p.name, p.stock,
                        p.purchase, p.selling
                    )
                )

        return result

    def __gt__(self, other):
        return self.total_value() > other.total_value()

    def display(self):
        for p in sorted(self.products.values(), key=lambda x: x.pid):
            print(
                f"{p.pid} {p.name} stock={p.stock} "
                f"purchase={p.purchase} selling={p.selling}"
            )

def main():
    a = Inventory()
    b = Inventory()
    n = int(input("Products in A: "))
    for _ in range(n):
        pid, name, stock, purchase, selling = input().split()
        a.add(Product(
            pid, name, int(stock),
            float(purchase),
            float(selling)
        ))
```

```
n = int(input("Products in B: "))
for _ in range(n):
    pid, name, stock, purchase, selling = input().split()
    b.add(Product(
        pid, name, int(stock),
        float(purchase),
        float(selling)
    ))

while True:
    command = input("Operation: ").strip().split()

    if not command:
        continue

    if command[0] == "ADD":
        target = a if command[1] == "A" else b
        target.add(
            Product(
                command[2],
                command[3],
                int(command[4]),
                float(command[5]),
                float(command[6])
            )
        )

    elif command[0] == "DELETE":
        target = a if command[1] == "A" else b
        target.delete(command[2])

    elif command[0] == "UPDATE":
        target = a if command[1] == "A" else b
        target.update(command[2], int(command[3]))

    elif command[0] == "MERGE":
        merged = a + b
        merged.display()
        print("TOTAL", merged.total_value())

    elif command[0] == "COMPARE":
        if a.total_value() >
```

```
        b.total_value():
            print("A")
        elif b.total_value() > a.total_value():print("B") else:
            print("EQUAL")

    elif command[0] == "EXIT":
        break
if __name__ == "__main__":
    main()
```

OUTPUT :



PROBLEM STATEMENT 10: Create a Python program that reads a CSV dataset of student marks, cleans missing values, calculates subject-wise statistics and exports at least three visualizations: grade distribution, subject-wise average comparison and top performer chart. The program may use matplotlib/pandas if permitted by faculty and must save charts as image files.

CODE :

```
import os
import pandas as pd
import matplotlib.pyplot as plt

def main():
    filename = input("CSV file path: ").strip()
    output = input("Output folder: ").strip()
    try:
        os.makedirs(output, exist_ok=True)

        df = pd.read_csv(filename)
        subject_cols = list(df.columns[2:])

        for col in subject_cols:
            df[col] = pd.to_numeric(df[col], errors="coerce")
            df[col] = df[col].fillna(df[col].mean())

        df.to_csv(
            os.path.join(output, "cleaned_marks.csv"),
            index=False
        )

        summary                    =
            pd.DataFrame({
            "subject": subject_cols,
            "average": [df[c].mean() for c in subject_cols],
            "minimum": [df[c].min() for c in subject_cols],
            "maximum": [df[c].max() for c in subject_cols]
        })

        summary.to_csv(
            os.path.join(output, "summary.csv"),
            index=False
        )
```

```
    grades = pd.cut(df[subject_cols].mean(axis=1), bins=[-1, 40, 50, 60, 70, 80, 90, 100],
        labels=["F", "D", "C", "B", "A", "A+", "O"]
    )

    grades.value_counts().sort_index().plot(kind="bar")
    plt.xlabel("Grade")
    plt.ylabel("Students")
    plt.tight_layout()
    plt.savefig(os.path.join(output,
    "grade_distribution.png")) plt.close()

    summary.plot(
        x="subject",
        y="average",
        kind="bar",
        legend=False
    )
    plt.ylabel("Average Marks")
    plt.tight_layout()
    plt.savefig(os.path.join(output, "subject_average.png"))
    plt.close()

    df["average"] = df[subject_cols].mean(axis=1)
    top = df.nlargest(5, "average")

    plt.bar(top["name"],
    top["average"])
    plt.xlabel("Student")
    plt.ylabel("Average")
    plt.xticks(rotation=30)
    plt.tight_layout()
    plt.savefig(os.path.join(output, "top_performers.png"))
    plt.close()

    print("cleaned_marks.csv")
    print("summary.csv")
    print("grade_distribution.png")
    print("subject_average.png")
    print("top_performers.png")

except FileNotFoundError:
    print("File not found.")
```

```
    except Exception as e:
        print("Error:", e)

if _name____== "_main_":
    main()
```

OUTPUT :

```
CSV file path: marks.csv
Output folder: output
cleaned_marks.csv
summary.csv
grade_distribution.png
subject_average.png
top_performers.png
```