

PHP Binance Api

Generated by Doxygen 1.8.6

Mon Apr 16 2018 04:39:18

Contents

| | | |
|----------|--|----------|
| 1 | Namespace Index | 1 |
| 1.1 | Namespace List | 1 |
| 2 | Class Index | 3 |
| 2.1 | Class List | 3 |
| 3 | Namespace Documentation | 5 |
| 3.1 | Binance Namespace Reference | 5 |
| 4 | Class Documentation | 7 |
| 4.1 | Binance\API Class Reference | 7 |
| 4.1.1 | Detailed Description | 9 |
| 4.1.2 | Constructor & Destructor Documentation | 10 |
| 4.1.2.1 | __construct | 10 |
| 4.1.3 | Member Function Documentation | 10 |
| 4.1.3.1 | __get | 10 |
| 4.1.3.2 | __set | 10 |
| 4.1.3.3 | account | 10 |
| 4.1.3.4 | addToTransferred | 10 |
| 4.1.3.5 | aggTrades | 11 |
| 4.1.3.6 | balances | 11 |
| 4.1.3.7 | bookPrices | 11 |
| 4.1.3.8 | buy | 12 |
| 4.1.3.9 | buyTest | 12 |
| 4.1.3.10 | cancel | 12 |
| 4.1.3.11 | candlesticks | 13 |
| 4.1.3.12 | chart | 13 |
| 4.1.3.13 | cumulative | 14 |
| 4.1.3.14 | depositAddress | 14 |
| 4.1.3.15 | depositHistory | 14 |
| 4.1.3.16 | depth | 15 |
| 4.1.3.17 | depthCache | 15 |

| | | |
|----------|---------------------------|----|
| 4.1.3.18 | displayDepth | 15 |
| 4.1.3.19 | exchangeInfo | 16 |
| 4.1.3.20 | first | 16 |
| 4.1.3.21 | getProxyUriString | 16 |
| 4.1.3.22 | getRequestCount | 16 |
| 4.1.3.23 | getTransferred | 17 |
| 4.1.3.24 | highstock | 17 |
| 4.1.3.25 | history | 17 |
| 4.1.3.26 | keepAlive | 18 |
| 4.1.3.27 | kline | 18 |
| 4.1.3.28 | last | 18 |
| 4.1.3.29 | marketBuy | 18 |
| 4.1.3.30 | marketBuyTest | 19 |
| 4.1.3.31 | marketSell | 19 |
| 4.1.3.32 | marketSellTest | 19 |
| 4.1.3.33 | miniTicker | 20 |
| 4.1.3.34 | openOrders | 20 |
| 4.1.3.35 | order | 20 |
| 4.1.3.36 | orders | 21 |
| 4.1.3.37 | orderStatus | 21 |
| 4.1.3.38 | prevDay | 22 |
| 4.1.3.39 | prices | 22 |
| 4.1.3.40 | sell | 22 |
| 4.1.3.41 | sellTest | 23 |
| 4.1.3.42 | setProxy | 23 |
| 4.1.3.43 | sortDepth | 23 |
| 4.1.3.44 | terminate | 24 |
| 4.1.3.45 | ticker | 24 |
| 4.1.3.46 | time | 24 |
| 4.1.3.47 | trades | 25 |
| 4.1.3.48 | userData | 26 |
| 4.1.3.49 | useServerTime | 26 |
| 4.1.3.50 | withdraw | 27 |
| 4.1.3.51 | withdrawFee | 27 |
| 4.1.3.52 | withdrawHistory | 27 |
| 4.1.4 | Member Data Documentation | 28 |
| 4.1.4.1 | \$api_key | 28 |
| 4.1.4.2 | \$api_secret | 28 |
| 4.1.4.3 | \$base | 28 |
| 4.1.4.4 | \$chartQueue | 28 |

| | | |
|----------|----------------|----|
| 4.1.4.5 | \$charts | 28 |
| 4.1.4.6 | \$curlOpts | 28 |
| 4.1.4.7 | \$depthCache | 28 |
| 4.1.4.8 | \$depthQueue | 28 |
| 4.1.4.9 | \$info | 28 |
| 4.1.4.10 | \$proxyConf | 29 |
| 4.1.4.11 | \$requestCount | 29 |
| 4.1.4.12 | \$stream | 29 |
| 4.1.4.13 | \$transferred | 29 |
| 4.1.4.14 | \$wapi | 29 |

Index**30**

Chapter 1

Namespace Index

1.1 Namespace List

Here is a list of all namespaces with brief descriptions:

| | |
|-----------------------------------|---|
| Binance | 5 |
|-----------------------------------|---|

Chapter 2

Class Index

2.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

| | |
|------------------------------|-------------------|
| Binance\API | |
| Main Binance class | 7 |

Chapter 3

Namespace Documentation

3.1 Binance Namespace Reference

Classes

- class [API](#)

Main Binance class.

Chapter 4

Class Documentation

4.1 Binance\API Class Reference

Main Binance class.

Public Member Functions

- [__construct](#) ()
Constructor for the class, send as many argument as you want.
- [__get](#) (string \$member)
magic get for private and protected members
- [__set](#) (string \$member, \$value)
magic set for private and protected members
- [buy](#) (string \$symbol, \$quantity, \$price, string \$type="LIMIT", array \$flags=[])
buy attempts to create a currency order each currency supports a number of order types, such as -LIMIT -MARKET -STOP_LOSS -STOP_LOSS_LIMIT -TAKE_PROFIT -TAKE_PROFIT_LIMIT -LIMIT_MAKER
- [buyTest](#) (string \$symbol, \$quantity, \$price, string \$type="LIMIT", array \$flags=[])
buyTest attempts to create a TEST currency order
- [sell](#) (string \$symbol, \$quantity, \$price, string \$type="LIMIT", array \$flags=[])
sell attempts to create a currency order each currency supports a number of order types, such as -LIMIT -MARKET -STOP_LOSS -STOP_LOSS_LIMIT -TAKE_PROFIT -TAKE_PROFIT_LIMIT -LIMIT_MAKER
- [sellTest](#) (string \$symbol, \$quantity, \$price, string \$type="LIMIT", array \$flags=[])
sellTest attempts to create a TEST currency order
- [marketBuy](#) (string \$symbol, \$quantity, array \$flags=[])
marketBuy attempts to create a currency order at given market price
- [marketBuyTest](#) (string \$symbol, \$quantity, array \$flags=[])
marketBuyTest attempts to create a TEST currency order at given market price
- [marketSell](#) (string \$symbol, \$quantity, array \$flags=[])
marketSell attempts to create a currency order at given market price
- [marketSellTest](#) (string \$symbol, \$quantity, array \$flags=[])
marketSellTest attempts to create a TEST currency order at given market price
- [cancel](#) (string \$symbol, \$orderid)
cancel attempts to cancel a currency order
- [orderStatus](#) (string \$symbol, \$orderid)
orderStatus attempts to get orders status
- [openOrders](#) (string \$symbol=null)
openOrders attempts to get open orders for all currencies or a specific currency

- **orders** (string \$symbol, int \$limit=500, int \$fromOrderId=1)
orders attempts to get the orders for all or a specific currency
- **history** (string \$symbol, int \$limit=500, int \$fromTradeId=1)
history Get the complete account trade history for all or a specific currency
- **useServerTime** ()
useServerTime adds the 'useServerTime'=>true to the API request to avoid time errors
- **time** ()
time Gets the server time
- **exchangeInfo** ()
exchangeInfo Gets the complete exchange info, including limits, currency options etc.
- **withdraw** (string \$asset, string \$address, \$amount, \$addressTag=null)
withdraw requests a asset be withdrawn from binance to another wallet
- **depositAddress** (string \$asset)
depositAddress get the deposit address for an asset
- **depositHistory** (string \$asset=null, array \$params=[])
depositAddress get the deposit history for an asset
- **withdrawHistory** (string \$asset=null, array \$params=[])
withdrawHistory get the withdrawal history for an asset
- **withdrawFee** (string \$asset)
withdrawFee get the withdrawal fee for an asset
- **prices** ()
prices get all the current prices
- **bookPrices** ()
bookPrices get all bid/asks prices
- **account** ()
account get all information about the api account
- **prevDay** (string \$symbol=null)
prevDay get 24hr ticker price change statistics for symbols
- **aggTrades** (string \$symbol)
aggTrades get Market History / Aggregate Trades
- **depth** (string \$symbol)
depth get Market depth
- **balances** (\$priceData=false)
balances get balances for the account assets
- **getProxyUriString** ()
getProxyUriString get Uniform Resource Identifier string associated with proxy config
- **setProxy** (array \$proxyconf)
setProxy set proxy config by passing in an array of the proxy configuration
- **order** (string \$side, string \$symbol, \$quantity, \$price, string \$type="LIMIT", array \$flags=[], bool \$test=false)
order formats the orders before sending them to the curl wrapper function You can call this function directly or use the helper functions
- **candlesticks** (string \$symbol, string \$interval="5m", int \$limit=null, \$startTime=null, \$endTime=null)
candlesticks get the candles for the given intervals 1m,3m,5m,15m,30m,1h,2h,4h,6h,8h,12h,1d,3d,1w,1M
- **cumulative** (array \$depth)
cumulative Converts depth cache into a cumulative array
- **highstock** (array \$chart, bool \$include_volume=false)
highstock Converts Chart Data into array for highstock & kline charts
- **first** (array \$array)
first Gets first key of an array
- **last** (array \$array)
last Gets last key of an array

- **displayDepth** (array \$array)
displayDepth Formats nicely for console output
- **getTransferred** ()
getTransferred gets the total transferred in b,Kb,Mb,Gb
- **getRequestCount** ()
getRequestCount gets the total number of API calls
- **addToTransferred** (int \$int)
addToTransferred add interger bytes to the total transferred also incrementes the api counter
- **sortDepth** (string \$symbol, int \$limit=11)
sortDepth Sorts depth data for display & getting highest bid and lowest ask
- **depthCache** (\$symbols, callable \$callback)
depthCache Pulls /depth data and subscribes to WebSocket endpoint Maintains a local Depth Cache in sync via lastUpdated.
- **trades** (\$symbols, callable \$callback)
trades Trades WebSocket Endpoint
- **ticker** (\$symbol, callable \$callback)
ticker pulls 24h price change statistics via WebSocket
- **chart** (\$symbols, string \$interval="30m", callable \$callback)
chart Pulls /kline data and subscribes to WebSocket endpoint
- **kline** (\$symbols, string \$interval="30m", callable \$callback)
kline Subscribes to WebSocket endpoint for latest chart data only
- **terminate** (\$endpoint)
terminate Terminates websocket endpoints.
- **keepAlive** ()
keepAlive Keep-alive function for userDataStream
- **userData** (&\$balance_callback, &\$execution_callback=false)
userData Issues userDataStream token and keepalive, subscribes to userData WebSocket
- **miniTicker** (callable \$callback)
miniTicker Get miniTicker for all symbols

Protected Attributes

- **\$base** = 'https://api.binance.com/api/'
- **\$wapi** = 'https://api.binance.com/wapi/'
- **\$stream** = 'wss://stream.binance.com:9443/ws/'
- **\$api_key**
- **\$api_secret**
- **\$depthCache** = []
- **\$depthQueue** = []
- **\$chartQueue** = []
- **\$charts** = []
- **\$curlOpts** = []
- **\$info**
- **\$proxyConf** = null
- **\$transferred** = 0
- **\$requestCount** = 0

4.1.1 Detailed Description

Main Binance class.

Eg. Usage: require 'vendor/autoload.php'; \$api = new Binance\API();

Definition at line 29 of file php-binance-api.php.

4.1.2 Constructor & Destructor Documentation

4.1.2.1 Binance\API::__construct ()

Constructor for the class, send as many argument as you want.

Returns

null

Definition at line 61 of file php-binance-api.php.

4.1.3 Member Function Documentation

4.1.3.1 Binance\API::__get (string \$member)

magic get for private and protected members

Parameters

| | |
|---------------|---|
| <i>\$file</i> | string the name of the property to return |
|---------------|---|

Returns

null

Definition at line 172 of file php-binance-api.php.

4.1.3.2 Binance\API::__set (string \$member, \$value)

magic set for private and protected members

Parameters

| | |
|-----------------|--|
| <i>\$member</i> | string the name of the member property |
| <i>\$value</i> | the value of the member property |

Definition at line 186 of file php-binance-api.php.

4.1.3.3 Binance\API::account ()

account get all information about the api account

```
$account = $api->account();
```

Returns

array with error message or array of all the account information

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 721 of file php-binance-api.php.

4.1.3.4 Binance\API::addToTransferred (int \$int)

addToTransferred add interger bytes to the total transferred also incrementes the api counter

```
$apiCount = $api->addToTransferred( $int );
```


Returns

null

Definition at line 1524 of file php-binance-api.php.

4.1.3.5 Binance\API::aggTrades (string \$symbol)

aggTrades get Market History / Aggregate Trades

```
$trades = $api->aggTrades("BNBBTC");
```

Parameters

| | |
|-----------------|--|
| <i>\$symbol</i> | string the symbol to get the trade information for |
|-----------------|--|

Returns

array with error message or array of market history

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 755 of file php-binance-api.php.

4.1.3.6 Binance\API::balances (\$priceData = false)

balances get balances for the account assets

```
$balances = $api->balances($ticker);
```

Parameters

| | | |
|------|--------------------|--|
| bool | <i>\$priceData</i> | array of the symbols balances are required for |
|------|--------------------|--|

Returns

array with error message or array of balances

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 795 of file php-binance-api.php.

4.1.3.7 Binance\API::bookPrices ()

bookPrices get all bid/asks prices

```
$ticker = $api->bookPrices();
```

Returns

array with error message or array of all the book prices

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 708 of file php-binance-api.php.

4.1.3.8 `Binance\API::buy (string $symbol, $quantity, $price, string $type = "LIMIT", array $flags = [])`

buy attempts to create a currency order each currency supports a number of order types, such as -LIMIT -MARKET -STOP_LOSS -STOP_LOSS_LIMIT -TAKE_PROFIT -TAKE_PROFIT_LIMIT -LIMIT_MAKER

You should check the

See Also

exchangeInfo for each currency to determine what types of orders can be placed against specific pairs

```
$quantity = 1; $price = 0.0005; $order = $api->buy("BNBBTC", $quantity, $price);
```

Parameters

| | |
|-------------------|---|
| <i>\$symbol</i> | string the currency symbol |
| <i>\$quantity</i> | string the quantity required |
| <i>\$price</i> | string price per unit you want to spend |
| <i>\$type</i> | string type of order |
| <i>\$flags</i> | array additional options for order type |

Returns

array with error message or the order details

Definition at line 299 of file php-binance-api.php.

4.1.3.9 `Binance\API::buyTest (string $symbol, $quantity, $price, string $type = "LIMIT", array $flags = [])`

buyTest attempts to create a TEST currency order

See Also

buy()

Parameters

| | |
|-------------------|---|
| <i>\$symbol</i> | string the currency symbol |
| <i>\$quantity</i> | string the quantity required |
| <i>\$price</i> | string price per unit you want to spend |
| <i>\$type</i> | string config |
| <i>\$flags</i> | array config |

Returns

array with error message or empty or the order details

Definition at line 316 of file php-binance-api.php.

4.1.3.10 `Binance\API::cancel (string $symbol, $orderid)`

cancel attempts to cancel a currency order

```
$orderid = "123456789"; $order = $api->cancel("BNBBTC", $orderid);
```

Parameters

| | |
|------------------|------------------------------|
| <i>\$symbol</i> | string the currency symbol |
| <i>\$orderid</i> | string the orderid to cancel |

Returns

array with error message or the order details

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 441 of file php-binance-api.php.

4.1.3.11 `Binance\API::candlesticks (string $symbol, string $interval = "5m", int $limit = null, $startTime = null, $endTime = null)`

candlesticks get the candles for the given intervals 1m,3m,5m,15m,30m,1h,2h,4h,6h,8h,12h,1d,3d,1w,1M

```
$candles = $api->candlesticks("BNBBTC", "5m");
```

Parameters

| | |
|--------------------|--|
| <i>\$symbol</i> | string to query |
| <i>\$interval</i> | string to request |
| <i>\$limit</i> | int limit the amount of candles |
| <i>\$startTime</i> | string request candle information starting from here |
| <i>\$endTime</i> | string request candle information ending here |

Returns

array containing the response

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 1050 of file php-binance-api.php.

4.1.3.12 `Binance\API::chart ($symbols, string $interval = "30m", callable $callback)`

chart Pulls /kline data and subscribes to WebSocket endpoint

```
$api->chart(["BNBBTC"], "15m", function($api, $symbol, $chart) { echo "{$symbol} chart update\n"; print_r($chart); });
```

Parameters

| | |
|-------------------|-------------------------|
| <i>\$symbols</i> | string required symbols |
| <i>\$interval</i> | string time interval |
| <i>\$callback</i> | callable closure |

Returns

null

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 1837 of file php-binance-api.php.

4.1.3.13 BinanceAPI::cumulative (array \$depth)

cumulative Converts depth cache into a cumulative array

```
$cumulative = $api->cumulative($depth);
```

Parameters

| | |
|----------------|-------------------|
| <i>\$depth</i> | array cache array |
|----------------|-------------------|

Returns

array cumulative depth cache

Definition at line 1342 of file php-binance-api.php.

4.1.3.14 BinanceAPI::depositAddress (string \$asset)

depositAddress get the deposit address for an asset

```
$depositAddress = $api->depositAddress("VEN");
```

Parameters

| | |
|----------------|---------------------------------|
| <i>\$asset</i> | string the currency such as BTC |
|----------------|---------------------------------|

Returns

array with error message or array deposit address information

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 618 of file php-binance-api.php.

4.1.3.15 BinanceAPI::depositHistory (string \$asset = null, array \$params = [])

depositAddress get the deposit history for an asset

```
$depositHistory = $api->depositHistory();
```

```
$depositHistory = $api->depositHistory( "BTC" );
```

Parameters

| | |
|-----------------|--|
| <i>\$asset</i> | string empty or the currency such as BTC |
| <i>\$params</i> | array optional startTime, endTime, status parameters |

Returns

array with error message or array deposit history information

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 639 of file php-binance-api.php.

4.1.3.16 **Binance\API::depth (string \$symbol)**

depth get Market depth

```
$depth = $api->depth("ETHBTC");
```

Parameters

| | |
|-----------------|--|
| <i>\$symbol</i> | string the symbol to get the depth information for |
|-----------------|--|

Returns

array with error message or array of market depth

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 771 of file php-binance-api.php.

4.1.3.17 **Binance\API::depthCache (\$symbols, callable \$callback)**

depthCache Pulls /depth data and subscribes to WebSocket endpoint Maintains a local Depth Cache in sync via lastUpdateId.

See depth() and depthHandler()

```
$api->depthCache(["BNBBTC"], function($api, $symbol, $depth) { echo "{$symbol} depth cache update".PHP_EOL; //print_r($depth); // Print all depth data $limit = 11; // Show only the closest asks/bids $sorted = $api->sortDepth($symbol, $limit); $bid = $api->first($sorted['bids']); $ask = $api->first($sorted['asks']); echo $api->displayDepth($sorted); echo "ask: {$ask}".PHP_EOL; echo "bid: {$bid}".PHP_EOL; });
```

Parameters

| | |
|-------------------|----------------------------------|
| <i>\$symbol</i> | string optional array of symbols |
| <i>\$callback</i> | callable closure |

Returns

null

Definition at line 1645 of file php-binance-api.php.

4.1.3.18 **Binance\API::displayDepth (array \$array)**

displayDepth Formats nicely for console output

```
$outputString = $api->displayDepth($array);
```

Parameters

| | |
|----------------|-------|
| <i>\$array</i> | array |
|----------------|-------|

Returns

string of the depth information

Definition at line 1437 of file php-binance-api.php.

4.1.3.19 Binance\API::exchangeInfo ()

exchangeInfo Gets the complete exchange info, including limits, currency options etc.

```
$info = $api->exchangeInfo();
```

Returns

array with error message or exchange info array

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 569 of file php-binance-api.php.

4.1.3.20 Binance\API::first (array \$array)

first Gets first key of an array

```
$first = $api->first($array);
```

Parameters

| | |
|----------------|-------|
| <i>\$array</i> | array |
|----------------|-------|

Returns

string key or null

Definition at line 1405 of file php-binance-api.php.

4.1.3.21 Binance\API::getProxyUriString ()

getProxyUriString get Uniform Resource Identifier string associated with proxy config

```
$balances = $api->getProxyUriString();
```

Returns

string uri

Definition at line 811 of file php-binance-api.php.

4.1.3.22 Binance\API::getRequestCount ()

getRequestCount gets the total number of API calls

```
$apiCount = $api->getRequestCount();
```

Returns

int get the total number of api calls

Definition at line 1511 of file php-binance-api.php.

4.1.3.23 Binance\API::getTransferred ()

getTransferred gets the total transferred in b,Kb,Mb,Gb

```
$transferred = $api->getTransferred();
```

Returns

string showing the total transferred

Definition at line 1491 of file php-binance-api.php.

4.1.3.24 Binance\API::highstock (array \$chart, bool \$include_volume = false)

highstock Converts Chart Data into array for highstock & kline charts

```
$highstock = $api->highstock($chart, $include_volume);
```

Parameters

| | |
|-------------------------|------------------------------|
| <i>\$chart</i> | array |
| <i>\$include_volume</i> | bool for inclusion of volume |

Returns

array highchart data

Definition at line 1377 of file php-binance-api.php.

4.1.3.25 Binance\API::history (string \$symbol, int \$limit = 500, int \$fromTraded = 1)

history Get the complete account trade history for all or a specific currency

```
$allHistory = $api->history(); $BNBHistory = $api->history("BNBBTC"); $limitBNBHistory = $api->history("BNBBTC",5); $limitBNBHistoryFromId = $api->history("BNBBTC",5,3);
```

Parameters

| | |
|---------------------|---|
| <i>\$symbol</i> | string the currency symbol |
| <i>\$limit</i> | int the amount of orders returned |
| <i>\$fromTraded</i> | int return the orders from this order onwards |

Returns

array with error message or array of orderDetails array

Exceptions

| |
|-------------------|
| <i>\Exception</i> |
|-------------------|

Definition at line 523 of file php-binance-api.php.

4.1.3.26 `BinanceAPI::keepAlive ()`

keepAlive Keep-alive function for userDataStream

```
$api->keepAlive();
```

Returns

null

Definition at line 1974 of file php-binance-api.php.

4.1.3.27 `BinanceAPI::kline ($symbols, string $interval = "30m", callable $callback)`

kline Subscribes to WebSocket endpoint for latest chart data only

```
$api->kline(["BNBBTC"], "15m", function($api, $symbol, $chart) { echo "{$symbol} chart update\n"; print_r($chart); });
```

Parameters

| | |
|-------------------|-------------------------|
| <i>\$symbols</i> | string required symbols |
| <i>\$interval</i> | string time interval |
| <i>\$callback</i> | callable closure |

Returns

null

Exceptions

| |
|-------------------|
| <i>\Exception</i> |
|-------------------|

Definition at line 1916 of file php-binance-api.php.

4.1.3.28 `BinanceAPI::last (array $array)`

last Gets last key of an array

```
$last = $api->last($array);
```

Parameters

| | |
|----------------|-------|
| <i>\$array</i> | array |
|----------------|-------|

Returns

string key or null

Definition at line 1421 of file php-binance-api.php.

4.1.3.29 `BinanceAPI::marketBuy (string $symbol, $quantity, array $flags = [])`

marketBuy attempts to create a currency order at given market price

```
$quantity = 1; $order = $api->marketBuy("BNBBTC", $quantity);
```


Parameters

| | |
|-------------------|---|
| <i>\$symbol</i> | string the currency symbol |
| <i>\$quantity</i> | string the quantity required |
| <i>\$flags</i> | array additional options for order type |

Returns

array with error message or the order details

Definition at line 379 of file php-binance-api.php.

4.1.3.30 `Binance\API::marketBuyTest (string $symbol, $quantity, array $flags = [])`

marketBuyTest attempts to create a TEST currency order at given market price

See Also

marketBuy()

Parameters

| | |
|-------------------|---|
| <i>\$symbol</i> | string the currency symbol |
| <i>\$quantity</i> | string the quantity required |
| <i>\$flags</i> | array additional options for order type |

Returns

array with error message or the order details

Definition at line 394 of file php-binance-api.php.

4.1.3.31 `Binance\API::marketSell (string $symbol, $quantity, array $flags = [])`

marketSell attempts to create a currency order at given market price

```
$quantity = 1; $order = $api->marketSell("BNBBTC", $quantity);
```

Parameters

| | |
|-------------------|---|
| <i>\$symbol</i> | string the currency symbol |
| <i>\$quantity</i> | string the quantity required |
| <i>\$flags</i> | array additional options for order type |

Returns

array with error message or the order details

Definition at line 410 of file php-binance-api.php.

4.1.3.32 `Binance\API::marketSellTest (string $symbol, $quantity, array $flags = [])`

marketSellTest attempts to create a TEST currency order at given market price

See Also

marketSellTest()

Parameters

| | |
|-------------------|---|
| <i>\$symbol</i> | string the currency symbol |
| <i>\$quantity</i> | string the quantity required |
| <i>\$flags</i> | array additional options for order type |

Returns

array with error message or the order details

Definition at line 425 of file php-binance-api.php.

4.1.3.33 BinanceAPI::miniTicker (callable \$callback)

miniTicker Get miniTicker for all symbols

```
$api->miniTicker(function($api, $ticker) { print_r($ticker); });
```

Parameters

| | |
|-------------------|--|
| <i>\$callback</i> | callable function closer that takes 2 arguments, \$pai and \$ticker data |
|-------------------|--|

Returns

null

Definition at line 2071 of file php-binance-api.php.

4.1.3.34 BinanceAPI::openOrders (string \$symbol = null)

openOrders attempts to get open orders for all currencies or a specific currency

```
$allOpenOrders = $api->openOrders(); $allBNBOrders = $api->openOrders( "BNBBTC" );
```

Parameters

| | |
|-----------------|----------------------------|
| <i>\$symbol</i> | string the currency symbol |
|-----------------|----------------------------|

Returns

array with error message or the order details

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 478 of file php-binance-api.php.

4.1.3.35 BinanceAPI::order (string \$side, string \$symbol, \$quantity, \$price, string \$type = "LIMIT", array \$flags = [], bool \$test = false)

order formats the orders before sending them to the curl wrapper function You can call this function directly or use the helper functions

See Also

```
buy()
sell()
marketBuy()
marketSell() $this->httpRequest( "https://api.binance.com/api/v1/ticker/24hr");
```

Parameters

| | |
|-------------------|--|
| <i>\$side</i> | string typically "BUY" or "SELL" |
| <i>\$symbol</i> | string to buy or sell |
| <i>\$quantity</i> | string in the order |
| <i>\$price</i> | string for the order |
| <i>\$type</i> | string is determined by the symbol bu typicall LIMIT, STOP_LOSS_LIMIT etc. |
| <i>\$flags</i> | array additional transaction options |
| <i>\$test</i> | bool whether to test or not, test only validates the query |

Returns

array containing the response

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 990 of file php-binance-api.php.

4.1.3.36 BinanceAPI::orders (string \$symbol, int \$limit = 500, int \$fromOrderId = 1)

orders attempts to get the orders for all or a specific currency

```
$allBNBOrders = $api->orders( "BNBBTC" );
```

Parameters

| | |
|----------------------|--|
| <i>\$symbol</i> | string the currency symbol |
| <i>\$limit</i> | int the amount of orders returned |
| <i>\$fromOrderId</i> | string return the orders from this order onwards |

Returns

array with error message or array of orderDetails array

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 500 of file php-binance-api.php.

4.1.3.37 BinanceAPI::orderStatus (string \$symbol, \$orderid)

orderStatus attempts to get orders status

```
$orderid = "123456789"; $order = $api->orderStatus("BNBBTC", $orderid);
```

Parameters

| | |
|------------------|------------------------------|
| <i>\$symbol</i> | string the currency symbol |
| <i>\$orderid</i> | string the orderid to cancel |

Returns

array with error message or the order details

Exceptions

| | |
|-------------------------|--|
| <code>\Exception</code> | |
|-------------------------|--|

Definition at line 460 of file php-binance-api.php.

4.1.3.38 `BinanceAPI::prevDay (string $symbol = null)`

prevDay get 24hr ticker price change statistics for symbols

```
$prevDay = $api->prevDay("BNBBTC");
```

Parameters

| | |
|-----------------------|--|
| <code>\$symbol</code> | (optional) symbol to get the previous day change for |
|-----------------------|--|

Returns

array with error message or array of prevDay change

Exceptions

| | |
|-------------------------|--|
| <code>\Exception</code> | |
|-------------------------|--|

Definition at line 735 of file php-binance-api.php.

4.1.3.39 `BinanceAPI::prices ()`

prices get all the current prices

```
$ticker = $api->prices();
```

Returns

array with error message or array of all the currencies prices

Exceptions

| | |
|-------------------------|--|
| <code>\Exception</code> | |
|-------------------------|--|

Definition at line 695 of file php-binance-api.php.

4.1.3.40 `BinanceAPI::sell (string $symbol, $quantity, $price, string $type = "LIMIT", array $flags = [])`

sell attempts to create a currency order each currency supports a number of order types, such as -LIMIT -MARKET -STOP_LOSS -STOP_LOSS_LIMIT -TAKE_PROFIT -TAKE_PROFIT_LIMIT -LIMIT_MAKER

You should check the

See Also

exchangeInfo for each currency to determine what types of orders can be placed against specific pairs

```
$quantity = 1; $price = 0.0005; $order = $api->sell("BNBBTC", $quantity, $price);
```

Parameters

| | |
|-------------------|---|
| <i>\$symbol</i> | string the currency symbol |
| <i>\$quantity</i> | string the quantity required |
| <i>\$price</i> | string price per unit you want to spend |
| <i>\$type</i> | string type of order |
| <i>\$flags</i> | array additional options for order type |

Returns

array with error message or the order details

Definition at line 346 of file php-binance-api.php.

4.1.3.41 `Binance\API::sellTest (string $symbol, $quantity, $price, string $type = "LIMIT", array $flags = [])`

sellTest attempts to create a TEST currency order

See Also

sell()

Parameters

| | |
|-------------------|---|
| <i>\$symbol</i> | string the currency symbol |
| <i>\$quantity</i> | string the quantity required |
| <i>\$price</i> | string price per unit you want to spend |
| <i>\$type</i> | array config |
| <i>\$flags</i> | array config |

Returns

array with error message or empty or the order details

Definition at line 363 of file php-binance-api.php.

4.1.3.42 `Binance\API::setProxy (array $proxyconf)`

setProxy set proxy config by passing in an array of the proxy configuration

```
$proxyConf = [ 'proto' => 'tcp', 'address' => '192.168.1.1', 'port' => '8080', 'user' => 'dude', 'pass' => 'd00d' ];
```

```
$api->setProxy( $proxyconf );
```

Returns

null

Definition at line 860 of file php-binance-api.php.

4.1.3.43 `Binance\API::sortDepth (string $symbol, int $limit = 11)`

sortDepth Sorts depth data for display & getting highest bid and lowest ask

```
$sorted = $api->sortDepth($symbol, $limit);
```

Parameters

| | |
|-----------------|----------------|
| <i>\$symbol</i> | string to sort |
| <i>\$limit</i> | int depth |

Returns

null

Definition at line 1612 of file php-binance-api.php.

4.1.3.44 `BinanceAPI::terminate ($endpoint)`

terminate Terminates websocket endpoints.

View endpoints first: `print_r($api->subscriptions)`

```
$api->terminate('ethbtc_kline@5m');
```

Returns

null

Definition at line 1961 of file php-binance-api.php.

4.1.3.45 `BinanceAPI::ticker ($symbol, callable $callback)`

ticker pulls 24h price change statistics via WebSocket

```
$api->ticker(false, function($api, $symbol, $ticker) { print_r($ticker); });
```

Parameters

| | |
|-------------------|---------------------------------|
| <i>\$symbol</i> | string optional symbol or false |
| <i>\$callback</i> | callable closure |

Returns

null

Definition at line 1789 of file php-binance-api.php.

4.1.3.46 `BinanceAPI::time ()`

time Gets the server time

```
$time = $api->time();
```

Returns

array with error message or array with server time key

Exceptions

| |
|-------------------|
| <i>\Exception</i> |
|-------------------|

Definition at line 556 of file php-binance-api.php.

4.1.3.47 Binance\API::trades (*\$symbols*, callable *\$callback*)

trades Trades WebSocket Endpoint

```
$api->trades(["BNBBTC"], function($api, $symbol, $trades) { echo "{$symbol} trades update".PHP_EOL; print_r($trades); });
```

Parameters

| | |
|-------------------|------------------|
| <i>\$symbols</i> | |
| <i>\$callback</i> | callable closure |

Returns

null

Definition at line 1723 of file php-binance-api.php.

4.1.3.48 Binance\API::userData (& \$balance_callback, & \$execution_callback = false)

userData Issues userDataStream token and keepalive, subscribes to userData WebSocket

```
$balance_update = function($api, $balances) { print_r($balances); echo "Balance update".PHP_EOL; };

$order_update = function($api, $report) { echo "Order update".PHP_EOL; print_r($report); $price = $report['price'];
$quantity = $report['quantity']; $symbol = $report['symbol']; $side = $report['side']; $orderType = $report['order-
Type']; $orderId = $report['orderId']; $orderStatus = $report['orderStatus']; $executionType = $report['orderStatus'];
if( $executionType == "NEW" ) { if( $executionType == "REJECTED" ) { echo "Order Failed! Reason: {"$report['reject-
Reason']}".PHP_EOL; } echo "{$symbol} {$side} {$orderType} ORDER #{orderId} ({$orderStatus})".PHP_EOL;
echo "..price: {"$price}, quantity: {"$quantity}".PHP_EOL; return; }

//NEW, CANCELED, REPLACED, REJECTED, TRADE, EXPIRED echo "{$symbol} {$side} {$executionType}
{$orderType} ORDER #{orderId}".PHP_EOL; }; $api->userData($balance_update, $order_update);
```

Parameters

| | | |
|------|------------------------------------|-------------------|
| | <i>\$balance_ - callback</i> | callable function |
| bool | <i>\$execution_ - callback</i> | callable function |

Returns

null

Exceptions

| |
|-------------------|
| <i>\Exception</i> |
|-------------------|

Definition at line 2022 of file php-binance-api.php.

4.1.3.49 Binance\API::useServerTime ()

useServerTime adds the 'useServerTime'=>true to the API request to avoid time errors

```
$api->useServerTime();
```

Returns

null

Exceptions

| |
|-------------------|
| <i>\Exception</i> |
|-------------------|

Definition at line 540 of file php-binance-api.php.

4.1.3.50 `Binance\API::withdraw (string $asset, string $address, $amount, $addressTag = null)`

withdraw requests a asset be withdrawn from binance to another wallet

```
$asset = "BTC"; $address = "1C5gqLRs96Xq4V2ZZAR1347yUCpHie7sa"; $amount = 0.2; $response = $api->withdraw($asset, $address, $amount);
```

```
$address = "44tLjmXrQNrWJ5NBsEj2R77ZBEgDa3fEe9GLpSf2FRmhhexPvfYDUAB7EXX1Hdb3aMQ9FLqdJ56ya-AhiXoRsceGJCRS3Jxkn"; $addressTag = "0e5e38a01058dbf64e53a4333a5acf98e0d5feb8e523d32e3186c664a9c762c1"; $amount = 0.1; $response = $api->withdraw($asset, $address, $amount, $addressTag);
```

Parameters

| | |
|---------------------|---|
| <i>\$asset</i> | string the currency such as BTC |
| <i>\$address</i> | string the addressed to whihc the asset should be deposited |
| <i>\$amount</i> | double the amount of the asset to transfer |
| <i>\$addressTag</i> | string adtional transactionid required by some assets |

Returns

array with error message or array transaction

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 594 of file php-binance-api.php.

4.1.3.51 `Binance\API::withdrawFee (string $asset)`

withdrawFee get the withdrawal fee for an asset

```
$withdrawFee = $api->withdrawFee( "BTC" );
```

Parameters

| | |
|----------------|-----------------------------|
| <i>\$asset</i> | string currency such as BTC |
|----------------|-----------------------------|

Returns

array with error message or array containing withdrawFee

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 678 of file php-binance-api.php.

4.1.3.52 `Binance\API::withdrawHistory (string $asset = null, array $params = [])`

withdrawHistory get the withdrawal history for an asset

```
$withdrawHistory = $api->withdrawHistory();
```

```
$withdrawHistory = $api->withdrawHistory( "BTC" );
```

Parameters

| | |
|-----------------|--|
| <i>\$asset</i> | string empty or the currency such as BTC |
| <i>\$params</i> | array optional startTime, endTime, status parameters |

Returns

array with error message or array deposit history information

Exceptions

| | |
|-------------------|--|
| <i>\Exception</i> | |
|-------------------|--|

Definition at line 660 of file php-binance-api.php.

4.1.4 Member Data Documentation**4.1.4.1 `Binance\API::$api_key` [protected]**

Definition at line 34 of file php-binance-api.php.

4.1.4.2 `Binance\API::$api_secret` [protected]

Definition at line 35 of file php-binance-api.php.

4.1.4.3 `Binance\API::$base = 'https://api.binance.com/api/'` [protected]

Definition at line 31 of file php-binance-api.php.

4.1.4.4 `Binance\API::$chartQueue = []` [protected]

Definition at line 38 of file php-binance-api.php.

4.1.4.5 `Binance\API::$charts = []` [protected]

Definition at line 39 of file php-binance-api.php.

4.1.4.6 `Binance\API::$curlOpts = []` [protected]

Definition at line 40 of file php-binance-api.php.

4.1.4.7 `Binance\API::$depthCache = []` [protected]

Definition at line 36 of file php-binance-api.php.

4.1.4.8 `Binance\API::$depthQueue = []` [protected]

Definition at line 37 of file php-binance-api.php.

4.1.4.9 `Binance\API::$info` [protected]**Initial value:**

```
= [  
    "timeOffset" => 0
```

Definition at line 41 of file php-binance-api.php.

4.1.4.10 `Binance\API::$proxyConf = null` `[protected]`

Definition at line 44 of file php-binance-api.php.

4.1.4.11 `Binance\API::$requestCount = 0` `[protected]`

Definition at line 46 of file php-binance-api.php.

4.1.4.12 `Binance\API::$stream = 'wss://stream.binance.com:9443/ws/'` `[protected]`

Definition at line 33 of file php-binance-api.php.

4.1.4.13 `Binance\API::$transferred = 0` `[protected]`

Definition at line 45 of file php-binance-api.php.

4.1.4.14 `Binance\API::$wapi = 'https://api.binance.com/wapi/'` `[protected]`

Definition at line 32 of file php-binance-api.php.

Index

\$api_key
 Binance::API, 28
\$api_secret
 Binance::API, 28
\$base
 Binance::API, 28
\$chartQueue
 Binance::API, 28
\$charts
 Binance::API, 28
\$curlOpts
 Binance::API, 28
\$depthCache
 Binance::API, 28
\$depthQueue
 Binance::API, 28
\$info
 Binance::API, 28
\$proxyConf
 Binance::API, 29
\$requestCount
 Binance::API, 29
\$stream
 Binance::API, 29
\$transferred
 Binance::API, 29
\$wapi
 Binance::API, 29
__construct
 Binance::API, 10
__get
 Binance::API, 10
__set
 Binance::API, 10

account
 Binance::API, 10
addToTransferred
 Binance::API, 10
aggTrades
 Binance::API, 11

balances
 Binance::API, 11
Binance, 5
Binance::API
 \$api_key, 28
 \$api_secret, 28
 \$base, 28
 \$chartQueue, 28
 \$charts, 28
 \$curlOpts, 28
 \$depthCache, 28
 \$depthQueue, 28
 \$info, 28
 \$proxyConf, 29
 \$requestCount, 29
 \$stream, 29
 \$transferred, 29
 \$wapi, 29
 __construct, 10
 __get, 10
 __set, 10
 account, 10
 addToTransferred, 10
 aggTrades, 11
 balances, 11
 bookPrices, 11
 buy, 12
 buyTest, 12
 cancel, 12
 candlesticks, 13
 chart, 13
 cumulative, 14
 depositAddress, 14
 depositHistory, 14
 depth, 15
 depthCache, 15
 displayDepth, 15
 exchangeInfo, 16
 first, 16
 getProxyUriString, 16
 getRequestCount, 16
 getTransferred, 17
 highstock, 17
 history, 17
 keepAlive, 17
 kline, 18
 last, 18
 marketBuy, 18
 marketBuyTest, 19
 marketSell, 19
 marketSellTest, 19
 miniTicker, 20
 openOrders, 20
 order, 20
 orderStatus, 21
 orders, 21
 prevDay, 22

- prices, [22](#)
- sell, [22](#)
- sellTest, [23](#)
- setProxy, [23](#)
- sortDepth, [23](#)
- terminate, [24](#)
- ticker, [24](#)
- time, [24](#)
- trades, [24](#)
- useServerTime, [26](#)
- userData, [26](#)
- withdraw, [26](#)
- withdrawFee, [27](#)
- withdrawHistory, [27](#)
- Binance\API, [7](#)
- bookPrices
 - Binance::API, [11](#)
- buy
 - Binance::API, [12](#)
- buyTest
 - Binance::API, [12](#)
- cancel
 - Binance::API, [12](#)
- candlesticks
 - Binance::API, [13](#)
- chart
 - Binance::API, [13](#)
- cumulative
 - Binance::API, [14](#)
- depositAddress
 - Binance::API, [14](#)
- depositHistory
 - Binance::API, [14](#)
- depth
 - Binance::API, [15](#)
- depthCache
 - Binance::API, [15](#)
- displayDepth
 - Binance::API, [15](#)
- exchangeInfo
 - Binance::API, [16](#)
- first
 - Binance::API, [16](#)
- getProxyUriString
 - Binance::API, [16](#)
- getRequestCount
 - Binance::API, [16](#)
- getTransferred
 - Binance::API, [17](#)
- highstock
 - Binance::API, [17](#)
- history
 - Binance::API, [17](#)
- keepAlive
 - Binance::API, [17](#)
- kline
 - Binance::API, [18](#)
- last
 - Binance::API, [18](#)
- marketBuy
 - Binance::API, [18](#)
- marketBuyTest
 - Binance::API, [19](#)
- marketSell
 - Binance::API, [19](#)
- marketSellTest
 - Binance::API, [19](#)
- miniTicker
 - Binance::API, [20](#)
- openOrders
 - Binance::API, [20](#)
- order
 - Binance::API, [20](#)
- orderStatus
 - Binance::API, [21](#)
- orders
 - Binance::API, [21](#)
- prevDay
 - Binance::API, [22](#)
- prices
 - Binance::API, [22](#)
- sell
 - Binance::API, [22](#)
- sellTest
 - Binance::API, [23](#)
- setProxy
 - Binance::API, [23](#)
- sortDepth
 - Binance::API, [23](#)
- terminate
 - Binance::API, [24](#)
- ticker
 - Binance::API, [24](#)
- time
 - Binance::API, [24](#)
- trades
 - Binance::API, [24](#)
- useServerTime
 - Binance::API, [26](#)
- userData
 - Binance::API, [26](#)
- withdraw
 - Binance::API, [26](#)
- withdrawFee
 - Binance::API, [27](#)

withdrawHistory
 Binance::API, [27](#)