



BITS Pilani
Pilani | Dubai | Goa | Hyderabad

Introduction

Network Core

innovate

achieve


lead

Mesh of interconnected routers

Fundamental question: how is data transferred through net?

circuit switching: dedicated circuit per call: telephone net

packet-switching: data sent thru net in discrete “chunks”



Circuit Switching


innovate

achieve

lead

End-end resources reserved for “call”

- link bandwidth, switch capacity
- dedicated resources: no sharing
- circuit-like (guaranteed) performance
- call setup required



Circuit Switching



Network resources (e.g., bandwidth) divided into “pieces”

Pieces allocated to calls

Resource piece *idle* if *not used* by owning call (*no sharing*)

Dividing link bandwidth into “pieces”

- frequency division
- time division

Packet Switching



Each end-end data stream
divided into *packets*

user A, B packets *share*
network resources

each packet uses full link
bandwidth

resources used *as needed*

Resource contention:

Aggregate resource demand
can exceed amount available.

Congestion: packets queue,
wait for link use

Store and forward: packets
move one hop at a time

-Node receives
complete packet before
forwarding


Packet Switching

innovate


achieve

lead

Sequence of A & B packets does not have fixed pattern, shared on demand □ *statistical multiplexing*.



Packet Switching



- Takes L/R seconds to transmit (push out) packet of L bits on to link or R bps
- Entire packet must arrive at router before it can be transmitted on next link: *store and forward*
- delay = $3L/R$ (assuming zero propagation delay)

Example:

- $L = 7.5$ Mbits
- $R = 1.5$ Mbps

Delay ??

Access networks and physical media



How to connect end systems to edge router?

residential access nets


institutional access networks
(school, company)

mobile access networks

Keep in mind:

bandwidth (bits per second) of
access network?

shared or dedicated?



Local area networks




*company/univ **local area network** (LAN) connects end system to edge router*

Ethernet:

shared or dedicated link
connects end system and
router

10 Mbs, 100Mbps, Gigabit
Ethernet



*Networking: A Top Down Approach Featuring the Internet,
Jim Kurose, Keith Ross*

A closer look



network edge:

- applications and hosts


network core:

- routers

- network of networks

access networks, physical media:

- communication links



Access networks and physical media

innovate

achieve

lead

How to connect end systems to edge router?

residential access nets


institutional access networks
(school, company)

mobile access networks

Keep in mind:

bandwidth (bits per second)
of access network?

shared or dedicated?



Local area networks




*company/univ **local area network** (LAN) connects end system to edge router*

Ethernet:

shared or dedicated link
connects end system and
router


10 Mbs, 100Mbps, Gigabit
Ethernet



Wireless access networks



- shared *wireless* access network connects end system to router
 - via base station aka “access point”
- **wireless LANs:**
 - 802.11b/g (WiFi): 11 or 54 Mbps
- **wider-area wireless access**
 - provided by telco operator
 - 3G ~ 384 kbps
 - GPRS in Europe/US



Home networks



Typical home network components:

ADSL or cable modem

router/firewall/NAT

Ethernet

wireless access point

