

# MY360/459 Quantitative Text Analysis: Supervised Scaling Methods

Patrick Gildersleve

Slide content courtesy of Dr Blake Miller

February 12, 2024

Course website: [lse-my459.github.io](https://lse-my459.github.io)

1. Overview and Fundamentals
2. Descriptive Statistical Methods for Text Analysis
3. Automated Dictionary Methods
4. Machine Learning for Texts
5. Supervised Scaling Models for Texts
6. *Reading Week*
7. Unsupervised Models for Scaling Texts
8. Similarity and Clustering Methods
9. Topic models
10. Word embeddings
11. Working with Social Media

# Overview of text as data methods



# Outline

- ▶ From classification to scaling
  - ▶ Basics of supervised scaling methods
  - ▶ Wordscores
  - ▶ Practical aspects
  - ▶ Examples

# From Classification to Scaling

- ▶ Machine learning focuses on identifying classes (**classification**), while social science is typically interested in locating things on latent traits (**scaling**), e.g.:
  - ▶ Policy positions on economic vs social dimension
  - ▶ Inter- and intra-party differences
  - ▶ Soft news vs hard news
  - ▶ Petitioner vs respondent in legal briefs
  - ▶ ...and any other continuous scale
- ▶ But the two methods overlap and can be adapted – will demonstrate later using the Naive Bayes classifier
- ▶ In fact, the class predictions for a collection of words from NB can be adapted to scaling

# Outline


- ▶ From classification to scaling
  - ▶ Basics of supervised scaling methods
  - ▶ [Wordscores](#)
  - ▶ Practical aspects
  - ▶ Examples

# Supervised scaling methods

Wordscores method (Laver, Benoit & Garry, 2003):


- ▶ Two sets of texts
  - ▶ **Reference texts**: texts about which we know something (a scalar dimensional score)
  - ▶ **Virgin texts**: texts about which we know nothing (but whose dimensional score we'd like to know)
- ▶ These are analogous to a “training set” and a “test set” in classification
- ▶ Basic procedure:
  1. Analyze reference texts to obtain word scores
  2. Use word scores to score virgin texts

# Wordscores Procedure






# Wordscores Procedure



# Wordscores Procedure

## The Wordscore Procedure

(Using the UK 1997-2001 Example)




Step 1: Obtain reference texts with a priori known positions (`setref`)

Step 2: Generate word scores from reference texts (`wordscore`)

Step 3: Score each virgin text using word scores (`textscore`)

Step 4: (optional) Transform virgin text scores to original metric

# Wordscores Procedure



## Wordscores mathematically: Reference texts

- ▶ Start with a set of  $I$  *reference* texts, represented by an  $I \times J$  document-feature matrix  $C_{ij}$ , where  $i$  indexes the document and  $j$  indexes the  $J$  total word types
- ▶ Each text will have an associated “score”  $a_i$ , which is a single number locating this text on a single dimension of difference
  - ▶ This can be on a scale metric, such as 1–20
  - ▶ Can use arbitrary endpoints, such as -1, 1
- ▶ We *normalize* the document-feature matrix within each document by converting  $C_{ij}$  into a *relative* document-feature matrix (within document), by dividing  $C_{ij}$  by its word total marginals:

$$F_{ij} = \frac{C_{ij}}{C_{i.}} \quad (1)$$

where  $C_{i.} = \sum_{j=1}^J C_{ij}$

## Wordscores mathematically: Word scores

- Compute an  $I \times J$  matrix of relative document probabilities  $P_{ij}$  for each word in each reference text, as

$$P_{ij} = \frac{F_{ij}}{\sum_{i=1}^I F_{ij}} \quad (2)$$

- This tells us the probability that given the observation of a specific word  $j$ , that we are reading a text of a certain reference document  $i$

## Wordscores mathematically: Word scores (example)

- ▶ Assume we have two reference texts, A and B
- ▶ The word “choice” is used 10 times per 1,000 words in Text A and 30 times per 1,000 words in Text B
- ▶ So  $F_i$  “choice” = { .010, .030 }
- ▶ If we know only that we are reading the word choice in one of the two reference texts, then probability is 0.25 that we are reading Text A, and 0.75 that we are reading Text B

$$P_A \text{ “choice”} = \frac{.010}{(.010 + .030)} = 0.25 \quad (3)$$

$$P_B \text{ “choice”} = \frac{.030}{(.010 + .030)} = 0.75 \quad (4)$$

## Wordscores mathematically: Word scores

- ▶ Compute a  $J$ -length “score” vector  $S$  for each word  $j$  as the average of each document  $i$ ’s scores  $a_i$ , weighted by each word’s  $P_{ij}$ :

$$S_j = \sum_{i=1}^I a_i P_{ij} \quad (5)$$

- ▶ In matrix algebra,  $S = \underset{1 \times J}{a} \cdot \underset{1 \times I}{a} \cdot \underset{I \times J}{P}$
- ▶ This procedure will yield a single “score” for every word that reflects the balance of the scores of the reference documents, weighted by the relative document frequency of its normalized term frequency

## Wordscores mathematically: Word scores

- ▶ Continuing with our example:
  - ▶ We “know” (from independent sources) that Reference Text A has a position of  $-1.0$ , and Reference Text B has a position of  $+1.0$
  - ▶ The score of the word “choice” is then
$$0.25(-1.0) + 0.75(1.0) = -0.25 + 0.75 = +0.50$$



## Wordscores mathematically: Scoring “virgin” texts

- ▶ Here the objective is to obtain a single score for any new text, relative to the reference texts
- ▶ We do this by taking the mean of the scores of its words, weighted by their term frequency
- ▶ So the score  $v_k$  of a virgin document  $k$  consisting of the  $j$  word types is:

$$v_k = \sum_j (F_{kj} \cdot s_j) \quad (6)$$

where  $F_{kj} = \frac{C_{kj}}{C_k}$  as in the reference document relative word frequencies

- ▶ Note that **new words** outside of the set  $J$  may appear in the  $K$  virgin documents — these are simply ignored (because we have no information on their scores)
- ▶ Note also that nothing prohibits reference documents from also being scored as virgin documents

## Wordscores mathematically: Rescaling raw text scores

- ▶ Because of overlapping or non-discriminating words, the raw text scores will be dragged to the interior of the reference scores (we will see this shortly in the results)
- ▶ Some procedures can be applied to rescale them, either to a unit normal metric or to a more “natural” metric
- ▶ Martin and Vanberg (2008) have proposed alternatives to the LBG (2003) rescaling

## Computing confidence intervals

- ▶ The score  $v_k$  of any text represents a weighted mean
- ▶ LBG (2003) used this logic to develop a standard error of this mean using a *weighted variance* of the scores in the virgin text
- ▶ Given some assumptions about the scores being fixed (and the words being conditionally independent), this yields approximately normally distributed errors for each  $v_k$
- ▶ An alternative would be to bootstrap the textual data prior to constructing  $C_{ij}$  and  $C_{kj}$  — see Lowe and Benoit (2012)



# Pros and Cons of the Wordscores approach

- ▶ Estimates unknown positions on a priori scales – hence no inductive scaling with a posteriori interpretation of unknown policy space
- ▶ Very dependent on correct identification of:
  - ▶ appropriate [reference texts](#)
  - ▶ appropriate [reference scores](#)

# Outline

- ▶ From classification to scaling
  - ▶ Basics of supervised scaling methods
  - ▶ Wordscores
  - ▶ Practical aspects
  - ▶ Examples

## Suggestions for choosing reference texts

- ▶ Texts need to contain information representing a clearly dimensional position
- ▶ Dimension must be known a priori. Sources might include:
  - ▶ Survey scores or manifesto scores
  - ▶ Arbitrarily defined scales (e.g. -1.0 and 1.0)
- ▶ Should be as discriminating as possible: extreme texts on the dimension of interest, to provide reference anchors
- ▶ Need to be from the same lexical universe as virgin texts
- ▶ Should contain lots of words

## Suggestions for choosing reference values

- ▶ Must be “known” through some trusted external source
- ▶ For any pair of reference values, all scores are simply linear rescalings, so might as well use  $(-1, 1)$
- ▶ The “middle point” will not be the midpoint, however, since this will depend on the relative word frequency of the reference documents
- ▶ Reference texts if scored as virgin texts will have document scores more extreme than other virgin texts
- ▶ With three or more reference values, the mid-point is mapped onto a multi-dimensional simplex. The values now matter but only in relative terms (we are still investigating this fully)



## Multinomial Bayes model of Class given a Word

### Class posterior probabilities

$$P(c_k|w_j) = \frac{P(w_j|c_k)P(c_k)}{P(w_j|c_k)P(c_k) + P(w_j|c_{\neg k})P(c_{\neg k})}$$

- ▶ This represents the **posterior probability of membership in class  $k$**  for word  $j$
- ▶ Under *certain conditions*, this is identical to what LBG (2003) called  $P_{wr}$
- ▶ Under those conditions, **the LBG “wordscore” is the linear difference between  $P(c_k|w_j)$  and  $P(c_{\neg k}|w_j)$**

## “Certain conditions”

- ▶ The LBG approach required the identification not only of texts for each training class, but also “reference” scores attached to each training class
- ▶ Consider two “reference” scores  $s_1$  and  $s_2$  attached to two classes  $k = 1$  and  $k = 2$ . Taking  $P_1$  as the posterior  $P(k = 1|w = j)$  and  $P_2$  as  $P(k = 2|w = j)$ , A generalised score  $s_j^*$  for the word  $j$  is then

$$\begin{aligned}s_j^* &= s_1 P_1 + s_2 P_2 \\&= s_1 P_1 + s_2 (1 - P_1) \\&= s_1 P_1 + s_2 - s_2 P_1 \\&= P_1 (s_1 - s_2) + s_2\end{aligned}$$

## “Certain conditions”: More than two reference classes

- For more than two reference classes, if the reference scores are ordered such that  $s_1 < s_2 < \cdots < s_K$ , then

$$\begin{aligned}s_j^* &= s_1 P_1 + s_2 P_2 + \cdots + s_K P_K \\&= s_1 P_1 + s_2 P_2 + \cdots + s_K \left(1 - \sum_{k=1}^{K-1} P_k\right) \\&= \sum_{k=1}^{K-1} P_i (s_k - s_K) + s_I\end{aligned}$$

A simpler formulation:

Use reference scores such that  $s_1 = -1.0, s_K = 1.0$

- ▶ From above equations, it should be clear that any set of reference scores can be linearly rescaled to endpoints of  $-1.0, 1.0$
- ▶ This simplifies the “simple word score”

$$s_j^* = (1 - 2P_1) + \sum_{k=2}^{K-1} P_k(s_k - 1)$$

- ▶ which simplifies with just two reference classes to:

$$s_j^* = 1 - 2P_1$$

# Implications

- ▶ LBG's “word scores” come from a linear combination of class posterior probabilities from a Bayesian model of class conditional on words
- ▶ We might as well always anchor reference scores at  $-1.0, 1.0$
- ▶ There is a special role for reference classes in between  $-1.0, 1.0$ , as they balance between “pure” classes — more in a moment
- ▶ There are alternative scaling models, such that used in Beauchamp's (2012) “Bayesscore”, which is simply the difference in logged class posteriors at the word level. For  $s_1 = -1.0, s_2 = 1.0$ ,

$$\begin{aligned}s_j^B &= -\log P_1 + \log P_2 \\ &= \log \frac{1 - P_1}{P_1}\end{aligned}$$

## Moving to the document level

- ▶ The “Naive” Bayes model of a joint document-level class posterior assumes conditional independence, to multiply the word likelihoods from a “test” document, to produce:

$$P(c|d) = P(c) \frac{\prod_j P(w_j|c)}{P(w_j)}$$

- ▶ So we *could* consider a document-level relative score, e.g.  $1 - 2P(c_1|d)$  (for a two-class problem)
- ▶ But this turns out to be *useless*, since the predictions of class are **highly separated**

## Moving to the document level

- ▶ A better solution is to score a test document as the **arithmetic mean** of the **scores of its words**
- ▶ This is exactly the solution proposed by LBG (2003)
- ▶ Beauchamp (2012) proposes a “Bayesscore” which is the arithmetic mean of the log difference word scores in a document – which yields extremely similar results

And now for some demonstrations with data...


# Outline

- ▶ From classification to scaling
  - ▶ Basics of supervised scaling methods
  - ▶ Wordscores
  - ▶ Practical aspects
  - ▶ [Examples](#)




# Application 1: Daily speeches from LBG (2003)

(a) NB Speech scores by party, smooth=0, imbalanced priors




(b) Document scores from NB v. Classic Wordscores




- ▶ three reference classes (Opposition, Opposition, Government) at  $\{-1, -1, 1\}$
- ▶ no smoothing

# Application 1: Daily speeches from LBG (2003)

(c) NB Speech scores by party, smooth=1, uniform class priors



(d) Document scores from NB v. Classic Wordscores




- ▶ two reference classes (Opposition+Opposition, Government) at  $\{-1, 1\}$
- ▶ Laplace smoothing


# Application 2: Classifying legal briefs (Evans et al 2007)

## Wordscores v. Bayesscore

(a) Word level




(b) Document level




- ▶ Training set: Petitioner and Respondent litigant briefs from *Grutter/Gratz v. Bollinger* (a U.S. Supreme Court case)
- ▶ Test set: 98 amicus curiae briefs (whose P or R class is known)

## Application 2: Classifying legal briefs (Evans et al 2007)

### Posterior class prediction from NB versus log wordscores




## Application 3: Scaling environmental interest groups (Klüver 2009)



- ▶ Dataset: text of online consultation on EU environmental regulations
- ▶ Reference texts: most extreme pro- and anti-regulation groups

## Application 4: LBG's British manifestos

### More than two reference classes



- ▶ x-axis: Reference scores of  $\{5.35, 8.21, 17.21\}$  for Lab, LD, Conservatives
- ▶ y-axis: Reference scores of  $\{10.21, 5.26, 15.61\}$