

10/10/2024 8:48:29 AM Autodesk Docs Micron-B42-Campus-2022-PAE-S&E-MAIN-XXXX.ctb

FRONT-OF-HOUSE LUMINAIRE SCHEDULE											
FIXTURE TYPE	PRODUCT DESCRIPTION	BASIS OF DESIGN MANUFACTURER	SIZE	LIGHT SOURCE	INPUT WATTS	POWER SUPPLY	INPUT VOLTAGE	FINISH	MOUNTING	NOTES	
L1	RECESSED 4" WIDE LINEAR IN ALUMINUM EXTRUSION FLUSH FROSTED LENS, WIDESPREAD DIRECT DISTRIBUTION, ACT COLLAB, MULTIPURPOSE, PROJECT ROOM	FINELITE HP-4 HP-4-R-D-(LENGTH)-H-835-F-98LG-(VOLTAGE)-SC-FC-1%-MOUNTING-FE-(FINISH)-(OPTIONS)	4" W x SEE PLANS FOR LENGTH x 4" H	LED, 3600K, 80 CRI, 932 lm/lf	9 W/lf	INTEGRAL, 0-10V, DIMS TO 1%	277V	WHITE	RECESSED	1. PROVIDE CONTINUOUS LENGTHS AS INDICATED IN ARCHITECTURAL RCPS. FIXTURES TO BE MOUNTED CONTINUOUSLY, END-TO-END WITH NO MORE THAN 3" OF UNIT SPACE AT EITHER END OF RUN.	
L2A	RECESSED 2" LINEAR IN ALUMINUM EXTRUSION FLUSH FROSTED LENS, WIDESPREAD DIRECT DISTRIBUTION, WOOD SLAT CEILING TYPICAL ELEVATOR LOBBY	FINELITE HP-2 HP-2-R-D-(LENGTH)-H-835-F-98LG-2-Z77-SC-FC-1%-MOUNTING-FE-(FINISH)-(OPTIONS)	2" W x SEE PLANS FOR LENGTH x 4" H	LED, 3600K, 80 CRI, 639 lm/lf	7 W/lf	INTEGRAL, 0-10V, DIMS TO 1%	277V	WHITE	RECESSED	1. PROVIDE CONTINUOUS LENGTHS AS INDICATED IN ARCHITECTURAL RCPS. FIXTURES TO BE MOUNTED CONTINUOUSLY, END-TO-END WITH NO MORE THAN 3" OF UNIT SPACE AT EITHER END OF RUN.	
L2B	RECESSED 2" WIDE LINEAR IN ALUMINUM EXTRUSION FLUSH FROSTED LENS, WIDESPREAD DIRECT DISTRIBUTION, GYP CEILING LEVEL 1 ELEVATOR LOBBY	FINELITE HP-2 HP-2-R-D-(LENGTH)-H-835-F-98LG-2-Z77-SC-FC-1%-MOUNTING-FE-(FINISH)-(OPTIONS)	2" W x SEE PLANS FOR LENGTH x 4" H	LED, 3600K, 80 CRI, 639 lm/lf	7 W/lf	INTEGRAL, 0-10V, DIMS TO 1%	277V	WHITE	RECESSED	1. PROVIDE CONTINUOUS LENGTHS AS INDICATED IN ARCHITECTURAL RCPS. FIXTURES TO BE MOUNTED CONTINUOUSLY, END-TO-END WITH NO MORE THAN 3" OF UNIT SPACE AT EITHER END OF RUN.	
L2C	RECESSED 2" WIDE LINEAR IN ALUMINUM EXTRUSION, FLUSH FROSTED LENS, WIDESPREAD DIRECT DISTRIBUTION, GYP CEILING LEVEL 1 ELEVATOR LOBBY	FINELITE HP-2 HP-2-R-D-(LENGTH)-H-835-F-98LG-2-Z77-SC-FC-1%-MOUNTING-FE-(FINISH)-(OPTIONS)	2" W x SEE PLANS FOR LENGTH x 4" H	LED, 3600K, 80 CRI, 336 lm/lf	4 W/lf	INTEGRAL, 0-10V, DIMS TO 1%	277V	WHITE	RECESSED	1. PROVIDE CONTINUOUS LENGTHS AS INDICATED IN ARCHITECTURAL RCPS. FIXTURES TO BE MOUNTED CONTINUOUSLY, END-TO-END WITH NO MORE THAN 3" OF UNIT SPACE AT EITHER END OF RUN.	
L3	PERIMETER SLOT 2" WIDE LINEAR IN ALUMINUM EXTRUSION FLUSH FROSTED LENS, ASYMMETRIC THROW COLLAB SPACE, FOCUS ROOM	FINELITE HP-2 HP-2WS-4D-(LENGTH)-H-835-98LG-2-Z77-SC-FC-1%-WB(MOUNTING)-FE-SW	3 1/8" W x SEE PLANS FOR LENGTH x 8" H	LED, 3600K, 80CRI, 619 lm/lf	7 W/lf	INTEGRAL, 0-10V, DIMS TO 10%	277V	WHITE	RECESSED	1. PROVIDE CONTINUOUS LENGTHS AS INDICATED IN ARCHITECTURAL RCPS. FIXTURES TO BE MOUNTED CONTINUOUSLY, END-TO-END WITH NO MORE THAN 3" OF UNIT SPACE AT EITHER END OF RUN.	
L3A	PERIMETER SLOT 2" WIDE LINEAR IN ALUMINUM EXTRUSION, FLUSH FROSTED LENS, ASYMMETRIC THROW, LOW OUTPUT RESTROOM	FINELITE HP-2 HP-2WS-4D-(LENGTH)-H-835-98LG-2-Z77-SC-FC-1%-WB(MOUNTING)-FE-SW	3 1/8" W x SEE PLANS FOR LENGTH x 8" H	LED, 3600K, 80CRI, 410 lm/lf	4 W/lf	INTEGRAL, 0-10V, DIMS TO 10%	277V	WHITE	RECESSED	1. PROVIDE CONTINUOUS LENGTHS AS INDICATED IN ARCHITECTURAL RCPS. FIXTURES TO BE MOUNTED CONTINUOUSLY, END-TO-END WITH NO MORE THAN 3" OF UNIT SPACE AT EITHER END OF RUN.	
L3B	PERIMETER SLOT 2" WIDE LINEAR IN ALUMINUM EXTRUSION, FLUSH FROSTED LENS, ASYMMETRIC THROW, LOW OUTPUT RESTROOM	FINELITE HP-2 HP-2WS-4D-(LENGTH)-H-835-98LG-2-Z77-SC-FC-1%-WB(MOUNTING)-FE-SW	3 1/8" W x SEE PLANS FOR LENGTH x 8" H	LED, 3000K, 80CRI, 410 lm/lf	4 W/lf	INTEGRAL, 0-10V, DIMS TO 10%	277V	WHITE	RECESSED	1. PROVIDE CONTINUOUS LENGTHS AS INDICATED IN ARCHITECTURAL RCPS. FIXTURES TO BE MOUNTED CONTINUOUSLY, END-TO-END WITH NO MORE THAN 3" OF UNIT SPACE AT EITHER END OF RUN.	
L4	RECESSED 2" WIDE LINEAR DOWNLIGHT ASYMMETRIC OPTIC IN ALUMINUM EXTRUSION, FLUSH FROSTED LENS, GYP CEILING COLLAB, PROJECT ROOM, COPY/SATELLITE	FINELITE HP-2 HP-2-R-D-(LENGTH)-H-835-(DAO)-98LG-2-Z77-SC-FC-1%-MOUNTING-FE-(FINISH)-(OPTIONS)	2 1/4" W x SEE PLANS FOR LENGTH x 4" H	LED, 3600K, 80CRI, 481 lm/lf	4 W/lf	INTEGRAL, 0-10V, DIMS TO 1%	277V	WHITE	RECESSED	1. PROVIDE CONTINUOUS LENGTHS AS INDICATED IN ARCHITECTURAL RCPS. FIXTURES TO BE MOUNTED CONTINUOUSLY, END-TO-END WITH NO MORE THAN 3" OF UNIT SPACE AT EITHER END OF RUN.	
L4A	RECESSED 2" WIDE LINEAR WALLWASH IN ALUMINUM EXTRUSION, FLUSH FROSTED LENS, GYP CEILING SATELLITE PANTRY, MOTHERS ROOM	FINELITE HP-2 HP-2-R-WW-D-(LENGTH)-H-835-F-98LG-2-Z77-SC-FC-1%-MOUNTING-FE-(FINISH)-(OPTIONS)	2 1/4" W x SEE PLANS FOR LENGTH x 4" H	LED, 3600K, 80CRI, 193 lm/lf	3 W/lf	INTEGRAL, 0-10V, DIMS TO 1%	277V	WHITE	RECESSED		
L4B	RECESSED 2" WIDE LINEAR DOWNLIGHT ASYMMETRIC OPTIC IN ALUMINUM EXTRUSION, FLUSH FROSTED LENS, ACT MEDIUM COLLAB	FINELITE HP-2 HP-2-R-D-(LENGTH)-H-835-(DAO)-98LG-2-Z77-SC-FC-1%-MOUNTING-FE-(FINISH)-(OPTIONS)	2 1/4" W x SEE PLANS FOR LENGTH x 4" H	LED, 3600K, 80CRI, 481 lm/lf	4 W/lf	INTEGRAL, 0-10V, DIMS TO 1%	277V	WHITE	RECESSED		
L5	SUSPENDED 2" WIDE LINEAR IN ALUMINUM EXTRUSION, ADJUSTABLE AIRCRAFT CABLE, FLUSH FROSTED LENS, WIDE SPREAD DIRECT DISTRIBUTION, NOMINAL 48" LENGTH LEVEL 2 DINING	FINELITE HP-2 HP-2-P-D-4FT-H-835-F-98LG-2-Z77-SC-FC-10%-FA(LENGTH)-CA-FE-(FINISH)-(OPTIONS)	2 1/4" W x SEE PLANS FOR LENGTH x 4" H	LED, 3600K, 80CRI, 612 lm/lf	7 W/lf	INTEGRAL, 0-10V, DIMS TO 10%	277V	STANDARD PER ARCHITECTURAL	SUSPENDED	ALIGN BOTTOM OF FIXTURE WITH BOTTOM OF BAFFLE. CONTRACTOR TO CONFIRM SUSPENSION LENGTH PRIOR TO ORDER.	
L6	SUSPENDED 2" WIDE LINEAR WALL WASH IN ALUMINUM EXTRUSION, DIRECT DISTRIBUTION, ADJUSTABLE AIRCRAFT CABLE, NOMINAL 48" LENGTH OPEN OFFICE/CIRCULATION	FINELITE HP-2 HP-2-P-WW-D-4FT-H-835-K-SW-Z77-SC-FC-10%-FA(LENGTH)-CA-FE-(FINISH)-(OPTIONS)	2 1/4" W x SEE PLANS FOR LENGTH x 4" H	LED, 3600K, 80CRI, 292 lm/lf	4 W/lf	INTEGRAL, 0-10V, DIMS TO 10%	277V	STANDARD PER ARCHITECTURAL	SUSPENDED	ALIGN BOTTOM OF FIXTURE WITH BOTTOM OF BAFFLE. CONTRACTOR TO CONFIRM SUSPENSION LENGTH PRIOR TO ORDER.	
L6A	SUSPENDED 2" WIDE LINEAR WALL WASH IN ALUMINUM EXTRUSION, DIRECT DISTRIBUTION, ADJUSTABLE AIRCRAFT CABLE LEVEL 2 DINING	FINELITE HP-2 HP-2-P-WW-D-(LENGTH)-(OUTPUT)-835-K-SW-Z77-SC-FC-10%-FA(LENGTH)-CA-FE-(FINISH)-(OPTIONS)	2 1/4" W x SEE PLANS FOR LENGTH x 4" H	LED, 3600K, 80CRI, 292 lm/lf	4 W/lf	INTEGRAL, 0-10V, DIMS TO 10%	277V	STANDARD PER ARCHITECTURAL	SUSPENDED	ALIGN BOTTOM OF FIXTURE WITH BOTTOM OF BAFFLE. CONTRACTOR TO CONFIRM SUSPENSION LENGTH PRIOR TO ORDER.	
L7	SUSPENDED 2" WIDE LINEAR IN ALUMINUM EXTRUSION, ADJUSTABLE AIRCRAFT CABLE, WIDE SPREAD BATWING DISTRIBUTION DOWN OPEN OFFICE	FOCALPOINT SEEM2 FMS02.S-BW-H-1000L-35K-1C-UW-L-1-(MOUNTING)-WH-(LENGTH)	2 6/4" W x SEE PLANS FOR LENGTH x 4 3/4" H	LED, 3600K, 80CRI, 1000 lm/lf	10 W/lf	INTEGRAL, 0-10V, DIMS TO 10%	UNV	WHITE	SUSPENDED	1. REFER TO ARCHITECTURAL ELEVATION FOR FIXTURE MOUNTING HEIGHT. LUMA RECOMMEND 9'-0" A.F.F. 2. FIXTURE TO APPEAR AS ONE CONTINUOUS LENGTH. PROVIDE DAYLIGHT AND EMERGENCY POWER SEGMENTS PER FIXTURE AS INDICATED ON ELECTRICAL DRAWINGS. DESIGN INTENT FOR DAYLIGHT CONTROLLED SEGMENTS TO BE THE SAME LENGTH ACROSS SPACE.	
L8	RECESSED 2" WIDE LINEAR IN ALUMINUM EXTRUSION FLUSH FROSTED LENS, WIDESPREAD DIRECT DISTRIBUTION, GYP CEILING LEVEL 2 CONNECTING SPACE	FINELITE HP-2 HP-2-R-D-(LENGTH)-H-835-F-98LG-2-Z77-SC-FC-1%-MOUNTING-FE-(FINISH)-(OPTIONS)	2" W x SEE PLANS FOR LENGTH x 4" H	LED, 3600K, 80 CRI, 639 lm/lf	7 W/lf	INTEGRAL, 0-10V, DIMS TO 1%	277V	WHITE	RECESSED	1. PROVIDE CONTINUOUS LENGTHS AS INDICATED IN ARCHITECTURAL RCPS. FIXTURES TO BE MOUNTED CONTINUOUSLY, END-TO-END WITH NO MORE THAN 3" OF UNIT SPACE AT EITHER END OF RUN.	
L8A	SUSPENDED 2" WIDE LINEAR IN ALUMINUM EXTRUSION, DIRECT AND INDIRECT DISTRIBUTION, ADJUSTABLE AIRCRAFT CABLE LEVEL 7 EXEC OFFICE	FINELITE HP-2 HP-2-P-RG-ID-(LENGTH)-S-835-W5Q-RG-D-98LG-2-Z77-SC-FC-10%-FA(LENGTH)-CA-DE-(FINISH)-(OPTIONS)	2 1/4" W x SEE PLANS FOR LENGTH x 2" H	LED, 3600K, 80CRI, 146 lm/lf	7 W/lf	INTEGRAL, 0-10V, DIMS TO 10%	277V	STANDARD PER ARCHITECTURAL	SUSPENDED	REFER TO ARCHITECTURAL ELEVATION FOR FIXTURE MOUNTING HEIGHT.	
L8B	SUSPENDED 2" WIDE LINEAR IN ALUMINUM EXTRUSION, DIRECT AND INDIRECT DISTRIBUTION, ADJUSTABLE AIRCRAFT CABLE LEVEL 7 EXEC CONFERENCE	FINELITE HP-2 HP-2-P-RG-ID-(LENGTH)-B-B-835-W5Q-RG-D-98LG-2-Z77-SC-FC-10%-FA(LENGTH)-CA-DE-(FINISH)-(OPTIONS)	2 1/4" W x SEE PLANS FOR LENGTH x 2" H	LED, 3600K, 80CRI, 938 lm/lf	9 W/lf	INTEGRAL, 0-10V, DIMS TO 10%	277V	STANDARD PER ARCHITECTURAL	SUSPENDED	REFER TO ARCHITECTURAL ELEVATION FOR FIXTURE MOUNTING HEIGHT.	
L9	LED RECESSED 2X2 TROFFER AT ACT OFFICE SPACE	LITHONIA LIGHTING 28L17 28L17-240L-ADSM-Z77-GZ1-LPR35-0-10V (OPTION)-H-(MOUNTING)	2" W x 2" H	LED, 3600K, 80CRI, 4000 lm/lf	16 W/lf	INTEGRAL, 0-10V, DIMS TO 10%	277V	WHITE	RECESSED	CONFIRM CEILING TYPE PRIOR TO ORDER.	
L10	4" ROUND RECESSED DOWNLIGHT, MEDIUM-WIDE DIFFUSE BEAM, CLEAR LENS WITH TRIM FOR GYP CEILING, NSF2 RATED FOH KITCHENS	GOTHAM EVO 4 EVO4FS-3915-DFF-SMO-MVOLT	4" DIA W x 6 5/8" H	LED, 3600K, 80CRI, 1500 lm	20 W	INTEGRAL, NON-DIMMING	UNV	WHITE TRIM CLEAR LENS	RECESSED	CONFIRM CEILING TYPE PRIOR TO ORDER. PROVIDE THICKER FLANGE AS NECESSARY FOR CEILING INSTALL.	
L11	4" ROUND RECESSED DOWNLIGHT, MEDIUM-WIDE DIFFUSE BEAM, DIFFUSE LENS WITH TRIM FOR ACT CIRCULATION	GOTHAM EVO 4 EVO4 3910-AR-LD-MMD-Z77-GZ10-(CONTROL INTERFACE)-(EM OPTION)	4" DIA W x 4" L x 6 5/8" H	LED, 3600K, 80CRI, 1000 lm	9 W	INTEGRAL, 0-10V, DIMS TO 10%	277V	MATTE-DIFFUSE REFLECTOR, WHITE TRIM	RECESSED	CONFIRM CEILING TYPE PRIOR TO ORDER. PROVIDE THICKER FLANGE AS NECESSARY FOR CEILING INSTALL.	
L11A	4" ROUND RECESSED DOWNLIGHT, MEDIUM-WIDE DIFFUSE BEAM, DIFFUSE LENS WITH TRIM FOR ACT, HIGH OUTPUT CIRCULATION	GOTHAM EVO 4 EVO4 3915-AR-LD-MMD-Z77-GZ10-(CONTROL INTERFACE)-(EM OPTION)	4" DIA W x 4" L x 6 5/8" H	LED, 3600K, 80CRI, 1500 lm	14 W	INTEGRAL, 0-10V, DIMS TO 10%	277V	MATTE-DIFFUSE REFLECTOR, WHITE TRIM	RECESSED	CONFIRM CEILING TYPE PRIOR TO ORDER. PROVIDE THICKER FLANGE AS NECESSARY FOR CEILING INSTALL.	
L11B	4" ROUND RECESSED DOWNLIGHT, MEDIUM-WIDE DIFFUSE BEAM, DIFFUSE LENS WITH TRIM FOR GYP CEILING GENERAL	GOTHAM EVO 4 EVO4 3910-AR-(TRIM STYLE)-LD-MMD-Z77-GZ10-(CONTROL INTERFACE)-(EM OPTION)	4" DIA W x 4" L x 6 5/8" H	LED, 3600K, 80CRI, 1000 lm	9 W	INTEGRAL, 0-10V, DIMS TO 10%	277V	MATTE-DIFFUSE REFLECTOR, WHITE TRIM	RECESSED	CONFIRM CEILING TYPE PRIOR TO ORDER. PROVIDE THICKER FLANGE AS NECESSARY FOR CEILING INSTALL.	
L11C	4" ROUND RECESSED DOWNLIGHT, MEDIUM-WIDE DIFFUSE BEAM, DIFFUSE LENS WITH TRIM, ACT MOTHERS ROOM, INTERFAITH, CARE ROOM	GOTHAM EVO 4 EVO4 2710-AR-(TRIM STYLE)-LD-MMD-Z77-GZ10-(CONTROL INTERFACE)-(EM OPTION)	4" DIA W x 4" L x 6 5/8" H	LED, 2700K, 80CRI, 1000 lm	9 W	INTEGRAL, 0-10V, DIMS TO 10%	277V	MATTE-DIFFUSE REFLECTOR, WHITE TRIM	RECESSED	CONFIRM CEILING TYPE PRIOR TO ORDER. PROVIDE THICKER FLANGE AS NECESSARY FOR CEILING INSTALL.	
L12	2" RECESSED SQUARE DOWNLIGHT, DEEP DOWNLIGHT REFLECTOR, SELF FLANGED, 80 DEG BEAM, PANEL CEILING SYSTEM LEVEL 1 AMENITIES	AQUILUX AX25Q SERIES AX25Q D G2-12LM-35K-90CRI-60Q-ZT-MVOLT-25QD-CD-SF-(CEILING THICKNESS)	3" W x 3" L x 3 1/2" H	LED, 3600K, 90CRI, 1200 lm	14 W	INTEGRAL, 0-10V, DIMS TO 1%	277V	CLEAR DIFFUSE REFLECTOR, WHITE PAINTABLE TRIM	RECESSED	CONFIRM CEILING THICKNESS PRIOR TO ORDER. PROVIDE THICKER FLANGE AS NECESSARY FOR CEILING INSTALL.	
L12A	2" RECESSED SQUARE DOWNLIGHT, DEEP DOWNLIGHT REFLECTOR, SELF FLANGED, 56 DEG BEAM, GYP CEILING LEVEL 7 EXEC, LEVEL 1	AQUILUX AX25Q SERIES AX25Q D G2-12LM-35K-90CRI-48Q-ZT-MVOLT-25QD-CD-SF-(CEILING THICKNESS)	3" W x 3" L x 3 1/2" H	LED, 3600K, 90CRI, 1206 lm	15 W	INTEGRAL, 0-10V, DIMS TO 1%	UNV	CLEAR DIFFUSE REFLECTOR, WHITE PAINTABLE TRIM	RECESSED	CONFIRM CEILING THICKNESS PRIOR TO ORDER. PROVIDE THICKER FLANGE AS NECESSARY FOR CEILING INSTALL.	
L12B	2" RECESSED SQUARE DOWNLIGHT, DEEP DOWNLIGHT REFLECTOR, SELF FLANGED, 45 DEG BEAM, HIGH OUTPUT, GYP CEILING LEVEL 1 DOUBLE-HEIGHT SPACES	AQUILUX AX25Q SERIES AX25Q D G2-16LM-35K-90CRI-48Q-ZT-MVOLT-25QD-CD-SF-(CEILING THICKNESS)	3" W x 3" L x 3 1/2" H	LED, 3600K, 90CRI, 1500 lm	17 W	INTEGRAL, 0-10V, DIMS TO 1%	277V	CLEAR DIFFUSE REFLECTOR, WHITE PAINTABLE TRIM	RECESSED	CONFIRM CEILING THICKNESS PRIOR TO ORDER. PROVIDE THICKER FLANGE AS NECESSARY FOR CEILING INSTALL.	
L12C	2" RECESSED SQUARE DOWNLIGHT, DEEP DOWNLIGHT REFLECTOR, SELF FLANGED, 45 DEG BEAM, ACT CEILING LEVEL 7, GREEN ROOM	AQUILUX AX25Q SERIES AX25Q D G2-12LM-35K-90CRI-48Q-ZT-MVOLT-25QD-CD-SF-(CEILING THICKNESS)	3" W x 3" L x 3 1/2" H	LED, 3600K, 90CRI, 1200 lm	14 W	INTEGRAL, 0-10V, DIMS TO 1%	277V	CLEAR DIFFUSE REFLECTOR, WHITE PAINTABLE TRIM	RECESSED	CONFIRM CEILING THICKNESS PRIOR TO ORDER. PROVIDE THICKER FLANGE AS NECESSARY FOR CEILING INSTALL.	
L12D	2" RECESSED SQUARE DOWNLIGHT, DEEP DOWNLIGHT REFLECTOR, SELF FLANGED, 60X20 LINEAR SPREAD LENS, LOWER OUTPUT, GYP CEILING CIRCULATION	AQUILUX AX25Q SERIES AX25Q D G2-98LM-35K-90CRI-48Q-ZT-MVOLT-25QD-CD-WHSF-(CEILING THICKNESS)	3" W x 3" L x 3 1/2" H	LED, 3600K, 90CRI, 800 lm	10 W	INTEGRAL, 0-10V, DIMS TO 1%	277V	CLEAR DIFFUSE REFLECTOR, WHITE PAINTABLE TRIM	RECESSED	1. CONFIRM CEILING THICKNESS PRIOR TO ORDER. PROVIDE THICKER FLANGE AS NECESSARY FOR CEILING INSTALL. 2. FIXTURE COMES WITH LINEAR SPREAD LENS. LENS TO BE ORIENTED ALONG FIXTURE'S MARCHING DIRECTION TO CREATE A CONSISTENT PATH OF LIGHT.	
L12F	2" RECESSED SQUARE DOWNLIGHT, DEEP DOWNLIGHT REFLECTOR, SELF FLANGED, 80 DEG BEAM, WOOD CEILING LEVEL 1 LOBBY	AQUILUX AX25Q SERIES AX25Q D G2-12LM-35K-90CRI-60Q-ZT-MVOLT-25QD-CD-FM-(CEILING THICKNESS)	3" W x 3" L x 3 1/2" H	LED, 3600K, 90CRI, 1200 lm	14 W	INTEGRAL, 0-10V, DIMS TO 1%	277V	CLEAR DIFFUSE REFLECTOR, WHITE PAINTABLE TRIM	RECESSED	CONFIRM CEILING THICKNESS PRIOR TO ORDER. PROVIDE THICKER FLANGE AS NECESSARY FOR CEILING INSTALL.	
L12G	2" RECESSED SQUARE DOWNLIGHT, DEEP REFLECTOR, FLANGELESS AT ACOUSTIC COFFERED CEILING, 45 DEG BEAM, DAMP LOCATION	AQUILUX AX25Q SERIES AX25Q D G2-16LM-35K-90CRI-48Q-ZT-MVOLT-25QD-CD-FM-(CEILING THICKNESS)	3" W x 3" L x 3 1/2" H	LED, 3600K, 90CRI, 1500 lm	17 W	INTEGRAL, 0-10V, DIMS TO 1%	UNV	CLEAR DIFFUSE REFLECTOR	RECESSED	CONFIRM CEILING THICKNESS PRIOR TO ORDER. PROVIDE THICKER FLANGE AS NECESSARY FOR CEILING INSTALL.	
L13	CHEF'S TABLE, PRIVATE DINING PENDANT 2" SQUARE CYLINDER DOWNLIGHT, STEM MOUNT, 40 DEG BEAM, SQUARE CANOPY THE GRILL AT COFFERED CEILING	LINDSEY SQUARE REED PENDANT LRD SQPN-6-35-10-(FINISH)-40-(CANOPY)-6-10V @ 10% DIMMING-SQB-R508	2 5/8" W x 6 5/8" H	LED, 3600K, 80CRI, 1000 lm	7 W	INTEGRAL, 0-10V, DIMS TO 10%	277	BLACK OR PER ARCHITECTURAL	SUSPENDED	FIELD-CUTTABLE STEM. FIXTURE TO SUSPENDED JUST BELOW BOTTOM OF COFFERED CEILING. REFER TO ARCHITECTURAL DRAWINGS.	
L14	CORD MOUNT SUSPENDED 2" CYLINDER DOWNLIGHT, 45 DEG, BEAM DISTRIBUTION DINING CIRCULATION BETWEEN BAFFLES	GOTHAM INICIO 2 IC02CC-35-10-AR-LS-45Q-MVOLT-45QZ-IBXCC-CCAN-C120-DBL	3 1/8" DIA W x 5" H	LED, 3600K, 80CRI, 1000 lm	12 W	INTEGRAL, 0-10V, DIMS TO 1%	UNV	REFLECTOR: CLEAR, SEMI-SPECULAR HOUSING: MATTE BLACK OR PER ARCHITECTURAL	SUSPENDED	ALIGN BOTTOM OF FIXTURE WITH BOTTOM OF CEILING BAFFLES.	