

10/10/2024 4:52:34 AM Autodesk Docs Micron B4 Campus 2022P&E-S&E-E-M&M-XXXX.dwg

DECORATIVE LUMINAIRE SCHEDULE											
FIXTURE TYPE	PRODUCT DESCRIPTION	BASIS OF DESIGN MANUFACTURER	SIZE	LIGHT SOURCE	INPUT WATTS	POWER SUPPLY	INPUT VOLTAGE	FINISH	MOUNTING	NOTES	
D23	CORD HUNG WIRE SHADE DECORATIVE PENDANT, ONE LAMP TYPE D-LAMP	BARN LIGHT ELECTRIC CO. CHICKEN WIRE PENDANT BLE-C-3(SHADE)-(MOUNTING)-(FINISH)-NA-E26	18.3" DIA W x 10.1" H	LED, 3000K, 90 CRI, 820 lm	9 W	INTEGRAL, DIMMING PER LAMP	120V	STANDARD PER ARCHITECTURAL	SUSPENDED AT 8'-0" TO BOTTOM OF FIXTURE, U.O.N	CONTRACTOR TO CONFIRM CORD LENGTH WITH ARCHTECT PRIOR TO CUTTING IN FIELD.	
	SEATING NOSE										
D24	CORD HUNG METAL PENDANT, ONE LAMP TYPE D-LAMP	BARN LIGHT ELECTRIC CO. DINO SERIES BLE-C-WHD12-(SHADE)-(MOUNTING)-(FINISH)-NA-NA-NA-NA-E26	12" DIA W x 7.75" H	LED, 3000K, 90 CRI, 820 lm	9 W	INTEGRAL, DIMMING PER LAMP	120V	STANDARD PER ARCHITECTURAL	SUSPENDED AT 7'-0" TO BOTTOM OF FIXTURE OR PER ARCH.	CONTRACTOR TO CONFIRM CORD LENGTH WITH ARCHTECT PRIOR TO CUTTING IN FIELD.	
	BREAKFAST COUNTER										
D24A	CORD HUNG METAL PENDANT, ONE LAMP TYPE D-LAMP	BARN LIGHT ELECTRIC CO. DINO SERIES BLE-C-WHD14-(SHADE)-(MOUNTING)-(FINISH)-NA-NA-NA-NA-E26	14" DIA W x 8.5" H	LED, 3000K, 90 CRI, 820 lm	9 W	INTEGRAL, DIMMING PER LAMP	120V	STANDARD PER ARCHITECTURAL	SUSPENDED AT 8'-0" TO BOTTOM OF FIXTURE, OR PER ARCH	CONTRACTOR TO CONFIRM CORD LENGTH WITH ARCHTECT PRIOR TO CUTTING IN FIELD.	
	BREAKFAST SEATING										
D25	CORD MOUNT 2" CYLINDER, 400GS, DIRECT DISTRIBUTION, ROUND CANOPY, DAMP RATED PASTRY COUNTER	UNDSLEY REED PENDANT LRD-PN-10-35-13-(FINISH)-40-(CORD-CANOPY)-0-10V@ 10% DIMMING-(ROUND CANOPY)-(CORD LENGTH)	2.5" DIA W x 10" H	LED, 3500K, 80CRI, 1300 lm	10 W	INTEGRAL, 1-10V DIMS TO 10%	UNV	HOUSING, CORD, AND CANOPY FINISH PER ARCHITECTURAL	SUSPENDED AT 7'-0" TO BOTTOM OF FIXTURE OR PER ARCH.	CONTRACTOR TO CONFIRM CORD LENGTH WITH ARCHTECT PRIOR TO CUTTING IN FIELD.	
D25A	CORD MOUNT 2" CYLINDER, 400GS, DIRECT DISTRIBUTION, ROUND CANOPY, DAMP RATED PRIVATE DINING	UNDSLEY REED PENDANT LRD-PN-10-35-10-(FINISH)-40-(CORD-CANOPY)-0-10V@ 10% DIMMING-(ROUND CANOPY)-(CORD LENGTH)	2.5" DIA W x 10" H	LED, 3500K, 80CRI, 1000 lm	7 W	INTEGRAL, 1-10V DIMS TO 10%	UNV	HOUSING, CORD, AND CANOPY FINISH PER ARCHITECTURAL	SUSPENDED AT 7'-0" TO BOTTOM OF FIXTURE OR PER ARCH.	CONTRACTOR TO CONFIRM CORD LENGTH WITH ARCHTECT PRIOR TO CUTTING IN FIELD.	
D26	DECORATIVE GLOBE WALL SCONCE, ONE LAMP TYPE D-LAMP CHEF'S TABLE	DUTTON BROWN HEMI SCONCE 10" 50121-10	10" DIA W x 6" H	LED, 3000K, 90 CRI, 820 lm	9 W	INTEGRAL, ELV, DIMS PER LAMP	120V	HOUSING: BRASS COLOR, CHALK OR PER ARCHITECTURAL	WALL MOUNTED	REFER TO ARCHITECTURAL ELEVATIONS FOR MOUNTING HEIGHT.	
D27	DECORATIVE CHANDELER, STEM MOUNT, FIVE FROSTED GLASS GLOBES WITH LAMP D-LAMP CHEF'S TABLE	DUTTON BROWN BIG PRISMA CHANDELER 30503	3'-6" W x 2'-2" H	LED, 3000K, 90 CRI, 4100 lm	45 W	INTEGRAL, ELV, DIMS PER LAMP	120V	HOUSING: BRASS GLOBE: FROSTED COLOR: CHALK OR PER ARCHITECTURAL	SUSPENDED AT 18" FROM CEILING TO TOP OF FIXTURE		
D28	DECORATIVE CHANDELER, STEM MOUNT, FROSTED GLASS GLOBES, TEN LAMPS TYPE D-LAMP PRIVATE DINING	DUTTON BROWN GRADIM CHANDELER 48" 31001	48" DIA W x 13" H	LED, 3000K, 90 CRI, 8200 lm	90 W	INTEGRAL, ELV, DIMS PER LAMP	120V	HOUSING: BRASS GLOBE: WHITE COLOR: BARELY OR PER ARCHITECTURAL	SUSPENDED AT 18" FROM CEILING TO TOP OF FIXTURE		
D29	16" PORCELAIN SHADE PENDANT, CORD HUNG, ONE LAMP TYPE D-LAMP SOUP STATION	BARN LIGHT ELECTRIC DOMINION BLE-C-SBD16-480-SBK-NA-NA-NA-NA-E26	16" DIA W x 6.75" H	LED, 3000K, 90 CRI, 820 lm	9 W	INTEGRAL, ELV, DIMMING OR PER MFR	120V	SHADE: BLUSH PINK OR PER ARCHITECTURAL	SUSPENDED AT 7'-0" TO BOTTOM OF FIXTURE OR PER ARCH.	CONTRACTOR TO CONFIRM CORD LENGTH WITH ARCHTECT PRIOR TO CUTTING IN FIELD.	
D30A	48" ACOUSTIC DRUM PENDANT, OPAL DIFFUSER, AIRCRAFT CABLE SUSPENDED, 75% OUTPUT, SURFACE CANOPY DRIVER	BARBICAN LIGHTING DRUM PENDANT 16-104-483-10H-HTO-ACM-UNV-BPC-BCF-370ULM-3500K-90-SCQL-S810V10-40DAC-(FINISH)-(COLOR)	48" DIA W x 10" H	LED, 3500K, 90CRI, 5700 lm	35 W	INTEGRAL IN CANOPY, 0-10V, DIMS TO 10%	UNV	CORD AND CANOPY: BLACK DRUM ACOUSTIC FABRIC PER ARCHITECTURAL	SUSPENDED AT 8'-0" TO BOTTOM OF FIXTURE, OR PER ARCH.	CONTRACTOR TO CONFIRM CORD LENGTH WITH ARCHTECT PRIOR TO CUTTING IN FIELD.	
	PANTRY SEATING LEVEL 2,6										
D30B	42" ACOUSTIC DRUM PENDANT, OPAL DIFFUSER, AIRCRAFT CABLE SUSPENDED, 75% OUTPUT, SURFACE CANOPY DRIVER	BARBICAN LIGHTING DRUM PENDANT 16-104-423-10H-HTO-ACM-UNV-BPC-BCF-4275LM-3500K-90-SCDL-S810V10-40DAC-(FINISH)-(COLOR)	42" DIA W x 10" H	LED, 3500K, 90CRI, 4275 lm	65 W	INTEGRAL IN CANOPY, 0-10V, DIMS TO 10%	UNV	CORD AND CANOPY: BLACK DRUM ACOUSTIC FABRIC PER ARCHITECTURAL	SUSPENDED AT 7'-0" TO BOTTOM OF FIXTURE OR PER ARCH.	CONTRACTOR TO CONFIRM CORD LENGTH WITH ARCHTECT PRIOR TO CUTTING IN FIELD.	
	PANTRY SEATING LEVEL 2,6										
D30C	36" ACOUSTIC DRUM PENDANT, OPAL DIFFUSER, AIRCRAFT CABLE SUSPENDED, 75% OUTPUT, SURFACE CANOPY DRIVER	BARBICAN LIGHTING DRUM PENDANT 16-104-363-10H-HTO-ACM-UNV-BPC-BCF-285ULM-3500K-90-SCQL-S810V10-40DAC-(FINISH)-(COLOR)	36" DIA W x 10" H	LED, 3500K, 90CRI, 2850 lm	30 W	INTEGRAL IN CANOPY, 0-10V, DIMS TO 10%	UNV	CORD AND CANOPY: BLACK DRUM ACOUSTIC FABRIC PER ARCHITECTURAL	SUSPENDED AT 7'-0" TO BOTTOM OF FIXTURE OR PER ARCH.	CONTRACTOR TO CONFIRM CORD LENGTH WITH ARCHTECT PRIOR TO CUTTING IN FIELD.	
	PANTRY SEATING LEVEL 2,6										
D31	15.75" CORD MOUNT SPUN ALUMINUM PENDANT, ONE LAMP TYPE D-LAMP LIVING ROOM BOOTHS, LEVEL 2,6	MULTO AMBT	15.75" DIA W x 9.4" H	LED, 3000K, 90 CRI, 820 lm	9 W	INTEGRAL, ELV, DIMMING OR PER MFR	120V	STANDARD PER ARCHITECTURAL	SUSPENDED AT 6'-6" TO BOTTOM OF FIXTURE OR PER ARCH.	CONTRACTOR TO CONFIRM CORD LENGTH WITH ARCHTECT PRIOR TO CUTTING IN FIELD.	
D32A	PENDANT MOUNT FROSTED GLOBE, 20" DIA, CORD MOUNT, SMALL DRIVER CANOPY	SPECTRUM LIGHTING GIANT GLOBE 20" GPRF2000GV-27L-0X-OM-(LENGTH)-(FINISH)	20" DIA W x 20" H	LED, 3500K, 90CRI, 2700 lm	18 W	INTEGRAL IN CANOPY, 0-10V, DIMS TO 1%	UNV	WHITE OR PER ARCHITECTURAL	SUSPENDED	CORD MOUNT AT VARYING HEIGHTS. CONTRACTOR TO CONFIRM CORD LENGTH WITH ARCHTECT PRIOR TO CUTTING IN FIELD.	
	LIVING ROOM SEATING LEVEL 2,6										
D32B	PENDANT MOUNT FROSTED GLOBE, 16" DIA, CORD MOUNT, SMALL DRIVER CANOPY	SPECTRUM LIGHTING GIANT GLOBE 16" GPRF1600GV-20L-0X-OM-(LENGTH)-(FINISH)	16" DIA W x 16" H	LED, 3500K, 90CRI, 2700 lm	18 W	INTEGRAL IN CANOPY, 0-10V, DIMS TO 1%	UNV	WHITE OR PER ARCHITECTURAL	SUSPENDED	CORD MOUNT AT VARYING HEIGHTS. CONTRACTOR TO CONFIRM CORD LENGTH WITH ARCHTECT PRIOR TO CUTTING IN FIELD.	
	LIVING ROOM SEATING LEVEL 2,6										
D32C	PENDANT MOUNT FROSTED GLOBE, 12" DIA, CORD MOUNT, SMALL DRIVER CANOPY	SPECTRUM LIGHTING GIANT GLOBE 12" GPRF1200GV-20L-0X-OM-(LENGTH)-(FINISH)	12" DIA W x 12" H	LED, 3500K, 90CRI, 2700 lm	10 W	INTEGRAL IN CANOPY, 0-10V, DIMS TO 1%	UNV	WHITE OR PER ARCHITECTURAL	SUSPENDED	CORD MOUNT AT VARYING HEIGHTS. CONTRACTOR TO CONFIRM CORD LENGTH WITH ARCHTECT PRIOR TO CUTTING IN FIELD.	
	LIVING ROOM SEATING LEVEL 2,6										
D33	DECORATIVE SUSPENDED LINEAR, THREE FROSTED GLOBES, INTEGRAL LED EXEC COFFEE COUNTER	VI8IA PALMA 3736	18 1/2" W x 76 3/4" L x 8 3/4" H	LED, 2700K, 90CRI, 2742 lm	30 W	INTEGRAL, 0-10V DIMMING	UNV	GRAPHITE	SUSPENDED AT 7'-0" TO BOTTOM OF FIXTURE OR PER ARCH.	CONTRACTOR TO CONFIRM CORD LENGTH WITH ARCHTECT PRIOR TO CUTTING IN FIELD.	
D34	DECORATIVE LINEAR PENDANT, DIRECT/INDIRECT DISTRIBUTION, BATWING INDIRECT DISTRIBUTION, NARROW SYMMETRIC DISTRIBUTION, DUAL CIRCUIT CONTROL	STICKBULB TRESLINE TL-D-(LENGTH)-(FINISH)-CSWCW-46-ME-35-D08-DN-H10-H-S-XX-010	2.25" W x 16'-0" L x 3.875" H	LED, 3500K, 90CRI, DIRECT 800lm/F, INDIRECT 1000 lm/LF	12 W/LF	INTEGRAL, 0-10V DIMMING	277V	CANOPY/CORD: SQUARE WHITE HOUSING: STANDARD PER ARCHITECTURAL	SUSPENDED	1. SUSPENDED AT 18" FROM CEILING TO TOP OF FIXTURE. 2. MOUNTING TYPE TO BE "END HANGING AND POWER"	
	EXEC DINING										
D35	SUSPENDED CHANDELER, THREE FROSTED ACRYLIC GLOBES, INTEGRAL LED EXEC WELCOME LOUNGE	SUNBEAM PILLOWS TRIPLE PENDANT 3612.14	36.5" DIA W x 5.5" H	LED, 3000K, 90CRI, 2675 lm	28 W	INTEGRAL, 0-10V DIMMING	UNV	BRASS OR PER ARCHITECTURAL	SUSPENDED AT 7'-0" TO BOTTOM OF FIXTURE OR PER ARCH.		
D37	SUSPENDED GLASS PENDANT, SINGLE FROSTED GLOBE EXEC CONFERENCE	VI8IA PALMA 3720	8 3/4" DIA W x 8 3/4" H	LED, 2700K, 90CRI, 888 lm	9 W	INTEGRAL, 0-10V DIMMING	UNV	GRAPHITE	SUSPENDED	SUSPEND PENDANTS AT VARYING HEIGHTS PER ARCHITECTURAL	
D38	DECORATIVE WOOD PENDANT LINEAR, DIRECT DISTRIBUTION, INTEGRAL LED THE GRILL COFFERED CEILING	CERNO UNA 66 07-230-66 W-D-30-P1	2" W x 66" L x 2.75" H	LED, 3500K, 90CRI, 2710 lm	39 W	INTEGRAL, 0-10V DIMMING	120V	WALNUT	SUSPENDED AT 7'-0" TO BOTTOM OF FIXTURE OR PER ARCH.	CONTRACTOR TO CONFIRM CORD LENGTH WITH ARCHTECT PRIOR TO CUTTING IN FIELD.	
D39	SUSPENDED 2" LINEAR ROTATABLE MODULAR SYSTEM, 360DEG. ROTATION, DIFFUSE LENS, 1430DEG. BEAM SPREAD, FLEXIBLE CONNECTORS, PIPED LINE SUSPENSION PISDM-(WATTAGE)-(LENGTH)-(SK)-(FINISH)	PUREEDGE LIGHTING PIPERLINE 1 SUSPENSION	2-1/2" W x SEE PLANS FOR LENGTH x 1.25" H	LED, 3600K, 95CRI, 1000 lm/LF	9 W/LF	REMOTE, TRIAC, DIMS TO 1%	24V DC	STANDARD PER ARCHITECTURAL	SUSPENDED	1. PROVIDE SHOP DRAWINGS FOR REVIEW. POWER FEED LOCATIONS TO BE COORDINATED WITH ARCHTECT PRIOR TO ORDER. 2. PROVIDE CONTINUOUS LENGTHS AS INDICATED IN DRAWINGS. 3. FIXTURE CONFIGURATION UNDER DESIGN DEVELOPMENT. REFER TO ARCHITECTURAL DRAWINGS FOR FIXTURE LENGTHS AND ORIENTATION. 4. LOCATE REMOTE DRIVER IN AN ACCESSIBLE, VENTILATED LOCATION PER MANUFACTURER RECOMMENDATIONS. COORDINATE FINAL LOCATION WITH ARCHTECT PRIOR TO INSTALL. 5. FINAL AMMIGROTATION OF FIXTURES TO BE COMPLETED IN FIELD WITH ARCHTECT AND/OR LIGHTING DESIGNER AFTER INSTALLATION.	
D40	STEM MOUNTED DECORATIVE PENDANT, LAMP TYPE D-LAMP SOUTHASIAN STATION	DUTTON BROWN COLOR LURE PENDANT 12" 30112-12	12" DIA W x 12" H	LED, 3000K, 90 CRI, 820 lm	9 W	INTEGRAL, ELV, DIMS PER LAMP	120V	HOUSING: BRASS COLOR, CHALK OR PER ARCHITECTURAL	SUSPENDED AT 7'-0" TO BOTTOM OF FIXTURE OR PER ARCH.		
D-LAMP	DECORATIVE FILAMENT LAMP, E26 BASE, A19 SHAPE, CLEAR, RATED FOR ENCLOSED FIXTURES DECORATIVE PENDANTS	GREEN CREATIVE VERSA FILAMENT SERIES 19A190M1930	2.38" DIA W x 4.316" H	LED, 3000K, 90 CRI, 820 lm	9 W	NA: ELV OR TRIAC DIMMING PER FIXTURE	120V	CLEAR	SURFACE	FOR FIXTURES SUPPLIED WITH E26 LAMP, PROVIDE LAMP TYPE D-LAMP FOR CONSISTENCY ACROSS PROJECT. RETURN UNUSED LAMP TO OWNER.	

SITE LUMINAIRE SCHEDULE											
FIXTURE TYPE	PRODUCT DESCRIPTION	BASIS OF DESIGN MANUFACTURER	SIZE	LIGHT SOURCE	INPUT WATTS	POWER SUPPLY	INPUT VOLTAGE	FINISH	MOUNTING	NOTES	
S1	18FT RAISED FOUNDATION LED AREA POLE LIGHT WITH ASYMMETRIC WIDE BEAM AND MARINE GRADE UNDERCOAT DRIVEWAY AND PARKING LOT	BEGA 84407-K3-0-10V 1%-BLK-MGU	11.5" DIA W x 9" L x 20" H	LED, 3000K, 80CRI, 6672lm	61 W	INTEGRAL, 0-10V, DIMS TO 1%	120-277VAC	BLACK OR PER ARCHITECTURAL	IN-GRADE ANCHOR	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS.	
S2	12FT GROUND MOUNTED LED PEDESTRIAN POLE LIGHT WITH MARINA GRADE UNDERCOAT EAST PLAZA	BEGA 88164-K3-0-10V 1%-BLK-MGU	26" DIA W x 5.5" H	LED, 3000K, 80CRI, 2531 lm	30 W	INTEGRAL, 0-10V, DIMS TO 1%	120-277VAC	BLACK OR PER ARCHITECTURAL	IN-GRADE ANCHOR	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS.	
S3	18FT GROUND MOUNTED LED 4 HEADS POLE LIGHT WITH MARINE GRADE UNDERCOAT SITE	BEGA 77885-K3-0-10V 1%-BLK-MGU	5.5" DIA W x 8" L x 5.5" H	LED, 3000K, 80CRI, TOTAL 5320 lm	64 W	INTEGRAL, 0-10V, DIMS TO 1%	277V	BLACK OR PER ARCHITECTURAL	IN-GRADE ANCHOR	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS.	
S4	20FT RAISED FOUNDATION LED AREA POLE LIGHT WITH ASYMMETRIC WIDE BEAM AND MARINE GRADE UNDERCOAT BASKETBALL COURT	GARCCO OPF-LA16-830-13M-ARI-277V-0-10V-OPTION-BK-MARINE GRADE PAINT	18" DIA W x 26.7" L x 3" H	LED, 3000K, 80CRI, 28917 lm	195 W	INTEGRAL, 0-10V, DIMS TO 1%	277V	BLACK OR PER ARCHITECTURAL	IN-GRADE ANCHOR	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS.	
S5	3FT GROUND MOUNTED LED BOLLARD WITH 360 DISTRIBUTION SITE PATHWAY	BEGA 98856-K3-0-10V 1%-BLK-MGU	3.5" DIA W x 3" H	LED, 3000K, 80CRI, 1838 lm	20 W	INTEGRAL, 0-10V, DIMS TO 1%	120-277VAC	BLACK OR PER ARCHITECTURAL	IN-GRADE ANCHOR	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS.	
S5A	3FT GROUND MOUNTED LED BOLLARD WITH 180 DISTRIBUTION SITE PATHWAY	BEGA 99867-K3-0-10V 1%-BLK-MGU	3.5" DIA W x 3" H	LED, 3000K, 80CRI, 923 lm	20 W	INTEGRAL, 0-10V, DIMS TO 1%	120-277VAC	BLACK OR PER ARCHITECTURAL	IN-GRADE ANCHOR	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS. 2. FIXTURE WITH 180 DISTRIBUTION TO BE AIMED AT PATHWAY.	
S6	SHALLOW HOUSING RECESSED LED STEPLIGHT WITH MARINE GRADE UNDERCOAT EXTERIOR STAIR	BEGA 24064-K3-0-10V 1%-BLK-MGU	W x	LED, 3000K, 80CRI, 489 lm	9 W	INTEGRAL, 0-10V, DIMS TO 1%	120-277VAC	BLACK OR PER ARCHITECTURAL	RECESSED WALL	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS. 2. FIXTURE TO BE CENTERED AT STAIR RISER	
S7	WALL MOUNTED LED CYLINDER AREA LIGHT EXTERIOR EXIT DOOR LOCATION	BEGA 24055-K3-0-10V 1%-BLK-MGU	4" DIA W x 12" H	LED, 3000K, 80CRI, 1725 lm	21 W	INTEGRAL, 0-10V, DIMS TO 1%	120-277VAC	CUSTOM RAIL TO MATCH BUILDING FACADE - ARCHITECT TO VERIFY	WALL MOUNTED	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS. 2. ARCHITECT TO VERIFY FIXTURE FINISH. 3. REFER TO ARCHITECTURAL ELEVATION FOR FIXTURE MOUNTING HEIGHT.	
S8	EXTERIOR RATED FLEXIBLE LED SIDE VIEW STRIP LIGHT WITH MOUNTING BRACKET LANDSCAPE LIGHTING DETAIL AT AUDITORIUM	OPTIC ARTS - KURBA MAX VERTICAL KBX-F-30K-(SECTION START)-(SECTION END)-(ACTUAL LENGTH) PDCU-0-10V 1%-W-(POWER)-24V	1.05" W x SEE PLANS FOR LENGTH x 1.04" H	LED, 3000K, 80CRI, 458 lm/LF	5 W/LF	REMOTE, 0-10V, DIMS TO 1%	24V DC	WHITE	SURFACE	1. EXTERIOR RATED FLEXIBLE LED SIDEVIEW TAPE LIGHT TO BE MOUNTED AT LANDSCAPE DETAIL. REFER TO LANDSCAPE DRAWING DETAIL <a href="#">80.1.50</a> , 131.1.50, and <a href="#">140.1.50</a> . 2. PROVIDE CONTINUOUS LENGTHS AS INDICATED IN DRAWINGS. FIXTURES TO BE MOUNTED END-TO-END WITH NO MORE THAN 3" OF UNLIT SPACE AT EITHER END OF RUN. 3. REMOTE LED DRIVERS TO BE LOCATED IN A WELL-VENTILATED ACCESSIBLE LOCATION INSIDE WET USED ENCLOSURE. DISTANCE BETWEEN FIXTURES AND DRIVERS NOT TO EXCEED MANUFACTURER RECOMMENDATIONS. 4. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS.	
S9	EXTERIOR RATED LENSED LED EXTRUSION WITH MOUNTING BRACKET LANDSCAPE BENCH AND PLANTER	LUMINI - BOSCA WET - STATIC WHITE BOSCA-LENGTH-HERMID-30K-F-(MOUNTING)-(FINISH)-(POSITION TYPE)-(POWER FEED) PDCU-0-10V 1%-W-(POWER)-24V	0.8" W x SEE PLANS FOR LENGTH x 0.65" H	LED, 3000K, 90CRI, 232 lm/LF	4 W/LF	REMOTE, 0-10V, DIMS TO 1%	24V DC	SILVER ANODIZED (STANDARD)	SURFACE	1. PROVIDE CONTINUOUS LENGTHS AS INDICATED IN DRAWINGS. FIXTURES TO BE MOUNTED END-TO-END WITH NO MORE THAN 3" OF UNLIT SPACE AT EITHER END OF RUN. 2. REMOTE LED DRIVERS TO BE LOCATED IN A WELL-VENTILATED ACCESSIBLE LOCATION INSIDE WET USED ENCLOSURE. DISTANCE BETWEEN FIXTURES AND DRIVERS NOT TO EXCEED MANUFACTURER RECOMMENDATIONS. 3. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS.	
S10	4" RECESSED INGRADE UPLIGHT WITH ASYMMETRICAL OPTIC AND REMOTE DRIVER BOX TREE	BEGA 77019-K3-REMOTE 24V 0-10V 1%	3 1/8" DIA W x 3 7/8" L x 4.5/8" H	LED, 3000K, 80CRI, 364 lm	6 W	REMOTE, 0-10V, DIMS TO 1%	24V DC	STAINLESS STEEL	INGRADE	1. REMOTE LED DRIVERS TO BE LOCATED IN A WELL-VENTILATED ACCESSIBLE LOCATION INSIDE WET USED ENCLOSURE. DISTANCE BETWEEN FIXTURES AND DRIVERS NOT TO EXCEED MANUFACTURER RECOMMENDATIONS. 2. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS.	
S12	EXTERIOR RATED HANDRAIL RECESSED ASYMMETRIC LED POINT SOURCE COMPATIBLE WITH 1.5"-1.75" DIA TUBE WITH REMOTE DRIVER EXTERIOR HANDRAIL	KLIKUSA - LEDPOD 40 LP-40-30K-A-(RAIL WALL THICKNESS)-FRS-LPD06M9PRTINDIM 0-10V 10%	1" DIA W x 1.18" H	LED, 3000K, 80CRI, 124 lm	2 W	REMOTE, 0-10V, DIMS TO 10%	24V DC	N/A	HANDRAIL RECESSED	1. FIXTURE TO BE CONCEALED IN STAIR HANDRAIL. MOUNTING TO BE COORDINATED WITH FINAL HANDRAIL DESIGN. 2. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS. 3. REMOTE LED DRIVERS TO BE LOCATED IN A WELL-VENTILATED ACCESSIBLE LOCATION INSIDE WET USED ENCLOSURE. DISTANCE BETWEEN FIXTURES AND DRIVERS NOT TO EXCEED MANUFACTURER RECOMMENDATIONS.	
S14	CLARE-FREE EXTERIOR GARDEN BOLLARD AT FOOTPATH WITH MARINE GRADE UNDERCOAT EAST PLAZA PATHWAY	BEGA 88261-K3-0-10 1%-BLK-MGU	4.5" DIA W x 3" H	LED, 3000K, 80CRI, 1571 lm	21 W	INTEGRAL, 0-10V, DIMS TO 1%	120-277VAC	BLACK OR PER ARCHITECTURAL	IN-GRADE ANCHOR	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS.	
S15	EXTERIOR RATED LENSED LED LINEAR DOWNLIGHT EAST PLAZA TRELLIS	BEGA 24312-K3-0-10 1%-BLK-MGU	2.5" W x SEE PLANS FOR LENGTH x 3.75" H	LED, 3000K, 80CRI, 2153 lm/LF	12 W/LF	INTEGRAL, 0-10V, DIMS TO 1%	120-277VAC	BLACK OR PER ARCHITECTURAL	SURFACE	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS.	
S18	SHALLOW HOUSING RECESSED LED STEPLIGHT WITH MARINE GRADE UNDERCOAT EXTERIOR RAMP	BEGA 33855-K3-0-10V 1%-BLK-MGU	12.5" W x 2.75" L x 5" H	LED, 3000K, 80CRI, 480 lm	11 W	INTEGRAL, 0-10V, DIMS TO 1%	120-277VAC	BLACK OR PER ARCHITECTURAL	RECESSED WALL	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS.	
S20	INGROUND TREE UPLIGHT WITH NARROW OPTIC FEATURE TREES	HK LIGHTING GROUP ZAL16-16-324-277V-7M-30-20-019-BK-EXTENSION-GROUND MOUNT EX-SQ-16-6K	2.5" W x 8" L x 2.5" H	LED, 3000K, 80CRI, 700 lm	7 W	INTEGRAL IN CANOPY, 0-10V, DIMS TO 10%	277V	BLACK	INGROUND	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS. 2. FIXTURE TO BE SPECIFIC WITH 6 INCH EXTENSION STEM.	
S21	2.58" W EXTERIOR RATED RECESSED LENS LINEAR LED BUILDING VESTIBULE CEILING	AXIS EXR-800-80-30-50-LENGTH-AP-120-DP-1-0F-OPTION	0.8" W x SEE PLANS FOR LENGTH x 0.44" H	LED, 3000K, 80CRI, 900 lm/LF	5 W/LF	INTEGRAL, 0-10V, DIMS TO 1%	120V	ALUMINUM PAINT	RECESSED	1. FIXTURE TO BE RECESSED INTO THE CEILING AND SIDE WALL TO ILLUMINATE THE VESTIBULE. 2. PROVIDE CONTINUOUS LENGTHS AS INDICATED IN DRAWINGS. COORDINATE FIXTURE LENGTH WITH VESTIBULE PANEL SIZES. 3. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS. 4. ARCHITECT TO VERIFY FIXTURE FINISH.	
S22	DUEL HEAD WALL MOUNTED FLOOD LIGHT OUTDOOR DINNING	ECODENSE F170-2H-HO-3-0-8-40-S-H-C   LDCM-PL-120-277-010V-GR   F170-H-S	5.2" W x 10.8" L x 6.8" H	LED, 3000K, 80CRI, 8700 x2 lm	78 W	INTEGRAL, 0-10V, DIMS TO 1%	120V	SILVER - ARCHITECT TO VERIFY	SURFACE	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS. 2. ARCHITECT TO VERIFY FIXTURE FINISH. 3. REFER TO ARCHITECTURAL ELEVATION FOR FIXTURE MOUNTING HEIGHT. RECOMMEND MOUNTING FIXTURE AT 12'-0" A.F.F. TO ITS COORRELATED FLOOR.	
S22A	SINGLE HEAD WALL MOUNTED FLOOD LIGHT LEVEL 2 LARGE TERRACE, TYPICAL BALCONY	ECODENSE F080-1S-HO-3-0-8-60-S-H-MOUNTING   LDCM-PL-120-277-010V-GR   F080-H-S	2.5" W x 2.5" L x 4.7" H	LED, 3000K, 80CRI, 740 lm	12 W	INTEGRAL, 0-10V, DIMS TO 1%	120V	SILVER - ARCHITECT TO VERIFY	SURFACE	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS. 2. ARCHITECT TO VERIFY FIXTURE FINISH. 3. REFER TO ARCHITECTURAL ELEVATION FOR FIXTURE MOUNTING HEIGHT. RECOMMEND MOUNTING FIXTURE AT 12'-0" A.F.F. TO ITS COORRELATED FLOOR.	
S22B	DUEL HEAD WALL MOUNTED FLOOD LIGHT LEVEL 2 TERRACE	ECODENSE F080-2H-HO-3-0-8-60-S-H-MOUNTING   LDCM-PL-120-277-010V-GR   F080-H-S	2.5" W x 5.1" L x 4.7" H	LED, 3000K, 80CRI, 2200 lm	23 W	INTEGRAL, 0-10V, DIMS TO 1%	120V	SILVER - ARCHITECT TO VERIFY	SURFACE	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS. 2. ARCHITECT TO VERIFY FIXTURE FINISH. 3. REFER TO ARCHITECTURAL ELEVATION FOR FIXTURE MOUNTING HEIGHT. RECOMMEND MOUNTING FIXTURE AT 12'-0" A.F.F. TO ITS COORRELATED FLOOR.	
S22C	SINGLE HEAD WALL MOUNTED FLOOD LIGHT LEVEL 2 EAST BALCONY	ECODENSE F170-1S-LC-3-0-8-60-S-H-MOUNTING   LDCM-PL-120-277-010V-GR   F170-H-S	5.2" W x 5.2" L x 6.8" H	LED, 3000K, 80CRI, 1633 lm	13 W	INTEGRAL, 0-10V, DIMS TO 1%	120V	SILVER - ARCHITECT TO VERIFY	SURFACE	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS. 2. ARCHITECT TO VERIFY FIXTURE FINISH. 3. REFER TO ARCHITECTURAL ELEVATION FOR FIXTURE MOUNTING HEIGHT. RECOMMEND MOUNTING FIXTURE AT 12'-0" A.F.F. TO ITS COORRELATED FLOOR.	
S22D	SINGLE HEAD WALL MOUNTED FLOOD LIGHT BUILDING FACADE	ECODENSE F170-1S-HO-3-0-8-40-S-H-MOUNTING   LDCM-PL-120-277-010V-GR   F170-H-S	5.2" W x 5.2" L x 6.8" H	LED, 3000K, 80CRI, 4350 lm	38 W	INTEGRAL, 0-10V, DIMS TO 1%	120V	SILVER - ARCHITECT	SURFACE	1. CONTRACTOR TO VERIFY THAT ALL FIXTURE LOCATIONS ARE VERIFIED WITH FIELD CONDITIONS PRIOR TO SETTING FINAL FIXTURE LOCATIONS. 2. ARCHITECT TO VERIFY FIXTURE FINISH. 3. REFER TO ARCHITECTURAL ELEVATION FOR FIXTURE MOUNTING HEIGHT. RECOMMEND MOUNTING FIXTURE AT 12'-0" A.F.F. TO ITS COORRELATED FLOOR.	