



University of  
St Andrews

CS4402 CONSTRAINT PROGRAMMING

---

## The Bombastic Modelling Problem

---

FEBRUARY 26, 2018

*Lecturer:*  
Ian Miguel

*Submitted By:*  
140011146

# 1 Introduction

## 2 Design and Implementation

### 2.1 Initial states

There are three sets of state variables that need to be set up as the initial states: the avatar's position, the locations of the blocks and the cells of the grid.

---

```
1 $ Avatar's initial position
2 avatarCurrentRow[0] = avatarInitRow,
3 avatarCurrentCol[0] = avatarInitCol,
4
5 $ Initial locations for blocks
6 forall block : int(1..numBlocks) .
7     blocksCurrentRow[0,block] = blocksInitRow[block] /\
8     blocksCurrentCol[0,block] = blocksInitCol[block],
9
10 $ Initial cells of grid
11 forall row : int(1..r) .
12     forall col : int(1..c) .
13         gridCurrent[0,row,col] = gridInit[row,col],
```

---

### 2.2 Invalid states

Next are the constraints for invalid states of the game. This restricts the model to not have states such as having the avatar and a block be in the same position.

---

---

## 2.3 Movement

## 2.4 Grid

# 3 Results




Figure 1: Time taken and number of solver nodes for all given parameters

## 3.1 Optimisations




Figure 2: Results with different optimisation flags

## 3.2 Heuristics




Figure 3: Number of solver nodes for different heuristics

## 3.3 Custom instances

## 4 Conclusion and evaluation