

PARAGRAPH FORMATTING



OBJECTIVES

1. Identify paragraph formatting tags.

2. Apply text formatting elements properly.

3. Organize webpage content using formatting tags.

HTML ELEMENTS

An HTML element is a part of a webpage, like a paragraph of text, an image, or a form. It's the basic unit of content and structure within an HTML document. Elements tell the web browser how to display the content.

HTML TAGS

Tags are the markers that define the start and end of an element. They are written with angle brackets, like <tag> for the start of an element and </tag> (with a forward slash before the tag name) for the end. Tags label the type of content they enclose, instructing the browser on how to process it.

UNDERSTANDING TAGS AND ELEMENTS

An HTML element encompasses everything from the start tag to the end tag, including the content and the tags themselves.

This means that the basic structure of an HTML element includes:

- the opening tag (<tag>),
- the content itself, and
- the closing tag (</tag>).

SUMMARY

An **element refers to the whole structure**, including the opening tag, the content, and the closing tag (if present). It's what you see rendered on a webpage.

A **tag refers specifically to the opening and closing markers** that define the start and end of an element. They are not displayed on the webpage but instruct the browser on how to interpret the content.

Block-Level and Inline Elements

TYPES OF ELEMENTS

In HTML5, there are two types of elements:

- block-level elements, and
- inline elements.

Examples of block-level elements include:

1. <h1> through <h6> for headings,
2. <p> for paragraphs,
3. and <ol> for lists, and
4. for grouping content.

INLINE ELEMETS

Inline elements, on the other hand, are used to **style content within block-level elements**, such as links and images. They don't start on a new line and only take up as much space as needed to display their content. This means that multiple inline elements can appear on the same line, separated by a space.

Examples of inline elements include:

- <a> for links,
- <img> for images, and
- for styling content.

HTML Attributes

HTML ATTRIBUTES

HTML Attributes are special words used within the opening tag of an HTML element. They provide additional information about HTML elements. HTML attributes are used to configure and adjust the element's behavior, appearance, or functionality in a variety of ways.

index.html > ...

```
1   <!DOCTYPE html>
2   <html>
3   <head>
4       <title>My First Web Page</title>
5   </head>
6
7   <body>
8       <img src="photos/eachbg.jpg">
9   </body>
10  </html>
```

Tag : <img>
Attribute : src
Value of Attribute : “photos/eacbg.jpg“
Syntax:
<tagname attribute_name = "attribute_value"> content... </tagname>

TYPES OF ATTRIBUTES

1. Global Attributes

These attributes can be used with any HTML element (though their effects might vary based on the element):

ATTRIBUTES	DESCRIPTION
class	Groups elements and allows styling.
style	Inline CSS styles.
contenteditable	Determines whether the content within the element is editable.
id	Assigns a unique identifier to an element, allowing targeting with CSS or JavaScript.
title	Creates a tooltip that appears when a user hovers over the element.

TYPES OF ATTRIBUTES

2. Element-Specific Attributes

These attributes can be used with specific and certain HTML tags.

ATTRIBUTES	DESCRIPTION
href	attribute of <a> specifies the URL of the page the link goes to
target	Used on <a> and <form> tags to specify where to open the linked document (e.g., _blank for a new tab).
src	attribute of <img> specifies the path to the image to be displayed
width and height	attributes of <img> provide size information for images
alt	attribute of <img> provides an alternate text for an image


THANK
YOU