Apply List Attributes and Values in Web Page Designs

HTML List → Attributes → Values

LEARNING COMPETENCIES

By the End of This Lesson, You Will...

01 **Differentiate** ordered and unordered lists.

02 **Apply** list attributes and values correctly.

03 **Create** organized webpage layouts using lists.

TODAY'S ROADMAP

HTML List → Attributes → Values

HTML List

The container: <ol> for ordered, <ul> for unordered, <li> for each item.

Attributes

Extra instructions inside the opening tag: type, start, reversed, value.

Values

The specific setting given to an attribute, e.g. type="A" or start="5".

QUICK REFRESHER

Ordered vs. Unordered Lists

 — Ordered List

Used when sequence matters (steps, rankings, instructions).

```
<ol>
  <li>Preheat oven</li>
  <li>Mix ingredients</li>
  <li>Bake for 20 mins</li>
</ol>
```

 — Unordered List

Used when order doesn't matter (ingredients, features, menu items).

```
<ul>
  <li>Flour</li>
  <li>Sugar</li>
  <li>Eggs</li>
</ul>
```

QUICK REFRESHER

List Attributes & Values

Attribute	Used On	Example Value	What It Does
type		1, A, a, I, i	Changes the numbering style
start		any number	Sets the starting count
reversed		reversed	Counts down instead of up
value		any number	Resets the count at that item

Unordered Lists —

An unordered list starts with <ul>. Each item starts with <li>. Items are marked with bullets by default.

```
<ul>
  <li>Coffee</li>
  <li>Tea</li>
  <li>Milk</li>
</ul>
```

Output: • Coffee • Tea • Milk

CHANGE THE BULLET STYLE (CSS list-style-type)

disc	Bullet (default)
circle	Hollow circle
square	Solid square
none	No marker

`e.g. <ul style="list-style-type:square;">`

Ordered Lists —

An ordered list starts with <ol>. Each item starts with <li>. Items are marked with numbers by default.

```
<ol type="A">
  <li>Coffee</li>
  <li>Tea</li>
  <li>Milk</li>
</ol>
```

Output: A. Coffee B. Tea C. Milk

THE type ATTRIBUTE

type="1"	Numbers (default)
type="A"	Uppercase letters
type="a"	Lowercase letters
type="I"	Uppercase roman numerals
type="i"	Lowercase roman numerals

Start counting elsewhere: <ol start="50"> begins the list at 50.

Other Lists — Description List <dl>

A description list pairs a term with its description. <dt> defines the term; <dd> describes it.

```
<dl>
  <dt>Coffee</dt>
  <dd>- black hot drink</dd>
  <dt>Milk</dt>
  <dd>- white cold drink</dd>
</dl>
```

TAG SUMMARY

<dl>	Defines the description list
<dt>	Defines a term (name)
<dd>	Describes the term

Useful for glossaries, FAQs, or any term-and-definition content.

EXERCISES 1

Warm-Up: Ordered or Unordered?

Shout "ORDERED" or "UNORDERED" and name the correct tag.

Steps to log into the school portal	**Ordered — **
List of favorite school subjects	**Unordered — **
Top 3 winners of a coding contest	**Ordered — **
Ingredients for a sandwich	**Unordered — **
Instructions to reset a Wi-Fi router	**Ordered — **

Attribute Match-Up

COLUMN A	COLUMN B
`<ol type="I">`	Numbers with Roman numerals (I, II, III...)
`<ol start="5">`	List begins counting at 5
`<ol reversed>`	List counts downward
`<li value="10">`	Resets this item's number to 10

EXERCISES 2

Code Detective: Spot the Bug

Each snippet below has one error. In groups, find it and write the corrected line.

Snippet 1

```
<ol type="1">
  <li
value="three">Third</li>
</ol>
```

HINT

value must be a number, not "three"

Snippet 2

```
<ul reversed>
  <li>Item A</li>
</ul>
```

HINT

reversed only works on <ol>, not

Snippet 3

```
<ol start="C">
  <li>First</li>
</ol>
```

HINT

start needs a number — use type="A" for letters, not start="C"

ACTIVITY 3

Individual Challenge: Webpage Layout Design

Choose ONE webpage section to design:

- **a recipe page,**
- **a class ranking page,**
- **a school event program,**
- **or a step-by-step tutorial.**

YOUR LAYOUT MUST INCLUDE

- ○ At least one <ol> using a non-default type or start value
- ○ At least one <ul> for supporting/unordered content
- ○ One <li> that uses the value attribute to reset numbering
- ○ A short paragraph or heading introducing the list

GREAT WORK, WEB DESIGNERS!

Lists organize content. Attributes and values make that content precise.