SENIOR HIGH SCHOOL • COMPUTER PROGRAMMING (.NET TECHNOLOGY)

CSS List & Links

Lesson 6

LESSON

6

CSS List & Links

Styling menus, lists, and hyperlinks for real navigation

CPNT 2.4

What You Will Be Able To Do

1. Apply CSS properties to style ordered and unordered lists.
2. Apply CSS properties to style hyperlinks and link states.
3. Design a fully styled webpage applying CSS text, color, gradient, box model, list, and link properties.

LESSON 6 • DISCUSSION

List Styling Properties

Lists aren't just bullet points — they're the backbone of real navigation menus.

•

`list-style-type`

Changes the marker style — disc, circle, square, decimal, upper-roman, or none.

▶

`list-style-position`

Controls whether the marker sits inside or outside the content box (inside / outside).



`list-style-image`

Swaps the default marker for a custom image — or combine everything with the list-style shorthand.

×

`list-style: none`

The most common real-world trick — strips markers entirely to turn a <ul> into a navigation menu.

LESSON 6 • DISCUSSION

Link Styling & Pseudo-Classes

Links have multiple states — CSS lets you style each one differently.

A

`color / text-decoration`

Sets a link's color and controls its underline (none, underline, line-through).

①

`:link / :visited`

Styles a link before it's clicked, and after the user has already visited it.

②

`:hover / :active`

Styles a link while the mouse hovers over it, and at the exact moment it's being clicked.

⇅

`LVHA Order`

Write these in order — link, visited, hover, active — so later rules aren't accidentally overridden.

LESSON 6 • EXAMPLES 1 & 2

List Marker Styles

The list-style-type property changes how each list item's marker looks.

1. Unordered — square markers

- Home
- Portfolio
- Contact

```
ul {

list-style-type: square;
}
```

2. Ordered — upper-roman markers

I. Sign up

II. Verify email

III. Set up profile

```
ol {

list-style-type: upper-roman;
}
```

LESSON 6 • EXAMPLES 3 & 4

From Bulleted List to Nav Menu

This is the single most common real-world use of list styling: turning a <ul> into a navigation bar.

3. Strip default markers

Before

- Home
- About
- Contact

After

Home

About

Contact

```
nav ul {
  list-style: none;
  margin: 0; padding: 0;
}
```

4. Lay items out horizontally

Home About Services Contact

```
nav li {
  display: inline-block;
  margin-right: 20px;
}
```

LESSON 6 • EXAMPLES 5 & 6

Styling Link States

Links can look different depending on whether they've been visited, are being hovered, or clicked.

5. Four link states, four colors

Read More
:link

Read More
:visited

Read More
:hover

Read More
:active

```
a:link { color: #1E2761; }
a:visited { color: #8B90AE; }
a:hover { color: #029C7C; }
```

6. Clean links, underline on hover

Learn more
default (no underline)

Learn more
on :hover

```
a { text-decoration: none; }
a:hover { text-decoration: underline; }
```

LESSON 6 • EXAMPLES 7 & 8

Real-World Patterns: Buttons & Navbars

Two of the most common link patterns on real websites — a call-to-action button and a full navigation bar.

7. A link styled as a button

Get Started

default

Get Started

:hover

```
.btn {
  padding: 12px 24px;
  border-radius: 999px;
  background: #02C39A; color: #fff; }
```

8. Full navbar (list + link styling combined)

Home Work About Contact

```
nav ul { list-style: none; display: flex; }
nav a { color: #fff; text-decoration: none; }
nav a:hover { color: #02C39A; }
```

NEXT UP

Lesson 7: CSS Z-index, Position & Float

Thank you!