

# ML/DL for Everyone with PYTORCH

## Lecture 8: DataLoader

Sung Kim <[hunkim+ml@gmail.com](mailto:hunkim+ml@gmail.com)> HKUST

Code: <https://github.com/hunkim/PyTorchZeroToAll>

Slides: <http://bit.ly/PyTorchZeroAll>



# Call for Comments

Please feel free to add comments directly on these slides.

Other slides: <http://bit.ly/PyTorchZeroAll>



# ML/DL for Everyone with PYTORCH

## Lecture 8: DataLoader

Sung Kim <[hunkim+ml@gmail.com](mailto:hunkim+ml@gmail.com)> HKUST

Code: <https://github.com/hunkim/PyTorchZeroToAll>

Slides: <http://bit.ly/PyTorchZeroAll>



# Manual data feed

```
xy = np.loadtxt('data-diabetes.csv', delimiter=',', dtype=np.float32)
x_data = Variable(torch.from_numpy(xy[:, 0:-1]))
y_data = Variable(torch.from_numpy(xy[:, [-1]]))
```

...

*# Training Loop*

```
for epoch in range(100):
```

*# Forward pass: Compute predicted y by passing x to the model*

```
y_pred = model(x_data)
```

*# Compute and print Loss*

```
loss = criterion(y_pred, y_data)
```

```
print(epoch, loss.data[0])
```

*# Zero gradients, perform a backward pass, and update the weights.*


```
optimizer.zero_grad()
```

```
loss.backward()
```

```
optimizer.step()
```



# DataLoader



```
for i, data in enumerate(train_loader, 0):  
    # get the inputs  
    inputs, labels = data  
  
    # wrap them in Variable  
    inputs, labels = Variable(inputs), Variable(labels)  
  
    # Run your training process  
    print(epoch, i, "inputs", inputs.data, "labels", labels.data)
```

# Custom DataLoader

```
class DiabetesDataset(Dataset):
```

```
    """ Diabetes dataset. """
```

```
    # Initialize your data, download, etc.
```

```
    def __init__(self):
```

1

download, read data, etc.

```
    def __getitem__(self, index):
```

```
        return
```

2

return one item on the index

```
    def __len__(self):
```

```
        return
```

3

return the data length

```
dataset = DiabetesDataset()
```

```
train_loader = DataLoader(dataset=dataset,
```

```
                           batch_size=32,
```

```
                           shuffle=True,
```

```
                           num_workers=2)
```

# Custom DataLoader

```
class DiabetesDataset(Dataset):
    """ Diabetes dataset. """

    # Initialize your data, download, etc.
    def __init__(self):
        xy = np.loadtxt('data-diabetes.csv', delimiter=',', dtype=np.float32)
        self.len = xy.shape[0]
        self.x_data = torch.from_numpy(xy[:, 0:-1])
        self.y_data = torch.from_numpy(xy[:, [-1]])

    def __getitem__(self, index):
        return self.x_data[index], self.y_data[index]

    def __len__(self):
        return self.len

dataset = DiabetesDataset()
train_loader = DataLoader(dataset=dataset,
                           batch_size=32,
                           shuffle=True,
                           num_workers=2)
```



# Classifying Diabetes

# References

# [https://github.com/yunjey/pytorch-tutorial/blob/master/tutorials/01-basics/pytorch\\_basics/main.py](https://github.com/yunjey/pytorch-tutorial/blob/master/tutorials/01-basics/pytorch_basics/main.py)

# [http://pytorch.org/tutorials/beginner/data\\_loading\\_tutorial.html#dataset-class](http://pytorch.org/tutorials/beginner/data_loading_tutorial.html#dataset-class)

```
import torch
import numpy as np
from torch.autograd import Variable
from torch.utils.data import Dataset, DataLoader
```

```
class DiabetesDataset(Dataset):
```

```
    """ Diabetes dataset. """
```

```
    # Initialize your data, download, etc.
```

```
    def __init__(self):
        xy = np.loadtxt('data-diabetes.csv', delimiter=',', dtype=np.float32)
        self.len = xy.shape[0]
        self.x_data = torch.from_numpy(xy[:, 0:-1])
        self.y_data = torch.from_numpy(xy[:, [-1]])
```

```
    def __getitem__(self, index):
        return self.x_data[index], self.y_data[index]
```

```
    def __len__(self):
        return self.len
```

```
dataset = DiabetesDataset()
train_loader = DataLoader(dataset=dataset,
                           batch_size=32,
                           shuffle=True,
                           num_workers=2)
```

```
class Model(torch.nn.Module):
```

```
    def __init__(self):
        """
        In the constructor we instantiate two nn.Linear module
        """
        super(Model, self).__init__()
        self.l1 = torch.nn.Linear(8, 6)
        self.l2 = torch.nn.Linear(6, 4)
        self.l3 = torch.nn.Linear(4, 1)
```

```
        self.sigmoid = torch.nn.Sigmoid()
```

```
    def forward(self, x):
        """
        In the forward function we accept a Variable of input data and we must return
        a Variable of output data. We can use Modules defined in the constructor as
        well as arbitrary operators on Variables.
        """
        out1 = self.sigmoid(self.l1(x))
        out2 = self.sigmoid(self.l2(out1))
        y_pred = self.sigmoid(self.l3(out2))
        return y_pred
```

```
    # our model
    model = Model()
```

```
    # Construct our Loss function and an Optimizer. The call to model.parameters()
    # in the SGD constructor will contain the learnable parameters of the two
    # nn.Linear modules which are members of the model.
    criterion = torch.nn.BCELoss(size_average=True)
    optimizer = torch.optim.SGD(model.parameters(), lr=0.1)
```

```
    # Training Loop
    for epoch in range(2):
        for i, data in enumerate(train_loader, 0):
```

```
            # get the inputs
            inputs, labels = data
```

```
            # wrap them in Variable
            inputs, labels = Variable(inputs), Variable(labels)
```

```
            # Forward pass: Compute predicted y by passing x to the model
            y_pred = model(inputs)
```

```
            # Compute and print loss
            loss = criterion(y_pred, labels)
            print(epoch, i, loss.data[0])
```

```
            # Zero gradients, perform a backward pass, and update the weights.
            optimizer.zero_grad()
            loss.backward()
            optimizer.step()
```



# The following dataset loaders are available

- MNIST and FashionMNIST
- COCO (Captioning and Detection)
- LSUN Classification
- ImageFolder
- Imagenet-12
- CIFAR10 and CIFAR100
- STL10
- SVHN
- PhotoTour

# MNIST dataset loading

```
# MNIST Dataset
train_dataset = datasets.MNIST(root='./data/',
                                train=True,
                                transform=transforms.ToTensor(),
                                download=True)

test_dataset = datasets.MNIST(root='./data/',
                               train=False,
                               transform=transforms.ToTensor())

# Data Loader (Input Pipeline)
train_loader = torch.utils.data.DataLoader(dataset=train_dataset,
                                             batch_size=batch_size,
                                             shuffle=True)

test_loader = torch.utils.data.DataLoader(dataset=test_dataset,
                                           batch_size=batch_size,
                                           shuffle=False)

for batch_idx, (data, target) in enumerate(train_loader):
    data, target = Variable(data), Variable(target)
    ...
```



# More dataset loaders are available

- MNIST and FashionMNIST
- COCO (Captioning and Detection)
- LSUN Classification
- ImageFolder
- Imagenet-12
- CIFAR10 and CIFAR100
- STL10
- SVHN
- PhotoTour

## Exercise 8-1:

- Check out existing data sets (torch.vision)
- Build DataLoader for
  - Titanic dataset: <https://www.kaggle.com/c/titanic/download/train.csv>
- Build a classifier using the DataLoader



## Lecture 9: Softmax Classifier