



30 JULY – 3 AUGUST *Los Angeles*
SIGGRAPH2017

IMPLICIT CROWDS: OPTIMIZATION INTEGRATOR FOR ROBUST CROWD SIMULATION

Ioannis Karamouzas¹, Nick Sohre², Rahul Narain², Stephen J. Guy²

¹Clemson University

²University of Minnesota




UNIVERSITY OF MINNESOTA
Driven to Discover®

COLLISION AVOIDANCE IN CROWDS




Given desired velocities, how should agents navigate around each other?



COLLISION AVOIDANCE IN CROWDS



Given desired velocities, how should agents navigate around each other?




LOCAL COLLISION AVOIDANCE



Adding Realism

- Vision-based approaches [Ondřej et al. 2010, Kapadia et al. 2012, Hughes et al. 2015, Dutra et al. 2017]
- Probabilistic approaches [Wolinski et al. 2016]
-



[Wolinski et al. 2016]



[Kapadia et al. 2012]




[Yu et al. 2012]

LOCAL COLLISION AVOIDANCE




Force-based methods [Reynolds 1987, 1999; Helbing et al. 2000; Pelechano et al. 2007, ...]

- Require very small time steps for stability



Velocity-based methods [van den Berg et al. 2008, 2011; Pettré et al 2011, ...]

- Overly conservative behavior



DESIDERATA



We seek a generic technique for multi-agent navigation that

- guarantees collision-free motion
- is robust to variations in scenario, density, time step
- exhibits high-fidelity behavior
- can update at footstep rates (0.3-0.5 s)

OUR CONTRIBUTIONS



1. General form of collision avoidance behaviors

$$\frac{d\mathbf{v}}{dt} = -\frac{\partial R(\mathbf{x}, \mathbf{v})}{\partial \mathbf{v}}$$

supporting optimization-based implicit integration

2. Application to state-of-the-art power law model

$$R(\mathbf{x}, \mathbf{v}) \propto \tau(\mathbf{x}, \mathbf{v})^{-p}$$

for practical crowd simulations



I. OPTIMIZATION INTEGRATOR FOR CROWDS

IMPLICIT INTEGRATION



- $$\frac{d}{dt} \begin{bmatrix} \mathbf{x} \\ \mathbf{v} \end{bmatrix} = \begin{bmatrix} \mathbf{v} \\ \mathbf{M}^{-1} \mathbf{f}(\mathbf{x}, \mathbf{v}) \end{bmatrix}$$



[Baraff and Witkin, 1998]

IMPLICIT INTEGRATION



- $\frac{d}{dt} \begin{bmatrix} \mathbf{x} \\ \mathbf{v} \end{bmatrix} = \begin{bmatrix} \mathbf{v} \\ \mathbf{M}^{-1} \mathbf{f}(\mathbf{x}, \mathbf{v}) \end{bmatrix} \Leftrightarrow$

$$\begin{aligned} \mathbf{x}^{n+1} - \mathbf{x}^n &= \mathbf{v}^{n+1} \Delta t, \\ \mathbf{M}(\mathbf{v}^{n+1} - \mathbf{v}^n) &= \mathbf{f}^{n+1} \Delta t \end{aligned}$$

- Unconditionally stable, but
- Need to solve a non linear system
- Slow (but we can use large time steps)



[Kaufman et al. 2014]

OPTIMIZATION INTEGRATORS




As long as forces are *conservative*:

$$\mathbf{f}(\mathbf{x}) = -\frac{dU(\mathbf{x})}{d\mathbf{x}},$$

we can express backward Euler in optimization form [Martin et al. 2011; Gast et al. 2015]:

$$\mathbf{x}^{n+1} = \arg \min_{\mathbf{x}} \left(\frac{1}{2\Delta t^2} \|\mathbf{x} - \tilde{\mathbf{x}}\|_{\mathbf{M}}^2 + U(\mathbf{x}) \right)$$



OPTIMIZATION INTEGRATORS




As long as forces are *conservative*:

$$\mathbf{f}(\mathbf{x}) = -\frac{dU(\mathbf{x})}{d\mathbf{x}},$$

we can express backward Euler in optimization form [Martin et al. 2011; Gast et al. 2015]:

$$\mathbf{x}^{n+1} = \arg \min_{\mathbf{x}} \left(\frac{1}{2\Delta t^2} \|\mathbf{x} - \tilde{\mathbf{x}}\|_{\mathbf{M}}^2 + U(\mathbf{x}) \right)$$

Interpretation: tradeoff between *maintaining velocity* and *reducing potential energy*




OPTIMIZATION INTEGRATORS



$$\mathbf{x}^{n+1} = \arg \min_{\mathbf{x}} \left(\frac{1}{2\Delta t^2} \|\mathbf{x} - \tilde{\mathbf{x}}\|_{\mathbf{M}}^2 + U(\mathbf{x}) \right)$$

Why this is good:

- Simple and fast algorithms (e.g. gradient descent, Gauss-Seidel) can be given guarantees
- Highly nonlinear forces can be used without linearization
- Lots of recent advances in optimization for data mining, machine learning, image processing, ...



[Fratarcangeli et al. 2016]

NON-CONSERVATIVE FORCES



Conservative potentials $U(\mathbf{x})$ can only model *position-dependent forces*

NON-CONSERVATIVE FORCES



Conservative potentials $U(\mathbf{x})$ can only model *position-dependent forces*

- Humans anticipate
 - People anticipate future trajectories of others [Cutting et al. 2005, Olivier et al. 2012; Karamouzas et al. 2014]
 - Brains have special neurons for estimating collisions [Gabbiani 2002]

Crowd forces depend both on positions and velocities!



ANTICIPATORY FORCES



Hypothesis: Multi-agent interactions can be expressed as

$$\mathbf{f}(\mathbf{x}, \mathbf{v}) = - \frac{\partial R(\mathbf{x}, \mathbf{v})}{\partial \mathbf{v}}$$

where R is an *anticipatory potential* that drives agents away from high-cost velocities

(This is analogous to dissipation potentials [Goldstein 1980] in classical mechanics)

OPTIMIZATION INTEGRATOR FOR NON-CONSERVATIVE FORCES



Anticipatory forces

$$\mathbf{v}^{n+1} = \arg \min_{\mathbf{v}} \frac{1}{2} \|\mathbf{v} - \tilde{\mathbf{v}}\|_{\mathbf{M}}^2 + R(\mathbf{x} + \mathbf{v}\Delta t, \mathbf{v})\Delta t$$

OPTIMIZATION INTEGRATOR FOR NON-CONSERVATIVE FORCES



Anticipatory + conservative forces

$$\mathbf{v}^{n+1} = \arg \min_{\mathbf{v}} \frac{1}{2} \|\mathbf{v} - \tilde{\mathbf{v}}\|_{\mathbf{M}}^2 + U(\mathbf{x} + \mathbf{v}\Delta t) + R(\mathbf{x} + \mathbf{v}\Delta t, \mathbf{v})\Delta t$$

- First-order accurate
- $U(\cdot) + R(\cdot)\Delta t$ is analogous to the “effective interaction potential” in symplectic integrators [Kane et al. 2000; Kharevych et al. 2006]
- Simple interpretation: tradeoff between maintaining velocity, reducing U , and reducing R

SOME EXISTING MODELS



Alignment behavior in boids [Reynolds 1987]:

$$\mathbf{f}_{ij} = -w(\|\mathbf{x}_{ij}\|)\mathbf{v}_{ij} \Leftrightarrow R_{ij} = w(\|\mathbf{x}_{ij}\|)\|\mathbf{v}_{ij}\|^2$$

SOME EXISTING MODELS




Alignment behavior in boids [Reynolds 1987]:

$$\mathbf{f}_{ij} = -w(\|\mathbf{x}_{ij}\|)\mathbf{v}_{ij} \Leftrightarrow R_{ij} = w(\|\mathbf{x}_{ij}\|)\|\mathbf{v}_{ij}\|^2$$

Velocity obstacles [Fiorini and Shiller 1998]:

$$\mathbf{v}_{ij} \notin VO(\mathbf{x}_{ij}) \Leftrightarrow R_{ij} = \begin{cases} \infty & \text{if } \mathbf{v}_{ij} \in VO(\mathbf{x}_{ij}) \\ 0 & \text{otherwise} \end{cases}$$



SOME EXISTING MODELS




Alignment behavior in boids [Reynolds 1987]:

$$\mathbf{f}_{ij} = -w(\|\mathbf{x}_{ij}\|)\mathbf{v}_{ij} \Leftrightarrow R_{ij} = w(\|\mathbf{x}_{ij}\|)\|\mathbf{v}_{ij}\|^2$$

Velocity obstacles [Fiorini and Shiller 1998]:

$$\mathbf{v}_{ij} \notin VO(\mathbf{x}_{ij}) \Leftrightarrow R_{ij} = \begin{cases} \infty & \text{if } \mathbf{v}_{ij} \in VO(\mathbf{x}_{ij}) \\ 0 & \text{otherwise} \end{cases}$$

What is R_{ij} for humans?



SOME EXISTING MODELS




Alignment behavior in boids [Reynolds 1987]:

$$\mathbf{f}_{ij} = -w(\|\mathbf{x}_{ij}\|)\mathbf{v}_{ij} \Leftrightarrow R_{ij} = w(\|\mathbf{x}_{ij}\|)\|\mathbf{v}_{ij}\|^2$$

Velocity obstacles [Fiorini and Shiller 1998]:

$$\mathbf{v}_{ij} \notin VO(\mathbf{x}_{ij}) \Leftrightarrow R_{ij} = \begin{cases} \infty & \text{if } \mathbf{v}_{ij} \in VO(\mathbf{x}_{ij}) \\ 0 & \text{otherwise} \end{cases}$$

What is R_{ij} for humans?





II. IMPLICIT CROWDS USING THE POWER-LAW MODEL

POWER-LAW MODEL [Karamouzas et al. 2014]





For each pair of agents:

- Compute time to collision $\tau(\mathbf{x}, \mathbf{v})$

Collisions occurs when

$$\|\mathbf{x}_{ij} + \mathbf{v}_{ij}\tau\| = r_i + r_j$$



POWER-LAW MODEL [Karamouzas et al. 2014]




For each pair of agents:

- Compute time to collision $\tau(\mathbf{x}, \mathbf{v})$

Collisions occurs when

$$\|\mathbf{x}_{ij} + \mathbf{v}_{ij}\tau\| = r_i + r_j$$



POWER-LAW MODEL [Karamouzas et al. 2014]




For each pair of agents:

- Compute time to collision $\tau(\mathbf{x}, \mathbf{v})$
- Compute potential $R(\mathbf{x}, \mathbf{v}) \propto \tau(\mathbf{x}, \mathbf{v})^{-p}$

Collisions occurs when

$$\|\mathbf{x}_{ij} + \mathbf{v}_{ij}\tau\| = r_i + r_j$$



POWER-LAW MODEL [Karamouzas et al. 2014]




For each pair of agents:

- Compute time to collision $\tau(\mathbf{x}, \mathbf{v})$
- Compute potential $R(\mathbf{x}, \mathbf{v}) \propto \tau(\mathbf{x}, \mathbf{v})^{-p}$

Collisions occurs when

$$\|\mathbf{x}_{ij} + \mathbf{v}_{ij}\tau\| = r_i + r_j$$



IMPLICIT POWER-LAW CROWDS




Problem: Apply power law potential to optimization-based backward Euler

Easy? Not quite...

- R is discontinuous at boundary of collision cone
- R becomes infinitely steep as agents graze past

Both phenomena cause numerical solvers to “get stuck”



IMPLICIT POWER-LAW CROWDS





Problem: Apply power law potential to optimization-based backward Euler

Easy? Not quite...

- R is discontinuous at boundary of collision cone
- R becomes infinitely steep as agents graze past



Both phenomena cause numerical solvers to “get stuck”



A CONTINUOUS TTC POTENTIAL




Discontinuity due to time to collision (finite if collision predicted, infinite if not)



A CONTINUOUS TTC POTENTIAL





Discontinuity due to time to collision (finite if collision predicted, infinite if not)



A CONTINUOUS TTC POTENTIAL



Discontinuity due to time to collision (finite if collision predicted, infinite if not)




A CONTINUOUS TTC POTENTIAL



Solution:

Let's work with $\frac{1}{\tau}$ (or, “imminence” of collision)

- Replace it with a continuous approximation, e.g., by linear extrapolation




A CONTINUOUS TTC POTENTIAL



Solution:

Let's work with $\frac{1}{\tau}$ (or, “imminence” of collision)


- Replace it with a continuous approximation, e.g., by linear extrapolation
- R becomes C^{p-1} -smooth



MAINTAINING SEPARATION



Grazing trajectories make R badly behaved



MAINTAINING SEPARATION



Grazing trajectories make R badly behaved

- Add some distance-based repulsion $U_{ij} \propto \frac{1}{\|\mathbf{x}_{ij}\| - r_{ij}}$
- Continuous collision detection: replace distance $\|\mathbf{x}_{ij}\|$ with *minimum* distance over the time step

Alternative approach to repulsion: add uncertainty to time-to-collision computation [Forootaninia et al. 2017]



III. ANALYSIS AND RESULTS

THEORETICAL ANALYSIS



Implicit integration + continuous PowerLaw potential

- Guaranteed collision-free motion
- Smooth (C^2 -continuous) trajectories

THEORETICAL ANALYSIS



Implicit integration + continuous PowerLaw potential

- Guaranteed collision-free motion
- Smooth (C^2 -continuous) trajectories

Collision-free proof

- \mathbf{v}^{n+1} minimizes $\frac{1}{2} \|\mathbf{v}^{n+1} - \tilde{\mathbf{v}}\|_{\mathbf{M}}^2 + U(\mathbf{x}^{n+1}) + R(\mathbf{x}^{n+1}, \mathbf{v}^{n+1})\Delta t$
- R is infinite for a colliding state. U is infinite for a tunneling step. So these cannot be minima.

COLLISION-FREE MOTION



- Comparisons to
 - ORCA [van den Berg et al. 2011] (representative velocity-based approach)
 - PowerLaw [Karamouzas et al. 2014] (non-continuous TTC + forward Euler)

	# Agents	# Obstacles	Roadmap	Density
Hallway	300	2	no	medium
Crossing	400	0	no	high
Random	500	0	no	low
Evacuation	1200	178	yes	very high
Blocks	2000	112	yes	low

COLLISION-FREE MOTION



- Comparisons to
 - ORCA [van den Berg et al. 2011] (representative velocity-based approach)
 - PowerLaw [Karamouzas et al. 2014] (non-continuous TTC + forward Euler)

	# Agents	# Obstacles	Roadmap	Density	Maximum collision-free Δt [ms]		
					PowerLaw	ORCA	Implicit
Hallway	300	2	no	medium	40	100	
Crossing	400	0	no	high	20	35	
Random	500	0	no	low	30	140	
Evacuation	1200	178	yes	very high	< 5	25	
Blocks	2000	112	yes	low	30	90	

COLLISION-FREE MOTION





- Comparisons to
 - ORCA [van den Berg et al. 2011] (representative velocity-based approach)
 - PowerLaw [Karamouzas et al. 2014] (non-continuous TTC + forward Euler)

	# Agents	# Obstacles	Roadmap	Density	Maximum collision-free Δt [ms]		
					PowerLaw	ORCA	Implicit
Hallway	300	2	no	medium	40	100	> 1000
Crossing	400	0	no	high	20	35	> 1000
Random	500	0	no	low	30	140	> 1000
Evacuation	1200	178	yes	very high	< 5	25	> 1000
Blocks	2000	112	yes	low	30	90	> 1000


FIDELITY TO HUMAN DATA



Comparison to human crowds [Charalambous et al. 2014]




TIME STEP STABILITY




TIME STEP STABILITY



Motion doesn't change significantly with time step




PERFORMANCE



Cost is linear in number of agents,
increases slowly with time step size

(Still, 2x-10x slower than ORCA or PowerLaw on
a 6-core Intel Xeon E5-1650)

Future work: Improve performance via
local-global alternating minimization techniques




[Liu et al. 2017]

[Narain et al. 2016]

LIMITATIONS AND FUTURE WORK




- Can other recent crowd models be formulated via interaction energies [Wolinski et al. 2016, Dutra et al. 2017; ...]?
- Incorporating asymmetrical interactions, e.g., leader-following behavior
- What is the Δt threshold where quality is maintained?



LIMITATIONS AND FUTURE WORK




- Can other recent crowd models be formulated via interaction energies [Wolinski et al. 2016, Dutra et al. 2017; ...]?
- Incorporating asymmetrical interactions, e.g., leader-following behavior
- What is the Δt threshold where quality is maintained?



FUTURE WORK



- Applications to LOD systems and footstep-based animation engines
- Applications to nonlinear dissipation forces in physics-based animation



[Zhu et al. 2015]



[Xu and Barbic 2017]



THANK YOU

<https://www.cs.clemson.edu/~ioannis/implicit-crowds/>