



Telecommunication
Networks Group

Technical University Berlin

Telecommunication Networks Group

Variations in Wi-Fi RSSI due to different types of Interferences

Aravinth, Sivalingam Panchadcharam

contact@aravinth.info

Berlin, March 2014

Project in advanced network technologies

Supervisors: Dr. Arash Behboodi, Filip Lemic

Abstract

WiFi Beacon packets are transmitted periodically to announce the presence of WLAN. RSSI is Received Signal Strength Indicator which indicates the power of signal that is received at the receiver. Beacon Packet RSSI values are extensively used for ranging and localization purpose. However, RSSI value changes with various interferences, different chipsets and distance. This project work includes an implementation of a software tool to visualize the raw data obtained during the experiments and examines how these RSSI values changed by controlled interferences.

Contents

1	Introduction	4
2	Problem Statement	5
3	Raw Ranging Data Visualization Tool	6
3.1	Database	6
3.2	Floor Plan	6
3.3	Graph	8
3.4	Experiment Description	8
3.5	API	8
4	Design	11
4.1	Interference	11
4.1.1	Introduction	11
4.1.2	Interference Scenarios	11
5	Experiments	16
5.1	Infrastructure	16
5.2	Testbed	16
5.2.1	TWIST	16
5.2.2	iLab.t	17
5.3	Experiment Procedure	17
6	Results	18
7	Conclusion	19

Chapter 1

Introduction

Beacon Packet

In Wireless Local Area Network (WLAN) Beacon Packets are transmitted periodically to announce the presence of WiFi Network. It contains information of the network such as SSID, BSSID and type of encryption.

Received Signal Strength Indicator (RSSI)

It indicates the power of signal which is received at the receiver and included into the beacon packet by Network Interface Card.

Chapter 2

Problem Statement

Beacon Packet frame RSSI Changes in RSSI by

Chapter 3

Raw Ranging Data Visualization Tool

Introduction

Measurements yield large amount of raw data which contains the complete information of experiments such as testbed measurement locations, access points, rssi, channel, ssid, bssid, latency. In order to track collected of raw data, a raw ranging data visualization tool was implemented.

This tools helps us to list and visualize the available databases and collections of experiments under one hood.

This tool is a web-based standalone software which was implemented using Javascript and various libraries. This tool can be simply started by opening it on a web browser. It needs an Internet connection to retrieve data from the backend servers.

This tool makes use of asynchronous (AJAX) ability of Javascript and processes large array of raw data.

This tool consists of 4 panels which showcases the work flow in an user friendly manner. Usage and functionality of each panel is explained in the following sections.

3.1 Database

Database panel is the landing page of this tool. It contains 4 sub-panels.

List of Servers lists URIs of server that contains various RAW data collected from the experiments.

Remote Server contains the complete set of RAW data. Copy of the RAW data can also be stored on the local machine. Static Data contains a simple set of RAW data for the purpose of debugging.

List of Databases lists URIs of databases which are stored in the server.

List of Collections lists the collections of experiments which were carried out. URI denotes the name of Testbed, experiment size and experiment type.

List of Floor Plans lists the names of the floor plans on which experiments were carried out. Floor Plan must be selected according to the experiment.

3.2 Floor Plan

Floor Plan panel contains the map of selected testbed. Once the appropriate floor plan for an experiment is selected, all the measurement points are loaded into the map. Measurement point is circular




Figure 3.1: Dashboard of the visualization tool




Figure 3.2: Floor Plan of the visualization tool




Figure 3.3: Graph of the visualization tool

button that turns blue when it is clicked and it lists RSSI values measured at that geographical point. On the right side of the Floor Plan, Channel and SSID information of the selected measurement point is shown. If the Raw Data contains channel information, then it will be listed in the dropdown other it will be listed as Unknown. RSSI values are grouped together on the basis of same SSID and BSSID. Info tab at the right below shows some specific information about the selected measurement point.

3.3 Graph

Graph panel contains a histogram that is generated dynamically by selected a particular access point on Floor Plan panel. Number of Bins of the histogram are also dynamically adjusted based on the total number of RSSI values measured. Info tab shows coordinate information of the selected measurement points as well as the statistics of RSSI values.

3.4 Experiment Description

Experiment Description panel contains detail of the experiment such as testbed environment, sender and receiver device specification and interference pattern. This information is stored in Metadata database.

3.5 API

API is a Javascript documentation which can be viewed by clicking on JavascriptDoc button on the top menu. API reveals the Functions, Constants, Views, Collections, Events and Utilities used to




Figure 3.4: Experiment Description of the visualization tool




Figure 3.5: API of the visualization tool

visualize the Raw Ranging Data. It helps to extend this program, do further implementation, add new features and debug the code.




Figure 4.1: Locations of measurement points

Chapter 4

Design

4.1 Interference

4.1.1 Introduction

This document shortly presents initial interference scenarios that will be artificially generated in TKN Wireless Indoor Sensor network Testbed (TWIST) testbed in order to benchmark different indoor localization solutions in the environments with controlled interference. The reason for benchmark representative indoor localization solutions in the environments with controlled interference is to determine if and to which extend different types and amounts of Radio Frequency (RF) interference can influence the indoor localization performance.

4.1.2 Interference Scenarios

Reference Scenario

This reference scenario is instantiated on the 2nd floor of the TWIST testbed in Berlin. It is called “Reference scenario”, while no artificial interference is generated and the presence of uncontrolled interference is minimized. According to the EVARILOS Benchmarking Handbook (EBH), this scenario is an instance of the “Small office” type of scenarios. In this scenario 20 measurement points are defined and their locations are given in Figure 1.

At each measurement point the indoor localization System Under Test (SUT) is requested to estimate location. The SUT device is carried to each measurement location using the robotic platform. The navigation stack of the robotic platform gives one order of magnitude more accurate location estimation than considered SUTs and the location obtained from the robotic platform is considered as the ground truth.

The experiments were performed at the weekend afternoon, so the influence of interferes has been minimized. Furthermore, the wireless spectrum has been measured using the WiSpy device attached to the robotic platform and all measurements with the interference threshold above certain level have been repeated. Finally, before each experiment a more detained measurement of the spectrum has been taken with the spectrum analyzer at a predefined location.

Interference Scenario 1

First interference scenario instantiated in TWIST testbed uses the testbed Wireless Fidelity (WiFi) nodes as interference sources. Interference type is jamming on one IEEE 802.11 channel with the maximum transmission power. Three of such jamming nodes are present at different locations in the testbed environment. Summary of this interference scenario is given in Table 4.1.

Interference Scenario 2

In this interference scenario instantiated in TWIST testbed interference is created using the IEEE 802.15.4 Tmote Sky nodes. The interference type is jamming on one IEEE 802.15.4 channel with a constant transmit power equal to 0 dBm. Five of these jamming nodes will be present in the testbed environment. Summary of this interference scenario is given in Table 4.2.

Interference Scenario 3

Second interference scenario instantiated in TWIST testbed defines interference types that is usual for the office and home environments. Namely, interference is emulated using 4 WiFi embedded Personal Computers (PCs), namely a server, email client, data client, and video client. The server acts as a WiFi Access Point (AP) and a gateway for the emulated services. The email client will “check email” once every 15 seconds for a duration of one second. The data client is emulated via TCP streams one starting at 45 seconds for a duration of 22.5 seconds and the other starting at 105 seconds for a duration of 45 seconds. The video client is emulated as a UDP stream of 100 kbps for half the experiment cycle and it will start at the middle of the experiment. In total, the experiment takes 150 seconds. Summary of this interference scenario is given in Table 4.3.

Table 4.1: Interference scenario summary

Types of interference sources	
WiFi	✓
Microwave	×
DECT	×
Bluetooth	×
3G	×
ZigBee	×
Types of interference sources	
Number of sources	3
Power	20 dBm
Waveform	Carrier jamming
Specific pattern	
Start & stop time	Beginning & end of experiment
Traffic model	
Traffic parameters of interference	
Packet size	
Inter-packet gap	
Bit rate	
File size	
Start & stop size	
Traffic model	
Network parameters	
Network size	
Node density	
Node mobility	
Node failures	

Table 4.2: Interference scenario summary

Types of interference sources	
WiFi	×
Microwave	×
DECT	×
Bluetooth	×
3G	×
ZigBee	✓
Types of interference sources	
Number of sources	5
Power	0 dBm
Waveform	Carrier jamming
Specific pattern	
Start & stop time	Beginning & end of experiment
Traffic model	IEEE 802.15.4 radio
Traffic parameters of interference	
Packet size	
Inter-packet gap	
Bit rate	
File size	
Start & stop size	
Traffic model	
Network parameters	
Network size	
Node density	
Node mobility	
Node failures	

Table 4.3: Interference scenario summary

Types of interference sources	
WiFi	✓
Microwave	×
DECT	×
Bluetooth	×
3G	×
ZigBee	×
Types of interference sources	
Number of sources	3
Power	20 dBm
Waveform	
Specific pattern	
Start & stop time	Beginning & end of experiment
Traffic model	WiFi traffic
Traffic parameters of interference	
Packet size	
Inter-packet gap	
Bit rate	
File size	
Start & stop size	
Traffic model	
Network parameters	
Network size	
Node density	
Node mobility	
Node failures	




Figure 5.1: Experiment Environment

Chapter 5

Experiments

5.1 Infrastructure

Experiments are carried on two different Testbeds. As shown in the figure 5.1, Testbeds provide a robotic automated platform to carry out the experiment. Setting up the measurement points, configuring the nodes, accessing signal generators and various other devices are done with the help of control center.

5.2 Testbed

5.2.1 TWIST

The TKN Wireless Indoor Sensor network Testbed (TWIST), developed by the Telecommunication Networks Group (TKN) at the Technische Universität Berlin, is a scalable and flexible testbed architecture for experimenting with wireless sensor network applications in an indoor setting. It provides basic services like node configuration, network-wide programming, out-of-band extraction of debug data and gathering of application data.

It is equipped with 102 TmoteSky nodes and 102 eyesIFX nodes. For the experiments 3 Different Floor Plans are used. Signal Generators are used to generate microwave signals which were used to jam the channel during the experiments. From control center fixed coordinates are set to the robot, so that accurate measurement points are achieved in the experiments.

5.2.2 iLab.t

The iMinds iLab.t technology centre offers the experimentation environments, the hardware, the measurement equipment and the software tools needed to develop your ICT innovations, and/or test their performance and service quality.

A generic experimentation facility of 100 nodes (dual processor, dual core servers) interconnected via non-blocking 1.5 Tb/s Ethernet switch, called the Virtual Wall. Two generic wireless experimentation facilities of 200 and 80 nodes respectively, specifically targeting innovations involving the use, configuration or set-up of wireless networks (includes Wi-Fi, 802.15.4, Bluetooth, sensor nodes, mobile robots and a mobility emulation set-up), called the w-iLab.t.

5.3 Experiment Procedure

This shows step by step how experiments were carried out. Even though the experiments were conducted in various environment, procedure of reference experiment is explained here. Since this experiment is conducted under environment where no artificial interference is generated and the presence of uncontrolled interference is minimized, this experiment is referred to as reference scenario.

-
- System Under Test (SUT) is
- Hola

Chapter 6

Results

Chapter 7

Conclusion

Bibliography

[1] Leslie Lamport

[2] Leslie Lamport