./Platform.Data.Doublets/Decorators/LinksCascadeUniquenessAndUsagesResolver.cs

```
#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

using System.Runtime.CompilerServices;

namespace Platform.Data.Doublets.Decorators
{
    public class LinksCascadeUniquenessAndUsagesResolver<TLink> : LinksUniquenessResolver<TLink>
    {
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinksCascadeUniquenessAndUsagesResolver(ILinks<TLink> links) : base(links) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink ResolveAddressChangeConflict(TLink oldLinkAddress, TLink
        ↪  newLinkAddress)
        {
            // Use Facade (the last decorator) to ensure recursion working correctly
            Facade.MergeUsages(oldLinkAddress, newLinkAddress);
            return base.ResolveAddressChangeConflict(oldLinkAddress, newLinkAddress);
        }
    }
}
```

./Platform.Data.Doublets/Decorators/LinksCascadeUsagesResolver.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Decorators
{
    /// <remarks>
    /// <para>Must be used in conjunction with NonNullContentsLinkDeletionResolver.</para>
    /// <para>Должен использоваться вместе с NonNullContentsLinkDeletionResolver.</para>
    /// </remarks>
    public class LinksCascadeUsagesResolver<TLink> : LinksDecoratorBase<TLink>
    {
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinksCascadeUsagesResolver(ILinks<TLink> links) : base(links) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override void Delete(IList<TLink> restrictions)
        {
            var linkIndex = restrictions[Constants.IndexPart];
            // Use Facade (the last decorator) to ensure recursion working correctly
            Facade.DeleteAllUsages(linkIndex);
            Links.Delete(linkIndex);
        }
    }
}
```

./Platform.Data.Doublets/Decorators/LinksDecoratorBase.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Decorators
{
    public abstract class LinksDecoratorBase<TLink> : LinksOperatorBase<TLink>, ILinks<TLink>
    {
        private ILinks<TLink> _facade;

        public LinksConstants<TLink> Constants { get; }

        public ILinks<TLink> Facade
        {
            get => _facade;
            set
            {
                _facade = value;
                if (Links is LinksDecoratorBase<TLink> decorator)
                {
                    decorator.Facade = value;
                }
                else if (Links is LinksDisposableDecoratorBase<TLink> disposableDecorator)
                {
```

```
                    disposableDecorator.Facade = value;
                }
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected LinksDecoratorBase(ILinks<TLink> links) : base(links)
        {
            Constants = links.Constants;
            Facade = this;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public virtual TLink Count(IList<TLink> restrictions) => Links.Count(restrictions);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public virtual TLink Each(Func<IList<TLink>, TLink> handler, IList<TLink> restrictions)
        ↪  => Links.Each(handler, restrictions);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public virtual TLink Create(IList<TLink> restrictions) => Links.Create(restrictions);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public virtual TLink Update(IList<TLink> restrictions, IList<TLink> substitution) =>
        ↪  Links.Update(restrictions, substitution);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public virtual void Delete(IList<TLink> restrictions) => Links.Delete(restrictions);
    }
}
```

./Platform.Data.Doublets/Decorators/LinksDisposableDecoratorBase.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Disposables;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Decorators
{
    public abstract class LinksDisposableDecoratorBase<TLink> : DisposableBase, ILinks<TLink>
    {
        private ILinks<TLink> _facade;

        public LinksConstants<TLink> Constants { get; }

        public ILinks<TLink> Links { get; }

        public ILinks<TLink> Facade
        {
            get => _facade;
            set
            {
                _facade = value;
                if (Links is LinksDecoratorBase<TLink> decorator)
                {
                    decorator.Facade = value;
                }
                else if (Links is LinksDisposableDecoratorBase<TLink> disposableDecorator)
                {
                    disposableDecorator.Facade = value;
                }
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected LinksDisposableDecoratorBase(ILinks<TLink> links)
        {
            Links = links;
            Constants = links.Constants;
            Facade = this;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public virtual TLink Count(IList<TLink> restrictions) => Links.Count(restrictions);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public virtual TLink Each(Func<IList<TLink>, TLink> handler, IList<TLink> restrictions)
        ↪  => Links.Each(handler, restrictions);
```

```

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public virtual TLink Create(IList<TLink> restrictions) => Links.Create(restrictions);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public virtual TLink Update(IList<TLink> restrictions, IList<TLink> substitution) =>
        ↪ Links.Update(restrictions, substitution);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public virtual void Delete(IList<TLink> restrictions) => Links.Delete(restrictions);

        protected override bool AllowMultipleDisposeCalls => true;

        protected override void Dispose(bool manual, bool wasDisposed)
        {
            if (!wasDisposed)
            {
                Links.DisposeIfPossible();
            }
        }
    }
}
```

./Platform.Data.Doublets/Decorators/LinksInnerReferenceExistenceValidator.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Decorators
{
    // TODO: Make LinksExternalReferenceValidator. A layer that checks each link to exist or to
    ↪ be external (hybrid link's raw number).
    public class LinksInnerReferenceExistenceValidator<TLink> : LinksDecoratorBase<TLink>
    {
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinksInnerReferenceExistenceValidator(ILinks<TLink> links) : base(links) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override TLink Each(Func<IList<TLink>, TLink> handler, IList<TLink> restrictions)
        {
            Links.EnsureInnerReferenceExists(restrictions, nameof(restrictions));
            return Links.Each(handler, restrictions);
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override TLink Update(IList<TLink> restrictions, IList<TLink> substitution)
        {
            // TODO: Possible values: null, ExistentLink or NonExistentHybrid(ExternalReference)
            Links.EnsureInnerReferenceExists(restrictions, nameof(restrictions));
            Links.EnsureInnerReferenceExists(substitution, nameof(substitution));
            return Links.Update(restrictions, substitution);
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override void Delete(IList<TLink> restrictions)
        {
            var link = restrictions[Constants.IndexPart];
            Links.EnsureLinkExists(link, nameof(link));
            Links.Delete(link);
        }
    }
}
```

./Platform.Data.Doublets/Decorators/LinksItselfConstantToSelfReferenceResolver.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Decorators
{
    public class LinksItselfConstantToSelfReferenceResolver<TLink> : LinksDecoratorBase<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪ EqualityComparer<TLink>.Default;

```

```
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinksItselfConstantToSelfReferenceResolver(ILinks<TLink> links) : base(links) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override TLink Each(Func<IList<TLink>, TLink> handler, IList<TLink> restrictions)
        {
            var constants = Constants;
            var itselfConstant = constants.Itself;
            var indexPartConstant = constants.IndexPart;
            var sourcePartConstant = constants.SourcePart;
            var targetPartConstant = constants.TargetPart;
            var restrictionsCount = restrictions.Count;
            if (!_equalityComparer.Equals(constants.Any, itselfConstant)
             && (((restrictionsCount > indexPartConstant) &&
              ↪  _equalityComparer.Equals(restrictions[indexPartConstant], itselfConstant))
             || ((restrictionsCount > sourcePartConstant) &&
              ↪  _equalityComparer.Equals(restrictions[sourcePartConstant], itselfConstant))
             || ((restrictionsCount > targetPartConstant) &&
              ↪  _equalityComparer.Equals(restrictions[targetPartConstant], itselfConstant))))
            {
                // Itself constant is not supported for Each method right now, skipping execution
                return constants.Continue;
            }
            return Links.Each(handler, restrictions);
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override TLink Update(IList<TLink> restrictions, IList<TLink> substitution) =>
         ↪  Links.Update(restrictions, Links.ResolveConstantAsSelfReference(Constants.Itself,
         ↪  restrictions, substitution));
    }
}
```

./Platform.Data.Doublets/Decorators/LinksNonExistentDependenciesCreator.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Decorators
{
    /// <remarks>
    /// Not practical if newSource and newTarget are too big.
    /// To be able to use practical version we should allow to create link at any specific
    ↪  location inside ResizableDirectMemoryLinks.
    /// This in turn will require to implement not a list of empty links, but a list of ranges
    ↪  to store it more efficiently.
    /// </remarks>
    public class LinksNonExistentDependenciesCreator<TLink> : LinksDecoratorBase<TLink>
    {
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinksNonExistentDependenciesCreator(ILinks<TLink> links) : base(links) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override TLink Update(IList<TLink> restrictions, IList<TLink> substitution)
        {
            var constants = Constants;
            Links.EnsureCreated(substitution[constants.SourcePart],
             ↪  substitution[constants.TargetPart]);
            return Links.Update(restrictions, substitution);
        }
    }
}
```

./Platform.Data.Doublets/Decorators/LinksNullConstantToSelfReferenceResolver.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Decorators
{
    public class LinksNullConstantToSelfReferenceResolver<TLink> : LinksDecoratorBase<TLink>
    {
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinksNullConstantToSelfReferenceResolver(ILinks<TLink> links) : base(links) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override TLink Create(IList<TLink> restrictions)
```

```
        {
            var link = Links.Create();
            return Links.Update(link, link, link);
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override TLink Update(IList<TLink> restrictions, IList<TLink> substitution) =>
        ↪  Links.Update(restrictions, Links.ResolveConstantAsSelfReference(Constants.Null,
        ↪  restrictions, substitution));
    }
}
```

./Platform.Data.Doublets/Decorators/LinksUniquenessResolver.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Decorators
{
    public class LinksUniquenessResolver<TLink> : LinksDecoratorBase<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪  EqualityComparer<TLink>.Default;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinksUniquenessResolver(ILinks<TLink> links) : base(links) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override TLink Update(IList<TLink> restrictions, IList<TLink> substitution)
        {
            var newLinkAddress = Links.SearchOrDefault(substitution[Constants.SourcePart],
            ↪  substitution[Constants.TargetPart]);
            if (_equalityComparer.Equals(newLinkAddress, default))
            {
                return Links.Update(restrictions, substitution);
            }
            return ResolveAddressChangeConflict(restrictions[Constants.IndexPart],
            ↪  newLinkAddress);
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected virtual TLink ResolveAddressChangeConflict(TLink oldLinkAddress, TLink
        ↪  newLinkAddress)
        {
            if (!_equalityComparer.Equals(oldLinkAddress, newLinkAddress) &&
            ↪  Links.Exists(oldLinkAddress))
            {
                Facade.Delete(oldLinkAddress);
            }
            return newLinkAddress;
        }
    }
}
```

./Platform.Data.Doublets/Decorators/LinksUniquenessValidator.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Decorators
{
    public class LinksUniquenessValidator<TLink> : LinksDecoratorBase<TLink>
    {
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinksUniquenessValidator(ILinks<TLink> links) : base(links) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override TLink Update(IList<TLink> restrictions, IList<TLink> substitution)
        {
            Links.EnsureDoesNotExists(substitution[Constants.SourcePart],
            ↪  substitution[Constants.TargetPart]);
            return Links.Update(restrictions, substitution);
        }
    }
}
```

./Platform.Data.Doublets/Decorators/LinksUsagesValidator.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Decorators
{
    public class LinksUsagesValidator<TLink> : LinksDecoratorBase<TLink>
    {
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinksUsagesValidator(ILinks<TLink> links) : base(links) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override TLink Update(IList<TLink> restrictions, IList<TLink> substitution)
        {
            Links.EnsureNoUsages(restrictions[Constants.IndexPart]);
            return Links.Update(restrictions, substitution);
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override void Delete(IList<TLink> restrictions)
        {
            var link = restrictions[Constants.IndexPart];
            Links.EnsureNoUsages(link);
            Links.Delete(link);
        }
    }
}
```

./Platform.Data.Doublets/Decorators/NonNullContentsLinkDeletionResolver.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Decorators
{
    public class NonNullContentsLinkDeletionResolver<TLink> : LinksDecoratorBase<TLink>
    {
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public NonNullContentsLinkDeletionResolver(ILinks<TLink> links) : base(links) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override void Delete(IList<TLink> restrictions)
        {
            var linkIndex = restrictions[Constants.IndexPart];
            Links.EnforceResetValues(linkIndex);
            Links.Delete(linkIndex);
        }
    }
}
```

./Platform.Data.Doublets/Decorators/UInt64Links.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Decorators
{
    /// <summary>
    /// Представляет объект для работы с базой данных (файлом) в формате Links (массива связей).
    /// </summary>
    /// <remarks>
    /// Возможные оптимизации:
    /// Объединение в одном поле Source и Target с уменьшением до 32 бит.
    ///     + меньше объём БД
    ///     - меньше производительность
    ///     - больше ограничение на количество связей в БД)
    /// Ленивое хранение размеров поддеревьев (расчитываемое по мере использования БД)
    ///     + меньше объём БД
    ///     - больше сложность
    ///
    /// Текущее теоретическое ограничение на индекс связи, из-за использования 5 бит в размере
    ↪  поддеревьев для AVL баланса и флагов нитей: 2 в степени(64 минус 5 равно 59 ) равно 576
    ↪  460 752 303 423 488
    /// Желательно реализовать поддержку переключения между деревьями и битовыми индексами
    ↪  (битовыми строками) - вариант матрицы (выстраеваемой лениво).
```

```
23      ///
24      /// Решить отключать ли проверки при компиляции под Release. Т.е. исключения будут
        ↪  выбрасываться только при #if DEBUG
25      /// </remarks>
26      public class UInt64Links : LinksDisposableDecoratorBase<ulong>
27      {
28          [MethodImpl(MethodImplOptions.AggressiveInlining)]
29          public UInt64Links(ILinks<ulong> links) : base(links) { }
30
31          [MethodImpl(MethodImplOptions.AggressiveInlining)]
32          public override ulong Create(IList<ulong> restrictions) => Links.CreatePoint();
33
34          public override ulong Update(IList<ulong> restrictions, IList<ulong> substitution)
35          {
36              var constants = Constants;
37              var indexPartConstant = constants.IndexPart;
38              var updatedLink = restrictions[indexPartConstant];
39              var sourcePartConstant = constants.SourcePart;
40              var newSource = substitution[sourcePartConstant];
41              var targetPartConstant = constants.TargetPart;
42              var newTarget = substitution[targetPartConstant];
43              var nullConstant = constants.Null;
44              var existedLink = nullConstant;
45              var itselfConstant = constants.Itself;
46              if (newSource != itselfConstant && newTarget != itselfConstant)
47              {
48                  existedLink = Links.SearchOrDefault(newSource, newTarget);
49              }
50              if (existedLink == nullConstant)
51              {
52                  var before = Links.GetLink(updatedLink);
53                  if (before[sourcePartConstant] != newSource || before[targetPartConstant] !=
                    ↪  newTarget)
54                  {
55                      Links.Update(updatedLink, newSource == itselfConstant ? updatedLink :
                        ↪  newSource,
56                                                newTarget == itselfConstant ? updatedLink :
                                                  ↪  newTarget);
57                  }
58                  return updatedLink;
59              }
60              else
61              {
62                  return Facade.MergeAndDelete(updatedLink, existedLink);
63              }
64          }
65
66          [MethodImpl(MethodImplOptions.AggressiveInlining)]
67          public override void Delete(IList<ulong> restrictions)
68          {
69              var linkIndex = restrictions[Constants.IndexPart];
70              Links.EnforceResetValues(linkIndex);
71              Facade.DeleteAllUsages(linkIndex);
72              Links.Delete(linkIndex);
73          }
74      }
75  }
```

./Platform.Data.Doublets/Decorators/UniLinks.cs

```
1   using System;
2   using System.Collections.Generic;
3   using System.Linq;
4   using Platform.Collections;
5   using Platform.Collections.Arrays;
6   using Platform.Collections.Lists;
7   using Platform.Data.Universal;
8
9   #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
10
11  namespace Platform.Data.Doublets.Decorators
12  {
13      /// <remarks>
14      /// What does empty pattern (for condition or substitution) mean? Nothing or Everything?
15      /// Now we go with nothing. And nothing is something one, but empty, and cannot be changed
        ↪  by itself. But can cause creation (update from nothing) or deletion (update to nothing).
16      ///
17      /// TODO: Decide to change to IDoubletLinks or not to change. (Better to create
        ↪  DefaultUniLinksBase, that contains logic itself and can be implemented using both
        ↪  IDoubletLinks and ILinks.)
```

```
18      /// </remarks>
19      internal class UniLinks<TLink> : LinksDecoratorBase<TLink>, IUniLinks<TLink>
20      {
21          private static readonly EqualityComparer<TLink> _equalityComparer =
            ↪ EqualityComparer<TLink>.Default;
22
23          public UniLinks(ILinks<TLink> links) : base(links) { }
24
25          private struct Transition
26          {
27              public IList<TLink> Before;
28              public IList<TLink> After;
29
30              public Transition(IList<TLink> before, IList<TLink> after)
31              {
32                  Before = before;
33                  After = after;
34              }
35          }
36
37          //public static readonly TLink NullConstant = Use<LinksConstants<TLink>>.Single.Null;
38          //public static readonly IReadOnlyList<TLink> NullLink = new
            ↪ ReadOnlyCollection<TLink>(new List<TLink> { NullConstant, NullConstant, NullConstant
            ↪ });
39
40          // TODO: Подумать о том, как реализовать древовидный Restriction и Substitution
            ↪ (Links-Expression)
41          public TLink Trigger(IList<TLink> restriction, Func<IList<TLink>, IList<TLink>, TLink>
            ↪ matchedHandler, IList<TLink> substitution, Func<IList<TLink>, IList<TLink>, TLink>
            ↪ substitutedHandler)
42          {
43              ////List<Transition> transitions = null;
44              ////if (!restriction.IsNullOrEmpty())
45              ////{
46              ////    // Есть причина делать проход (чтение)
47              ////    if (matchedHandler != null)
48              ////    {
49              ////        if (!substitution.IsNullOrEmpty())
50              ////        {
51              ////            // restriction => { 0, 0, 0 } | { 0 } // Create
52              ////            // substitution => { itself, 0, 0 } | { itself, itself, itself } //
                ↪ Create / Update
53              ////            // substitution => { 0, 0, 0 } | { 0 } // Delete
54              ////            transitions = new List<Transition>();
55              ////            if (Equals(substitution[Constants.IndexPart], Constants.Null))
56              ////            {
57              ////                // If index is Null, that means we always ignore every other
                ↪ value (they are also Null by definition)
58              ////                var matchDecision = matchedHandler(, NullLink);
59              ////                if (Equals(matchDecision, Constants.Break))
60              ////                    return false;
61              ////                if (!Equals(matchDecision, Constants.Skip))
62              ////                    transitions.Add(new Transition(matchedLink, newValue));
63              ////            }
64              ////            else
65              ////            {
66              ////                Func<T, bool> handler;
67              ////                handler = link =>
68              ////                {
69              ////                    var matchedLink = Memory.GetLinkValue(link);
70              ////                    var newValue = Memory.GetLinkValue(link);
71              ////                    newValue[Constants.IndexPart] = Constants.Itself;
72              ////                    newValue[Constants.SourcePart] =
                ↪ Equals(substitution[Constants.SourcePart], Constants.Itself) ?
                ↪ matchedLink[Constants.IndexPart] : substitution[Constants.SourcePart];
73              ////                    newValue[Constants.TargetPart] =
                ↪ Equals(substitution[Constants.TargetPart], Constants.Itself) ?
                ↪ matchedLink[Constants.IndexPart] : substitution[Constants.TargetPart];
74              ////                    var matchDecision = matchedHandler(matchedLink, newValue);
75              ////                    if (Equals(matchDecision, Constants.Break))
76              ////                        return false;
77              ////                    if (!Equals(matchDecision, Constants.Skip))
78              ////                        transitions.Add(new Transition(matchedLink, newValue));
79              ////                    return true;
80              ////                };
81              ////                if (!Memory.Each(handler, restriction))
82              ////                    return Constants.Break;
83              ////            }
```

```
////        }
////        else
////        {
////            Func<T, bool> handler = link =>
////            {
////                var matchedLink = Memory.GetLinkValue(link);
////                var matchDecision = matchedHandler(matchedLink, matchedLink);
////                return !Equals(matchDecision, Constants.Break);
////            };
////            if (!Memory.Each(handler, restriction))
////                return Constants.Break;
////        }
////    }
////    else
////    {
////        if (substitution != null)
////        {
////            transitions = new List<IList<T>>();
////            Func<T, bool> handler = link =>
////            {
////                var matchedLink = Memory.GetLinkValue(link);
////                transitions.Add(matchedLink);
////                return true;
////            };
////            if (!Memory.Each(handler, restriction))
////                return Constants.Break;
////        }
////        else
////        {
////            return Constants.Continue;
////        }
////    }
////}
////if (substitution != null)
////{
////    // Есть причина делать замену (запись)
////    if (substitutedHandler != null)
////    {
////    }
////    else
////    {
////    }
////}
////return Constants.Continue;

//if (restriction.IsNullOrEmpty()) // Create
//{
//    substitution[Constants.IndexPart] = Memory.AllocateLink();
//    Memory.SetLinkValue(substitution);
//}
//else if (substitution.IsNullOrEmpty()) // Delete
//{
//    Memory.FreeLink(restriction[Constants.IndexPart]);
//}
//else if (restriction.EqualTo(substitution)) // Read or ("repeat" the state) // Each
//{
//    // No need to collect links to list
//    // Skip == Continue
//    // No need to check substituedHandler
//    if (!Memory.Each(link => !Equals(matchedHandler(Memory.GetLinkValue(link)),
↪  Constants.Break), restriction))
//        return Constants.Break;
//}
//else // Update
//{
//    //List<IList<T>> matchedLinks = null;
//    if (matchedHandler != null)
//    {
//        matchedLinks = new List<IList<T>>();
//        Func<T, bool> handler = link =>
//        {
//            var matchedLink = Memory.GetLinkValue(link);
//            var matchDecision = matchedHandler(matchedLink);
//            if (Equals(matchDecision, Constants.Break))
//                return false;
//            if (!Equals(matchDecision, Constants.Skip))
//                matchedLinks.Add(matchedLink);
//            return true;
```

```
161             //        };
162             //        if (!Memory.Each(handler, restriction))
163             //            return Constants.Break;
164             //    }
165             //    if (!matchedLinks.IsNullOrEmpty())
166             //    {
167             //        var totalMatchedLinks = matchedLinks.Count;
168             //        for (var i = 0; i < totalMatchedLinks; i++)
169             //        {
170             //            var matchedLink = matchedLinks[i];
171             //            if (substitutedHandler != null)
172             //            {
173             //                var newValue = new List<T>(); // TODO: Prepare value to update here
174             //                // TODO: Decide is it actually needed to use Before and After
                ↪  substitution handling.
175             //                var substitutedDecision = substitutedHandler(matchedLink,
                ↪  newValue);
176             //                if (Equals(substitutedDecision, Constants.Break))
177             //                    return Constants.Break;
178             //                if (Equals(substitutedDecision, Constants.Continue))
179             //                {
180             //                    // Actual update here
181             //                    Memory.SetLinkValue(newValue);
182             //                }
183             //                if (Equals(substitutedDecision, Constants.Skip))
184             //                {
185             //                    // Cancel the update. TODO: decide use separate Cancel
                ↪  constant or Skip is enough?
186             //                }
187             //            }
188             //        }
189             //    }
190             //}
191             return Constants.Continue;
192         }
193
194         public TLink Trigger(IList<TLink> patternOrCondition, Func<IList<TLink>, TLink>
            ↪  matchHandler, IList<TLink> substitution, Func<IList<TLink>, IList<TLink>, TLink>
            ↪  substitutionHandler)
195         {
196             if (patternOrCondition.IsNullOrEmpty() && substitution.IsNullOrEmpty())
197             {
198                 return Constants.Continue;
199             }
200             else if (patternOrCondition.EqualTo(substitution)) // Should be Each here TODO:
                ↪  Check if it is a correct condition
201             {
202                 // Or it only applies to trigger without matchHandler.
203                 throw new NotImplementedException();
204             }
205             else if (!substitution.IsNullOrEmpty()) // Creation
206             {
207                 var before = ArrayPool<TLink>.Empty;
208                 // Что должно означать False здесь? Остановиться (перестать идти) или пропустить
                    ↪  (пройти мимо) или пустить (взять)?
209                 if (matchHandler != null && _equalityComparer.Equals(matchHandler(before),
                    ↪  Constants.Break))
210                 {
211                     return Constants.Break;
212                 }
213                 var after = (IList<TLink>)substitution.ToArray();
214                 if (_equalityComparer.Equals(after[0], default))
215                 {
216                     var newLink = Links.Create();
217                     after[0] = newLink;
218                 }
219                 if (substitution.Count == 1)
220                 {
221                     after = Links.GetLink(substitution[0]);
222                 }
223                 else if (substitution.Count == 3)
224                 {
225                     //Links.Create(after);
226                 }
227                 else
228                 {
229                     throw new NotSupportedException();
230                 }
```

```
231                 if (matchHandler != null)
232                 {
233                     return substitutionHandler(before, after);
234                 }
235                 return Constants.Continue;
236             }
237             else if (!patternOrCondition.IsNullOrEmpty()) // Deletion
238             {
239                 if (patternOrCondition.Count == 1)
240                 {
241                     var linkToDelete = patternOrCondition[0];
242                     var before = Links.GetLink(linkToDelete);
243                     if (matchHandler != null && _equalityComparer.Equals(matchHandler(before),
                        ↪ Constants.Break))
244                     {
245                         return Constants.Break;
246                     }
247                     var after = ArrayPool<TLink>.Empty;
248                     Links.Update(linkToDelete, Constants.Null, Constants.Null);
249                     Links.Delete(linkToDelete);
250                     if (matchHandler != null)
251                     {
252                         return substitutionHandler(before, after);
253                     }
254                     return Constants.Continue;
255                 }
256                 else
257                 {
258                     throw new NotSupportedException();
259                 }
260             }
261             else // Replace / Update
262             {
263                 if (patternOrCondition.Count == 1) //-V3125
264                 {
265                     var linkToUpdate = patternOrCondition[0];
266                     var before = Links.GetLink(linkToUpdate);
267                     if (matchHandler != null && _equalityComparer.Equals(matchHandler(before),
                        ↪ Constants.Break))
268                     {
269                         return Constants.Break;
270                     }
271                     var after = (IList<TLink>)substitution.ToArray(); //-V3125
272                     if (_equalityComparer.Equals(after[0], default))
273                     {
274                         after[0] = linkToUpdate;
275                     }
276                     if (substitution.Count == 1)
277                     {
278                         if (!_equalityComparer.Equals(substitution[0], linkToUpdate))
279                         {
280                             after = Links.GetLink(substitution[0]);
281                             Links.Update(linkToUpdate, Constants.Null, Constants.Null);
282                             Links.Delete(linkToUpdate);
283                         }
284                     }
285                     else if (substitution.Count == 3)
286                     {
287                         //Links.Update(after);
288                     }
289                     else
290                     {
291                         throw new NotSupportedException();
292                     }
293                     if (matchHandler != null)
294                     {
295                         return substitutionHandler(before, after);
296                     }
297                     return Constants.Continue;
298                 }
299                 else
300                 {
301                     throw new NotSupportedException();
302                 }
303             }
304         }
305 
306         /// <remarks>
```

```
        /// IList[IList[IList[T]]]
        /// |      |      |      |||
        /// |      |      |      ------ ||
        /// |      |      |       link  ||
        /// |      |       ------------- |
        /// |      |          change     |
        ///  --------------------
        ///         changes
        /// </remarks>
        public IList<IList<IList<TLink>>> Trigger(IList<TLink> condition, IList<TLink>
        ↪  substitution)
        {
            var changes = new List<IList<IList<TLink>>>();
            Trigger(condition, AlwaysContinue, substitution, (before, after) =>
            {
                var change = new[] { before, after };
                changes.Add(change);
                return Constants.Continue;
            });
            return changes;
        }

        private TLink AlwaysContinue(IList<TLink> linkToMatch) => Constants.Continue;
    }
}
```

./Platform.Data.Doublets/DoubletComparer.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets
{
    /// <remarks>
    /// TODO: Может стоит попробовать ref во всех методах (IRefEqualityComparer)
    /// 2x faster with comparer
    /// </remarks>
    public class DoubletComparer<T> : IEqualityComparer<Doublet<T>>
    {
        public static readonly DoubletComparer<T> Default = new DoubletComparer<T>();

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public bool Equals(Doublet<T> x, Doublet<T> y) => x.Equals(y);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public int GetHashCode(Doublet<T> obj) => obj.GetHashCode();
    }
}
```

./Platform.Data.Doublets/Doublet.cs

```
using System;
using System.Collections.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets
{
    public struct Doublet<T> : IEquatable<Doublet<T>>
    {
        private static readonly EqualityComparer<T> _equalityComparer =
        ↪  EqualityComparer<T>.Default;

        public T Source { get; set; }
        public T Target { get; set; }

        public Doublet(T source, T target)
        {
            Source = source;
            Target = target;
        }

        public override string ToString() => $"{Source}->{Target}";

        public bool Equals(Doublet<T> other) => _equalityComparer.Equals(Source, other.Source)
        ↪  && _equalityComparer.Equals(Target, other.Target);

        public override bool Equals(object obj) => obj is Doublet<T> doublet ?
        ↪  base.Equals(doublet) : false;
```

```

        public override int GetHashCode() => (Source, Target).GetHashCode();
    }
}
```

./Platform.Data.Doublets/Hybrid.cs

```
using System;
using System.Reflection;
using System.Reflection.Emit;
using Platform.Reflection;
using Platform.Converters;
using Platform.Exceptions;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets
{
    public struct Hybrid<T>
    {
        private static readonly Func<object, T> _absAndConvert;
        private static readonly Func<object, T> _absAndNegateAndConvert;

        static Hybrid()
        {
            _absAndConvert = DelegateHelpers.Compile<Func<object, T>>(emiter =>
            {
                Ensure.Always.IsUnsignedInteger<T>();
                emiter.LoadArgument(0);
                var signedVersion = NumericType<T>.SignedVersion;
                var signedVersionField =
                ↪  typeof(NumericType<T>).GetTypeInfo().GetField("SignedVersion",
                ↪  BindingFlags.Static | BindingFlags.Public);
                //emiter.LoadField(signedVersionField);
                emiter.Emit(OpCodes.Ldsfld, signedVersionField);
                var changeTypeMethod = typeof(Convert).GetTypeInfo().GetMethod("ChangeType",
                ↪  Types<object, Type>.Array);
                emiter.Call(changeTypeMethod);
                emiter.UnboxValue(signedVersion);
                var absMethod = typeof(Math).GetTypeInfo().GetMethod("Abs", new[] {
                ↪  signedVersion });
                emiter.Call(absMethod);
                var unsignedMethod = typeof(To).GetTypeInfo().GetMethod("Unsigned", new[] {
                ↪  signedVersion });
                emiter.Call(unsignedMethod);
                emiter.Return();
            });
            _absAndNegateAndConvert = DelegateHelpers.Compile<Func<object, T>>(emiter =>
            {
                Ensure.Always.IsUnsignedInteger<T>();
                emiter.LoadArgument(0);
                var signedVersion = NumericType<T>.SignedVersion;
                var signedVersionField =
                ↪  typeof(NumericType<T>).GetTypeInfo().GetField("SignedVersion",
                ↪  BindingFlags.Static | BindingFlags.Public);
                //emiter.LoadField(signedVersionField);
                emiter.Emit(OpCodes.Ldsfld, signedVersionField);
                var changeTypeMethod = typeof(Convert).GetTypeInfo().GetMethod("ChangeType",
                ↪  Types<object, Type>.Array);
                emiter.Call(changeTypeMethod);
                emiter.UnboxValue(signedVersion);
                var absMethod = typeof(Math).GetTypeInfo().GetMethod("Abs", new[] {
                ↪  signedVersion });
                emiter.Call(absMethod);
                var negateMethod = typeof(Platform.Numbers.Math).GetTypeInfo().GetMethod("Negate
                ↪  ").MakeGenericMethod(signedVersion);
                emiter.Call(negateMethod);
                var unsignedMethod = typeof(To).GetTypeInfo().GetMethod("Unsigned", new[] {
                ↪  signedVersion });
                emiter.Call(unsignedMethod);
                emiter.Return();
            });
        }

        public readonly T Value;
        public bool IsNothing => Convert.ToInt64(To.Signed(Value)) == 0;
        public bool IsInternal => Convert.ToInt64(To.Signed(Value)) > 0;
        public bool IsExternal => Convert.ToInt64(To.Signed(Value)) < 0;
        public long AbsoluteValue =>
        ↪  Platform.Numbers.Math.Abs(Convert.ToInt64(To.Signed(Value)));
```

```
62
63          public Hybrid(T value)
64          {
65              Ensure.OnDebug.IsUnsignedInteger<T>();
66              Value = value;
67          }
68
69          public Hybrid(object value) => Value = To.UnsignedAs<T>(Convert.ChangeType(value,
            ↪  NumericType<T>.SignedVersion));
70
71          public Hybrid(object value, bool isExternal)
72          {
73              //var signedType = Type<T>.SignedVersion;
74              //var signedValue = Convert.ChangeType(value, signedType);
75              //var abs = typeof(Platform.Numbers.Math).GetTypeInfo().GetMethod("Abs").MakeGeneric
                ↪  Method(signedType);
76              //var negate = typeof(Platform.Numbers.Math).GetTypeInfo().GetMethod("Negate").MakeG
                ↪  enericMethod(signedType);
77              //var absoluteValue = abs.Invoke(null, new[] { signedValue });
78              //var resultValue = isExternal ? negate.Invoke(null, new[] { absoluteValue }) :
                ↪  absoluteValue;
79              //Value = To.UnsignedAs<T>(resultValue);
80              if (isExternal)
81              {
82                  Value = _absAndNegateAndConvert(value);
83              }
84              else
85              {
86                  Value = _absAndConvert(value);
87              }
88          }
89
90          public static implicit operator Hybrid<T>(T integer) => new Hybrid<T>(integer);
91
92          public static explicit operator Hybrid<T>(ulong integer) => new Hybrid<T>(integer);
93
94          public static explicit operator Hybrid<T>(long integer) => new Hybrid<T>(integer);
95
96          public static explicit operator Hybrid<T>(uint integer) => new Hybrid<T>(integer);
97
98          public static explicit operator Hybrid<T>(int integer) => new Hybrid<T>(integer);
99
100         public static explicit operator Hybrid<T>(ushort integer) => new Hybrid<T>(integer);
101
102         public static explicit operator Hybrid<T>(short integer) => new Hybrid<T>(integer);
103
104         public static explicit operator Hybrid<T>(byte integer) => new Hybrid<T>(integer);
105
106         public static explicit operator Hybrid<T>(sbyte integer) => new Hybrid<T>(integer);
107
108         public static implicit operator T(Hybrid<T> hybrid) => hybrid.Value;
109
110         public static explicit operator ulong(Hybrid<T> hybrid) =>
            ↪  Convert.ToUInt64(hybrid.Value);
111
112         public static explicit operator long(Hybrid<T> hybrid) => hybrid.AbsoluteValue;
113
114         public static explicit operator uint(Hybrid<T> hybrid) => Convert.ToUInt32(hybrid.Value);
115
116         public static explicit operator int(Hybrid<T> hybrid) =>
            ↪  Convert.ToInt32(hybrid.AbsoluteValue);
117
118         public static explicit operator ushort(Hybrid<T> hybrid) =>
            ↪  Convert.ToUInt16(hybrid.Value);
119
120         public static explicit operator short(Hybrid<T> hybrid) =>
            ↪  Convert.ToInt16(hybrid.AbsoluteValue);
121
122         public static explicit operator byte(Hybrid<T> hybrid) => Convert.ToByte(hybrid.Value);
123
124         public static explicit operator sbyte(Hybrid<T> hybrid) =>
            ↪  Convert.ToSByte(hybrid.AbsoluteValue);
125
126         public override string ToString() => IsNothing ? default(T) == null ? "Nothing" :
            ↪  default(T).ToString() : IsExternal ? $"<{AbsoluteValue}>" : Value.ToString();
127     }
128 }
```

./Platform.Data.Doublets/ILinks.cs

```
#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

using System.Collections.Generic;

namespace Platform.Data.Doublets
{
    public interface ILinks<TLink> : ILinks<TLink, LinksConstants<TLink>>
    {
    }
}
```

./Platform.Data.Doublets/ILinksExtensions.cs

```
using System;
using System.Collections;
using System.Collections.Generic;
using System.Linq;
using System.Runtime.CompilerServices;
using Platform.Ranges;
using Platform.Collections.Arrays;
using Platform.Numbers;
using Platform.Random;
using Platform.Setters;
using Platform.Data.Exceptions;
using Platform.Data.Doublets.Decorators;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets
{
    public static class ILinksExtensions
    {
        public static void RunRandomCreations<TLink>(this ILinks<TLink> links, long
        ↪  amountOfCreations)
        {
            for (long i = 0; i < amountOfCreations; i++)
            {
                var linksAddressRange = new Range<ulong>(0, (Integer<TLink>)links.Count());
                Integer<TLink> source = RandomHelpers.Default.NextUInt64(linksAddressRange);
                Integer<TLink> target = RandomHelpers.Default.NextUInt64(linksAddressRange);
                links.CreateAndUpdate(source, target);
            }
        }

        public static void RunRandomSearches<TLink>(this ILinks<TLink> links, long
        ↪  amountOfSearches)
        {
            for (long i = 0; i < amountOfSearches; i++)
            {
                var linkAddressRange = new Range<ulong>(1, (Integer<TLink>)links.Count());
                Integer<TLink> source = RandomHelpers.Default.NextUInt64(linkAddressRange);
                Integer<TLink> target = RandomHelpers.Default.NextUInt64(linkAddressRange);
                links.SearchOrDefault(source, target);
            }
        }

        public static void RunRandomDeletions<TLink>(this ILinks<TLink> links, long
        ↪  amountOfDeletions)
        {
            var min = (ulong)amountOfDeletions > (Integer<TLink>)links.Count() ? 1 :
            ↪  (Integer<TLink>)links.Count() - (ulong)amountOfDeletions;
            for (long i = 0; i < amountOfDeletions; i++)
            {
                var linksAddressRange = new Range<ulong>(min, (Integer<TLink>)links.Count());
                Integer<TLink> link = RandomHelpers.Default.NextUInt64(linksAddressRange);
                links.Delete(link);
                if ((Integer<TLink>)links.Count() < min)
                {
                    break;
                }
            }
        }

        public static void Delete<TLink>(this ILinks<TLink> links, TLink linkToDelete) =>
        ↪  links.Delete(new LinkAddress<TLink>(linkToDelete));

        /// <remarks>
        /// TODO: Возможно есть очень простой способ это сделать.
        /// (Например просто удалить файл, или изменить его размер таким образом,
```

```
62          /// чтобы удалился весь контент)
63          /// Например через _header->AllocatedLinks в ResizableDirectMemoryLinks
64          /// </remarks>
65          public static void DeleteAll<TLink>(this ILinks<TLink> links)
66          {
67              var equalityComparer = EqualityComparer<TLink>.Default;
68              var comparer = Comparer<TLink>.Default;
69              for (var i = links.Count(); comparer.Compare(i, default) > 0; i =
                ↪ Arithmetic.Decrement(i))
70              {
71                  links.Delete(i);
72                  if (!equalityComparer.Equals(links.Count(), Arithmetic.Decrement(i)))
73                  {
74                      i = links.Count();
75                  }
76              }
77          }
78
79          public static TLink First<TLink>(this ILinks<TLink> links)
80          {
81              TLink firstLink = default;
82              var equalityComparer = EqualityComparer<TLink>.Default;
83              if (equalityComparer.Equals(links.Count(), default))
84              {
85                  throw new InvalidOperationException("В хранилище нет связей.");
86              }
87              links.Each(links.Constants.Any, links.Constants.Any, link =>
88              {
89                  firstLink = link[links.Constants.IndexPart];
90                  return links.Constants.Break;
91              });
92              if (equalityComparer.Equals(firstLink, default))
93              {
94                  throw new InvalidOperationException("В процессе поиска по хранилищу не было
                    ↪ найдено связей.");
95              }
96              return firstLink;
97          }
98
99          #region Paths
100
101         /// <remarks>
102         /// TODO: Как так? Как то что ниже может быть корректно?
103         /// Скорее всего практически не применимо
104         /// Предполагалось, что можно было конвертировать формируемый в проходе через
            ↪ SequenceWalker
105         /// Stack в конкретный путь из Source, Target до связи, но это не всегда так.
106         /// TODO: Возможно нужен метод, который именно выбрасывает исключения (EnsurePathExists)
107         /// </remarks>
108         public static bool CheckPathExistance<TLink>(this ILinks<TLink> links, params TLink[]
            ↪ path)
109         {
110             var current = path[0];
111             //EnsureLinkExists(current, "path");
112             if (!links.Exists(current))
113             {
114                 return false;
115             }
116             var equalityComparer = EqualityComparer<TLink>.Default;
117             var constants = links.Constants;
118             for (var i = 1; i < path.Length; i++)
119             {
120                 var next = path[i];
121                 var values = links.GetLink(current);
122                 var source = values[constants.SourcePart];
123                 var target = values[constants.TargetPart];
124                 if (equalityComparer.Equals(source, target) && equalityComparer.Equals(source,
                    ↪ next))
125                 {
126                     //throw new InvalidOperationException(string.Format("Невозможно выбрать
                        ↪ путь, так как и Source и Target совпадают с элементом пути {0}.", next));
127                     return false;
128                 }
129                 if (!equalityComparer.Equals(next, source) && !equalityComparer.Equals(next,
                    ↪ target))
130                 {
131                     //throw new InvalidOperationException(string.Format("Невозможно продолжить
                        ↪ путь через элемент пути {0}", next));
```

```
                return false;
            }
            current = next;
        }
        return true;
    }

    /// <remarks>
    /// Может потребовать дополнительного стека для PathElement's при использовании SequenceWalker.
    /// </remarks>
    public static TLink GetByKeys<TLink>(this ILinks<TLink> links, TLink root, params int[] path)
    {
        links.EnsureLinkExists(root, "root");
        var currentLink = root;
        for (var i = 0; i < path.Length; i++)
        {
            currentLink = links.GetLink(currentLink)[path[i]];
        }
        return currentLink;
    }

    public static TLink GetSquareMatrixSequenceElementByIndex<TLink>(this ILinks<TLink> links, TLink root, ulong size, ulong index)
    {
        var constants = links.Constants;
        var source = constants.SourcePart;
        var target = constants.TargetPart;
        if (!Platform.Numbers.Math.IsPowerOfTwo(size))
        {
            throw new ArgumentOutOfRangeException(nameof(size), "Sequences with sizes other than powers of two are not supported.");
        }
        var path = new BitArray(BitConverter.GetBytes(index));
        var length = Bit.GetLowestPosition(size);
        links.EnsureLinkExists(root, "root");
        var currentLink = root;
        for (var i = length - 1; i >= 0; i--)
        {
            currentLink = links.GetLink(currentLink)[path[i] ? target : source];
        }
        return currentLink;
    }

    #endregion

    /// <summary>
    /// Возвращает индекс указанной связи.
    /// </summary>
    /// <param name="links">Хранилище связей.</param>
    /// <param name="link">Связь представленная списком, состоящим из её адреса и содержимого.</param>
    /// <returns>Индекс начальной связи для указанной связи.</returns>
    [MethodImpl(MethodImplOptions.AggressiveInlining)]
    public static TLink GetIndex<TLink>(this ILinks<TLink> links, IList<TLink> link) => link[links.Constants.IndexPart];

    /// <summary>
    /// Возвращает индекс начальной (Source) связи для указанной связи.
    /// </summary>
    /// <param name="links">Хранилище связей.</param>
    /// <param name="link">Индекс связи.</param>
    /// <returns>Индекс начальной связи для указанной связи.</returns>
    [MethodImpl(MethodImplOptions.AggressiveInlining)]
    public static TLink GetSource<TLink>(this ILinks<TLink> links, TLink link) => links.GetLink(link)[links.Constants.SourcePart];

    /// <summary>
    /// Возвращает индекс начальной (Source) связи для указанной связи.
    /// </summary>
    /// <param name="links">Хранилище связей.</param>
    /// <param name="link">Связь представленная списком, состоящим из её адреса и содержимого.</param>
    /// <returns>Индекс начальной связи для указанной связи.</returns>
    [MethodImpl(MethodImplOptions.AggressiveInlining)]
    public static TLink GetSource<TLink>(this ILinks<TLink> links, IList<TLink> link) => link[links.Constants.SourcePart];
```

```
201
202         /// <summary>
203         /// Возвращает индекс конечной (Target) связи для указанной связи.
204         /// </summary>
205         /// <param name="links">Хранилище связей.</param>
206         /// <param name="link">Индекс связи.</param>
207         /// <returns>Индекс конечной связи для указанной связи.</returns>
208         [MethodImpl(MethodImplOptions.AggressiveInlining)]
209         public static TLink GetTarget<TLink>(this ILinks<TLink> links, TLink link) =>
            ↪ links.GetLink(link)[links.Constants.TargetPart];
210
211         /// <summary>
212         /// Возвращает индекс конечной (Target) связи для указанной связи.
213         /// </summary>
214         /// <param name="links">Хранилище связей.</param>
215         /// <param name="link">Связь представленная списком, состоящим из её адреса и
            ↪ содержимого.</param>
216         /// <returns>Индекс конечной связи для указанной связи.</returns>
217         [MethodImpl(MethodImplOptions.AggressiveInlining)]
218         public static TLink GetTarget<TLink>(this ILinks<TLink> links, IList<TLink> link) =>
            ↪ link[links.Constants.TargetPart];
219
220         /// <summary>
221         /// Выполняет проход по всем связям, соответствующим шаблону, вызывая обработчик
            ↪ (handler) для каждой подходящей связи.
222         /// </summary>
223         /// <param name="links">Хранилище связей.</param>
224         /// <param name="handler">Обработчик каждой подходящей связи.</param>
225         /// <param name="restrictions">Ограничения на содержимое связей. Каждое ограничение
            ↪ может иметь значения: Constants.Null - 0-я связь, обозначающая ссылку на пустоту,
            ↪ Any - отсутствие ограничения, 1..∞ конкретный адрес связи.</param>
226         /// <returns>True, в случае если проход по связям не был прерван и False в обратном
            ↪ случае.</returns>
227         [MethodImpl(MethodImplOptions.AggressiveInlining)]
228         public static bool Each<TLink>(this ILinks<TLink> links, Func<IList<TLink>, TLink>
            ↪ handler, params TLink[] restrictions)
229             => EqualityComparer<TLink>.Default.Equals(links.Each(handler, restrictions),
                ↪ links.Constants.Continue);
230
231         /// <summary>
232         /// Выполняет проход по всем связям, соответствующим шаблону, вызывая обработчик
            ↪ (handler) для каждой подходящей связи.
233         /// </summary>
234         /// <param name="links">Хранилище связей.</param>
235         /// <param name="source">Значение, определяющее соответствующие шаблону связи.
            ↪ (Constants.Null - 0-я связь, обозначающая ссылку на пустоту в качестве начала,
            ↪ Constants.Any - любое начало, 1..∞ конкретное начало)</param>
236         /// <param name="target">Значение, определяющее соответствующие шаблону связи.
            ↪ (Constants.Null - 0-я связь, обозначающая ссылку на пустоту в качестве конца,
            ↪ Constants.Any - любой конец, 1..∞ конкретный конец)</param>
237         /// <param name="handler">Обработчик каждой подходящей связи.</param>
238         /// <returns>True, в случае если проход по связям не был прерван и False в обратном
            ↪ случае.</returns>
239         [MethodImpl(MethodImplOptions.AggressiveInlining)]
240         public static bool Each<TLink>(this ILinks<TLink> links, TLink source, TLink target,
            ↪ Func<TLink, bool> handler)
241         {
242             var constants = links.Constants;
243             return links.Each(link => handler(link[constants.IndexPart]) ? constants.Continue :
                ↪ constants.Break, constants.Any, source, target);
244         }
245
246         /// <summary>
247         /// Выполняет проход по всем связям, соответствующим шаблону, вызывая обработчик
            ↪ (handler) для каждой подходящей связи.
248         /// </summary>
249         /// <param name="links">Хранилище связей.</param>
250         /// <param name="source">Значение, определяющее соответствующие шаблону связи.
            ↪ (Constants.Null - 0-я связь, обозначающая ссылку на пустоту в качестве начала,
            ↪ Constants.Any - любое начало, 1..∞ конкретное начало)</param>
251         /// <param name="target">Значение, определяющее соответствующие шаблону связи.
            ↪ (Constants.Null - 0-я связь, обозначающая ссылку на пустоту в качестве конца,
            ↪ Constants.Any - любой конец, 1..∞ конкретный конец)</param>
252         /// <param name="handler">Обработчик каждой подходящей связи.</param>
253         /// <returns>True, в случае если проход по связям не был прерван и False в обратном
            ↪ случае.</returns>
```

```
254         [MethodImpl(MethodImplOptions.AggressiveInlining)]
255         public static bool Each<TLink>(this ILinks<TLink> links, TLink source, TLink target,
            ↪  Func<IList<TLink>, TLink> handler)
256         {
257             var constants = links.Constants;
258             return links.Each(handler, constants.Any, source, target);
259         }
260
261         [MethodImpl(MethodImplOptions.AggressiveInlining)]
262         public static IList<IList<TLink>> All<TLink>(this ILinks<TLink> links, params TLink[]
            ↪  restrictions)
263         {
264             long arraySize = (Integer<TLink>)links.Count(restrictions);
265             var array = new IList<TLink>[arraySize];
266             if (arraySize > 0)
267             {
268                 var filler = new ArrayFiller<IList<TLink>, TLink>(array,
                    ↪  links.Constants.Continue);
269                 links.Each(filler.AddAndReturnConstant, restrictions);
270             }
271             return array;
272         }
273
274         [MethodImpl(MethodImplOptions.AggressiveInlining)]
275         public static IList<TLink> AllIndices<TLink>(this ILinks<TLink> links, params TLink[]
            ↪  restrictions)
276         {
277             long arraySize = (Integer<TLink>)links.Count(restrictions);
278             var array = new TLink[arraySize];
279             if (arraySize > 0)
280             {
281                 var filler = new ArrayFiller<TLink, TLink>(array, links.Constants.Continue);
282                 links.Each(filler.AddFirstAndReturnConstant, restrictions);
283             }
284             return array;
285         }
286
287         /// <summary>
288         /// Возвращает значение, определяющее существует ли связь с указанными началом и концом
            ↪  в хранилище связей.
289         /// </summary>
290         /// <param name="links">Хранилище связей.</param>
291         /// <param name="source">Начало связи.</param>
292         /// <param name="target">Конец связи.</param>
293         /// <returns>Значение, определяющее существует ли связь.</returns>
294         [MethodImpl(MethodImplOptions.AggressiveInlining)]
295         public static bool Exists<TLink>(this ILinks<TLink> links, TLink source, TLink target)
            ↪  => Comparer<TLink>.Default.Compare(links.Count(links.Constants.Any, source, target),
            ↪  default) > 0;
296
297         #region Ensure
298         // TODO: May be move to EnsureExtensions or make it both there and here
299
300         [MethodImpl(MethodImplOptions.AggressiveInlining)]
301         public static void EnsureInnerReferenceExists<TLink>(this ILinks<TLink> links, TLink
            ↪  reference, string argumentName)
302         {
303             if (links.Constants.IsInnerReference(reference) && !links.Exists(reference))
304             {
305                 throw new ArgumentLinkDoesNotExistsException<TLink>(reference, argumentName);
306             }
307         }
308
309         [MethodImpl(MethodImplOptions.AggressiveInlining)]
310         public static void EnsureInnerReferenceExists<TLink>(this ILinks<TLink> links,
            ↪  IList<TLink> restrictions, string argumentName)
311         {
312             for (int i = 0; i < restrictions.Count; i++)
313             {
314                 links.EnsureInnerReferenceExists(restrictions[i], argumentName);
315             }
316         }
317
318         [MethodImpl(MethodImplOptions.AggressiveInlining)]
319         public static void EnsureLinkIsAnyOrExists<TLink>(this ILinks<TLink> links, IList<TLink>
            ↪  restrictions)
320         {
321             for (int i = 0; i < restrictions.Count; i++)
```

```
            {
                links.EnsureLinkIsAnyOrExists(restrictions[i], nameof(restrictions));
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static void EnsureLinkIsAnyOrExists<TLink>(this ILinks<TLink> links, TLink link,
        ↪  string argumentName)
        {
            var equalityComparer = EqualityComparer<TLink>.Default;
            if (!equalityComparer.Equals(link, links.Constants.Any) && !links.Exists(link))
            {
                throw new ArgumentLinkDoesNotExistsException<TLink>(link, argumentName);
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static void EnsureLinkIsItselfOrExists<TLink>(this ILinks<TLink> links, TLink
        ↪  link, string argumentName)
        {
            var equalityComparer = EqualityComparer<TLink>.Default;
            if (!equalityComparer.Equals(link, links.Constants.Itself) && !links.Exists(link))
            {
                throw new ArgumentLinkDoesNotExistsException<TLink>(link, argumentName);
            }
        }

        /// <param name="links">Хранилище связей.</param>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static void EnsureDoesNotExists<TLink>(this ILinks<TLink> links, TLink source,
        ↪  TLink target)
        {
            if (links.Exists(source, target))
            {
                throw new LinkWithSameValueAlreadyExistsException();
            }
        }

        /// <param name="links">Хранилище связей.</param>
        public static void EnsureNoUsages<TLink>(this ILinks<TLink> links, TLink link)
        {
            if (links.HasUsages(link))
            {
                throw new ArgumentLinkHasDependenciesException<TLink>(link);
            }
        }

        /// <param name="links">Хранилище связей.</param>
        public static void EnsureCreated<TLink>(this ILinks<TLink> links, params TLink[]
        ↪  addresses) => links.EnsureCreated(links.Create, addresses);

        /// <param name="links">Хранилище связей.</param>
        public static void EnsurePointsCreated<TLink>(this ILinks<TLink> links, params TLink[]
        ↪  addresses) => links.EnsureCreated(links.CreatePoint, addresses);

        /// <param name="links">Хранилище связей.</param>
        public static void EnsureCreated<TLink>(this ILinks<TLink> links, Func<TLink> creator,
        ↪  params TLink[] addresses)
        {
            var constants = links.Constants;

            var nonExistentAddresses = new HashSet<TLink>(addresses.Where(x =>
            ↪  !links.Exists(x)));
            if (nonExistentAddresses.Count > 0)
            {
                var max = nonExistentAddresses.Max();
                max = (Integer<TLink>)System.Math.Min((ulong)(Integer<TLink>)max,
                ↪  (ulong)(Integer<TLink>)constants.PossibleInnerReferencesRange.Maximum);
                var createdLinks = new List<TLink>();
                var equalityComparer = EqualityComparer<TLink>.Default;
                TLink createdLink = creator();
                while (!equalityComparer.Equals(createdLink, max))
                {
                    createdLinks.Add(createdLink);
                }
                for (var i = 0; i < createdLinks.Count; i++)
                {
                    if (!nonExistentAddresses.Contains(createdLinks[i]))
```

```
                {
                    links.Delete(createdLinks[i]);
                }
            }
        }
    }

    #endregion

    /// <param name="links">Хранилище связей.</param>
    public static TLink CountUsages<TLink>(this ILinks<TLink> links, TLink link)
    {
        var constants = links.Constants;
        var values = links.GetLink(link);
        TLink usagesAsSource = links.Count(new Link<TLink>(constants.Any, link,
        ↪  constants.Any));
        var equalityComparer = EqualityComparer<TLink>.Default;
        if (equalityComparer.Equals(values[constants.SourcePart], link))
        {
            usagesAsSource = Arithmetic<TLink>.Decrement(usagesAsSource);
        }
        TLink usagesAsTarget = links.Count(new Link<TLink>(constants.Any, constants.Any,
        ↪  link));
        if (equalityComparer.Equals(values[constants.TargetPart], link))
        {
            usagesAsTarget = Arithmetic<TLink>.Decrement(usagesAsTarget);
        }
        return Arithmetic<TLink>.Add(usagesAsSource, usagesAsTarget);
    }

    /// <param name="links">Хранилище связей.</param>
    [MethodImpl(MethodImplOptions.AggressiveInlining)]
    public static bool HasUsages<TLink>(this ILinks<TLink> links, TLink link) =>
    ↪  Comparer<TLink>.Default.Compare(links.CountUsages(link), Integer<TLink>.Zero) > 0;

    /// <param name="links">Хранилище связей.</param>
    [MethodImpl(MethodImplOptions.AggressiveInlining)]
    public static bool Equals<TLink>(this ILinks<TLink> links, TLink link, TLink source,
    ↪  TLink target)
    {
        var constants = links.Constants;
        var values = links.GetLink(link);
        var equalityComparer = EqualityComparer<TLink>.Default;
        return equalityComparer.Equals(values[constants.SourcePart], source) &&
        ↪  equalityComparer.Equals(values[constants.TargetPart], target);
    }

    /// <summary>
    /// Выполняет поиск связи с указанными Source (началом) и Target (концом).
    /// </summary>
    /// <param name="links">Хранилище связей.</param>
    /// <param name="source">Индекс связи, которая является началом для искомой
    ↪  связи.</param>
    /// <param name="target">Индекс связи, которая является концом для искомой связи.</param>
    /// <returns>Индекс искомой связи с указанными Source (началом) и Target
    ↪  (концом).</returns>
    [MethodImpl(MethodImplOptions.AggressiveInlining)]
    public static TLink SearchOrDefault<TLink>(this ILinks<TLink> links, TLink source, TLink
    ↪  target)
    {
        var contants = links.Constants;
        var setter = new Setter<TLink, TLink>(contants.Continue, contants.Break, default);
        links.Each(setter.SetFirstAndReturnFalse, contants.Any, source, target);
        return setter.Result;
    }

    /// <param name="links">Хранилище связей.</param>
    [MethodImpl(MethodImplOptions.AggressiveInlining)]
    public static TLink Create<TLink>(this ILinks<TLink> links) => links.Create(null);

    /// <param name="links">Хранилище связей.</param>
    [MethodImpl(MethodImplOptions.AggressiveInlining)]
    public static TLink CreatePoint<TLink>(this ILinks<TLink> links)
    {
        var link = links.Create();
        return links.Update(link, link, link);
    }

```

```
462         /// <param name="links">Хранилище связей.</param>
463         [MethodImpl(MethodImplOptions.AggressiveInlining)]
464         public static TLink CreateAndUpdate<TLink>(this ILinks<TLink> links, TLink source, TLink
            ↪ target) => links.Update(links.Create(), source, target);
465
466         /// <summary>
467         /// Обновляет связь с указанными началом (Source) и концом (Target)
468         /// на связь с указанными началом (NewSource) и концом (NewTarget).
469         /// </summary>
470         /// <param name="links">Хранилище связей.</param>
471         /// <param name="link">Индекс обновляемой связи.</param>
472         /// <param name="newSource">Индекс связи, которая является началом связи, на которую
            ↪ выполняется обновление.</param>
473         /// <param name="newTarget">Индекс связи, которая является концом связи, на которую
            ↪ выполняется обновление.</param>
474         /// <returns>Индекс обновлённой связи.</returns>
475         [MethodImpl(MethodImplOptions.AggressiveInlining)]
476         public static TLink Update<TLink>(this ILinks<TLink> links, TLink link, TLink newSource,
            ↪ TLink newTarget) => links.Update(new LinkAddress<TLink>(link), new Link<TLink>(link,
            ↪ newSource, newTarget));
477
478         /// <summary>
479         /// Обновляет связь с указанными началом (Source) и концом (Target)
480         /// на связь с указанными началом (NewSource) и концом (NewTarget).
481         /// </summary>
482         /// <param name="links">Хранилище связей.</param>
483         /// <param name="restrictions">Ограничения на содержимое связей. Каждое ограничение
            ↪ может иметь значения: Constants.Null - 0-я связь, обозначающая ссылку на пустоту,
            ↪ Itself - требование установить ссылку на себя, 1..∞ конкретный адрес другой
            ↪ связи.</param>
484         /// <returns>Индекс обновлённой связи.</returns>
485         [MethodImpl(MethodImplOptions.AggressiveInlining)]
486         public static TLink Update<TLink>(this ILinks<TLink> links, params TLink[] restrictions)
487         {
488             if (restrictions.Length == 2)
489             {
490                 return links.MergeAndDelete(restrictions[0], restrictions[1]);
491             }
492             if (restrictions.Length == 4)
493             {
494                 return links.UpdateOrCreateOrGet(restrictions[0], restrictions[1],
                    ↪ restrictions[2], restrictions[3]);
495             }
496             else
497             {
498                 return links.Update(new LinkAddress<TLink>(restrictions[0]), restrictions);
499             }
500         }
501
502         [MethodImpl(MethodImplOptions.AggressiveInlining)]
503         public static IList<TLink> ResolveConstantAsSelfReference<TLink>(this ILinks<TLink>
            ↪ links, TLink constant, IList<TLink> restrictions, IList<TLink> substitution)
504         {
505             var equalityComparer = EqualityComparer<TLink>.Default;
506             var constants = links.Constants;
507             var restrictionsIndex = restrictions[constants.IndexPart];
508             var substitutionIndex = substitution[constants.IndexPart];
509             if (equalityComparer.Equals(substitutionIndex, default))
510             {
511                 substitutionIndex = restrictionsIndex;
512             }
513             var source = substitution[constants.SourcePart];
514             var target = substitution[constants.TargetPart];
515             source = equalityComparer.Equals(source, constant) ? substitutionIndex : source;
516             target = equalityComparer.Equals(target, constant) ? substitutionIndex : target;
517             return new Link<TLink>(substitutionIndex, source, target);
518         }
519
520         /// <summary>
521         /// Создаёт связь (если она не существовала), либо возвращает индекс существующей связи
            ↪ с указанными Source (началом) и Target (концом).
522         /// </summary>
523         /// <param name="links">Хранилище связей.</param>
524         /// <param name="source">Индекс связи, которая является началом на создаваемой
            ↪ связи.</param>
525         /// <param name="target">Индекс связи, которая является концом для создаваемой
            ↪ связи.</param>
```

```
526         /// <returns>Индекс связи, с указанным Source (началом) и Target (концом)</returns>
527         [MethodImpl(MethodImplOptions.AggressiveInlining)]
528         public static TLink GetOrCreate<TLink>(this ILinks<TLink> links, TLink source, TLink
            ↪ target)
529         {
530             var link = links.SearchOrDefault(source, target);
531             if (EqualityComparer<TLink>.Default.Equals(link, default))
532             {
533                 link = links.CreateAndUpdate(source, target);
534             }
535             return link;
536         }
537 
538         /// <summary>
539         /// Обновляет связь с указанными началом (Source) и концом (Target)
540         /// на связь с указанными началом (NewSource) и концом (NewTarget).
541         /// </summary>
542         /// <param name="links">Хранилище связей.</param>
543         /// <param name="source">Индекс связи, которая является началом обновляемой
            ↪ связи.</param>
544         /// <param name="target">Индекс связи, которая является концом обновляемой связи.</param>
545         /// <param name="newSource">Индекс связи, которая является началом связи, на которую
            ↪ выполняется обновление.</param>
546         /// <param name="newTarget">Индекс связи, которая является концом связи, на которую
            ↪ выполняется обновление.</param>
547         /// <returns>Индекс обновлённой связи.</returns>
548         [MethodImpl(MethodImplOptions.AggressiveInlining)]
549         public static TLink UpdateOrCreateOrGet<TLink>(this ILinks<TLink> links, TLink source,
            ↪ TLink target, TLink newSource, TLink newTarget)
550         {
551             var equalityComparer = EqualityComparer<TLink>.Default;
552             var link = links.SearchOrDefault(source, target);
553             if (equalityComparer.Equals(link, default))
554             {
555                 return links.CreateAndUpdate(newSource, newTarget);
556             }
557             if (equalityComparer.Equals(newSource, source) && equalityComparer.Equals(newTarget,
                ↪ target))
558             {
559                 return link;
560             }
561             return links.Update(link, newSource, newTarget);
562         }
563 
564         /// <summary>Удаляет связь с указанными началом (Source) и концом (Target).</summary>
565         /// <param name="links">Хранилище связей.</param>
566         /// <param name="source">Индекс связи, которая является началом удаляемой связи.</param>
567         /// <param name="target">Индекс связи, которая является концом удаляемой связи.</param>
568         [MethodImpl(MethodImplOptions.AggressiveInlining)]
569         public static TLink DeleteIfExists<TLink>(this ILinks<TLink> links, TLink source, TLink
            ↪ target)
570         {
571             var link = links.SearchOrDefault(source, target);
572             if (!EqualityComparer<TLink>.Default.Equals(link, default))
573             {
574                 links.Delete(link);
575                 return link;
576             }
577             return default;
578         }
579 
580         /// <summary>Удаляет несколько связей.</summary>
581         /// <param name="links">Хранилище связей.</param>
582         /// <param name="deletedLinks">Список адресов связей к удалению.</param>
583         [MethodImpl(MethodImplOptions.AggressiveInlining)]
584         public static void DeleteMany<TLink>(this ILinks<TLink> links, IList<TLink> deletedLinks)
585         {
586             for (int i = 0; i < deletedLinks.Count; i++)
587             {
588                 links.Delete(deletedLinks[i]);
589             }
590         }
591 
592         /// <remarks>Before execution of this method ensure that deleted link is detached (all
            ↪ values - source and target are reset to null) or it might enter into infinite
            ↪ recursion.</remarks>
593         public static void DeleteAllUsages<TLink>(this ILinks<TLink> links, TLink linkIndex)
594         {
```

```
595             var anyConstant = links.Constants.Any;
596             var usagesAsSourceQuery = new Link<TLink>(anyConstant, linkIndex, anyConstant);
597             links.DeleteByQuery(usagesAsSourceQuery);
598             var usagesAsTargetQuery = new Link<TLink>(anyConstant, linkIndex, anyConstant);
599             links.DeleteByQuery(usagesAsTargetQuery);
600         }
601
602         public static void DeleteByQuery<TLink>(this ILinks<TLink> links, Link<TLink> query)
603         {
604             var count = (Integer<TLink>)links.Count(query);
605             if (count > 0)
606             {
607                 var queryResult = new TLink[count];
608                 var queryResultFiller = new ArrayFiller<TLink, TLink>(queryResult,
                    ↪ links.Constants.Continue);
609                 links.Each(queryResultFiller.AddFirstAndReturnConstant, query);
610                 for (var i = (long)count - 1; i >= 0; i--)
611                 {
612                     links.Delete(queryResult[i]);
613                 }
614             }
615         }
616
617         // TODO: Move to Platform.Data
618         public static bool AreValuesReset<TLink>(this ILinks<TLink> links, TLink linkIndex)
619         {
620             var nullConstant = links.Constants.Null;
621             var equalityComparer = EqualityComparer<TLink>.Default;
622             var link = links.GetLink(linkIndex);
623             for (int i = 1; i < link.Count; i++)
624             {
625                 if (!equalityComparer.Equals(link[i], nullConstant))
626                 {
627                     return false;
628                 }
629             }
630             return true;
631         }
632
633         // TODO: Create a universal version of this method in Platform.Data (with using of for
            ↪ loop)
634         public static void ResetValues<TLink>(this ILinks<TLink> links, TLink linkIndex)
635         {
636             var nullConstant = links.Constants.Null;
637             var updateRequest = new Link<TLink>(linkIndex, nullConstant, nullConstant);
638             links.Update(updateRequest);
639         }
640
641         // TODO: Create a universal version of this method in Platform.Data (with using of for
            ↪ loop)
642         public static void EnforceResetValues<TLink>(this ILinks<TLink> links, TLink linkIndex)
643         {
644             if (!links.AreValuesReset(linkIndex))
645             {
646                 links.ResetValues(linkIndex);
647             }
648         }
649
650         /// <summary>
651         /// Merging two usages graphs, all children of old link moved to be children of new link
            ↪ or deleted.
652         /// </summary>
653         public static TLink MergeUsages<TLink>(this ILinks<TLink> links, TLink oldLinkIndex,
            ↪ TLink newLinkIndex)
654         {
655             var equalityComparer = EqualityComparer<TLink>.Default;
656             if (!equalityComparer.Equals(oldLinkIndex, newLinkIndex))
657             {
658                 var constants = links.Constants;
659                 var usagesAsSourceQuery = new Link<TLink>(constants.Any, oldLinkIndex,
                    ↪ constants.Any);
660                 long usagesAsSourceCount = (Integer<TLink>)links.Count(usagesAsSourceQuery);
661                 var usagesAsTargetQuery = new Link<TLink>(constants.Any, constants.Any,
                    ↪ oldLinkIndex);
662                 long usagesAsTargetCount = (Integer<TLink>)links.Count(usagesAsTargetQuery);
663                 var isStandalonePoint = Point<TLink>.IsFullPoint(links.GetLink(oldLinkIndex)) &&
                    ↪ usagesAsSourceCount == 1 && usagesAsTargetCount == 1;
664                 if (!isStandalonePoint)
```

```
                {
                    var totalUsages = usagesAsSourceCount + usagesAsTargetCount;
                    if (totalUsages > 0)
                    {
                        var usages = ArrayPool.Allocate<TLink>(totalUsages);
                        var usagesFiller = new ArrayFiller<TLink, TLink>(usages,
                        ↪  links.Constants.Continue);
                        var i = 0L;
                        if (usagesAsSourceCount > 0)
                        {
                            links.Each(usagesFiller.AddFirstAndReturnConstant,
                            ↪  usagesAsSourceQuery);
                            for (; i < usagesAsSourceCount; i++)
                            {
                                var usage = usages[i];
                                if (!equalityComparer.Equals(usage, oldLinkIndex))
                                {
                                    links.Update(usage, newLinkIndex, links.GetTarget(usage));
                                }
                            }
                        }
                        if (usagesAsTargetCount > 0)
                        {
                            links.Each(usagesFiller.AddFirstAndReturnConstant,
                            ↪  usagesAsTargetQuery);
                            for (; i < usages.Length; i++)
                            {
                                var usage = usages[i];
                                if (!equalityComparer.Equals(usage, oldLinkIndex))
                                {
                                    links.Update(usage, links.GetSource(usage), newLinkIndex);
                                }
                            }
                        }
                        ArrayPool.Free(usages);
                    }
                }
            }
            return newLinkIndex;
        }

        /// <summary>
        /// Replace one link with another (replaced link is deleted, children are updated or
        ↪  deleted).
        /// </summary>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static TLink MergeAndDelete<TLink>(this ILinks<TLink> links, TLink oldLinkIndex,
        ↪  TLink newLinkIndex)
        {
            var equalityComparer = EqualityComparer<TLink>.Default;
            if (!equalityComparer.Equals(oldLinkIndex, newLinkIndex))
            {
                links.MergeUsages(oldLinkIndex, newLinkIndex);
                links.Delete(oldLinkIndex);
            }
            return newLinkIndex;
        }

        public static ILinks<TLink>
        ↪  DecorateWithAutomaticUniquenessAndUsagesResolution<TLink>(this ILinks<TLink> links)
        {
            links = new LinksCascadeUsagesResolver<TLink>(links);
            links = new NonNullContentsLinkDeletionResolver<TLink>(links);
            links = new LinksCascadeUniquenessAndUsagesResolver<TLink>(links);
            return links;
        }
    }
}
```

./Platform.Data.Doublets/Incrementers/FrequencyIncrementer.cs

```
using System.Collections.Generic;
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Incrementers
{
    public class FrequencyIncrementer<TLink> : LinksOperatorBase<TLink>, IIncrementer<TLink>
```

```
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪ EqualityComparer<TLink>.Default;

        private readonly TLink _frequencyMarker;
        private readonly TLink _unaryOne;
        private readonly IIncrementer<TLink> _unaryNumberIncrementer;

        public FrequencyIncrementer(ILinks<TLink> links, TLink frequencyMarker, TLink unaryOne,
        ↪ IIncrementer<TLink> unaryNumberIncrementer)
            : base(links)
        {
            _frequencyMarker = frequencyMarker;
            _unaryOne = unaryOne;
            _unaryNumberIncrementer = unaryNumberIncrementer;
        }

        public TLink Increment(TLink frequency)
        {
            if (_equalityComparer.Equals(frequency, default))
            {
                return Links.GetOrCreate(_unaryOne, _frequencyMarker);
            }
            var source = Links.GetSource(frequency);
            var incrementedSource = _unaryNumberIncrementer.Increment(source);
            return Links.GetOrCreate(incrementedSource, _frequencyMarker);
        }
    }
}
```

./Platform.Data.Doublets/Incrementers/UnaryNumberIncrementer.cs

```
using System.Collections.Generic;
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Incrementers
{
    public class UnaryNumberIncrementer<TLink> : LinksOperatorBase<TLink>, IIncrementer<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪ EqualityComparer<TLink>.Default;

        private readonly TLink _unaryOne;

        public UnaryNumberIncrementer(ILinks<TLink> links, TLink unaryOne) : base(links) =>
        ↪ _unaryOne = unaryOne;

        public TLink Increment(TLink unaryNumber)
        {
            if (_equalityComparer.Equals(unaryNumber, _unaryOne))
            {
                return Links.GetOrCreate(_unaryOne, _unaryOne);
            }
            var source = Links.GetSource(unaryNumber);
            var target = Links.GetTarget(unaryNumber);
            if (_equalityComparer.Equals(source, target))
            {
                return Links.GetOrCreate(unaryNumber, _unaryOne);
            }
            else
            {
                return Links.GetOrCreate(source, Increment(target));
            }
        }
    }
}
```

./Platform.Data.Doublets/ISynchronizedLinks.cs

```
#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets
{
    public interface ISynchronizedLinks<TLink> : ISynchronizedLinks<TLink, ILinks<TLink>,
    ↪ LinksConstants<TLink>>, ILinks<TLink>
    {
    }
}
```

./Platform.Data.Doublets/Link.cs

```
using Platform.Collections.Lists;
using Platform.Exceptions;
using Platform.Ranges;
using Platform.Singletons;
using System;
using System.Collections;
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets
{
    /// <summary>
    /// Структура описывающая уникальную связь.
    /// </summary>
    public struct Link<TLink> : IEquatable<Link<TLink>>, IReadOnlyList<TLink>, IList<TLink>
    {
        public static readonly Link<TLink> Null = new Link<TLink>();

        private static readonly LinksConstants<TLink> _constants = Default<LinksConstants<TLink>>.Instance;
        private static readonly EqualityComparer<TLink> _equalityComparer = EqualityComparer<TLink>.Default;

        private const int Length = 3;

        public readonly TLink Index;
        public readonly TLink Source;
        public readonly TLink Target;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public Link(params TLink[] values) => SetValues(values, out Index, out Source, out Target);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public Link(IList<TLink> values) => SetValues(values, out Index, out Source, out Target);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public Link(object other)
        {
            if (other is Link<TLink> otherLink)
            {
                SetValues(ref otherLink, out Index, out Source, out Target);
            }
            else if(other is IList<TLink> otherList)
            {
                SetValues(otherList, out Index, out Source, out Target);
            }
            else
            {
                throw new NotSupportedException();
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public Link(ref Link<TLink> other) => SetValues(ref other, out Index, out Source, out Target);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public Link(TLink index, TLink source, TLink target)
        {
            Index = index;
            Source = source;
            Target = target;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private static void SetValues(ref Link<TLink> other, out TLink index, out TLink source, out TLink target)
        {
            index = other.Index;
            source = other.Source;
            target = other.Target;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private static void SetValues(IList<TLink> values, out TLink index, out TLink source, out TLink target)
```

```
        {
            switch (values.Count)
            {
                case 3:
                    index = values[0];
                    source = values[1];
                    target = values[2];
                    break;
                case 2:
                    index = values[0];
                    source = values[1];
                    target = default;
                    break;
                case 1:
                    index = values[0];
                    source = default;
                    target = default;
                    break;
                default:
                    index = default;
                    source = default;
                    target = default;
                    break;
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override int GetHashCode() => (Index, Source, Target).GetHashCode();

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public bool IsNull() => _equalityComparer.Equals(Index, _constants.Null)
                             && _equalityComparer.Equals(Source, _constants.Null)
                             && _equalityComparer.Equals(Target, _constants.Null);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override bool Equals(object other) => other is Link<TLink> &&
        ↪  Equals((Link<TLink>)other);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public bool Equals(Link<TLink> other) => _equalityComparer.Equals(Index, other.Index)
                                              && _equalityComparer.Equals(Source, other.Source)
                                              && _equalityComparer.Equals(Target, other.Target);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static string ToString(TLink index, TLink source, TLink target) => $"({index}:
        ↪  {source}->{target})";

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static string ToString(TLink source, TLink target) => $"({source}->{target})";

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static implicit operator TLink[](Link<TLink> link) => link.ToArray();

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static implicit operator Link<TLink>(TLink[] linkArray) => new
        ↪  Link<TLink>(linkArray);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public override string ToString() => _equalityComparer.Equals(Index, _constants.Null) ?
        ↪  ToString(Source, Target) : ToString(Index, Source, Target);

        #region IList

        public int Count => Length;

        public bool IsReadOnly => true;

        public TLink this[int index]
        {
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            get
            {
                Ensure.OnDebug.ArgumentInRange(index, new Range<int>(0, Length - 1),
                ↪  nameof(index));
                if (index == _constants.IndexPart)
                {
                    return Index;
                }
                if (index == _constants.SourcePart)
                {
```

```
                    return Source;
                }
                if (index == _constants.TargetPart)
                {
                    return Target;
                }
                throw new NotSupportedException(); // Impossible path due to Ensure.ArgumentInRange
            }
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            set => throw new NotSupportedException();
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        IEnumerator IEnumerable.GetEnumerator() => GetEnumerator();

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public IEnumerator<TLink> GetEnumerator()
        {
            yield return Index;
            yield return Source;
            yield return Target;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public void Add(TLink item) => throw new NotSupportedException();

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public void Clear() => throw new NotSupportedException();

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public bool Contains(TLink item) => IndexOf(item) >= 0;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public void CopyTo(TLink[] array, int arrayIndex)
        {
            Ensure.OnDebug.ArgumentNotNull(array, nameof(array));
            Ensure.OnDebug.ArgumentInRange(arrayIndex, new Range<int>(0, array.Length - 1), nameof(arrayIndex));
            if (arrayIndex + Length > array.Length)
            {
                throw new InvalidOperationException();
            }
            array[arrayIndex++] = Index;
            array[arrayIndex++] = Source;
            array[arrayIndex] = Target;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public bool Remove(TLink item) => Throw.A.NotSupportedExceptionAndReturn<bool>();

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public int IndexOf(TLink item)
        {
            if (_equalityComparer.Equals(Index, item))
            {
                return _constants.IndexPart;
            }
            if (_equalityComparer.Equals(Source, item))
            {
                return _constants.SourcePart;
            }
            if (_equalityComparer.Equals(Target, item))
            {
                return _constants.TargetPart;
            }
            return -1;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public void Insert(int index, TLink item) => throw new NotSupportedException();

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public void RemoveAt(int index) => throw new NotSupportedException();

        #endregion
    }
}
```

./Platform.Data.Doublets/LinkExtensions.cs

```
#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets
{
    public static class LinkExtensions
    {
        public static bool IsFullPoint<TLink>(this Link<TLink> link) =>
        ↪ Point<TLink>.IsFullPoint(link);
        public static bool IsPartialPoint<TLink>(this Link<TLink> link) =>
        ↪ Point<TLink>.IsPartialPoint(link);
    }
}
```

./Platform.Data.Doublets/LinksOperatorBase.cs

```
#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets
{
    public abstract class LinksOperatorBase<TLink>
    {
        public ILinks<TLink> Links { get; }
        protected LinksOperatorBase(ILinks<TLink> links) => Links = links;
    }
}
```

./Platform.Data.Doublets/Numbers/Raw/AddressToRawNumberConverter.cs

```
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Numbers.Raw
{
    public class AddressToRawNumberConverter<TLink> : IConverter<TLink>
    {
        public TLink Convert(TLink source) => new Hybrid<TLink>(source, isExternal: true);
    }
}
```

./Platform.Data.Doublets/Numbers/Raw/RawNumberToAddressConverter.cs

```
using Platform.Interfaces;
using Platform.Numbers;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Numbers.Raw
{
    public class RawNumberToAddressConverter<TLink> : IConverter<TLink>
    {
        public TLink Convert(TLink source) => (Integer<TLink>)new
        ↪ Hybrid<TLink>(source).AbsoluteValue;
    }
}
```

./Platform.Data.Doublets/Numbers/Unary/AddressToUnaryNumberConverter.cs

```
using System.Collections.Generic;
using Platform.Interfaces;
using Platform.Reflection;
using Platform.Numbers;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Numbers.Unary
{
    public class AddressToUnaryNumberConverter<TLink> : LinksOperatorBase<TLink>,
    ↪ IConverter<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪ EqualityComparer<TLink>.Default;

        private readonly IConverter<int, TLink> _powerOf2ToUnaryNumberConverter;

        public AddressToUnaryNumberConverter(ILinks<TLink> links, IConverter<int, TLink>
        ↪ powerOf2ToUnaryNumberConverter) : base(links) => _powerOf2ToUnaryNumberConverter =
        ↪ powerOf2ToUnaryNumberConverter;

        public TLink Convert(TLink number)
        {
            var nullConstant = Links.Constants.Null;
```

```
            var one = Integer<TLink>.One;
            var target = nullConstant;
            for (int i = 0; !_equalityComparer.Equals(number, default) && i < NumericType<TLink>.BitsLength; i++)
            {
                if (_equalityComparer.Equals(Bit.And(number, one), one))
                {
                    target = _equalityComparer.Equals(target, nullConstant)
                        ? _powerOf2ToUnaryNumberConverter.Convert(i)
                        : Links.GetOrCreate(_powerOf2ToUnaryNumberConverter.Convert(i), target);
                }
                number = Bit.ShiftRight(number, 1);
            }
            return target;
        }
    }
}
```

./Platform.Data.Doublets/Numbers/Unary/LinkToItsFrequencyNumberConveter.cs

```
using System;
using System.Collections.Generic;
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Numbers.Unary
{
    public class LinkToItsFrequencyNumberConveter<TLink> : LinksOperatorBase<TLink>, IConverter<Doublet<TLink>, TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer = EqualityComparer<TLink>.Default;

        private readonly IPropertyOperator<TLink, TLink> _frequencyPropertyOperator;
        private readonly IConverter<TLink> _unaryNumberToAddressConverter;

        public LinkToItsFrequencyNumberConveter(
            ILinks<TLink> links,
            IPropertyOperator<TLink, TLink> frequencyPropertyOperator,
            IConverter<TLink> unaryNumberToAddressConverter)
            : base(links)
        {
            _frequencyPropertyOperator = frequencyPropertyOperator;
            _unaryNumberToAddressConverter = unaryNumberToAddressConverter;
        }

        public TLink Convert(Doublet<TLink> doublet)
        {
            var link = Links.SearchOrDefault(doublet.Source, doublet.Target);
            if (_equalityComparer.Equals(link, default))
            {
                throw new ArgumentException($"Link ({doublet}) not found.", nameof(doublet));
            }
            var frequency = _frequencyPropertyOperator.Get(link);
            if (_equalityComparer.Equals(frequency, default))
            {
                return default;
            }
            var frequencyNumber = Links.GetSource(frequency);
            return _unaryNumberToAddressConverter.Convert(frequencyNumber);
        }
    }
}
```

./Platform.Data.Doublets/Numbers/Unary/PowerOf2ToUnaryNumberConverter.cs

```
using System.Collections.Generic;
using Platform.Exceptions;
using Platform.Interfaces;
using Platform.Ranges;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Numbers.Unary
{
    public class PowerOf2ToUnaryNumberConverter<TLink> : LinksOperatorBase<TLink>, IConverter<int, TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer = EqualityComparer<TLink>.Default;

```

```
        private readonly TLink[] _unaryNumberPowersOf2;

        public PowerOf2ToUnaryNumberConverter(ILinks<TLink> links, TLink one) : base(links)
        {
            _unaryNumberPowersOf2 = new TLink[64];
            _unaryNumberPowersOf2[0] = one;
        }

        public TLink Convert(int power)
        {
            Ensure.Always.ArgumentInRange(power, new Range<int>(0, _unaryNumberPowersOf2.Length - 1), nameof(power));
            if (!_equalityComparer.Equals(_unaryNumberPowersOf2[power], default))
            {
                return _unaryNumberPowersOf2[power];
            }
            var previousPowerOf2 = Convert(power - 1);
            var powerOf2 = Links.GetOrCreate(previousPowerOf2, previousPowerOf2);
            _unaryNumberPowersOf2[power] = powerOf2;
            return powerOf2;
        }
    }
}
```

./Platform.Data.Doublets/Numbers/Unary/UnaryNumberToAddressAddOperationConverter.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Interfaces;
using Platform.Numbers;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Numbers.Unary
{
    public class UnaryNumberToAddressAddOperationConverter<TLink> : LinksOperatorBase<TLink>, IConverter<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer = EqualityComparer<TLink>.Default;

        private Dictionary<TLink, TLink> _unaryToUInt64;
        private readonly TLink _unaryOne;

        public UnaryNumberToAddressAddOperationConverter(ILinks<TLink> links, TLink unaryOne)
            : base(links)
        {
            _unaryOne = unaryOne;
            InitUnaryToUInt64();
        }

        private void InitUnaryToUInt64()
        {
            var one = Integer<TLink>.One;
            _unaryToUInt64 = new Dictionary<TLink, TLink>
            {
                { _unaryOne, one }
            };
            var unary = _unaryOne;
            var number = one;
            for (var i = 1; i < 64; i++)
            {
                unary = Links.GetOrCreate(unary, unary);
                number = Double(number);
                _unaryToUInt64.Add(unary, number);
            }
        }

        public TLink Convert(TLink unaryNumber)
        {
            if (_equalityComparer.Equals(unaryNumber, default))
            {
                return default;
            }
            if (_equalityComparer.Equals(unaryNumber, _unaryOne))
            {
                return Integer<TLink>.One;
            }
            var source = Links.GetSource(unaryNumber);
            var target = Links.GetTarget(unaryNumber);
            if (_equalityComparer.Equals(source, target))
```

```
            {
                return _unaryToUInt64[unaryNumber];
            }
            else
            {
                var result = _unaryToUInt64[source];
                TLink lastValue;
                while (!_unaryToUInt64.TryGetValue(target, out lastValue))
                {
                    source = Links.GetSource(target);
                    result = Arithmetic<TLink>.Add(result, _unaryToUInt64[source]);
                    target = Links.GetTarget(target);
                }
                result = Arithmetic<TLink>.Add(result, lastValue);
                return result;
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private static TLink Double(TLink number) => (Integer<TLink>)((Integer<TLink>)number *
        ↪  2UL);
    }
}
```

./Platform.Data.Doublets/Numbers/Unary/UnaryNumberToAddressOrOperationConverter.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Interfaces;
using Platform.Reflection;
using Platform.Numbers;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Numbers.Unary
{
    public class UnaryNumberToAddressOrOperationConverter<TLink> : LinksOperatorBase<TLink>,
    ↪  IConverter<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪  EqualityComparer<TLink>.Default;

        private readonly IDictionary<TLink, int> _unaryNumberPowerOf2Indicies;

        public UnaryNumberToAddressOrOperationConverter(ILinks<TLink> links, IConverter<int,
        ↪  TLink> powerOf2ToUnaryNumberConverter)
            : base(links)
        {
            _unaryNumberPowerOf2Indicies = new Dictionary<TLink, int>();
            for (int i = 0; i < NumericType<TLink>.BitsLength; i++)
            {
                _unaryNumberPowerOf2Indicies.Add(powerOf2ToUnaryNumberConverter.Convert(i), i);
            }
        }

        public TLink Convert(TLink sourceNumber)
        {
            var nullConstant = Links.Constants.Null;
            var source = sourceNumber;
            var target = nullConstant;
            if (!_equalityComparer.Equals(source, nullConstant))
            {
                while (true)
                {
                    if (_unaryNumberPowerOf2Indicies.TryGetValue(source, out int powerOf2Index))
                    {
                        SetBit(ref target, powerOf2Index);
                        break;
                    }
                    else
                    {
                        powerOf2Index = _unaryNumberPowerOf2Indicies[Links.GetSource(source)];
                        SetBit(ref target, powerOf2Index);
                        source = Links.GetTarget(source);
                    }
                }
            }
            return target;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
```

```
53          private static void SetBit(ref TLink target, int powerOf2Index) => target =
            ↪ Bit.Or(target, Bit.ShiftLeft(Integer<TLink>.One, powerOf2Index));
54      }
55  }
```

./Platform.Data.Doublets/PropertyOperators/PropertiesOperator.cs

```
1   using System.Linq;
2   using System.Collections.Generic;
3   using Platform.Interfaces;
4
5   #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
6
7   namespace Platform.Data.Doublets.PropertyOperators
8   {
9       public class PropertiesOperator<TLink> : LinksOperatorBase<TLink>,
        ↪ IPropertiesOperator<TLink, TLink, TLink>
10      {
11          private static readonly EqualityComparer<TLink> _equalityComparer =
            ↪ EqualityComparer<TLink>.Default;
12
13          public PropertiesOperator(ILinks<TLink> links) : base(links) { }
14
15          public TLink GetValue(TLink @object, TLink property)
16          {
17              var objectProperty = Links.SearchOrDefault(@object, property);
18              if (_equalityComparer.Equals(objectProperty, default))
19              {
20                  return default;
21              }
22              var valueLink = Links.All(Links.Constants.Any, objectProperty).SingleOrDefault();
23              if (valueLink == null)
24              {
25                  return default;
26              }
27              return Links.GetTarget(valueLink[Links.Constants.IndexPart]);
28          }
29
30          public void SetValue(TLink @object, TLink property, TLink value)
31          {
32              var objectProperty = Links.GetOrCreate(@object, property);
33              Links.DeleteMany(Links.AllIndices(Links.Constants.Any, objectProperty));
34              Links.GetOrCreate(objectProperty, value);
35          }
36      }
37  }
```

./Platform.Data.Doublets/PropertyOperators/PropertyOperator.cs

```
1   using System.Collections.Generic;
2   using Platform.Interfaces;
3
4   #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6   namespace Platform.Data.Doublets.PropertyOperators
7   {
8       public class PropertyOperator<TLink> : LinksOperatorBase<TLink>, IPropertyOperator<TLink,
        ↪ TLink>
9       {
10          private static readonly EqualityComparer<TLink> _equalityComparer =
            ↪ EqualityComparer<TLink>.Default;
11
12          private readonly TLink _propertyMarker;
13          private readonly TLink _propertyValueMarker;
14
15          public PropertyOperator(ILinks<TLink> links, TLink propertyMarker, TLink
            ↪ propertyValueMarker) : base(links)
16          {
17              _propertyMarker = propertyMarker;
18              _propertyValueMarker = propertyValueMarker;
19          }
20
21          public TLink Get(TLink link)
22          {
23              var property = Links.SearchOrDefault(link, _propertyMarker);
24              var container = GetContainer(property);
25              var value = GetValue(container);
26              return value;
27          }
28
29          private TLink GetContainer(TLink property)
30          {
```

```
            var valueContainer = default(TLink);
            if (_equalityComparer.Equals(property, default))
            {
                return valueContainer;
            }
            var constants = Links.Constants;
            var countinueConstant = constants.Continue;
            var breakConstant = constants.Break;
            var anyConstant = constants.Any;
            var query = new Link<TLink>(anyConstant, property, anyConstant);
            Links.Each(candidate =>
            {
                var candidateTarget = Links.GetTarget(candidate);
                var valueTarget = Links.GetTarget(candidateTarget);
                if (_equalityComparer.Equals(valueTarget, _propertyValueMarker))
                {
                    valueContainer = Links.GetIndex(candidate);
                    return breakConstant;
                }
                return countinueConstant;
            }, query);
            return valueContainer;
        }

        private TLink GetValue(TLink container) => _equalityComparer.Equals(container, default)
        ↪  ? default : Links.GetTarget(container);

        public void Set(TLink link, TLink value)
        {
            var property = Links.GetOrCreate(link, _propertyMarker);
            var container = GetContainer(property);
            if (_equalityComparer.Equals(container, default))
            {
                Links.GetOrCreate(property, value);
            }
            else
            {
                Links.Update(container, property, value);
            }
        }
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/Generic/LinksAvlBalancedTreeMethodsBase.cs

```
using System;
using System.Text;
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Numbers;
using Platform.Collections.Methods.Trees;
using static System.Runtime.CompilerServices.Unsafe;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.ResizableDirectMemory.Generic
{
    public unsafe abstract class LinksAvlBalancedTreeMethodsBase<TLink> :
    ↪  SizedAndThreadedAVLBalancedTreeMethods<TLink>, ILinksTreeMethods<TLink>
    {
        protected readonly TLink Break;
        protected readonly TLink Continue;
        protected readonly byte* Links;
        protected readonly byte* Header;

        public LinksAvlBalancedTreeMethodsBase(LinksConstants<TLink> constants, byte* links,
        ↪  byte* header)
        {
            Links = links;
            Header = header;
            Break = constants.Break;
            Continue = constants.Continue;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected abstract TLink GetTreeRoot();

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected abstract TLink GetBasePartValue(TLink link);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
```

```
35          protected abstract bool FirstIsToTheRightOfSecond(TLink source, TLink target, TLink
            ↪  rootSource, TLink rootTarget);
36
37          [MethodImpl(MethodImplOptions.AggressiveInlining)]
38          protected abstract bool FirstIsToTheLeftOfSecond(TLink source, TLink target, TLink
            ↪  rootSource, TLink rootTarget);
39
40          [MethodImpl(MethodImplOptions.AggressiveInlining)]
41          protected virtual ref LinksHeader<TLink> GetHeaderReference() => ref
            ↪  AsRef<LinksHeader<TLink>>(Header);
42
43          [MethodImpl(MethodImplOptions.AggressiveInlining)]
44          protected virtual ref RawLink<TLink> GetLinkReference(TLink link) => ref
            ↪  AsRef<RawLink<TLink>>(Links + RawLink<TLink>.SizeInBytes * (Integer<TLink>)link);
45
46          [MethodImpl(MethodImplOptions.AggressiveInlining)]
47          protected virtual IList<TLink> GetLinkValues(TLink linkIndex)
48          {
49              ref var link = ref GetLinkReference(linkIndex);
50              return new Link<TLink>(linkIndex, link.Source, link.Target);
51          }
52
53          [MethodImpl(MethodImplOptions.AggressiveInlining)]
54          protected override bool FirstIsToTheLeftOfSecond(TLink first, TLink second)
55          {
56              ref var firstLink = ref GetLinkReference(first);
57              ref var secondLink = ref GetLinkReference(second);
58              return FirstIsToTheLeftOfSecond(firstLink.Source, firstLink.Target,
                ↪  secondLink.Source, secondLink.Target);
59          }
60
61          [MethodImpl(MethodImplOptions.AggressiveInlining)]
62          protected override bool FirstIsToTheRightOfSecond(TLink first, TLink second)
63          {
64              ref var firstLink = ref GetLinkReference(first);
65              ref var secondLink = ref GetLinkReference(second);
66              return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
                ↪  secondLink.Source, secondLink.Target);
67          }
68
69          [MethodImpl(MethodImplOptions.AggressiveInlining)]
70          protected virtual TLink GetSizeValue(TLink value) => Bit<TLink>.PartialRead(value, 5,
            ↪  -5);
71
72          [MethodImpl(MethodImplOptions.AggressiveInlining)]
73          protected virtual void SetSizeValue(ref TLink storedValue, TLink size) => storedValue =
            ↪  Bit<TLink>.PartialWrite(storedValue, size, 5, -5);
74
75          [MethodImpl(MethodImplOptions.AggressiveInlining)]
76          protected virtual bool GetLeftIsChildValue(TLink value)
77          {
78              unchecked
79              {
80                  //return (Integer<TLink>)Bit<TLink>.PartialRead(previousValue, 4, 1);
81                  return !EqualityComparer.Equals(Bit<TLink>.PartialRead(value, 4, 1), default);
82              }
83          }
84
85          [MethodImpl(MethodImplOptions.AggressiveInlining)]
86          protected virtual void SetLeftIsChildValue(ref TLink storedValue, bool value)
87          {
88              unchecked
89              {
90                  var previousValue = storedValue;
91                  var modified = Bit<TLink>.PartialWrite(previousValue, (Integer<TLink>)value, 4,
                    ↪  1);
92                  storedValue = modified;
93              }
94          }
95
96          [MethodImpl(MethodImplOptions.AggressiveInlining)]
97          protected virtual bool GetRightIsChildValue(TLink value)
98          {
99              unchecked
100             {
101                 //return (Integer<TLink>)Bit<TLink>.PartialRead(previousValue, 3, 1);
102                 return !EqualityComparer.Equals(Bit<TLink>.PartialRead(value, 3, 1), default);
103             }
```

```
104         }
105
106         [MethodImpl(MethodImplOptions.AggressiveInlining)]
107         protected virtual void SetRightIsChildValue(ref TLink storedValue, bool value)
108         {
109             unchecked
110             {
111                 var previousValue = storedValue;
112                 var modified = Bit<TLink>.PartialWrite(previousValue, (Integer<TLink>)value, 3,
                        ↪  1);
113                 storedValue = modified;
114             }
115         }
116
117         [MethodImpl(MethodImplOptions.AggressiveInlining)]
118         protected virtual sbyte GetBalanceValue(TLink storedValue)
119         {
120             unchecked
121             {
122                 var value = (int)(Integer<TLink>)Bit<TLink>.PartialRead(storedValue, 0, 3);
123                 value |= 0xF8 * ((value & 4) >> 2); // if negative, then continue ones to the
                        ↪  end of sbyte
124                 return (sbyte)value;
125             }
126         }
127
128         [MethodImpl(MethodImplOptions.AggressiveInlining)]
129         protected virtual void SetBalanceValue(ref TLink storedValue, sbyte value)
130         {
131             unchecked
132             {
133                 var packagedValue = (TLink)(Integer<TLink>)((byte)value >> 5 & 4 | value & 3);
134                 var modified = Bit<TLink>.PartialWrite(storedValue, packagedValue, 0, 3);
135                 storedValue = modified;
136             }
137         }
138
139         public TLink this[TLink index]
140         {
141             get
142             {
143                 var root = GetTreeRoot();
144                 if (GreaterOrEqualThan(index, GetSize(root)))
145                 {
146                     return Zero;
147                 }
148                 while (!EqualToZero(root))
149                 {
150                     var left = GetLeftOrDefault(root);
151                     var leftSize = GetSizeOrZero(left);
152                     if (LessThan(index, leftSize))
153                     {
154                         root = left;
155                         continue;
156                     }
157                     if (IsEquals(index, leftSize))
158                     {
159                         return root;
160                     }
161                     root = GetRightOrDefault(root);
162                     index = Subtract(index, Increment(leftSize));
163                 }
164                 return Zero; // TODO: Impossible situation exception (only if tree structure
                        ↪  broken)
165             }
166         }
167
168         /// <summary>
169         /// Выполняет поиск и возвращает индекс связи с указанными Source (началом) и Target
                ↪  (концом).
170         /// </summary>
171         /// <param name="source">Индекс связи, которая является началом на искомой связи.</param>
172         /// <param name="target">Индекс связи, которая является концом на искомой связи.</param>
173         /// <returns>Индекс искомой связи.</returns>
174         public TLink Search(TLink source, TLink target)
175         {
176             var root = GetTreeRoot();
177             while (!EqualToZero(root))
178             {
```

```
                ref var rootLink = ref GetLinkReference(root);
                var rootSource = rootLink.Source;
                var rootTarget = rootLink.Target;
                if (FirstIsToTheLeftOfSecond(source, target, rootSource, rootTarget)) //
                ↪  node.Key < root.Key
                {
                    root = GetLeftOrDefault(root);
                }
                else if (FirstIsToTheRightOfSecond(source, target, rootSource, rootTarget)) //
                ↪  node.Key > root.Key
                {
                    root = GetRightOrDefault(root);
                }
                else // node.Key == root.Key
                {
                    return root;
                }
            }
            return Zero;
        }

        // TODO: Return indices range instead of references count
        public TLink CountUsages(TLink link)
        {
            var root = GetTreeRoot();
            var total = GetSize(root);
            var totalRightIgnore = Zero;
            while (!EqualToZero(root))
            {
                var @base = GetBasePartValue(root);
                if (LessOrEqualThan(@base, link))
                {
                    root = GetRightOrDefault(root);
                }
                else
                {
                    totalRightIgnore = Add(totalRightIgnore, Increment(GetRightSize(root)));
                    root = GetLeftOrDefault(root);
                }
            }
            root = GetTreeRoot();
            var totalLeftIgnore = Zero;
            while (!EqualToZero(root))
            {
                var @base = GetBasePartValue(root);
                if (GreaterOrEqualThan(@base, link))
                {
                    root = GetLeftOrDefault(root);
                }
                else
                {
                    totalLeftIgnore = Add(totalLeftIgnore, Increment(GetLeftSize(root)));

                    root = GetRightOrDefault(root);
                }
            }
            return Subtract(Subtract(total, totalRightIgnore), totalLeftIgnore);
        }

        public TLink EachUsage(TLink link, Func<IList<TLink>, TLink> handler)
        {
            var root = GetTreeRoot();
            if (EqualToZero(root))
            {
                return Continue;
            }
            TLink first = Zero, current = root;
            while (!EqualToZero(current))
            {
                var @base = GetBasePartValue(current);
                if (GreaterOrEqualThan(@base, link))
                {
                    if (IsEquals(@base, link))
                    {
                        first = current;
                    }
                    current = GetLeftOrDefault(current);
                }
                else
```

```
                {
                    current = GetRightOrDefault(current);
                }
            }
            if (!EqualToZero(first))
            {
                current = first;
                while (true)
                {
                    if (IsEquals(handler(GetLinkValues(current)), Break))
                    {
                        return Break;
                    }
                    current = GetNext(current);
                    if (EqualToZero(current) || !IsEquals(GetBasePartValue(current), link))
                    {
                        break;
                    }
                }
            }
            return Continue;
        }

        protected override void PrintNodeValue(TLink node, StringBuilder sb)
        {
            ref var link = ref GetLinkReference(node);
            sb.Append(' ');
            sb.Append(link.Source);
            sb.Append('-');
            sb.Append('>');
            sb.Append(link.Target);
        }
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/Generic/LinksSizeBalancedTreeMethodsBase.cs

```
using System;
using System.Text;
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Numbers;
using Platform.Collections.Methods.Trees;
using static System.Runtime.CompilerServices.Unsafe;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.ResizableDirectMemory.Generic
{
    public unsafe abstract class LinksSizeBalancedTreeMethodsBase<TLink> : SizeBalancedTreeMethods2<TLink>, ILinksTreeMethods<TLink>
    {
        protected readonly TLink Break;
        protected readonly TLink Continue;
        protected readonly byte* Links;
        protected readonly byte* Header;

        public LinksSizeBalancedTreeMethodsBase(LinksConstants<TLink> constants, byte* links, byte* header)
        {
            Links = links;
            Header = header;
            Break = constants.Break;
            Continue = constants.Continue;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected abstract TLink GetTreeRoot();

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected abstract TLink GetBasePartValue(TLink link);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected abstract bool FirstIsToTheRightOfSecond(TLink source, TLink target, TLink rootSource, TLink rootTarget);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected abstract bool FirstIsToTheLeftOfSecond(TLink source, TLink target, TLink rootSource, TLink rootTarget);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
```

```
41          protected virtual ref LinksHeader<TLink> GetHeaderReference() => ref
            ↪ AsRef<LinksHeader<TLink>>(Header);
42
43          [MethodImpl(MethodImplOptions.AggressiveInlining)]
44          protected virtual ref RawLink<TLink> GetLinkReference(TLink link) => ref
            ↪ AsRef<RawLink<TLink>>(Links + RawLink<TLink>.SizeInBytes * (Integer<TLink>)link);
45
46          [MethodImpl(MethodImplOptions.AggressiveInlining)]
47          protected virtual IList<TLink> GetLinkValues(TLink linkIndex)
48          {
49              ref var link = ref GetLinkReference(linkIndex);
50              return new Link<TLink>(linkIndex, link.Source, link.Target);
51          }
52
53          [MethodImpl(MethodImplOptions.AggressiveInlining)]
54          protected override bool FirstIsToTheLeftOfSecond(TLink first, TLink second)
55          {
56              ref var firstLink = ref GetLinkReference(first);
57              ref var secondLink = ref GetLinkReference(second);
58              return FirstIsToTheLeftOfSecond(firstLink.Source, firstLink.Target,
                ↪ secondLink.Source, secondLink.Target);
59          }
60
61          [MethodImpl(MethodImplOptions.AggressiveInlining)]
62          protected override bool FirstIsToTheRightOfSecond(TLink first, TLink second)
63          {
64              ref var firstLink = ref GetLinkReference(first);
65              ref var secondLink = ref GetLinkReference(second);
66              return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
                ↪ secondLink.Source, secondLink.Target);
67          }
68
69          public TLink this[TLink index]
70          {
71              get
72              {
73                  var root = GetTreeRoot();
74                  if (GreaterOrEqualThan(index, GetSize(root)))
75                  {
76                      return Zero;
77                  }
78                  while (!EqualToZero(root))
79                  {
80                      var left = GetLeftOrDefault(root);
81                      var leftSize = GetSizeOrZero(left);
82                      if (LessThan(index, leftSize))
83                      {
84                          root = left;
85                          continue;
86                      }
87                      if (IsEquals(index, leftSize))
88                      {
89                          return root;
90                      }
91                      root = GetRightOrDefault(root);
92                      index = Subtract(index, Increment(leftSize));
93                  }
94                  return Zero; // TODO: Impossible situation exception (only if tree structure
                    ↪ broken)
95              }
96          }
97
98          /// <summary>
99          /// Выполняет поиск и возвращает индекс связи с указанными Source (началом) и Target
            ↪ (концом).
100         /// </summary>
101         /// <param name="source">Индекс связи, которая является началом на искомой связи.</param>
102         /// <param name="target">Индекс связи, которая является концом на искомой связи.</param>
103         /// <returns>Индекс искомой связи.</returns>
104         public TLink Search(TLink source, TLink target)
105         {
106             var root = GetTreeRoot();
107             while (!EqualToZero(root))
108             {
109                 ref var rootLink = ref GetLinkReference(root);
110                 var rootSource = rootLink.Source;
111                 var rootTarget = rootLink.Target;
```

```
                if (FirstIsToTheLeftOfSecond(source, target, rootSource, rootTarget)) //
                ↪  node.Key < root.Key
                {
                    root = GetLeftOrDefault(root);
                }
                else if (FirstIsToTheRightOfSecond(source, target, rootSource, rootTarget)) //
                ↪  node.Key > root.Key
                {
                    root = GetRightOrDefault(root);
                }
                else // node.Key == root.Key
                {
                    return root;
                }
            }
            return Zero;
        }

        // TODO: Return indices range instead of references count
        public TLink CountUsages(TLink link)
        {
            var root = GetTreeRoot();
            var total = GetSize(root);
            var totalRightIgnore = Zero;
            while (!EqualToZero(root))
            {
                var @base = GetBasePartValue(root);
                if (LessOrEqualThan(@base, link))
                {
                    root = GetRightOrDefault(root);
                }
                else
                {
                    totalRightIgnore = Add(totalRightIgnore, Increment(GetRightSize(root)));
                    root = GetLeftOrDefault(root);
                }
            }
            root = GetTreeRoot();
            var totalLeftIgnore = Zero;
            while (!EqualToZero(root))
            {
                var @base = GetBasePartValue(root);
                if (GreaterOrEqualThan(@base, link))
                {
                    root = GetLeftOrDefault(root);
                }
                else
                {
                    totalLeftIgnore = Add(totalLeftIgnore, Increment(GetLeftSize(root)));

                    root = GetRightOrDefault(root);
                }
            }
            return Subtract(Subtract(total, totalRightIgnore), totalLeftIgnore);
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public TLink EachUsage(TLink @base, Func<IList<TLink>, TLink> handler) =>
        ↪  EachUsageCore(@base, GetTreeRoot(), handler);

        // TODO: 1. Move target, handler to separate object. 2. Use stack or walker 3. Use
        ↪  low-level MSIL stack.
        private TLink EachUsageCore(TLink @base, TLink link, Func<IList<TLink>, TLink> handler)
        {
            var @continue = Continue;
            if (EqualToZero(link))
            {
                return @continue;
            }
            var linkBasePart = GetBasePartValue(link);
            var @break = Break;
            if (GreaterThan(linkBasePart, @base))
            {
                if (IsEquals(EachUsageCore(@base, GetLeftOrDefault(link), handler), @break))
                {
                    return @break;
                }
            }
            else if (LessThan(linkBasePart, @base))
```

```
            {
                if (IsEquals(EachUsageCore(@base, GetRightOrDefault(link), handler), @break))
                {
                    return @break;
                }
            }
            else //if (linkBasePart == @base)
            {
                if (IsEquals(handler(GetLinkValues(link)), @break))
                {
                    return @break;
                }
                if (IsEquals(EachUsageCore(@base, GetLeftOrDefault(link), handler), @break))
                {
                    return @break;
                }
                if (IsEquals(EachUsageCore(@base, GetRightOrDefault(link), handler), @break))
                {
                    return @break;
                }
            }
            return @continue;
        }

        protected override void PrintNodeValue(TLink node, StringBuilder sb)
        {
            ref var link = ref GetLinkReference(node);
            sb.Append(' ');
            sb.Append(link.Source);
            sb.Append('-');
            sb.Append('>');
            sb.Append(link.Target);
        }
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/Generic/LinksSourcesAvlBalancedTreeMethods.cs

```
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.ResizableDirectMemory.Generic
{
    public unsafe class LinksSourcesAvlBalancedTreeMethods<TLink> :
    ↪ LinksAvlBalancedTreeMethodsBase<TLink>
    {
        public LinksSourcesAvlBalancedTreeMethods(LinksConstants<TLink> constants, byte* links,
        ↪ byte* header) : base(constants, links, header) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected unsafe override ref TLink GetLeftReference(TLink node) => ref
        ↪ GetLinkReference(node).LeftAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected unsafe override ref TLink GetRightReference(TLink node) => ref
        ↪ GetLinkReference(node).RightAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetLeft(TLink node) => GetLinkReference(node).LeftAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetRight(TLink node) => GetLinkReference(node).RightAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetLeft(TLink node, TLink left) =>
        ↪ GetLinkReference(node).LeftAsSource = left;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetRight(TLink node, TLink right) =>
        ↪ GetLinkReference(node).RightAsSource = right;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetSize(TLink node) =>
        ↪ GetSizeValue(GetLinkReference(node).SizeAsSource);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetSize(TLink node, TLink size) => SetSizeValue(ref
        ↪ GetLinkReference(node).SizeAsSource, size);

```

```
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool GetLeftIsChild(TLink node) =>
        ↪ GetLeftIsChildValue(GetLinkReference(node).SizeAsSource);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetLeftIsChild(TLink node, bool value) =>
        ↪ SetLeftIsChildValue(ref GetLinkReference(node).SizeAsSource, value);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool GetRightIsChild(TLink node) =>
        ↪ GetRightIsChildValue(GetLinkReference(node).SizeAsSource);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetRightIsChild(TLink node, bool value) =>
        ↪ SetRightIsChildValue(ref GetLinkReference(node).SizeAsSource, value);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override sbyte GetBalance(TLink node) =>
        ↪ GetBalanceValue(GetLinkReference(node).SizeAsSource);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetBalance(TLink node, sbyte value) => SetBalanceValue(ref
        ↪ GetLinkReference(node).SizeAsSource, value);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetTreeRoot() => GetHeaderReference().FirstAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetBasePartValue(TLink link) => GetLinkReference(link).Source;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool FirstIsToTheLeftOfSecond(TLink firstSource, TLink firstTarget,
        ↪ TLink secondSource, TLink secondTarget) => LessThan(firstSource, secondSource) ||
        ↪ IsEquals(firstSource, secondSource) && LessThan(firstTarget, secondTarget);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool FirstIsToTheRightOfSecond(TLink firstSource, TLink firstTarget,
        ↪ TLink secondSource, TLink secondTarget) => GreaterThan(firstSource, secondSource) ||
        ↪ IsEquals(firstSource, secondSource) && GreaterThan(firstTarget, secondTarget);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void ClearNode(TLink node)
        {
            ref var link = ref GetLinkReference(node);
            link.LeftAsSource = Zero;
            link.RightAsSource = Zero;
            link.SizeAsSource = Zero;
        }
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/Generic/LinksSourcesSizeBalancedTreeMethods.cs

```
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.ResizableDirectMemory.Generic
{
    public unsafe class LinksSourcesSizeBalancedTreeMethods<TLink> :
    ↪ LinksSizeBalancedTreeMethodsBase<TLink>
    {
        public LinksSourcesSizeBalancedTreeMethods(LinksConstants<TLink> constants, byte* links,
        ↪ byte* header) : base(constants, links, header) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected unsafe override ref TLink GetLeftReference(TLink node) => ref
        ↪ GetLinkReference(node).LeftAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected unsafe override ref TLink GetRightReference(TLink node) => ref
        ↪ GetLinkReference(node).RightAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetLeft(TLink node) => GetLinkReference(node).LeftAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetRight(TLink node) => GetLinkReference(node).RightAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
```

```
24          protected override void SetLeft(TLink node, TLink left) =>
            ↪ GetLinkReference(node).LeftAsSource = left;
25
26          [MethodImpl(MethodImplOptions.AggressiveInlining)]
27          protected override void SetRight(TLink node, TLink right) =>
            ↪ GetLinkReference(node).RightAsSource = right;
28
29          [MethodImpl(MethodImplOptions.AggressiveInlining)]
30          protected override TLink GetSize(TLink node) => GetLinkReference(node).SizeAsSource;
31
32          [MethodImpl(MethodImplOptions.AggressiveInlining)]
33          protected override void SetSize(TLink node, TLink size) =>
            ↪ GetLinkReference(node).SizeAsSource = size;
34
35          [MethodImpl(MethodImplOptions.AggressiveInlining)]
36          protected override TLink GetTreeRoot() => GetHeaderReference().FirstAsSource;
37
38          [MethodImpl(MethodImplOptions.AggressiveInlining)]
39          protected override TLink GetBasePartValue(TLink link) => GetLinkReference(link).Source;
40
41          [MethodImpl(MethodImplOptions.AggressiveInlining)]
42          protected override bool FirstIsToTheLeftOfSecond(TLink firstSource, TLink firstTarget,
            ↪ TLink secondSource, TLink secondTarget) => LessThan(firstSource, secondSource) ||
            ↪ IsEquals(firstSource, secondSource) && LessThan(firstTarget, secondTarget);
43
44          [MethodImpl(MethodImplOptions.AggressiveInlining)]
45          protected override bool FirstIsToTheRightOfSecond(TLink firstSource, TLink firstTarget,
            ↪ TLink secondSource, TLink secondTarget) => GreaterThan(firstSource, secondSource) ||
            ↪ IsEquals(firstSource, secondSource) && GreaterThan(firstTarget, secondTarget);
46
47          [MethodImpl(MethodImplOptions.AggressiveInlining)]
48          protected override void ClearNode(TLink node)
49          {
50              ref var link = ref GetLinkReference(node);
51              link.LeftAsSource = Zero;
52              link.RightAsSource = Zero;
53              link.SizeAsSource = Zero;
54          }
55      }
56  }
```

./Platform.Data.Doublets/ResizableDirectMemory/Generic/LinksTargetsAvlBalancedTreeMethods.cs

```
1   using System.Runtime.CompilerServices;
2
3   #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5   namespace Platform.Data.Doublets.ResizableDirectMemory.Generic
6   {
7       public unsafe class LinksTargetsAvlBalancedTreeMethods<TLink> :
        ↪ LinksAvlBalancedTreeMethodsBase<TLink>
8       {
9           public LinksTargetsAvlBalancedTreeMethods(LinksConstants<TLink> constants, byte* links,
            ↪ byte* header) : base(constants, links, header) { }
10
11          [MethodImpl(MethodImplOptions.AggressiveInlining)]
12          protected unsafe override ref TLink GetLeftReference(TLink node) => ref
            ↪ GetLinkReference(node).LeftAsTarget;
13
14          [MethodImpl(MethodImplOptions.AggressiveInlining)]
15          protected unsafe override ref TLink GetRightReference(TLink node) => ref
            ↪ GetLinkReference(node).RightAsTarget;
16
17          [MethodImpl(MethodImplOptions.AggressiveInlining)]
18          protected override TLink GetLeft(TLink node) => GetLinkReference(node).LeftAsTarget;
19
20          [MethodImpl(MethodImplOptions.AggressiveInlining)]
21          protected override TLink GetRight(TLink node) => GetLinkReference(node).RightAsTarget;
22
23          [MethodImpl(MethodImplOptions.AggressiveInlining)]
24          protected override void SetLeft(TLink node, TLink left) =>
            ↪ GetLinkReference(node).LeftAsTarget = left;
25
26          [MethodImpl(MethodImplOptions.AggressiveInlining)]
27          protected override void SetRight(TLink node, TLink right) =>
            ↪ GetLinkReference(node).RightAsTarget = right;
28
29          [MethodImpl(MethodImplOptions.AggressiveInlining)]
30          protected override TLink GetSize(TLink node) =>
            ↪ GetSizeValue(GetLinkReference(node).SizeAsTarget);
```

```
31
32          [MethodImpl(MethodImplOptions.AggressiveInlining)]
33          protected override void SetSize(TLink node, TLink size) => SetSizeValue(ref
            ↪ GetLinkReference(node).SizeAsTarget, size);
34
35          [MethodImpl(MethodImplOptions.AggressiveInlining)]
36          protected override bool GetLeftIsChild(TLink node) =>
            ↪ GetLeftIsChildValue(GetLinkReference(node).SizeAsTarget);
37
38          [MethodImpl(MethodImplOptions.AggressiveInlining)]
39          protected override void SetLeftIsChild(TLink node, bool value) =>
            ↪ SetLeftIsChildValue(ref GetLinkReference(node).SizeAsTarget, value);
40
41          [MethodImpl(MethodImplOptions.AggressiveInlining)]
42          protected override bool GetRightIsChild(TLink node) =>
            ↪ GetRightIsChildValue(GetLinkReference(node).SizeAsTarget);
43
44          [MethodImpl(MethodImplOptions.AggressiveInlining)]
45          protected override void SetRightIsChild(TLink node, bool value) =>
            ↪ SetRightIsChildValue(ref GetLinkReference(node).SizeAsTarget, value);
46
47          [MethodImpl(MethodImplOptions.AggressiveInlining)]
48          protected override sbyte GetBalance(TLink node) =>
            ↪ GetBalanceValue(GetLinkReference(node).SizeAsTarget);
49
50          [MethodImpl(MethodImplOptions.AggressiveInlining)]
51          protected override void SetBalance(TLink node, sbyte value) => SetBalanceValue(ref
            ↪ GetLinkReference(node).SizeAsTarget, value);
52
53          [MethodImpl(MethodImplOptions.AggressiveInlining)]
54          protected override TLink GetTreeRoot() => GetHeaderReference().FirstAsTarget;
55
56          [MethodImpl(MethodImplOptions.AggressiveInlining)]
57          protected override TLink GetBasePartValue(TLink link) => GetLinkReference(link).Target;
58
59          [MethodImpl(MethodImplOptions.AggressiveInlining)]
60          protected override bool FirstIsToTheLeftOfSecond(TLink firstSource, TLink firstTarget,
            ↪ TLink secondSource, TLink secondTarget) => LessThan(firstTarget, secondTarget) ||
            ↪ IsEquals(firstTarget, secondTarget) && LessThan(firstSource, secondSource);
61
62          [MethodImpl(MethodImplOptions.AggressiveInlining)]
63          protected override bool FirstIsToTheRightOfSecond(TLink firstSource, TLink firstTarget,
            ↪ TLink secondSource, TLink secondTarget) => GreaterThan(firstTarget, secondTarget) ||
            ↪ IsEquals(firstTarget, secondTarget) && GreaterThan(firstSource, secondSource);
64
65          [MethodImpl(MethodImplOptions.AggressiveInlining)]
66          protected override void ClearNode(TLink node)
67          {
68              ref var link = ref GetLinkReference(node);
69              link.LeftAsTarget = Zero;
70              link.RightAsTarget = Zero;
71              link.SizeAsTarget = Zero;
72          }
73      }
74  }
```

./Platform.Data.Doublets/ResizableDirectMemory/Generic/LinksTargetsSizeBalancedTreeMethods.cs

```
1   using System.Runtime.CompilerServices;
2
3   #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
4
5   namespace Platform.Data.Doublets.ResizableDirectMemory.Generic
6   {
7       public unsafe class LinksTargetsSizeBalancedTreeMethods<TLink> :
        ↪ LinksSizeBalancedTreeMethodsBase<TLink>
8       {
9           public LinksTargetsSizeBalancedTreeMethods(LinksConstants<TLink> constants, byte* links,
            ↪ byte* header) : base(constants, links, header) { }
10
11          [MethodImpl(MethodImplOptions.AggressiveInlining)]
12          protected unsafe override ref TLink GetLeftReference(TLink node) => ref
            ↪ GetLinkReference(node).LeftAsTarget;
13
14          [MethodImpl(MethodImplOptions.AggressiveInlining)]
15          protected unsafe override ref TLink GetRightReference(TLink node) => ref
            ↪ GetLinkReference(node).RightAsTarget;
16
17          [MethodImpl(MethodImplOptions.AggressiveInlining)]
```

```
18          protected override TLink GetLeft(TLink node) => GetLinkReference(node).LeftAsTarget;
19
20          [MethodImpl(MethodImplOptions.AggressiveInlining)]
21          protected override TLink GetRight(TLink node) => GetLinkReference(node).RightAsTarget;
22
23          [MethodImpl(MethodImplOptions.AggressiveInlining)]
24          protected override void SetLeft(TLink node, TLink left) =>
            ↪  GetLinkReference(node).LeftAsTarget = left;
25
26          [MethodImpl(MethodImplOptions.AggressiveInlining)]
27          protected override void SetRight(TLink node, TLink right) =>
            ↪  GetLinkReference(node).RightAsTarget = right;
28
29          [MethodImpl(MethodImplOptions.AggressiveInlining)]
30          protected override TLink GetSize(TLink node) => GetLinkReference(node).SizeAsTarget;
31
32          [MethodImpl(MethodImplOptions.AggressiveInlining)]
33          protected override void SetSize(TLink node, TLink size) =>
            ↪  GetLinkReference(node).SizeAsTarget = size;
34
35          [MethodImpl(MethodImplOptions.AggressiveInlining)]
36          protected override TLink GetTreeRoot() => GetHeaderReference().FirstAsTarget;
37
38          [MethodImpl(MethodImplOptions.AggressiveInlining)]
39          protected override TLink GetBasePartValue(TLink link) => GetLinkReference(link).Target;
40
41          [MethodImpl(MethodImplOptions.AggressiveInlining)]
42          protected override bool FirstIsToTheLeftOfSecond(TLink firstSource, TLink firstTarget,
            ↪  TLink secondSource, TLink secondTarget) => LessThan(firstTarget, secondTarget) ||
            ↪  IsEquals(firstTarget, secondTarget) && LessThan(firstSource, secondSource);
43
44          [MethodImpl(MethodImplOptions.AggressiveInlining)]
45          protected override bool FirstIsToTheRightOfSecond(TLink firstSource, TLink firstTarget,
            ↪  TLink secondSource, TLink secondTarget) => GreaterThan(firstTarget, secondTarget) ||
            ↪  IsEquals(firstTarget, secondTarget) && GreaterThan(firstSource, secondSource);
46
47          [MethodImpl(MethodImplOptions.AggressiveInlining)]
48          protected override void ClearNode(TLink node)
49          {
50              ref var link = ref GetLinkReference(node);
51              link.LeftAsTarget = Zero;
52              link.RightAsTarget = Zero;
53              link.SizeAsTarget = Zero;
54          }
55      }
56  }
```

./Platform.Data.Doublets/ResizableDirectMemory/Generic/ResizableDirectMemoryLinksBase.cs

```
1   using System;
2   using System.Collections.Generic;
3   using System.Runtime.CompilerServices;
4   using Platform.Collections.Arrays;
5   using Platform.Data.Exceptions;
6   using Platform.Disposables;
7   using Platform.Memory;
8   using Platform.Numbers;
9   using Platform.Singletons;
10
11  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
12
13  namespace Platform.Data.Doublets.ResizableDirectMemory.Generic
14  {
15      public abstract class ResizableDirectMemoryLinksBase<TLink> : DisposableBase, ILinks<TLink>
16      {
17          protected static readonly EqualityComparer<TLink> EqualityComparer =
            ↪  EqualityComparer<TLink>.Default;
18          protected static readonly Comparer<TLink> Comparer = Comparer<TLink>.Default;
19
20          /// <summary>Возвращает размер одной связи в байтах.</summary>
21          /// <remarks>
22          /// Используется только во вне класса, не рекомедуется использовать внутри.
23          /// Так как во вне не обязательно будет доступен unsafe C#.
24          /// </remarks>
25          public static readonly long LinkSizeInBytes = RawLink<TLink>.SizeInBytes;
26
27          public static readonly long LinkHeaderSizeInBytes = LinksHeader<TLink>.SizeInBytes;
28
29          public static readonly long DefaultLinksSizeStep = LinkSizeInBytes * 1024 * 1024;
30
31          protected readonly IResizableDirectMemory _memory;
```

```
32          protected readonly long _memoryReservationStep;
33
34          protected ILinksTreeMethods<TLink> TargetsTreeMethods;
35          protected ILinksTreeMethods<TLink> SourcesTreeMethods;
36          // TODO: Возможно чтобы гарантированно проверять на то, является ли связь удалённой,
            ↪  нужно использовать не список а дерево, так как так можно быстрее проверить на
            ↪  наличие связи внутри
37          protected ILinksListMethods<TLink> UnusedLinksListMethods;
38
39          /// <summary>
40          /// Возвращает общее число связей находящихся в хранилище.
41          /// </summary>
42          protected virtual TLink Total
43          {
44              get
45              {
46                  ref var header = ref GetHeaderReference();
47                  return Subtract(header.AllocatedLinks, header.FreeLinks);
48              }
49          }
50
51          public virtual LinksConstants<TLink> Constants { get; }
52
53          [MethodImpl(MethodImplOptions.AggressiveInlining)]
54          public ResizableDirectMemoryLinksBase(IResizableDirectMemory memory, long
            ↪  memoryReservationStep, LinksConstants<TLink> constants)
55          {
56              _memory = memory;
57              _memoryReservationStep = memoryReservationStep;
58              Constants = constants;
59          }
60
61          [MethodImpl(MethodImplOptions.AggressiveInlining)]
62          public ResizableDirectMemoryLinksBase(IResizableDirectMemory memory, long
            ↪  memoryReservationStep) : this(memory, memoryReservationStep,
            ↪  Default<LinksConstants<TLink>>.Instance) { }
63
64          protected virtual void Init(IResizableDirectMemory memory, long memoryReservationStep)
65          {
66              if (memory.ReservedCapacity < memoryReservationStep)
67              {
68                  memory.ReservedCapacity = memoryReservationStep;
69              }
70              SetPointers(_memory);
71              ref var header = ref GetHeaderReference();
72              // Гарантия корректности _memory.UsedCapacity относительно _header->AllocatedLinks
73              _memory.UsedCapacity = ConvertToUInt64(header.AllocatedLinks) * LinkSizeInBytes +
                ↪  LinkHeaderSizeInBytes;
74              // Гарантия корректности _header->ReservedLinks относительно _memory.ReservedCapacity
75              header.ReservedLinks = ConvertToAddress((_memory.ReservedCapacity -
                ↪  LinkHeaderSizeInBytes) / LinkSizeInBytes);
76          }
77
78          [MethodImpl(MethodImplOptions.AggressiveInlining)]
79          public virtual TLink Count(IList<TLink> restrictions)
80          {
81              // Если нет ограничений, тогда возвращаем общее число связей находящихся в хранилище.
82              if (restrictions.Count == 0)
83              {
84                  return Total;
85              }
86              var constants = Constants;
87              var any = constants.Any;
88              var index = restrictions[constants.IndexPart];
89              if (restrictions.Count == 1)
90              {
91                  if (AreEqual(index, any))
92                  {
93                      return Total;
94                  }
95                  return Exists(index) ? GetOne() : GetZero();
96              }
97              if (restrictions.Count == 2)
98              {
99                  var value = restrictions[1];
100                 if (AreEqual(index, any))
101                 {
102                     if (AreEqual(value, any))
103                     {
```

```
                        return Total; // Any - как отсутствие ограничения
                    }
                    return Add(SourcesTreeMethods.CountUsages(value),
                    ↪  TargetsTreeMethods.CountUsages(value));
                }
                else
                {
                    if (!Exists(index))
                    {
                        return GetZero();
                    }
                    if (AreEqual(value, any))
                    {
                        return GetOne();
                    }
                    ref var storedLinkValue = ref GetLinkReference(index);
                    if (AreEqual(storedLinkValue.Source, value) ||
                    ↪  AreEqual(storedLinkValue.Target, value))
                    {
                        return GetOne();
                    }
                    return GetZero();
                }
            }
            if (restrictions.Count == 3)
            {
                var source = restrictions[constants.SourcePart];
                var target = restrictions[constants.TargetPart];
                if (AreEqual(index, any))
                {
                    if (AreEqual(source, any) && AreEqual(target, any))
                    {
                        return Total;
                    }
                    else if (AreEqual(source, any))
                    {
                        return TargetsTreeMethods.CountUsages(target);
                    }
                    else if (AreEqual(target, any))
                    {
                        return SourcesTreeMethods.CountUsages(source);
                    }
                    else //if(source != Any && target != Any)
                    {
                        // Эквивалент Exists(source, target) => Count(Any, source, target) > 0
                        var link = SourcesTreeMethods.Search(source, target);
                        return AreEqual(link, constants.Null) ? GetZero() : GetOne();
                    }
                }
                else
                {
                    if (!Exists(index))
                    {
                        return GetZero();
                    }
                    if (AreEqual(source, any) && AreEqual(target, any))
                    {
                        return GetOne();
                    }
                    ref var storedLinkValue = ref GetLinkReference(index);
                    if (!AreEqual(source, any) && !AreEqual(target, any))
                    {
                        if (AreEqual(storedLinkValue.Source, source) &&
                        ↪  AreEqual(storedLinkValue.Target, target))
                        {
                            return GetOne();
                        }
                        return GetZero();
                    }
                    var value = default(TLink);
                    if (AreEqual(source, any))
                    {
                        value = target;
                    }
                    if (AreEqual(target, any))
                    {
                        value = source;
                    }
```

```
                    if (AreEqual(storedLinkValue.Source, value) ||
                        AreEqual(storedLinkValue.Target, value))
                    {
                        return GetOne();
                    }
                    return GetZero();
                }
            }
            throw new NotSupportedException("Другие размеры и способы ограничений не
                поддерживаются.");
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public virtual TLink Each(Func<IList<TLink>, TLink> handler, IList<TLink> restrictions)
        {
            var constants = Constants;
            var @break = constants.Break;
            if (restrictions.Count == 0)
            {
                for (var link = GetOne(); LessOrEqualThan(link,
                    GetHeaderReference().AllocatedLinks); link = Increment(link))
                {
                    if (Exists(link) && AreEqual(handler(GetLinkStruct(link)), @break))
                    {
                        return @break;
                    }
                }
                return @break;
            }
            var @continue = constants.Continue;
            var any = constants.Any;
            var index = restrictions[constants.IndexPart];
            if (restrictions.Count == 1)
            {
                if (AreEqual(index, any))
                {
                    return Each(handler, GetEmptyList());
                }
                if (!Exists(index))
                {
                    return @continue;
                }
                return handler(GetLinkStruct(index));
            }
            if (restrictions.Count == 2)
            {
                var value = restrictions[1];
                if (AreEqual(index, any))
                {
                    if (AreEqual(value, any))
                    {
                        return Each(handler, GetEmptyList());
                    }
                    if (AreEqual(Each(handler, new Link<TLink>(index, value, any)), @break))
                    {
                        return @break;
                    }
                    return Each(handler, new Link<TLink>(index, any, value));
                }
                else
                {
                    if (!Exists(index))
                    {
                        return @continue;
                    }
                    if (AreEqual(value, any))
                    {
                        return handler(GetLinkStruct(index));
                    }
                    ref var storedLinkValue = ref GetLinkReference(index);
                    if (AreEqual(storedLinkValue.Source, value) ||
                        AreEqual(storedLinkValue.Target, value))
                    {
                        return handler(GetLinkStruct(index));
                    }
                    return @continue;
                }
            }
```

```
254             if (restrictions.Count == 3)
255             {
256                 var source = restrictions[constants.SourcePart];
257                 var target = restrictions[constants.TargetPart];
258                 if (AreEqual(index, any))
259                 {
260                     if (AreEqual(source, any) && AreEqual(target, any))
261                     {
262                         return Each(handler, GetEmptyList());
263                     }
264                     else if (AreEqual(source, any))
265                     {
266                         return TargetsTreeMethods.EachUsage(target, handler);
267                     }
268                     else if (AreEqual(target, any))
269                     {
270                         return SourcesTreeMethods.EachUsage(source, handler);
271                     }
272                     else //if(source != Any && target != Any)
273                     {
274                         var link = SourcesTreeMethods.Search(source, target);
275                         return AreEqual(link, constants.Null) ? @continue :
                             ↪ handler(GetLinkStruct(link));
276                     }
277                 }
278                 else
279                 {
280                     if (!Exists(index))
281                     {
282                         return @continue;
283                     }
284                     if (AreEqual(source, any) && AreEqual(target, any))
285                     {
286                         return handler(GetLinkStruct(index));
287                     }
288                     ref var storedLinkValue = ref GetLinkReference(index);
289                     if (!AreEqual(source, any) && !AreEqual(target, any))
290                     {
291                         if (AreEqual(storedLinkValue.Source, source) &&
292                             AreEqual(storedLinkValue.Target, target))
293                         {
294                             return handler(GetLinkStruct(index));
295                         }
296                         return @continue;
297                     }
298                     var value = default(TLink);
299                     if (AreEqual(source, any))
300                     {
301                         value = target;
302                     }
303                     if (AreEqual(target, any))
304                     {
305                         value = source;
306                     }
307                     if (AreEqual(storedLinkValue.Source, value) ||
308                         AreEqual(storedLinkValue.Target, value))
309                     {
310                         return handler(GetLinkStruct(index));
311                     }
312                     return @continue;
313                 }
314             }
315             throw new NotSupportedException("Другие размеры и способы ограничений не
                 ↪ поддерживаются.");
316         }
317 
318         /// <remarks>
319         /// TODO: Возможно можно перемещать значения, если указан индекс, но значение существует
                 ↪ в другом месте (но не в менеджере памяти, а в логике Links)
320         /// </remarks>
321         [MethodImpl(MethodImplOptions.AggressiveInlining)]
322         public virtual TLink Update(IList<TLink> restrictions, IList<TLink> substitution)
323         {
324             var constants = Constants;
325             var @null = constants.Null;
326             var linkIndex = restrictions[constants.IndexPart];
327             ref var link = ref GetLinkReference(linkIndex);
328             ref var header = ref GetHeaderReference();
```

```
329             ref var firstAsSource = ref header.FirstAsSource;
330             ref var firstAsTarget = ref header.FirstAsTarget;
331             // Будет корректно работать только в том случае, если пространство выделенной связи
                ↪  предварительно заполнено нулями
332             if (!AreEqual(link.Source, @null))
333             {
334                 SourcesTreeMethods.Detach(ref firstAsSource, linkIndex);
335             }
336             if (!AreEqual(link.Target, @null))
337             {
338                 TargetsTreeMethods.Detach(ref firstAsTarget, linkIndex);
339             }
340             link.Source = substitution[constants.SourcePart];
341             link.Target = substitution[constants.TargetPart];
342             if (!AreEqual(link.Source, @null))
343             {
344                 SourcesTreeMethods.Attach(ref firstAsSource, linkIndex);
345             }
346             if (!AreEqual(link.Target, @null))
347             {
348                 TargetsTreeMethods.Attach(ref firstAsTarget, linkIndex);
349             }
350             return linkIndex;
351         }
352
353         /// <remarks>
354         /// TODO: Возможно нужно будет заполнение нулями, если внешнее API ими не заполняет
                ↪  пространство
355         /// </remarks>
356         public virtual TLink Create(IList<TLink> restrictions)
357         {
358             ref var header = ref GetHeaderReference();
359             var freeLink = header.FirstFreeLink;
360             if (!AreEqual(freeLink, Constants.Null))
361             {
362                 UnusedLinksListMethods.Detach(freeLink);
363             }
364             else
365             {
366                 var maximumPossibleInnerReference =
                    ↪  Constants.PossibleInnerReferencesRange.Maximum;
367                 if (GreaterThan(header.AllocatedLinks, maximumPossibleInnerReference))
368                 {
369                     throw new LinksLimitReachedException<TLink>(maximumPossibleInnerReference);
370                 }
371                 if (GreaterOrEqualThan(header.AllocatedLinks, Decrement(header.ReservedLinks)))
372                 {
373                     _memory.ReservedCapacity += _memoryReservationStep;
374                     SetPointers(_memory);
375                     header.ReservedLinks = ConvertToAddress(_memory.ReservedCapacity /
                        ↪  LinkSizeInBytes);
376                 }
377                 header.AllocatedLinks = Increment(header.AllocatedLinks);
378                 _memory.UsedCapacity += LinkSizeInBytes;
379                 freeLink = header.AllocatedLinks;
380             }
381             return freeLink;
382         }
383
384         [MethodImpl(MethodImplOptions.AggressiveInlining)]
385         public virtual void Delete(IList<TLink> restrictions)
386         {
387             ref var header = ref GetHeaderReference();
388             var link = restrictions[Constants.IndexPart];
389             if (LessThan(link, header.AllocatedLinks))
390             {
391                 UnusedLinksListMethods.AttachAsFirst(link);
392             }
393             else if (AreEqual(link, header.AllocatedLinks))
394             {
395                 header.AllocatedLinks = Decrement(header.AllocatedLinks);
396                 _memory.UsedCapacity -= LinkSizeInBytes;
397                 // Убираем все связи, находящиеся в списке свободных в конце файла, до тех пор,
                    ↪  пока не дойдём до первой существующей связи
398                 // Позволяет оптимизировать количество выделенных связей (AllocatedLinks)
399                 while (GreaterThan(header.AllocatedLinks, GetZero()) &&
                    ↪  IsUnusedLink(header.AllocatedLinks))
400                 {
401                     UnusedLinksListMethods.Detach(header.AllocatedLinks);
```

```
402                 header.AllocatedLinks = Decrement(header.AllocatedLinks);
403                 _memory.UsedCapacity -= LinkSizeInBytes;
404             }
405         }
406     }
407 
408     [MethodImpl(MethodImplOptions.AggressiveInlining)]
409     public IList<TLink> GetLinkStruct(TLink linkIndex)
410     {
411         ref var link = ref GetLinkReference(linkIndex);
412         return new Link<TLink>(linkIndex, link.Source, link.Target);
413     }
414 
415     /// <remarks>
416     /// TODO: Возможно это должно быть событием, вызываемым из IMemory, в том случае, если
        ↪  адрес реально поменялся
417     ///
418     /// Указатель this.links может быть в том же месте,
419     /// так как 0-я связь не используется и имеет такой же размер как Header,
420     /// поэтому header размещается в том же месте, что и 0-я связь
421     /// </remarks>
422     [MethodImpl(MethodImplOptions.AggressiveInlining)]
423     protected abstract void SetPointers(IResizableDirectMemory memory);
424 
425     [MethodImpl(MethodImplOptions.AggressiveInlining)]
426     protected virtual void ResetPointers()
427     {
428         SourcesTreeMethods = null;
429         TargetsTreeMethods = null;
430         UnusedLinksListMethods = null;
431     }
432 
433     [MethodImpl(MethodImplOptions.AggressiveInlining)]
434     protected abstract ref LinksHeader<TLink> GetHeaderReference();
435 
436     [MethodImpl(MethodImplOptions.AggressiveInlining)]
437     protected abstract ref RawLink<TLink> GetLinkReference(TLink linkIndex);
438 
439     [MethodImpl(MethodImplOptions.AggressiveInlining)]
440     protected virtual bool Exists(TLink link)
441         => GreaterOrEqualThan(link, Constants.PossibleInnerReferencesRange.Minimum)
442         && LessOrEqualThan(link, GetHeaderReference().AllocatedLinks)
443         && !IsUnusedLink(link);
444 
445     [MethodImpl(MethodImplOptions.AggressiveInlining)]
446     protected virtual bool IsUnusedLink(TLink linkIndex)
447     {
448         if (!AreEqual(GetHeaderReference().FirstFreeLink, linkIndex)) // May be this check
            ↪  is not needed
449         {
450             ref var link = ref GetLinkReference(linkIndex);
451             return AreEqual(link.SizeAsSource, default) && !AreEqual(link.Source, default);
452         }
453         else
454         {
455             return true;
456         }
457     }
458 
459     [MethodImpl(MethodImplOptions.AggressiveInlining)]
460     protected virtual TLink GetOne() => Integer<TLink>.One;
461 
462     [MethodImpl(MethodImplOptions.AggressiveInlining)]
463     protected virtual TLink GetZero() => Integer<TLink>.Zero;
464 
465     [MethodImpl(MethodImplOptions.AggressiveInlining)]
466     protected virtual bool AreEqual(TLink first, TLink second) =>
        ↪  EqualityComparer.Equals(first, second);
467 
468     [MethodImpl(MethodImplOptions.AggressiveInlining)]
469     protected virtual bool LessThan(TLink first, TLink second) => Comparer.Compare(first,
        ↪  second) < 0;
470 
471     [MethodImpl(MethodImplOptions.AggressiveInlining)]
472     protected virtual bool LessOrEqualThan(TLink first, TLink second) =>
        ↪  Comparer.Compare(first, second) <= 0;
473 
474     [MethodImpl(MethodImplOptions.AggressiveInlining)]
```

```
475         protected virtual bool GreaterThan(TLink first, TLink second) => Comparer.Compare(first,
            ↪ second) > 0;
476
477         [MethodImpl(MethodImplOptions.AggressiveInlining)]
478         protected virtual bool GreaterOrEqualThan(TLink first, TLink second) =>
            ↪ Comparer.Compare(first, second) >= 0;
479
480         [MethodImpl(MethodImplOptions.AggressiveInlining)]
481         protected virtual long ConvertToUInt64(TLink value) => (Integer<TLink>)value;
482
483         [MethodImpl(MethodImplOptions.AggressiveInlining)]
484         protected virtual TLink ConvertToAddress(long value) => (Integer<TLink>)value;
485
486         [MethodImpl(MethodImplOptions.AggressiveInlining)]
487         protected virtual TLink Add(TLink first, TLink second) => Arithmetic<TLink>.Add(first,
            ↪ second);
488
489         [MethodImpl(MethodImplOptions.AggressiveInlining)]
490         protected virtual TLink Subtract(TLink first, TLink second) =>
            ↪ Arithmetic<TLink>.Subtract(first, second);
491
492         [MethodImpl(MethodImplOptions.AggressiveInlining)]
493         protected virtual TLink Increment(TLink link) => Arithmetic<TLink>.Increment(link);
494
495         [MethodImpl(MethodImplOptions.AggressiveInlining)]
496         protected virtual TLink Decrement(TLink link) => Arithmetic<TLink>.Decrement(link);
497
498         [MethodImpl(MethodImplOptions.AggressiveInlining)]
499         protected virtual IList<TLink> GetEmptyList() => ArrayPool<TLink>.Empty;
500
501         #region Disposable
502
503         protected override bool AllowMultipleDisposeCalls => true;
504
505         protected override void Dispose(bool manual, bool wasDisposed)
506         {
507             if (!wasDisposed)
508             {
509                 ResetPointers();
510                 _memory.DisposeIfPossible();
511             }
512         }
513
514         #endregion
515     }
516 }
```

./Platform.Data.Doublets/ResizableDirectMemory/Generic/ResizableDirectMemoryLinks.cs

```
1  using System.Runtime.CompilerServices;
2  using Platform.Numbers;
3  using Platform.Memory;
4  using static System.Runtime.CompilerServices.Unsafe;
5  using System;
6  using Platform.Singletons;
7
8  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
9
10 namespace Platform.Data.Doublets.ResizableDirectMemory.Generic
11 {
12     public unsafe partial class ResizableDirectMemoryLinks<TLink> :
       ↪ ResizableDirectMemoryLinksBase<TLink>
13     {
14         private readonly Func<ILinksTreeMethods<TLink>> _createSourceTreeMethods;
15         private readonly Func<ILinksTreeMethods<TLink>> _createTargetTreeMethods;
16         private byte* _header;
17         private byte* _links;
18
19         [MethodImpl(MethodImplOptions.AggressiveInlining)]
20         public ResizableDirectMemoryLinks(string address) : this(address, DefaultLinksSizeStep)
           ↪ { }
21
22         /// <summary>
23         /// Создаёт экземпляр базы данных Links в файле по указанному адресу, с указанным
           ↪ минимальным шагом расширения базы данных.
24         /// </summary>
25         /// <param name="address">Полный пусть к файлу базы данных.</param>
26         /// <param name="memoryReservationStep">Минимальный шаг расширения базы данных в
           ↪ байтах.</param>
27         [MethodImpl(MethodImplOptions.AggressiveInlining)]
```

```
28          public ResizableDirectMemoryLinks(string address, long memoryReservationStep) : this(new
            ↪  FileMappedResizableDirectMemory(address, memoryReservationStep),
            ↪  memoryReservationStep) { }
29
30          [MethodImpl(MethodImplOptions.AggressiveInlining)]
31          public ResizableDirectMemoryLinks(IResizableDirectMemory memory) : this(memory,
            ↪  DefaultLinksSizeStep) { }
32
33          [MethodImpl(MethodImplOptions.AggressiveInlining)]
34          public ResizableDirectMemoryLinks(IResizableDirectMemory memory, long
            ↪  memoryReservationStep) : this(memory, memoryReservationStep,
            ↪  Default<LinksConstants<TLink>>.Instance, true) { }
35
36          [MethodImpl(MethodImplOptions.AggressiveInlining)]
37          public ResizableDirectMemoryLinks(IResizableDirectMemory memory, long
            ↪  memoryReservationStep, LinksConstants<TLink> constants, bool useAvlBasedIndex) :
            ↪  base(memory, memoryReservationStep, constants)
38          {
39              if (useAvlBasedIndex)
40              {
41                  _createSourceTreeMethods = () => new
                    ↪  LinksSourcesAvlBalancedTreeMethods<TLink>(Constants, _links, _header);
42                  _createTargetTreeMethods = () => new
                    ↪  LinksTargetsAvlBalancedTreeMethods<TLink>(Constants, _links, _header);
43              }
44              else
45              {
46                  _createSourceTreeMethods = () => new
                    ↪  LinksSourcesSizeBalancedTreeMethods<TLink>(Constants, _links, _header);
47                  _createTargetTreeMethods = () => new
                    ↪  LinksTargetsSizeBalancedTreeMethods<TLink>(Constants, _links, _header);
48              }
49              Init(memory, memoryReservationStep);
50          }
51
52          [MethodImpl(MethodImplOptions.AggressiveInlining)]
53          protected override void SetPointers(IResizableDirectMemory memory)
54          {
55              _links = (byte*)memory.Pointer;
56              _header = _links;
57              SourcesTreeMethods = _createSourceTreeMethods();
58              TargetsTreeMethods = _createTargetTreeMethods();
59              UnusedLinksListMethods = new UnusedLinksListMethods<TLink>(_links, _header);
60          }
61
62          [MethodImpl(MethodImplOptions.AggressiveInlining)]
63          protected override void ResetPointers()
64          {
65              base.ResetPointers();
66              _links = null;
67              _header = null;
68          }
69
70          [MethodImpl(MethodImplOptions.AggressiveInlining)]
71          protected override ref LinksHeader<TLink> GetHeaderReference() => ref
            ↪  AsRef<LinksHeader<TLink>>(_header);
72
73          [MethodImpl(MethodImplOptions.AggressiveInlining)]
74          protected override ref RawLink<TLink> GetLinkReference(TLink linkIndex) => ref
            ↪  AsRef<RawLink<TLink>>(_links + LinkSizeInBytes * (Integer<TLink>)linkIndex);
75      }
76  }
```

./Platform.Data.Doublets/ResizableDirectMemory/Generic/UnusedLinksListMethods.cs

```
1   using System.Runtime.CompilerServices;
2   using Platform.Collections.Methods.Lists;
3   using Platform.Numbers;
4   using static System.Runtime.CompilerServices.Unsafe;
5
6   #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
7
8   namespace Platform.Data.Doublets.ResizableDirectMemory.Generic
9   {
10      public unsafe class UnusedLinksListMethods<TLink> : CircularDoublyLinkedListMethods<TLink>,
        ↪  ILinksListMethods<TLink>
11      {
12          private readonly byte* _links;
13          private readonly byte* _header;
```

```

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public UnusedLinksListMethods(byte* links, byte* header)
        {
            _links = links;
            _header = header;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected virtual ref LinksHeader<TLink> GetHeaderReference() => ref
        ↪  AsRef<LinksHeader<TLink>>(_header);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected virtual ref RawLink<TLink> GetLinkReference(TLink link) => ref
        ↪  AsRef<RawLink<TLink>>(_links + RawLink<TLink>.SizeInBytes * (Integer<TLink>)link);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetFirst() => GetHeaderReference().FirstFreeLink;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetLast() => GetHeaderReference().LastFreeLink;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetPrevious(TLink element) => GetLinkReference(element).Source;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetNext(TLink element) => GetLinkReference(element).Target;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetSize() => GetHeaderReference().FreeLinks;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetFirst(TLink element) => GetHeaderReference().FirstFreeLink =
        ↪  element;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetLast(TLink element) => GetHeaderReference().LastFreeLink =
        ↪  element;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetPrevious(TLink element, TLink previous) =>
        ↪  GetLinkReference(element).Source = previous;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetNext(TLink element, TLink next) =>
        ↪  GetLinkReference(element).Target = next;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetSize(TLink size) => GetHeaderReference().FreeLinks = size;
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/ILinksListMethods.cs

```
#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.ResizableDirectMemory
{
    public interface ILinksListMethods<TLink>
    {
        void Detach(TLink freeLink);
        void AttachAsFirst(TLink link);
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/ILinksTreeMethods.cs

```
using System;
using System.Collections.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.ResizableDirectMemory
{
    public interface ILinksTreeMethods<TLink>
    {
        TLink CountUsages(TLink link);
        TLink Search(TLink source, TLink target);
        TLink EachUsage(TLink source, Func<IList<TLink>, TLink> handler);
        void Detach(ref TLink firstAsSource, TLink linkIndex);
        void Attach(ref TLink firstAsSource, TLink linkIndex);
```

```
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/LinksHeader.cs
```
using Platform.Unsafe;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.ResizableDirectMemory
{
    public struct LinksHeader<TLink>
    {
        public static readonly long SizeInBytes = Structure<LinksHeader<TLink>>.Size;

        public TLink AllocatedLinks;
        public TLink ReservedLinks;
        public TLink FreeLinks;
        public TLink FirstFreeLink;
        public TLink FirstAsSource;
        public TLink FirstAsTarget;
        public TLink LastFreeLink;
        public TLink Reserved8;
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/RawLink.cs
```
using Platform.Unsafe;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.ResizableDirectMemory
{
    public struct RawLink<TLink>
    {
        public static readonly long SizeInBytes = Structure<RawLink<TLink>>.Size;

        public TLink Source;
        public TLink Target;
        public TLink LeftAsSource;
        public TLink RightAsSource;
        public TLink SizeAsSource;
        public TLink LeftAsTarget;
        public TLink RightAsTarget;
        public TLink SizeAsTarget;
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/Specific/UInt64LinksAvlBalancedTreeMethodsBase.cs
```
using System.Runtime.CompilerServices;
using Platform.Data.Doublets.ResizableDirectMemory.Generic;
using static System.Runtime.CompilerServices.Unsafe;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.ResizableDirectMemory.Specific
{
    public unsafe abstract class UInt64LinksAvlBalancedTreeMethodsBase :
    ↪ LinksAvlBalancedTreeMethodsBase<ulong>
    {
        protected new readonly RawLink<ulong>* Links;
        protected new readonly LinksHeader<ulong>* Header;

        public UInt64LinksAvlBalancedTreeMethodsBase(LinksConstants<ulong> constants,
        ↪ RawLink<ulong>* links, LinksHeader<ulong>* header)
            : base(constants, (byte*)links, (byte*)header)
        {
            Links = links;
            Header = header;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetZero() => 0UL;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool EqualToZero(ulong value) => value == 0UL;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool IsEquals(ulong first, ulong second) => first == second;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool GreaterThanZero(ulong value) => value > 0UL;
```

```
32
33          [MethodImpl(MethodImplOptions.AggressiveInlining)]
34          protected override bool GreaterThan(ulong first, ulong second) => first > second;
35
36          [MethodImpl(MethodImplOptions.AggressiveInlining)]
37          protected override bool GreaterOrEqualThan(ulong first, ulong second) => first >= second;
38
39          [MethodImpl(MethodImplOptions.AggressiveInlining)]
40          protected override bool GreaterOrEqualThanZero(ulong value) => true; // value >= 0 is
            ↪  always true for ulong
41
42          [MethodImpl(MethodImplOptions.AggressiveInlining)]
43          protected override bool LessOrEqualThanZero(ulong value) => value == 0UL; // value is
            ↪  always >= 0 for ulong
44
45          [MethodImpl(MethodImplOptions.AggressiveInlining)]
46          protected override bool LessOrEqualThan(ulong first, ulong second) => first <= second;
47
48          [MethodImpl(MethodImplOptions.AggressiveInlining)]
49          protected override bool LessThanZero(ulong value) => false; // value < 0 is always false
            ↪  for ulong
50
51          [MethodImpl(MethodImplOptions.AggressiveInlining)]
52          protected override bool LessThan(ulong first, ulong second) => first < second;
53
54          [MethodImpl(MethodImplOptions.AggressiveInlining)]
55          protected override ulong Increment(ulong value) => ++value;
56
57          [MethodImpl(MethodImplOptions.AggressiveInlining)]
58          protected override ulong Decrement(ulong value) => --value;
59
60          [MethodImpl(MethodImplOptions.AggressiveInlining)]
61          protected override ulong Add(ulong first, ulong second) => first + second;
62
63          [MethodImpl(MethodImplOptions.AggressiveInlining)]
64          protected override ulong Subtract(ulong first, ulong second) => first - second;
65
66          [MethodImpl(MethodImplOptions.AggressiveInlining)]
67          protected override bool FirstIsToTheLeftOfSecond(ulong first, ulong second)
68          {
69              ref var firstLink = ref Links[first];
70              ref var secondLink = ref Links[second];
71              return FirstIsToTheLeftOfSecond(firstLink.Source, firstLink.Target,
                ↪  secondLink.Source, secondLink.Target);
72          }
73
74          [MethodImpl(MethodImplOptions.AggressiveInlining)]
75          protected override bool FirstIsToTheRightOfSecond(ulong first, ulong second)
76          {
77              ref var firstLink = ref Links[first];
78              ref var secondLink = ref Links[second];
79              return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
                ↪  secondLink.Source, secondLink.Target);
80          }
81
82          [MethodImpl(MethodImplOptions.AggressiveInlining)]
83          protected override ulong GetSizeValue(ulong value) => unchecked((value & 4294967264UL)
            ↪  >> 5);
84
85          [MethodImpl(MethodImplOptions.AggressiveInlining)]
86          protected override void SetSizeValue(ref ulong storedValue, ulong size) => storedValue =
            ↪  unchecked(storedValue & 31UL | (size & 134217727UL) << 5);
87
88          [MethodImpl(MethodImplOptions.AggressiveInlining)]
89          protected override bool GetLeftIsChildValue(ulong value) => unchecked((value & 16UL) >>
            ↪  4 == 1UL);
90
91          [MethodImpl(MethodImplOptions.AggressiveInlining)]
92          protected override void SetLeftIsChildValue(ref ulong storedValue, bool value) =>
            ↪  storedValue = unchecked(storedValue & 4294967279UL | (As<bool, byte>(ref value) &
            ↪  1UL) << 4);
93
94          [MethodImpl(MethodImplOptions.AggressiveInlining)]
95          protected override bool GetRightIsChildValue(ulong value) => unchecked((value & 8UL) >>
            ↪  3 == 1UL);
96
97          [MethodImpl(MethodImplOptions.AggressiveInlining)]
```

```
98          protected override void SetRightIsChildValue(ref ulong storedValue, bool value) =>
            ↪ storedValue = unchecked(storedValue & 4294967287UL | (As<bool, byte>(ref value) &
            ↪ 1UL) << 3);
99
100         [MethodImpl(MethodImplOptions.AggressiveInlining)]
101         protected override sbyte GetBalanceValue(ulong value) => unchecked((sbyte)(value & 7UL |
            ↪ 0xF8UL * ((value & 4UL) >> 2))); // if negative, then continue ones to the end of
            ↪ sbyte
102
103         [MethodImpl(MethodImplOptions.AggressiveInlining)]
104         protected override void SetBalanceValue(ref ulong storedValue, sbyte value) =>
            ↪ storedValue = unchecked(storedValue & 4294967288UL | (ulong)((byte)value >> 5 & 4 |
            ↪ value & 3) & 7UL);
105
106         [MethodImpl(MethodImplOptions.AggressiveInlining)]
107         protected override ref LinksHeader<ulong> GetHeaderReference() => ref *Header;
108
109         [MethodImpl(MethodImplOptions.AggressiveInlining)]
110         protected override ref RawLink<ulong> GetLinkReference(ulong link) => ref Links[link];
111     }
112 }
```

./Platform.Data.Doublets/ResizableDirectMemory/Specific/UInt64LinksSizeBalancedTreeMethodsBase.cs

```
1  using System.Runtime.CompilerServices;
2  using Platform.Data.Doublets.ResizableDirectMemory.Generic;
3
4  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
5
6  namespace Platform.Data.Doublets.ResizableDirectMemory.Specific
7  {
8      public unsafe abstract class UInt64LinksSizeBalancedTreeMethodsBase :
       ↪ LinksSizeBalancedTreeMethodsBase<ulong>
9      {
10         protected new readonly RawLink<ulong>* Links;
11         protected new readonly LinksHeader<ulong>* Header;
12
13         public UInt64LinksSizeBalancedTreeMethodsBase(LinksConstants<ulong> constants,
           ↪ RawLink<ulong>* links, LinksHeader<ulong>* header)
14             : base(constants, (byte*)links, (byte*)header)
15         {
16             Links = links;
17             Header = header;
18         }
19
20         [MethodImpl(MethodImplOptions.AggressiveInlining)]
21         protected override ulong GetZero() => 0UL;
22
23         [MethodImpl(MethodImplOptions.AggressiveInlining)]
24         protected override bool EqualToZero(ulong value) => value == 0UL;
25
26         [MethodImpl(MethodImplOptions.AggressiveInlining)]
27         protected override bool IsEquals(ulong first, ulong second) => first == second;
28
29         [MethodImpl(MethodImplOptions.AggressiveInlining)]
30         protected override bool GreaterThanZero(ulong value) => value > 0UL;
31
32         [MethodImpl(MethodImplOptions.AggressiveInlining)]
33         protected override bool GreaterThan(ulong first, ulong second) => first > second;
34
35         [MethodImpl(MethodImplOptions.AggressiveInlining)]
36         protected override bool GreaterOrEqualThan(ulong first, ulong second) => first >= second;
37
38         [MethodImpl(MethodImplOptions.AggressiveInlining)]
39         protected override bool GreaterOrEqualThanZero(ulong value) => true; // value >= 0 is
           ↪ always true for ulong
40
41         [MethodImpl(MethodImplOptions.AggressiveInlining)]
42         protected override bool LessOrEqualThanZero(ulong value) => value == 0UL; // value is
           ↪ always >= 0 for ulong
43
44         [MethodImpl(MethodImplOptions.AggressiveInlining)]
45         protected override bool LessOrEqualThan(ulong first, ulong second) => first <= second;
46
47         [MethodImpl(MethodImplOptions.AggressiveInlining)]
48         protected override bool LessThanZero(ulong value) => false; // value < 0 is always false
           ↪ for ulong
49
50         [MethodImpl(MethodImplOptions.AggressiveInlining)]
51         protected override bool LessThan(ulong first, ulong second) => first < second;
52
```

```
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong Increment(ulong value) => ++value;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong Decrement(ulong value) => --value;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong Add(ulong first, ulong second) => first + second;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong Subtract(ulong first, ulong second) => first - second;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool FirstIsToTheLeftOfSecond(ulong first, ulong second)
        {
            ref var firstLink = ref Links[first];
            ref var secondLink = ref Links[second];
            return FirstIsToTheLeftOfSecond(firstLink.Source, firstLink.Target,
            ↪  secondLink.Source, secondLink.Target);
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool FirstIsToTheRightOfSecond(ulong first, ulong second)
        {
            ref var firstLink = ref Links[first];
            ref var secondLink = ref Links[second];
            return FirstIsToTheRightOfSecond(firstLink.Source, firstLink.Target,
            ↪  secondLink.Source, secondLink.Target);
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ref LinksHeader<ulong> GetHeaderReference() => ref *Header;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ref RawLink<ulong> GetLinkReference(ulong link) => ref Links[link];
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/Specific/UInt64LinksSourcesAvlBalancedTreeMethods.cs

```
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.ResizableDirectMemory.Specific
{
    public unsafe class UInt64LinksSourcesAvlBalancedTreeMethods :
    ↪  UInt64LinksAvlBalancedTreeMethodsBase
    {
        public UInt64LinksSourcesAvlBalancedTreeMethods(LinksConstants<ulong> constants,
        ↪  RawLink<ulong>* links, LinksHeader<ulong>* header) : base(constants, links, header)
        ↪  { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ref ulong GetLeftReference(ulong node) => ref
        ↪  Links[node].LeftAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ref ulong GetRightReference(ulong node) => ref
        ↪  Links[node].RightAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetLeft(ulong node) => Links[node].LeftAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetRight(ulong node) => Links[node].RightAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetLeft(ulong node, ulong left) => Links[node].LeftAsSource =
        ↪  left;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetRight(ulong node, ulong right) => Links[node].RightAsSource =
        ↪  right;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetSize(ulong node) => GetSizeValue(Links[node].SizeAsSource);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
```

```
        protected override void SetSize(ulong node, ulong size) => SetSizeValue(ref Links[node].SizeAsSource, size);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool GetLeftIsChild(ulong node) => GetLeftIsChildValue(Links[node].SizeAsSource);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetLeftIsChild(ulong node, bool value) => SetLeftIsChildValue(ref Links[node].SizeAsSource, value);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool GetRightIsChild(ulong node) => GetRightIsChildValue(Links[node].SizeAsSource);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetRightIsChild(ulong node, bool value) => SetRightIsChildValue(ref Links[node].SizeAsSource, value);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override sbyte GetBalance(ulong node) => GetBalanceValue(Links[node].SizeAsSource);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetBalance(ulong node, sbyte value) => SetBalanceValue(ref Links[node].SizeAsSource, value);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetTreeRoot() => Header->FirstAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetBasePartValue(ulong link) => Links[link].Source;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool FirstIsToTheLeftOfSecond(ulong firstSource, ulong firstTarget,
            ulong secondSource, ulong secondTarget)
            => firstSource < secondSource || firstSource == secondSource && firstTarget <
                secondTarget;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool FirstIsToTheRightOfSecond(ulong firstSource, ulong firstTarget,
            ulong secondSource, ulong secondTarget)
            => firstSource > secondSource || firstSource == secondSource && firstTarget >
                secondTarget;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void ClearNode(ulong node)
        {
            ref var link = ref Links[node];
            link.LeftAsSource = 0UL;
            link.RightAsSource = 0UL;
            link.SizeAsSource = 0UL;
        }
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/Specific/UInt64LinksSourcesSizeBalancedTreeMethods.cs

```
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.ResizableDirectMemory.Specific
{
    public unsafe class UInt64LinksSourcesSizeBalancedTreeMethods :
        UInt64LinksSizeBalancedTreeMethodsBase
    {
        public UInt64LinksSourcesSizeBalancedTreeMethods(LinksConstants<ulong> constants,
            RawLink<ulong>* links, LinksHeader<ulong>* header) : base(constants, links, header)
            { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ref ulong GetLeftReference(ulong node) => ref
            Links[node].LeftAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ref ulong GetRightReference(ulong node) => ref
            Links[node].RightAsSource;

```

```
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetLeft(ulong node) => Links[node].LeftAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetRight(ulong node) => Links[node].RightAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetLeft(ulong node, ulong left) => Links[node].LeftAsSource =
        ↪  left;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetRight(ulong node, ulong right) => Links[node].RightAsSource =
        ↪  right;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetSize(ulong node) => Links[node].SizeAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetSize(ulong node, ulong size) => Links[node].SizeAsSource =
        ↪  size;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetTreeRoot() => Header->FirstAsSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetBasePartValue(ulong link) => Links[link].Source;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool FirstIsToTheLeftOfSecond(ulong firstSource, ulong firstTarget,
        ↪  ulong secondSource, ulong secondTarget)
            => firstSource < secondSource || firstSource == secondSource && firstTarget <
            ↪  secondTarget;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool FirstIsToTheRightOfSecond(ulong firstSource, ulong firstTarget,
        ↪  ulong secondSource, ulong secondTarget)
            => firstSource > secondSource || firstSource == secondSource && firstTarget >
            ↪  secondTarget;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void ClearNode(ulong node)
        {
            ref var link = ref Links[node];
            link.LeftAsSource = 0UL;
            link.RightAsSource = 0UL;
            link.SizeAsSource = 0UL;
        }
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/Specific/UInt64LinksTargetsAvlBalancedTreeMethods.cs

```
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.ResizableDirectMemory.Specific
{
    public unsafe class UInt64LinksTargetsAvlBalancedTreeMethods :
    ↪  UInt64LinksAvlBalancedTreeMethodsBase
    {
        public UInt64LinksTargetsAvlBalancedTreeMethods(LinksConstants<ulong> constants,
        ↪  RawLink<ulong>* links, LinksHeader<ulong>* header) : base(constants, links, header)
        ↪  { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ref ulong GetLeftReference(ulong node) => ref
        ↪  Links[node].LeftAsTarget;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ref ulong GetRightReference(ulong node) => ref
        ↪  Links[node].RightAsTarget;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetLeft(ulong node) => Links[node].LeftAsTarget;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetRight(ulong node) => Links[node].RightAsTarget;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
```

```
        protected override void SetLeft(ulong node, ulong left) => Links[node].LeftAsTarget = left;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetRight(ulong node, ulong right) => Links[node].RightAsTarget = right;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetSize(ulong node) => GetSizeValue(Links[node].SizeAsTarget);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetSize(ulong node, ulong size) => SetSizeValue(ref Links[node].SizeAsTarget, size);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool GetLeftIsChild(ulong node) => GetLeftIsChildValue(Links[node].SizeAsTarget);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetLeftIsChild(ulong node, bool value) => SetLeftIsChildValue(ref Links[node].SizeAsTarget, value);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool GetRightIsChild(ulong node) => GetRightIsChildValue(Links[node].SizeAsTarget);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetRightIsChild(ulong node, bool value) => SetRightIsChildValue(ref Links[node].SizeAsTarget, value);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override sbyte GetBalance(ulong node) => GetBalanceValue(Links[node].SizeAsTarget);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetBalance(ulong node, sbyte value) => SetBalanceValue(ref Links[node].SizeAsTarget, value);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetTreeRoot() => Header->FirstAsTarget;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetBasePartValue(ulong link) => Links[link].Target;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool FirstIsToTheLeftOfSecond(ulong firstSource, ulong firstTarget,
        ulong secondSource, ulong secondTarget)
            => firstTarget < secondTarget || firstTarget == secondTarget && firstSource <
            secondSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool FirstIsToTheRightOfSecond(ulong firstSource, ulong firstTarget,
        ulong secondSource, ulong secondTarget)
            => firstTarget > secondTarget || firstTarget == secondTarget && firstSource >
            secondSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void ClearNode(ulong node)
        {
            ref var link = ref Links[node];
            link.LeftAsTarget = OUL;
            link.RightAsTarget = OUL;
            link.SizeAsTarget = OUL;
        }
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/Specific/UInt64LinksTargetsSizeBalancedTreeMethods.cs

```
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.ResizableDirectMemory.Specific
{
    public unsafe class UInt64LinksTargetsSizeBalancedTreeMethods :
    UInt64LinksSizeBalancedTreeMethodsBase
    {
```

```
        public UInt64LinksTargetsSizeBalancedTreeMethods(LinksConstants<ulong> constants,
        ↪  RawLink<ulong>* links, LinksHeader<ulong>* header) : base(constants, links, header)
        ↪  { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ref ulong GetLeftReference(ulong node) => ref
        ↪  Links[node].LeftAsTarget;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ref ulong GetRightReference(ulong node) => ref
        ↪  Links[node].RightAsTarget;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetLeft(ulong node) => Links[node].LeftAsTarget;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetRight(ulong node) => Links[node].RightAsTarget;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetLeft(ulong node, ulong left) => Links[node].LeftAsTarget =
        ↪  left;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetRight(ulong node, ulong right) => Links[node].RightAsTarget =
        ↪  right;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetSize(ulong node) => Links[node].SizeAsTarget;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void SetSize(ulong node, ulong size) => Links[node].SizeAsTarget =
        ↪  size;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetTreeRoot() => Header->FirstAsTarget;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetBasePartValue(ulong link) => Links[link].Target;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool FirstIsToTheLeftOfSecond(ulong firstSource, ulong firstTarget,
        ↪  ulong secondSource, ulong secondTarget)
            => firstTarget < secondTarget || firstTarget == secondTarget && firstSource <
            ↪  secondSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool FirstIsToTheRightOfSecond(ulong firstSource, ulong firstTarget,
        ↪  ulong secondSource, ulong secondTarget)
            => firstTarget > secondTarget || firstTarget == secondTarget && firstSource >
            ↪  secondSource;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override void ClearNode(ulong node)
        {
            ref var link = ref Links[node];
            link.LeftAsTarget = OUL;
            link.RightAsTarget = OUL;
            link.SizeAsTarget = OUL;
        }
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/Specific/UInt64ResizableDirectMemoryLinks.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Memory;
using Platform.Data.Doublets.ResizableDirectMemory.Generic;
using Platform.Singletons;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.ResizableDirectMemory.Specific
{
    public unsafe class UInt64ResizableDirectMemoryLinks : ResizableDirectMemoryLinksBase<ulong>
    {
        private readonly Func<ILinksTreeMethods<ulong>> _createSourceTreeMethods;
        private readonly Func<ILinksTreeMethods<ulong>> _createTargetTreeMethods;
        private LinksHeader<ulong>* _header;
        private RawLink<ulong>* _links;
```

```
18
19          [MethodImpl(MethodImplOptions.AggressiveInlining)]
20          public UInt64ResizableDirectMemoryLinks(string address) : this(address,
            ↪  DefaultLinksSizeStep) { }
21
22          /// <summary>
23          /// Создаёт экземпляр базы данных Links в файле по указанному адресу, с указанным
            ↪  минимальным шагом расширения базы данных.
24          /// </summary>
25          /// <param name="address">Полный пусть к файлу базы данных.</param>
26          /// <param name="memoryReservationStep">Минимальный шаг расширения базы данных в
            ↪  байтах.</param>
27          [MethodImpl(MethodImplOptions.AggressiveInlining)]
28          public UInt64ResizableDirectMemoryLinks(string address, long memoryReservationStep) :
            ↪  this(new FileMappedResizableDirectMemory(address, memoryReservationStep),
            ↪  memoryReservationStep) { }
29
30          [MethodImpl(MethodImplOptions.AggressiveInlining)]
31          public UInt64ResizableDirectMemoryLinks(IResizableDirectMemory memory) : this(memory,
            ↪  DefaultLinksSizeStep) { }
32
33          [MethodImpl(MethodImplOptions.AggressiveInlining)]
34          public UInt64ResizableDirectMemoryLinks(IResizableDirectMemory memory, long
            ↪  memoryReservationStep) : this(memory, memoryReservationStep,
            ↪  Default<LinksConstants<ulong>>.Instance, true) { }
35
36          [MethodImpl(MethodImplOptions.AggressiveInlining)]
37          public UInt64ResizableDirectMemoryLinks(IResizableDirectMemory memory, long
            ↪  memoryReservationStep, LinksConstants<ulong> constants, bool useAvlBasedIndex) :
            ↪  base(memory, memoryReservationStep, constants)
38          {
39              if (useAvlBasedIndex)
40              {
41                  _createSourceTreeMethods = () => new
                    ↪  UInt64LinksSourcesAvlBalancedTreeMethods(Constants, _links, _header);
42                  _createTargetTreeMethods = () => new
                    ↪  UInt64LinksTargetsAvlBalancedTreeMethods(Constants, _links, _header);
43              }
44              else
45              {
46                  _createSourceTreeMethods = () => new
                    ↪  UInt64LinksSourcesSizeBalancedTreeMethods(Constants, _links, _header);
47                  _createTargetTreeMethods = () => new
                    ↪  UInt64LinksTargetsSizeBalancedTreeMethods(Constants, _links, _header);
48              }
49              Init(memory, memoryReservationStep);
50          }
51
52          [MethodImpl(MethodImplOptions.AggressiveInlining)]
53          protected override void SetPointers(IResizableDirectMemory memory)
54          {
55              _header = (LinksHeader<ulong>*)memory.Pointer;
56              _links = (RawLink<ulong>*)memory.Pointer;
57              SourcesTreeMethods = _createSourceTreeMethods();
58              TargetsTreeMethods = _createTargetTreeMethods();
59              UnusedLinksListMethods = new UInt64UnusedLinksListMethods(_links, _header);
60          }
61
62          [MethodImpl(MethodImplOptions.AggressiveInlining)]
63          protected override void ResetPointers()
64          {
65              base.ResetPointers();
66              _links = null;
67              _header = null;
68          }
69
70          [MethodImpl(MethodImplOptions.AggressiveInlining)]
71          protected override ref LinksHeader<ulong> GetHeaderReference() => ref *_header;
72
73          [MethodImpl(MethodImplOptions.AggressiveInlining)]
74          protected override ref RawLink<ulong> GetLinkReference(ulong linkIndex) => ref
            ↪  _links[linkIndex];
75
76          [MethodImpl(MethodImplOptions.AggressiveInlining)]
77          protected override bool AreEqual(ulong first, ulong second) => first == second;
78
79          [MethodImpl(MethodImplOptions.AggressiveInlining)]
```

```
        protected override bool LessThan(ulong first, ulong second) => first < second;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool LessOrEqualThan(ulong first, ulong second) => first <= second;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool GreaterThan(ulong first, ulong second) => first > second;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override bool GreaterOrEqualThan(ulong first, ulong second) => first >= second;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetZero() => 0UL;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong GetOne() => 1UL;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override long ConvertToUInt64(ulong value) => (long)value;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong ConvertToAddress(long value) => (ulong)value;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong Add(ulong first, ulong second) => first + second;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong Subtract(ulong first, ulong second) => first - second;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong Increment(ulong link) => ++link;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ulong Decrement(ulong link) => --link;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override IList<ulong> GetEmptyList() => new ulong[0];
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/Specific/UInt64UnusedLinksListMethods.cs

```
using System.Runtime.CompilerServices;
using Platform.Data.Doublets.ResizableDirectMemory.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.ResizableDirectMemory.Specific
{
    public unsafe class UInt64UnusedLinksListMethods : UnusedLinksListMethods<ulong>
    {
        private readonly RawLink<ulong>* _links;
        private readonly LinksHeader<ulong>* _header;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public UInt64UnusedLinksListMethods(RawLink<ulong>* links, LinksHeader<ulong>* header)
            : base((byte*)links, (byte*)header)
        {
            _links = links;
            _header = header;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ref RawLink<ulong> GetLinkReference(ulong link) => ref _links[link];

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override ref LinksHeader<ulong> GetHeaderReference() => ref *_header;
    }
}
```

./Platform.Data.Doublets/Sequences/ArrayExtensions.cs

```
using System;
using System.Collections.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences
{
    public static class ArrayExtensions
    {
        public static IList<TLink> ConvertToRestrictionsValues<TLink>(this TLink[] array)
```

```
        {
            var restrictions = new TLink[array.Length + 1];
            Array.Copy(array, 0, restrictions, 1, array.Length);
            return restrictions;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Converters/BalancedVariantConverter.cs

```
using System.Collections.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Converters
{
    public class BalancedVariantConverter<TLink> : LinksListToSequenceConverterBase<TLink>
    {
        public BalancedVariantConverter(ILinks<TLink> links) : base(links) { }

        public override TLink Convert(IList<TLink> sequence)
        {
            var length = sequence.Count;
            if (length < 1)
            {
                return default;
            }
            if (length == 1)
            {
                return sequence[0];
            }
            // Make copy of next layer
            if (length > 2)
            {
                // TODO: Try to use stackalloc (which at the moment is not working with
                ↪  generics) but will be possible with Sigil
                var halvedSequence = new TLink[(length / 2) + (length % 2)];
                HalveSequence(halvedSequence, sequence, length);
                sequence = halvedSequence;
                length = halvedSequence.Length;
            }
            // Keep creating layer after layer
            while (length > 2)
            {
                HalveSequence(sequence, sequence, length);
                length = (length / 2) + (length % 2);
            }
            return Links.GetOrCreate(sequence[0], sequence[1]);
        }

        private void HalveSequence(IList<TLink> destination, IList<TLink> source, int length)
        {
            var loopedLength = length - (length % 2);
            for (var i = 0; i < loopedLength; i += 2)
            {
                destination[i / 2] = Links.GetOrCreate(source[i], source[i + 1]);
            }
            if (length > loopedLength)
            {
                destination[length / 2] = source[length - 1];
            }
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Converters/CompressingConverter.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Interfaces;
using Platform.Collections;
using Platform.Singletons;
using Platform.Numbers;
using Platform.Data.Doublets.Sequences.Frequencies.Cache;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Converters
{
    /// <remarks>
```

```
15      /// TODO: Возможно будет лучше если алгоритм будет выполняться полностью изолированно от
        ↪  Links на этапе сжатия.
16      ///     А именно будет создаваться временный список пар необходимых для выполнения сжатия, в
        ↪  таком случае тип значения элемента массива может быть любым, как char так и ulong.
17      ///     Как только список/словарь пар был выявлен можно разом выполнить создание всех этих
        ↪  пар, а так же разом выполнить замену.
18      /// </remarks>
19      public class CompressingConverter<TLink> : LinksListToSequenceConverterBase<TLink>
20      {
21          private static readonly LinksConstants<TLink> _constants =
            ↪  Default<LinksConstants<TLink>>.Instance;
22          private static readonly EqualityComparer<TLink> _equalityComparer =
            ↪  EqualityComparer<TLink>.Default;
23          private static readonly Comparer<TLink> _comparer = Comparer<TLink>.Default;
24
25          private readonly IConverter<IList<TLink>, TLink> _baseConverter;
26          private readonly LinkFrequenciesCache<TLink> _doubletFrequenciesCache;
27          private readonly TLink _minFrequencyToCompress;
28          private readonly bool _doInitialFrequenciesIncrement;
29          private Doublet<TLink> _maxDoublet;
30          private LinkFrequency<TLink> _maxDoubletData;
31
32          private struct HalfDoublet
33          {
34              public TLink Element;
35              public LinkFrequency<TLink> DoubletData;
36
37              public HalfDoublet(TLink element, LinkFrequency<TLink> doubletData)
38              {
39                  Element = element;
40                  DoubletData = doubletData;
41              }
42
43              public override string ToString() => $"{Element}: ({DoubletData})";
44          }
45
46          public CompressingConverter(ILinks<TLink> links, IConverter<IList<TLink>, TLink>
            ↪  baseConverter, LinkFrequenciesCache<TLink> doubletFrequenciesCache)
47              : this(links, baseConverter, doubletFrequenciesCache, Integer<TLink>.One, true)
48          {
49          }
50
51          public CompressingConverter(ILinks<TLink> links, IConverter<IList<TLink>, TLink>
            ↪  baseConverter, LinkFrequenciesCache<TLink> doubletFrequenciesCache, bool
            ↪  doInitialFrequenciesIncrement)
52              : this(links, baseConverter, doubletFrequenciesCache, Integer<TLink>.One,
                ↪  doInitialFrequenciesIncrement)
53          {
54          }
55
56          public CompressingConverter(ILinks<TLink> links, IConverter<IList<TLink>, TLink>
            ↪  baseConverter, LinkFrequenciesCache<TLink> doubletFrequenciesCache, TLink
            ↪  minFrequencyToCompress, bool doInitialFrequenciesIncrement)
57              : base(links)
58          {
59              _baseConverter = baseConverter;
60              _doubletFrequenciesCache = doubletFrequenciesCache;
61              if (_comparer.Compare(minFrequencyToCompress, Integer<TLink>.One) < 0)
62              {
63                  minFrequencyToCompress = Integer<TLink>.One;
64              }
65              _minFrequencyToCompress = minFrequencyToCompress;
66              _doInitialFrequenciesIncrement = doInitialFrequenciesIncrement;
67              ResetMaxDoublet();
68          }
69
70          public override TLink Convert(IList<TLink> source) =>
            ↪  _baseConverter.Convert(Compress(source));
71
72          /// <remarks>
73          /// Original algorithm idea: https://en.wikipedia.org/wiki/Byte_pair_encoding .
74          /// Faster version (doublets' frequencies dictionary is not recreated).
75          /// </remarks>
76          private IList<TLink> Compress(IList<TLink> sequence)
77          {
78              if (sequence.IsNullOrEmpty())
79              {
80                  return null;
81              }
82              if (sequence.Count == 1)
```

```
            {
                return sequence;
            }
            if (sequence.Count == 2)
            {
                return new[] { Links.GetOrCreate(sequence[0], sequence[1]) };
            }
            // TODO: arraypool with min size (to improve cache locality) or stackallow with Sigil
            var copy = new HalfDoublet[sequence.Count];
            Doublet<TLink> doublet = default;
            for (var i = 1; i < sequence.Count; i++)
            {
                doublet.Source = sequence[i - 1];
                doublet.Target = sequence[i];
                LinkFrequency<TLink> data;
                if (_doInitialFrequenciesIncrement)
                {
                    data = _doubletFrequenciesCache.IncrementFrequency(ref doublet);
                }
                else
                {
                    data = _doubletFrequenciesCache.GetFrequency(ref doublet);
                    if (data == null)
                    {
                        throw new NotSupportedException("If you ask not to increment
                        ↪  frequencies, it is expected that all frequencies for the sequence
                        ↪  are prepared.");
                    }
                }
                copy[i - 1].Element = sequence[i - 1];
                copy[i - 1].DoubletData = data;
                UpdateMaxDoublet(ref doublet, data);
            }
            copy[sequence.Count - 1].Element = sequence[sequence.Count - 1];
            copy[sequence.Count - 1].DoubletData = new LinkFrequency<TLink>();
            if (_comparer.Compare(_maxDoubletData.Frequency, default) > 0)
            {
                var newLength = ReplaceDoublets(copy);
                sequence = new TLink[newLength];
                for (int i = 0; i < newLength; i++)
                {
                    sequence[i] = copy[i].Element;
                }
            }
            return sequence;
        }

        /// <remarks>
        /// Original algorithm idea: https://en.wikipedia.org/wiki/Byte_pair_encoding
        /// </remarks>
        private int ReplaceDoublets(HalfDoublet[] copy)
        {
            var oldLength = copy.Length;
            var newLength = copy.Length;
            while (_comparer.Compare(_maxDoubletData.Frequency, default) > 0)
            {
                var maxDoubletSource = _maxDoublet.Source;
                var maxDoubletTarget = _maxDoublet.Target;
                if (_equalityComparer.Equals(_maxDoubletData.Link, _constants.Null))
                {
                    _maxDoubletData.Link = Links.GetOrCreate(maxDoubletSource, maxDoubletTarget);
                }
                var maxDoubletReplacementLink = _maxDoubletData.Link;
                oldLength--;
                var oldLengthMinusTwo = oldLength - 1;
                // Substitute all usages
                int w = 0, r = 0; // (r == read, w == write)
                for (; r < oldLength; r++)
                {
                    if (_equalityComparer.Equals(copy[r].Element, maxDoubletSource) &&
                    ↪  _equalityComparer.Equals(copy[r + 1].Element, maxDoubletTarget))
                    {
                        if (r > 0)
                        {
                            var previous = copy[w - 1].Element;
                            copy[w - 1].DoubletData.DecrementFrequency();
                            copy[w - 1].DoubletData =
                            ↪  _doubletFrequenciesCache.IncrementFrequency(previous,
                            ↪  maxDoubletReplacementLink);
```

```
                        }
                        if (r < oldLengthMinusTwo)
                        {
                            var next = copy[r + 2].Element;
                            copy[r + 1].DoubletData.DecrementFrequency();
                            copy[w].DoubletData = _doubletFrequenciesCache.IncrementFrequency(ma
                            ↪  xDoubletReplacementLink,
                            ↪  next);
                        }
                        copy[w++].Element = maxDoubletReplacementLink;
                        r++;
                        newLength--;
                    }
                    else
                    {
                        copy[w++] = copy[r];
                    }
                }
                if (w < newLength)
                {
                    copy[w] = copy[r];
                }
                oldLength = newLength;
                ResetMaxDoublet();
                UpdateMaxDoublet(copy, newLength);
            }
            return newLength;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private void ResetMaxDoublet()
        {
            _maxDoublet = new Doublet<TLink>();
            _maxDoubletData = new LinkFrequency<TLink>();
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private void UpdateMaxDoublet(HalfDoublet[] copy, int length)
        {
            Doublet<TLink> doublet = default;
            for (var i = 1; i < length; i++)
            {
                doublet.Source = copy[i - 1].Element;
                doublet.Target = copy[i].Element;
                UpdateMaxDoublet(ref doublet, copy[i - 1].DoubletData);
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private void UpdateMaxDoublet(ref Doublet<TLink> doublet, LinkFrequency<TLink> data)
        {
            var frequency = data.Frequency;
            var maxFrequency = _maxDoubletData.Frequency;
            //if (frequency > _minFrequencyToCompress && (maxFrequency < frequency ||
            ↪  (maxFrequency == frequency && doublet.Source + doublet.Target < /* gives better
            ↪  compression string data (and gives collisions quickly) */ _maxDoublet.Source +
            ↪  _maxDoublet.Target)))
            if (_comparer.Compare(frequency, _minFrequencyToCompress) > 0 &&
               (_comparer.Compare(maxFrequency, frequency) < 0 ||
                ↪  (_equalityComparer.Equals(maxFrequency, frequency) &&
                ↪  _comparer.Compare(Arithmetic.Add(doublet.Source, doublet.Target),
                ↪  Arithmetic.Add(_maxDoublet.Source, _maxDoublet.Target)) > 0))) /* gives
                ↪  better stability and better compression on sequent data and even on rundom
                ↪  numbers data (but gives collisions anyway) */
            {
                _maxDoublet = doublet;
                _maxDoubletData = data;
            }
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Converters/LinksListToSequenceConverterBase.cs

```
using System.Collections.Generic;
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Converters
```

```
{
    public abstract class LinksListToSequenceConverterBase<TLink> : IConverter<IList<TLink>,
    ↪ TLink>
    {
        protected readonly ILinks<TLink> Links;
        public LinksListToSequenceConverterBase(ILinks<TLink> links) => Links = links;
        public abstract TLink Convert(IList<TLink> source);
    }
}
```

./Platform.Data.Doublets/Sequences/Converters/OptimalVariantConverter.cs

```
using System.Collections.Generic;
using System.Linq;
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Converters
{
    public class OptimalVariantConverter<TLink> : LinksListToSequenceConverterBase<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪ EqualityComparer<TLink>.Default;
        private static readonly Comparer<TLink> _comparer = Comparer<TLink>.Default;

        private readonly IConverter<IList<TLink>> _sequenceToItsLocalElementLevelsConverter;

        public OptimalVariantConverter(ILinks<TLink> links, IConverter<IList<TLink>>
        ↪ sequenceToItsLocalElementLevelsConverter) : base(links)
            => _sequenceToItsLocalElementLevelsConverter =
            ↪ sequenceToItsLocalElementLevelsConverter;

        public override TLink Convert(IList<TLink> sequence)
        {
            var length = sequence.Count;
            if (length == 1)
            {
                return sequence[0];
            }
            var links = Links;
            if (length == 2)
            {
                return links.GetOrCreate(sequence[0], sequence[1]);
            }
            sequence = sequence.ToArray();
            var levels = _sequenceToItsLocalElementLevelsConverter.Convert(sequence);
            while (length > 2)
            {
                var levelRepeat = 1;
                var currentLevel = levels[0];
                var previousLevel = levels[0];
                var skipOnce = false;
                var w = 0;
                for (var i = 1; i < length; i++)
                {
                    if (_equalityComparer.Equals(currentLevel, levels[i]))
                    {
                        levelRepeat++;
                        skipOnce = false;
                        if (levelRepeat == 2)
                        {
                            sequence[w] = links.GetOrCreate(sequence[i - 1], sequence[i]);
                            var newLevel = i >= length - 1 ?
                                GetPreviousLowerThanCurrentOrCurrent(previousLevel,
                                ↪ currentLevel) :
                                i < 2 ?
                                GetNextLowerThanCurrentOrCurrent(currentLevel, levels[i + 1]) :
                                GetGreatestNeigbourLowerThanCurrentOrCurrent(previousLevel,
                                ↪ currentLevel, levels[i + 1]);
                            levels[w] = newLevel;
                            previousLevel = currentLevel;
                            w++;
                            levelRepeat = 0;
                            skipOnce = true;
                        }
                        else if (i == length - 1)
                        {
                            sequence[w] = sequence[i];
                            levels[w] = levels[i];
                            w++;
```

```
                        }
                    }
                    else
                    {
                        currentLevel = levels[i];
                        levelRepeat = 1;
                        if (skipOnce)
                        {
                            skipOnce = false;
                        }
                        else
                        {
                            sequence[w] = sequence[i - 1];
                            levels[w] = levels[i - 1];
                            previousLevel = levels[w];
                            w++;
                        }
                        if (i == length - 1)
                        {
                            sequence[w] = sequence[i];
                            levels[w] = levels[i];
                            w++;
                        }
                    }
                }
                length = w;
            }
            return links.GetOrCreate(sequence[0], sequence[1]);
        }

        private static TLink GetGreatestNeigbourLowerThanCurrentOrCurrent(TLink previous, TLink current, TLink next)
        {
            return _comparer.Compare(previous, next) > 0
                ? _comparer.Compare(previous, current) < 0 ? previous : current
                : _comparer.Compare(next, current) < 0 ? next : current;
        }

        private static TLink GetNextLowerThanCurrentOrCurrent(TLink current, TLink next) => _comparer.Compare(next, current) < 0 ? next : current;

        private static TLink GetPreviousLowerThanCurrentOrCurrent(TLink previous, TLink current) => _comparer.Compare(previous, current) < 0 ? previous : current;
    }
}
```

./Platform.Data.Doublets/Sequences/Converters/SequenceToItsLocalElementLevelsConverter.cs

```
using System.Collections.Generic;
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Converters
{
    public class SequenceToItsLocalElementLevelsConverter<TLink> : LinksOperatorBase<TLink>, IConverter<IList<TLink>>
    {
        private static readonly Comparer<TLink> _comparer = Comparer<TLink>.Default;

        private readonly IConverter<Doublet<TLink>, TLink> _linkToItsFrequencyToNumberConveter;

        public SequenceToItsLocalElementLevelsConverter(ILinks<TLink> links, IConverter<Doublet<TLink>, TLink> linkToItsFrequencyToNumberConveter) : base(links) => _linkToItsFrequencyToNumberConveter = linkToItsFrequencyToNumberConveter;

        public IList<TLink> Convert(IList<TLink> sequence)
        {
            var levels = new TLink[sequence.Count];
            levels[0] = GetFrequencyNumber(sequence[0], sequence[1]);
            for (var i = 1; i < sequence.Count - 1; i++)
            {
                var previous = GetFrequencyNumber(sequence[i - 1], sequence[i]);
                var next = GetFrequencyNumber(sequence[i], sequence[i + 1]);
                levels[i] = _comparer.Compare(previous, next) > 0 ? previous : next;
            }
            levels[levels.Length - 1] = GetFrequencyNumber(sequence[sequence.Count - 2], sequence[sequence.Count - 1]);
            return levels;
        }
```

```

        public TLink GetFrequencyNumber(TLink source, TLink target) =>
            _linkToItsFrequencyToNumberConveter.Convert(new Doublet<TLink>(source, target));
    }
}
```

./Platform.Data.Doublets/Sequences/CreteriaMatchers/DefaultSequenceElementCriterionMatcher.cs

```
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.CreteriaMatchers
{
    public class DefaultSequenceElementCriterionMatcher<TLink> : LinksOperatorBase<TLink>, ICriterionMatcher<TLink>
    {
        public DefaultSequenceElementCriterionMatcher(ILinks<TLink> links) : base(links) { }
        public bool IsMatched(TLink argument) => Links.IsPartialPoint(argument);
    }
}
```

./Platform.Data.Doublets/Sequences/CreteriaMatchers/MarkedSequenceCriterionMatcher.cs

```
using System.Collections.Generic;
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.CreteriaMatchers
{
    public class MarkedSequenceCriterionMatcher<TLink> : ICriterionMatcher<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer = EqualityComparer<TLink>.Default;

        private readonly ILinks<TLink> _links;
        private readonly TLink _sequenceMarkerLink;

        public MarkedSequenceCriterionMatcher(ILinks<TLink> links, TLink sequenceMarkerLink)
        {
            _links = links;
            _sequenceMarkerLink = sequenceMarkerLink;
        }

        public bool IsMatched(TLink sequenceCandidate)
            => _equalityComparer.Equals(_links.GetSource(sequenceCandidate), _sequenceMarkerLink)
            || !_equalityComparer.Equals(_links.SearchOrDefault(_sequenceMarkerLink, sequenceCandidate), _links.Constants.Null);
    }
}
```

./Platform.Data.Doublets/Sequences/DefaultSequenceAppender.cs

```
using System.Collections.Generic;
using Platform.Collections.Stacks;
using Platform.Data.Doublets.Sequences.HeightProviders;
using Platform.Data.Sequences;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences
{
    public class DefaultSequenceAppender<TLink> : LinksOperatorBase<TLink>, ISequenceAppender<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer = EqualityComparer<TLink>.Default;

        private readonly IStack<TLink> _stack;
        private readonly ISequenceHeightProvider<TLink> _heightProvider;

        public DefaultSequenceAppender(ILinks<TLink> links, IStack<TLink> stack, ISequenceHeightProvider<TLink> heightProvider)
            : base(links)
        {
            _stack = stack;
            _heightProvider = heightProvider;
        }

        public TLink Append(TLink sequence, TLink appendant)
        {
            var cursor = sequence;
```

```
            while (!_equalityComparer.Equals(_heightProvider.Get(cursor), default))
            {
                var source = Links.GetSource(cursor);
                var target = Links.GetTarget(cursor);
                if (_equalityComparer.Equals(_heightProvider.Get(source),
                ↪  _heightProvider.Get(target)))
                {
                    break;
                }
                else
                {
                    _stack.Push(source);
                    cursor = target;
                }
            }
            var left = cursor;
            var right = appendant;
            while (!_equalityComparer.Equals(cursor = _stack.Pop(), Links.Constants.Null))
            {
                right = Links.GetOrCreate(left, right);
                left = cursor;
            }
            return Links.GetOrCreate(left, right);
        }
    }
}
```

./Platform.Data.Doublets/Sequences/DuplicateSegmentsCounter.cs

```
using System.Collections.Generic;
using System.Linq;
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences
{
    public class DuplicateSegmentsCounter<TLink> : ICounter<int>
    {
        private readonly IProvider<IList<KeyValuePair<IList<TLink>, IList<TLink>>>>
        ↪  _duplicateFragmentsProvider;
        public DuplicateSegmentsCounter(IProvider<IList<KeyValuePair<IList<TLink>,
        ↪  IList<TLink>>>> duplicateFragmentsProvider) => _duplicateFragmentsProvider =
        ↪  duplicateFragmentsProvider;
        public int Count() => _duplicateFragmentsProvider.Get().Sum(x => x.Value.Count);
    }
}
```

./Platform.Data.Doublets/Sequences/DuplicateSegmentsProvider.cs

```
using System;
using System.Linq;
using System.Collections.Generic;
using Platform.Interfaces;
using Platform.Collections;
using Platform.Collections.Lists;
using Platform.Collections.Segments;
using Platform.Collections.Segments.Walkers;
using Platform.Singletons;
using Platform.Numbers;
using Platform.Data.Doublets.Unicode;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences
{
    public class DuplicateSegmentsProvider<TLink> :
    ↪  DictionaryBasedDuplicateSegmentsWalkerBase<TLink>,
    ↪  IProvider<IList<KeyValuePair<IList<TLink>, IList<TLink>>>>
    {
        private readonly ILinks<TLink> _links;
        private readonly ILinks<TLink> _sequences;
        private HashSet<KeyValuePair<IList<TLink>, IList<TLink>>> _groups;
        private BitString _visited;

        private class ItemEquilityComparer : IEqualityComparer<KeyValuePair<IList<TLink>,
        ↪  IList<TLink>>>
        {
            private readonly IListEqualityComparer<TLink> _listComparer;
            public ItemEquilityComparer() => _listComparer =
            ↪  Default<IListEqualityComparer<TLink>>.Instance;
```

```
28              public bool Equals(KeyValuePair<IList<TLink>, IList<TLink>> left,
                ↪  KeyValuePair<IList<TLink>, IList<TLink>> right) =>
                ↪  _listComparer.Equals(left.Key, right.Key) && _listComparer.Equals(left.Value,
                ↪  right.Value);
29              public int GetHashCode(KeyValuePair<IList<TLink>, IList<TLink>> pair) =>
                ↪  (_listComparer.GetHashCode(pair.Key),
                ↪  _listComparer.GetHashCode(pair.Value)).GetHashCode();
30          }
31
32          private class ItemComparer : IComparer<KeyValuePair<IList<TLink>, IList<TLink>>>
33          {
34              private readonly IListComparer<TLink> _listComparer;
35
36              public ItemComparer() => _listComparer = Default<IListComparer<TLink>>.Instance;
37
38              public int Compare(KeyValuePair<IList<TLink>, IList<TLink>> left,
                ↪  KeyValuePair<IList<TLink>, IList<TLink>> right)
39              {
40                  var intermediateResult = _listComparer.Compare(left.Key, right.Key);
41                  if (intermediateResult == 0)
42                  {
43                      intermediateResult = _listComparer.Compare(left.Value, right.Value);
44                  }
45                  return intermediateResult;
46              }
47          }
48
49          public DuplicateSegmentsProvider(ILinks<TLink> links, ILinks<TLink> sequences)
50              : base(minimumStringSegmentLength: 2)
51          {
52              _links = links;
53              _sequences = sequences;
54          }
55
56          public IList<KeyValuePair<IList<TLink>, IList<TLink>>> Get()
57          {
58              _groups = new HashSet<KeyValuePair<IList<TLink>,
                ↪  IList<TLink>>>(Default<ItemEquilityComparer>.Instance);
59              var count = _links.Count();
60              _visited = new BitString((long)(Integer<TLink>)count + 1);
61              _links.Each(link =>
62              {
63                  var linkIndex = _links.GetIndex(link);
64                  var linkBitIndex = (long)(Integer<TLink>)linkIndex;
65                  if (!_visited.Get(linkBitIndex))
66                  {
67                      var sequenceElements = new List<TLink>();
68                      var filler = new ListFiller<TLink, TLink>(sequenceElements,
                        ↪  _sequences.Constants.Break);
69                      _sequences.Each(filler.AddAllValuesAndReturnConstant, new
                        ↪  LinkAddress<TLink>(linkIndex));
70                      if (sequenceElements.Count > 2)
71                      {
72                          WalkAll(sequenceElements);
73                      }
74                  }
75                  return _links.Constants.Continue;
76              });
77              var resultList = _groups.ToList();
78              var comparer = Default<ItemComparer>.Instance;
79              resultList.Sort(comparer);
80  #if DEBUG
81              foreach (var item in resultList)
82              {
83                  PrintDuplicates(item);
84              }
85  #endif
86              return resultList;
87          }
88
89          protected override Segment<TLink> CreateSegment(IList<TLink> elements, int offset, int
            ↪  length) => new Segment<TLink>(elements, offset, length);
90
91          protected override void OnDublicateFound(Segment<TLink> segment)
92          {
93              var duplicates = CollectDuplicatesForSegment(segment);
94              if (duplicates.Count > 1)
95              {
```

```
                _groups.Add(new KeyValuePair<IList<TLink>, IList<TLink>>(segment.ToArray(),
                ↪  duplicates));
            }
        }

        private List<TLink> CollectDuplicatesForSegment(Segment<TLink> segment)
        {
            var duplicates = new List<TLink>();
            var readAsElement = new HashSet<TLink>();
            var restrictions = segment.ConvertToRestrictionsValues();
            restrictions[0] = _sequences.Constants.Any;
            _sequences.Each(sequence =>
            {
                var sequenceIndex = sequence[_sequences.Constants.IndexPart];
                duplicates.Add(sequenceIndex);
                readAsElement.Add(sequenceIndex);
                return _sequences.Constants.Continue;
            }, restrictions);
            if (duplicates.Any(x => _visited.Get((Integer<TLink>)x)))
            {
                return new List<TLink>();
            }
            foreach (var duplicate in duplicates)
            {
                var duplicateBitIndex = (long)(Integer<TLink>)duplicate;
                _visited.Set(duplicateBitIndex);
            }
            if (_sequences is Sequences sequencesExperiments)
            {
                var partiallyMatched = sequencesExperiments.GetAllPartiallyMatchingSequences4((H
                ↪  ashSet<ulong>)(object)readAsElement,
                ↪  (IList<ulong>)segment);
                foreach (var partiallyMatchedSequence in partiallyMatched)
                {
                    TLink sequenceIndex = (Integer<TLink>)partiallyMatchedSequence;
                    duplicates.Add(sequenceIndex);
                }
            }
            duplicates.Sort();
            return duplicates;
        }

        private void PrintDuplicates(KeyValuePair<IList<TLink>, IList<TLink>> duplicatesItem)
        {
            if (!(_links is ILinks<ulong> ulongLinks))
            {
                return;
            }
            var duplicatesKey = duplicatesItem.Key;
            var keyString = UnicodeMap.FromLinksToString((IList<ulong>)duplicatesKey);
            Console.WriteLine($"> {keyString} ({string.Join(", ", duplicatesKey)})");
            var duplicatesList = duplicatesItem.Value;
            for (int i = 0; i < duplicatesList.Count; i++)
            {
                ulong sequenceIndex = (Integer<TLink>)duplicatesList[i];
                var formatedSequenceStructure = ulongLinks.FormatStructure(sequenceIndex, x =>
                ↪  Point<ulong>.IsPartialPoint(x), (sb, link) => _ =
                ↪  UnicodeMap.IsCharLink(link.Index) ?
                ↪  sb.Append(UnicodeMap.FromLinkToChar(link.Index)) : sb.Append(link.Index));
                Console.WriteLine(formatedSequenceStructure);
                var sequenceString = UnicodeMap.FromSequenceLinkToString(sequenceIndex,
                ↪  ulongLinks);
                Console.WriteLine(sequenceString);
            }
            Console.WriteLine();
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Cache/LinkFrequenciesCache.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Interfaces;
using Platform.Numbers;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

```

```
namespace Platform.Data.Doublets.Sequences.Frequencies.Cache
{
    /// <remarks>
    /// Can be used to operate with many CompressingConverters (to keep global frequencies data between them).
    /// TODO: Extract interface to implement frequencies storage inside Links storage
    /// </remarks>
    public class LinkFrequenciesCache<TLink> : LinksOperatorBase<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer = EqualityComparer<TLink>.Default;
        private static readonly Comparer<TLink> _comparer = Comparer<TLink>.Default;

        private readonly Dictionary<Doublet<TLink>, LinkFrequency<TLink>> _doubletsCache;
        private readonly ICounter<TLink, TLink> _frequencyCounter;

        public LinkFrequenciesCache(ILinks<TLink> links, ICounter<TLink, TLink> frequencyCounter)
            : base(links)
        {
            _doubletsCache = new Dictionary<Doublet<TLink>, LinkFrequency<TLink>>(4096, DoubletComparer<TLink>.Default);
            _frequencyCounter = frequencyCounter;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinkFrequency<TLink> GetFrequency(TLink source, TLink target)
        {
            var doublet = new Doublet<TLink>(source, target);
            return GetFrequency(ref doublet);
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinkFrequency<TLink> GetFrequency(ref Doublet<TLink> doublet)
        {
            _doubletsCache.TryGetValue(doublet, out LinkFrequency<TLink> data);
            return data;
        }

        public void IncrementFrequencies(IList<TLink> sequence)
        {
            for (var i = 1; i < sequence.Count; i++)
            {
                IncrementFrequency(sequence[i - 1], sequence[i]);
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinkFrequency<TLink> IncrementFrequency(TLink source, TLink target)
        {
            var doublet = new Doublet<TLink>(source, target);
            return IncrementFrequency(ref doublet);
        }

        public void PrintFrequencies(IList<TLink> sequence)
        {
            for (var i = 1; i < sequence.Count; i++)
            {
                PrintFrequency(sequence[i - 1], sequence[i]);
            }
        }

        public void PrintFrequency(TLink source, TLink target)
        {
            var number = GetFrequency(source, target).Frequency;
            Console.WriteLine("({0},{1}) - {2}", source, target, number);
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinkFrequency<TLink> IncrementFrequency(ref Doublet<TLink> doublet)
        {
            if (_doubletsCache.TryGetValue(doublet, out LinkFrequency<TLink> data))
            {
                data.IncrementFrequency();
            }
            else
            {
                var link = Links.SearchOrDefault(doublet.Source, doublet.Target);
                data = new LinkFrequency<TLink>(Integer<TLink>.One, link);
                if (!_equalityComparer.Equals(link, default))
```

```
                {
                    data.Frequency = Arithmetic.Add(data.Frequency,
                    ↪  _frequencyCounter.Count(link));
                }
                _doubletsCache.Add(doublet, data);
            }
            return data;
        }

        public void ValidateFrequencies()
        {
            foreach (var entry in _doubletsCache)
            {
                var value = entry.Value;
                var linkIndex = value.Link;
                if (!_equalityComparer.Equals(linkIndex, default))
                {
                    var frequency = value.Frequency;
                    var count = _frequencyCounter.Count(linkIndex);
                    // TODO: Why `frequency` always greater than `count` by 1?
                    if (((_comparer.Compare(frequency, count) > 0) &&
                    ↪  (_comparer.Compare(Arithmetic.Subtract(frequency, count),
                    ↪  Integer<TLink>.One) > 0))
                     || ((_comparer.Compare(count, frequency) > 0) &&
                     ↪  (_comparer.Compare(Arithmetic.Subtract(count, frequency),
                     ↪  Integer<TLink>.One) > 0)))
                    {
                        throw new InvalidOperationException("Frequencies validation failed.");
                    }
                }
                //else
                //{
                //    if (value.Frequency > 0)
                //    {
                //        var frequency = value.Frequency;
                //        linkIndex = _createLink(entry.Key.Source, entry.Key.Target);
                //        var count = _countLinkFrequency(linkIndex);

                //        if ((frequency > count && frequency - count > 1) || (count > frequency
                ↪  && count - frequency > 1))
                //            throw new Exception("Frequencies validation failed.");
                //    }
                //}
            }
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Cache/LinkFrequency.cs

```
using System.Runtime.CompilerServices;
using Platform.Numbers;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Frequencies.Cache
{
    public class LinkFrequency<TLink>
    {
        public TLink Frequency { get; set; }
        public TLink Link { get; set; }

        public LinkFrequency(TLink frequency, TLink link)
        {
            Frequency = frequency;
            Link = link;
        }

        public LinkFrequency() { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public void IncrementFrequency() => Frequency = Arithmetic<TLink>.Increment(Frequency);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public void DecrementFrequency() => Frequency = Arithmetic<TLink>.Decrement(Frequency);

        public override string ToString() => $"F: {Frequency}, L: {Link}";
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Cache/LinkToItsFrequencyValueConverter.cs

```
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Frequencies.Cache
{
    public class FrequenciesCacheBasedLinkToItsFrequencyNumberConverter<TLink> :
    ↪ IConverter<Doublet<TLink>, TLink>
    {
        private readonly LinkFrequenciesCache<TLink> _cache;
        public
        ↪ FrequenciesCacheBasedLinkToItsFrequencyNumberConverter(LinkFrequenciesCache<TLink>
        ↪ cache) => _cache = cache;
        public TLink Convert(Doublet<TLink> source) => _cache.GetFrequency(ref source).Frequency;
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Counters/MarkedSequenceSymbolFrequencyOneOffCounter.cs

```
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Frequencies.Counters
{
    public class MarkedSequenceSymbolFrequencyOneOffCounter<TLink> :
    ↪ SequenceSymbolFrequencyOneOffCounter<TLink>
    {
        private readonly ICriterionMatcher<TLink> _markedSequenceMatcher;

        public MarkedSequenceSymbolFrequencyOneOffCounter(ILinks<TLink> links,
        ↪ ICriterionMatcher<TLink> markedSequenceMatcher, TLink sequenceLink, TLink symbol)
            : base(links, sequenceLink, symbol)
            => _markedSequenceMatcher = markedSequenceMatcher;

        public override TLink Count()
        {
            if (!_markedSequenceMatcher.IsMatched(_sequenceLink))
            {
                return default;
            }
            return base.Count();
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Counters/SequenceSymbolFrequencyOneOffCounter.cs

```
using System.Collections.Generic;
using Platform.Interfaces;
using Platform.Numbers;
using Platform.Data.Sequences;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Frequencies.Counters
{
    public class SequenceSymbolFrequencyOneOffCounter<TLink> : ICounter<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪ EqualityComparer<TLink>.Default;
        private static readonly Comparer<TLink> _comparer = Comparer<TLink>.Default;

        protected readonly ILinks<TLink> _links;
        protected readonly TLink _sequenceLink;
        protected readonly TLink _symbol;
        protected TLink _total;

        public SequenceSymbolFrequencyOneOffCounter(ILinks<TLink> links, TLink sequenceLink,
        ↪ TLink symbol)
        {
            _links = links;
            _sequenceLink = sequenceLink;
            _symbol = symbol;
            _total = default;
        }

        public virtual TLink Count()
        {
            if (_comparer.Compare(_total, default) > 0)
            {
```

```
                return _total;
            }
            StopableSequenceWalker.WalkRight(_sequenceLink, _links.GetSource, _links.GetTarget,
            ↪  IsElement, VisitElement);
            return _total;
        }

        private bool IsElement(TLink x) => _equalityComparer.Equals(x, _symbol) ||
        ↪  _links.IsPartialPoint(x); // TODO: Use SequenceElementCreteriaMatcher instead of
        ↪  IsPartialPoint

        private bool VisitElement(TLink element)
        {
            if (_equalityComparer.Equals(element, _symbol))
            {
                _total = Arithmetic.Increment(_total);
            }
            return true;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Counters/TotalMarkedSequenceSymbolFrequencyCounter.cs

```
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Frequencies.Counters
{
    public class TotalMarkedSequenceSymbolFrequencyCounter<TLink> : ICounter<TLink, TLink>
    {
        private readonly ILinks<TLink> _links;
        private readonly ICriterionMatcher<TLink> _markedSequenceMatcher;

        public TotalMarkedSequenceSymbolFrequencyCounter(ILinks<TLink> links,
        ↪  ICriterionMatcher<TLink> markedSequenceMatcher)
        {
            _links = links;
            _markedSequenceMatcher = markedSequenceMatcher;
        }

        public TLink Count(TLink argument) => new
        ↪  TotalMarkedSequenceSymbolFrequencyOneOffCounter<TLink>(_links,
        ↪  _markedSequenceMatcher, argument).Count();
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Counters/TotalMarkedSequenceSymbolFrequencyOneOffCounter

```
using Platform.Interfaces;
using Platform.Numbers;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Frequencies.Counters
{
    public class TotalMarkedSequenceSymbolFrequencyOneOffCounter<TLink> :
    ↪  TotalSequenceSymbolFrequencyOneOffCounter<TLink>
    {
        private readonly ICriterionMatcher<TLink> _markedSequenceMatcher;

        public TotalMarkedSequenceSymbolFrequencyOneOffCounter(ILinks<TLink> links,
        ↪  ICriterionMatcher<TLink> markedSequenceMatcher, TLink symbol)
            : base(links, symbol)
            => _markedSequenceMatcher = markedSequenceMatcher;

        protected override void CountSequenceSymbolFrequency(TLink link)
        {
            var symbolFrequencyCounter = new
            ↪  MarkedSequenceSymbolFrequencyOneOffCounter<TLink>(_links,
            ↪  _markedSequenceMatcher, link, _symbol);
            _total = Arithmetic.Add(_total, symbolFrequencyCounter.Count());
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Counters/TotalSequenceSymbolFrequencyCounter.cs

```
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
```

```

namespace Platform.Data.Doublets.Sequences.Frequencies.Counters
{
    public class TotalSequenceSymbolFrequencyCounter<TLink> : ICounter<TLink, TLink>
    {
        private readonly ILinks<TLink> _links;
        public TotalSequenceSymbolFrequencyCounter(ILinks<TLink> links) => _links = links;
        public TLink Count(TLink symbol) => new
        ↪  TotalSequenceSymbolFrequencyOneOffCounter<TLink>(_links, symbol).Count();
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Counters/TotalSequenceSymbolFrequencyOneOffCounter.cs

```
using System.Collections.Generic;
using Platform.Interfaces;
using Platform.Numbers;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Frequencies.Counters
{
    public class TotalSequenceSymbolFrequencyOneOffCounter<TLink> : ICounter<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪  EqualityComparer<TLink>.Default;
        private static readonly Comparer<TLink> _comparer = Comparer<TLink>.Default;

        protected readonly ILinks<TLink> _links;
        protected readonly TLink _symbol;
        protected readonly HashSet<TLink> _visits;
        protected TLink _total;

        public TotalSequenceSymbolFrequencyOneOffCounter(ILinks<TLink> links, TLink symbol)
        {
            _links = links;
            _symbol = symbol;
            _visits = new HashSet<TLink>();
            _total = default;
        }

        public TLink Count()
        {
            if (_comparer.Compare(_total, default) > 0 || _visits.Count > 0)
            {
                return _total;
            }
            CountCore(_symbol);
            return _total;
        }

        private void CountCore(TLink link)
        {
            var any = _links.Constants.Any;
            if (_equalityComparer.Equals(_links.Count(any, link), default))
            {
                CountSequenceSymbolFrequency(link);
            }
            else
            {
                _links.Each(EachElementHandler, any, link);
            }
        }

        protected virtual void CountSequenceSymbolFrequency(TLink link)
        {
            var symbolFrequencyCounter = new SequenceSymbolFrequencyOneOffCounter<TLink>(_links,
            ↪  link, _symbol);
            _total = Arithmetic.Add(_total, symbolFrequencyCounter.Count());
        }

        private TLink EachElementHandler(IList<TLink> doublet)
        {
            var constants = _links.Constants;
            var doubletIndex = doublet[constants.IndexPart];
            if (_visits.Add(doubletIndex))
            {
                CountCore(doubletIndex);
            }
            return constants.Continue;
        }
```

```
    }
}
```

./Platform.Data.Doublets/Sequences/HeightProviders/CachedSequenceHeightProvider.cs

```
using System.Collections.Generic;
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.HeightProviders
{
    public class CachedSequenceHeightProvider<TLink> : LinksOperatorBase<TLink>,
    ↪ ISequenceHeightProvider<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪ EqualityComparer<TLink>.Default;

        private readonly TLink _heightPropertyMarker;
        private readonly ISequenceHeightProvider<TLink> _baseHeightProvider;
        private readonly IConverter<TLink> _addressToUnaryNumberConverter;
        private readonly IConverter<TLink> _unaryNumberToAddressConverter;
        private readonly IPropertiesOperator<TLink, TLink, TLink> _propertyOperator;

        public CachedSequenceHeightProvider(
            ILinks<TLink> links,
            ISequenceHeightProvider<TLink> baseHeightProvider,
            IConverter<TLink> addressToUnaryNumberConverter,
            IConverter<TLink> unaryNumberToAddressConverter,
            TLink heightPropertyMarker,
            IPropertiesOperator<TLink, TLink, TLink> propertyOperator)
            : base(links)
        {
            _heightPropertyMarker = heightPropertyMarker;
            _baseHeightProvider = baseHeightProvider;
            _addressToUnaryNumberConverter = addressToUnaryNumberConverter;
            _unaryNumberToAddressConverter = unaryNumberToAddressConverter;
            _propertyOperator = propertyOperator;
        }

        public TLink Get(TLink sequence)
        {
            TLink height;
            var heightValue = _propertyOperator.GetValue(sequence, _heightPropertyMarker);
            if (_equalityComparer.Equals(heightValue, default))
            {
                height = _baseHeightProvider.Get(sequence);
                heightValue = _addressToUnaryNumberConverter.Convert(height);
                _propertyOperator.SetValue(sequence, _heightPropertyMarker, heightValue);
            }
            else
            {
                height = _unaryNumberToAddressConverter.Convert(heightValue);
            }
            return height;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/HeightProviders/DefaultSequenceRightHeightProvider.cs

```
using Platform.Interfaces;
using Platform.Numbers;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.HeightProviders
{
    public class DefaultSequenceRightHeightProvider<TLink> : LinksOperatorBase<TLink>,
    ↪ ISequenceHeightProvider<TLink>
    {
        private readonly ICriterionMatcher<TLink> _elementMatcher;

        public DefaultSequenceRightHeightProvider(ILinks<TLink> links, ICriterionMatcher<TLink>
        ↪ elementMatcher) : base(links) => _elementMatcher = elementMatcher;

        public TLink Get(TLink sequence)
        {
            var height = default(TLink);
            var pairOrElement = sequence;
            while (!_elementMatcher.IsMatched(pairOrElement))
            {
```

```
                pairOrElement = Links.GetTarget(pairOrElement);
                height = Arithmetic.Increment(height);
            }
            return height;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/HeightProviders/ISequenceHeightProvider.cs

```
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.HeightProviders
{
    public interface ISequenceHeightProvider<TLink> : IProvider<TLink, TLink>
    {
    }
}
```

./Platform.Data.Doublets/Sequences/IListExtensions.cs

```
using Platform.Collections;
using System.Collections.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences
{
    public static class IListExtensions
    {
        public static TLink[] ExtractValues<TLink>(this IList<TLink> restrictions)
        {
            if(restrictions.IsNullOrEmpty() || restrictions.Count == 1)
            {
                return new TLink[0];
            }
            var values = new TLink[restrictions.Count - 1];
            for (int i = 1, j = 0; i < restrictions.Count; i++, j++)
            {
                values[j] = restrictions[i];
            }
            return values;
        }

        public static IList<TLink> ConvertToRestrictionsValues<TLink>(this IList<TLink> list)
        {
            var restrictions = new TLink[list.Count + 1];
            for (int i = 0, j = 1; i < list.Count; i++, j++)
            {
                restrictions[j] = list[i];
            }
            return restrictions;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Indexes/CachedFrequencyIncrementingSequenceIndex.cs

```
using System.Collections.Generic;
using Platform.Data.Doublets.Sequences.Frequencies.Cache;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Indexes
{
    public class CachedFrequencyIncrementingSequenceIndex<TLink> : ISequenceIndex<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪  EqualityComparer<TLink>.Default;

        private readonly LinkFrequenciesCache<TLink> _cache;

        public CachedFrequencyIncrementingSequenceIndex(LinkFrequenciesCache<TLink> cache) =>
        ↪  _cache = cache;

        public bool Add(IList<TLink> sequence)
        {
            var indexed = true;
            var i = sequence.Count;
            while (--i >= 1 && (indexed = IsIndexedWithIncrement(sequence[i - 1], sequence[i])))
            ↪  { }
```

```
            for (; i >= 1; i--)
            {
                _cache.IncrementFrequency(sequence[i - 1], sequence[i]);
            }
            return indexed;
        }

        private bool IsIndexedWithIncrement(TLink source, TLink target)
        {
            var frequency = _cache.GetFrequency(source, target);
            if (frequency == null)
            {
                return false;
            }
            var indexed = !_equalityComparer.Equals(frequency.Frequency, default);
            if (indexed)
            {
                _cache.IncrementFrequency(source, target);
            }
            return indexed;
        }

        public bool MightContain(IList<TLink> sequence)
        {
            var indexed = true;
            var i = sequence.Count;
            while (--i >= 1 && (indexed = IsIndexed(sequence[i - 1], sequence[i]))) { }
            return indexed;
        }

        private bool IsIndexed(TLink source, TLink target)
        {
            var frequency = _cache.GetFrequency(source, target);
            if (frequency == null)
            {
                return false;
            }
            return !_equalityComparer.Equals(frequency.Frequency, default);
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Indexes/FrequencyIncrementingSequenceIndex.cs

```
using Platform.Interfaces;
using System.Collections.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Indexes
{
    public class FrequencyIncrementingSequenceIndex<TLink> : SequenceIndex<TLink>,
    ↪ ISequenceIndex<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪ EqualityComparer<TLink>.Default;

        private readonly IPropertyOperator<TLink, TLink> _frequencyPropertyOperator;
        private readonly IIncrementer<TLink> _frequencyIncrementer;

        public FrequencyIncrementingSequenceIndex(ILinks<TLink> links, IPropertyOperator<TLink,
        ↪ TLink> frequencyPropertyOperator, IIncrementer<TLink> frequencyIncrementer)
            : base(links)
        {
            _frequencyPropertyOperator = frequencyPropertyOperator;
            _frequencyIncrementer = frequencyIncrementer;
        }

        public override bool Add(IList<TLink> sequence)
        {
            var indexed = true;
            var i = sequence.Count;
            while (--i >= 1 && (indexed = IsIndexedWithIncrement(sequence[i - 1], sequence[i])))
            ↪ { }
            for (; i >= 1; i--)
            {
                Increment(Links.GetOrCreate(sequence[i - 1], sequence[i]));
            }
            return indexed;
        }

```

```
        private bool IsIndexedWithIncrement(TLink source, TLink target)
        {
            var link = Links.SearchOrDefault(source, target);
            var indexed = !_equalityComparer.Equals(link, default);
            if (indexed)
            {
                Increment(link);
            }
            return indexed;
        }

        private void Increment(TLink link)
        {
            var previousFrequency = _frequencyPropertyOperator.Get(link);
            var frequency = _frequencyIncrementer.Increment(previousFrequency);
            _frequencyPropertyOperator.Set(link, frequency);
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Indexes/ISequenceIndex.cs

```
using System.Collections.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Indexes
{
    public interface ISequenceIndex<TLink>
    {
        /// <summary>
        /// Индексирует последовательность глобально, и возвращает значение,
        /// определяющие была ли запрошенная последовательность проиндексирована ранее.
        /// </summary>
        /// <param name="sequence">Последовательность для индексации.</param>
        bool Add(IList<TLink> sequence);

        bool MightContain(IList<TLink> sequence);
    }
}
```

./Platform.Data.Doublets/Sequences/Indexes/SequenceIndex.cs

```
using System.Collections.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Indexes
{
    public class SequenceIndex<TLink> : LinksOperatorBase<TLink>, ISequenceIndex<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪  EqualityComparer<TLink>.Default;

        public SequenceIndex(ILinks<TLink> links) : base(links) { }

        public virtual bool Add(IList<TLink> sequence)
        {
            var indexed = true;
            var i = sequence.Count;
            while (--i >= 1 && (indexed =
            ↪  !_equalityComparer.Equals(Links.SearchOrDefault(sequence[i - 1], sequence[i]),
            ↪  default))) { }
            for (; i >= 1; i--)
            {
                Links.GetOrCreate(sequence[i - 1], sequence[i]);
            }
            return indexed;
        }

        public virtual bool MightContain(IList<TLink> sequence)
        {
            var indexed = true;
            var i = sequence.Count;
            while (--i >= 1 && (indexed =
            ↪  !_equalityComparer.Equals(Links.SearchOrDefault(sequence[i - 1], sequence[i]),
            ↪  default))) { }
            return indexed;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Indexes/SynchronizedSequenceIndex.cs

```
using System.Collections.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Indexes
{
    public class SynchronizedSequenceIndex<TLink> : ISequenceIndex<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪  EqualityComparer<TLink>.Default;

        private readonly ISynchronizedLinks<TLink> _links;

        public SynchronizedSequenceIndex(ISynchronizedLinks<TLink> links) => _links = links;

        public bool Add(IList<TLink> sequence)
        {
            var indexed = true;
            var i = sequence.Count;
            var links = _links.Unsync;
            _links.SyncRoot.ExecuteReadOperation(() =>
            {
                while (--i >= 1 && (indexed =
                ↪  !_equalityComparer.Equals(links.SearchOrDefault(sequence[i - 1],
                ↪  sequence[i]), default))) { }
            });
            if (!indexed)
            {
                _links.SyncRoot.ExecuteWriteOperation(() =>
                {
                    for (; i >= 1; i--)
                    {
                        links.GetOrCreate(sequence[i - 1], sequence[i]);
                    }
                });
            }
            return indexed;
        }

        public bool MightContain(IList<TLink> sequence)
        {
            var links = _links.Unsync;
            return _links.SyncRoot.ExecuteReadOperation(() =>
            {
                var indexed = true;
                var i = sequence.Count;
                while (--i >= 1 && (indexed =
                ↪  !_equalityComparer.Equals(links.SearchOrDefault(sequence[i - 1],
                ↪  sequence[i]), default))) { }
                return indexed;
            });
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Indexes/Unindex.cs

```
using System.Collections.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Indexes
{
    public class Unindex<TLink> : ISequenceIndex<TLink>
    {
        public virtual bool Add(IList<TLink> sequence) => false;

        public virtual bool MightContain(IList<TLink> sequence) => true;
    }
}
```

./Platform.Data.Doublets/Sequences/ListFiller.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences
{
    public class ListFiller<TElement, TReturnConstant>
```

```
    {
        protected readonly List<TElement> _list;
        protected readonly TReturnConstant _returnConstant;

        public ListFiller(List<TElement> list, TReturnConstant returnConstant)
        {
            _list = list;
            _returnConstant = returnConstant;
        }

        public ListFiller(List<TElement> list) : this(list, default) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public void Add(TElement element) => _list.Add(element);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public bool AddAndReturnTrue(TElement element)
        {
            _list.Add(element);
            return true;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public bool AddFirstAndReturnTrue(IList<TElement> collection)
        {
            _list.Add(collection[0]);
            return true;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public TReturnConstant AddAndReturnConstant(TElement element)
        {
            _list.Add(element);
            return _returnConstant;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public TReturnConstant AddFirstAndReturnConstant(IList<TElement> collection)
        {
            _list.Add(collection[0]);
            return _returnConstant;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public TReturnConstant AddAllValuesAndReturnConstant(IList<TElement> collection)
        {
            for (int i = 1; i < collection.Count; i++)
            {
                _list.Add(collection[i]);
            }
            return _returnConstant;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Sequences.cs

```
using System;
using System.Collections.Generic;
using System.Linq;
using System.Runtime.CompilerServices;
using Platform.Collections;
using Platform.Collections.Lists;
using Platform.Threading.Synchronization;
using Platform.Singletons;
using LinkIndex = System.UInt64;
using Platform.Data.Doublets.Sequences.Walkers;
using Platform.Collections.Stacks;
using Platform.Collections.Arrays;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences
{
    /// <summary>
    /// Представляет коллекцию последовательностей связей.
    /// </summary>
    /// <remarks>
    /// Обязательно реализовать атомарность каждого публичного метода.
    ///
    /// TODO:
```

```
25      ///
26      /// !!! Повышение вероятности повторного использования групп (подпоследовательностей),
27      /// через естественную группировку по unicode типам, все whitespace вместе, все символы
        ↪ вместе, все числа вместе и т.п.
28      /// + использовать ровно сбалансированный вариант, чтобы уменьшать вложенность (глубину
        ↪ графа)
29      ///
30      /// x*y - найти все связи между, в последовательностях любой формы, если не стоит
        ↪ ограничитель на то, что является последовательностью, а что нет,
31      /// то находятся любые структуры связей, которые содержат эти элементы именно в таком
        ↪ порядке.
32      ///
33      /// Рост последовательности слева и справа.
34      /// Поиск со звёздочкой.
35      /// URL, PURL - реестр используемых во вне ссылок на ресурсы,
36      /// так же проблема может быть решена при реализации дистанционных триггеров.
37      /// Нужны ли уникальные указатели вообще?
38      /// Что если обращение к информации будет происходить через содержимое всегда?
39      ///
40      /// Писать тесты.
41      ///
42      ///
43      /// Можно убрать зависимость от конкретной реализации Links,
44      /// на зависимость от абстрактного элемента, который может быть представлен несколькими
        ↪ способами.
45      ///
46      /// Можно ли как-то сделать один общий интерфейс
47      ///
48      ///
49      /// Блокчейн и/или гит для распределённой записи транзакций.
50      ///
51      /// </remarks>
52      public partial class Sequences : ILinks<LinkIndex> // IList<string>, IList<LinkIndex[]>
        ↪ (после завершения реализации Sequences)
53      {
54          /// <summary>Возвращает значение LinkIndex, обозначающее любое количество
            ↪ связей.</summary>
55          public const LinkIndex ZeroOrMany = LinkIndex.MaxValue;
56
57          public SequencesOptions<LinkIndex> Options { get; }
58          public SynchronizedLinks<LinkIndex> Links { get; }
59          private readonly ISynchronization _sync;
60
61          public LinksConstants<LinkIndex> Constants { get; }
62
63          public Sequences(SynchronizedLinks<LinkIndex> links, SequencesOptions<LinkIndex> options)
64          {
65              Links = links;
66              _sync = links.SyncRoot;
67              Options = options;
68              Options.ValidateOptions();
69              Options.InitOptions(Links);
70              Constants = Default<LinksConstants<LinkIndex>>.Instance;
71          }
72
73          public Sequences(SynchronizedLinks<LinkIndex> links)
74              : this(links, new SequencesOptions<LinkIndex>())
75          {
76          }
77
78          public bool IsSequence(LinkIndex sequence)
79          {
80              return _sync.ExecuteReadOperation(() =>
81              {
82                  if (Options.UseSequenceMarker)
83                  {
84                      return Options.MarkedSequenceMatcher.IsMatched(sequence);
85                  }
86                  return !Links.Unsync.IsPartialPoint(sequence);
87              });
88          }
89
90          [MethodImpl(MethodImplOptions.AggressiveInlining)]
91          private LinkIndex GetSequenceByElements(LinkIndex sequence)
92          {
93              if (Options.UseSequenceMarker)
94              {
95                  return Links.SearchOrDefault(Options.SequenceMarkerLink, sequence);
96              }
```

```
            return sequence;
        }

        private LinkIndex GetSequenceElements(LinkIndex sequence)
        {
            if (Options.UseSequenceMarker)
            {
                var linkContents = new Link<ulong>(Links.GetLink(sequence));
                if (linkContents.Source == Options.SequenceMarkerLink)
                {
                    return linkContents.Target;
                }
                if (linkContents.Target == Options.SequenceMarkerLink)
                {
                    return linkContents.Source;
                }
            }
            return sequence;
        }

        #region Count

        public LinkIndex Count(IList<LinkIndex> restrictions)
        {
            if (restrictions.IsNullOrEmpty())
            {
                return Links.Count(Constants.Any, Options.SequenceMarkerLink, Constants.Any);
            }
            if (restrictions.Count == 1) // Первая связь это адрес
            {
                var sequenceIndex = restrictions[0];
                if (sequenceIndex == Constants.Null)
                {
                    return 0;
                }
                if (sequenceIndex == Constants.Any)
                {
                    return Count(null);
                }
                if (Options.UseSequenceMarker)
                {
                    return Links.Count(Constants.Any, Options.SequenceMarkerLink, sequenceIndex);
                }
                return Links.Exists(sequenceIndex) ? 1UL : 0;
            }
            throw new NotImplementedException();
        }

        private LinkIndex CountUsages(params LinkIndex[] restrictions)
        {
            if (restrictions.Length == 0)
            {
                return 0;
            }
            if (restrictions.Length == 1) // Первая связь это адрес
            {
                if (restrictions[0] == Constants.Null)
                {
                    return 0;
                }
                if (Options.UseSequenceMarker)
                {
                    var elementsLink = GetSequenceElements(restrictions[0]);
                    var sequenceLink = GetSequenceByElements(elementsLink);
                    if (sequenceLink != Constants.Null)
                    {
                        return Links.Count(sequenceLink) + Links.Count(elementsLink) - 1;
                    }
                    return Links.Count(elementsLink);
                }
                return Links.Count(restrictions[0]);
            }
            throw new NotImplementedException();
        }

        #endregion

        #region Create

```

```
176         public LinkIndex Create(IList<LinkIndex> restrictions)
177         {
178             return _sync.ExecuteWriteOperation(() =>
179             {
180                 if (restrictions.IsNullOrEmpty())
181                 {
182                     return Constants.Null;
183                 }
184                 Links.EnsureInnerReferenceExists(restrictions, nameof(restrictions));
185                 return CreateCore(restrictions);
186             });
187         }
188 
189         private LinkIndex CreateCore(IList<LinkIndex> restrictions)
190         {
191             LinkIndex[] sequence = restrictions.ExtractValues();
192             if (Options.UseIndex)
193             {
194                 Options.Index.Add(sequence);
195             }
196             var sequenceRoot = default(LinkIndex);
197             if (Options.EnforceSingleSequenceVersionOnWriteBasedOnExisting)
198             {
199                 var matches = Each(restrictions);
200                 if (matches.Count > 0)
201                 {
202                     sequenceRoot = matches[0];
203                 }
204             }
205             else if (Options.EnforceSingleSequenceVersionOnWriteBasedOnNew)
206             {
207                 return CompactCore(sequence);
208             }
209             if (sequenceRoot == default)
210             {
211                 sequenceRoot = Options.LinksToSequenceConverter.Convert(sequence);
212             }
213             if (Options.UseSequenceMarker)
214             {
215                 Links.Unsync.CreateAndUpdate(Options.SequenceMarkerLink, sequenceRoot);
216             }
217             return sequenceRoot; // Возвращаем корень последовательности (т.е. сами элементы)
218         }
219 
220         #endregion
221 
222         #region Each
223 
224         public List<LinkIndex> Each(IList<LinkIndex> sequence)
225         {
226             var results = new List<LinkIndex>();
227             var filler = new ListFiller<LinkIndex, LinkIndex>(results, Constants.Continue);
228             Each(filler.AddFirstAndReturnConstant, sequence);
229             return results;
230         }
231 
232         public LinkIndex Each(Func<IList<LinkIndex>, LinkIndex> handler, IList<LinkIndex>
    ↪ restrictions)
233         {
234             return _sync.ExecuteReadOperation(() =>
235             {
236                 if (restrictions.IsNullOrEmpty())
237                 {
238                     return Constants.Continue;
239                 }
240                 Links.EnsureInnerReferenceExists(restrictions, nameof(restrictions));
241                 if (restrictions.Count == 1)
242                 {
243                     var link = restrictions[0];
244                     var any = Constants.Any;
245                     if (link == any)
246                     {
247                         if (Options.UseSequenceMarker)
248                         {
249                             return Links.Unsync.Each(handler, new Link<LinkIndex>(any,
                                ↪ Options.SequenceMarkerLink, any));
250                         }
251                         else
```

```
252                         {
253                             return Links.Unsync.Each(handler, new Link<LinkIndex>(any, any,
                                ↪  any));
254                         }
255                     }
256                     var sequence =
                        ↪  Options.Walker.Walk(link).ToArray().ConvertToRestrictionsValues();
257                     sequence[0] = link;
258                     return handler(sequence);
259                 }
260                 else if (restrictions.Count == 2)
261                 {
262                     throw new NotImplementedException();
263                 }
264                 else if (restrictions.Count == 3)
265                 {
266                     return Links.Unsync.Each(handler, restrictions);
267                 }
268                 else
269                 {
270                     var sequence = restrictions.ExtractValues();
271                     if (Options.UseIndex && !Options.Index.MightContain(sequence))
272                     {
273                         return Constants.Break;
274                     }
275                     return EachCore(handler, sequence);
276                 }
277             });
278         }
279 
280         private LinkIndex EachCore(Func<IList<LinkIndex>, LinkIndex> handler, IList<LinkIndex>
            ↪  values)
281         {
282             var matcher = new Matcher(this, values, new HashSet<LinkIndex>(), handler);
283             // TODO: Find out why matcher.HandleFullMatched executed twice for the same sequence
                ↪  Id.
284             Func<IList<LinkIndex>, LinkIndex> innerHandler = Options.UseSequenceMarker ?
                ↪  (Func<IList<LinkIndex>, LinkIndex>)matcher.HandleFullMatchedSequence :
                ↪  matcher.HandleFullMatched;
285             //if (sequence.Length >= 2)
286             if (StepRight(innerHandler, values[0], values[1]) != Constants.Continue)
287             {
288                 return Constants.Break;
289             }
290             var last = values.Count - 2;
291             for (var i = 1; i < last; i++)
292             {
293                 if (PartialStepRight(innerHandler, values[i], values[i + 1]) !=
                    ↪  Constants.Continue)
294                 {
295                     return Constants.Break;
296                 }
297             }
298             if (values.Count >= 3)
299             {
300                 if (StepLeft(innerHandler, values[values.Count - 2], values[values.Count - 1])
                    ↪  != Constants.Continue)
301                 {
302                     return Constants.Break;
303                 }
304             }
305             return Constants.Continue;
306         }
307 
308         private LinkIndex PartialStepRight(Func<IList<LinkIndex>, LinkIndex> handler, LinkIndex
            ↪  left, LinkIndex right)
309         {
310             return Links.Unsync.Each(doublet =>
311             {
312                 var doubletIndex = doublet[Constants.IndexPart];
313                 if (StepRight(handler, doubletIndex, right) != Constants.Continue)
314                 {
315                     return Constants.Break;
316                 }
317                 if (left != doubletIndex)
318                 {
319                     return PartialStepRight(handler, doubletIndex, right);
320                 }
```

```
321                 return Constants.Continue;
322             }, new Link<LinkIndex>(Constants.Any, Constants.Any, left));
323         }
324 
325         private LinkIndex StepRight(Func<IList<LinkIndex>, LinkIndex> handler, LinkIndex left,
        ↪   LinkIndex right) => Links.Unsync.Each(rightStep => TryStepRightUp(handler, right,
        ↪   rightStep[Constants.IndexPart]), new Link<LinkIndex>(Constants.Any, left,
        ↪   Constants.Any));
326 
327         private LinkIndex TryStepRightUp(Func<IList<LinkIndex>, LinkIndex> handler, LinkIndex
        ↪   right, LinkIndex stepFrom)
328         {
329             var upStep = stepFrom;
330             var firstSource = Links.Unsync.GetTarget(upStep);
331             while (firstSource != right && firstSource != upStep)
332             {
333                 upStep = firstSource;
334                 firstSource = Links.Unsync.GetSource(upStep);
335             }
336             if (firstSource == right)
337             {
338                 return handler(new LinkAddress<LinkIndex>(stepFrom));
339             }
340             return Constants.Continue;
341         }
342 
343         private LinkIndex StepLeft(Func<IList<LinkIndex>, LinkIndex> handler, LinkIndex left,
        ↪   LinkIndex right) => Links.Unsync.Each(leftStep => TryStepLeftUp(handler, left,
        ↪   leftStep[Constants.IndexPart]), new Link<LinkIndex>(Constants.Any, Constants.Any,
        ↪   right));
344 
345         private LinkIndex TryStepLeftUp(Func<IList<LinkIndex>, LinkIndex> handler, LinkIndex
        ↪   left, LinkIndex stepFrom)
346         {
347             var upStep = stepFrom;
348             var firstTarget = Links.Unsync.GetSource(upStep);
349             while (firstTarget != left && firstTarget != upStep)
350             {
351                 upStep = firstTarget;
352                 firstTarget = Links.Unsync.GetTarget(upStep);
353             }
354             if (firstTarget == left)
355             {
356                 return handler(new LinkAddress<LinkIndex>(stepFrom));
357             }
358             return Constants.Continue;
359         }
360 
361         #endregion
362 
363         #region Update
364 
365         public LinkIndex Update(IList<LinkIndex> restrictions, IList<LinkIndex> substitution)
366         {
367             var sequence = restrictions.ExtractValues();
368             var newSequence = substitution.ExtractValues();
369 
370             if (sequence.IsNullOrEmpty() && newSequence.IsNullOrEmpty())
371             {
372                 return Constants.Null;
373             }
374             if (sequence.IsNullOrEmpty())
375             {
376                 return Create(substitution);
377             }
378             if (newSequence.IsNullOrEmpty())
379             {
380                 Delete(restrictions);
381                 return Constants.Null;
382             }
383             return _sync.ExecuteWriteOperation(() =>
384             {
385                 Links.EnsureEachLinkIsAnyOrExists(sequence);
386                 Links.EnsureEachLinkExists(newSequence);
387                 return UpdateCore(sequence, newSequence);
388             });
389         }
390 
391         private LinkIndex UpdateCore(LinkIndex[] sequence, LinkIndex[] newSequence)
```

```
392         {
393             LinkIndex bestVariant;
394             if (Options.EnforceSingleSequenceVersionOnWriteBasedOnNew &&
                ↪  !sequence.EqualTo(newSequence))
395             {
396                 bestVariant = CompactCore(newSequence);
397             }
398             else
399             {
400                 bestVariant = CreateCore(newSequence);
401             }
402             // TODO: Check all options only ones before loop execution
403             // Возможно нужно две версии Each, возвращающий фактические последовательности и с
                ↪  маркером,
404             // или возможно даже возвращать и тот и тот вариант. С другой стороны все варианты
                ↪  можно получить имея только фактические последовательности.
405             foreach (var variant in Each(sequence))
406             {
407                 if (variant != bestVariant)
408                 {
409                     UpdateOneCore(variant, bestVariant);
410                 }
411             }
412             return bestVariant;
413         }
414
415         private void UpdateOneCore(LinkIndex sequence, LinkIndex newSequence)
416         {
417             if (Options.UseGarbageCollection)
418             {
419                 var sequenceElements = GetSequenceElements(sequence);
420                 var sequenceElementsContents = new Link<ulong>(Links.GetLink(sequenceElements));
421                 var sequenceLink = GetSequenceByElements(sequenceElements);
422                 var newSequenceElements = GetSequenceElements(newSequence);
423                 var newSequenceLink = GetSequenceByElements(newSequenceElements);
424                 if (Options.UseCascadeUpdate || CountUsages(sequence) == 0)
425                 {
426                     if (sequenceLink != Constants.Null)
427                     {
428                         Links.Unsync.MergeUsages(sequenceLink, newSequenceLink);
429                     }
430                     Links.Unsync.MergeUsages(sequenceElements, newSequenceElements);
431                 }
432                 ClearGarbage(sequenceElementsContents.Source);
433                 ClearGarbage(sequenceElementsContents.Target);
434             }
435             else
436             {
437                 if (Options.UseSequenceMarker)
438                 {
439                     var sequenceElements = GetSequenceElements(sequence);
440                     var sequenceLink = GetSequenceByElements(sequenceElements);
441                     var newSequenceElements = GetSequenceElements(newSequence);
442                     var newSequenceLink = GetSequenceByElements(newSequenceElements);
443                     if (Options.UseCascadeUpdate || CountUsages(sequence) == 0)
444                     {
445                         if (sequenceLink != Constants.Null)
446                         {
447                             Links.Unsync.MergeUsages(sequenceLink, newSequenceLink);
448                         }
449                         Links.Unsync.MergeUsages(sequenceElements, newSequenceElements);
450                     }
451                 }
452                 else
453                 {
454                     if (Options.UseCascadeUpdate || CountUsages(sequence) == 0)
455                     {
456                         Links.Unsync.MergeUsages(sequence, newSequence);
457                     }
458                 }
459             }
460         }
461
462         #endregion
463
464         #region Delete
465
466         public void Delete(IList<LinkIndex> restrictions)
```

```
        {
            _sync.ExecuteWriteOperation(() =>
            {
                var sequence = restrictions.ExtractValues();
                // TODO: Check all options only ones before loop execution
                foreach (var linkToDelete in Each(sequence))
                {
                    DeleteOneCore(linkToDelete);
                }
            });
        }

        private void DeleteOneCore(LinkIndex link)
        {
            if (Options.UseGarbageCollection)
            {
                var sequenceElements = GetSequenceElements(link);
                var sequenceElementsContents = new Link<ulong>(Links.GetLink(sequenceElements));
                var sequenceLink = GetSequenceByElements(sequenceElements);
                if (Options.UseCascadeDelete || CountUsages(link) == 0)
                {
                    if (sequenceLink != Constants.Null)
                    {
                        Links.Unsync.Delete(sequenceLink);
                    }
                    Links.Unsync.Delete(link);
                }
                ClearGarbage(sequenceElementsContents.Source);
                ClearGarbage(sequenceElementsContents.Target);
            }
            else
            {
                if (Options.UseSequenceMarker)
                {
                    var sequenceElements = GetSequenceElements(link);
                    var sequenceLink = GetSequenceByElements(sequenceElements);
                    if (Options.UseCascadeDelete || CountUsages(link) == 0)
                    {
                        if (sequenceLink != Constants.Null)
                        {
                            Links.Unsync.Delete(sequenceLink);
                        }
                        Links.Unsync.Delete(link);
                    }
                }
                else
                {
                    if (Options.UseCascadeDelete || CountUsages(link) == 0)
                    {
                        Links.Unsync.Delete(link);
                    }
                }
            }
        }

        #endregion

        #region Compactification

        /// <remarks>
        /// bestVariant можно выбирать по максимальному числу использований,
        /// но балансированный позволяет гарантировать уникальность (если есть возможность,
        /// гарантировать его использование в других местах).
        ///
        /// Получается этот метод должен игнорировать Options.EnforceSingleSequenceVersionOnWrite
        /// </remarks>
        public LinkIndex Compact(params LinkIndex[] sequence)
        {
            return _sync.ExecuteWriteOperation(() =>
            {
                if (sequence.IsNullOrEmpty())
                {
                    return Constants.Null;
                }
                Links.EnsureEachLinkExists(sequence);
                return CompactCore(sequence);
            });
        }
```

```
545
546         [MethodImpl(MethodImplOptions.AggressiveInlining)]
547         private LinkIndex CompactCore(params LinkIndex[] sequence) => UpdateCore(sequence,
            ↪ sequence);
548
549         #endregion
550
551         #region Garbage Collection
552
553         /// <remarks>
554         /// TODO: Добавить дополнительный обработчик / событие CanBeDeleted которое можно
            ↪ определить извне или в унаследованном классе
555         /// </remarks>
556         [MethodImpl(MethodImplOptions.AggressiveInlining)]
557         private bool IsGarbage(LinkIndex link) => link != Options.SequenceMarkerLink &&
            ↪ !Links.Unsync.IsPartialPoint(link) && Links.Count(link) == 0;
558
559         private void ClearGarbage(LinkIndex link)
560         {
561             if (IsGarbage(link))
562             {
563                 var contents = new Link<ulong>(Links.GetLink(link));
564                 Links.Unsync.Delete(link);
565                 ClearGarbage(contents.Source);
566                 ClearGarbage(contents.Target);
567             }
568         }
569
570         #endregion
571
572         #region Walkers
573
574         public bool EachPart(Func<LinkIndex, bool> handler, LinkIndex sequence)
575         {
576             return _sync.ExecuteReadOperation(() =>
577             {
578                 var links = Links.Unsync;
579                 foreach (var part in Options.Walker.Walk(sequence))
580                 {
581                     if (!handler(part))
582                     {
583                         return false;
584                     }
585                 }
586                 return true;
587             });
588         }
589
590         public class Matcher : RightSequenceWalker<LinkIndex>
591         {
592             private readonly Sequences _sequences;
593             private readonly IList<LinkIndex> _patternSequence;
594             private readonly HashSet<LinkIndex> _linksInSequence;
595             private readonly HashSet<LinkIndex> _results;
596             private readonly Func<IList<LinkIndex>, LinkIndex> _stopableHandler;
597             private readonly HashSet<LinkIndex> _readAsElements;
598             private int _filterPosition;
599
600             public Matcher(Sequences sequences, IList<LinkIndex> patternSequence,
                ↪ HashSet<LinkIndex> results, Func<IList<LinkIndex>, LinkIndex> stopableHandler,
                ↪ HashSet<LinkIndex> readAsElements = null)
601                 : base(sequences.Links.Unsync, new DefaultStack<LinkIndex>())
602             {
603                 _sequences = sequences;
604                 _patternSequence = patternSequence;
605                 _linksInSequence = new HashSet<LinkIndex>(patternSequence.Where(x => x !=
                    ↪ Links.Constants.Any && x != ZeroOrMany));
606                 _results = results;
607                 _stopableHandler = stopableHandler;
608                 _readAsElements = readAsElements;
609             }
610
611             protected override bool IsElement(LinkIndex link) => base.IsElement(link) ||
                ↪ (_readAsElements != null && _readAsElements.Contains(link)) ||
                ↪ _linksInSequence.Contains(link);
612
613             public bool FullMatch(LinkIndex sequenceToMatch)
614             {
615                 _filterPosition = 0;
616                 foreach (var part in Walk(sequenceToMatch))
```

```
617                 {
618                     if (!FullMatchCore(part))
619                     {
620                         break;
621                     }
622                 }
623                 return _filterPosition == _patternSequence.Count;
624             }
625 
626             private bool FullMatchCore(LinkIndex element)
627             {
628                 if (_filterPosition == _patternSequence.Count)
629                 {
630                     _filterPosition = -2; // Длиннее чем нужно
631                     return false;
632                 }
633                 if (_patternSequence[_filterPosition] != Links.Constants.Any
634                  && element != _patternSequence[_filterPosition])
635                 {
636                     _filterPosition = -1;
637                     return false; // Начинается/Продолжается иначе
638                 }
639                 _filterPosition++;
640                 return true;
641             }
642 
643             public void AddFullMatchedToResults(IList<LinkIndex> restrictions)
644             {
645                 var sequenceToMatch = restrictions[Links.Constants.IndexPart];
646                 if (FullMatch(sequenceToMatch))
647                 {
648                     _results.Add(sequenceToMatch);
649                 }
650             }
651 
652             public LinkIndex HandleFullMatched(IList<LinkIndex> restrictions)
653             {
654                 var sequenceToMatch = restrictions[Links.Constants.IndexPart];
655                 if (FullMatch(sequenceToMatch) && _results.Add(sequenceToMatch))
656                 {
657                     return _stopableHandler(new LinkAddress<LinkIndex>(sequenceToMatch));
658                 }
659                 return Links.Constants.Continue;
660             }
661 
662             public LinkIndex HandleFullMatchedSequence(IList<LinkIndex> restrictions)
663             {
664                 var sequenceToMatch = restrictions[Links.Constants.IndexPart];
665                 var sequence = _sequences.GetSequenceByElements(sequenceToMatch);
666                 if (sequence != Links.Constants.Null && FullMatch(sequenceToMatch) &&
                    ↪  _results.Add(sequenceToMatch))
667                 {
668                     return _stopableHandler(new LinkAddress<LinkIndex>(sequence));
669                 }
670                 return Links.Constants.Continue;
671             }
672 
673             /// <remarks>
674             /// TODO: Add support for LinksConstants.Any
675             /// </remarks>
676             public bool PartialMatch(LinkIndex sequenceToMatch)
677             {
678                 _filterPosition = -1;
679                 foreach (var part in Walk(sequenceToMatch))
680                 {
681                     if (!PartialMatchCore(part))
682                     {
683                         break;
684                     }
685                 }
686                 return _filterPosition == _patternSequence.Count - 1;
687             }
688 
689             private bool PartialMatchCore(LinkIndex element)
690             {
691                 if (_filterPosition == (_patternSequence.Count - 1))
692                 {
693                     return false; // Нашлось
694                 }
```

```
                if (_filterPosition >= 0)
                {
                    if (element == _patternSequence[_filterPosition + 1])
                    {
                        _filterPosition++;
                    }
                    else
                    {
                        _filterPosition = -1;
                    }
                }
                if (_filterPosition < 0)
                {
                    if (element == _patternSequence[0])
                    {
                        _filterPosition = 0;
                    }
                }
                return true; // Ищем дальше
            }

            public void AddPartialMatchedToResults(LinkIndex sequenceToMatch)
            {
                if (PartialMatch(sequenceToMatch))
                {
                    _results.Add(sequenceToMatch);
                }
            }

            public LinkIndex HandlePartialMatched(IList<LinkIndex> restrictions)
            {
                var sequenceToMatch = restrictions[Links.Constants.IndexPart];
                if (PartialMatch(sequenceToMatch))
                {
                    return _stopableHandler(new LinkAddress<LinkIndex>(sequenceToMatch));
                }
                return Links.Constants.Continue;
            }

            public void AddAllPartialMatchedToResults(IEnumerable<LinkIndex> sequencesToMatch)
            {
                foreach (var sequenceToMatch in sequencesToMatch)
                {
                    if (PartialMatch(sequenceToMatch))
                    {
                        _results.Add(sequenceToMatch);
                    }
                }
            }

            public void AddAllPartialMatchedToResultsAndReadAsElements(IEnumerable<LinkIndex>
            ↪  sequencesToMatch)
            {
                foreach (var sequenceToMatch in sequencesToMatch)
                {
                    if (PartialMatch(sequenceToMatch))
                    {
                        _readAsElements.Add(sequenceToMatch);
                        _results.Add(sequenceToMatch);
                    }
                }
            }
        }

        #endregion
    }
}
```

./Platform.Data.Doublets/Sequences/Sequences.Experiments.cs

```
using System;
using LinkIndex = System.UInt64;
using System.Collections.Generic;
using Stack = System.Collections.Generic.Stack<ulong>;
using System.Linq;
using System.Text;
using Platform.Collections;
using Platform.Data.Exceptions;
using Platform.Data.Sequences;
using Platform.Data.Doublets.Sequences.Frequencies.Counters;
```

```
11  using Platform.Data.Doublets.Sequences.Walkers;
12  using Platform.Collections.Stacks;
13
14  #pragma warning disable CS1591 // Missing XML comment for publicly visible type or member
15
16  namespace Platform.Data.Doublets.Sequences
17  {
18      partial class Sequences
19      {
20          #region Create All Variants (Not Practical)
21
22          /// <remarks>
23          /// Number of links that is needed to generate all variants for
24          /// sequence of length N corresponds to https://oeis.org/A014143/list sequence.
25          /// </remarks>
26          public ulong[] CreateAllVariants2(ulong[] sequence)
27          {
28              return _sync.ExecuteWriteOperation(() =>
29              {
30                  if (sequence.IsNullOrEmpty())
31                  {
32                      return new ulong[0];
33                  }
34                  Links.EnsureEachLinkExists(sequence);
35                  if (sequence.Length == 1)
36                  {
37                      return sequence;
38                  }
39                  return CreateAllVariants2Core(sequence, 0, sequence.Length - 1);
40              });
41          }
42
43          private ulong[] CreateAllVariants2Core(ulong[] sequence, long startAt, long stopAt)
44          {
45  #if DEBUG
46              if ((stopAt - startAt) < 0)
47              {
48                  throw new ArgumentOutOfRangeException(nameof(startAt), "startAt должен быть
                    ↪  меньше или равен stopAt");
49              }
50  #endif
51              if ((stopAt - startAt) == 0)
52              {
53                  return new[] { sequence[startAt] };
54              }
55              if ((stopAt - startAt) == 1)
56              {
57                  return new[] { Links.Unsync.CreateAndUpdate(sequence[startAt], sequence[stopAt])
                    ↪  };
58              }
59              var variants = new ulong[(ulong)Platform.Numbers.Math.Catalan(stopAt - startAt)];
60              var last = 0;
61              for (var splitter = startAt; splitter < stopAt; splitter++)
62              {
63                  var left = CreateAllVariants2Core(sequence, startAt, splitter);
64                  var right = CreateAllVariants2Core(sequence, splitter + 1, stopAt);
65                  for (var i = 0; i < left.Length; i++)
66                  {
67                      for (var j = 0; j < right.Length; j++)
68                      {
69                          var variant = Links.Unsync.CreateAndUpdate(left[i], right[j]);
70                          if (variant == Constants.Null)
71                          {
72                              throw new NotImplementedException("Creation cancellation is not
                                ↪  implemented.");
73                          }
74                          variants[last++] = variant;
75                      }
76                  }
77              }
78              return variants;
79          }
80
81          public List<ulong> CreateAllVariants1(params ulong[] sequence)
82          {
83              return _sync.ExecuteWriteOperation(() =>
84              {
85                  if (sequence.IsNullOrEmpty())
```

```
            {
                return new List<ulong>();
            }
            Links.Unsync.EnsureEachLinkExists(sequence);
            if (sequence.Length == 1)
            {
                return new List<ulong> { sequence[0] };
            }
            var results = new
            ↪  List<ulong>((int)Platform.Numbers.Math.Catalan(sequence.Length));
            return CreateAllVariants1Core(sequence, results);
        });
    }

    private List<ulong> CreateAllVariants1Core(ulong[] sequence, List<ulong> results)
    {
        if (sequence.Length == 2)
        {
            var link = Links.Unsync.CreateAndUpdate(sequence[0], sequence[1]);
            if (link == Constants.Null)
            {
                throw new NotImplementedException("Creation cancellation is not
                ↪  implemented.");
            }
            results.Add(link);
            return results;
        }
        var innerSequenceLength = sequence.Length - 1;
        var innerSequence = new ulong[innerSequenceLength];
        for (var li = 0; li < innerSequenceLength; li++)
        {
            var link = Links.Unsync.CreateAndUpdate(sequence[li], sequence[li + 1]);
            if (link == Constants.Null)
            {
                throw new NotImplementedException("Creation cancellation is not
                ↪  implemented.");
            }
            for (var isi = 0; isi < li; isi++)
            {
                innerSequence[isi] = sequence[isi];
            }
            innerSequence[li] = link;
            for (var isi = li + 1; isi < innerSequenceLength; isi++)
            {
                innerSequence[isi] = sequence[isi + 1];
            }
            CreateAllVariants1Core(innerSequence, results);
        }
        return results;
    }

    #endregion

    public HashSet<ulong> Each1(params ulong[] sequence)
    {
        var visitedLinks = new HashSet<ulong>(); // Заменить на bitstring
        Each1(link =>
        {
            if (!visitedLinks.Contains(link))
            {
                visitedLinks.Add(link); // изучить почему случаются повторы
            }
            return true;
        }, sequence);
        return visitedLinks;
    }

    private void Each1(Func<ulong, bool> handler, params ulong[] sequence)
    {
        if (sequence.Length == 2)
        {
            Links.Unsync.Each(sequence[0], sequence[1], handler);
        }
        else
        {
            var innerSequenceLength = sequence.Length - 1;
            for (var li = 0; li < innerSequenceLength; li++)
            {
```

```
                var left = sequence[li];
                var right = sequence[li + 1];
                if (left == 0 && right == 0)
                {
                    continue;
                }
                var linkIndex = li;
                ulong[] innerSequence = null;
                Links.Unsync.Each(doublet =>
                {
                    if (innerSequence == null)
                    {
                        innerSequence = new ulong[innerSequenceLength];
                        for (var isi = 0; isi < linkIndex; isi++)
                        {
                            innerSequence[isi] = sequence[isi];
                        }
                        for (var isi = linkIndex + 1; isi < innerSequenceLength; isi++)
                        {
                            innerSequence[isi] = sequence[isi + 1];
                        }
                    }
                    innerSequence[linkIndex] = doublet[Constants.IndexPart];
                    Each1(handler, innerSequence);
                    return Constants.Continue;
                }, Constants.Any, left, right);
            }
        }
    }

    public HashSet<ulong> EachPart(params ulong[] sequence)
    {
        var visitedLinks = new HashSet<ulong>(); // Заменить на bitstring
        EachPartCore(link =>
        {
            var linkIndex = link[Constants.IndexPart];
            if (!visitedLinks.Contains(linkIndex))
            {
                visitedLinks.Add(linkIndex); // изучить почему случаются повторы
            }
            return Constants.Continue;
        }, sequence);
        return visitedLinks;
    }

    public void EachPart(Func<IList<LinkIndex>, LinkIndex> handler, params ulong[] sequence)
    {
        var visitedLinks = new HashSet<ulong>(); // Заменить на bitstring
        EachPartCore(link =>
        {
            var linkIndex = link[Constants.IndexPart];
            if (!visitedLinks.Contains(linkIndex))
            {
                visitedLinks.Add(linkIndex); // изучить почему случаются повторы
                return handler(new LinkAddress<LinkIndex>(linkIndex));
            }
            return Constants.Continue;
        }, sequence);
    }

    private void EachPartCore(Func<IList<LinkIndex>, LinkIndex> handler, params ulong[]
    ↪ sequence)
    {
        if (sequence.IsNullOrEmpty())
        {
            return;
        }
        Links.EnsureEachLinkIsAnyOrExists(sequence);
        if (sequence.Length == 1)
        {
            var link = sequence[0];
            if (link > 0)
            {
                handler(new LinkAddress<LinkIndex>(link));
            }
            else
            {
                Links.Each(Constants.Any, Constants.Any, handler);
```

```
                }
            }
            else if (sequence.Length == 2)
            {
                //_links.Each(sequence[0], sequence[1], handler);
                //  o_|      x_o ...
                // x_|        |___|
                Links.Each(sequence[1], Constants.Any, doublet =>
                {
                    var match = Links.SearchOrDefault(sequence[0], doublet);
                    if (match != Constants.Null)
                    {
                        handler(new LinkAddress<LinkIndex>(match));
                    }
                    return true;
                });
                // |_x      ... x_o
                //  |_o      |___|
                Links.Each(Constants.Any, sequence[0], doublet =>
                {
                    var match = Links.SearchOrDefault(doublet, sequence[1]);
                    if (match != 0)
                    {
                        handler(new LinkAddress<LinkIndex>(match));
                    }
                    return true;
                });
                //           ._x o_.
                //            |___|
                PartialStepRight(x => handler(x), sequence[0], sequence[1]);
            }
            else
            {
                throw new NotImplementedException();
            }
        }

        private void PartialStepRight(Action<IList<LinkIndex>> handler, ulong left, ulong right)
        {
            Links.Unsync.Each(Constants.Any, left, doublet =>
            {
                StepRight(handler, doublet, right);
                if (left != doublet)
                {
                    PartialStepRight(handler, doublet, right);
                }
                return true;
            });
        }

        private void StepRight(Action<IList<LinkIndex>> handler, ulong left, ulong right)
        {
            Links.Unsync.Each(left, Constants.Any, rightStep =>
            {
                TryStepRightUp(handler, right, rightStep);
                return true;
            });
        }

        private void TryStepRightUp(Action<IList<LinkIndex>> handler, ulong right, ulong
        ↪  stepFrom)
        {
            var upStep = stepFrom;
            var firstSource = Links.Unsync.GetTarget(upStep);
            while (firstSource != right && firstSource != upStep)
            {
                upStep = firstSource;
                firstSource = Links.Unsync.GetSource(upStep);
            }
            if (firstSource == right)
            {
                handler(new LinkAddress<LinkIndex>(stepFrom));
            }
        }

        // TODO: Test
        private void PartialStepLeft(Action<IList<LinkIndex>> handler, ulong left, ulong right)
        {
```

```
            Links.Unsync.Each(right, Constants.Any, doublet =>
            {
                StepLeft(handler, left, doublet);
                if (right != doublet)
                {
                    PartialStepLeft(handler, left, doublet);
                }
                return true;
            });
        }

        private void StepLeft(Action<IList<LinkIndex>> handler, ulong left, ulong right)
        {
            Links.Unsync.Each(Constants.Any, right, leftStep =>
            {
                TryStepLeftUp(handler, left, leftStep);
                return true;
            });
        }

        private void TryStepLeftUp(Action<IList<LinkIndex>> handler, ulong left, ulong stepFrom)
        {
            var upStep = stepFrom;
            var firstTarget = Links.Unsync.GetSource(upStep);
            while (firstTarget != left && firstTarget != upStep)
            {
                upStep = firstTarget;
                firstTarget = Links.Unsync.GetTarget(upStep);
            }
            if (firstTarget == left)
            {
                handler(new LinkAddress<LinkIndex>(stepFrom));
            }
        }

        private bool StartsWith(ulong sequence, ulong link)
        {
            var upStep = sequence;
            var firstSource = Links.Unsync.GetSource(upStep);
            while (firstSource != link && firstSource != upStep)
            {
                upStep = firstSource;
                firstSource = Links.Unsync.GetSource(upStep);
            }
            return firstSource == link;
        }

        private bool EndsWith(ulong sequence, ulong link)
        {
            var upStep = sequence;
            var lastTarget = Links.Unsync.GetTarget(upStep);
            while (lastTarget != link && lastTarget != upStep)
            {
                upStep = lastTarget;
                lastTarget = Links.Unsync.GetTarget(upStep);
            }
            return lastTarget == link;
        }

        public List<ulong> GetAllMatchingSequences0(params ulong[] sequence)
        {
            return _sync.ExecuteReadOperation(() =>
            {
                var results = new List<ulong>();
                if (sequence.Length > 0)
                {
                    Links.EnsureEachLinkExists(sequence);
                    var firstElement = sequence[0];
                    if (sequence.Length == 1)
                    {
                        results.Add(firstElement);
                        return results;
                    }
                    if (sequence.Length == 2)
                    {
                        var doublet = Links.SearchOrDefault(firstElement, sequence[1]);
                        if (doublet != Constants.Null)
                        {
                            results.Add(doublet);
```

```
                    }
                    return results;
                }
                var linksInSequence = new HashSet<ulong>(sequence);
                void handler(IList<LinkIndex> result)
                {
                    var resultIndex = result[Links.Constants.IndexPart];
                    var filterPosition = 0;
                    StopableSequenceWalker.WalkRight(resultIndex, Links.Unsync.GetSource,
                    ↪  Links.Unsync.GetTarget,
                        x => linksInSequence.Contains(x) || Links.Unsync.GetTarget(x) == x,
                        ↪  x =>
                        {
                            if (filterPosition == sequence.Length)
                            {
                                filterPosition = -2; // Длиннее чем нужно
                                return false;
                            }
                            if (x != sequence[filterPosition])
                            {
                                filterPosition = -1;
                                return false; // Начинается иначе
                            }
                            filterPosition++;

                            return true;
                        });
                    if (filterPosition == sequence.Length)
                    {
                        results.Add(resultIndex);
                    }
                }
                if (sequence.Length >= 2)
                {
                    StepRight(handler, sequence[0], sequence[1]);
                }
                var last = sequence.Length - 2;
                for (var i = 1; i < last; i++)
                {
                    PartialStepRight(handler, sequence[i], sequence[i + 1]);
                }
                if (sequence.Length >= 3)
                {
                    StepLeft(handler, sequence[sequence.Length - 2],
                    ↪  sequence[sequence.Length - 1]);
                }
            }
            return results;
        });
    }

    public HashSet<ulong> GetAllMatchingSequences1(params ulong[] sequence)
    {
        return _sync.ExecuteReadOperation(() =>
        {
            var results = new HashSet<ulong>();
            if (sequence.Length > 0)
            {
                Links.EnsureEachLinkExists(sequence);
                var firstElement = sequence[0];
                if (sequence.Length == 1)
                {
                    results.Add(firstElement);
                    return results;
                }
                if (sequence.Length == 2)
                {
                    var doublet = Links.SearchOrDefault(firstElement, sequence[1]);
                    if (doublet != Constants.Null)
                    {
                        results.Add(doublet);
                    }
                    return results;
                }
                var matcher = new Matcher(this, sequence, results, null);
                if (sequence.Length >= 2)
                {
                    StepRight(matcher.AddFullMatchedToResults, sequence[0], sequence[1]);
                }
```

```
                var last = sequence.Length - 2;
                for (var i = 1; i < last; i++)
                {
                    PartialStepRight(matcher.AddFullMatchedToResults, sequence[i],
                    ↪  sequence[i + 1]);
                }
                if (sequence.Length >= 3)
                {
                    StepLeft(matcher.AddFullMatchedToResults, sequence[sequence.Length - 2],
                    ↪  sequence[sequence.Length - 1]);
                }
            }
            return results;
        });
    }

    public const int MaxSequenceFormatSize = 200;

    public string FormatSequence(LinkIndex sequenceLink, params LinkIndex[] knownElements)
    ↪  => FormatSequence(sequenceLink, (sb, x) => sb.Append(x), true, knownElements);

    public string FormatSequence(LinkIndex sequenceLink, Action<StringBuilder, LinkIndex>
    ↪  elementToString, bool insertComma, params LinkIndex[] knownElements) =>
    ↪  Links.SyncRoot.ExecuteReadOperation(() => FormatSequence(Links.Unsync, sequenceLink,
    ↪  elementToString, insertComma, knownElements));

    private string FormatSequence(ILinks<LinkIndex> links, LinkIndex sequenceLink,
    ↪  Action<StringBuilder, LinkIndex> elementToString, bool insertComma, params
    ↪  LinkIndex[] knownElements)
    {
        var linksInSequence = new HashSet<ulong>(knownElements);
        //var entered = new HashSet<ulong>();
        var sb = new StringBuilder();
        sb.Append('{');
        if (links.Exists(sequenceLink))
        {
            StopableSequenceWalker.WalkRight(sequenceLink, links.GetSource, links.GetTarget,
                x => linksInSequence.Contains(x) || links.IsPartialPoint(x), element => //
                ↪  entered.AddAndReturnVoid, x => { }, entered.DoNotContains
                {
                    if (insertComma && sb.Length > 1)
                    {
                        sb.Append(',');
                    }
                    //if (entered.Contains(element))
                    //{
                    //    sb.Append('{');
                    //    elementToString(sb, element);
                    //    sb.Append('}');
                    //}
                    //else
                    elementToString(sb, element);
                    if (sb.Length < MaxSequenceFormatSize)
                    {
                        return true;
                    }
                    sb.Append(insertComma ? ", ..." : "...");
                    return false;
                });
        }
        sb.Append('}');
        return sb.ToString();
    }

    public string SafeFormatSequence(LinkIndex sequenceLink, params LinkIndex[]
    ↪  knownElements) => SafeFormatSequence(sequenceLink, (sb, x) => sb.Append(x), true,
    ↪  knownElements);

    public string SafeFormatSequence(LinkIndex sequenceLink, Action<StringBuilder,
    ↪  LinkIndex> elementToString, bool insertComma, params LinkIndex[] knownElements) =>
    ↪  Links.SyncRoot.ExecuteReadOperation(() => SafeFormatSequence(Links.Unsync,
    ↪  sequenceLink, elementToString, insertComma, knownElements));

    private string SafeFormatSequence(ILinks<LinkIndex> links, LinkIndex sequenceLink,
    ↪  Action<StringBuilder, LinkIndex> elementToString, bool insertComma, params
    ↪  LinkIndex[] knownElements)
    {
```

```
            var linksInSequence = new HashSet<ulong>(knownElements);
            var entered = new HashSet<ulong>();
            var sb = new StringBuilder();
            sb.Append('{');
            if (links.Exists(sequenceLink))
            {
                StopableSequenceWalker.WalkRight(sequenceLink, links.GetSource, links.GetTarget,
                    x => linksInSequence.Contains(x) || links.IsFullPoint(x),
                    ↪ entered.AddAndReturnVoid, x => { }, entered.DoNotContains, element =>
                    {
                        if (insertComma && sb.Length > 1)
                        {
                            sb.Append(',');
                        }
                        if (entered.Contains(element))
                        {
                            sb.Append('{');
                            elementToString(sb, element);
                            sb.Append('}');
                        }
                        else
                        {
                            elementToString(sb, element);
                        }
                        if (sb.Length < MaxSequenceFormatSize)
                        {
                            return true;
                        }
                        sb.Append(insertComma ? ", ..." : "...");
                        return false;
                    });
            }
            sb.Append('}');
            return sb.ToString();
        }

        public List<ulong> GetAllPartiallyMatchingSequences0(params ulong[] sequence)
        {
            return _sync.ExecuteReadOperation(() =>
            {
                if (sequence.Length > 0)
                {
                    Links.EnsureEachLinkExists(sequence);
                    var results = new HashSet<ulong>();
                    for (var i = 0; i < sequence.Length; i++)
                    {
                        AllUsagesCore(sequence[i], results);
                    }
                    var filteredResults = new List<ulong>();
                    var linksInSequence = new HashSet<ulong>(sequence);
                    foreach (var result in results)
                    {
                        var filterPosition = -1;
                        StopableSequenceWalker.WalkRight(result, Links.Unsync.GetSource,
                            ↪ Links.Unsync.GetTarget,
                            x => linksInSequence.Contains(x) || Links.Unsync.GetTarget(x) == x,
                            ↪ x =>
                            {
                                if (filterPosition == (sequence.Length - 1))
                                {
                                    return false;
                                }
                                if (filterPosition >= 0)
                                {
                                    if (x == sequence[filterPosition + 1])
                                    {
                                        filterPosition++;
                                    }
                                    else
                                    {
                                        return false;
                                    }
                                }
                                if (filterPosition < 0)
                                {
                                    if (x == sequence[0])
                                    {
                                        filterPosition = 0;
```

```
                                }
                            }
                            return true;
                        });
                    if (filterPosition == (sequence.Length - 1))
                    {
                        filteredResults.Add(result);
                    }
                }
                return filteredResults;
            }
            return new List<ulong>();
        });
    }

    public HashSet<ulong> GetAllPartiallyMatchingSequences1(params ulong[] sequence)
    {
        return _sync.ExecuteReadOperation(() =>
        {
            if (sequence.Length > 0)
            {
                Links.EnsureEachLinkExists(sequence);
                var results = new HashSet<ulong>();
                for (var i = 0; i < sequence.Length; i++)
                {
                    AllUsagesCore(sequence[i], results);
                }
                var filteredResults = new HashSet<ulong>();
                var matcher = new Matcher(this, sequence, filteredResults, null);
                matcher.AddAllPartialMatchedToResults(results);
                return filteredResults;
            }
            return new HashSet<ulong>();
        });
    }

    public bool GetAllPartiallyMatchingSequences2(Func<IList<LinkIndex>, LinkIndex> handler,
    ↪  params ulong[] sequence)
    {
        return _sync.ExecuteReadOperation(() =>
        {
            if (sequence.Length > 0)
            {
                Links.EnsureEachLinkExists(sequence);

                var results = new HashSet<ulong>();
                var filteredResults = new HashSet<ulong>();
                var matcher = new Matcher(this, sequence, filteredResults, handler);
                for (var i = 0; i < sequence.Length; i++)
                {
                    if (!AllUsagesCore1(sequence[i], results, matcher.HandlePartialMatched))
                    {
                        return false;
                    }
                }
                return true;
            }
            return true;
        });
    }

    //public HashSet<ulong> GetAllPartiallyMatchingSequences3(params ulong[] sequence)
    //{
    //    return Sync.ExecuteReadOperation(() =>
    //    {
    //        if (sequence.Length > 0)
    //        {
    //            _links.EnsureEachLinkIsAnyOrExists(sequence);

    //            var firstResults = new HashSet<ulong>();
    //            var lastResults = new HashSet<ulong>();

    //            var first = sequence.First(x => x != LinksConstants.Any);
    //            var last = sequence.Last(x => x != LinksConstants.Any);

    //            AllUsagesCore(first, firstResults);
    //            AllUsagesCore(last, lastResults);

    //            firstResults.IntersectWith(lastResults);
```

```
684
685             //            //for (var i = 0; i < sequence.Length; i++)
686             //            //    AllUsagesCore(sequence[i], results);
687
688             //            var filteredResults = new HashSet<ulong>();
689             //            var matcher = new Matcher(this, sequence, filteredResults, null);
690             //            matcher.AddAllPartialMatchedToResults(firstResults);
691             //            return filteredResults;
692             //        }
693
694             //        return new HashSet<ulong>();
695             //    });
696             //}
697
698             public HashSet<ulong> GetAllPartiallyMatchingSequences3(params ulong[] sequence)
699             {
700                 return _sync.ExecuteReadOperation(() =>
701                 {
702                     if (sequence.Length > 0)
703                     {
704                         Links.EnsureEachLinkIsAnyOrExists(sequence);
705                         var firstResults = new HashSet<ulong>();
706                         var lastResults = new HashSet<ulong>();
707                         var first = sequence.First(x => x != Constants.Any);
708                         var last = sequence.Last(x => x != Constants.Any);
709                         AllUsagesCore(first, firstResults);
710                         AllUsagesCore(last, lastResults);
711                         firstResults.IntersectWith(lastResults);
712                         //for (var i = 0; i < sequence.Length; i++)
713                         //    AllUsagesCore(sequence[i], results);
714                         var filteredResults = new HashSet<ulong>();
715                         var matcher = new Matcher(this, sequence, filteredResults, null);
716                         matcher.AddAllPartialMatchedToResults(firstResults);
717                         return filteredResults;
718                     }
719                     return new HashSet<ulong>();
720                 });
721             }
722
723             public HashSet<ulong> GetAllPartiallyMatchingSequences4(HashSet<ulong> readAsElements,
                ↪  IList<ulong> sequence)
724             {
725                 return _sync.ExecuteReadOperation(() =>
726                 {
727                     if (sequence.Count > 0)
728                     {
729                         Links.EnsureEachLinkExists(sequence);
730                         var results = new HashSet<LinkIndex>();
731                         //var nextResults = new HashSet<ulong>();
732                         //for (var i = 0; i < sequence.Length; i++)
733                         //{
734                         //    AllUsagesCore(sequence[i], nextResults);
735                         //    if (results.IsNullOrEmpty())
736                         //    {
737                         //        results = nextResults;
738                         //        nextResults = new HashSet<ulong>();
739                         //    }
740                         //    else
741                         //    {
742                         //        results.IntersectWith(nextResults);
743                         //        nextResults.Clear();
744                         //    }
745                         //}
746                         var collector1 = new AllUsagesCollector1(Links.Unsync, results);
747                         collector1.Collect(Links.Unsync.GetLink(sequence[0]));
748                         var next = new HashSet<ulong>();
749                         for (var i = 1; i < sequence.Count; i++)
750                         {
751                             var collector = new AllUsagesCollector1(Links.Unsync, next);
752                             collector.Collect(Links.Unsync.GetLink(sequence[i]));
753
754                             results.IntersectWith(next);
755                             next.Clear();
756                         }
757                         var filteredResults = new HashSet<ulong>();
758                         var matcher = new Matcher(this, sequence, filteredResults, null,
                            ↪  readAsElements);
```

```
759                     matcher.AddAllPartialMatchedToResultsAndReadAsElements(results.OrderBy(x =>
                        ↪  x)); // OrderBy is a Hack
760                     return filteredResults;
761                 }
762                 return new HashSet<ulong>();
763             });
764         }
765 
766         // Does not work
767         //public HashSet<ulong> GetAllPartiallyMatchingSequences5(HashSet<ulong> readAsElements,
                ↪  params ulong[] sequence)
768         //{
769         //    var visited = new HashSet<ulong>();
770         //    var results = new HashSet<ulong>();
771         //    var matcher = new Matcher(this, sequence, visited, x => { results.Add(x); return
                ↪  true; }, readAsElements);
772         //    var last = sequence.Length - 1;
773         //    for (var i = 0; i < last; i++)
774         //    {
775         //        PartialStepRight(matcher.PartialMatch, sequence[i], sequence[i + 1]);
776         //    }
777         //    return results;
778         //}
779 
780         public List<ulong> GetAllPartiallyMatchingSequences(params ulong[] sequence)
781         {
782             return _sync.ExecuteReadOperation(() =>
783             {
784                 if (sequence.Length > 0)
785                 {
786                     Links.EnsureEachLinkExists(sequence);
787                     //var firstElement = sequence[0];
788                     //if (sequence.Length == 1)
789                     //{
790                     //    //results.Add(firstElement);
791                     //    return results;
792                     //}
793                     //if (sequence.Length == 2)
794                     //{
795                     //    //var doublet = _links.SearchCore(firstElement, sequence[1]);
796                     //    //if (doublet != Doublets.Links.Null)
797                     //    //    results.Add(doublet);
798                     //    return results;
799                     //}
800                     //var lastElement = sequence[sequence.Length - 1];
801                     //Func<ulong, bool> handler = x =>
802                     //{
803                     //    if (StartsWith(x, firstElement) && EndsWith(x, lastElement))
                            ↪  results.Add(x);
804                     //    return true;
805                     //};
806                     //if (sequence.Length >= 2)
807                     //    StepRight(handler, sequence[0], sequence[1]);
808                     //var last = sequence.Length - 2;
809                     //for (var i = 1; i < last; i++)
810                     //    PartialStepRight(handler, sequence[i], sequence[i + 1]);
811                     //if (sequence.Length >= 3)
812                     //    StepLeft(handler, sequence[sequence.Length - 2],
                            ↪  sequence[sequence.Length - 1]);
813                     //////if (sequence.Length == 1)
814                     //////{
815                     //////    throw new NotImplementedException(); // all sequences, containing
                            ↪  this element?
816                     //////}
817                     //////if (sequence.Length == 2)
818                     //////{
819                     //////    var results = new List<ulong>();
820                     //////    PartialStepRight(results.Add, sequence[0], sequence[1]);
821                     //////    return results;
822                     //////}
823                     //////var matches = new List<List<ulong>>();
824                     //////var last = sequence.Length - 1;
825                     //////for (var i = 0; i < last; i++)
826                     //////{
827                     //////    var results = new List<ulong>();
828                     //////    //StepRight(results.Add, sequence[i], sequence[i + 1]);
829                     //////    PartialStepRight(results.Add, sequence[i], sequence[i + 1]);
```

```
//////    if (results.Count > 0)
//////        matches.Add(results);
//////    else
//////        return results;
//////    if (matches.Count == 2)
//////    {
//////        var merged = new List<ulong>();
//////        for (var j = 0; j < matches[0].Count; j++)
//////            for (var k = 0; k < matches[1].Count; k++)
//////                CloseInnerConnections(merged.Add, matches[0][j], matches[1][k]);
//////        if (merged.Count > 0)
//////            matches = new List<List<ulong>> { merged };
//////        else
//////            return new List<ulong>();
//////    }
//////}
//////if (matches.Count > 0)
//////{
//////    var usages = new HashSet<ulong>();
//////    for (int i = 0; i < sequence.Length; i++)
//////    {
//////        AllUsagesCore(sequence[i], usages);
//////    }
//////    //for (int i = 0; i < matches[0].Count; i++)
//////    //    AllUsagesCore(matches[0][i], usages);
//////    //usages.UnionWith(matches[0]);
//////    return usages.ToList();
//////}
var firstLinkUsages = new HashSet<ulong>();
AllUsagesCore(sequence[0], firstLinkUsages);
firstLinkUsages.Add(sequence[0]);
//var previousMatchings = firstLinkUsages.ToList(); //new List<ulong>() { sequence[0] }; // or all sequences, containing this element?
//return GetAllPartiallyMatchingSequencesCore(sequence, firstLinkUsages, 1).ToList();
var results = new HashSet<ulong>();
foreach (var match in GetAllPartiallyMatchingSequencesCore(sequence, firstLinkUsages, 1))
{
    AllUsagesCore(match, results);
}
return results.ToList();
            }
            return new List<ulong>();
        });
    }

    /// <remarks>
    /// TODO: Может потробоваться ограничение на уровень глубины рекурсии
    /// </remarks>
    public HashSet<ulong> AllUsages(ulong link)
    {
        return _sync.ExecuteReadOperation(() =>
        {
            var usages = new HashSet<ulong>();
            AllUsagesCore(link, usages);
            return usages;
        });
    }

    // При сборе всех использований (последовательностей) можно сохранять обратный путь к той связи с которой начинался поиск (STTTSSSTT),
    // причём достаточно одного бита для хранения перехода влево или вправо
    private void AllUsagesCore(ulong link, HashSet<ulong> usages)
    {
        bool handler(ulong doublet)
        {
            if (usages.Add(doublet))
            {
                AllUsagesCore(doublet, usages);
            }
            return true;
        }
        Links.Unsync.Each(link, Constants.Any, handler);
        Links.Unsync.Each(Constants.Any, link, handler);
    }
```

```
902
903         public HashSet<ulong> AllBottomUsages(ulong link)
904         {
905             return _sync.ExecuteReadOperation(() =>
906             {
907                 var visits = new HashSet<ulong>();
908                 var usages = new HashSet<ulong>();
909                 AllBottomUsagesCore(link, visits, usages);
910                 return usages;
911             });
912         }
913
914         private void AllBottomUsagesCore(ulong link, HashSet<ulong> visits, HashSet<ulong>
        ↪  usages)
915         {
916             bool handler(ulong doublet)
917             {
918                 if (visits.Add(doublet))
919                 {
920                     AllBottomUsagesCore(doublet, visits, usages);
921                 }
922                 return true;
923             }
924             if (Links.Unsync.Count(Constants.Any, link) == 0)
925             {
926                 usages.Add(link);
927             }
928             else
929             {
930                 Links.Unsync.Each(link, Constants.Any, handler);
931                 Links.Unsync.Each(Constants.Any, link, handler);
932             }
933         }
934
935         public ulong CalculateTotalSymbolFrequencyCore(ulong symbol)
936         {
937             if (Options.UseSequenceMarker)
938             {
939                 var counter = new TotalMarkedSequenceSymbolFrequencyOneOffCounter<ulong>(Links,
                    ↪  Options.MarkedSequenceMatcher, symbol);
940                 return counter.Count();
941             }
942             else
943             {
944                 var counter = new TotalSequenceSymbolFrequencyOneOffCounter<ulong>(Links,
                    ↪  symbol);
945                 return counter.Count();
946             }
947         }
948
949         private bool AllUsagesCore1(ulong link, HashSet<ulong> usages, Func<IList<LinkIndex>,
        ↪  LinkIndex> outerHandler)
950         {
951             bool handler(ulong doublet)
952             {
953                 if (usages.Add(doublet))
954                 {
955                     if (outerHandler(new LinkAddress<LinkIndex>(doublet)) != Constants.Continue)
956                     {
957                         return false;
958                     }
959                     if (!AllUsagesCore1(doublet, usages, outerHandler))
960                     {
961                         return false;
962                     }
963                 }
964                 return true;
965             }
966             return Links.Unsync.Each(link, Constants.Any, handler)
967                 && Links.Unsync.Each(Constants.Any, link, handler);
968         }
969
970         public void CalculateAllUsages(ulong[] totals)
971         {
972             var calculator = new AllUsagesCalculator(Links, totals);
973             calculator.Calculate();
974         }
975
```

```
976         public void CalculateAllUsages2(ulong[] totals)
977         {
978             var calculator = new AllUsagesCalculator2(Links, totals);
979             calculator.Calculate();
980         }
981 
982         private class AllUsagesCalculator
983         {
984             private readonly SynchronizedLinks<ulong> _links;
985             private readonly ulong[] _totals;
986 
987             public AllUsagesCalculator(SynchronizedLinks<ulong> links, ulong[] totals)
988             {
989                 _links = links;
990                 _totals = totals;
991             }
992 
993             public void Calculate() => _links.Each(_links.Constants.Any, _links.Constants.Any,
                ↪ CalculateCore);
994 
995             private bool CalculateCore(ulong link)
996             {
997                 if (_totals[link] == 0)
998                 {
999                     var total = 1UL;
1000                    _totals[link] = total;
1001                    var visitedChildren = new HashSet<ulong>();
1002                    bool linkCalculator(ulong child)
1003                    {
1004                        if (link != child && visitedChildren.Add(child))
1005                        {
1006                            total += _totals[child] == 0 ? 1 : _totals[child];
1007                        }
1008                        return true;
1009                    }
1010                    _links.Unsync.Each(link, _links.Constants.Any, linkCalculator);
1011                    _links.Unsync.Each(_links.Constants.Any, link, linkCalculator);
1012                    _totals[link] = total;
1013                }
1014                return true;
1015            }
1016        }
1017 
1018        private class AllUsagesCalculator2
1019        {
1020            private readonly SynchronizedLinks<ulong> _links;
1021            private readonly ulong[] _totals;
1022 
1023            public AllUsagesCalculator2(SynchronizedLinks<ulong> links, ulong[] totals)
1024            {
1025                _links = links;
1026                _totals = totals;
1027            }
1028 
1029            public void Calculate() => _links.Each(_links.Constants.Any, _links.Constants.Any,
                ↪ CalculateCore);
1030 
1031            private bool IsElement(ulong link)
1032            {
1033                //_linksInSequence.Contains(link) ||
1034                return _links.Unsync.GetTarget(link) == link || _links.Unsync.GetSource(link) ==
                    ↪ link;
1035            }
1036 
1037            private bool CalculateCore(ulong link)
1038            {
1039                // TODO: Проработать защиту от зацикливания
1040                // Основано на SequenceWalker.WalkLeft
1041                Func<ulong, ulong> getSource = _links.Unsync.GetSource;
1042                Func<ulong, ulong> getTarget = _links.Unsync.GetTarget;
1043                Func<ulong, bool> isElement = IsElement;
1044                void visitLeaf(ulong parent)
1045                {
1046                    if (link != parent)
1047                    {
1048                        _totals[parent]++;
1049                    }
1050                }
1051                void visitNode(ulong parent)
```

```
                {
                    if (link != parent)
                    {
                        _totals[parent]++;
                    }
                }
                var stack = new Stack();
                var element = link;
                if (isElement(element))
                {
                    visitLeaf(element);
                }
                else
                {
                    while (true)
                    {
                        if (isElement(element))
                        {
                            if (stack.Count == 0)
                            {
                                break;
                            }
                            element = stack.Pop();
                            var source = getSource(element);
                            var target = getTarget(element);
                            // Обработка элемента
                            if (isElement(target))
                            {
                                visitLeaf(target);
                            }
                            if (isElement(source))
                            {
                                visitLeaf(source);
                            }
                            element = source;
                        }
                        else
                        {
                            stack.Push(element);
                            visitNode(element);
                            element = getTarget(element);
                        }
                    }
                }
                _totals[link]++;
                return true;
            }
        }

        private class AllUsagesCollector
        {
            private readonly ILinks<ulong> _links;
            private readonly HashSet<ulong> _usages;

            public AllUsagesCollector(ILinks<ulong> links, HashSet<ulong> usages)
            {
                _links = links;
                _usages = usages;
            }

            public bool Collect(ulong link)
            {
                if (_usages.Add(link))
                {
                    _links.Each(link, _links.Constants.Any, Collect);
                    _links.Each(_links.Constants.Any, link, Collect);
                }
                return true;
            }
        }

        private class AllUsagesCollector1
        {
            private readonly ILinks<ulong> _links;
            private readonly HashSet<ulong> _usages;
            private readonly ulong _continue;

            public AllUsagesCollector1(ILinks<ulong> links, HashSet<ulong> usages)
            {
```

```
                _links = links;
                _usages = usages;
                _continue = _links.Constants.Continue;
            }

            public ulong Collect(IList<ulong> link)
            {
                var linkIndex = _links.GetIndex(link);
                if (_usages.Add(linkIndex))
                {
                    _links.Each(Collect, _links.Constants.Any, linkIndex);
                }
                return _continue;
            }
        }

        private class AllUsagesCollector2
        {
            private readonly ILinks<ulong> _links;
            private readonly BitString _usages;

            public AllUsagesCollector2(ILinks<ulong> links, BitString usages)
            {
                _links = links;
                _usages = usages;
            }

            public bool Collect(ulong link)
            {
                if (_usages.Add((long)link))
                {
                    _links.Each(link, _links.Constants.Any, Collect);
                    _links.Each(_links.Constants.Any, link, Collect);
                }
                return true;
            }
        }

        private class AllUsagesIntersectingCollector
        {
            private readonly SynchronizedLinks<ulong> _links;
            private readonly HashSet<ulong> _intersectWith;
            private readonly HashSet<ulong> _usages;
            private readonly HashSet<ulong> _enter;

            public AllUsagesIntersectingCollector(SynchronizedLinks<ulong> links, HashSet<ulong>
            ↪  intersectWith, HashSet<ulong> usages)
            {
                _links = links;
                _intersectWith = intersectWith;
                _usages = usages;
                _enter = new HashSet<ulong>(); // защита от зацикливания
            }

            public bool Collect(ulong link)
            {
                if (_enter.Add(link))
                {
                    if (_intersectWith.Contains(link))
                    {
                        _usages.Add(link);
                    }
                    _links.Unsync.Each(link, _links.Constants.Any, Collect);
                    _links.Unsync.Each(_links.Constants.Any, link, Collect);
                }
                return true;
            }
        }

        private void CloseInnerConnections(Action<IList<LinkIndex>> handler, ulong left, ulong
        ↪  right)
        {
            TryStepLeftUp(handler, left, right);
            TryStepRightUp(handler, right, left);
        }

        private void AllCloseConnections(Action<IList<LinkIndex>> handler, ulong left, ulong
        ↪  right)
        {
            // Direct
```

```
            if (left == right)
            {
                handler(new LinkAddress<LinkIndex>(left));
            }
            var doublet = Links.Unsync.SearchOrDefault(left, right);
            if (doublet != Constants.Null)
            {
                handler(new LinkAddress<LinkIndex>(doublet));
            }
            // Inner
            CloseInnerConnections(handler, left, right);
            // Outer
            StepLeft(handler, left, right);
            StepRight(handler, left, right);
            PartialStepRight(handler, left, right);
            PartialStepLeft(handler, left, right);
        }

        private HashSet<ulong> GetAllPartiallyMatchingSequencesCore(ulong[] sequence,
        ↪  HashSet<ulong> previousMatchings, long startAt)
        {
            if (startAt >= sequence.Length) // ?
            {
                return previousMatchings;
            }
            var secondLinkUsages = new HashSet<ulong>();
            AllUsagesCore(sequence[startAt], secondLinkUsages);
            secondLinkUsages.Add(sequence[startAt]);
            var matchings = new HashSet<ulong>();
            var filler = new SetFiller<LinkIndex, LinkIndex>(matchings, Constants.Continue);
            //for (var i = 0; i < previousMatchings.Count; i++)
            foreach (var secondLinkUsage in secondLinkUsages)
            {
                foreach (var previousMatching in previousMatchings)
                {
                    //AllCloseConnections(matchings.AddAndReturnVoid, previousMatching,
                    ↪  secondLinkUsage);
                    StepRight(filler.AddFirstAndReturnConstant, previousMatching,
                    ↪  secondLinkUsage);
                    TryStepRightUp(filler.AddFirstAndReturnConstant, secondLinkUsage,
                    ↪  previousMatching);
                    //PartialStepRight(matchings.AddAndReturnVoid, secondLinkUsage,
                    ↪  sequence[startAt]); // почему-то эта ошибочная запись приводит к
                    ↪  желаемым результам.
                    PartialStepRight(filler.AddFirstAndReturnConstant, previousMatching,
                    ↪  secondLinkUsage);
                }
            }
            if (matchings.Count == 0)
            {
                return matchings;
            }
            return GetAllPartiallyMatchingSequencesCore(sequence, matchings, startAt + 1); // ??
        }

        private static void EnsureEachLinkIsAnyOrZeroOrManyOrExists(SynchronizedLinks<ulong>
        ↪  links, params ulong[] sequence)
        {
            if (sequence == null)
            {
                return;
            }
            for (var i = 0; i < sequence.Length; i++)
            {
                if (sequence[i] != links.Constants.Any && sequence[i] != ZeroOrMany &&
                ↪  !links.Exists(sequence[i]))
                {
                    throw new ArgumentLinkDoesNotExistsException<ulong>(sequence[i],
                    ↪  $"patternSequence[{i}]");
                }
            }
        }

        // Pattern Matching -> Key To Triggers
        public HashSet<ulong> MatchPattern(params ulong[] patternSequence)
        {
            return _sync.ExecuteReadOperation(() =>
```

```
1275                {
1276                    patternSequence = Simplify(patternSequence);
1277                    if (patternSequence.Length > 0)
1278                    {
1279                        EnsureEachLinkIsAnyOrZeroOrManyOrExists(Links, patternSequence);
1280                        var uniqueSequenceElements = new HashSet<ulong>();
1281                        for (var i = 0; i < patternSequence.Length; i++)
1282                        {
1283                            if (patternSequence[i] != Constants.Any && patternSequence[i] !=
                                ↪  ZeroOrMany)
1284                            {
1285                                uniqueSequenceElements.Add(patternSequence[i]);
1286                            }
1287                        }
1288                        var results = new HashSet<ulong>();
1289                        foreach (var uniqueSequenceElement in uniqueSequenceElements)
1290                        {
1291                            AllUsagesCore(uniqueSequenceElement, results);
1292                        }
1293                        var filteredResults = new HashSet<ulong>();
1294                        var matcher = new PatternMatcher(this, patternSequence, filteredResults);
1295                        matcher.AddAllPatternMatchedToResults(results);
1296                        return filteredResults;
1297                    }
1298                    return new HashSet<ulong>();
1299                });
1300            }
1301
1302            // Найти все возможные связи между указанным списком связей.
1303            // Находит связи между всеми указанными связями в любом порядке.
1304            // TODO: решить что делать с повторами (когда одни и те же элементы встречаются
                ↪  несколько раз в последовательности)
1305            public HashSet<ulong> GetAllConnections(params ulong[] linksToConnect)
1306            {
1307                return _sync.ExecuteReadOperation(() =>
1308                {
1309                    var results = new HashSet<ulong>();
1310                    if (linksToConnect.Length > 0)
1311                    {
1312                        Links.EnsureEachLinkExists(linksToConnect);
1313                        AllUsagesCore(linksToConnect[0], results);
1314                        for (var i = 1; i < linksToConnect.Length; i++)
1315                        {
1316                            var next = new HashSet<ulong>();
1317                            AllUsagesCore(linksToConnect[i], next);
1318                            results.IntersectWith(next);
1319                        }
1320                    }
1321                    return results;
1322                });
1323            }
1324
1325            public HashSet<ulong> GetAllConnections1(params ulong[] linksToConnect)
1326            {
1327                return _sync.ExecuteReadOperation(() =>
1328                {
1329                    var results = new HashSet<ulong>();
1330                    if (linksToConnect.Length > 0)
1331                    {
1332                        Links.EnsureEachLinkExists(linksToConnect);
1333                        var collector1 = new AllUsagesCollector(Links.Unsync, results);
1334                        collector1.Collect(linksToConnect[0]);
1335                        var next = new HashSet<ulong>();
1336                        for (var i = 1; i < linksToConnect.Length; i++)
1337                        {
1338                            var collector = new AllUsagesCollector(Links.Unsync, next);
1339                            collector.Collect(linksToConnect[i]);
1340                            results.IntersectWith(next);
1341                            next.Clear();
1342                        }
1343                    }
1344                    return results;
1345                });
1346            }
1347
1348            public HashSet<ulong> GetAllConnections2(params ulong[] linksToConnect)
1349            {
1350                return _sync.ExecuteReadOperation(() =>
```

```
            {
                var results = new HashSet<ulong>();
                if (linksToConnect.Length > 0)
                {
                    Links.EnsureEachLinkExists(linksToConnect);
                    var collector1 = new AllUsagesCollector(Links, results);
                    collector1.Collect(linksToConnect[0]);
                    //AllUsagesCore(linksToConnect[0], results);
                    for (var i = 1; i < linksToConnect.Length; i++)
                    {
                        var next = new HashSet<ulong>();
                        var collector = new AllUsagesIntersectingCollector(Links, results, next);
                        collector.Collect(linksToConnect[i]);
                        //AllUsagesCore(linksToConnect[i], next);
                        //results.IntersectWith(next);
                        results = next;
                    }
                }
                return results;
            });
        }

        public List<ulong> GetAllConnections3(params ulong[] linksToConnect)
        {
            return _sync.ExecuteReadOperation(() =>
            {
                var results = new BitString((long)Links.Unsync.Count() + 1); // new
                ↪  BitArray((int)_links.Total + 1);
                if (linksToConnect.Length > 0)
                {
                    Links.EnsureEachLinkExists(linksToConnect);
                    var collector1 = new AllUsagesCollector2(Links.Unsync, results);
                    collector1.Collect(linksToConnect[0]);
                    for (var i = 1; i < linksToConnect.Length; i++)
                    {
                        var next = new BitString((long)Links.Unsync.Count() + 1); //new
                        ↪  BitArray((int)_links.Total + 1);
                        var collector = new AllUsagesCollector2(Links.Unsync, next);
                        collector.Collect(linksToConnect[i]);
                        results = results.And(next);
                    }
                }
                return results.GetSetUInt64Indices();
            });
        }

        private static ulong[] Simplify(ulong[] sequence)
        {
            // Считаем новый размер последовательности
            long newLength = 0;
            var zeroOrManyStepped = false;
            for (var i = 0; i < sequence.Length; i++)
            {
                if (sequence[i] == ZeroOrMany)
                {
                    if (zeroOrManyStepped)
                    {
                        continue;
                    }
                    zeroOrManyStepped = true;
                }
                else
                {
                    //if (zeroOrManyStepped) Is it efficient?
                    zeroOrManyStepped = false;
                }
                newLength++;
            }
            // Строим новую последовательность
            zeroOrManyStepped = false;
            var newSequence = new ulong[newLength];
            long j = 0;
            for (var i = 0; i < sequence.Length; i++)
            {
                //var current = zeroOrManyStepped;
                //zeroOrManyStepped = patternSequence[i] == zeroOrMany;
                //if (current && zeroOrManyStepped)
                //    continue;
```

```
1427                //var newZeroOrManyStepped = patternSequence[i] == zeroOrMany;
1428                //if (zeroOrManyStepped && newZeroOrManyStepped)
1429                //    continue;
1430                //zeroOrManyStepped = newZeroOrManyStepped;
1431                if (sequence[i] == ZeroOrMany)
1432                {
1433                    if (zeroOrManyStepped)
1434                    {
1435                        continue;
1436                    }
1437                    zeroOrManyStepped = true;
1438                }
1439                else
1440                {
1441                    //if (zeroOrManyStepped) Is it efficient?
1442                    zeroOrManyStepped = false;
1443                }
1444                newSequence[j++] = sequence[i];
1445            }
1446            return newSequence;
1447        }
1448
1449        public static void TestSimplify()
1450        {
1451            var sequence = new ulong[] { ZeroOrMany, ZeroOrMany, 2, 3, 4, ZeroOrMany,
                ↪  ZeroOrMany, ZeroOrMany, 4, ZeroOrMany, ZeroOrMany, ZeroOrMany };
1452            var simplifiedSequence = Simplify(sequence);
1453        }
1454
1455        public List<ulong> GetSimilarSequences() => new List<ulong>();
1456
1457        public void Prediction()
1458        {
1459            //_links
1460            //sequences
1461        }
1462
1463        #region From Triplets
1464
1465        //public static void DeleteSequence(Link sequence)
1466        //{
1467        //}
1468
1469        public List<ulong> CollectMatchingSequences(ulong[] links)
1470        {
1471            if (links.Length == 1)
1472            {
1473                throw new Exception("Подпоследовательности с одним элементом не
                    ↪  поддерживаются.");
1474            }
1475            var leftBound = 0;
1476            var rightBound = links.Length - 1;
1477            var left = links[leftBound++];
1478            var right = links[rightBound--];
1479            var results = new List<ulong>();
1480            CollectMatchingSequences(left, leftBound, links, right, rightBound, ref results);
1481            return results;
1482        }
1483
1484        private void CollectMatchingSequences(ulong leftLink, int leftBound, ulong[]
        ↪  middleLinks, ulong rightLink, int rightBound, ref List<ulong> results)
1485        {
1486            var leftLinkTotalReferers = Links.Unsync.Count(leftLink);
1487            var rightLinkTotalReferers = Links.Unsync.Count(rightLink);
1488            if (leftLinkTotalReferers <= rightLinkTotalReferers)
1489            {
1490                var nextLeftLink = middleLinks[leftBound];
1491                var elements = GetRightElements(leftLink, nextLeftLink);
1492                if (leftBound <= rightBound)
1493                {
1494                    for (var i = elements.Length - 1; i >= 0; i--)
1495                    {
1496                        var element = elements[i];
1497                        if (element != 0)
1498                        {
1499                            CollectMatchingSequences(element, leftBound + 1, middleLinks,
                                ↪  rightLink, rightBound, ref results);
1500                        }
1501                    }
```

```
                }
                else
                {
                    for (var i = elements.Length - 1; i >= 0; i--)
                    {
                        var element = elements[i];
                        if (element != 0)
                        {
                            results.Add(element);
                        }
                    }
                }
            }
            else
            {
                var nextRightLink = middleLinks[rightBound];
                var elements = GetLeftElements(rightLink, nextRightLink);
                if (leftBound <= rightBound)
                {
                    for (var i = elements.Length - 1; i >= 0; i--)
                    {
                        var element = elements[i];
                        if (element != 0)
                        {
                            CollectMatchingSequences(leftLink, leftBound, middleLinks,
                             ↪  elements[i], rightBound - 1, ref results);
                        }
                    }
                }
                else
                {
                    for (var i = elements.Length - 1; i >= 0; i--)
                    {
                        var element = elements[i];
                        if (element != 0)
                        {
                            results.Add(element);
                        }
                    }
                }
            }
        }

        public ulong[] GetRightElements(ulong startLink, ulong rightLink)
        {
            var result = new ulong[5];
            TryStepRight(startLink, rightLink, result, 0);
            Links.Each(Constants.Any, startLink, couple =>
            {
                if (couple != startLink)
                {
                    if (TryStepRight(couple, rightLink, result, 2))
                    {
                        return false;
                    }
                }
                return true;
            });
            if (Links.GetTarget(Links.GetTarget(startLink)) == rightLink)
            {
                result[4] = startLink;
            }
            return result;
        }

        public bool TryStepRight(ulong startLink, ulong rightLink, ulong[] result, int offset)
        {
            var added = 0;
            Links.Each(startLink, Constants.Any, couple =>
            {
                if (couple != startLink)
                {
                    var coupleTarget = Links.GetTarget(couple);
                    if (coupleTarget == rightLink)
                    {
                        result[offset] = couple;
                        if (++added == 2)
                        {
```

```
                        return false;
                    }
                }
                else if (Links.GetSource(coupleTarget) == rightLink) // coupleTarget.Linker
                ↪  == Net.And &&
                {
                    result[offset + 1] = couple;
                    if (++added == 2)
                    {
                        return false;
                    }
                }
            }
            return true;
        });
        return added > 0;
    }

    public ulong[] GetLeftElements(ulong startLink, ulong leftLink)
    {
        var result = new ulong[5];
        TryStepLeft(startLink, leftLink, result, 0);
        Links.Each(startLink, Constants.Any, couple =>
        {
            if (couple != startLink)
            {
                if (TryStepLeft(couple, leftLink, result, 2))
                {
                    return false;
                }
            }
            return true;
        });
        if (Links.GetSource(Links.GetSource(leftLink)) == startLink)
        {
            result[4] = leftLink;
        }
        return result;
    }

    public bool TryStepLeft(ulong startLink, ulong leftLink, ulong[] result, int offset)
    {
        var added = 0;
        Links.Each(Constants.Any, startLink, couple =>
        {
            if (couple != startLink)
            {
                var coupleSource = Links.GetSource(couple);
                if (coupleSource == leftLink)
                {
                    result[offset] = couple;
                    if (++added == 2)
                    {
                        return false;
                    }
                }
                else if (Links.GetTarget(coupleSource) == leftLink) // coupleSource.Linker
                ↪  == Net.And &&
                {
                    result[offset + 1] = couple;
                    if (++added == 2)
                    {
                        return false;
                    }
                }
            }
            return true;
        });
        return added > 0;
    }

    #endregion

    #region Walkers

    public class PatternMatcher : RightSequenceWalker<ulong>
    {
        private readonly Sequences _sequences;
        private readonly ulong[] _patternSequence;
```

```
1656            private readonly HashSet<LinkIndex> _linksInSequence;
1657            private readonly HashSet<LinkIndex> _results;
1658
1659            #region Pattern Match
1660
1661            enum PatternBlockType
1662            {
1663                Undefined,
1664                Gap,
1665                Elements
1666            }
1667
1668            struct PatternBlock
1669            {
1670                public PatternBlockType Type;
1671                public long Start;
1672                public long Stop;
1673            }
1674
1675            private readonly List<PatternBlock> _pattern;
1676            private int _patternPosition;
1677            private long _sequencePosition;
1678
1679            #endregion
1680
1681            public PatternMatcher(Sequences sequences, LinkIndex[] patternSequence,
                ↪ HashSet<LinkIndex> results)
1682                : base(sequences.Links.Unsync, new DefaultStack<ulong>())
1683            {
1684                _sequences = sequences;
1685                _patternSequence = patternSequence;
1686                _linksInSequence = new HashSet<LinkIndex>(patternSequence.Where(x => x !=
                    ↪ _sequences.Constants.Any && x != ZeroOrMany));
1687                _results = results;
1688                _pattern = CreateDetailedPattern();
1689            }
1690
1691            protected override bool IsElement(ulong link) => _linksInSequence.Contains(link) ||
                ↪ base.IsElement(link);
1692
1693            public bool PatternMatch(LinkIndex sequenceToMatch)
1694            {
1695                _patternPosition = 0;
1696                _sequencePosition = 0;
1697                foreach (var part in Walk(sequenceToMatch))
1698                {
1699                    if (!PatternMatchCore(part))
1700                    {
1701                        break;
1702                    }
1703                }
1704                return _patternPosition == _pattern.Count || (_patternPosition == _pattern.Count
                    ↪ - 1 && _pattern[_patternPosition].Start == 0);
1705            }
1706
1707            private List<PatternBlock> CreateDetailedPattern()
1708            {
1709                var pattern = new List<PatternBlock>();
1710                var patternBlock = new PatternBlock();
1711                for (var i = 0; i < _patternSequence.Length; i++)
1712                {
1713                    if (patternBlock.Type == PatternBlockType.Undefined)
1714                    {
1715                        if (_patternSequence[i] == _sequences.Constants.Any)
1716                        {
1717                            patternBlock.Type = PatternBlockType.Gap;
1718                            patternBlock.Start = 1;
1719                            patternBlock.Stop = 1;
1720                        }
1721                        else if (_patternSequence[i] == ZeroOrMany)
1722                        {
1723                            patternBlock.Type = PatternBlockType.Gap;
1724                            patternBlock.Start = 0;
1725                            patternBlock.Stop = long.MaxValue;
1726                        }
1727                        else
1728                        {
1729                            patternBlock.Type = PatternBlockType.Elements;
1730                            patternBlock.Start = i;
1731                            patternBlock.Stop = i;
1732                        }
```

```
                }
                else if (patternBlock.Type == PatternBlockType.Elements)
                {
                    if (_patternSequence[i] == _sequences.Constants.Any)
                    {
                        pattern.Add(patternBlock);
                        patternBlock = new PatternBlock
                        {
                            Type = PatternBlockType.Gap,
                            Start = 1,
                            Stop = 1
                        };
                    }
                    else if (_patternSequence[i] == ZeroOrMany)
                    {
                        pattern.Add(patternBlock);
                        patternBlock = new PatternBlock
                        {
                            Type = PatternBlockType.Gap,
                            Start = 0,
                            Stop = long.MaxValue
                        };
                    }
                    else
                    {
                        patternBlock.Stop = i;
                    }
                }
                else // patternBlock.Type == PatternBlockType.Gap
                {
                    if (_patternSequence[i] == _sequences.Constants.Any)
                    {
                        patternBlock.Start++;
                        if (patternBlock.Stop < patternBlock.Start)
                        {
                            patternBlock.Stop = patternBlock.Start;
                        }
                    }
                    else if (_patternSequence[i] == ZeroOrMany)
                    {
                        patternBlock.Stop = long.MaxValue;
                    }
                    else
                    {
                        pattern.Add(patternBlock);
                        patternBlock = new PatternBlock
                        {
                            Type = PatternBlockType.Elements,
                            Start = i,
                            Stop = i
                        };
                    }
                }
            }
            if (patternBlock.Type != PatternBlockType.Undefined)
            {
                pattern.Add(patternBlock);
            }
            return pattern;
        }

        // match: search for regexp anywhere in text
        //int match(char* regexp, char* text)
        //{
        //    do
        //    {
        //    } while (*text++ != '\0');
        //    return 0;
        //}

        // matchhere: search for regexp at beginning of text
        //int matchhere(char* regexp, char* text)
        //{
        //    if (regexp[0] == '\0')
        //        return 1;
        //    if (regexp[1] == '*')
        //        return matchstar(regexp[0], regexp + 2, text);
        //    if (regexp[0] == '$' && regexp[1] == '\0')
        //        return *text == '\0';
```

```
//    if (*text != '\0' && (regexp[0] == '.' || regexp[0] == *text))
//        return matchhere(regexp + 1, text + 1);
//    return 0;
//}

// matchstar: search for c*regexp at beginning of text
//int matchstar(int c, char* regexp, char* text)
//{
//    do
//    {    /* a * matches zero or more instances */
//        if (matchhere(regexp, text))
//            return 1;
//    } while (*text != '\0' && (*text++ == c || c == '.'));
//    return 0;
//}

//private void GetNextPatternElement(out LinkIndex element, out long mininumGap, out long maximumGap)
//{
//    mininumGap = 0;
//    maximumGap = 0;
//    element = 0;
//    for (; _patternPosition < _patternSequence.Length; _patternPosition++)
//    {
//        if (_patternSequence[_patternPosition] == Doublets.Links.Null)
//            mininumGap++;
//        else if (_patternSequence[_patternPosition] == ZeroOrMany)
//            maximumGap = long.MaxValue;
//        else
//            break;
//    }

//    if (maximumGap < mininumGap)
//        maximumGap = mininumGap;
//}

private bool PatternMatchCore(LinkIndex element)
{
    if (_patternPosition >= _pattern.Count)
    {
        _patternPosition = -2;
        return false;
    }
    var currentPatternBlock = _pattern[_patternPosition];
    if (currentPatternBlock.Type == PatternBlockType.Gap)
    {
        //var currentMatchingBlockLength = (_sequencePosition - _lastMatchedBlockPosition);
        if (_sequencePosition < currentPatternBlock.Start)
        {
            _sequencePosition++;
            return true; // Двигаемся дальше
        }
        // Это последний блок
        if (_pattern.Count == _patternPosition + 1)
        {
            _patternPosition++;
            _sequencePosition = 0;
            return false; // Полное соответствие
        }
        else
        {
            if (_sequencePosition > currentPatternBlock.Stop)
            {
                return false; // Соответствие невозможно
            }
            var nextPatternBlock = _pattern[_patternPosition + 1];
            if (_patternSequence[nextPatternBlock.Start] == element)
            {
                if (nextPatternBlock.Start < nextPatternBlock.Stop)
                {
                    _patternPosition++;
                    _sequencePosition = 1;
                }
                else
                {
                    _patternPosition += 2;
                    _sequencePosition = 0;
                }
```

```
                        }
                    }
                }
                else // currentPatternBlock.Type == PatternBlockType.Elements
                {
                    var patternElementPosition = currentPatternBlock.Start + _sequencePosition;
                    if (_patternSequence[patternElementPosition] != element)
                    {
                        return false; // Соответствие невозможно
                    }
                    if (patternElementPosition == currentPatternBlock.Stop)
                    {
                        _patternPosition++;
                        _sequencePosition = 0;
                    }
                    else
                    {
                        _sequencePosition++;
                    }
                }
                return true;
                //if (_patternSequence[_patternPosition] != element)
                //    return false;
                //else
                //{
                //    _sequencePosition++;
                //    _patternPosition++;
                //    return true;
                //}
                ////////
                //if (_filterPosition == _patternSequence.Length)
                //{
                //    _filterPosition = -2; // Длиннее чем нужно
                //    return false;
                //}
                //if (element != _patternSequence[_filterPosition])
                //{
                //    _filterPosition = -1;
                //    return false; // Начинается иначе
                //}
                //_filterPosition++;
                //if (_filterPosition == (_patternSequence.Length - 1))
                //    return false;
                //if (_filterPosition >= 0)
                //{
                //    if (element == _patternSequence[_filterPosition + 1])
                //        _filterPosition++;
                //    else
                //        return false;
                //}
                //if (_filterPosition < 0)
                //{
                //    if (element == _patternSequence[0])
                //        _filterPosition = 0;
                //}
            }

            public void AddAllPatternMatchedToResults(IEnumerable<ulong> sequencesToMatch)
            {
                foreach (var sequenceToMatch in sequencesToMatch)
                {
                    if (PatternMatch(sequenceToMatch))
                    {
                        _results.Add(sequenceToMatch);
                    }
                }
            }
        }

        #endregion
    }
}
```

./Platform.Data.Doublets/Sequences/SequencesExtensions.cs

```
using System;
using System.Collections.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

```

```
namespace Platform.Data.Doublets.Sequences
{
    public static class SequencesExtensions
    {
        public static TLink Create<TLink>(this ILinks<TLink> sequences, IList<TLink[]>
        ↪ groupedSequence)
        {
            var finalSequence = new TLink[groupedSequence.Count];
            for (var i = 0; i < finalSequence.Length; i++)
            {
                var part = groupedSequence[i];
                finalSequence[i] = part.Length == 1 ? part[0] :
                ↪ sequences.Create(part.ConvertToRestrictionsValues());
            }
            return sequences.Create(finalSequence.ConvertToRestrictionsValues());
        }

        public static IList<TLink> ToList<TLink>(this ILinks<TLink> sequences, TLink sequence)
        {
            var list = new List<TLink>();
            var filler = new ListFiller<TLink, TLink>(list, sequences.Constants.Break);
            sequences.Each(filler.AddAllValuesAndReturnConstant, new
            ↪ LinkAddress<TLink>(sequence));
            return list;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/SequencesOptions.cs

```
using System;
using System.Collections.Generic;
using Platform.Interfaces;
using Platform.Collections.Stacks;
using Platform.Data.Doublets.Sequences.Frequencies.Cache;
using Platform.Data.Doublets.Sequences.Frequencies.Counters;
using Platform.Data.Doublets.Sequences.Converters;
using Platform.Data.Doublets.Sequences.CreteriaMatchers;
using Platform.Data.Doublets.Sequences.Walkers;
using Platform.Data.Doublets.Sequences.Indexes;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences
{
    public class SequencesOptions<TLink> // TODO: To use type parameter <TLink> the
    ↪ ILinks<TLink> must contain GetConstants function.
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪ EqualityComparer<TLink>.Default;

        public TLink SequenceMarkerLink { get; set; }
        public bool UseCascadeUpdate { get; set; }
        public bool UseCascadeDelete { get; set; }
        public bool UseIndex { get; set; } // TODO: Update Index on sequence update/delete.
        public bool UseSequenceMarker { get; set; }
        public bool UseCompression { get; set; }
        public bool UseGarbageCollection { get; set; }
        public bool EnforceSingleSequenceVersionOnWriteBasedOnExisting { get; set; }
        public bool EnforceSingleSequenceVersionOnWriteBasedOnNew { get; set; }

        public MarkedSequenceCriterionMatcher<TLink> MarkedSequenceMatcher { get; set; }
        public IConverter<IList<TLink>, TLink> LinksToSequenceConverter { get; set; }
        public ISequenceIndex<TLink> Index { get; set; }
        public ISequenceWalker<TLink> Walker { get; set; }
        public bool ReadFullSequence { get; set; }

        // TODO: Реализовать компактификацию при чтении
        //public bool EnforceSingleSequenceVersionOnRead { get; set; }
        //public bool UseRequestMarker { get; set; }
        //public bool StoreRequestResults { get; set; }

        public void InitOptions(ISynchronizedLinks<TLink> links)
        {
            if (UseSequenceMarker)
            {
                if (_equalityComparer.Equals(SequenceMarkerLink, links.Constants.Null))
                {
                    SequenceMarkerLink = links.CreatePoint();
                }
```

```
                else
                {
                    if (!links.Exists(SequenceMarkerLink))
                    {
                        var link = links.CreatePoint();
                        if (!_equalityComparer.Equals(link, SequenceMarkerLink))
                        {
                            throw new InvalidOperationException("Cannot recreate sequence marker link.");
                        }
                    }
                }
                if (MarkedSequenceMatcher == null)
                {
                    MarkedSequenceMatcher = new MarkedSequenceCriterionMatcher<TLink>(links, SequenceMarkerLink);
                }
            }
            var balancedVariantConverter = new BalancedVariantConverter<TLink>(links);
            if (UseCompression)
            {
                if (LinksToSequenceConverter == null)
                {
                    ICounter<TLink, TLink> totalSequenceSymbolFrequencyCounter;
                    if (UseSequenceMarker)
                    {
                        totalSequenceSymbolFrequencyCounter = new TotalMarkedSequenceSymbolFrequencyCounter<TLink>(links, MarkedSequenceMatcher);
                    }
                    else
                    {
                        totalSequenceSymbolFrequencyCounter = new TotalSequenceSymbolFrequencyCounter<TLink>(links);
                    }
                    var doubletFrequenciesCache = new LinkFrequenciesCache<TLink>(links, totalSequenceSymbolFrequencyCounter);
                    var compressingConverter = new CompressingConverter<TLink>(links, balancedVariantConverter, doubletFrequenciesCache);
                    LinksToSequenceConverter = compressingConverter;
                }
            }
            else
            {
                if (LinksToSequenceConverter == null)
                {
                    LinksToSequenceConverter = balancedVariantConverter;
                }
            }
            if (UseIndex && Index == null)
            {
                Index = new SequenceIndex<TLink>(links);
            }
            if (Walker == null)
            {
                Walker = new RightSequenceWalker<TLink>(links, new DefaultStack<TLink>());
            }
        }

        public void ValidateOptions()
        {
            if (UseGarbageCollection && !UseSequenceMarker)
            {
                throw new NotSupportedException("To use garbage collection UseSequenceMarker option must be on.");
            }
        }
    }
}
```

./Platform.Data.Doublets/Sequences/SetFiller.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences
{
```

```
    public class SetFiller<TElement, TReturnConstant>
    {
        protected readonly ISet<TElement> _set;
        protected readonly TReturnConstant _returnConstant;

        public SetFiller(ISet<TElement> set, TReturnConstant returnConstant)
        {
            _set = set;
            _returnConstant = returnConstant;
        }

        public SetFiller(ISet<TElement> set) : this(set, default) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public void Add(TElement element) => _set.Add(element);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public bool AddAndReturnTrue(TElement element)
        {
            _set.Add(element);
            return true;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public bool AddFirstAndReturnTrue(IList<TElement> collection)
        {
            _set.Add(collection[0]);
            return true;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public TReturnConstant AddAndReturnConstant(TElement element)
        {
            _set.Add(element);
            return _returnConstant;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public TReturnConstant AddFirstAndReturnConstant(IList<TElement> collection)
        {
            _set.Add(collection[0]);
            return _returnConstant;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Walkers/ISequenceWalker.cs

```
using System.Collections.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Walkers
{
    public interface ISequenceWalker<TLink>
    {
        IEnumerable<TLink> Walk(TLink sequence);
    }
}
```

./Platform.Data.Doublets/Sequences/Walkers/LeftSequenceWalker.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Collections.Stacks;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Walkers
{
    public class LeftSequenceWalker<TLink> : SequenceWalkerBase<TLink>
    {
        public LeftSequenceWalker(ILinks<TLink> links, IStack<TLink> stack, Func<TLink, bool>
        ↪  isElement) : base(links, stack, isElement) { }

        public LeftSequenceWalker(ILinks<TLink> links, IStack<TLink> stack) : base(links, stack,
        ↪  links.IsPartialPoint) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetNextElementAfterPop(TLink element) =>
        ↪  Links.GetSource(element);
```

```

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetNextElementAfterPush(TLink element) =>
        ↪ Links.GetTarget(element);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override IEnumerable<TLink> WalkContents(TLink element)
        {
            var parts = Links.GetLink(element);
            var start = Links.Constants.IndexPart + 1;
            for (var i = parts.Count - 1; i >= start; i--)
            {
                var part = parts[i];
                if (IsElement(part))
                {
                    yield return part;
                }
            }
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Walkers/LeveledSequenceWalker.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

//#define USEARRAYPOOL
#if USEARRAYPOOL
using Platform.Collections;
#endif

namespace Platform.Data.Doublets.Sequences.Walkers
{
    public class LeveledSequenceWalker<TLink> : LinksOperatorBase<TLink>, ISequenceWalker<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪ EqualityComparer<TLink>.Default;

        private readonly Func<TLink, bool> _isElement;

        public LeveledSequenceWalker(ILinks<TLink> links, Func<TLink, bool> isElement) :
        ↪ base(links) => _isElement = isElement;

        public LeveledSequenceWalker(ILinks<TLink> links) : base(links) => _isElement =
        ↪ Links.IsPartialPoint;

        public IEnumerable<TLink> Walk(TLink sequence) => ToArray(sequence);

        public TLink[] ToArray(TLink sequence)
        {
            var length = 1;
            var array = new TLink[length];
            array[0] = sequence;
            if (_isElement(sequence))
            {
                return array;
            }
            bool hasElements;
            do
            {
                length *= 2;
#if USEARRAYPOOL
                var nextArray = ArrayPool.Allocate<ulong>(length);
#else
                var nextArray = new TLink[length];
#endif
                hasElements = false;
                for (var i = 0; i < array.Length; i++)
                {
                    var candidate = array[i];
                    if (_equalityComparer.Equals(array[i], default))
                    {
                        continue;
                    }
                    var doubletOffset = i * 2;
                    if (_isElement(candidate))
                    {
```

```
                        nextArray[doubletOffset] = candidate;
                    }
                    else
                    {
                        var link = Links.GetLink(candidate);
                        var linkSource = Links.GetSource(link);
                        var linkTarget = Links.GetTarget(link);
                        nextArray[doubletOffset] = linkSource;
                        nextArray[doubletOffset + 1] = linkTarget;
                        if (!hasElements)
                        {
                            hasElements = !(_isElement(linkSource) && _isElement(linkTarget));
                        }
                    }
                }
#if USEARRAYPOOL
                if (array.Length > 1)
                {
                    ArrayPool.Free(array);
                }
#endif
                array = nextArray;
            }
            while (hasElements);
            var filledElementsCount = CountFilledElements(array);
            if (filledElementsCount == array.Length)
            {
                return array;
            }
            else
            {
                return CopyFilledElements(array, filledElementsCount);
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private static TLink[] CopyFilledElements(TLink[] array, int filledElementsCount)
        {
            var finalArray = new TLink[filledElementsCount];
            for (int i = 0, j = 0; i < array.Length; i++)
            {
                if (!_equalityComparer.Equals(array[i], default))
                {
                    finalArray[j] = array[i];
                    j++;
                }
            }
#if USEARRAYPOOL
                ArrayPool.Free(array);
#endif
            return finalArray;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private static int CountFilledElements(TLink[] array)
        {
            var count = 0;
            for (var i = 0; i < array.Length; i++)
            {
                if (!_equalityComparer.Equals(array[i], default))
                {
                    count++;
                }
            }
            return count;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Walkers/RightSequenceWalker.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Collections.Stacks;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Walkers
{
    public class RightSequenceWalker<TLink> : SequenceWalkerBase<TLink>
```

```
    {
        public RightSequenceWalker(ILinks<TLink> links, IStack<TLink> stack, Func<TLink, bool>
        ↪  isElement) : base(links, stack, isElement) { }

        public RightSequenceWalker(ILinks<TLink> links, IStack<TLink> stack) : base(links,
        ↪  stack, links.IsPartialPoint) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetNextElementAfterPop(TLink element) =>
        ↪  Links.GetTarget(element);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetNextElementAfterPush(TLink element) =>
        ↪  Links.GetSource(element);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override IEnumerable<TLink> WalkContents(TLink element)
        {
            var parts = Links.GetLink(element);
            for (var i = Links.Constants.IndexPart + 1; i < parts.Count; i++)
            {
                var part = parts[i];
                if (IsElement(part))
                {
                    yield return part;
                }
            }
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Walkers/SequenceWalkerBase.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Collections.Stacks;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Sequences.Walkers
{
    public abstract class SequenceWalkerBase<TLink> : LinksOperatorBase<TLink>,
    ↪  ISequenceWalker<TLink>
    {
        private readonly IStack<TLink> _stack;
        private readonly Func<TLink, bool> _isElement;

        protected SequenceWalkerBase(ILinks<TLink> links, IStack<TLink> stack, Func<TLink, bool>
        ↪  isElement) : base(links)
        {
            _stack = stack;
            _isElement = isElement;
        }

        protected SequenceWalkerBase(ILinks<TLink> links, IStack<TLink> stack) : this(links,
        ↪  stack, links.IsPartialPoint)
        {
        }

        public IEnumerable<TLink> Walk(TLink sequence)
        {
            _stack.Clear();
            var element = sequence;
            if (IsElement(element))
            {
                yield return element;
            }
            else
            {
                while (true)
                {
                    if (IsElement(element))
                    {
                        if (_stack.IsEmpty)
                        {
                            break;
                        }
                        element = _stack.Pop();
                        foreach (var output in WalkContents(element))
```

```
                        {
                            yield return output;
                        }
                        element = GetNextElementAfterPop(element);
                    }
                    else
                    {
                        _stack.Push(element);
                        element = GetNextElementAfterPush(element);
                    }
                }
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected virtual bool IsElement(TLink elementLink) => _isElement(elementLink);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected abstract TLink GetNextElementAfterPop(TLink element);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected abstract TLink GetNextElementAfterPush(TLink element);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected abstract IEnumerable<TLink> WalkContents(TLink element);
    }
}
```

./Platform.Data.Doublets/Stacks/Stack.cs

```
using System.Collections.Generic;
using Platform.Collections.Stacks;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Stacks
{
    public class Stack<TLink> : IStack<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪  EqualityComparer<TLink>.Default;

        private readonly ILinks<TLink> _links;
        private readonly TLink _stack;

        public bool IsEmpty => _equalityComparer.Equals(Peek(), _stack);

        public Stack(ILinks<TLink> links, TLink stack)
        {
            _links = links;
            _stack = stack;
        }

        private TLink GetStackMarker() => _links.GetSource(_stack);

        private TLink GetTop() => _links.GetTarget(_stack);

        public TLink Peek() => _links.GetTarget(GetTop());

        public TLink Pop()
        {
            var element = Peek();
            if (!_equalityComparer.Equals(element, _stack))
            {
                var top = GetTop();
                var previousTop = _links.GetSource(top);
                _links.Update(_stack, GetStackMarker(), previousTop);
                _links.Delete(top);
            }
            return element;
        }

        public void Push(TLink element) => _links.Update(_stack, GetStackMarker(),
        ↪  _links.GetOrCreate(GetTop(), element));
    }
}
```

./Platform.Data.Doublets/Stacks/StackExtensions.cs

```
#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Stacks
```

```
{
    public static class StackExtensions
    {
        public static TLink CreateStack<TLink>(this ILinks<TLink> links, TLink stackMarker)
        {
            var stackPoint = links.CreatePoint();
            var stack = links.Update(stackPoint, stackMarker, stackPoint);
            return stack;
        }
    }
}
```

./Platform.Data.Doublets/SynchronizedLinks.cs

```
using System;
using System.Collections.Generic;
using Platform.Data.Doublets;
using Platform.Threading.Synchronization;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets
{
    /// <remarks>
    /// TODO: Autogeneration of synchronized wrapper (decorator).
    /// TODO: Try to unfold code of each method using IL generation for performance improvements.
    /// TODO: Or even to unfold multiple layers of implementations.
    /// </remarks>
    public class SynchronizedLinks<TLinkAddress> : ISynchronizedLinks<TLinkAddress>
    {
        public LinksConstants<TLinkAddress> Constants { get; }
        public ISynchronization SyncRoot { get; }
        public ILinks<TLinkAddress> Sync { get; }
        public ILinks<TLinkAddress> Unsync { get; }

        public SynchronizedLinks(ILinks<TLinkAddress> links) : this(new
        ↪  ReaderWriterLockSynchronization(), links) { }

        public SynchronizedLinks(ISynchronization synchronization, ILinks<TLinkAddress> links)
        {
            SyncRoot = synchronization;
            Sync = this;
            Unsync = links;
            Constants = links.Constants;
        }

        public TLinkAddress Count(IList<TLinkAddress> restriction) =>
        ↪  SyncRoot.ExecuteReadOperation(restriction, Unsync.Count);
        public TLinkAddress Each(Func<IList<TLinkAddress>, TLinkAddress> handler,
        ↪  IList<TLinkAddress> restrictions) => SyncRoot.ExecuteReadOperation(handler,
        ↪  restrictions, (handler1, restrictions1) => Unsync.Each(handler1, restrictions1));
        public TLinkAddress Create(IList<TLinkAddress> restrictions) =>
        ↪  SyncRoot.ExecuteWriteOperation(restrictions, Unsync.Create);
        public TLinkAddress Update(IList<TLinkAddress> restrictions, IList<TLinkAddress>
        ↪  substitution) => SyncRoot.ExecuteWriteOperation(restrictions, substitution,
        ↪  Unsync.Update);
        public void Delete(IList<TLinkAddress> restrictions) =>
        ↪  SyncRoot.ExecuteWriteOperation(restrictions, Unsync.Delete);

        //public T Trigger(IList<T> restriction, Func<IList<T>, IList<T>, T> matchedHandler,
        ↪  IList<T> substitution, Func<IList<T>, IList<T>, T> substitutedHandler)
        //{
        //    if (restriction != null && substitution != null &&
        ↪  !substitution.EqualTo(restriction))
        //        return SyncRoot.ExecuteWriteOperation(restriction, matchedHandler,
        ↪  substitution, substitutedHandler, Unsync.Trigger);

        //    return SyncRoot.ExecuteReadOperation(restriction, matchedHandler, substitution,
        ↪  substitutedHandler, Unsync.Trigger);
        //}
    }
}
```

./Platform.Data.Doublets/UInt64LinksExtensions.cs

```
using System;
using System.Text;
using System.Collections.Generic;
using Platform.Singletons;
using Platform.Data.Exceptions;
```

```
using Platform.Data.Doublets.Unicode;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets
{
    public static class UInt64LinksExtensions
    {
        public static readonly LinksConstants<ulong> Constants =
        ↪  Default<LinksConstants<ulong>>.Instance;

        public static void UseUnicode(this ILinks<ulong> links) => UnicodeMap.InitNew(links);

        public static void EnsureEachLinkExists(this ILinks<ulong> links, IList<ulong> sequence)
        {
            if (sequence == null)
            {
                return;
            }
            for (var i = 0; i < sequence.Count; i++)
            {
                if (!links.Exists(sequence[i]))
                {
                    throw new ArgumentLinkDoesNotExistsException<ulong>(sequence[i],
                    ↪  $"sequence[{i}]");
                }
            }
        }

        public static void EnsureEachLinkIsAnyOrExists(this ILinks<ulong> links, IList<ulong>
        ↪  sequence)
        {
            if (sequence == null)
            {
                return;
            }
            for (var i = 0; i < sequence.Count; i++)
            {
                if (sequence[i] != Constants.Any && !links.Exists(sequence[i]))
                {
                    throw new ArgumentLinkDoesNotExistsException<ulong>(sequence[i],
                    ↪  $"sequence[{i}]");
                }
            }
        }

        public static bool AnyLinkIsAny(this ILinks<ulong> links, params ulong[] sequence)
        {
            if (sequence == null)
            {
                return false;
            }
            var constants = links.Constants;
            for (var i = 0; i < sequence.Length; i++)
            {
                if (sequence[i] == constants.Any)
                {
                    return true;
                }
            }
            return false;
        }

        public static string FormatStructure(this ILinks<ulong> links, ulong linkIndex,
        ↪  Func<Link<ulong>, bool> isElement, bool renderIndex = false, bool renderDebug =
        ↪  false)
        {
            var sb = new StringBuilder();
            var visited = new HashSet<ulong>();
            links.AppendStructure(sb, visited, linkIndex, isElement, (innerSb, link) =>
            ↪  innerSb.Append(link.Index), renderIndex, renderDebug);
            return sb.ToString();
        }

        public static string FormatStructure(this ILinks<ulong> links, ulong linkIndex,
        ↪  Func<Link<ulong>, bool> isElement, Action<StringBuilder, Link<ulong>> appendElement,
        ↪  bool renderIndex = false, bool renderDebug = false)
        {
```

```
75              var sb = new StringBuilder();
76              var visited = new HashSet<ulong>();
77              links.AppendStructure(sb, visited, linkIndex, isElement, appendElement, renderIndex,
                ↪  renderDebug);
78              return sb.ToString();
79          }
80
81          public static void AppendStructure(this ILinks<ulong> links, StringBuilder sb,
            ↪  HashSet<ulong> visited, ulong linkIndex, Func<Link<ulong>, bool> isElement,
            ↪  Action<StringBuilder, Link<ulong>> appendElement, bool renderIndex = false, bool
            ↪  renderDebug = false)
82          {
83              if (sb == null)
84              {
85                  throw new ArgumentNullException(nameof(sb));
86              }
87              if (linkIndex == Constants.Null || linkIndex == Constants.Any || linkIndex ==
                ↪  Constants.Itself)
88              {
89                  return;
90              }
91              if (links.Exists(linkIndex))
92              {
93                  if (visited.Add(linkIndex))
94                  {
95                      sb.Append('(');
96                      var link = new Link<ulong>(links.GetLink(linkIndex));
97                      if (renderIndex)
98                      {
99                          sb.Append(link.Index);
100                         sb.Append(':');
101                     }
102                     if (link.Source == link.Index)
103                     {
104                         sb.Append(link.Index);
105                     }
106                     else
107                     {
108                         var source = new Link<ulong>(links.GetLink(link.Source));
109                         if (isElement(source))
110                         {
111                             appendElement(sb, source);
112                         }
113                         else
114                         {
115                             links.AppendStructure(sb, visited, source.Index, isElement,
                                ↪  appendElement, renderIndex);
116                         }
117                     }
118                     sb.Append(' ');
119                     if (link.Target == link.Index)
120                     {
121                         sb.Append(link.Index);
122                     }
123                     else
124                     {
125                         var target = new Link<ulong>(links.GetLink(link.Target));
126                         if (isElement(target))
127                         {
128                             appendElement(sb, target);
129                         }
130                         else
131                         {
132                             links.AppendStructure(sb, visited, target.Index, isElement,
                                ↪  appendElement, renderIndex);
133                         }
134                     }
135                     sb.Append(')');
136                 }
137                 else
138                 {
139                     if (renderDebug)
140                     {
141                         sb.Append('*');
142                     }
143                     sb.Append(linkIndex);
144                 }
145             }
```

```
            else
            {
                if (renderDebug)
                {
                    sb.Append('~');
                }
                sb.Append(linkIndex);
            }
        }
    }
}
```

./Platform.Data.Doublets/UInt64LinksTransactionsLayer.cs

```
using System;
using System.Linq;
using System.Collections.Generic;
using System.IO;
using System.Runtime.CompilerServices;
using System.Threading;
using System.Threading.Tasks;
using Platform.Disposables;
using Platform.Timestamps;
using Platform.Unsafe;
using Platform.IO;
using Platform.Data.Doublets.Decorators;
using Platform.Exceptions;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets
{
    public class UInt64LinksTransactionsLayer : LinksDisposableDecoratorBase<ulong> //-V3073
    {
        /// <remarks>
        /// Альтернативные варианты хранения трансформации (элемента транзакции):
        ///
        /// private enum TransitionType
        /// {
        ///     Creation,
        ///     UpdateOf,
        ///     UpdateTo,
        ///     Deletion
        /// }
        ///
        /// private struct Transition
        /// {
        ///     public ulong TransactionId;
        ///     public UniqueTimestamp Timestamp;
        ///     public TransactionItemType Type;
        ///     public Link Source;
        ///     public Link Linker;
        ///     public Link Target;
        /// }
        ///
        /// Или
        ///
        /// public struct TransitionHeader
        /// {
        ///     public ulong TransactionIdCombined;
        ///     public ulong TimestampCombined;
        ///
        ///     public ulong TransactionId
        ///     {
        ///         get
        ///         {
        ///             return (ulong) mask &amp; TransactionIdCombined;
        ///         }
        ///     }
        ///
        ///     public UniqueTimestamp Timestamp
        ///     {
        ///         get
        ///         {
        ///             return (UniqueTimestamp)mask &amp; TransactionIdCombined;
        ///         }
        ///     }
        ///
        ///     public TransactionItemType Type
        ///     {
```

```
67          ///         get
68          ///         {
69          ///             // Использовать по одному биту из TransactionId и Timestamp,
70          ///             // для значения в 2 бита, которое представляет тип операции
71          ///             throw new NotImplementedException();
72          ///         }
73          ///     }
74          /// }
75          ///
76          /// private struct Transition
77          /// {
78          ///     public TransitionHeader Header;
79          ///     public Link Source;
80          ///     public Link Linker;
81          ///     public Link Target;
82          /// }
83          ///
84          /// </remarks>
85          public struct Transition
86          {
87              public static readonly long Size = Structure<Transition>.Size;
88
89              public readonly ulong TransactionId;
90              public readonly Link<ulong> Before;
91              public readonly Link<ulong> After;
92              public readonly Timestamp Timestamp;
93
94              public Transition(UniqueTimestampFactory uniqueTimestampFactory, ulong
                ↪  transactionId, Link<ulong> before, Link<ulong> after)
95              {
96                  TransactionId = transactionId;
97                  Before = before;
98                  After = after;
99                  Timestamp = uniqueTimestampFactory.Create();
100             }
101
102             public Transition(UniqueTimestampFactory uniqueTimestampFactory, ulong
                ↪  transactionId, Link<ulong> before)
103                 : this(uniqueTimestampFactory, transactionId, before, default)
104             {
105             }
106
107             public Transition(UniqueTimestampFactory uniqueTimestampFactory, ulong transactionId)
108                 : this(uniqueTimestampFactory, transactionId, default, default)
109             {
110             }
111
112             public override string ToString() => $"{Timestamp} {TransactionId}: {Before} =>
                ↪  {After}";
113         }
114
115         /// <remarks>
116         /// Другие варианты реализации транзакций (атомарности):
117         ///     1. Разделение хранения значения связи ((Source Target) или (Source Linker
                ↪  Target)) и индексов.
118         ///     2. Хранение трансформаций/операций в отдельном хранилище Links, но дополнительно
                ↪  потребуется решить вопрос
119         ///        со ссылками на внешние идентификаторы, или как-то иначе решить вопрос с
                ↪  пересечениями идентификаторов.
120         ///
121         /// Где хранить промежуточный список транзакций?
122         ///
123         /// В оперативной памяти:
124         ///  Минусы:
125         ///     1. Может усложнить систему, если она будет функционировать самостоятельно,
126         ///     так как нужно отдельно выделять память под список трансформаций.
127         ///     2. Выделенной оперативной памяти может не хватить, в том случае,
128         ///     если транзакция использует слишком много трансформаций.
129         ///         -> Можно использовать жёсткий диск для слишком длинных транзакций.
130         ///         -> Максимальный размер списка трансформаций можно ограничить / задать
                ↪  константой.
131         ///     3. При подтверждении транзакции (Commit) все трансформации записываются разом
                ↪  создавая задержку.
132         ///
133         /// На жёстком диске:
134         ///  Минусы:
135         ///     1. Длительный отклик, на запись каждой трансформации.
136         ///     2. Лог транзакций дополнительно наполняется отменёнными транзакциями.
```

```
137         ///         -> Это может решаться упаковкой/исключением дублирующих операций.
138         ///         -> Также это может решаться тем, что короткие транзакции вообще
139         ///            не будут записываться в случае отката.
140         ///     3. Перед тем как выполнять отмену операций транзакции нужно дождаться пока все
            ↪  операции (трансформации)
141         ///        будут записаны в лог.
142         ///
143         /// </remarks>
144         public class Transaction : DisposableBase
145         {
146             private readonly Queue<Transition> _transitions;
147             private readonly UInt64LinksTransactionsLayer _layer;
148             public bool IsCommitted { get; private set; }
149             public bool IsReverted { get; private set; }
150
151             public Transaction(UInt64LinksTransactionsLayer layer)
152             {
153                 _layer = layer;
154                 if (_layer._currentTransactionId != 0)
155                 {
156                     throw new NotSupportedException("Nested transactions not supported.");
157                 }
158                 IsCommitted = false;
159                 IsReverted = false;
160                 _transitions = new Queue<Transition>();
161                 SetCurrentTransaction(layer, this);
162             }
163
164             public void Commit()
165             {
166                 EnsureTransactionAllowsWriteOperations(this);
167                 while (_transitions.Count > 0)
168                 {
169                     var transition = _transitions.Dequeue();
170                     _layer._transitions.Enqueue(transition);
171                 }
172                 _layer._lastCommitedTransactionId = _layer._currentTransactionId;
173                 IsCommitted = true;
174             }
175
176             private void Revert()
177             {
178                 EnsureTransactionAllowsWriteOperations(this);
179                 var transitionsToRevert = new Transition[_transitions.Count];
180                 _transitions.CopyTo(transitionsToRevert, 0);
181                 for (var i = transitionsToRevert.Length - 1; i >= 0; i--)
182                 {
183                     _layer.RevertTransition(transitionsToRevert[i]);
184                 }
185                 IsReverted = true;
186             }
187
188             public static void SetCurrentTransaction(UInt64LinksTransactionsLayer layer,
                ↪  Transaction transaction)
189             {
190                 layer._currentTransactionId = layer._lastCommitedTransactionId + 1;
191                 layer._currentTransactionTransitions = transaction._transitions;
192                 layer._currentTransaction = transaction;
193             }
194
195             public static void EnsureTransactionAllowsWriteOperations(Transaction transaction)
196             {
197                 if (transaction.IsReverted)
198                 {
199                     throw new InvalidOperationException("Transation is reverted.");
200                 }
201                 if (transaction.IsCommitted)
202                 {
203                     throw new InvalidOperationException("Transation is commited.");
204                 }
205             }
206
207             protected override void Dispose(bool manual, bool wasDisposed)
208             {
209                 if (!wasDisposed && _layer != null && !_layer.IsDisposed)
210                 {
211                     if (!IsCommitted && !IsReverted)
212                     {
213                         Revert();
```

```
                }
                _layer.ResetCurrentTransation();
            }
        }
    }

    public static readonly TimeSpan DefaultPushDelay = TimeSpan.FromSeconds(0.1);

    private readonly string _logAddress;
    private readonly FileStream _log;
    private readonly Queue<Transition> _transitions;
    private readonly UniqueTimestampFactory _uniqueTimestampFactory;
    private Task _transitionsPusher;
    private Transition _lastCommitedTransition;
    private ulong _currentTransactionId;
    private Queue<Transition> _currentTransactionTransitions;
    private Transaction _currentTransaction;
    private ulong _lastCommitedTransactionId;

    public UInt64LinksTransactionsLayer(ILinks<ulong> links, string logAddress)
        : base(links)
    {
        if (string.IsNullOrWhiteSpace(logAddress))
        {
            throw new ArgumentNullException(nameof(logAddress));
        }
        // В первой строке файла хранится последняя закоммиченную транзакцию.
        // При запуске это используется для проверки удачного закрытия файла лога.
        // In the first line of the file the last committed transaction is stored.
        // On startup, this is used to check that the log file is successfully closed.
        var lastCommitedTransition = FileHelpers.ReadFirstOrDefault<Transition>(logAddress);
        var lastWrittenTransition = FileHelpers.ReadLastOrDefault<Transition>(logAddress);
        if (!lastCommitedTransition.Equals(lastWrittenTransition))
        {
            Dispose();
            throw new NotSupportedException("Database is damaged, autorecovery is not
            ↪  supported yet.");
        }
        if (lastCommitedTransition.Equals(default(Transition)))
        {
            FileHelpers.WriteFirst(logAddress, lastCommitedTransition);
        }
        _lastCommitedTransition = lastCommitedTransition;
        // TODO: Think about a better way to calculate or store this value
        var allTransitions = FileHelpers.ReadAll<Transition>(logAddress);
        _lastCommitedTransactionId = allTransitions.Max(x => x.TransactionId);
        _uniqueTimestampFactory = new UniqueTimestampFactory();
        _logAddress = logAddress;
        _log = FileHelpers.Append(logAddress);
        _transitions = new Queue<Transition>();
        _transitionsPusher = new Task(TransitionsPusher);
        _transitionsPusher.Start();
    }

    public IList<ulong> GetLinkValue(ulong link) => Links.GetLink(link);

    public override ulong Create(IList<ulong> restrictions)
    {
        var createdLinkIndex = Links.Create();
        var createdLink = new Link<ulong>(Links.GetLink(createdLinkIndex));
        CommitTransition(new Transition(_uniqueTimestampFactory, _currentTransactionId,
        ↪  default, createdLink));
        return createdLinkIndex;
    }

    public override ulong Update(IList<ulong> restrictions, IList<ulong> substitution)
    {
        var linkIndex = restrictions[Constants.IndexPart];
        var beforeLink = new Link<ulong>(Links.GetLink(linkIndex));
        linkIndex = Links.Update(restrictions, substitution);
        var afterLink = new Link<ulong>(Links.GetLink(linkIndex));
        CommitTransition(new Transition(_uniqueTimestampFactory, _currentTransactionId,
        ↪  beforeLink, afterLink));
        return linkIndex;
    }

    public override void Delete(IList<ulong> restrictions)
    {
        var link = restrictions[Constants.IndexPart];
```

```
290             var deletedLink = new Link<ulong>(Links.GetLink(link));
291             Links.Delete(link);
292             CommitTransition(new Transition(_uniqueTimestampFactory, _currentTransactionId,
                    ↪ deletedLink, default));
293         }
294 
295         [MethodImpl(MethodImplOptions.AggressiveInlining)]
296         private Queue<Transition> GetCurrentTransitions() => _currentTransactionTransitions ??
                ↪ _transitions;
297 
298         private void CommitTransition(Transition transition)
299         {
300             if (_currentTransaction != null)
301             {
302                 Transaction.EnsureTransactionAllowsWriteOperations(_currentTransaction);
303             }
304             var transitions = GetCurrentTransitions();
305             transitions.Enqueue(transition);
306         }
307 
308         private void RevertTransition(Transition transition)
309         {
310             if (transition.After.IsNull()) // Revert Deletion with Creation
311             {
312                 Links.Create();
313             }
314             else if (transition.Before.IsNull()) // Revert Creation with Deletion
315             {
316                 Links.Delete(transition.After.Index);
317             }
318             else // Revert Update
319             {
320                 Links.Update(new[] { transition.After.Index, transition.Before.Source,
                        ↪ transition.Before.Target });
321             }
322         }
323 
324         private void ResetCurrentTransation()
325         {
326             _currentTransactionId = 0;
327             _currentTransactionTransitions = null;
328             _currentTransaction = null;
329         }
330 
331         private void PushTransitions()
332         {
333             if (_log == null || _transitions == null)
334             {
335                 return;
336             }
337             for (var i = 0; i < _transitions.Count; i++)
338             {
339                 var transition = _transitions.Dequeue();
340 
341                 _log.Write(transition);
342                 _lastCommitedTransition = transition;
343             }
344         }
345 
346         private void TransitionsPusher()
347         {
348             while (!IsDisposed && _transitionsPusher != null)
349             {
350                 Thread.Sleep(DefaultPushDelay);
351                 PushTransitions();
352             }
353         }
354 
355         public Transaction BeginTransaction() => new Transaction(this);
356 
357         private void DisposeTransitions()
358         {
359             try
360             {
361                 var pusher = _transitionsPusher;
362                 if (pusher != null)
363                 {
364                     _transitionsPusher = null;
365                     pusher.Wait();
```

```
                }
                if (_transitions != null)
                {
                    PushTransitions();
                }
                _log.DisposeIfPossible();
                FileHelpers.WriteFirst(_logAddress, _lastCommitedTransition);
            }
            catch (Exception ex)
            {
                ex.Ignore();
            }
        }

        #region DisposalBase

        protected override void Dispose(bool manual, bool wasDisposed)
        {
            if (!wasDisposed)
            {
                DisposeTransitions();
            }
            base.Dispose(manual, wasDisposed);
        }

        #endregion
    }
}
```

./Platform.Data.Doublets/Unicode/CharToUnicodeSymbolConverter.cs

```
using Platform.Interfaces;
using Platform.Numbers;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Unicode
{
    public class CharToUnicodeSymbolConverter<TLink> : LinksOperatorBase<TLink>,
    ↪ IConverter<char, TLink>
    {
        private readonly IConverter<TLink> _addressToNumberConverter;
        private readonly TLink _unicodeSymbolMarker;

        public CharToUnicodeSymbolConverter(ILinks<TLink> links, IConverter<TLink>
        ↪ addressToNumberConverter, TLink unicodeSymbolMarker) : base(links)
        {
            _addressToNumberConverter = addressToNumberConverter;
            _unicodeSymbolMarker = unicodeSymbolMarker;
        }

        public TLink Convert(char source)
        {
            var unaryNumber = _addressToNumberConverter.Convert((Integer<TLink>)source);
            return Links.GetOrCreate(unaryNumber, _unicodeSymbolMarker);
        }
    }
}
```

./Platform.Data.Doublets/Unicode/StringToUnicodeSequenceConverter.cs

```
using Platform.Data.Doublets.Sequences.Indexes;
using Platform.Interfaces;
using System.Collections.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Unicode
{
    public class StringToUnicodeSequenceConverter<TLink> : LinksOperatorBase<TLink>,
    ↪ IConverter<string, TLink>
    {
        private readonly IConverter<char, TLink> _charToUnicodeSymbolConverter;
        private readonly ISequenceIndex<TLink> _index;
        private readonly IConverter<IList<TLink>, TLink> _listToSequenceLinkConverter;
        private readonly TLink _unicodeSequenceMarker;

        public StringToUnicodeSequenceConverter(ILinks<TLink> links, IConverter<char, TLink>
        ↪ charToUnicodeSymbolConverter, ISequenceIndex<TLink> index, IConverter<IList<TLink>,
        ↪ TLink> listToSequenceLinkConverter, TLink unicodeSequenceMarker) : base(links)
        {
            _charToUnicodeSymbolConverter = charToUnicodeSymbolConverter;
```

```
            _index = index;
            _listToSequenceLinkConverter = listToSequenceLinkConverter;
            _unicodeSequenceMarker = unicodeSequenceMarker;
        }

        public TLink Convert(string source)
        {
            var elements = new TLink[source.Length];
            for (int i = 0; i < source.Length; i++)
            {
                elements[i] = _charToUnicodeSymbolConverter.Convert(source[i]);
            }
            _index.Add(elements);
            var sequence = _listToSequenceLinkConverter.Convert(elements);
            return Links.GetOrCreate(sequence, _unicodeSequenceMarker);
        }
    }
}
```

./Platform.Data.Doublets/Unicode/UnicodeMap.cs

```
using System;
using System.Collections.Generic;
using System.Globalization;
using System.Runtime.CompilerServices;
using System.Text;
using Platform.Data.Sequences;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Unicode
{
    public class UnicodeMap
    {
        public static readonly ulong FirstCharLink = 1;
        public static readonly ulong LastCharLink = FirstCharLink + char.MaxValue;
        public static readonly ulong MapSize = 1 + char.MaxValue;

        private readonly ILinks<ulong> _links;
        private bool _initialized;

        public UnicodeMap(ILinks<ulong> links) => _links = links;

        public static UnicodeMap InitNew(ILinks<ulong> links)
        {
            var map = new UnicodeMap(links);
            map.Init();
            return map;
        }

        public void Init()
        {
            if (_initialized)
            {
                return;
            }
            _initialized = true;
            var firstLink = _links.CreatePoint();
            if (firstLink != FirstCharLink)
            {
                _links.Delete(firstLink);
            }
            else
            {
                for (var i = FirstCharLink + 1; i <= LastCharLink; i++)
                {
                    // From NIL to It (NIL -> Character) transformation meaning, (or infinite
                    ↪  amount of NIL characters before actual Character)
                    var createdLink = _links.CreatePoint();
                    _links.Update(createdLink, firstLink, createdLink);
                    if (createdLink != i)
                    {
                        throw new InvalidOperationException("Unable to initialize UTF 16
                        ↪  table.");
                    }
                }
            }
        }

        // 0 - null link
        // 1 - nil character (0 character)
```

```
        // ...
        // 65536 (0(1) + 65535 = 65536 possible values)

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static ulong FromCharToLink(char character) => (ulong)character + 1;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static char FromLinkToChar(ulong link) => (char)(link - 1);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static bool IsCharLink(ulong link) => link <= MapSize;

        public static string FromLinksToString(IList<ulong> linksList)
        {
            var sb = new StringBuilder();
            for (int i = 0; i < linksList.Count; i++)
            {
                sb.Append(FromLinkToChar(linksList[i]));
            }
            return sb.ToString();
        }

        public static string FromSequenceLinkToString(ulong link, ILinks<ulong> links)
        {
            var sb = new StringBuilder();
            if (links.Exists(link))
            {
                StopableSequenceWalker.WalkRight(link, links.GetSource, links.GetTarget,
                    x => x <= MapSize || links.GetSource(x) == x || links.GetTarget(x) == x,
                    element =>
                    {
                        sb.Append(FromLinkToChar(element));
                        return true;
                    });
            }
            return sb.ToString();
        }

        public static ulong[] FromCharsToLinkArray(char[] chars) => FromCharsToLinkArray(chars,
        chars.Length);

        public static ulong[] FromCharsToLinkArray(char[] chars, int count)
        {
            // char array to ulong array
            var linksSequence = new ulong[count];
            for (var i = 0; i < count; i++)
            {
                linksSequence[i] = FromCharToLink(chars[i]);
            }
            return linksSequence;
        }

        public static ulong[] FromStringToLinkArray(string sequence)
        {
            // char array to ulong array
            var linksSequence = new ulong[sequence.Length];
            for (var i = 0; i < sequence.Length; i++)
            {
                linksSequence[i] = FromCharToLink(sequence[i]);
            }
            return linksSequence;
        }

        public static List<ulong[]> FromStringToLinkArrayGroups(string sequence)
        {
            var result = new List<ulong[]>();
            var offset = 0;
            while (offset < sequence.Length)
            {
                var currentCategory = CharUnicodeInfo.GetUnicodeCategory(sequence[offset]);
                var relativeLength = 1;
                var absoluteLength = offset + relativeLength;
                while (absoluteLength < sequence.Length &&
                       currentCategory ==
                       CharUnicodeInfo.GetUnicodeCategory(sequence[absoluteLength]))
                {
                    relativeLength++;
                    absoluteLength++;
                }
```

```
                // char array to ulong array
                var innerSequence = new ulong[relativeLength];
                var maxLength = offset + relativeLength;
                for (var i = offset; i < maxLength; i++)
                {
                    innerSequence[i - offset] = FromCharToLink(sequence[i]);
                }
                result.Add(innerSequence);
                offset += relativeLength;
            }
            return result;
        }

        public static List<ulong[]> FromLinkArrayToLinkArrayGroups(ulong[] array)
        {
            var result = new List<ulong[]>();
            var offset = 0;
            while (offset < array.Length)
            {
                var relativeLength = 1;
                if (array[offset] <= LastCharLink)
                {
                    var currentCategory =
                    ↪  CharUnicodeInfo.GetUnicodeCategory(FromLinkToChar(array[offset]));
                    var absoluteLength = offset + relativeLength;
                    while (absoluteLength < array.Length &&
                           array[absoluteLength] <= LastCharLink &&
                           currentCategory == CharUnicodeInfo.GetUnicodeCategory(FromLinkToChar(
                           ↪  array[absoluteLength])))
                    {
                        relativeLength++;
                        absoluteLength++;
                    }
                }
                else
                {
                    var absoluteLength = offset + relativeLength;
                    while (absoluteLength < array.Length && array[absoluteLength] > LastCharLink)
                    {
                        relativeLength++;
                        absoluteLength++;
                    }
                }
                // copy array
                var innerSequence = new ulong[relativeLength];
                var maxLength = offset + relativeLength;
                for (var i = offset; i < maxLength; i++)
                {
                    innerSequence[i - offset] = array[i];
                }
                result.Add(innerSequence);
                offset += relativeLength;
            }
            return result;
        }
    }
}
```

./Platform.Data.Doublets/Unicode/UnicodeSequenceCriterionMatcher.cs

```
using Platform.Interfaces;
using System.Collections.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Unicode
{
    public class UnicodeSequenceCriterionMatcher<TLink> : LinksOperatorBase<TLink>,
    ↪  ICriterionMatcher<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪  EqualityComparer<TLink>.Default;
        private readonly TLink _unicodeSequenceMarker;
        public UnicodeSequenceCriterionMatcher(ILinks<TLink> links, TLink unicodeSequenceMarker)
        ↪  : base(links) => _unicodeSequenceMarker = unicodeSequenceMarker;
        public bool IsMatched(TLink link) => _equalityComparer.Equals(Links.GetTarget(link),
        ↪  _unicodeSequenceMarker);
    }
}
```

./Platform.Data.Doublets/Unicode/UnicodeSequenceToStringConverter.cs

```
using System;
using System.Linq;
using Platform.Data.Doublets.Sequences.Walkers;
using Platform.Interfaces;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Unicode
{
    public class UnicodeSequenceToStringConverter<TLink> : LinksOperatorBase<TLink>,
    ↪ IConverter<TLink, string>
    {
        private readonly ICriterionMatcher<TLink> _unicodeSequenceCriterionMatcher;
        private readonly ISequenceWalker<TLink> _sequenceWalker;
        private readonly IConverter<TLink, char> _unicodeSymbolToCharConverter;

        public UnicodeSequenceToStringConverter(ILinks<TLink> links, ICriterionMatcher<TLink>
        ↪ unicodeSequenceCriterionMatcher, ISequenceWalker<TLink> sequenceWalker,
        ↪ IConverter<TLink, char> unicodeSymbolToCharConverter) : base(links)
        {
            _unicodeSequenceCriterionMatcher = unicodeSequenceCriterionMatcher;
            _sequenceWalker = sequenceWalker;
            _unicodeSymbolToCharConverter = unicodeSymbolToCharConverter;
        }

        public string Convert(TLink source)
        {
            if(!_unicodeSequenceCriterionMatcher.IsMatched(source))
            {
                throw new ArgumentOutOfRangeException(nameof(source), source, "Specified link is
                ↪ not a unicode sequence.");
            }
            var sequence = Links.GetSource(source);
            var charArray = _sequenceWalker.Walk(sequence).Select(_unicodeSymbolToCharConverter.
            ↪ Convert).ToArray();
            return new string(charArray);
        }
    }
}
```

./Platform.Data.Doublets/Unicode/UnicodeSymbolCriterionMatcher.cs

```
using Platform.Interfaces;
using System.Collections.Generic;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Unicode
{
    public class UnicodeSymbolCriterionMatcher<TLink> : LinksOperatorBase<TLink>,
    ↪ ICriterionMatcher<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪ EqualityComparer<TLink>.Default;
        private readonly TLink _unicodeSymbolMarker;
        public UnicodeSymbolCriterionMatcher(ILinks<TLink> links, TLink unicodeSymbolMarker) :
        ↪ base(links) => _unicodeSymbolMarker = unicodeSymbolMarker;
        public bool IsMatched(TLink link) => _equalityComparer.Equals(Links.GetTarget(link),
        ↪ _unicodeSymbolMarker);
    }
}
```

./Platform.Data.Doublets/Unicode/UnicodeSymbolToCharConverter.cs

```
using System;
using Platform.Interfaces;
using Platform.Numbers;

#pragma warning disable CS1591 // Missing XML comment for publicly visible type or member

namespace Platform.Data.Doublets.Unicode
{
    public class UnicodeSymbolToCharConverter<TLink> : LinksOperatorBase<TLink>,
    ↪ IConverter<TLink, char>
    {
        private readonly IConverter<TLink> _numberToAddressConverter;
        private readonly ICriterionMatcher<TLink> _unicodeSymbolCriterionMatcher;

        public UnicodeSymbolToCharConverter(ILinks<TLink> links, IConverter<TLink>
        ↪ numberToAddressConverter, ICriterionMatcher<TLink> unicodeSymbolCriterionMatcher) :
        ↪ base(links)
```

```
        {
            _numberToAddressConverter = numberToAddressConverter;
            _unicodeSymbolCriterionMatcher = unicodeSymbolCriterionMatcher;
        }

        public char Convert(TLink source)
        {
            if (!_unicodeSymbolCriterionMatcher.IsMatched(source))
            {
                throw new ArgumentOutOfRangeException(nameof(source), source, "Specified link is not a unicode symbol.");
            }
            return (char)(ushort)(Integer<TLink>)_numberToAddressConverter.Convert(Links.GetSource(source));
        }
    }
}
```

./Platform.Data.Doublets.Tests/ComparisonTests.cs

```
using System;
using System.Collections.Generic;
using Xunit;
using Platform.Diagnostics;

namespace Platform.Data.Doublets.Tests
{
    public static class ComparisonTests
    {
        private class UInt64Comparer : IComparer<ulong>
        {
            public int Compare(ulong x, ulong y) => x.CompareTo(y);
        }

        private static int Compare(ulong x, ulong y) => x.CompareTo(y);

        [Fact]
        public static void GreaterOrEqualPerfomanceTest()
        {
            const int N = 1000000;

            ulong x = 10;
            ulong y = 500;

            bool result = false;

            var ts1 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = Compare(x, y) >= 0;
                }
            });

            var comparer1 = Comparer<ulong>.Default;

            var ts2 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = comparer1.Compare(x, y) >= 0;
                }
            });

            Func<ulong, ulong, int> compareReference = comparer1.Compare;

            var ts3 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = compareReference(x, y) >= 0;
                }
            });

            var comparer2 = new UInt64Comparer();

            var ts4 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = comparer2.Compare(x, y) >= 0;
```

```
                }
            });

            Console.WriteLine($"{ts1} {ts2} {ts3} {ts4} {result}");
        }
    }
}
```

./Platform.Data.Doublets.Tests/EqualityTests.cs

```
using System;
using System.Collections.Generic;
using Xunit;
using Platform.Diagnostics;

namespace Platform.Data.Doublets.Tests
{
    public static class EqualityTests
    {
        protected class UInt64EqualityComparer : IEqualityComparer<ulong>
        {
            public bool Equals(ulong x, ulong y) => x == y;

            public int GetHashCode(ulong obj) => obj.GetHashCode();
        }

        private static bool Equals1<T>(T x, T y) => Equals(x, y);

        private static bool Equals2<T>(T x, T y) => x.Equals(y);

        private static bool Equals3(ulong x, ulong y) => x == y;

        [Fact]
        public static void EqualsPerfomanceTest()
        {
            const int N = 1000000;

            ulong x = 10;
            ulong y = 500;

            bool result = false;

            var ts1 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = Equals1(x, y);
                }
            });

            var ts2 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = Equals2(x, y);
                }
            });

            var ts3 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = Equals3(x, y);
                }
            });

            var equalityComparer1 = EqualityComparer<ulong>.Default;

            var ts4 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = equalityComparer1.Equals(x, y);
                }
            });

            var equalityComparer2 = new UInt64EqualityComparer();

            var ts5 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
```

```
                {
                    result = equalityComparer2.Equals(x, y);
                }
            });

            Func<ulong, ulong, bool> equalityComparer3 = equalityComparer2.Equals;

            var ts6 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = equalityComparer3(x, y);
                }
            });

            var comparer = Comparer<ulong>.Default;

            var ts7 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = comparer.Compare(x, y) == 0;
                }
            });

            Assert.True(ts2 < ts1);
            Assert.True(ts3 < ts2);
            Assert.True(ts5 < ts4);
            Assert.True(ts5 < ts6);

            Console.WriteLine($"{ts1} {ts2} {ts3} {ts4} {ts5} {ts6} {ts7} {result}");
        }
    }
}
```

./Platform.Data.Doublets.Tests/GenericLinksTests.cs

```
using System;
using Xunit;
using Platform.Reflection;
using Platform.Memory;
using Platform.Scopes;
using Platform.Data.Doublets.ResizableDirectMemory.Generic;

namespace Platform.Data.Doublets.Tests
{
    public unsafe static class GenericLinksTests
    {
        [Fact]
        public static void CRUDTest()
        {
            Using<byte>(links => links.TestCRUDOperations());
            Using<ushort>(links => links.TestCRUDOperations());
            Using<uint>(links => links.TestCRUDOperations());
            Using<ulong>(links => links.TestCRUDOperations());
        }

        [Fact]
        public static void RawNumbersCRUDTest()
        {
            Using<byte>(links => links.TestRawNumbersCRUDOperations());
            Using<ushort>(links => links.TestRawNumbersCRUDOperations());
            Using<uint>(links => links.TestRawNumbersCRUDOperations());
            Using<ulong>(links => links.TestRawNumbersCRUDOperations());
        }

        [Fact]
        public static void MultipleRandomCreationsAndDeletionsTest()
        {
            Using<byte>(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().TestMultipleRandomCreationsAndDeletions(16)); // Cannot use more because current implementation of tree cuts out 5 bits from the address space.
            Using<ushort>(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().TestMultipleRandomCreationsAndDeletions(100));
            Using<uint>(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().TestMultipleRandomCreationsAndDeletions(100));
            Using<ulong>(links => links.DecorateWithAutomaticUniquenessAndUsagesResolution().TestMultipleRandomCreationsAndDeletions(100));
        }

```

```
        private static void Using<TLink>(Action<ILinks<TLink>> action)
        {
            using (var scope = new Scope<Types<HeapResizableDirectMemory,
            ↪  ResizableDirectMemoryLinks<TLink>>>())
            {
                action(scope.Use<ILinks<TLink>>());
            }
        }
    }
}
```

./Platform.Data.Doublets.Tests/LinksConstantsTests.cs

```
using Xunit;

namespace Platform.Data.Doublets.Tests
{
    public static class LinksConstantsTests
    {
        [Fact]
        public static void ExternalReferencesTest()
        {
            LinksConstants<ulong> constants = new LinksConstants<ulong>((1, long.MaxValue),
            ↪  (long.MaxValue + 1UL, ulong.MaxValue));

            //var minimum = new Hybrid<ulong>(0, isExternal: true);
            var minimum = new Hybrid<ulong>(1, isExternal: true);
            var maximum = new Hybrid<ulong>(long.MaxValue, isExternal: true);

            Assert.True(constants.IsExternalReference(minimum));
            Assert.True(constants.IsExternalReference(maximum));
        }
    }
}
```

./Platform.Data.Doublets.Tests/OptimalVariantSequenceTests.cs

```
using System;
using System.Linq;
using System.Collections.Generic;
using Xunit;
using Platform.Data.Doublets.Sequences;
using Platform.Data.Doublets.Sequences.Frequencies.Cache;
using Platform.Data.Doublets.Sequences.Frequencies.Counters;
using Platform.Data.Doublets.Sequences.Converters;
using Platform.Data.Doublets.PropertyOperators;
using Platform.Data.Doublets.Incrementers;
using Platform.Data.Doublets.Sequences.Walkers;
using Platform.Data.Doublets.Sequences.Indexes;
using Platform.Data.Doublets.Unicode;
using Platform.Data.Doublets.Numbers.Unary;
using Platform.Memory;
using Platform.Data.Doublets.ResizableDirectMemory;
using Platform.Data.Doublets.Decorators;
using Platform.Data.Doublets.ResizableDirectMemory.Specific;

namespace Platform.Data.Doublets.Tests
{
    public static class OptimalVariantSequenceTests
    {
        private const string SequenceExample = "зеленела зелёная зелень";

        [Fact]
        public static void LinksBasedFrequencyStoredOptimalVariantSequenceTest()
        {
            using (var scope = new TempLinksTestScope(useSequences: false))
            {
                var links = scope.Links;
                var constants = links.Constants;

                links.UseUnicode();

                var sequence = UnicodeMap.FromStringToLinkArray(SequenceExample);

                var meaningRoot = links.CreatePoint();
                var unaryOne = links.CreateAndUpdate(meaningRoot, constants.Itself);
                var frequencyMarker = links.CreateAndUpdate(meaningRoot, constants.Itself);
                var frequencyPropertyMarker = links.CreateAndUpdate(meaningRoot,
                ↪  constants.Itself);

                var unaryNumberToAddressConverter = new
                ↪  UnaryNumberToAddressAddOperationConverter<ulong>(links, unaryOne);
```

```
            var unaryNumberIncrementer = new UnaryNumberIncrementer<ulong>(links, unaryOne);
            var frequencyIncrementer = new FrequencyIncrementer<ulong>(links,
            ↪  frequencyMarker, unaryOne, unaryNumberIncrementer);
            var frequencyPropertyOperator = new PropertyOperator<ulong>(links,
            ↪  frequencyPropertyMarker, frequencyMarker);
            var index = new FrequencyIncrementingSequenceIndex<ulong>(links,
            ↪  frequencyPropertyOperator, frequencyIncrementer);
            var linkToItsFrequencyNumberConverter = new
            ↪  LinkToItsFrequencyNumberConveter<ulong>(links, frequencyPropertyOperator,
            ↪  unaryNumberToAddressConverter);
            var sequenceToItsLocalElementLevelsConverter = new
            ↪  SequenceToItsLocalElementLevelsConverter<ulong>(links,
            ↪  linkToItsFrequencyNumberConverter);
            var optimalVariantConverter = new OptimalVariantConverter<ulong>(links,
            ↪  sequenceToItsLocalElementLevelsConverter);

            var sequences = new Sequences.Sequences(links, new SequencesOptions<ulong>() {
            ↪  Walker = new LeveledSequenceWalker<ulong>(links) });

            ExecuteTest(sequences, sequence, sequenceToItsLocalElementLevelsConverter,
            ↪  index, optimalVariantConverter);
        }
    }

    [Fact]
    public static void DictionaryBasedFrequencyStoredOptimalVariantSequenceTest()
    {
        using (var scope = new TempLinksTestScope(useSequences: false))
        {
            var links = scope.Links;

            links.UseUnicode();

            var sequence = UnicodeMap.FromStringToLinkArray(SequenceExample);

            var linksToFrequencies = new Dictionary<ulong, ulong>();

            var totalSequenceSymbolFrequencyCounter = new
            ↪  TotalSequenceSymbolFrequencyCounter<ulong>(links);

            var linkFrequenciesCache = new LinkFrequenciesCache<ulong>(links,
            ↪  totalSequenceSymbolFrequencyCounter);

            var index = new
            ↪  CachedFrequencyIncrementingSequenceIndex<ulong>(linkFrequenciesCache);
            var linkToItsFrequencyNumberConverter = new FrequenciesCacheBasedLinkToItsFreque
            ↪  ncyNumberConverter<ulong>(linkFrequenciesCache);

            var sequenceToItsLocalElementLevelsConverter = new
            ↪  SequenceToItsLocalElementLevelsConverter<ulong>(links,
            ↪  linkToItsFrequencyNumberConverter);
            var optimalVariantConverter = new OptimalVariantConverter<ulong>(links,
            ↪  sequenceToItsLocalElementLevelsConverter);

            var sequences = new Sequences.Sequences(links, new SequencesOptions<ulong>() {
            ↪  Walker = new LeveledSequenceWalker<ulong>(links) });

            ExecuteTest(sequences, sequence, sequenceToItsLocalElementLevelsConverter,
            ↪  index, optimalVariantConverter);
        }
    }

    private static void ExecuteTest(Sequences.Sequences sequences, ulong[] sequence,
    ↪  SequenceToItsLocalElementLevelsConverter<ulong>
    ↪  sequenceToItsLocalElementLevelsConverter, ISequenceIndex<ulong> index,
    ↪  OptimalVariantConverter<ulong> optimalVariantConverter)
    {
        index.Add(sequence);

        var optimalVariant = optimalVariantConverter.Convert(sequence);

        var readSequence1 = sequences.ToList(optimalVariant);

        Assert.True(sequence.SequenceEqual(readSequence1));
    }

    [Fact]
    public static void SavedSequencesOptimizationTest()
```

```
100         {
101             using (var memory = new HeapResizableDirectMemory())
102             using (var disposableLinks = new UInt64ResizableDirectMemoryLinks(memory))
103             {
104                 var links = new UInt64Links(disposableLinks);
105 
106                 var meaningRoot = links.CreatePoint();
107                 var unaryOne = links.CreateAndUpdate(meaningRoot, links.Constants.Itself);
108 
109                 var linksToFrequencies = new Dictionary<ulong, ulong>();
110                 var totalSequenceSymbolFrequencyCounter = new
                    ↪  TotalSequenceSymbolFrequencyCounter<ulong>(links);
111                 var linkFrequenciesCache = new LinkFrequenciesCache<ulong>(links,
                    ↪  totalSequenceSymbolFrequencyCounter);
112                 var index = new
                    ↪  CachedFrequencyIncrementingSequenceIndex<ulong>(linkFrequenciesCache);
113                 var linkToItsFrequencyNumberConverter = new FrequenciesCacheBasedLinkToItsFreque
                    ↪  ncyNumberConverter<ulong>(linkFrequenciesCache);
114                 var sequenceToItsLocalElementLevelsConverter = new
                    ↪  SequenceToItsLocalElementLevelsConverter<ulong>(links,
                    ↪  linkToItsFrequencyNumberConverter);
115                 var optimalVariantConverter = new OptimalVariantConverter<ulong>(links,
                    ↪  sequenceToItsLocalElementLevelsConverter);
116 
117                 var sequencesOptions = new SequencesOptions<ulong>()
118                 {
119 
120                 };
121 
122                 var sequences = new Sequences.Sequences(new SynchronizedLinks<ulong>(links));
123 
124 
125             }
126             // create some sequences
127             // get list of sequences links
128             // for each sequence link
129             //   create new sequence version
130             //   if new sequence is not the same as sequence link
131             //     delete sequence link
132             //     collect garbadge
133         }
134     }
135 }
```

./Platform.Data.Doublets.Tests/ReadSequenceTests.cs

```
1   using System;
2   using System.Collections.Generic;
3   using System.Diagnostics;
4   using System.Linq;
5   using Xunit;
6   using Platform.Data.Sequences;
7   using Platform.Data.Doublets.Sequences.Converters;
8   using Platform.Data.Doublets.Sequences.Walkers;
9   using Platform.Data.Doublets.Sequences;
10 
11  namespace Platform.Data.Doublets.Tests
12  {
13      public static class ReadSequenceTests
14      {
15          [Fact]
16          public static void ReadSequenceTest()
17          {
18              const long sequenceLength = 2000;
19 
20              using (var scope = new TempLinksTestScope(useSequences: false))
21              {
22                  var links = scope.Links;
23                  var sequences = new Sequences.Sequences(links, new SequencesOptions<ulong> {
                        ↪  Walker = new LeveledSequenceWalker<ulong>(links) });
24 
25                  var sequence = new ulong[sequenceLength];
26                  for (var i = 0; i < sequenceLength; i++)
27                  {
28                      sequence[i] = links.Create();
29                  }
30 
31                  var balancedVariantConverter = new BalancedVariantConverter<ulong>(links);
32 
33                  var sw1 = Stopwatch.StartNew();
```

```
                var balancedVariant = balancedVariantConverter.Convert(sequence); sw1.Stop();

                var sw2 = Stopwatch.StartNew();
                var readSequence1 = sequences.ToList(balancedVariant); sw2.Stop();

                var sw3 = Stopwatch.StartNew();
                var readSequence2 = new List<ulong>();
                SequenceWalker.WalkRight(balancedVariant,
                                         links.GetSource,
                                         links.GetTarget,
                                         links.IsPartialPoint,
                                         readSequence2.Add);
                sw3.Stop();

                Assert.True(sequence.SequenceEqual(readSequence1));

                Assert.True(sequence.SequenceEqual(readSequence2));

                // Assert.True(sw2.Elapsed < sw3.Elapsed);

                Console.WriteLine($"Stack-based walker: {sw3.Elapsed}, Level-based reader:
                ↪ {sw2.Elapsed}");

                for (var i = 0; i < sequenceLength; i++)
                {
                    links.Delete(sequence[i]);
                }
            }
        }
    }
}
```

./Platform.Data.Doublets.Tests/ResizableDirectMemoryLinksTests.cs

```
using System.IO;
using Xunit;
using Platform.Singletons;
using Platform.Memory;
using Platform.Data.Doublets.ResizableDirectMemory.Specific;

namespace Platform.Data.Doublets.Tests
{
    public static class ResizableDirectMemoryLinksTests
    {
        private static readonly LinksConstants<ulong> _constants =
        ↪ Default<LinksConstants<ulong>>.Instance;

        [Fact]
        public static void BasicFileMappedMemoryTest()
        {
            var tempFilename = Path.GetTempFileName();
            using (var memoryAdapter = new UInt64ResizableDirectMemoryLinks(tempFilename))
            {
                memoryAdapter.TestBasicMemoryOperations();
            }
            File.Delete(tempFilename);
        }

        [Fact]
        public static void BasicHeapMemoryTest()
        {
            using (var memory = new
            ↪ HeapResizableDirectMemory(UInt64ResizableDirectMemoryLinks.DefaultLinksSizeStep))
            using (var memoryAdapter = new UInt64ResizableDirectMemoryLinks(memory,
            ↪ UInt64ResizableDirectMemoryLinks.DefaultLinksSizeStep))
            {
                memoryAdapter.TestBasicMemoryOperations();
            }
        }

        private static void TestBasicMemoryOperations(this ILinks<ulong> memoryAdapter)
        {
            var link = memoryAdapter.Create();
            memoryAdapter.Delete(link);
        }

        [Fact]
        public static void NonexistentReferencesHeapMemoryTest()
        {
            using (var memory = new
            ↪ HeapResizableDirectMemory(UInt64ResizableDirectMemoryLinks.DefaultLinksSizeStep))
```

```
            using (var memoryAdapter = new UInt64ResizableDirectMemoryLinks(memory,
            ↪ UInt64ResizableDirectMemoryLinks.DefaultLinksSizeStep))
            {
                memoryAdapter.TestNonexistentReferences();
            }
        }

        private static void TestNonexistentReferences(this ILinks<ulong> memoryAdapter)
        {
            var link = memoryAdapter.Create();
            memoryAdapter.Update(link, ulong.MaxValue, ulong.MaxValue);
            var resultLink = _constants.Null;
            memoryAdapter.Each(foundLink =>
            {
                resultLink = foundLink[_constants.IndexPart];
                return _constants.Break;
            }, _constants.Any, ulong.MaxValue, ulong.MaxValue);
            Assert.True(resultLink == link);
            Assert.True(memoryAdapter.Count(ulong.MaxValue) == 0);
            memoryAdapter.Delete(link);
        }
    }
}
```

./Platform.Data.Doublets.Tests/ScopeTests.cs

```
using Xunit;
using Platform.Scopes;
using Platform.Memory;
using Platform.Data.Doublets.Decorators;
using Platform.Reflection;
using Platform.Data.Doublets.ResizableDirectMemory.Generic;
using Platform.Data.Doublets.ResizableDirectMemory.Specific;

namespace Platform.Data.Doublets.Tests
{
    public static class ScopeTests
    {
        [Fact]
        public static void SingleDependencyTest()
        {
            using (var scope = new Scope())
            {
                scope.IncludeAssemblyOf<IMemory>();
                var instance = scope.Use<IDirectMemory>();
                Assert.IsType<HeapResizableDirectMemory>(instance);
            }
        }

        [Fact]
        public static void CascadeDependencyTest()
        {
            using (var scope = new Scope())
            {
                scope.Include<TemporaryFileMappedResizableDirectMemory>();
                scope.Include<UInt64ResizableDirectMemoryLinks>();
                var instance = scope.Use<ILinks<ulong>>();
                Assert.IsType<UInt64ResizableDirectMemoryLinks>(instance);
            }
        }

        [Fact]
        public static void FullAutoResolutionTest()
        {
            using (var scope = new Scope(autoInclude: true, autoExplore: true))
            {
                var instance = scope.Use<UInt64Links>();
                Assert.IsType<UInt64Links>(instance);
            }
        }

        [Fact]
        public static void TypeParametersTest()
        {
            using (var scope = new Scope<Types<HeapResizableDirectMemory,
            ↪ ResizableDirectMemoryLinks<ulong>>>())
            {
                var links = scope.Use<ILinks<ulong>>();
                Assert.IsType<ResizableDirectMemoryLinks<ulong>>(links);
            }
```

```
        }
    }
}
```

./Platform.Data.Doublets.Tests/SequencesTests.cs

```
using System;
using System.Collections.Generic;
using System.Diagnostics;
using System.Linq;
using Xunit;
using Platform.Collections;
using Platform.Random;
using Platform.IO;
using Platform.Singletons;
using Platform.Data.Doublets.Sequences;
using Platform.Data.Doublets.Sequences.Frequencies.Cache;
using Platform.Data.Doublets.Sequences.Frequencies.Counters;
using Platform.Data.Doublets.Sequences.Converters;
using Platform.Data.Doublets.Unicode;

namespace Platform.Data.Doublets.Tests
{
    public static class SequencesTests
    {
        private static readonly LinksConstants<ulong> _constants = Default<LinksConstants<ulong>>.Instance;

        static SequencesTests()
        {
            // Trigger static constructor to not mess with perfomance measurements
            _ = BitString.GetBitMaskFromIndex(1);
        }

        [Fact]
        public static void CreateAllVariantsTest()
        {
            const long sequenceLength = 8;

            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var sequence = new ulong[sequenceLength];
                for (var i = 0; i < sequenceLength; i++)
                {
                    sequence[i] = links.Create();
                }

                var sw1 = Stopwatch.StartNew();
                var results1 = sequences.CreateAllVariants1(sequence); sw1.Stop();

                var sw2 = Stopwatch.StartNew();
                var results2 = sequences.CreateAllVariants2(sequence); sw2.Stop();

                Assert.True(results1.Count > results2.Length);
                Assert.True(sw1.Elapsed > sw2.Elapsed);

                for (var i = 0; i < sequenceLength; i++)
                {
                    links.Delete(sequence[i]);
                }

                Assert.True(links.Count() == 0);
            }
        }

        //[Fact]
        //public void CUDTest()
        //{
        //    var tempFilename = Path.GetTempFileName();

        //    const long sequenceLength = 8;

        //    const ulong itself = LinksConstants.Itself;

        //    using (var memoryAdapter = new ResizableDirectMemoryLinks(tempFilename, DefaultLinksSizeStep))
        //    using (var links = new Links(memoryAdapter))
        //    {
        //        var sequence = new ulong[sequenceLength];
```

```
75          //        for (var i = 0; i < sequenceLength; i++)
76          //            sequence[i] = links.Create(itself, itself);
77
78          //        SequencesOptions o = new SequencesOptions();
79
80          // TODO: Из числа в bool значения o.UseSequenceMarker = ((value & 1) != 0)
81          //        o.
82
83          //        var sequences = new Sequences(links);
84
85          //        var sw1 = Stopwatch.StartNew();
86          //        var results1 = sequences.CreateAllVariants1(sequence); sw1.Stop();
87
88          //        var sw2 = Stopwatch.StartNew();
89          //        var results2 = sequences.CreateAllVariants2(sequence); sw2.Stop();
90
91          //        Assert.True(results1.Count > results2.Length);
92          //        Assert.True(sw1.Elapsed > sw2.Elapsed);
93
94          //        for (var i = 0; i < sequenceLength; i++)
95          //            links.Delete(sequence[i]);
96          //    }
97
98          //    File.Delete(tempFilename);
99          //}
100
101         [Fact]
102         public static void AllVariantsSearchTest()
103         {
104             const long sequenceLength = 8;
105
106             using (var scope = new TempLinksTestScope(useSequences: true))
107             {
108                 var links = scope.Links;
109                 var sequences = scope.Sequences;
110
111                 var sequence = new ulong[sequenceLength];
112                 for (var i = 0; i < sequenceLength; i++)
113                 {
114                     sequence[i] = links.Create();
115                 }
116
117                 var createResults = sequences.CreateAllVariants2(sequence).Distinct().ToArray();
118
119                 //for (int i = 0; i < createResults.Length; i++)
120                 //    sequences.Create(createResults[i]);
121
122                 var sw0 = Stopwatch.StartNew();
123                 var searchResults0 = sequences.GetAllMatchingSequences0(sequence); sw0.Stop();
124
125                 var sw1 = Stopwatch.StartNew();
126                 var searchResults1 = sequences.GetAllMatchingSequences1(sequence); sw1.Stop();
127
128                 var sw2 = Stopwatch.StartNew();
129                 var searchResults2 = sequences.Each1(sequence); sw2.Stop();
130
131                 var sw3 = Stopwatch.StartNew();
132                 var searchResults3 = sequences.Each(sequence.ConvertToRestrictionsValues());
                    ↪  sw3.Stop();
133
134                 var intersection0 = createResults.Intersect(searchResults0).ToList();
135                 Assert.True(intersection0.Count == searchResults0.Count);
136                 Assert.True(intersection0.Count == createResults.Length);
137
138                 var intersection1 = createResults.Intersect(searchResults1).ToList();
139                 Assert.True(intersection1.Count == searchResults1.Count);
140                 Assert.True(intersection1.Count == createResults.Length);
141
142                 var intersection2 = createResults.Intersect(searchResults2).ToList();
143                 Assert.True(intersection2.Count == searchResults2.Count);
144                 Assert.True(intersection2.Count == createResults.Length);
145
146                 var intersection3 = createResults.Intersect(searchResults3).ToList();
147                 Assert.True(intersection3.Count == searchResults3.Count);
148                 Assert.True(intersection3.Count == createResults.Length);
149
150                 for (var i = 0; i < sequenceLength; i++)
151                 {
152                     links.Delete(sequence[i]);
153                 }
```

```
154             }
155         }
156 
157         [Fact]
158         public static void BalancedVariantSearchTest()
159         {
160             const long sequenceLength = 200;
161 
162             using (var scope = new TempLinksTestScope(useSequences: true))
163             {
164                 var links = scope.Links;
165                 var sequences = scope.Sequences;
166 
167                 var sequence = new ulong[sequenceLength];
168                 for (var i = 0; i < sequenceLength; i++)
169                 {
170                     sequence[i] = links.Create();
171                 }
172 
173                 var balancedVariantConverter = new BalancedVariantConverter<ulong>(links);
174 
175                 var sw1 = Stopwatch.StartNew();
176                 var balancedVariant = balancedVariantConverter.Convert(sequence); sw1.Stop();
177 
178                 var sw2 = Stopwatch.StartNew();
179                 var searchResults2 = sequences.GetAllMatchingSequences0(sequence); sw2.Stop();
180 
181                 var sw3 = Stopwatch.StartNew();
182                 var searchResults3 = sequences.GetAllMatchingSequences1(sequence); sw3.Stop();
183 
184                 // На количестве в 200 элементов это будет занимать вечность
185                 //var sw4 = Stopwatch.StartNew();
186                 //var searchResults4 = sequences.Each(sequence); sw4.Stop();
187 
188                 Assert.True(searchResults2.Count == 1 && balancedVariant == searchResults2[0]);
189 
190                 Assert.True(searchResults3.Count == 1 && balancedVariant ==
                    ↪ searchResults3.First());
191 
192                 //Assert.True(sw1.Elapsed < sw2.Elapsed);
193 
194                 for (var i = 0; i < sequenceLength; i++)
195                 {
196                     links.Delete(sequence[i]);
197                 }
198             }
199         }
200 
201         [Fact]
202         public static void AllPartialVariantsSearchTest()
203         {
204             const long sequenceLength = 8;
205 
206             using (var scope = new TempLinksTestScope(useSequences: true))
207             {
208                 var links = scope.Links;
209                 var sequences = scope.Sequences;
210 
211                 var sequence = new ulong[sequenceLength];
212                 for (var i = 0; i < sequenceLength; i++)
213                 {
214                     sequence[i] = links.Create();
215                 }
216 
217                 var createResults = sequences.CreateAllVariants2(sequence);
218 
219                 //var createResultsStrings = createResults.Select(x => x + ": " +
                    ↪ sequences.FormatSequence(x)).ToList();
220                 //Global.Trash = createResultsStrings;
221 
222                 var partialSequence = new ulong[sequenceLength - 2];
223 
224                 Array.Copy(sequence, 1, partialSequence, 0, (int)sequenceLength - 2);
225 
226                 var sw1 = Stopwatch.StartNew();
227                 var searchResults1 =
                    ↪ sequences.GetAllPartiallyMatchingSequences0(partialSequence); sw1.Stop();
228 
229                 var sw2 = Stopwatch.StartNew();
```

```
230                 var searchResults2 =
                    ↪  sequences.GetAllPartiallyMatchingSequences1(partialSequence); sw2.Stop();
231
232                 //var sw3 = Stopwatch.StartNew();
233                 //var searchResults3 =
                    ↪  sequences.GetAllPartiallyMatchingSequences2(partialSequence); sw3.Stop();
234
235                 var sw4 = Stopwatch.StartNew();
236                 var searchResults4 =
                    ↪  sequences.GetAllPartiallyMatchingSequences3(partialSequence); sw4.Stop();
237
238                 //Global.Trash = searchResults3;
239
240                 //var searchResults1Strings = searchResults1.Select(x => x + ": " +
                    ↪  sequences.FormatSequence(x)).ToList();
241                 //Global.Trash = searchResults1Strings;
242
243                 var intersection1 = createResults.Intersect(searchResults1).ToList();
244                 Assert.True(intersection1.Count == createResults.Length);
245
246                 var intersection2 = createResults.Intersect(searchResults2).ToList();
247                 Assert.True(intersection2.Count == createResults.Length);
248
249                 var intersection4 = createResults.Intersect(searchResults4).ToList();
250                 Assert.True(intersection4.Count == createResults.Length);
251
252                 for (var i = 0; i < sequenceLength; i++)
253                 {
254                     links.Delete(sequence[i]);
255                 }
256             }
257         }
258
259         [Fact]
260         public static void BalancedPartialVariantsSearchTest()
261         {
262             const long sequenceLength = 200;
263
264             using (var scope = new TempLinksTestScope(useSequences: true))
265             {
266                 var links = scope.Links;
267                 var sequences = scope.Sequences;
268
269                 var sequence = new ulong[sequenceLength];
270                 for (var i = 0; i < sequenceLength; i++)
271                 {
272                     sequence[i] = links.Create();
273                 }
274
275                 var balancedVariantConverter = new BalancedVariantConverter<ulong>(links);
276
277                 var balancedVariant = balancedVariantConverter.Convert(sequence);
278
279                 var partialSequence = new ulong[sequenceLength - 2];
280
281                 Array.Copy(sequence, 1, partialSequence, 0, (int)sequenceLength - 2);
282
283                 var sw1 = Stopwatch.StartNew();
284                 var searchResults1 =
                    ↪  sequences.GetAllPartiallyMatchingSequences0(partialSequence); sw1.Stop();
285
286                 var sw2 = Stopwatch.StartNew();
287                 var searchResults2 =
                    ↪  sequences.GetAllPartiallyMatchingSequences1(partialSequence); sw2.Stop();
288
289                 Assert.True(searchResults1.Count == 1 && balancedVariant == searchResults1[0]);
290
291                 Assert.True(searchResults2.Count == 1 && balancedVariant ==
                    ↪  searchResults2.First());
292
293                 for (var i = 0; i < sequenceLength; i++)
294                 {
295                     links.Delete(sequence[i]);
296                 }
297             }
298         }
299
300         [Fact(Skip = "Correct implementation is pending")]
301         public static void PatternMatchTest()
```

```
        {
            var zeroOrMany = Sequences.Sequences.ZeroOrMany;

            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var e1 = links.Create();
                var e2 = links.Create();

                var sequence = new[]
                {
                    e1, e2, e1, e2 // mama / papa
                };

                var balancedVariantConverter = new BalancedVariantConverter<ulong>(links);

                var balancedVariant = balancedVariantConverter.Convert(sequence);

                // 1: [1]
                // 2: [2]
                // 3: [1,2]
                // 4: [1,2,1,2]

                var doublet = links.GetSource(balancedVariant);

                var matchedSequences1 = sequences.MatchPattern(e2, e1, zeroOrMany);

                Assert.True(matchedSequences1.Count == 0);

                var matchedSequences2 = sequences.MatchPattern(zeroOrMany, e2, e1);

                Assert.True(matchedSequences2.Count == 0);

                var matchedSequences3 = sequences.MatchPattern(e1, zeroOrMany, e1);

                Assert.True(matchedSequences3.Count == 0);

                var matchedSequences4 = sequences.MatchPattern(e1, zeroOrMany, e2);

                Assert.Contains(doublet, matchedSequences4);
                Assert.Contains(balancedVariant, matchedSequences4);

                for (var i = 0; i < sequence.Length; i++)
                {
                    links.Delete(sequence[i]);
                }
            }
        }

        [Fact]
        public static void IndexTest()
        {
            using (var scope = new TempLinksTestScope(new SequencesOptions<ulong> { UseIndex =
            ↪  true }, useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;
                var index = sequences.Options.Index;

                var e1 = links.Create();
                var e2 = links.Create();

                var sequence = new[]
                {
                    e1, e2, e1, e2 // mama / papa
                };

                Assert.False(index.MightContain(sequence));

                index.Add(sequence);

                Assert.True(index.MightContain(sequence));
            }
        }

        /// <summary>Imported from https://raw.githubusercontent.com/wiki/Konard/LinksPlatform/%
        ↪  D0%9E-%D1%82%D0%BE%D0%BC%2C-%D0%BA%D0%B0%D0%BA-%D0%B2%D1%81%D1%91-%D0%BD%D0%B0%D1%87
        ↪  %D0%B8%D0%BD%D0%B0%D0%BB%D0%BE%D1%81%D1%8C.md</summary>
```

```
379         private static readonly string _exampleText =
380             @"([english
                ↪  version](https://github.com/Konard/LinksPlatform/wiki/About-the-beginning))
381 
382 Обозначение пустоты, какое оно? Темнота ли это? Там где отсутствие света, отсутствие фотонов
    ↪  (носителей света)? Или это то, что полностью отражает свет? Пустой белый лист бумаги? Там
    ↪  где есть место для нового начала? Разве пустота это не характеристика пространства?
    ↪  Пространство это то, что можно чем-то наполнить?
383 
384 [![чёрное пространство, белое
    ↪  пространство](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/1.png
    ↪  ""чёрное пространство, белое пространство"")](https://raw.githubusercontent.com/Konard/Links
    ↪  Platform/master/doc/Intro/1.png)
385 
386 Что может быть минимальным рисунком, образом, графикой? Может быть это точка? Это ли простейшая
    ↪  форма? Но есть ли у точки размер? Цвет? Масса? Координаты? Время существования?
387 
388 [![чёрное пространство, чёрная
    ↪  точка](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/2.png
    ↪  ""чёрное пространство, чёрная
    ↪  точка"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/2.png)
389 
390 А что если повторить? Сделать копию? Создать дубликат? Из одного сделать два? Может это быть
    ↪  так? Инверсия? Отражение? Сумма?
391 
392 [![белая точка, чёрная
    ↪  точка](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/3.png ""белая
    ↪  точка, чёрная
    ↪  точка"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/3.png)
393 
394 А что если мы вообразим движение? Нужно ли время? Каким самым коротким будет путь? Что будет
    ↪  если этот путь зафиксировать? Запомнить след? Как две точки становятся линией? Чертой?
    ↪  Гранью? Разделителем? Единицей?
395 
396 [![две белые точки, чёрная вертикальная
    ↪  линия](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/4.png ""две
    ↪  белые точки, чёрная вертикальная
    ↪  линия"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/4.png)
397 
398 Можно ли замкнуть движение? Может ли это быть кругом? Можно ли замкнуть время? Или остаётся
    ↪  только спираль? Но что если замкнуть предел? Создать ограничение, разделение? Получится
    ↪  замкнутая область? Полностью отделённая от всего остального? Но что это всё остальное? Что
    ↪  можно делить? В каком направлении? Ничего или всё? Пустота или полнота? Начало или конец?
    ↪  Или может быть это единица и ноль? Дуальность? Противоположность? А что будет с кругом если
    ↪  у него нет размера? Будет ли круг точкой? Точка состоящая из точек?
399 
400 [![белая вертикальная линия, чёрный
    ↪  круг](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/5.png ""белая
    ↪  вертикальная линия, чёрный
    ↪  круг"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/5.png)
401 
402 Как ещё можно использовать грань, черту, линию? А что если она может что-то соединять, может
    ↪  тогда её нужно повернуть? Почему то, что перпендикулярно вертикальному горизонтально?
    ↪  Горизонт? Инвертирует ли это смысл? Что такое смысл? Из чего состоит смысл? Существует ли
    ↪  элементарная единица смысла?
403 
404 [![белый круг, чёрная горизонтальная
    ↪  линия](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/6.png ""белый
    ↪  круг, чёрная горизонтальная
    ↪  линия"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/6.png)
405 
406 Соединять, допустим, а какой смысл в этом есть ещё? Что если помимо смысла ""соединить,
    ↪  связать"", есть ещё и смысл направления ""от начала к концу""? От предка к потомку? От
    ↪  родителя к ребёнку? От общего к частному?
407 
408 [![белая горизонтальная линия, чёрная горизонтальная
    ↪  стрелка](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/7.png
    ↪  ""белая горизонтальная линия, чёрная горизонтальная
    ↪  стрелка"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/7.png)
409 
410 Шаг назад. Возьмём опять отделённую область, которая лишь та же замкнутая линия, что ещё она
    ↪  может представлять собой? Объект? Но в чём его суть? Разве не в том, что у него есть
    ↪  граница, разделяющая внутреннее и внешнее? Допустим связь, стрелка, линия соединяет два
    ↪  объекта, как бы это выглядело?
411 
412 [![белая связь, чёрная направленная
    ↪  связь](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/8.png ""белая
    ↪  связь, чёрная направленная
    ↪  связь"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/8.png)
413 
```

```
Допустим у нас есть смысл ""связать"" и смысл ""направления"", много ли это нам даёт? Много ли вариантов интерпретации? А что если уточнить, каким именно образом выполнена связь? Что если можно задать ей чёткий, конкретный смысл? Что это будет? Тип? Глагол? Связка? Действие? Трансформация? Переход из состояния в состояние? Или всё это и есть объект, суть которого в его конечном состоянии, если конечно конец определён направлением?

[![белая обычная и направленная связи, чёрная типизированная связь](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/9.png ""белая обычная и направленная связи, чёрная типизированная связь"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/9.png)

А что если всё это время, мы смотрели на суть как бы снаружи? Можно ли взглянуть на это изнутри? Что будет внутри объектов? Объекты ли это? Или это связи? Может ли эта структура описать сама себя? Но что тогда получится, разве это не рекурсия? Может это фрактал?

[![белая обычная и направленная связи с рекурсивной внутренней структурой, чёрная типизированная связь с рекурсивной внутренней структурой](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/10.png ""белая обычная и направленная связи с рекурсивной внутренней структурой, чёрная типизированная связь с рекурсивной внутренней структурой"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/10.png)

На один уровень внутрь (вниз)? Или на один уровень во вне (вверх)? Или это можно назвать шагом рекурсии или фрактала?

[![белая обычная и направленная связи с двойной рекурсивной внутренней структурой, чёрная типизированная связь с двойной рекурсивной внутренней структурой](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/11.png ""белая обычная и направленная связи с двойной рекурсивной внутренней структурой, чёрная типизированная связь с двойной рекурсивной внутренней структурой"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/11.png)

Последовательность? Массив? Список? Множество? Объект? Таблица? Элементы? Цвета? Символы? Буквы? Слово? Цифры? Число? Алфавит? Дерево? Сеть? Граф? Гиперграф?

[![белая обычная и направленная связи со структурой из 8 цветных элементов последовательности, чёрная типизированная связь со структурой из 8 цветных элементов последовательности](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/12.png ""белая обычная и направленная связи со структурой из 8 цветных элементов последовательности, чёрная типизированная связь со структурой из 8 цветных элементов последовательности"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/12.png)

...

[![анимация](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/intro-animation-500.gif ""анимация"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/intro-animation-500.gif)";

        private static readonly string _exampleLoremIpsumText =
            @"Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.
Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat.";

        [Fact]
        public static void CompressionTest()
        {
            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var e1 = links.Create();
                var e2 = links.Create();

                var sequence = new[]
                {
                    e1, e2, e1, e2 // mama / papa / template [(m/p), a] { [1] [2] [1] [2] }
                };

                var balancedVariantConverter = new BalancedVariantConverter<ulong>(links.Unsync);
                var totalSequenceSymbolFrequencyCounter = new TotalSequenceSymbolFrequencyCounter<ulong>(links.Unsync);
                var doubletFrequenciesCache = new LinkFrequenciesCache<ulong>(links.Unsync, totalSequenceSymbolFrequencyCounter);
                var compressingConverter = new CompressingConverter<ulong>(links.Unsync, balancedVariantConverter, doubletFrequenciesCache);

```

```
459                 var compressedVariant = compressingConverter.Convert(sequence);
460
461                 // 1: [1]       (1->1) point
462                 // 2: [2]       (2->2) point
463                 // 3: [1,2]     (1->2) doublet
464                 // 4: [1,2,1,2] (3->3) doublet
465
466                 Assert.True(links.GetSource(links.GetSource(compressedVariant)) == sequence[0]);
467                 Assert.True(links.GetTarget(links.GetSource(compressedVariant)) == sequence[1]);
468                 Assert.True(links.GetSource(links.GetTarget(compressedVariant)) == sequence[2]);
469                 Assert.True(links.GetTarget(links.GetTarget(compressedVariant)) == sequence[3]);
470
471                 var source = _constants.SourcePart;
472                 var target = _constants.TargetPart;
473
474                 Assert.True(links.GetByKeys(compressedVariant, source, source) == sequence[0]);
475                 Assert.True(links.GetByKeys(compressedVariant, source, target) == sequence[1]);
476                 Assert.True(links.GetByKeys(compressedVariant, target, source) == sequence[2]);
477                 Assert.True(links.GetByKeys(compressedVariant, target, target) == sequence[3]);
478
479                 // 4 - length of sequence
480                 Assert.True(links.GetSquareMatrixSequenceElementByIndex(compressedVariant, 4, 0)
                    ↪  == sequence[0]);
481                 Assert.True(links.GetSquareMatrixSequenceElementByIndex(compressedVariant, 4, 1)
                    ↪  == sequence[1]);
482                 Assert.True(links.GetSquareMatrixSequenceElementByIndex(compressedVariant, 4, 2)
                    ↪  == sequence[2]);
483                 Assert.True(links.GetSquareMatrixSequenceElementByIndex(compressedVariant, 4, 3)
                    ↪  == sequence[3]);
484             }
485         }
486
487         [Fact]
488         public static void CompressionEfficiencyTest()
489         {
490             var strings = _exampleLoremIpsumText.Split(new[] { '\n', '\r' },
                ↪  StringSplitOptions.RemoveEmptyEntries);
491             var arrays = strings.Select(UnicodeMap.FromStringToLinkArray).ToArray();
492             var totalCharacters = arrays.Select(x => x.Length).Sum();
493
494             using (var scope1 = new TempLinksTestScope(useSequences: true))
495             using (var scope2 = new TempLinksTestScope(useSequences: true))
496             using (var scope3 = new TempLinksTestScope(useSequences: true))
497             {
498                 scope1.Links.Unsync.UseUnicode();
499                 scope2.Links.Unsync.UseUnicode();
500                 scope3.Links.Unsync.UseUnicode();
501
502                 var balancedVariantConverter1 = new
                    ↪  BalancedVariantConverter<ulong>(scope1.Links.Unsync);
503                 var totalSequenceSymbolFrequencyCounter = new
                    ↪  TotalSequenceSymbolFrequencyCounter<ulong>(scope1.Links.Unsync);
504                 var linkFrequenciesCache1 = new LinkFrequenciesCache<ulong>(scope1.Links.Unsync,
                    ↪  totalSequenceSymbolFrequencyCounter);
505                 var compressor1 = new CompressingConverter<ulong>(scope1.Links.Unsync,
                    ↪  balancedVariantConverter1, linkFrequenciesCache1,
                    ↪  doInitialFrequenciesIncrement: false);
506
507                 //var compressor2 = scope2.Sequences;
508                 var compressor3 = scope3.Sequences;
509
510                 var constants = Default<LinksConstants<ulong>>.Instance;
511
512                 var sequences = compressor3;
513                 //var meaningRoot = links.CreatePoint();
514                 //var unaryOne = links.CreateAndUpdate(meaningRoot, constants.Itself);
515                 //var frequencyMarker = links.CreateAndUpdate(meaningRoot, constants.Itself);
516                 //var frequencyPropertyMarker = links.CreateAndUpdate(meaningRoot,
                    ↪  constants.Itself);
517
518                 //var unaryNumberToAddressConverter = new
                    ↪  UnaryNumberToAddressAddOperationConverter<ulong>(links, unaryOne);
519                 //var unaryNumberIncrementer = new UnaryNumberIncrementer<ulong>(links,
                    ↪  unaryOne);
520                 //var frequencyIncrementer = new FrequencyIncrementer<ulong>(links,
                    ↪  frequencyMarker, unaryOne, unaryNumberIncrementer);
521                 //var frequencyPropertyOperator = new FrequencyPropertyOperator<ulong>(links,
                    ↪  frequencyPropertyMarker, frequencyMarker);
```

```
522                 //var linkFrequencyIncrementer = new LinkFrequencyIncrementer<ulong>(links,
                    ↪  frequencyPropertyOperator, frequencyIncrementer);
523                 //var linkToItsFrequencyNumberConverter = new
                    ↪  LinkToItsFrequencyNumberConveter<ulong>(links, frequencyPropertyOperator,
                    ↪  unaryNumberToAddressConverter);
524
525                 var linkFrequenciesCache3 = new LinkFrequenciesCache<ulong>(scope3.Links.Unsync,
                    ↪  totalSequenceSymbolFrequencyCounter);
526
527                 var linkToItsFrequencyNumberConverter = new FrequenciesCacheBasedLinkToItsFreque
                    ↪  ncyNumberConverter<ulong>(linkFrequenciesCache3);
528
529                 var sequenceToItsLocalElementLevelsConverter = new
                    ↪  SequenceToItsLocalElementLevelsConverter<ulong>(scope3.Links.Unsync,
                    ↪  linkToItsFrequencyNumberConverter);
530                 var optimalVariantConverter = new
                    ↪  OptimalVariantConverter<ulong>(scope3.Links.Unsync,
                    ↪  sequenceToItsLocalElementLevelsConverter);
531
532                 var compressed1 = new ulong[arrays.Length];
533                 var compressed2 = new ulong[arrays.Length];
534                 var compressed3 = new ulong[arrays.Length];
535
536                 var START = 0;
537                 var END = arrays.Length;
538
539                 //for (int i = START; i < END; i++)
540                 //    linkFrequenciesCache1.IncrementFrequencies(arrays[i]);
541
542                 var initialCount1 = scope2.Links.Unsync.Count();
543
544                 var sw1 = Stopwatch.StartNew();
545
546                 for (int i = START; i < END; i++)
547                 {
548                     linkFrequenciesCache1.IncrementFrequencies(arrays[i]);
549                     compressed1[i] = compressor1.Convert(arrays[i]);
550                 }
551
552                 var elapsed1 = sw1.Elapsed;
553
554                 var balancedVariantConverter2 = new
                    ↪  BalancedVariantConverter<ulong>(scope2.Links.Unsync);
555
556                 var initialCount2 = scope2.Links.Unsync.Count();
557
558                 var sw2 = Stopwatch.StartNew();
559
560                 for (int i = START; i < END; i++)
561                 {
562                     compressed2[i] = balancedVariantConverter2.Convert(arrays[i]);
563                 }
564
565                 var elapsed2 = sw2.Elapsed;
566
567                 for (int i = START; i < END; i++)
568                 {
569                     linkFrequenciesCache3.IncrementFrequencies(arrays[i]);
570                 }
571
572                 var initialCount3 = scope3.Links.Unsync.Count();
573
574                 var sw3 = Stopwatch.StartNew();
575
576                 for (int i = START; i < END; i++)
577                 {
578                     //linkFrequenciesCache3.IncrementFrequencies(arrays[i]);
579                     compressed3[i] = optimalVariantConverter.Convert(arrays[i]);
580                 }
581
582                 var elapsed3 = sw3.Elapsed;
583
584                 Console.WriteLine($"Compressor: {elapsed1}, Balanced variant: {elapsed2},
                    ↪  Optimal variant: {elapsed3}");
585
586                 // Assert.True(elapsed1 > elapsed2);
587
588                 // Checks
589                 for (int i = START; i < END; i++)
```

```
590                 {
591                     var sequence1 = compressed1[i];
592                     var sequence2 = compressed2[i];
593                     var sequence3 = compressed3[i];
594 
595                     var decompress1 = UnicodeMap.FromSequenceLinkToString(sequence1,
                        ↪ scope1.Links.Unsync);
596 
597                     var decompress2 = UnicodeMap.FromSequenceLinkToString(sequence2,
                        ↪ scope2.Links.Unsync);
598 
599                     var decompress3 = UnicodeMap.FromSequenceLinkToString(sequence3,
                        ↪ scope3.Links.Unsync);
600 
601                     var structure1 = scope1.Links.Unsync.FormatStructure(sequence1, link =>
                        ↪ link.IsPartialPoint());
602                     var structure2 = scope2.Links.Unsync.FormatStructure(sequence2, link =>
                        ↪ link.IsPartialPoint());
603                     var structure3 = scope3.Links.Unsync.FormatStructure(sequence3, link =>
                        ↪ link.IsPartialPoint());
604 
605                     //if (sequence1 != Constants.Null && sequence2 != Constants.Null &&
                        ↪ arrays[i].Length > 3)
606                     //    Assert.False(structure1 == structure2);
607                     //if (sequence3 != Constants.Null && sequence2 != Constants.Null &&
                        ↪ arrays[i].Length > 3)
608                     //    Assert.False(structure3 == structure2);
609 
610                     Assert.True(strings[i] == decompress1 && decompress1 == decompress2);
611                     Assert.True(strings[i] == decompress3 && decompress3 == decompress2);
612                 }
613 
614                 Assert.True((int)(scope1.Links.Unsync.Count() - initialCount1) <
                    ↪ totalCharacters);
615                 Assert.True((int)(scope2.Links.Unsync.Count() - initialCount2) <
                    ↪ totalCharacters);
616                 Assert.True((int)(scope3.Links.Unsync.Count() - initialCount3) <
                    ↪ totalCharacters);
617 
618                 Console.WriteLine($"{(double)(scope1.Links.Unsync.Count() - initialCount1) /
                    ↪ totalCharacters} | {(double)(scope2.Links.Unsync.Count() - initialCount2) /
                    ↪ totalCharacters} | {(double)(scope3.Links.Unsync.Count() - initialCount3) /
                    ↪ totalCharacters}");
619 
620                 Assert.True(scope1.Links.Unsync.Count() - initialCount1 <
                    ↪ scope2.Links.Unsync.Count() - initialCount2);
621                 Assert.True(scope3.Links.Unsync.Count() - initialCount3 <
                    ↪ scope2.Links.Unsync.Count() - initialCount2);
622 
623                 var duplicateProvider1 = new
                    ↪ DuplicateSegmentsProvider<ulong>(scope1.Links.Unsync, scope1.Sequences);
624                 var duplicateProvider2 = new
                    ↪ DuplicateSegmentsProvider<ulong>(scope2.Links.Unsync, scope2.Sequences);
625                 var duplicateProvider3 = new
                    ↪ DuplicateSegmentsProvider<ulong>(scope3.Links.Unsync, scope3.Sequences);
626 
627                 var duplicateCounter1 = new DuplicateSegmentsCounter<ulong>(duplicateProvider1);
628                 var duplicateCounter2 = new DuplicateSegmentsCounter<ulong>(duplicateProvider2);
629                 var duplicateCounter3 = new DuplicateSegmentsCounter<ulong>(duplicateProvider3);
630 
631                 var duplicates1 = duplicateCounter1.Count();
632 
633                 ConsoleHelpers.Debug("------");
634 
635                 var duplicates2 = duplicateCounter2.Count();
636 
637                 ConsoleHelpers.Debug("------");
638 
639                 var duplicates3 = duplicateCounter3.Count();
640 
641                 Console.WriteLine($"{duplicates1} | {duplicates2} | {duplicates3}");
642 
643                 linkFrequenciesCache1.ValidateFrequencies();
644                 linkFrequenciesCache3.ValidateFrequencies();
645             }
646         }
647 
648         [Fact]
```

```
649         public static void CompressionStabilityTest()
650         {
651             // TODO: Fix bug (do a separate test)
652             //const ulong minNumbers = 0;
653             //const ulong maxNumbers = 1000;
654 
655             const ulong minNumbers = 10000;
656             const ulong maxNumbers = 12500;
657 
658             var strings = new List<string>();
659 
660             for (ulong i = minNumbers; i < maxNumbers; i++)
661             {
662                 strings.Add(i.ToString());
663             }
664 
665             var arrays = strings.Select(UnicodeMap.FromStringToLinkArray).ToArray();
666             var totalCharacters = arrays.Select(x => x.Length).Sum();
667 
668             using (var scope1 = new TempLinksTestScope(useSequences: true, sequencesOptions: new
                ↪  SequencesOptions<ulong> { UseCompression = true,
                ↪  EnforceSingleSequenceVersionOnWriteBasedOnExisting = true }))
669             using (var scope2 = new TempLinksTestScope(useSequences: true))
670             {
671                 scope1.Links.UseUnicode();
672                 scope2.Links.UseUnicode();
673 
674                 //var compressor1 = new Compressor(scope1.Links.Unsync, scope1.Sequences);
675                 var compressor1 = scope1.Sequences;
676                 var compressor2 = scope2.Sequences;
677 
678                 var compressed1 = new ulong[arrays.Length];
679                 var compressed2 = new ulong[arrays.Length];
680 
681                 var sw1 = Stopwatch.StartNew();
682 
683                 var START = 0;
684                 var END = arrays.Length;
685 
686                 // Collisions proved (cannot be solved by max doublet comparison, no stable rule)
687                 // Stability issue starts at 10001 or 11000
688                 //for (int i = START; i < END; i++)
689                 //{
690                 //    var first = compressor1.Compress(arrays[i]);
691                 //    var second = compressor1.Compress(arrays[i]);
692 
693                 //    if (first == second)
694                 //        compressed1[i] = first;
695                 //    else
696                 //    {
697                 //        // TODO: Find a solution for this case
698                 //    }
699                 //}
700 
701                 for (int i = START; i < END; i++)
702                 {
703                     var first = compressor1.Create(arrays[i].ConvertToRestrictionsValues());
704                     var second = compressor1.Create(arrays[i].ConvertToRestrictionsValues());
705 
706                     if (first == second)
707                     {
708                         compressed1[i] = first;
709                     }
710                     else
711                     {
712                         // TODO: Find a solution for this case
713                     }
714                 }
715 
716                 var elapsed1 = sw1.Elapsed;
717 
718                 var balancedVariantConverter = new BalancedVariantConverter<ulong>(scope2.Links);
719 
720                 var sw2 = Stopwatch.StartNew();
721 
722                 for (int i = START; i < END; i++)
723                 {
724                     var first = balancedVariantConverter.Convert(arrays[i]);
725                     var second = balancedVariantConverter.Convert(arrays[i]);
726 
```

```
727                     if (first == second)
728                     {
729                         compressed2[i] = first;
730                     }
731                 }
732 
733                 var elapsed2 = sw2.Elapsed;
734 
735                 Debug.WriteLine($"Compressor: {elapsed1}, Balanced sequence creator:
                    ↪ {elapsed2}");
736 
737                 Assert.True(elapsed1 > elapsed2);
738 
739                 // Checks
740                 for (int i = START; i < END; i++)
741                 {
742                     var sequence1 = compressed1[i];
743                     var sequence2 = compressed2[i];
744 
745                     if (sequence1 != _constants.Null && sequence2 != _constants.Null)
746                     {
747                         var decompress1 = UnicodeMap.FromSequenceLinkToString(sequence1,
                            ↪ scope1.Links);
748 
749                         var decompress2 = UnicodeMap.FromSequenceLinkToString(sequence2,
                            ↪ scope2.Links);
750 
751                         //var structure1 = scope1.Links.FormatStructure(sequence1, link =>
                            ↪ link.IsPartialPoint());
752                         //var structure2 = scope2.Links.FormatStructure(sequence2, link =>
                            ↪ link.IsPartialPoint());
753 
754                         //if (sequence1 != Constants.Null && sequence2 != Constants.Null &&
                            ↪ arrays[i].Length > 3)
755                         //    Assert.False(structure1 == structure2);
756 
757                         Assert.True(strings[i] == decompress1 && decompress1 == decompress2);
758                     }
759                 }
760 
761                 Assert.True((int)(scope1.Links.Count() - UnicodeMap.MapSize) < totalCharacters);
762                 Assert.True((int)(scope2.Links.Count() - UnicodeMap.MapSize) < totalCharacters);
763 
764                 Debug.WriteLine($"{(double)(scope1.Links.Count() - UnicodeMap.MapSize) /
                    ↪ totalCharacters} | {(double)(scope2.Links.Count() - UnicodeMap.MapSize) /
                    ↪ totalCharacters}");
765 
766                 Assert.True(scope1.Links.Count() <= scope2.Links.Count());
767 
768                 //compressor1.ValidateFrequencies();
769             }
770         }
771 
772         [Fact]
773         public static void RundomNumbersCompressionQualityTest()
774         {
775             const ulong N = 500;
776 
777             //const ulong minNumbers = 10000;
778             //const ulong maxNumbers = 20000;
779 
780             //var strings = new List<string>();
781 
782             //for (ulong i = 0; i < N; i++)
783             //    strings.Add(RandomHelpers.DefaultFactory.NextUInt64(minNumbers,
                    ↪ maxNumbers).ToString());
784 
785             var strings = new List<string>();
786 
787             for (ulong i = 0; i < N; i++)
788             {
789                 strings.Add(RandomHelpers.Default.NextUInt64().ToString());
790             }
791 
792             strings = strings.Distinct().ToList();
793 
794             var arrays = strings.Select(UnicodeMap.FromStringToLinkArray).ToArray();
795             var totalCharacters = arrays.Select(x => x.Length).Sum();
796 
```

```
797             using (var scope1 = new TempLinksTestScope(useSequences: true, sequencesOptions: new
                ↪  SequencesOptions<ulong> { UseCompression = true,
                ↪  EnforceSingleSequenceVersionOnWriteBasedOnExisting = true }))
798             using (var scope2 = new TempLinksTestScope(useSequences: true))
799             {
800                 scope1.Links.UseUnicode();
801                 scope2.Links.UseUnicode();
802
803                 var compressor1 = scope1.Sequences;
804                 var compressor2 = scope2.Sequences;
805
806                 var compressed1 = new ulong[arrays.Length];
807                 var compressed2 = new ulong[arrays.Length];
808
809                 var sw1 = Stopwatch.StartNew();
810
811                 var START = 0;
812                 var END = arrays.Length;
813
814                 for (int i = START; i < END; i++)
815                 {
816                     compressed1[i] = compressor1.Create(arrays[i].ConvertToRestrictionsValues());
817                 }
818
819                 var elapsed1 = sw1.Elapsed;
820
821                 var balancedVariantConverter = new BalancedVariantConverter<ulong>(scope2.Links);
822
823                 var sw2 = Stopwatch.StartNew();
824
825                 for (int i = START; i < END; i++)
826                 {
827                     compressed2[i] = balancedVariantConverter.Convert(arrays[i]);
828                 }
829
830                 var elapsed2 = sw2.Elapsed;
831
832                 Debug.WriteLine($"Compressor: {elapsed1}, Balanced sequence creator:
                ↪  {elapsed2}");
833
834                 Assert.True(elapsed1 > elapsed2);
835
836                 // Checks
837                 for (int i = START; i < END; i++)
838                 {
839                     var sequence1 = compressed1[i];
840                     var sequence2 = compressed2[i];
841
842                     if (sequence1 != _constants.Null && sequence2 != _constants.Null)
843                     {
844                         var decompress1 = UnicodeMap.FromSequenceLinkToString(sequence1,
                        ↪  scope1.Links);
845
846                         var decompress2 = UnicodeMap.FromSequenceLinkToString(sequence2,
                        ↪  scope2.Links);
847
848                         Assert.True(strings[i] == decompress1 && decompress1 == decompress2);
849                     }
850                 }
851
852                 Assert.True((int)(scope1.Links.Count() - UnicodeMap.MapSize) < totalCharacters);
853                 Assert.True((int)(scope2.Links.Count() - UnicodeMap.MapSize) < totalCharacters);
854
855                 Debug.WriteLine($"{(double)(scope1.Links.Count() - UnicodeMap.MapSize) /
                ↪  totalCharacters} | {(double)(scope2.Links.Count() - UnicodeMap.MapSize) /
                ↪  totalCharacters}");
856
857                 // Can be worse than balanced variant
858                 //Assert.True(scope1.Links.Count() <= scope2.Links.Count());
859
860                 //compressor1.ValidateFrequencies();
861             }
862         }
863
864         [Fact]
865         public static void AllTreeBreakDownAtSequencesCreationBugTest()
866         {
867             // Made out of AllPossibleConnectionsTest test.
868
```

```
            //const long sequenceLength = 5; //100% bug
            const long sequenceLength = 4; //100% bug
            //const long sequenceLength = 3; //100% _no_bug (ok)

            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var sequence = new ulong[sequenceLength];
                for (var i = 0; i < sequenceLength; i++)
                {
                    sequence[i] = links.Create();
                }

                var createResults = sequences.CreateAllVariants2(sequence);

                Global.Trash = createResults;

                for (var i = 0; i < sequenceLength; i++)
                {
                    links.Delete(sequence[i]);
                }
            }
        }

        [Fact]
        public static void AllPossibleConnectionsTest()
        {
            const long sequenceLength = 5;

            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var sequence = new ulong[sequenceLength];
                for (var i = 0; i < sequenceLength; i++)
                {
                    sequence[i] = links.Create();
                }

                var createResults = sequences.CreateAllVariants2(sequence);
                var reverseResults = sequences.CreateAllVariants2(sequence.Reverse().ToArray());

                for (var i = 0; i < 1; i++)
                {
                    var sw1 = Stopwatch.StartNew();
                    var searchResults1 = sequences.GetAllConnections(sequence); sw1.Stop();

                    var sw2 = Stopwatch.StartNew();
                    var searchResults2 = sequences.GetAllConnections1(sequence); sw2.Stop();

                    var sw3 = Stopwatch.StartNew();
                    var searchResults3 = sequences.GetAllConnections2(sequence); sw3.Stop();

                    var sw4 = Stopwatch.StartNew();
                    var searchResults4 = sequences.GetAllConnections3(sequence); sw4.Stop();

                    Global.Trash = searchResults3;
                    Global.Trash = searchResults4; //-V3008

                    var intersection1 = createResults.Intersect(searchResults1).ToList();
                    Assert.True(intersection1.Count == createResults.Length);

                    var intersection2 = reverseResults.Intersect(searchResults1).ToList();
                    Assert.True(intersection2.Count == reverseResults.Length);

                    var intersection0 = searchResults1.Intersect(searchResults2).ToList();
                    Assert.True(intersection0.Count == searchResults2.Count);

                    var intersection3 = searchResults2.Intersect(searchResults3).ToList();
                    Assert.True(intersection3.Count == searchResults3.Count);

                    var intersection4 = searchResults3.Intersect(searchResults4).ToList();
                    Assert.True(intersection4.Count == searchResults4.Count);
                }

                for (var i = 0; i < sequenceLength; i++)
                {
```

```
                    links.Delete(sequence[i]);
                }
            }
        }

        [Fact(Skip = "Correct implementation is pending")]
        public static void CalculateAllUsagesTest()
        {
            const long sequenceLength = 3;

            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var sequence = new ulong[sequenceLength];
                for (var i = 0; i < sequenceLength; i++)
                {
                    sequence[i] = links.Create();
                }

                var createResults = sequences.CreateAllVariants2(sequence);

                //var reverseResults =
                ↪  sequences.CreateAllVariants2(sequence.Reverse().ToArray());

                for (var i = 0; i < 1; i++)
                {
                    var linksTotalUsages1 = new ulong[links.Count() + 1];

                    sequences.CalculateAllUsages(linksTotalUsages1);

                    var linksTotalUsages2 = new ulong[links.Count() + 1];

                    sequences.CalculateAllUsages2(linksTotalUsages2);

                    var intersection1 = linksTotalUsages1.Intersect(linksTotalUsages2).ToList();
                    Assert.True(intersection1.Count == linksTotalUsages2.Length);
                }

                for (var i = 0; i < sequenceLength; i++)
                {
                    links.Delete(sequence[i]);
                }
            }
        }
    }
}
```

./Platform.Data.Doublets.Tests/TempLinksTestScope.cs

```
using System.IO;
using Platform.Disposables;
using Platform.Data.Doublets.Sequences;
using Platform.Data.Doublets.Decorators;
using Platform.Data.Doublets.ResizableDirectMemory.Specific;

namespace Platform.Data.Doublets.Tests
{
    public class TempLinksTestScope : DisposableBase
    {
        public ILinks<ulong> MemoryAdapter { get; }
        public SynchronizedLinks<ulong> Links { get; }
        public Sequences.Sequences Sequences { get; }
        public string TempFilename { get; }
        public string TempTransactionLogFilename { get; }
        private readonly bool _deleteFiles;

        public TempLinksTestScope(bool deleteFiles = true, bool useSequences = false, bool
        ↪  useLog = false) : this(new SequencesOptions<ulong>(), deleteFiles, useSequences,
        ↪  useLog) { }

        public TempLinksTestScope(SequencesOptions<ulong> sequencesOptions, bool deleteFiles =
        ↪  true, bool useSequences = false, bool useLog = false)
        {
            _deleteFiles = deleteFiles;
            TempFilename = Path.GetTempFileName();
            TempTransactionLogFilename = Path.GetTempFileName();
            var coreMemoryAdapter = new UInt64ResizableDirectMemoryLinks(TempFilename);
```

```
            MemoryAdapter = useLog ? (ILinks<ulong>)new
            ↪  UInt64LinksTransactionsLayer(coreMemoryAdapter, TempTransactionLogFilename) :
            ↪  coreMemoryAdapter;
            Links = new SynchronizedLinks<ulong>(new UInt64Links(MemoryAdapter));
            if (useSequences)
            {
                Sequences = new Sequences.Sequences(Links, sequencesOptions);
            }
        }

        protected override void Dispose(bool manual, bool wasDisposed)
        {
            if (!wasDisposed)
            {
                Links.Unsync.DisposeIfPossible();
                if (_deleteFiles)
                {
                    DeleteFiles();
                }
            }
        }

        public void DeleteFiles()
        {
            File.Delete(TempFilename);
            File.Delete(TempTransactionLogFilename);
        }
    }
}
```

./Platform.Data.Doublets.Tests/TestExtensions.cs

```
using System.Collections.Generic;
using Xunit;
using Platform.Ranges;
using Platform.Numbers;
using Platform.Random;
using Platform.Setters;

namespace Platform.Data.Doublets.Tests
{
    public static class TestExtensions
    {
        public static void TestCRUDOperations<T>(this ILinks<T> links)
        {
            var constants = links.Constants;

            var equalityComparer = EqualityComparer<T>.Default;

            // Create Link
            Assert.True(equalityComparer.Equals(links.Count(), Integer<T>.Zero));

            var setter = new Setter<T>(constants.Null);
            links.Each(constants.Any, constants.Any, setter.SetAndReturnTrue);

            Assert.True(equalityComparer.Equals(setter.Result, constants.Null));

            var linkAddress = links.Create();

            var link = new Link<T>(links.GetLink(linkAddress));

            Assert.True(link.Count == 3);
            Assert.True(equalityComparer.Equals(link.Index, linkAddress));
            Assert.True(equalityComparer.Equals(link.Source, constants.Null));
            Assert.True(equalityComparer.Equals(link.Target, constants.Null));

            Assert.True(equalityComparer.Equals(links.Count(), Integer<T>.One));

            // Get first link
            setter = new Setter<T>(constants.Null);
            links.Each(constants.Any, constants.Any, setter.SetAndReturnFalse);

            Assert.True(equalityComparer.Equals(setter.Result, linkAddress));

            // Update link to reference itself
            links.Update(linkAddress, linkAddress, linkAddress);

            link = new Link<T>(links.GetLink(linkAddress));

            Assert.True(equalityComparer.Equals(link.Source, linkAddress));
            Assert.True(equalityComparer.Equals(link.Target, linkAddress));
```

```
50
51              // Update link to reference null (prepare for delete)
52              var updated = links.Update(linkAddress, constants.Null, constants.Null);
53
54              Assert.True(equalityComparer.Equals(updated, linkAddress));
55
56              link = new Link<T>(links.GetLink(linkAddress));
57
58              Assert.True(equalityComparer.Equals(link.Source, constants.Null));
59              Assert.True(equalityComparer.Equals(link.Target, constants.Null));
60
61              // Delete link
62              links.Delete(linkAddress);
63
64              Assert.True(equalityComparer.Equals(links.Count(), Integer<T>.Zero));
65
66              setter = new Setter<T>(constants.Null);
67              links.Each(constants.Any, constants.Any, setter.SetAndReturnTrue);
68
69              Assert.True(equalityComparer.Equals(setter.Result, constants.Null));
70          }
71
72          public static void TestRawNumbersCRUDOperations<T>(this ILinks<T> links)
73          {
74              // Constants
75              var constants = links.Constants;
76              var equalityComparer = EqualityComparer<T>.Default;
77
78              var h106E = new Hybrid<T>(106L, isExternal: true);
79              var h107E = new Hybrid<T>(-char.ConvertFromUtf32(107)[0]);
80              var h108E = new Hybrid<T>(-108L);
81
82              Assert.Equal(106L, h106E.AbsoluteValue);
83              Assert.Equal(107L, h107E.AbsoluteValue);
84              Assert.Equal(108L, h108E.AbsoluteValue);
85
86              // Create Link (External -> External)
87              var linkAddress1 = links.Create();
88
89              links.Update(linkAddress1, h106E, h108E);
90
91              var link1 = new Link<T>(links.GetLink(linkAddress1));
92
93              Assert.True(equalityComparer.Equals(link1.Source, h106E));
94              Assert.True(equalityComparer.Equals(link1.Target, h108E));
95
96              // Create Link (Internal -> External)
97              var linkAddress2 = links.Create();
98
99              links.Update(linkAddress2, linkAddress1, h108E);
100
101             var link2 = new Link<T>(links.GetLink(linkAddress2));
102
103             Assert.True(equalityComparer.Equals(link2.Source, linkAddress1));
104             Assert.True(equalityComparer.Equals(link2.Target, h108E));
105
106             // Create Link (Internal -> Internal)
107             var linkAddress3 = links.Create();
108
109             links.Update(linkAddress3, linkAddress1, linkAddress2);
110
111             var link3 = new Link<T>(links.GetLink(linkAddress3));
112
113             Assert.True(equalityComparer.Equals(link3.Source, linkAddress1));
114             Assert.True(equalityComparer.Equals(link3.Target, linkAddress2));
115
116             // Search for created link
117             var setter1 = new Setter<T>(constants.Null);
118             links.Each(h106E, h108E, setter1.SetAndReturnFalse);
119
120             Assert.True(equalityComparer.Equals(setter1.Result, linkAddress1));
121
122             // Search for nonexistent link
123             var setter2 = new Setter<T>(constants.Null);
124             links.Each(h106E, h107E, setter2.SetAndReturnFalse);
125
126             Assert.True(equalityComparer.Equals(setter2.Result, constants.Null));
127
128             // Update link to reference null (prepare for delete)
129             var updated = links.Update(linkAddress3, constants.Null, constants.Null);
```

```
130
131             Assert.True(equalityComparer.Equals(updated, linkAddress3));
132
133             link3 = new Link<T>(links.GetLink(linkAddress3));
134
135             Assert.True(equalityComparer.Equals(link3.Source, constants.Null));
136             Assert.True(equalityComparer.Equals(link3.Target, constants.Null));
137
138             // Delete link
139             links.Delete(linkAddress3);
140
141             Assert.True(equalityComparer.Equals(links.Count(), Integer<T>.Two));
142
143             var setter3 = new Setter<T>(constants.Null);
144             links.Each(constants.Any, constants.Any, setter3.SetAndReturnTrue);
145
146             Assert.True(equalityComparer.Equals(setter3.Result, linkAddress2));
147         }
148
149         public static void TestMultipleRandomCreationsAndDeletions<TLink>(this ILinks<TLink>
            ↪ links, int maximumOperationsPerCycle)
150         {
151             var comparer = Comparer<TLink>.Default;
152             for (var N = 1; N < maximumOperationsPerCycle; N++)
153             {
154                 var random = new System.Random(N);
155                 var created = 0;
156                 var deleted = 0;
157                 for (var i = 0; i < N; i++)
158                 {
159                     long linksCount = (Integer<TLink>)links.Count();
160                     var createPoint = random.NextBoolean();
161                     if (linksCount > 2 && createPoint)
162                     {
163                         var linksAddressRange = new Range<ulong>(1, (ulong)linksCount);
164                         TLink source = (Integer<TLink>)random.NextUInt64(linksAddressRange);
165                         TLink target = (Integer<TLink>)random.NextUInt64(linksAddressRange);
                            ↪ //-V3086
166                         var resultLink = links.CreateAndUpdate(source, target);
167                         if (comparer.Compare(resultLink, (Integer<TLink>)linksCount) > 0)
168                         {
169                             created++;
170                         }
171                     }
172                     else
173                     {
174                         links.Create();
175                         created++;
176                     }
177                 }
178                 Assert.True(created == (Integer<TLink>)links.Count());
179                 for (var i = 0; i < N; i++)
180                 {
181                     TLink link = (Integer<TLink>)(i + 1);
182                     if (links.Exists(link))
183                     {
184                         links.Delete(link);
185                         deleted++;
186                     }
187                 }
188                 Assert.True((Integer<TLink>)links.Count() == 0);
189             }
190         }
191     }
192 }
```

./Platform.Data.Doublets.Tests/UInt64LinksTests.cs

```
1  using System;
2  using System.Collections.Generic;
3  using System.Diagnostics;
4  using System.IO;
5  using System.Text;
6  using System.Threading;
7  using System.Threading.Tasks;
8  using Xunit;
9  using Platform.Disposables;
10 using Platform.IO;
11 using Platform.Ranges;
12 using Platform.Random;
13 using Platform.Timestamps;
```

```
14  using Platform.Reflection;
15  using Platform.Singletons;
16  using Platform.Scopes;
17  using Platform.Counters;
18  using Platform.Diagnostics;
19  using Platform.Memory;
20  using Platform.Data.Doublets.Decorators;
21  using Platform.Data.Doublets.ResizableDirectMemory.Specific;
22
23  namespace Platform.Data.Doublets.Tests
24  {
25      public static class UInt64LinksTests
26      {
27          private static readonly LinksConstants<ulong> _constants =
            ↪ Default<LinksConstants<ulong>>.Instance;
28
29          private const long Iterations = 10 * 1024;
30
31          #region Concept
32
33          [Fact]
34          public static void MultipleCreateAndDeleteTest()
35          {
36              using (var scope = new Scope<Types<HeapResizableDirectMemory,
                ↪ UInt64ResizableDirectMemoryLinks>>())
37              {
38                  new UInt64Links(scope.Use<ILinks<ulong>>()).TestMultipleRandomCreationsAndDeleti
                    ↪ ons(100);
39              }
40          }
41
42          [Fact]
43          public static void CascadeUpdateTest()
44          {
45              var itself = _constants.Itself;
46
47              using (var scope = new TempLinksTestScope(useLog: true))
48              {
49                  var links = scope.Links;
50
51                  var l1 = links.Create();
52                  var l2 = links.Create();
53
54                  l2 = links.Update(l2, l2, l1, l2);
55
56                  links.CreateAndUpdate(l2, itself);
57                  links.CreateAndUpdate(l2, itself);
58
59                  l2 = links.Update(l2, l1);
60
61                  links.Delete(l2);
62
63                  Global.Trash = links.Count();
64
65                  links.Unsync.DisposeIfPossible(); // Close links to access log
66
67                  Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(scop
                    ↪ e.TempTransactionLogFilename);
68              }
69          }
70
71          [Fact]
72          public static void BasicTransactionLogTest()
73          {
74              using (var scope = new TempLinksTestScope(useLog: true))
75              {
76                  var links = scope.Links;
77                  var l1 = links.Create();
78                  var l2 = links.Create();
79
80                  Global.Trash = links.Update(l2, l2, l1, l2);
81
82                  links.Delete(l1);
83
84                  links.Unsync.DisposeIfPossible(); // Close links to access log
85
86                  Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(scop
                    ↪ e.TempTransactionLogFilename);
87              }
88          }
```

```
89
90          [Fact]
91          public static void TransactionAutoRevertedTest()
92          {
93              // Auto Reverted (Because no commit at transaction)
94              using (var scope = new TempLinksTestScope(useLog: true))
95              {
96                  var links = scope.Links;
97                  var transactionsLayer = (UInt64LinksTransactionsLayer)scope.MemoryAdapter;
98                  using (var transaction = transactionsLayer.BeginTransaction())
99                  {
100                     var l1 = links.Create();
101                     var l2 = links.Create();
102
103                     links.Update(l2, l2, l1, l2);
104                 }
105
106                 Assert.Equal(0UL, links.Count());
107
108                 links.Unsync.DisposeIfPossible();
109
110                 var transitions = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(s
                    ↪ cope.TempTransactionLogFilename);
111                 Assert.Single(transitions);
112             }
113         }
114
115         [Fact]
116         public static void TransactionUserCodeErrorNoDataSavedTest()
117         {
118             // User Code Error (Autoreverted), no data saved
119             var itself = _constants.Itself;
120
121             TempLinksTestScope lastScope = null;
122             try
123             {
124                 using (var scope = lastScope = new TempLinksTestScope(deleteFiles: false,
                    ↪ useLog: true))
125                 {
126                     var links = scope.Links;
127                     var transactionsLayer = (UInt64LinksTransactionsLayer)((LinksDisposableDecor
                        ↪ atorBase<ulong>)links.Unsync).Links;
128                     using (var transaction = transactionsLayer.BeginTransaction())
129                     {
130                         var l1 = links.CreateAndUpdate(itself, itself);
131                         var l2 = links.CreateAndUpdate(itself, itself);
132
133                         l2 = links.Update(l2, l2, l1, l2);
134
135                         links.CreateAndUpdate(l2, itself);
136                         links.CreateAndUpdate(l2, itself);
137
138                         //Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transi
                            ↪ tion>(scope.TempTransactionLogFilename);
139
140                         l2 = links.Update(l2, l1);
141
142                         links.Delete(l2);
143
144                         ExceptionThrower();
145
146                         transaction.Commit();
147                     }
148
149                     Global.Trash = links.Count();
150                 }
151             }
152             catch
153             {
154                 Assert.False(lastScope == null);
155
156                 var transitions = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(l
                    ↪ astScope.TempTransactionLogFilename);
157
158                 Assert.True(transitions.Length == 1 && transitions[0].Before.IsNull() &&
                    ↪ transitions[0].After.IsNull());
159
160                 lastScope.DeleteFiles();
161             }
```

```
        }

        [Fact]
        public static void TransactionUserCodeErrorSomeDataSavedTest()
        {
            // User Code Error (Autoreverted), some data saved
            var itself = _constants.Itself;

            TempLinksTestScope lastScope = null;
            try
            {
                ulong l1;
                ulong l2;

                using (var scope = new TempLinksTestScope(useLog: true))
                {
                    var links = scope.Links;
                    l1 = links.CreateAndUpdate(itself, itself);
                    l2 = links.CreateAndUpdate(itself, itself);

                    l2 = links.Update(l2, l2, l1, l2);

                    links.CreateAndUpdate(l2, itself);
                    links.CreateAndUpdate(l2, itself);

                    links.Unsync.DisposeIfPossible();

                    Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(
                    ↪  scope.TempTransactionLogFilename);
                }

                using (var scope = lastScope = new TempLinksTestScope(deleteFiles: false,
                ↪  useLog: true))
                {
                    var links = scope.Links;
                    var transactionsLayer = (UInt64LinksTransactionsLayer)links.Unsync;
                    using (var transaction = transactionsLayer.BeginTransaction())
                    {
                        l2 = links.Update(l2, l1);

                        links.Delete(l2);

                        ExceptionThrower();

                        transaction.Commit();
                    }

                    Global.Trash = links.Count();
                }
            }
            catch
            {
                Assert.False(lastScope == null);

                Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(last
                ↪  Scope.TempTransactionLogFilename);

                lastScope.DeleteFiles();
            }
        }

        [Fact]
        public static void TransactionCommit()
        {
            var itself = _constants.Itself;

            var tempDatabaseFilename = Path.GetTempFileName();
            var tempTransactionLogFilename = Path.GetTempFileName();

            // Commit
            using (var memoryAdapter = new UInt64LinksTransactionsLayer(new
            ↪  UInt64ResizableDirectMemoryLinks(tempDatabaseFilename),
            ↪  tempTransactionLogFilename))
            using (var links = new UInt64Links(memoryAdapter))
            {
                using (var transaction = memoryAdapter.BeginTransaction())
                {
                    var l1 = links.CreateAndUpdate(itself, itself);
                    var l2 = links.CreateAndUpdate(itself, itself);
```

```
236
237                     Global.Trash = links.Update(l2, l2, l1, l2);
238
239                     links.Delete(l1);
240
241                     transaction.Commit();
242                 }
243
244                 Global.Trash = links.Count();
245             }
246
247             Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(tempTran
                ↪  sactionLogFilename);
248         }
249
250         [Fact]
251         public static void TransactionDamage()
252         {
253             var itself = _constants.Itself;
254
255             var tempDatabaseFilename = Path.GetTempFileName();
256             var tempTransactionLogFilename = Path.GetTempFileName();
257
258             // Commit
259             using (var memoryAdapter = new UInt64LinksTransactionsLayer(new
                ↪  UInt64ResizableDirectMemoryLinks(tempDatabaseFilename),
                ↪  tempTransactionLogFilename))
260             using (var links = new UInt64Links(memoryAdapter))
261             {
262                 using (var transaction = memoryAdapter.BeginTransaction())
263                 {
264                     var l1 = links.CreateAndUpdate(itself, itself);
265                     var l2 = links.CreateAndUpdate(itself, itself);
266
267                     Global.Trash = links.Update(l2, l2, l1, l2);
268
269                     links.Delete(l1);
270
271                     transaction.Commit();
272                 }
273
274                 Global.Trash = links.Count();
275             }
276
277             Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(tempTran
                ↪  sactionLogFilename);
278
279             // Damage database
280
281             FileHelpers.WriteFirst(tempTransactionLogFilename, new
                ↪  UInt64LinksTransactionsLayer.Transition(new UniqueTimestampFactory(), 555));
282
283             // Try load damaged database
284             try
285             {
286                 // TODO: Fix
287                 using (var memoryAdapter = new UInt64LinksTransactionsLayer(new
                    ↪  UInt64ResizableDirectMemoryLinks(tempDatabaseFilename),
                    ↪  tempTransactionLogFilename))
288                 using (var links = new UInt64Links(memoryAdapter))
289                 {
290                     Global.Trash = links.Count();
291                 }
292             }
293             catch (NotSupportedException ex)
294             {
295                 Assert.True(ex.Message == "Database is damaged, autorecovery is not supported
                    ↪  yet.");
296             }
297
298             Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(tempTran
                ↪  sactionLogFilename);
299
300             File.Delete(tempDatabaseFilename);
301             File.Delete(tempTransactionLogFilename);
302         }
303
304         [Fact]
305         public static void Bug1Test()
```

```
306         {
307             var tempDatabaseFilename = Path.GetTempFileName();
308             var tempTransactionLogFilename = Path.GetTempFileName();
309 
310             var itself = _constants.Itself;
311 
312             // User Code Error (Autoreverted), some data saved
313             try
314             {
315                 ulong l1;
316                 ulong l2;
317 
318                 using (var memoryAdapter = new UInt64LinksTransactionsLayer(new
                    ↪  UInt64ResizableDirectMemoryLinks(tempDatabaseFilename),
                    ↪  tempTransactionLogFilename))
319                 using (var links = new UInt64Links(memoryAdapter))
320                 {
321                     l1 = links.CreateAndUpdate(itself, itself);
322                     l2 = links.CreateAndUpdate(itself, itself);
323 
324                     l2 = links.Update(l2, l2, l1, l2);
325 
326                     links.CreateAndUpdate(l2, itself);
327                     links.CreateAndUpdate(l2, itself);
328                 }
329 
330                 Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(temp
                    ↪  TransactionLogFilename);
331 
332                 using (var memoryAdapter = new UInt64LinksTransactionsLayer(new
                    ↪  UInt64ResizableDirectMemoryLinks(tempDatabaseFilename),
                    ↪  tempTransactionLogFilename))
333                 using (var links = new UInt64Links(memoryAdapter))
334                 {
335                     using (var transaction = memoryAdapter.BeginTransaction())
336                     {
337                         l2 = links.Update(l2, l1);
338 
339                         links.Delete(l2);
340 
341                         ExceptionThrower();
342 
343                         transaction.Commit();
344                     }
345 
346                     Global.Trash = links.Count();
347                 }
348             }
349             catch
350             {
351                 Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(temp
                    ↪  TransactionLogFilename);
352             }
353 
354             File.Delete(tempDatabaseFilename);
355             File.Delete(tempTransactionLogFilename);
356         }
357 
358         private static void ExceptionThrower() => throw new InvalidOperationException();
359 
360         [Fact]
361         public static void PathsTest()
362         {
363             var source = _constants.SourcePart;
364             var target = _constants.TargetPart;
365 
366             using (var scope = new TempLinksTestScope())
367             {
368                 var links = scope.Links;
369                 var l1 = links.CreatePoint();
370                 var l2 = links.CreatePoint();
371 
372                 var r1 = links.GetByKeys(l1, source, target, source);
373                 var r2 = links.CheckPathExistance(l2, l2, l2, l2);
374             }
375         }
376 
377         [Fact]
378         public static void RecursiveStringFormattingTest()
```

```
379         {
380             using (var scope = new TempLinksTestScope(useSequences: true))
381             {
382                 var links = scope.Links;
383                 var sequences = scope.Sequences; // TODO: Auto use sequences on Sequences getter.
384 
385                 var a = links.CreatePoint();
386                 var b = links.CreatePoint();
387                 var c = links.CreatePoint();
388 
389                 var ab = links.CreateAndUpdate(a, b);
390                 var cb = links.CreateAndUpdate(c, b);
391                 var ac = links.CreateAndUpdate(a, c);
392 
393                 a = links.Update(a, c, b);
394                 b = links.Update(b, a, c);
395                 c = links.Update(c, a, b);
396 
397                 Debug.WriteLine(links.FormatStructure(ab, link => link.IsFullPoint(), true));
398                 Debug.WriteLine(links.FormatStructure(cb, link => link.IsFullPoint(), true));
399                 Debug.WriteLine(links.FormatStructure(ac, link => link.IsFullPoint(), true));
400 
401                 Assert.True(links.FormatStructure(cb, link => link.IsFullPoint(), true) ==
                    ↪  "(5:(4:5 (6:5 4)) 6)");
402                 Assert.True(links.FormatStructure(ac, link => link.IsFullPoint(), true) ==
                    ↪  "(6:(5:(4:5 6) 6) 4)");
403                 Assert.True(links.FormatStructure(ab, link => link.IsFullPoint(), true) ==
                    ↪  "(4:(5:4 (6:5 4)) 6)");
404 
405                 // TODO: Think how to build balanced syntax tree while formatting structure (eg.
                    ↪  "(4:(5:4 6) (6:5 4)") instead of "(4:(5:4 (6:5 4)) 6)"
406 
407                 Assert.True(sequences.SafeFormatSequence(cb, DefaultFormatter, false) ==
                    ↪  "{{5}{5}{4}{6}}");
408                 Assert.True(sequences.SafeFormatSequence(ac, DefaultFormatter, false) ==
                    ↪  "{{5}{6}{6}{4}}");
409                 Assert.True(sequences.SafeFormatSequence(ab, DefaultFormatter, false) ==
                    ↪  "{{4}{5}{4}{6}}");
410             }
411         }
412 
413         private static void DefaultFormatter(StringBuilder sb, ulong link)
414         {
415             sb.Append(link.ToString());
416         }
417 
418         #endregion
419 
420         #region Performance
421 
422         /*
423         public static void RunAllPerformanceTests()
424         {
425             try
426             {
427                 links.TestLinksInSteps();
428             }
429             catch (Exception ex)
430             {
431                 ex.WriteToConsole();
432             }
433 
434             return;
435 
436             try
437             {
438                 //ThreadPool.SetMaxThreads(2, 2);
439 
440                 // Запускаем все тесты дважды, чтобы первоначальная инициализация не повлияла на
    ↪  результат
441                 // Также это дополнительно помогает в отладке
442                 // Увеличивает вероятность попадания информации в кэши
443                 for (var i = 0; i < 10; i++)
444                 {
445                     //0 - 10 ГБ
446                     //Каждые 100 МБ срез цифр
447 
448                     //links.TestGetSourceFunction();
449                     //links.TestGetSourceFunctionInParallel();
```

```
450                     //links.TestGetTargetFunction();
451                     //links.TestGetTargetFunctionInParallel();
452                     links.Create64BillionLinks();
453
454                     links.TestRandomSearchFixed();
455                     //links.Create64BillionLinksInParallel();
456                     links.TestEachFunction();
457                     //links.TestForeach();
458                     //links.TestParallelForeach();
459                 }
460
461                 links.TestDeletionOfAllLinks();
462
463             }
464             catch (Exception ex)
465             {
466                 ex.WriteToConsole();
467             }
468         }*/
469
470          /*
471         public static void TestLinksInSteps()
472         {
473             const long gibibyte = 1024 * 1024 * 1024;
474             const long mebibyte = 1024 * 1024;
475
476             var totalLinksToCreate = gibibyte /
    ↪  Platform.Links.Data.Core.Doublets.Links.LinkSizeInBytes;
477             var linksStep = 102 * mebibyte /
    ↪  Platform.Links.Data.Core.Doublets.Links.LinkSizeInBytes;
478
479             var creationMeasurements = new List<TimeSpan>();
480             var searchMeasuremets = new List<TimeSpan>();
481             var deletionMeasurements = new List<TimeSpan>();
482
483             GetBaseRandomLoopOverhead(linksStep);
484             GetBaseRandomLoopOverhead(linksStep);
485
486             var stepLoopOverhead = GetBaseRandomLoopOverhead(linksStep);
487
488             ConsoleHelpers.Debug("Step loop overhead: {0}.", stepLoopOverhead);
489
490             var loops = totalLinksToCreate / linksStep;
491
492             for (int i = 0; i < loops; i++)
493             {
494                 creationMeasurements.Add(Measure(() => links.RunRandomCreations(linksStep)));
495                 searchMeasuremets.Add(Measure(() => links.RunRandomSearches(linksStep)));
496
497                 Console.Write("\rC + S {0}/{1}", i + 1, loops);
498             }
499
500             ConsoleHelpers.Debug();
501
502             for (int i = 0; i < loops; i++)
503             {
504                 deletionMeasurements.Add(Measure(() => links.RunRandomDeletions(linksStep)));
505
506                 Console.Write("\rD {0}/{1}", i + 1, loops);
507             }
508
509             ConsoleHelpers.Debug();
510
511             ConsoleHelpers.Debug("C S D");
512
513             for (int i = 0; i < loops; i++)
514             {
515                 ConsoleHelpers.Debug("{0} {1} {2}", creationMeasurements[i],
    ↪  searchMeasuremets[i], deletionMeasurements[i]);
516             }
517
518             ConsoleHelpers.Debug("C S D (no overhead)");
519
520             for (int i = 0; i < loops; i++)
521             {
522                 ConsoleHelpers.Debug("{0} {1} {2}", creationMeasurements[i] - stepLoopOverhead,
    ↪  searchMeasuremets[i] - stepLoopOverhead, deletionMeasurements[i] - stepLoopOverhead);
523             }
524
```

```
525             ConsoleHelpers.Debug("All tests done. Total links left in database: {0}.",
    ↪  links.Total);
526         }
527 
528         private static void CreatePoints(this Platform.Links.Data.Core.Doublets.Links links, long
    ↪  amountToCreate)
529         {
530             for (long i = 0; i < amountToCreate; i++)
531                 links.Create(0, 0);
532         }
533 
534         private static TimeSpan GetBaseRandomLoopOverhead(long loops)
535         {
536             return Measure(() =>
537             {
538                 ulong maxValue = RandomHelpers.DefaultFactory.NextUInt64();
539                 ulong result = 0;
540                 for (long i = 0; i < loops; i++)
541                 {
542                     var source = RandomHelpers.DefaultFactory.NextUInt64(maxValue);
543                     var target = RandomHelpers.DefaultFactory.NextUInt64(maxValue);
544 
545                     result += maxValue + source + target;
546                 }
547                 Global.Trash = result;
548             });
549         }
550          */
551 
552         [Fact(Skip = "performance test")]
553         public static void GetSourceTest()
554         {
555             using (var scope = new TempLinksTestScope())
556             {
557                 var links = scope.Links;
558                 ConsoleHelpers.Debug("Testing GetSource function with {0} Iterations.",
                    ↪  Iterations);
559 
560                 ulong counter = 0;
561 
562                 //var firstLink = links.First();
563                 // Создаём одну связь, из которой будет производить считывание
564                 var firstLink = links.Create();
565 
566                 var sw = Stopwatch.StartNew();
567 
568                 // Тестируем саму функцию
569                 for (ulong i = 0; i < Iterations; i++)
570                 {
571                     counter += links.GetSource(firstLink);
572                 }
573 
574                 var elapsedTime = sw.Elapsed;
575 
576                 var iterationsPerSecond = Iterations / elapsedTime.TotalSeconds;
577 
578                 // Удаляем связь, из которой производилось считывание
579                 links.Delete(firstLink);
580 
581                 ConsoleHelpers.Debug(
582                     "{0} Iterations of GetSource function done in {1} ({2} Iterations per
                        ↪  second), counter result: {3}",
583                     Iterations, elapsedTime, (long)iterationsPerSecond, counter);
584             }
585         }
586 
587         [Fact(Skip = "performance test")]
588         public static void GetSourceInParallel()
589         {
590             using (var scope = new TempLinksTestScope())
591             {
592                 var links = scope.Links;
593                 ConsoleHelpers.Debug("Testing GetSource function with {0} Iterations in
                    ↪  parallel.", Iterations);
594 
595                 long counter = 0;
596 
597                 //var firstLink = links.First();
598                 var firstLink = links.Create();
```

```
599
600                 var sw = Stopwatch.StartNew();
601
602                 // Тестируем саму функцию
603                 Parallel.For(0, Iterations, x =>
604                 {
605                     Interlocked.Add(ref counter, (long)links.GetSource(firstLink));
606                     //Interlocked.Increment(ref counter);
607                 });
608
609                 var elapsedTime = sw.Elapsed;
610
611                 var iterationsPerSecond = Iterations / elapsedTime.TotalSeconds;
612
613                 links.Delete(firstLink);
614
615                 ConsoleHelpers.Debug(
616                     "{0} Iterations of GetSource function done in {1} ({2} Iterations per
                        ↪  second), counter result: {3}",
617                     Iterations, elapsedTime, (long)iterationsPerSecond, counter);
618             }
619         }
620
621         [Fact(Skip = "performance test")]
622         public static void TestGetTarget()
623         {
624             using (var scope = new TempLinksTestScope())
625             {
626                 var links = scope.Links;
627                 ConsoleHelpers.Debug("Testing GetTarget function with {0} Iterations.",
                    ↪  Iterations);
628
629                 ulong counter = 0;
630
631                 //var firstLink = links.First();
632                 var firstLink = links.Create();
633
634                 var sw = Stopwatch.StartNew();
635
636                 for (ulong i = 0; i < Iterations; i++)
637                 {
638                     counter += links.GetTarget(firstLink);
639                 }
640
641                 var elapsedTime = sw.Elapsed;
642
643                 var iterationsPerSecond = Iterations / elapsedTime.TotalSeconds;
644
645                 links.Delete(firstLink);
646
647                 ConsoleHelpers.Debug(
648                     "{0} Iterations of GetTarget function done in {1} ({2} Iterations per
                        ↪  second), counter result: {3}",
649                     Iterations, elapsedTime, (long)iterationsPerSecond, counter);
650             }
651         }
652
653         [Fact(Skip = "performance test")]
654         public static void TestGetTargetInParallel()
655         {
656             using (var scope = new TempLinksTestScope())
657             {
658                 var links = scope.Links;
659                 ConsoleHelpers.Debug("Testing GetTarget function with {0} Iterations in
                    ↪  parallel.", Iterations);
660
661                 long counter = 0;
662
663                 //var firstLink = links.First();
664                 var firstLink = links.Create();
665
666                 var sw = Stopwatch.StartNew();
667
668                 Parallel.For(0, Iterations, x =>
669                 {
670                     Interlocked.Add(ref counter, (long)links.GetTarget(firstLink));
671                     //Interlocked.Increment(ref counter);
672                 });
673
674                 var elapsedTime = sw.Elapsed;
```

```
675
676                 var iterationsPerSecond = Iterations / elapsedTime.TotalSeconds;
677
678                 links.Delete(firstLink);
679
680                 ConsoleHelpers.Debug(
681                     "{0} Iterations of GetTarget function done in {1} ({2} Iterations per
                        ↪  second), counter result: {3}",
682                     Iterations, elapsedTime, (long)iterationsPerSecond, counter);
683             }
684         }
685
686         // TODO: Заполнить базу данных перед тестом
687         /*
688         [Fact]
689         public void TestRandomSearchFixed()
690         {
691             var tempFilename = Path.GetTempFileName();
692
693             using (var links = new Platform.Links.Data.Core.Doublets.Links(tempFilename,
    ↪  DefaultLinksSizeStep))
694             {
695                 long iterations = 64 * 1024 * 1024 /
    ↪  Platform.Links.Data.Core.Doublets.Links.LinkSizeInBytes;
696
697                 ulong counter = 0;
698                 var maxLink = links.Total;
699
700                 ConsoleHelpers.Debug("Testing Random Search with {0} Iterations.", iterations);
701
702                 var sw = Stopwatch.StartNew();
703
704                 for (var i = iterations; i > 0; i--)
705                 {
706                     var source =
    ↪  RandomHelpers.DefaultFactory.NextUInt64(LinksConstants.MinPossibleIndex, maxLink);
707                     var target =
    ↪  RandomHelpers.DefaultFactory.NextUInt64(LinksConstants.MinPossibleIndex, maxLink);
708
709                     counter += links.Search(source, target);
710                 }
711
712                 var elapsedTime = sw.Elapsed;
713
714                 var iterationsPerSecond = iterations / elapsedTime.TotalSeconds;
715
716                 ConsoleHelpers.Debug("{0} Iterations of Random Search done in {1} ({2}
    ↪  Iterations per second), c: {3}", iterations, elapsedTime, (long)iterationsPerSecond,
    ↪  counter);
717             }
718
719             File.Delete(tempFilename);
720         }*/
721
722         [Fact(Skip = "useless: 0(0), was dependent on creation tests")]
723         public static void TestRandomSearchAll()
724         {
725             using (var scope = new TempLinksTestScope())
726             {
727                 var links = scope.Links;
728                 ulong counter = 0;
729
730                 var maxLink = links.Count();
731
732                 var iterations = links.Count();
733
734                 ConsoleHelpers.Debug("Testing Random Search with {0} Iterations.",
                    ↪  links.Count());
735
736                 var sw = Stopwatch.StartNew();
737
738                 for (var i = iterations; i > 0; i--)
739                 {
740                     var linksAddressRange = new
                        ↪  Range<ulong>(_constants.PossibleInnerReferencesRange.Minimum, maxLink);
741
742                     var source = RandomHelpers.Default.NextUInt64(linksAddressRange);
743                     var target = RandomHelpers.Default.NextUInt64(linksAddressRange);
744
```

```
745                     counter += links.SearchOrDefault(source, target);
746                 }
747
748                 var elapsedTime = sw.Elapsed;
749
750                 var iterationsPerSecond = iterations / elapsedTime.TotalSeconds;
751
752                 ConsoleHelpers.Debug("{0} Iterations of Random Search done in {1} ({2}
    ↪  Iterations per second), c: {3}",
753                     iterations, elapsedTime, (long)iterationsPerSecond, counter);
754             }
755         }
756
757         [Fact(Skip = "useless: 0(0), was dependent on creation tests")]
758         public static void TestEach()
759         {
760             using (var scope = new TempLinksTestScope())
761             {
762                 var links = scope.Links;
763
764                 var counter = new Counter<IList<ulong>, ulong>(links.Constants.Continue);
765
766                 ConsoleHelpers.Debug("Testing Each function.");
767
768                 var sw = Stopwatch.StartNew();
769
770                 links.Each(counter.IncrementAndReturnTrue);
771
772                 var elapsedTime = sw.Elapsed;
773
774                 var linksPerSecond = counter.Count / elapsedTime.TotalSeconds;
775
776                 ConsoleHelpers.Debug("{0} Iterations of Each's handler function done in {1} ({2}
    ↪  links per second)",
777                     counter, elapsedTime, (long)linksPerSecond);
778             }
779         }
780
781         /*
782         [Fact]
783         public static void TestForeach()
784         {
785             var tempFilename = Path.GetTempFileName();
786
787             using (var links = new Platform.Links.Data.Core.Doublets.Links(tempFilename,
    ↪  DefaultLinksSizeStep))
788             {
789                 ulong counter = 0;
790
791                 ConsoleHelpers.Debug("Testing foreach through links.");
792
793                 var sw = Stopwatch.StartNew();
794
795                 //foreach (var link in links)
796                 //{
797                 //    counter++;
798                 //}
799
800                 var elapsedTime = sw.Elapsed;
801
802                 var linksPerSecond = (double)counter / elapsedTime.TotalSeconds;
803
804                 ConsoleHelpers.Debug("{0} Iterations of Foreach's handler block done in {1} ({2}
    ↪  links per second)", counter, elapsedTime, (long)linksPerSecond);
805             }
806
807             File.Delete(tempFilename);
808         }
809         */
810
811         /*
812         [Fact]
813         public static void TestParallelForeach()
814         {
815             var tempFilename = Path.GetTempFileName();
816
817             using (var links = new Platform.Links.Data.Core.Doublets.Links(tempFilename,
    ↪  DefaultLinksSizeStep))
818             {
819
```

```
820                 long counter = 0;
821
822                 ConsoleHelpers.Debug("Testing parallel foreach through links.");
823
824                 var sw = Stopwatch.StartNew();
825
826                 //Parallel.ForEach((IEnumerable<ulong>)links, x =>
827                 //{
828                 //    Interlocked.Increment(ref counter);
829                 //});
830
831                 var elapsedTime = sw.Elapsed;
832
833                 var linksPerSecond = (double)counter / elapsedTime.TotalSeconds;
834
835                 ConsoleHelpers.Debug("{0} Iterations of Parallel Foreach's handler block done in
    ↪  {1} ({2} links per second)", counter, elapsedTime, (long)linksPerSecond);
836             }
837
838             File.Delete(tempFilename);
839         }
840         */
841
842         [Fact(Skip = "performance test")]
843         public static void Create64BillionLinks()
844         {
845             using (var scope = new TempLinksTestScope())
846             {
847                 var links = scope.Links;
848                 var linksBeforeTest = links.Count();
849
850                 long linksToCreate = 64 * 1024 * 1024 /
                    ↪  UInt64ResizableDirectMemoryLinks.LinkSizeInBytes;
851
852                 ConsoleHelpers.Debug("Creating {0} links.", linksToCreate);
853
854                 var elapsedTime = Performance.Measure(() =>
855                 {
856                     for (long i = 0; i < linksToCreate; i++)
857                     {
858                         links.Create();
859                     }
860                 });
861
862                 var linksCreated = links.Count() - linksBeforeTest;
863                 var linksPerSecond = linksCreated / elapsedTime.TotalSeconds;
864
865                 ConsoleHelpers.Debug("Current links count: {0}.", links.Count());
866
867                 ConsoleHelpers.Debug("{0} links created in {1} ({2} links per second)",
                    ↪  linksCreated, elapsedTime,
868                     (long)linksPerSecond);
869             }
870         }
871
872         [Fact(Skip = "performance test")]
873         public static void Create64BillionLinksInParallel()
874         {
875             using (var scope = new TempLinksTestScope())
876             {
877                 var links = scope.Links;
878                 var linksBeforeTest = links.Count();
879
880                 var sw = Stopwatch.StartNew();
881
882                 long linksToCreate = 64 * 1024 * 1024 /
                    ↪  UInt64ResizableDirectMemoryLinks.LinkSizeInBytes;
883
884                 ConsoleHelpers.Debug("Creating {0} links in parallel.", linksToCreate);
885
886                 Parallel.For(0, linksToCreate, x => links.Create());
887
888                 var elapsedTime = sw.Elapsed;
889
890                 var linksCreated = links.Count() - linksBeforeTest;
891                 var linksPerSecond = linksCreated / elapsedTime.TotalSeconds;
892
893                 ConsoleHelpers.Debug("{0} links created in {1} ({2} links per second)",
                    ↪  linksCreated, elapsedTime,
894                     (long)linksPerSecond);
```

```
            }
        }

        [Fact(Skip = "useless: 0(0), was dependent on creation tests")]
        public static void TestDeletionOfAllLinks()
        {
            using (var scope = new TempLinksTestScope())
            {
                var links = scope.Links;
                var linksBeforeTest = links.Count();

                ConsoleHelpers.Debug("Deleting all links");

                var elapsedTime = Performance.Measure(links.DeleteAll);

                var linksDeleted = linksBeforeTest - links.Count();
                var linksPerSecond = linksDeleted / elapsedTime.TotalSeconds;

                ConsoleHelpers.Debug("{0} links deleted in {1} ({2} links per second)",
                ↪  linksDeleted, elapsedTime,
                    (long)linksPerSecond);
            }
        }

        #endregion
    }
}
```

./Platform.Data.Doublets.Tests/UnaryNumberConvertersTests.cs

```
using Xunit;
using Platform.Random;
using Platform.Data.Doublets.Numbers.Unary;

namespace Platform.Data.Doublets.Tests
{
    public static class UnaryNumberConvertersTests
    {
        [Fact]
        public static void ConvertersTest()
        {
            using (var scope = new TempLinksTestScope())
            {
                const int N = 10;
                var links = scope.Links;
                var meaningRoot = links.CreatePoint();
                var one = links.CreateAndUpdate(meaningRoot, links.Constants.Itself);
                var powerOf2ToUnaryNumberConverter = new
                ↪  PowerOf2ToUnaryNumberConverter<ulong>(links, one);
                var toUnaryNumberConverter = new AddressToUnaryNumberConverter<ulong>(links,
                ↪  powerOf2ToUnaryNumberConverter);
                var random = new System.Random(0);
                ulong[] numbers = new ulong[N];
                ulong[] unaryNumbers = new ulong[N];
                for (int i = 0; i < N; i++)
                {
                    numbers[i] = random.NextUInt64();
                    unaryNumbers[i] = toUnaryNumberConverter.Convert(numbers[i]);
                }
                var fromUnaryNumberConverterUsingOrOperation = new
                ↪  UnaryNumberToAddressOrOperationConverter<ulong>(links,
                ↪  powerOf2ToUnaryNumberConverter);
                var fromUnaryNumberConverterUsingAddOperation = new
                ↪  UnaryNumberToAddressAddOperationConverter<ulong>(links, one);
                for (int i = 0; i < N; i++)
                {
                    Assert.Equal(numbers[i],
                    ↪  fromUnaryNumberConverterUsingOrOperation.Convert(unaryNumbers[i]));
                    Assert.Equal(numbers[i],
                    ↪  fromUnaryNumberConverterUsingAddOperation.Convert(unaryNumbers[i]));
                }
            }
        }
    }
}
```

./Platform.Data.Doublets.Tests/UnicodeConvertersTests.cs

```
using Xunit;
using Platform.Interfaces;
```

```
using Platform.Memory;
using Platform.Reflection;
using Platform.Scopes;
using Platform.Data.Doublets.Incrementers;
using Platform.Data.Doublets.Numbers.Raw;
using Platform.Data.Doublets.Numbers.Unary;
using Platform.Data.Doublets.PropertyOperators;
using Platform.Data.Doublets.Sequences.Converters;
using Platform.Data.Doublets.Sequences.Indexes;
using Platform.Data.Doublets.Sequences.Walkers;
using Platform.Data.Doublets.Unicode;
using Platform.Data.Doublets.ResizableDirectMemory.Generic;

namespace Platform.Data.Doublets.Tests
{
    public static class UnicodeConvertersTests
    {
        [Fact]
        public static void CharAndUnaryNumberUnicodeSymbolConvertersTest()
        {
            using (var scope = new TempLinksTestScope())
            {
                var links = scope.Links;
                var meaningRoot = links.CreatePoint();
                var one = links.CreateAndUpdate(meaningRoot, links.Constants.Itself);
                var powerOf2ToUnaryNumberConverter = new
                ↪  PowerOf2ToUnaryNumberConverter<ulong>(links, one);
                var addressToUnaryNumberConverter = new
                ↪  AddressToUnaryNumberConverter<ulong>(links, powerOf2ToUnaryNumberConverter);
                var unaryNumberToAddressConverter = new
                ↪  UnaryNumberToAddressOrOperationConverter<ulong>(links,
                ↪  powerOf2ToUnaryNumberConverter);
                TestCharAndUnicodeSymbolConverters(links, meaningRoot,
                ↪  addressToUnaryNumberConverter, unaryNumberToAddressConverter);
            }
        }

        [Fact]
        public static void CharAndRawNumberUnicodeSymbolConvertersTest()
        {
            using (var scope = new Scope<Types<HeapResizableDirectMemory,
            ↪  ResizableDirectMemoryLinks<ulong>>>())
            {
                var links = scope.Use<ILinks<ulong>>();
                var meaningRoot = links.CreatePoint();
                var addressToRawNumberConverter = new AddressToRawNumberConverter<ulong>();
                var rawNumberToAddressConverter = new RawNumberToAddressConverter<ulong>();
                TestCharAndUnicodeSymbolConverters(links, meaningRoot,
                ↪  addressToRawNumberConverter, rawNumberToAddressConverter);
            }
        }

        private static void TestCharAndUnicodeSymbolConverters(ILinks<ulong> links, ulong
        ↪  meaningRoot, IConverter<ulong> addressToNumberConverter, IConverter<ulong>
        ↪  numberToAddressConverter)
        {
            var unicodeSymbolMarker = links.CreateAndUpdate(meaningRoot, links.Constants.Itself);
            var charToUnicodeSymbolConverter = new CharToUnicodeSymbolConverter<ulong>(links,
            ↪  addressToNumberConverter, unicodeSymbolMarker);
            var originalCharacter = 'H';
            var characterLink = charToUnicodeSymbolConverter.Convert(originalCharacter);
            var unicodeSymbolCriterionMatcher = new UnicodeSymbolCriterionMatcher<ulong>(links,
            ↪  unicodeSymbolMarker);
            var unicodeSymbolToCharConverter = new UnicodeSymbolToCharConverter<ulong>(links,
            ↪  numberToAddressConverter, unicodeSymbolCriterionMatcher);
            var resultingCharacter = unicodeSymbolToCharConverter.Convert(characterLink);
            Assert.Equal(originalCharacter, resultingCharacter);
        }

        [Fact]
        public static void StringAndUnicodeSequenceConvertersTest()
        {
            using (var scope = new TempLinksTestScope())
            {
                var links = scope.Links;

                var itself = links.Constants.Itself;

                var meaningRoot = links.CreatePoint();
```

```
                var unaryOne = links.CreateAndUpdate(meaningRoot, itself);
                var unicodeSymbolMarker = links.CreateAndUpdate(meaningRoot, itself);
                var unicodeSequenceMarker = links.CreateAndUpdate(meaningRoot, itself);
                var frequencyMarker = links.CreateAndUpdate(meaningRoot, itself);
                var frequencyPropertyMarker = links.CreateAndUpdate(meaningRoot, itself);

                var powerOf2ToUnaryNumberConverter = new
                ↪  PowerOf2ToUnaryNumberConverter<ulong>(links, unaryOne);
                var addressToUnaryNumberConverter = new
                ↪  AddressToUnaryNumberConverter<ulong>(links, powerOf2ToUnaryNumberConverter);
                var charToUnicodeSymbolConverter = new
                ↪  CharToUnicodeSymbolConverter<ulong>(links, addressToUnaryNumberConverter,
                ↪  unicodeSymbolMarker);

                var unaryNumberToAddressConverter = new
                ↪  UnaryNumberToAddressOrOperationConverter<ulong>(links,
                ↪  powerOf2ToUnaryNumberConverter);
                var unaryNumberIncrementer = new UnaryNumberIncrementer<ulong>(links, unaryOne);
                var frequencyIncrementer = new FrequencyIncrementer<ulong>(links,
                ↪  frequencyMarker, unaryOne, unaryNumberIncrementer);
                var frequencyPropertyOperator = new PropertyOperator<ulong>(links,
                ↪  frequencyPropertyMarker, frequencyMarker);
                var index = new FrequencyIncrementingSequenceIndex<ulong>(links,
                ↪  frequencyPropertyOperator, frequencyIncrementer);
                var linkToItsFrequencyNumberConverter = new
                ↪  LinkToItsFrequencyNumberConveter<ulong>(links, frequencyPropertyOperator,
                ↪  unaryNumberToAddressConverter);
                var sequenceToItsLocalElementLevelsConverter = new
                ↪  SequenceToItsLocalElementLevelsConverter<ulong>(links,
                ↪  linkToItsFrequencyNumberConverter);
                var optimalVariantConverter = new OptimalVariantConverter<ulong>(links,
                ↪  sequenceToItsLocalElementLevelsConverter);

                var stringToUnicodeSequenceConverter = new
                ↪  StringToUnicodeSequenceConverter<ulong>(links, charToUnicodeSymbolConverter,
                ↪  index, optimalVariantConverter, unicodeSequenceMarker);

                var originalString = "Hello";

                var unicodeSequenceLink =
                ↪  stringToUnicodeSequenceConverter.Convert(originalString);

                var unicodeSymbolCriterionMatcher = new
                ↪  UnicodeSymbolCriterionMatcher<ulong>(links, unicodeSymbolMarker);
                var unicodeSymbolToCharConverter = new
                ↪  UnicodeSymbolToCharConverter<ulong>(links, unaryNumberToAddressConverter,
                ↪  unicodeSymbolCriterionMatcher);

                var unicodeSequenceCriterionMatcher = new
                ↪  UnicodeSequenceCriterionMatcher<ulong>(links, unicodeSequenceMarker);

                var sequenceWalker = new LeveledSequenceWalker<ulong>(links,
                ↪  unicodeSymbolCriterionMatcher.IsMatched);

                var unicodeSequenceToStringConverter = new
                ↪  UnicodeSequenceToStringConverter<ulong>(links,
                ↪  unicodeSequenceCriterionMatcher, sequenceWalker,
                ↪  unicodeSymbolToCharConverter);

                var resultingString =
                ↪  unicodeSequenceToStringConverter.Convert(unicodeSequenceLink);

                Assert.Equal(originalString, resultingString);
            }
        }
    }
}
```

Index