LinksPlatform's Platform.Data.Doublets Class Library

./Platform.Data.Doublets/Converters/AddressToUnaryNumberConverter.cs

```csharp
using System.Collections.Generic;
using Platform.Interfaces;
using Platform.Reflection;
using Platform.Numbers;

namespace Platform.Data.Doublets.Converters
{
    public class AddressToUnaryNumberConverter<TLink> : LinksOperatorBase<TLink>,
     ↪  IConverter<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;

        private readonly IConverter<int, TLink> _powerOf2ToUnaryNumberConverter;

        public AddressToUnaryNumberConverter(ILinks<TLink> links, IConverter<int, TLink>
         ↪  powerOf2ToUnaryNumberConverter) : base(links) => _powerOf2ToUnaryNumberConverter =
         ↪  powerOf2ToUnaryNumberConverter;

        public TLink Convert(TLink sourceAddress)
        {
            var number = sourceAddress;
            var nullConstant = Links.Constants.Null;
            var one = Integer<TLink>.One;
            var target = nullConstant;
            for (int i = 0; !_equalityComparer.Equals(number, default) && i <
             ↪  Type<TLink>.BitsLength; i++)
            {
                if (_equalityComparer.Equals(Arithmetic.And(number, one), one))
                {
                    target = _equalityComparer.Equals(target, nullConstant)
                        ? _powerOf2ToUnaryNumberConverter.Convert(i)
                        : Links.GetOrCreate(_powerOf2ToUnaryNumberConverter.Convert(i), target);
                }
                number = (Integer<TLink>)((ulong)(Integer<TLink>)number >> 1); // Should be
                 ↪  Bit.ShiftRight(number, 1)
            }
            return target;
        }
    }
}
```

./Platform.Data.Doublets/Converters/LinkToItsFrequencyNumberConveter.cs

```csharp
using System;
using System.Collections.Generic;
using Platform.Interfaces;

namespace Platform.Data.Doublets.Converters
{
    public class LinkToItsFrequencyNumberConveter<TLink> : LinksOperatorBase<TLink>,
     ↪  IConverter<Doublet<TLink>, TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;

        private readonly IPropertyOperator<TLink, TLink> _frequencyPropertyOperator;
        private readonly IConverter<TLink> _unaryNumberToAddressConverter;

        public LinkToItsFrequencyNumberConveter(
            ILinks<TLink> links,
            IPropertyOperator<TLink, TLink> frequencyPropertyOperator,
            IConverter<TLink> unaryNumberToAddressConverter)
            : base(links)
        {
            _frequencyPropertyOperator = frequencyPropertyOperator;
            _unaryNumberToAddressConverter = unaryNumberToAddressConverter;
        }

        public TLink Convert(Doublet<TLink> doublet)
        {
            var link = Links.SearchOrDefault(doublet.Source, doublet.Target);
            if (_equalityComparer.Equals(link, Links.Constants.Null))
            {
                throw new ArgumentException($"Link ({doublet}) not found.", nameof(doublet));
            }
            var frequency = _frequencyPropertyOperator.Get(link);
            if (_equalityComparer.Equals(frequency, default))
            {
                return default;
            }
            var frequencyNumber = Links.GetSource(frequency);
            return _unaryNumberToAddressConverter.Convert(frequencyNumber);
        }
    }
}
```

./Platform.Data.Doublets/Converters/PowerOf2ToUnaryNumberConverter.cs

```
using System.Collections.Generic;
using Platform.Exceptions;
using Platform.Interfaces;
using Platform.Ranges;

namespace Platform.Data.Doublets.Converters
{
    public class PowerOf2ToUnaryNumberConverter<TLink> : LinksOperatorBase<TLink>,
     ↪  IConverter<int, TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;

        private readonly TLink[] _unaryNumberPowersOf2;

        public PowerOf2ToUnaryNumberConverter(ILinks<TLink> links, TLink one) : base(links)
        {
            _unaryNumberPowersOf2 = new TLink[64];
            _unaryNumberPowersOf2[0] = one;
        }

        public TLink Convert(int power)
        {
            Ensure.Always.ArgumentInRange(power, new Range<int>(0, _unaryNumberPowersOf2.Length
             ↪   - 1), nameof(power));
            if (!_equalityComparer.Equals(_unaryNumberPowersOf2[power], default))
            {
                return _unaryNumberPowersOf2[power];
            }
            var previousPowerOf2 = Convert(power - 1);
            var powerOf2 = Links.GetOrCreate(previousPowerOf2, previousPowerOf2);
            _unaryNumberPowersOf2[power] = powerOf2;
            return powerOf2;
        }
    }
}
```

./Platform.Data.Doublets/Converters/UnaryNumberToAddressAddOperationConverter.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Interfaces;
using Platform.Numbers;

namespace Platform.Data.Doublets.Converters
{
    public class UnaryNumberToAddressAddOperationConverter<TLink> : LinksOperatorBase<TLink>,
     ↪  IConverter<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;

        private Dictionary<TLink, TLink> _unaryToUInt64;
        private readonly TLink _unaryOne;

        public UnaryNumberToAddressAddOperationConverter(ILinks<TLink> links, TLink unaryOne)
            : base(links)
        {
            _unaryOne = unaryOne;
            InitUnaryToUInt64();
        }

        private void InitUnaryToUInt64()
        {
            var one = Integer<TLink>.One;
            _unaryToUInt64 = new Dictionary<TLink, TLink>
            {
                { _unaryOne, one }
            };
            var unary = _unaryOne;
            var number = one;
            for (var i = 1; i < 64; i++)
            {
                unary = Links.GetOrCreate(unary, unary);
                number = Double(number);
                _unaryToUInt64.Add(unary, number);
            }
        }

        public TLink Convert(TLink unaryNumber)
        {
            if (_equalityComparer.Equals(unaryNumber, default))
            {
                return default;
            }
            if (_equalityComparer.Equals(unaryNumber, _unaryOne))
            {
                return Integer<TLink>.One;
            }
            var source = Links.GetSource(unaryNumber);
            var target = Links.GetTarget(unaryNumber);
            if (_equalityComparer.Equals(source, target))
            {
                return _unaryToUInt64[unaryNumber];
            }
            else
            {
                var result = _unaryToUInt64[source];
                TLink lastValue;
                while (!_unaryToUInt64.TryGetValue(target, out lastValue))
                {
                    source = Links.GetSource(target);
                    result = Arithmetic<TLink>.Add(result, _unaryToUInt64[source]);
                    target = Links.GetTarget(target);
                }
                result = Arithmetic<TLink>.Add(result, lastValue);
                return result;
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private static TLink Double(TLink number) => (Integer<TLink>)((Integer<TLink>)number *
        ↪  2UL);
    }
}
```

./Platform.Data.Doublets/Converters/UnaryNumberToAddressOrOperationConverter.cs

```
using System.Collections.Generic;
using Platform.Interfaces;
using Platform.Reflection;
using Platform.Numbers;
using System.Runtime.CompilerServices;

namespace Platform.Data.Doublets.Converters
{
    public class UnaryNumberToAddressOrOperationConverter<TLink> : LinksOperatorBase<TLink>,
    ↪  IConverter<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪  EqualityComparer<TLink>.Default;

        private readonly IDictionary<TLink, int> _unaryNumberPowerOf2Indicies;

        public UnaryNumberToAddressOrOperationConverter(ILinks<TLink> links, IConverter<int,
        ↪  TLink> powerOf2ToUnaryNumberConverter)
            : base(links)
        {
            _unaryNumberPowerOf2Indicies = new Dictionary<TLink, int>();
            for (int i = 0; i < Type<TLink>.BitsLength; i++)
            {
                _unaryNumberPowerOf2Indicies.Add(powerOf2ToUnaryNumberConverter.Convert(i), i);
            }
        }

        public TLink Convert(TLink sourceNumber)
        {
            var nullConstant = Links.Constants.Null;
            var source = sourceNumber;
            var target = nullConstant;
            if (!_equalityComparer.Equals(source, nullConstant))
            {
                while (true)
                {
                    if (_unaryNumberPowerOf2Indicies.TryGetValue(source, out int powerOf2Index))
                    {
                        SetBit(ref target, powerOf2Index);
                        break;
                    }
                    else
                    {
                        powerOf2Index = _unaryNumberPowerOf2Indicies[Links.GetSource(source)];
                        SetBit(ref target, powerOf2Index);
                        source = Links.GetTarget(source);
                    }
                }
            }
            return target;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private static void SetBit(ref TLink target, int powerOf2Index) => target =
        ↪  (Integer<TLink>)((Integer<TLink>)target | 1UL << powerOf2Index); // Should be
        ↪  Math.Or(target, Math.ShiftLeft(One, powerOf2Index))
    }
}
```

./Platform.Data.Doublets/Decorators/LinksCascadeUniquenessAndUsagesResolver.cs

```
namespace Platform.Data.Doublets.Decorators
{
    public class LinksCascadeUniquenessAndUsagesResolver<TLink> : LinksUniquenessResolver<TLink>
    {
        public LinksCascadeUniquenessAndUsagesResolver(ILinks<TLink> links) : base(links) { }

        protected override TLink ResolveAddressChangeConflict(TLink oldLinkAddress, TLink
        ↪  newLinkAddress)
        {
            Links.MergeUsages(oldLinkAddress, newLinkAddress);
            return base.ResolveAddressChangeConflict(oldLinkAddress, newLinkAddress);
        }
    }
}
```

./Platform.Data.Doublets/Decorators/LinksCascadeUsagesResolver.cs

```
namespace Platform.Data.Doublets.Decorators
{
    /// <remarks>
    /// <para>Must be used in conjunction with NonNullContentsLinkDeletionResolver.</para>
    /// <para>Должен использоваться вместе с NonNullContentsLinkDeletionResolver.</para>
    /// </remarks>
    public class LinksCascadeUsagesResolver<TLink> : LinksDecoratorBase<TLink>
    {
        public LinksCascadeUsagesResolver(ILinks<TLink> links) : base(links) { }

        public override void Delete(TLink linkIndex)
        {
            this.DeleteAllUsages(linkIndex);
            Links.Delete(linkIndex);
        }
    }
}
```

./Platform.Data.Doublets/Decorators/LinksDecoratorBase.cs

```
using System;
using System.Collections.Generic;
using Platform.Data.Constants;

namespace Platform.Data.Doublets.Decorators
{
    public abstract class LinksDecoratorBase<TLink> : LinksOperatorBase<TLink>, ILinks<TLink>
    {
        public LinksCombinedConstants<TLink, TLink, int> Constants { get; }
        protected LinksDecoratorBase(ILinks<TLink> links) : base(links) => Constants =
        ↪  links.Constants;
        public virtual TLink Count(IList<TLink> restriction) => Links.Count(restriction);
        public virtual TLink Each(Func<IList<TLink>, TLink> handler, IList<TLink> restrictions)
        ↪  => Links.Each(handler, restrictions);
        public virtual TLink Create() => Links.Create();
        public virtual TLink Update(IList<TLink> restrictions) => Links.Update(restrictions);
        public virtual void Delete(TLink link) => Links.Delete(link);
    }
}
```

./Platform.Data.Doublets/Decorators/LinksDisposableDecoratorBase.cs

```
using System;
using System.Collections.Generic;
using Platform.Disposables;
using Platform.Data.Constants;

namespace Platform.Data.Doublets.Decorators
{
    public abstract class LinksDisposableDecoratorBase<T> : DisposableBase, ILinks<T>
    {
        public LinksCombinedConstants<T, T, int> Constants { get; }

        public ILinks<T> Links { get; }

        protected LinksDisposableDecoratorBase(ILinks<T> links)
        {
            Links = links;
            Constants = links.Constants;
        }

        public virtual T Count(IList<T> restriction) => Links.Count(restriction);

        public virtual T Each(Func<IList<T>, T> handler, IList<T> restrictions) =>
         ↪  Links.Each(handler, restrictions);

        public virtual T Create() => Links.Create();

        public virtual T Update(IList<T> restrictions) => Links.Update(restrictions);

        public virtual void Delete(T link) => Links.Delete(link);

        protected override bool AllowMultipleDisposeCalls => true;

        protected override void Dispose(bool manual, bool wasDisposed)
        {
            if (!wasDisposed)
            {
                Links.DisposeIfPossible();
            }
        }
    }
}
```

./Platform.Data.Doublets/Decorators/LinksInnerReferenceExistenceValidator.cs

```
using System;
using System.Collections.Generic;

namespace Platform.Data.Doublets.Decorators
{
    // TODO: Make LinksExternalReferenceValidator. A layer that checks each link to exist or to
     ↪  be external (hybrid link's raw number).
    public class LinksInnerReferenceExistenceValidator<TLink> : LinksDecoratorBase<TLink>
    {
        public LinksInnerReferenceExistenceValidator(ILinks<TLink> links) : base(links) { }

        public override TLink Each(Func<IList<TLink>, TLink> handler, IList<TLink> restrictions)
        {
            Links.EnsureInnerReferenceExists(restrictions, nameof(restrictions));
            return Links.Each(handler, restrictions);
        }

        public override TLink Count(IList<TLink> restriction)
        {
            Links.EnsureInnerReferenceExists(restriction, nameof(restriction));
            return Links.Count(restriction);
        }

        public override TLink Update(IList<TLink> restrictions)
        {
            // TODO: Possible values: null, ExistentLink or NonExistentHybrid(ExternalReference)
            Links.EnsureInnerReferenceExists(restrictions, nameof(restrictions));
            return Links.Update(restrictions);
        }

        public override void Delete(TLink link)
        {
            Links.EnsureLinkExists(link, nameof(link));
```

```
                Links.Delete(link);
            }
        }
    }
```

./Platform.Data.Doublets/Decorators/LinksItselfConstantToSelfReferenceResolver.cs

```
using System;
using System.Collections.Generic;

namespace Platform.Data.Doublets.Decorators
{
    public class LinksItselfConstantToSelfReferenceResolver<TLink> : LinksDecoratorBase<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪  EqualityComparer<TLink>.Default;

        public LinksItselfConstantToSelfReferenceResolver(ILinks<TLink> links) : base(links) { }

        public override TLink Each(Func<IList<TLink>, TLink> handler, IList<TLink> restrictions)
        {
            var constants = Constants;
            var itselfConstant = constants.Itself;
            var indexPartConstant = constants.IndexPart;
            var sourcePartConstant = constants.SourcePart;
            var targetPartConstant = constants.TargetPart;
            var restrictionsCount = restrictions.Count;
            if (!_equalityComparer.Equals(constants.Any, itselfConstant)
             && (((restrictionsCount > indexPartConstant) &&
              ↪  _equalityComparer.Equals(restrictions[indexPartConstant], itselfConstant))
             || ((restrictionsCount > sourcePartConstant) &&
              ↪  _equalityComparer.Equals(restrictions[sourcePartConstant], itselfConstant))
             || ((restrictionsCount > targetPartConstant) &&
              ↪  _equalityComparer.Equals(restrictions[targetPartConstant], itselfConstant))))
            {
                // Itself constant is not supported for Each method right now, skipping execution
                return constants.Continue;
            }
            return Links.Each(handler, restrictions);
        }

        public override TLink Update(IList<TLink> restrictions) =>
        ↪  Links.Update(Links.ResolveConstantAsSelfReference(Constants.Itself, restrictions));
    }
}
```

./Platform.Data.Doublets/Decorators/LinksNonExistentDependenciesCreator.cs

```
using System.Collections.Generic;

namespace Platform.Data.Doublets.Decorators
{
    /// <remarks>
    /// Not practical if newSource and newTarget are too big.
    /// To be able to use practical version we should allow to create link at any specific
    ↪  location inside ResizableDirectMemoryLinks.
    /// This in turn will require to implement not a list of empty links, but a list of ranges
    ↪  to store it more efficiently.
    /// </remarks>
    public class LinksNonExistentDependenciesCreator<TLink> : LinksDecoratorBase<TLink>
    {
        public LinksNonExistentDependenciesCreator(ILinks<TLink> links) : base(links) { }

        public override TLink Update(IList<TLink> restrictions)
        {
            var constants = Constants;
            Links.EnsureCreated(restrictions[constants.SourcePart],
            ↪  restrictions[constants.TargetPart]);
            return Links.Update(restrictions);
        }
    }
}
```

./Platform.Data.Doublets/Decorators/LinksNullConstantToSelfReferenceResolver.cs

```
using System.Collections.Generic;

namespace Platform.Data.Doublets.Decorators
{
    public class LinksNullConstantToSelfReferenceResolver<TLink> : LinksDecoratorBase<TLink>
    {
        public LinksNullConstantToSelfReferenceResolver(ILinks<TLink> links) : base(links) { }

        public override TLink Create()
        {
            var link = Links.Create();
            return Links.Update(link, link, link);
        }

        public override TLink Update(IList<TLink> restrictions) =>
         ↪  Links.Update(Links.ResolveConstantAsSelfReference(Constants.Null, restrictions));
    }
}
```

./Platform.Data.Doublets/Decorators/LinksUniquenessResolver.cs

```
using System.Collections.Generic;

namespace Platform.Data.Doublets.Decorators
{
    public class LinksUniquenessResolver<TLink> : LinksDecoratorBase<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;

        public LinksUniquenessResolver(ILinks<TLink> links) : base(links) { }

        public override TLink Update(IList<TLink> restrictions)
        {
            var newLinkAddress = Links.SearchOrDefault(restrictions[Constants.SourcePart],
             ↪  restrictions[Constants.TargetPart]);
            if (_equalityComparer.Equals(newLinkAddress, default))
            {
                return Links.Update(restrictions);
            }
            return ResolveAddressChangeConflict(restrictions[Constants.IndexPart],
             ↪  newLinkAddress);
        }

        protected virtual TLink ResolveAddressChangeConflict(TLink oldLinkAddress, TLink
         ↪  newLinkAddress)
        {
            if (!_equalityComparer.Equals(oldLinkAddress, newLinkAddress) &&
             ↪  Links.Exists(oldLinkAddress))
            {
                Delete(oldLinkAddress);
            }
            return newLinkAddress;
        }
    }
}
```

./Platform.Data.Doublets/Decorators/LinksUniquenessValidator.cs

```
using System.Collections.Generic;

namespace Platform.Data.Doublets.Decorators
{
    public class LinksUniquenessValidator<TLink> : LinksDecoratorBase<TLink>
    {
        public LinksUniquenessValidator(ILinks<TLink> links) : base(links) { }

        public override TLink Update(IList<TLink> restrictions)
        {
            Links.EnsureDoesNotExists(restrictions[Constants.SourcePart],
             ↪  restrictions[Constants.TargetPart]);
            return Links.Update(restrictions);
        }
    }
}
```

./Platform.Data.Doublets/Decorators/LinksUsagesValidator.cs

```
using System.Collections.Generic;

namespace Platform.Data.Doublets.Decorators
{
    public class LinksUsagesValidator<TLink> : LinksDecoratorBase<TLink>
    {
        public LinksUsagesValidator(ILinks<TLink> links) : base(links) { }

        public override TLink Update(IList<TLink> restrictions)
        {
                Links.EnsureNoUsages(restrictions[Constants.IndexPart]);
                return Links.Update(restrictions);
            }

            public override void Delete(TLink link)
            {
                Links.EnsureNoUsages(link);
                Links.Delete(link);
            }
        }
    }
```

./Platform.Data.Doublets/Decorators/NonNullContentsLinkDeletionResolver.cs

```
    namespace Platform.Data.Doublets.Decorators
    {
        public class NonNullContentsLinkDeletionResolver<TLink> : LinksDecoratorBase<TLink>
        {
            public NonNullContentsLinkDeletionResolver(ILinks<TLink> links) : base(links) { }

            public override void Delete(TLink linkIndex)
            {
                Links.EnforceResetValues(linkIndex);
                Links.Delete(linkIndex);
            }
        }
    }
```

./Platform.Data.Doublets/Decorators/UInt64Links.cs

```
    using System;
    using System.Collections.Generic;
    using Platform.Collections;

    namespace Platform.Data.Doublets.Decorators
    {
        /// <summary>
        /// Представляет объект для работы с базой данных (файлом) в формате Links (массива связей).
        /// </summary>
        /// <remarks>
        /// Возможные оптимизации:
        /// Объединение в одном поле Source и Target с уменьшением до 32 бит.
        ///     + меньше объём БД
        ///     - меньше производительность
        ///     - больше ограничение на количество связей в БД)
        /// Ленивое хранение размеров поддеревьев (расчитываемое по мере использования БД)
        ///     + меньше объём БД
        ///     - больше сложность
        ///
        /// Текущее теоретическое ограничение на индекс связи, из-за использования 5 бит в размере
        ↪  поддеревьев для AVL баланса и флагов нитей: 2 в степени(64 минус 5 равно 59 ) равно 576
        ↪  460 752 303 423 488
        /// Желательно реализовать поддержку переключения между деревьями и битовыми индексами
        ↪  (битовыми строками) - вариант матрицы (выстраеваемой лениво).
        ///
        /// Решить отключать ли проверки при компиляции под Release. Т.е. исключения будут
        ↪  выбрасываться только при #if DEBUG
        /// </remarks>
        public class UInt64Links : LinksDisposableDecoratorBase<ulong>
        {
            public UInt64Links(ILinks<ulong> links) : base(links) { }

            public override ulong Each(Func<IList<ulong>, ulong> handler, IList<ulong> restrictions)
            {
                this.EnsureLinkIsAnyOrExists(restrictions);
                return Links.Each(handler, restrictions);
            }

            public override ulong Create() => Links.CreatePoint();

            public override ulong Update(IList<ulong> restrictions)
            {
                var constants = Constants;
                var nullConstant = constants.Null;
                if (restrictions.IsNullOrEmpty())
                {
                    return nullConstant;
                }
                // TODO: Looks like this is a common type of exceptions linked with restrictions
                 ↪  support
                if (restrictions.Count != 3)
            {
                throw new NotSupportedException();
            }
            var indexPartConstant = constants.IndexPart;
            var updatedLink = restrictions[indexPartConstant];
            this.EnsureLinkExists(updatedLink, $"{nameof(restrictions)}[{nameof(indexPartConstant)}]");
            var sourcePartConstant = constants.SourcePart;
            var newSource = restrictions[sourcePartConstant];
            this.EnsureLinkIsItselfOrExists(newSource, $"{nameof(restrictions)}[{nameof(sourcePartConstant)}]");
            var targetPartConstant = constants.TargetPart;
            var newTarget = restrictions[targetPartConstant];
            this.EnsureLinkIsItselfOrExists(newTarget, $"{nameof(restrictions)}[{nameof(targetPartConstant)}]");
            var existedLink = nullConstant;
            var itselfConstant = constants.Itself;
            if (newSource != itselfConstant && newTarget != itselfConstant)
            {
                existedLink = this.SearchOrDefault(newSource, newTarget);
            }
            if (existedLink == nullConstant)
            {
                var before = Links.GetLink(updatedLink);
                if (before[sourcePartConstant] != newSource || before[targetPartConstant] != newTarget)
                {
                    Links.Update(updatedLink, newSource == itselfConstant ? updatedLink : newSource,
                                              newTarget == itselfConstant ? updatedLink : newTarget);
                }
                return updatedLink;
            }
            else
            {
                return this.MergeAndDelete(updatedLink, existedLink);
            }
        }

        public override void Delete(ulong linkIndex)
        {
            Links.EnsureLinkExists(linkIndex);
            Links.EnforceResetValues(linkIndex);
            this.DeleteAllUsages(linkIndex);
            Links.Delete(linkIndex);
        }
    }
}
```

./Platform.Data.Doublets/Decorators/UniLinks.cs

```
using System;
using System.Collections.Generic;
using System.Linq;
using Platform.Collections;
using Platform.Collections.Arrays;
using Platform.Collections.Lists;
using Platform.Data.Universal;

namespace Platform.Data.Doublets.Decorators
{
    /// <remarks>
    /// What does empty pattern (for condition or substitution) mean? Nothing or Everything?
    /// Now we go with nothing. And nothing is something one, but empty, and cannot be changed by itself. But can cause creation (update from nothing) or deletion (update to nothing).
    ///
    /// TODO: Decide to change to IDoubletLinks or not to change. (Better to create DefaultUniLinksBase, that contains logic itself and can be implemented using both IDoubletLinks and ILinks.)
    /// </remarks>
    internal class UniLinks<TLink> : LinksDecoratorBase<TLink>, IUniLinks<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer = EqualityComparer<TLink>.Default;

        public UniLinks(ILinks<TLink> links) : base(links) { }

        private struct Transition
        {
            public IList<TLink> Before;
            public IList<TLink> After;

            public Transition(IList<TLink> before, IList<TLink> after)
            {
                Before = before;
                After = after;
            }
        }

        //public static readonly TLink NullConstant = Use<LinksCombinedConstants<TLink, TLink,
         ↪  int>>.Single.Null;
        //public static readonly IReadOnlyList<TLink> NullLink = new
         ↪  ReadOnlyCollection<TLink>(new List<TLink> { NullConstant, NullConstant, NullConstant
         ↪  });

        // TODO: Подумать о том, как реализовать древовидный Restriction и Substitution
         ↪  (Links-Expression)
        public TLink Trigger(IList<TLink> restriction, Func<IList<TLink>, IList<TLink>, TLink>
         ↪  matchedHandler, IList<TLink> substitution, Func<IList<TLink>, IList<TLink>, TLink>
         ↪  substitutedHandler)
        {
            ////List<Transition> transitions = null;
            ////if (!restriction.IsNullOrEmpty())
            ////{
            ////    // Есть причина делать проход (чтение)
            ////    if (matchedHandler != null)
            ////    {
            ////        if (!substitution.IsNullOrEmpty())
            ////        {
            ////            // restriction => { 0, 0, 0 } | { 0 } // Create
            ////            // substitution => { itself, 0, 0 } | { itself, itself, itself } //
             ↪  Create / Update
            ////            // substitution => { 0, 0, 0 } | { 0 } // Delete
            ////            transitions = new List<Transition>();
            ////            if (Equals(substitution[Constants.IndexPart], Constants.Null))
            ////            {
            ////                // If index is Null, that means we always ignore every other
             ↪  value (they are also Null by definition)
            ////                var matchDecision = matchedHandler(, NullLink);
            ////                if (Equals(matchDecision, Constants.Break))
            ////                    return false;
            ////                if (!Equals(matchDecision, Constants.Skip))
            ////                    transitions.Add(new Transition(matchedLink, newValue));
            ////            }
            ////            else
            ////            {
            ////                Func<T, bool> handler;
            ////                handler = link =>
            ////                {
            ////                    var matchedLink = Memory.GetLinkValue(link);
            ////                    var newValue = Memory.GetLinkValue(link);
            ////                    newValue[Constants.IndexPart] = Constants.Itself;
            ////                    newValue[Constants.SourcePart] =
             ↪  Equals(substitution[Constants.SourcePart], Constants.Itself) ?
             ↪  matchedLink[Constants.IndexPart] : substitution[Constants.SourcePart];
            ////                    newValue[Constants.TargetPart] =
             ↪  Equals(substitution[Constants.TargetPart], Constants.Itself) ?
             ↪  matchedLink[Constants.IndexPart] : substitution[Constants.TargetPart];
            ////                    var matchDecision = matchedHandler(matchedLink, newValue);
            ////                    if (Equals(matchDecision, Constants.Break))
            ////                        return false;
            ////                    if (!Equals(matchDecision, Constants.Skip))
            ////                        transitions.Add(new Transition(matchedLink, newValue));
            ////                    return true;
            ////                };
            ////                if (!Memory.Each(handler, restriction))
            ////                    return Constants.Break;
            ////            }
            ////        }
            ////        else
            ////        {
            ////            Func<T, bool> handler = link =>
            ////            {
            ////                var matchedLink = Memory.GetLinkValue(link);
            ////                var matchDecision = matchedHandler(matchedLink, matchedLink);
            ////                return !Equals(matchDecision, Constants.Break);
            ////            };
            ////            if (!Memory.Each(handler, restriction))
            ////                return Constants.Break;
            ////        }
            ////    }
            ////    else
            ////    {
            ////        if (substitution != null)
            ////        {
            ////            transitions = new List<IList<T>>();
            ////            Func<T, bool> handler = link =>
            ////            {
            ////                var matchedLink = Memory.GetLinkValue(link);
            ////                transitions.Add(matchedLink);
            ////                return true;
            ////            };
            ////            if (!Memory.Each(handler, restriction))
            ////                return Constants.Break;
            ////        }
            ////        else
            ////        {
            ////            return Constants.Continue;
            ////        }
            ////    }
            ////}
            ////if (substitution != null)
            ////{
            ////    // Есть причина делать замену (запись)
            ////    if (substitutedHandler != null)
            ////    {
            ////    }
            ////    else
            ////    {
            ////    }
            ////}
            ////return Constants.Continue;

            //if (restriction.IsNullOrEmpty()) // Create
            //{
            //    substitution[Constants.IndexPart] = Memory.AllocateLink();
            //    Memory.SetLinkValue(substitution);
            //}
            //else if (substitution.IsNullOrEmpty()) // Delete
            //{
            //    Memory.FreeLink(restriction[Constants.IndexPart]);
            //}
            //else if (restriction.EqualTo(substitution)) // Read or ("repeat" the state) // Each
            //{
            //    // No need to collect links to list
            //    // Skip == Continue
            //    // No need to check substituedHandler
            //    if (!Memory.Each(link => !Equals(matchedHandler(Memory.GetLinkValue(link)),
            ↪  Constants.Break), restriction))
            //        return Constants.Break;
            //}
            //else // Update
            //{
            //    //List<IList<T>> matchedLinks = null;
            //    if (matchedHandler != null)
            //    {
            //        matchedLinks = new List<IList<T>>();
            //        Func<T, bool> handler = link =>
            //        {
            //            var matchedLink = Memory.GetLinkValue(link);
            //            var matchDecision = matchedHandler(matchedLink);
            //            if (Equals(matchDecision, Constants.Break))
            //                return false;
            //            if (!Equals(matchDecision, Constants.Skip))
            //                matchedLinks.Add(matchedLink);
            //            return true;
            //        };
            //        if (!Memory.Each(handler, restriction))
            //            return Constants.Break;
            //    }
            //    if (!matchedLinks.IsNullOrEmpty())
            //    {
            //        var totalMatchedLinks = matchedLinks.Count;
            //        for (var i = 0; i < totalMatchedLinks; i++)
            //        {
            //            var matchedLink = matchedLinks[i];
            //            if (substitutedHandler != null)
            //            {
            //                var newValue = new List<T>(); // TODO: Prepare value to update here
            //                // TODO: Decide is it actually needed to use Before and After
             ↪  substitution handling.
            //                var substitutedDecision = substitutedHandler(matchedLink,
             ↪  newValue);
            //                if (Equals(substitutedDecision, Constants.Break))
            //                    return Constants.Break;
            //                if (Equals(substitutedDecision, Constants.Continue))
            //                {
            //                    // Actual update here
            //                    Memory.SetLinkValue(newValue);
            //                }
            //                if (Equals(substitutedDecision, Constants.Skip))
            //                {
            //                    // Cancel the update. TODO: decide use separate Cancel
             ↪  constant or Skip is enough?
            //                }
            //            }
            //        }
            //    }
            //}
            return Constants.Continue;
        }

        public TLink Trigger(IList<TLink> patternOrCondition, Func<IList<TLink>, TLink>
         ↪  matchHandler, IList<TLink> substitution, Func<IList<TLink>, IList<TLink>, TLink>
         ↪  substitutionHandler)
        {
            if (patternOrCondition.IsNullOrEmpty() && substitution.IsNullOrEmpty())
            {
                return Constants.Continue;
            }
            else if (patternOrCondition.EqualTo(substitution)) // Should be Each here TODO:
             ↪  Check if it is a correct condition
            {
                // Or it only applies to trigger without matchHandler.
                throw new NotImplementedException();
            }
            else if (!substitution.IsNullOrEmpty()) // Creation
            {
                var before = ArrayPool<TLink>.Empty;
                // Что должно означать False здесь? Остановиться (перестать идти) или пропустить
                 ↪  (пройти мимо) или пустить (взять)?
                if (matchHandler != null && _equalityComparer.Equals(matchHandler(before),
                 ↪  Constants.Break))
                {
                    return Constants.Break;
                }
                var after = (IList<TLink>)substitution.ToArray();
                if (_equalityComparer.Equals(after[0], default))
                {
                    var newLink = Links.Create();
                    after[0] = newLink;
                }
                if (substitution.Count == 1)
                {
                    after = Links.GetLink(substitution[0]);
                }
                else if (substitution.Count == 3)
                {
                    Links.Update(after);
                }
                else
                {
                    throw new NotSupportedException();
                }
                if (matchHandler != null)
                {
                    return substitutionHandler(before, after);
                }
                return Constants.Continue;
            }
            else if (!patternOrCondition.IsNullOrEmpty()) // Deletion
            {
                if (patternOrCondition.Count == 1)
                {
                    var linkToDelete = patternOrCondition[0];
                    var before = Links.GetLink(linkToDelete);
                    if (matchHandler != null && _equalityComparer.Equals(matchHandler(before),
                     ↪  Constants.Break))
                    {
                        return Constants.Break;
                    }
                    var after = ArrayPool<TLink>.Empty;
                    Links.Update(linkToDelete, Constants.Null, Constants.Null);
                    Links.Delete(linkToDelete);
                    if (matchHandler != null)
                    {
                        return substitutionHandler(before, after);
                    }
                    return Constants.Continue;
                }
                else
                {
                    throw new NotSupportedException();
                }
            }
            else // Replace / Update
            {
                if (patternOrCondition.Count == 1) //-V3125
                {
                    var linkToUpdate = patternOrCondition[0];
                    var before = Links.GetLink(linkToUpdate);
                    if (matchHandler != null && _equalityComparer.Equals(matchHandler(before),
                     ↪  Constants.Break))
                    {
                        return Constants.Break;
                    }
                    var after = (IList<TLink>)substitution.ToArray(); //-V3125
                    if (_equalityComparer.Equals(after[0], default))
                    {
                        after[0] = linkToUpdate;
                    }
                    if (substitution.Count == 1)
                    {
                        if (!_equalityComparer.Equals(substitution[0], linkToUpdate))
                        {
                            after = Links.GetLink(substitution[0]);
                            Links.Update(linkToUpdate, Constants.Null, Constants.Null);
                            Links.Delete(linkToUpdate);
                        }
                    }
                    else if (substitution.Count == 3)
                    {
                        Links.Update(after);
                    }
                    else
                    {
                        throw new NotSupportedException();
                    }
                    if (matchHandler != null)
                    {
                        return substitutionHandler(before, after);
                    }
                    return Constants.Continue;
                }
                else
                {
                    throw new NotSupportedException();
                }
            }
        }

        /// <remarks>
        /// IList[IList[IList[T]]]
        /// |     |     |      |||
        /// |     |      ------ ||
        /// |     |       link  ||
        /// |      ------------- |
        /// |         change     |
        ///  --------------------
        ///        changes
        /// </remarks>
        public IList<IList<IList<TLink>>> Trigger(IList<TLink> condition, IList<TLink>
         ↪  substitution)
        {
            var changes = new List<IList<IList<TLink>>>();
            Trigger(condition, AlwaysContinue, substitution, (before, after) =>
            {
                var change = new[] { before, after };
                changes.Add(change);
                return Constants.Continue;
            });
            return changes;
        }

        private TLink AlwaysContinue(IList<TLink> linkToMatch) => Constants.Continue;
    }
}
```

./Platform.Data.Doublets/DoubletComparer.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;

namespace Platform.Data.Doublets
{
    /// <remarks>
    /// TODO: Может стоит попробовать ref во всех методах (IRefEqualityComparer)
    /// 2x faster with comparer
    /// </remarks>
    public class DoubletComparer<T> : IEqualityComparer<Doublet<T>>
    {
        public static readonly DoubletComparer<T> Default = new DoubletComparer<T>();

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public bool Equals(Doublet<T> x, Doublet<T> y) => x.Equals(y);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public int GetHashCode(Doublet<T> obj) => obj.GetHashCode();
    }
}
```

./Platform.Data.Doublets/Doublet.cs

```
using System;
using System.Collections.Generic;

namespace Platform.Data.Doublets
{
    public struct Doublet<T> : IEquatable<Doublet<T>>
    {
        private static readonly EqualityComparer<T> _equalityComparer =
         ↪  EqualityComparer<T>.Default;

        public T Source { get; set; }
        public T Target { get; set; }

        public Doublet(T source, T target)
        {
            Source = source;
            Target = target;
        }

        public override string ToString() => $"{Source}->{Target}";

        public bool Equals(Doublet<T> other) => _equalityComparer.Equals(Source, other.Source)
         ↪  && _equalityComparer.Equals(Target, other.Target);

        public override bool Equals(object obj) => obj is Doublet<T> doublet ?
         ↪  base.Equals(doublet) : false;

        public override int GetHashCode() => (Source, Target).GetHashCode();
    }
}
```

./Platform.Data.Doublets/Hybrid.cs

```
using System;
using System.Reflection;
using Platform.Reflection;
using Platform.Converters;
using Platform.Exceptions;

```

```
namespace Platform.Data.Doublets
{
    public class Hybrid<T>
    {
        public readonly T Value;
        public bool IsNothing => Convert.ToInt64(To.Signed(Value)) == 0;
        public bool IsInternal => Convert.ToInt64(To.Signed(Value)) > 0;
        public bool IsExternal => Convert.ToInt64(To.Signed(Value)) < 0;
        public long AbsoluteValue => Numbers.Math.Abs(Convert.ToInt64(To.Signed(Value)));

        public Hybrid(T value)
        {
            Ensure.Always.IsUnsignedInteger<T>();
            Value = value;
        }

        public Hybrid(object value) => Value = To.UnsignedAs<T>(Convert.ChangeType(value, Type<T>.SignedVersion));

        public Hybrid(object value, bool isExternal)
        {
            var signedType = Type<T>.SignedVersion;
            var signedValue = Convert.ChangeType(value, signedType);
            var abs = typeof(Numbers.Math).GetTypeInfo().GetMethod("Abs").MakeGenericMethod(signedType);
            var negate = typeof(Numbers.Math).GetTypeInfo().GetMethod("Negate").MakeGenericMethod(signedType);
            var absoluteValue = abs.Invoke(null, new[] { signedValue });
            var resultValue = isExternal ? negate.Invoke(null, new[] { absoluteValue }) : absoluteValue;
            Value = To.UnsignedAs<T>(resultValue);
        }

        public static implicit operator Hybrid<T>(T integer) => new Hybrid<T>(integer);

        public static explicit operator Hybrid<T>(ulong integer) => new Hybrid<T>(integer);

        public static explicit operator Hybrid<T>(long integer) => new Hybrid<T>(integer);

        public static explicit operator Hybrid<T>(uint integer) => new Hybrid<T>(integer);

        public static explicit operator Hybrid<T>(int integer) => new Hybrid<T>(integer);

        public static explicit operator Hybrid<T>(ushort integer) => new Hybrid<T>(integer);

        public static explicit operator Hybrid<T>(short integer) => new Hybrid<T>(integer);

        public static explicit operator Hybrid<T>(byte integer) => new Hybrid<T>(integer);

        public static explicit operator Hybrid<T>(sbyte integer) => new Hybrid<T>(integer);

        public static implicit operator T(Hybrid<T> hybrid) => hybrid.Value;

        public static explicit operator ulong(Hybrid<T> hybrid) => Convert.ToUInt64(hybrid.Value);

        public static explicit operator long(Hybrid<T> hybrid) => hybrid.AbsoluteValue;

        public static explicit operator uint(Hybrid<T> hybrid) => Convert.ToUInt32(hybrid.Value);

        public static explicit operator int(Hybrid<T> hybrid) => Convert.ToInt32(hybrid.AbsoluteValue);

        public static explicit operator ushort(Hybrid<T> hybrid) => Convert.ToUInt16(hybrid.Value);

        public static explicit operator short(Hybrid<T> hybrid) => Convert.ToInt16(hybrid.AbsoluteValue);

        public static explicit operator byte(Hybrid<T> hybrid) => Convert.ToByte(hybrid.Value);

        public static explicit operator sbyte(Hybrid<T> hybrid) => Convert.ToSByte(hybrid.AbsoluteValue);

        public override string ToString() => IsNothing ? default(T) == null ? "Nothing" : default(T).ToString() : IsExternal ? $"<{AbsoluteValue}>" : Value.ToString();
    }
}
```

./Platform.Data.Doublets/ILinks.cs

```
using Platform.Data.Constants;

namespace Platform.Data.Doublets
{
    public interface ILinks<TLink> : ILinks<TLink, LinksCombinedConstants<TLink, TLink, int>>
    {
    }
}
```

./Platform.Data.Doublets/ILinksExtensions.cs

```
using System;
using System.Collections;
using System.Collections.Generic;
using System.Linq;
using System.Runtime.CompilerServices;
using Platform.Ranges;
using Platform.Collections.Arrays;
using Platform.Numbers;
using Platform.Random;
using Platform.Setters;
using Platform.Data.Exceptions;

namespace Platform.Data.Doublets
{
    public static class ILinksExtensions
    {
        public static void RunRandomCreations<TLink>(this ILinks<TLink> links, long
         ↪  amountOfCreations)
        {
            for (long i = 0; i < amountOfCreations; i++)
            {
                var linksAddressRange = new Range<ulong>(0, (Integer<TLink>)links.Count());
                Integer<TLink> source = RandomHelpers.Default.NextUInt64(linksAddressRange);
                Integer<TLink> target = RandomHelpers.Default.NextUInt64(linksAddressRange);
                links.CreateAndUpdate(source, target);
            }
        }

        public static void RunRandomSearches<TLink>(this ILinks<TLink> links, long
         ↪  amountOfSearches)
        {
            for (long i = 0; i < amountOfSearches; i++)
            {
                var linkAddressRange = new Range<ulong>(1, (Integer<TLink>)links.Count());
                Integer<TLink> source = RandomHelpers.Default.NextUInt64(linkAddressRange);
                Integer<TLink> target = RandomHelpers.Default.NextUInt64(linkAddressRange);
                links.SearchOrDefault(source, target);
            }
        }

        public static void RunRandomDeletions<TLink>(this ILinks<TLink> links, long
         ↪  amountOfDeletions)
        {
            var min = (ulong)amountOfDeletions > (Integer<TLink>)links.Count() ? 1 :
             ↪  (Integer<TLink>)links.Count() - (ulong)amountOfDeletions;
            for (long i = 0; i < amountOfDeletions; i++)
            {
                var linksAddressRange = new Range<ulong>(min, (Integer<TLink>)links.Count());
                Integer<TLink> link = RandomHelpers.Default.NextUInt64(linksAddressRange);
                links.Delete(link);
                if ((Integer<TLink>)links.Count() < min)
                {
                    break;
                }
            }
        }

        /// <remarks>
        /// TODO: Возможно есть очень простой способ это сделать.
        /// (Например просто удалить файл, или изменить его размер таким образом,
        /// чтобы удалился весь контент)
        /// Например через _header->AllocatedLinks в ResizableDirectMemoryLinks
        /// </remarks>
        public static void DeleteAll<TLink>(this ILinks<TLink> links)
        {
            var equalityComparer = EqualityComparer<TLink>.Default;
            var comparer = Comparer<TLink>.Default;
            for (var i = links.Count(); comparer.Compare(i, default) > 0; i =
             ↪  Arithmetic.Decrement(i))
            {
                links.Delete(i);
                if (!equalityComparer.Equals(links.Count(), Arithmetic.Decrement(i)))
                {
                    i = links.Count();
                }
            }
        }

        public static TLink First<TLink>(this ILinks<TLink> links)
        {
            TLink firstLink = default;
            var equalityComparer = EqualityComparer<TLink>.Default;
            if (equalityComparer.Equals(links.Count(), default))
            {
                throw new Exception("В хранилище нет связей.");
            }
            links.Each(links.Constants.Any, links.Constants.Any, link =>
            {
                firstLink = link[links.Constants.IndexPart];
                return links.Constants.Break;
            });
            if (equalityComparer.Equals(firstLink, default))
            {
                throw new Exception("В процессе поиска по хранилищу не было найдено связей.");
            }
            return firstLink;
        }

        public static bool IsInnerReference<TLink>(this ILinks<TLink> links, TLink reference)
        {
            var constants = links.Constants;
            var comparer = Comparer<TLink>.Default;
            return comparer.Compare(constants.MinPossibleIndex, reference) >= 0 &&
             ↪  comparer.Compare(reference, constants.MaxPossibleIndex) <= 0;
        }

        #region Paths

        /// <remarks>
        /// TODO: Как так? Как то что ниже может быть корректно?
        /// Скорее всего практически не применимо
        /// Предполагалось, что можно было конвертировать формируемый в проходе через
         ↪  SequenceWalker
        /// Stack в конкретный путь из Source, Target до связи, но это не всегда так.
        /// TODO: Возможно нужен метод, который именно выбрасывает исключения (EnsurePathExists)
        /// </remarks>
        public static bool CheckPathExistance<TLink>(this ILinks<TLink> links, params TLink[]
         ↪  path)
        {
            var current = path[0];
            //EnsureLinkExists(current, "path");
            if (!links.Exists(current))
            {
                return false;
            }
            var equalityComparer = EqualityComparer<TLink>.Default;
            var constants = links.Constants;
            for (var i = 1; i < path.Length; i++)
            {
                var next = path[i];
                var values = links.GetLink(current);
                var source = values[constants.SourcePart];
                var target = values[constants.TargetPart];
                if (equalityComparer.Equals(source, target) && equalityComparer.Equals(source,
                 ↪  next))
                {
                    //throw new Exception(string.Format("Невозможно выбрать путь, так как и
                     ↪  Source и Target совпадают с элементом пути {0}.", next));
                    return false;
                }
                if (!equalityComparer.Equals(next, source) && !equalityComparer.Equals(next,
                 ↪  target))
                {
                    //throw new Exception(string.Format("Невозможно продолжить путь через
                     ↪  элемент пути {0}", next));
                    return false;
                }
                current = next;
            }
            return true;
        }

        /// <remarks>
        /// Может потребовать дополнительного стека для PathElement's при использовании
        ↪  SequenceWalker.
        /// </remarks>
        public static TLink GetByKeys<TLink>(this ILinks<TLink> links, TLink root, params int[]
        ↪  path)
        {
            links.EnsureLinkExists(root, "root");
            var currentLink = root;
            for (var i = 0; i < path.Length; i++)
            {
                currentLink = links.GetLink(currentLink)[path[i]];
            }
            return currentLink;
        }

        public static TLink GetSquareMatrixSequenceElementByIndex<TLink>(this ILinks<TLink>
        ↪  links, TLink root, ulong size, ulong index)
        {
            var constants = links.Constants;
            var source = constants.SourcePart;
            var target = constants.TargetPart;
            if (!Numbers.Math.IsPowerOfTwo(size))
            {
                throw new ArgumentOutOfRangeException(nameof(size), "Sequences with sizes other
                ↪  than powers of two are not supported.");
            }
            var path = new BitArray(BitConverter.GetBytes(index));
            var length = Bit.GetLowestPosition(size);
            links.EnsureLinkExists(root, "root");
            var currentLink = root;
            for (var i = length - 1; i >= 0; i--)
            {
                currentLink = links.GetLink(currentLink)[path[i] ? target : source];
            }
            return currentLink;
        }

        #endregion

        /// <summary>
        /// Возвращает индекс указанной связи.
        /// </summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="link">Связь представленная списком, состоящим из её адреса и
        ↪  содержимого.</param>
        /// <returns>Индекс начальной связи для указанной связи.</returns>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static TLink GetIndex<TLink>(this ILinks<TLink> links, IList<TLink> link) =>
        ↪  link[links.Constants.IndexPart];

        /// <summary>
        /// Возвращает индекс начальной (Source) связи для указанной связи.
        /// </summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="link">Индекс связи.</param>
        /// <returns>Индекс начальной связи для указанной связи.</returns>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static TLink GetSource<TLink>(this ILinks<TLink> links, TLink link) =>
        ↪  links.GetLink(link)[links.Constants.SourcePart];

        /// <summary>
        /// Возвращает индекс начальной (Source) связи для указанной связи.
        /// </summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="link">Связь представленная списком, состоящим из её адреса и
        ↪  содержимого.</param>
        /// <returns>Индекс начальной связи для указанной связи.</returns>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static TLink GetSource<TLink>(this ILinks<TLink> links, IList<TLink> link) =>
        ↪  link[links.Constants.SourcePart];
        /// <summary>
        /// Возвращает индекс конечной (Target) связи для указанной связи.
        /// </summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="link">Индекс связи.</param>
        /// <returns>Индекс конечной связи для указанной связи.</returns>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static TLink GetTarget<TLink>(this ILinks<TLink> links, TLink link) =>
         ↪  links.GetLink(link)[links.Constants.TargetPart];

        /// <summary>
        /// Возвращает индекс конечной (Target) связи для указанной связи.
        /// </summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="link">Связь представленная списком, состоящим из её адреса и
         ↪  содержимого.</param>
        /// <returns>Индекс конечной связи для указанной связи.</returns>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static TLink GetTarget<TLink>(this ILinks<TLink> links, IList<TLink> link) =>
         ↪  link[links.Constants.TargetPart];

        /// <summary>
        /// Выполняет проход по всем связям, соответствующим шаблону, вызывая обработчик
         ↪  (handler) для каждой подходящей связи.
        /// </summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="handler">Обработчик каждой подходящей связи.</param>
        /// <param name="restrictions">Ограничения на содержимое связей. Каждое ограничение
         ↪  может иметь значения: Constants.Null - 0-я связь, обозначающая ссылку на пустоту,
         ↪  Any - отсутствие ограничения, 1..∞ конкретный адрес связи.</param>
        /// <returns>True, в случае если проход по связям не был прерван и False в обратном
         ↪  случае.</returns>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static bool Each<TLink>(this ILinks<TLink> links, Func<IList<TLink>, TLink>
         ↪  handler, params TLink[] restrictions)
            => EqualityComparer<TLink>.Default.Equals(links.Each(handler, restrictions),
             ↪  links.Constants.Continue);

        /// <summary>
        /// Выполняет проход по всем связям, соответствующим шаблону, вызывая обработчик
         ↪  (handler) для каждой подходящей связи.
        /// </summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="source">Значение, определяющее соответствующие шаблону связи.
         ↪  (Constants.Null - 0-я связь, обозначающая ссылку на пустоту в качестве начала,
         ↪  Constants.Any - любое начало, 1..∞ конкретное начало)</param>
        /// <param name="target">Значение, определяющее соответствующие шаблону связи.
         ↪  (Constants.Null - 0-я связь, обозначающая ссылку на пустоту в качестве конца,
         ↪  Constants.Any - любой конец, 1..∞ конкретный конец)</param>
        /// <param name="handler">Обработчик каждой подходящей связи.</param>
        /// <returns>True, в случае если проход по связям не был прерван и False в обратном
         ↪  случае.</returns>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static bool Each<TLink>(this ILinks<TLink> links, TLink source, TLink target,
         ↪  Func<TLink, bool> handler)
        {
            var constants = links.Constants;
            return links.Each(link => handler(link[constants.IndexPart]) ? constants.Continue :
             ↪  constants.Break, constants.Any, source, target);
        }

        /// <summary>
        /// Выполняет проход по всем связям, соответствующим шаблону, вызывая обработчик
         ↪  (handler) для каждой подходящей связи.
        /// </summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="source">Значение, определяющее соответствующие шаблону связи.
         ↪  (Constants.Null - 0-я связь, обозначающая ссылку на пустоту в качестве начала,
         ↪  Constants.Any - любое начало, 1..∞ конкретное начало)</param>
        /// <param name="target">Значение, определяющее соответствующие шаблону связи.
         ↪  (Constants.Null - 0-я связь, обозначающая ссылку на пустоту в качестве конца,
         ↪  Constants.Any - любой конец, 1..∞ конкретный конец)</param>
        /// <param name="handler">Обработчик каждой подходящей связи.</param>
        /// <returns>True, в случае если проход по связям не был прерван и False в обратном
         ↪  случае.</returns>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static bool Each<TLink>(this ILinks<TLink> links, TLink source, TLink target,
         ↪  Func<IList<TLink>, TLink> handler)
        {
            var constants = links.Constants;
            return links.Each(handler, constants.Any, source, target);
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static IList<IList<TLink>> All<TLink>(this ILinks<TLink> links, params TLink[]
         ↪  restrictions)
        {
            long arraySize = (Integer<TLink>)links.Count(restrictions);
            var array = new IList<TLink>[arraySize];
            if (arraySize > 0)
            {
                var filler = new ArrayFiller<IList<TLink>, TLink>(array,
                 ↪  links.Constants.Continue);
                links.Each(filler.AddAndReturnConstant, restrictions);
            }
            return array;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static IList<TLink> AllIndices<TLink>(this ILinks<TLink> links, params TLink[]
         ↪  restrictions)
        {
            long arraySize = (Integer<TLink>)links.Count(restrictions);
            var array = new TLink[arraySize];
            if (arraySize > 0)
            {
                var filler = new ArrayFiller<TLink, TLink>(array, links.Constants.Continue);
                links.Each(filler.AddFirstAndReturnConstant, restrictions);
            }
            return array;
        }

        /// <summary>
        /// Возвращает значение, определяющее существует ли связь с указанными началом и концом
         ↪  в хранилище связей.
        /// </summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="source">Начало связи.</param>
        /// <param name="target">Конец связи.</param>
        /// <returns>Значение, определяющее существует ли связь.</returns>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static bool Exists<TLink>(this ILinks<TLink> links, TLink source, TLink target)
         ↪  => Comparer<TLink>.Default.Compare(links.Count(links.Constants.Any, source, target),
         ↪  default) > 0;

        #region Ensure
        // TODO: May be move to EnsureExtensions or make it both there and here

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static void EnsureInnerReferenceExists<TLink>(this ILinks<TLink> links, TLink
         ↪  reference, string argumentName)
        {
            if (links.IsInnerReference(reference) && !links.Exists(reference))
            {
                throw new ArgumentLinkDoesNotExistsException<TLink>(reference, argumentName);
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static void EnsureInnerReferenceExists<TLink>(this ILinks<TLink> links,
         ↪  IList<TLink> restrictions, string argumentName)
        {
            for (int i = 0; i < restrictions.Count; i++)
            {
                links.EnsureInnerReferenceExists(restrictions[i], argumentName);
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static void EnsureLinkIsAnyOrExists<TLink>(this ILinks<TLink> links, IList<TLink>
         ↪  restrictions)
        {
            for (int i = 0; i < restrictions.Count; i++)
            {
                links.EnsureLinkIsAnyOrExists(restrictions[i], nameof(restrictions));
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static void EnsureLinkIsAnyOrExists<TLink>(this ILinks<TLink> links, TLink link,
         ↪  string argumentName)
        {
            var equalityComparer = EqualityComparer<TLink>.Default;
            if (!equalityComparer.Equals(link, links.Constants.Any) && !links.Exists(link))
            {
                throw new ArgumentLinkDoesNotExistsException<TLink>(link, argumentName);
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static void EnsureLinkIsItselfOrExists<TLink>(this ILinks<TLink> links, TLink
         ↪  link, string argumentName)
        {
            var equalityComparer = EqualityComparer<TLink>.Default;
            if (!equalityComparer.Equals(link, links.Constants.Itself) && !links.Exists(link))
            {
                throw new ArgumentLinkDoesNotExistsException<TLink>(link, argumentName);
            }
        }

        /// <param name="links">Хранилище связей.</param>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static void EnsureDoesNotExists<TLink>(this ILinks<TLink> links, TLink source,
         ↪  TLink target)
        {
            if (links.Exists(source, target))
            {
                throw new LinkWithSameValueAlreadyExistsException();
            }
        }

        /// <param name="links">Хранилище связей.</param>
        public static void EnsureNoUsages<TLink>(this ILinks<TLink> links, TLink link)
        {
            if (links.HasUsages(link))
            {
                throw new ArgumentLinkHasDependenciesException<TLink>(link);
            }
        }

        /// <param name="links">Хранилище связей.</param>
        public static void EnsureCreated<TLink>(this ILinks<TLink> links, params TLink[]
         ↪  addresses) => links.EnsureCreated(links.Create, addresses);

        /// <param name="links">Хранилище связей.</param>
        public static void EnsurePointsCreated<TLink>(this ILinks<TLink> links, params TLink[]
         ↪  addresses) => links.EnsureCreated(links.CreatePoint, addresses);

        /// <param name="links">Хранилище связей.</param>
        public static void EnsureCreated<TLink>(this ILinks<TLink> links, Func<TLink> creator,
         ↪  params TLink[] addresses)
        {
            var constants = links.Constants;
            var nonExistentAddresses = new HashSet<ulong>(addresses.Where(x =>
             ↪  !links.Exists(x)).Select(x => (ulong)(Integer<TLink>)x));
            if (nonExistentAddresses.Count > 0)
            {
                var max = nonExistentAddresses.Max();
                // TODO: Эту верхнюю границу нужно разрешить переопределять (проверить
                 ↪  применяется ли эта логика)
                max = System.Math.Min(max, (Integer<TLink>)constants.MaxPossibleIndex);
                var createdLinks = new List<TLink>();
                var equalityComparer = EqualityComparer<TLink>.Default;
                TLink createdLink = creator();
                while (!equalityComparer.Equals(createdLink, (Integer<TLink>)max))
                {
                    createdLinks.Add(createdLink);
                }
                for (var i = 0; i < createdLinks.Count; i++)
                {
                    if (!nonExistentAddresses.Contains((Integer<TLink>)createdLinks[i]))
                    {
                        links.Delete(createdLinks[i]);
                    }
                }
            }
        }

        #endregion

        /// <param name="links">Хранилище связей.</param>
        public static ulong CountUsages<TLink>(this ILinks<TLink> links, TLink link)
        {
            var constants = links.Constants;
            var values = links.GetLink(link);
            ulong usagesAsSource = (Integer<TLink>)links.Count(new Link<TLink>(constants.Any,
             ↪  link, constants.Any));
            var equalityComparer = EqualityComparer<TLink>.Default;
            if (equalityComparer.Equals(values[constants.SourcePart], link))
            {
                usagesAsSource--;
            }
            ulong usagesAsTarget = (Integer<TLink>)links.Count(new Link<TLink>(constants.Any,
             ↪  constants.Any, link));
            if (equalityComparer.Equals(values[constants.TargetPart], link))
            {
                usagesAsTarget--;
            }
            return usagesAsSource + usagesAsTarget;
        }

        /// <param name="links">Хранилище связей.</param>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static bool HasUsages<TLink>(this ILinks<TLink> links, TLink link) =>
         ↪  links.CountUsages(link) > 0;

        /// <param name="links">Хранилище связей.</param>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static bool Equals<TLink>(this ILinks<TLink> links, TLink link, TLink source,
         ↪  TLink target)
        {
            var constants = links.Constants;
            var values = links.GetLink(link);
            var equalityComparer = EqualityComparer<TLink>.Default;
            return equalityComparer.Equals(values[constants.SourcePart], source) &&
             ↪  equalityComparer.Equals(values[constants.TargetPart], target);
        }

        /// <summary>
        /// Выполняет поиск связи с указанными Source (началом) и Target (концом).
        /// </summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="source">Индекс связи, которая является началом для искомой
         ↪  связи.</param>
        /// <param name="target">Индекс связи, которая является концом для искомой связи.</param>
        /// <returns>Индекс искомой связи с указанными Source (началом) и Target
         ↪  (концом).</returns>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static TLink SearchOrDefault<TLink>(this ILinks<TLink> links, TLink source, TLink
         ↪  target)
        {
            var contants = links.Constants;
            var setter = new Setter<TLink, TLink>(contants.Continue, contants.Break, default);
            links.Each(setter.SetFirstAndReturnFalse, contants.Any, source, target);
            return setter.Result;
        }

        /// <param name="links">Хранилище связей.</param>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static TLink CreatePoint<TLink>(this ILinks<TLink> links)
        {
            var link = links.Create();
            return links.Update(link, link, link);
        }

        /// <param name="links">Хранилище связей.</param>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static TLink CreateAndUpdate<TLink>(this ILinks<TLink> links, TLink source, TLink
         ↪  target) => links.Update(links.Create(), source, target);
        /// <summary>
        /// Обновляет связь с указанными началом (Source) и концом (Target)
        /// на связь с указанными началом (NewSource) и концом (NewTarget).
        /// </summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="link">Индекс обновляемой связи.</param>
        /// <param name="newSource">Индекс связи, которая является началом связи, на которую
         ↪  выполняется обновление.</param>
        /// <param name="newTarget">Индекс связи, которая является концом связи, на которую
         ↪  выполняется обновление.</param>
        /// <returns>Индекс обновлённой связи.</returns>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static TLink Update<TLink>(this ILinks<TLink> links, TLink link, TLink newSource,
         ↪  TLink newTarget) => links.Update(new Link<TLink>(link, newSource, newTarget));

        /// <summary>
        /// Обновляет связь с указанными началом (Source) и концом (Target)
        /// на связь с указанными началом (NewSource) и концом (NewTarget).
        /// </summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="restrictions">Ограничения на содержимое связей. Каждое ограничение
         ↪  может иметь значения: Constants.Null - 0-я связь, обозначающая ссылку на пустоту,
         ↪  Itself - требование установить ссылку на себя, 1..∞ конкретный адрес другой
         ↪  связи.</param>
        /// <returns>Индекс обновлённой связи.</returns>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static TLink Update<TLink>(this ILinks<TLink> links, params TLink[] restrictions)
        {
            if (restrictions.Length == 2)
            {
                return links.MergeAndDelete(restrictions[0], restrictions[1]);
            }
            if (restrictions.Length == 4)
            {
                return links.UpdateOrCreateOrGet(restrictions[0], restrictions[1],
                 ↪  restrictions[2], restrictions[3]);
            }
            else
            {
                return links.Update(restrictions);
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static IList<TLink> ResolveConstantAsSelfReference<TLink>(this ILinks<TLink>
         ↪  links, TLink constant, IList<TLink> restrictions)
        {
            var equalityComparer = EqualityComparer<TLink>.Default;
            var constants = links.Constants;
            var index = restrictions[constants.IndexPart];
            var source = restrictions[constants.SourcePart];
            var target = restrictions[constants.TargetPart];
            source = equalityComparer.Equals(source, constant) ? index : source;
            target = equalityComparer.Equals(target, constant) ? index : target;
            return new Link<TLink>(index, source, target);
        }

        /// <summary>
        /// Создаёт связь (если она не существовала), либо возвращает индекс существующей связи
         ↪  с указанными Source (началом) и Target (концом).
        /// </summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="source">Индекс связи, которая является началом на создаваемой
         ↪  связи.</param>
        /// <param name="target">Индекс связи, которая является концом для создаваемой
         ↪  связи.</param>
        /// <returns>Индекс связи, с указанным Source (началом) и Target (концом)</returns>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static TLink GetOrCreate<TLink>(this ILinks<TLink> links, TLink source, TLink
         ↪  target)
        {
            var link = links.SearchOrDefault(source, target);
            if (EqualityComparer<TLink>.Default.Equals(link, default))
            {
                link = links.CreateAndUpdate(source, target);
            }
            return link;
        }

        /// <summary>
        /// Обновляет связь с указанными началом (Source) и концом (Target)
        /// на связь с указанными началом (NewSource) и концом (NewTarget).
        /// </summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="source">Индекс связи, которая является началом обновляемой
        ↪  связи.</param>
        /// <param name="target">Индекс связи, которая является концом обновляемой связи.</param>
        /// <param name="newSource">Индекс связи, которая является началом связи, на которую
        ↪  выполняется обновление.</param>
        /// <param name="newTarget">Индекс связи, которая является концом связи, на которую
        ↪  выполняется обновление.</param>
        /// <returns>Индекс обновлённой связи.</returns>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static TLink UpdateOrCreateOrGet<TLink>(this ILinks<TLink> links, TLink source,
        ↪  TLink target, TLink newSource, TLink newTarget)
        {
            var equalityComparer = EqualityComparer<TLink>.Default;
            var link = links.SearchOrDefault(source, target);
            if (equalityComparer.Equals(link, default))
            {
                return links.CreateAndUpdate(newSource, newTarget);
            }
            if (equalityComparer.Equals(newSource, source) && equalityComparer.Equals(newTarget,
            ↪  target))
            {
                return link;
            }
            return links.Update(link, newSource, newTarget);
        }

        /// <summary>Удаляет связь с указанными началом (Source) и концом (Target).</summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="source">Индекс связи, которая является началом удаляемой связи.</param>
        /// <param name="target">Индекс связи, которая является концом удаляемой связи.</param>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static TLink DeleteIfExists<TLink>(this ILinks<TLink> links, TLink source, TLink
        ↪  target)
        {
            var link = links.SearchOrDefault(source, target);
            if (!EqualityComparer<TLink>.Default.Equals(link, default))
            {
                links.Delete(link);
                return link;
            }
            return default;
        }

        /// <summary>Удаляет несколько связей.</summary>
        /// <param name="links">Хранилище связей.</param>
        /// <param name="deletedLinks">Список адресов связей к удалению.</param>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static void DeleteMany<TLink>(this ILinks<TLink> links, IList<TLink> deletedLinks)
        {
            for (int i = 0; i < deletedLinks.Count; i++)
            {
                links.Delete(deletedLinks[i]);
            }
        }

        /// <remarks>Before execution of this method ensure that deleted link is detached (all
        ↪  values - source and target are reset to null) or it might enter into infinite
        ↪  recursion.</remarks>
        public static void DeleteAllUsages<TLink>(this ILinks<TLink> links, TLink linkIndex)
        {
            var anyConstant = links.Constants.Any;
            var usagesAsSourceQuery = new Link<TLink>(anyConstant, linkIndex, anyConstant);
            links.DeleteByQuery(usagesAsSourceQuery);
            var usagesAsTargetQuery = new Link<TLink>(anyConstant, linkIndex, anyConstant);
            links.DeleteByQuery(usagesAsTargetQuery);
        }

        public static void DeleteByQuery<TLink>(this ILinks<TLink> links, Link<TLink> query)
        {
            var count = (Integer<TLink>)links.Count(query);
```

```
                if (count > 0)
                {
                    var queryResult = new TLink[count];
                    var queryResultFiller = new ArrayFiller<TLink, TLink>(queryResult,
                     ↪  links.Constants.Continue);
                    links.Each(queryResultFiller.AddFirstAndReturnConstant, query);
                    for (var i = (long)count - 1; i >= 0; i--)
                    {
                        links.Delete(queryResult[i]);
                    }
                }
            }

            // TODO: Move to Platform.Data
            public static bool AreValuesReset<TLink>(this ILinks<TLink> links, TLink linkIndex)
            {
                var nullConstant = links.Constants.Null;
                var equalityComparer = EqualityComparer<TLink>.Default;
                var link = links.GetLink(linkIndex);
                for (int i = 1; i < link.Count; i++)
                {
                    if (!equalityComparer.Equals(link[i], nullConstant))
                    {
                        return false;
                    }
                }
                return true;
            }

            // TODO: Create a universal version of this method in Platform.Data (with using of for
             ↪  loop)
            public static void ResetValues<TLink>(this ILinks<TLink> links, TLink linkIndex)
            {
                var nullConstant = links.Constants.Null;
                var updateRequest = new Link<TLink>(linkIndex, nullConstant, nullConstant);
                links.Update(updateRequest);
            }

            // TODO: Create a universal version of this method in Platform.Data (with using of for
             ↪  loop)
            public static void EnforceResetValues<TLink>(this ILinks<TLink> links, TLink linkIndex)
            {
                if (!links.AreValuesReset(linkIndex))
                {
                    links.ResetValues(linkIndex);
                }
            }

            /// <summary>
            /// Merging two usages graphs, all children of old link moved to be children of new link
             ↪  or deleted.
            /// </summary>
            public static TLink MergeUsages<TLink>(this ILinks<TLink> links, TLink oldLinkIndex,
             ↪  TLink newLinkIndex)
            {
                var equalityComparer = EqualityComparer<TLink>.Default;
                if (!equalityComparer.Equals(oldLinkIndex, newLinkIndex))
                {
                    var constants = links.Constants;
                    var usagesAsSourceQuery = new Link<TLink>(constants.Any, oldLinkIndex,
                     ↪  constants.Any);
                    long usagesAsSourceCount = (Integer<TLink>)links.Count(usagesAsSourceQuery);
                    var usagesAsTargetQuery = new Link<TLink>(constants.Any, constants.Any,
                     ↪  oldLinkIndex);
                    long usagesAsTargetCount = (Integer<TLink>)links.Count(usagesAsTargetQuery);
                    var isStandalonePoint = Point<TLink>.IsFullPoint(links.GetLink(oldLinkIndex)) &&
                     ↪  usagesAsSourceCount == 1 && usagesAsTargetCount == 1;
                    if (!isStandalonePoint)
                    {
                        var totalUsages = usagesAsSourceCount + usagesAsTargetCount;
                        if (totalUsages > 0)
                        {
                            var usages = ArrayPool.Allocate<TLink>(totalUsages);
                            var usagesFiller = new ArrayFiller<TLink, TLink>(usages,
                             ↪  links.Constants.Continue);
                            var i = 0L;
                            if (usagesAsSourceCount > 0)
                            {
```

```
                            links.Each(usagesFiller.AddFirstAndReturnConstant, usagesAsSourceQuery);
                            for (; i < usagesAsSourceCount; i++)
                            {
                                var usage = usages[i];
                                if (!equalityComparer.Equals(usage, oldLinkIndex))
                                {
                                    links.Update(usage, newLinkIndex, links.GetTarget(usage));
                                }
                            }
                        }
                        if (usagesAsTargetCount > 0)
                        {
                            links.Each(usagesFiller.AddFirstAndReturnConstant, usagesAsTargetQuery);
                            for (; i < usages.Length; i++)
                            {
                                var usage = usages[i];
                                if (!equalityComparer.Equals(usage, oldLinkIndex))
                                {
                                    links.Update(usage, links.GetSource(usage), newLinkIndex);
                                }
                            }
                        }
                        ArrayPool.Free(usages);
                    }
                }
            }
            return newLinkIndex;
        }

        /// <summary>
        /// Replace one link with another (replaced link is deleted, children are updated or deleted).
        /// </summary>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static TLink MergeAndDelete<TLink>(this ILinks<TLink> links, TLink oldLinkIndex, TLink newLinkIndex)
        {
            var equalityComparer = EqualityComparer<TLink>.Default;
            if (!equalityComparer.Equals(oldLinkIndex, newLinkIndex))
            {
                links.MergeUsages(oldLinkIndex, newLinkIndex);
                links.Delete(oldLinkIndex);
            }
            return newLinkIndex;
        }
    }
}
```

./Platform.Data.Doublets/Incrementers/FrequencyIncrementer.cs

```
using System.Collections.Generic;
using Platform.Interfaces;

namespace Platform.Data.Doublets.Incrementers
{
    public class FrequencyIncrementer<TLink> : LinksOperatorBase<TLink>, IIncrementer<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer = EqualityComparer<TLink>.Default;

        private readonly TLink _frequencyMarker;
        private readonly TLink _unaryOne;
        private readonly IIncrementer<TLink> _unaryNumberIncrementer;

        public FrequencyIncrementer(ILinks<TLink> links, TLink frequencyMarker, TLink unaryOne, IIncrementer<TLink> unaryNumberIncrementer)
            : base(links)
        {
            _frequencyMarker = frequencyMarker;
            _unaryOne = unaryOne;
            _unaryNumberIncrementer = unaryNumberIncrementer;
        }

        public TLink Increment(TLink frequency)
        {
            if (_equalityComparer.Equals(frequency, default))
            {
                return Links.GetOrCreate(_unaryOne, _frequencyMarker);
            }
            var source = Links.GetSource(frequency);
            var incrementedSource = _unaryNumberIncrementer.Increment(source);
            return Links.GetOrCreate(incrementedSource, _frequencyMarker);
        }
    }
}
```

./Platform.Data.Doublets/Incrementers/LinkFrequencyIncrementer.cs

```
using System.Collections.Generic;
using Platform.Interfaces;

namespace Platform.Data.Doublets.Incrementers
{
    public class LinkFrequencyIncrementer<TLink> : LinksOperatorBase<TLink>,
     ↪  IIncrementer<IList<TLink>>
    {
        private readonly IPropertyOperator<TLink, TLink> _frequencyPropertyOperator;
        private readonly IIncrementer<TLink> _frequencyIncrementer;

        public LinkFrequencyIncrementer(ILinks<TLink> links, IPropertyOperator<TLink, TLink>
         ↪  frequencyPropertyOperator, IIncrementer<TLink> frequencyIncrementer)
            : base(links)
        {
            _frequencyPropertyOperator = frequencyPropertyOperator;
            _frequencyIncrementer = frequencyIncrementer;
        }

        /// <remarks>Sequence itseft is not changed, only frequency of its doublets is
         ↪  incremented.</remarks>
        public IList<TLink> Increment(IList<TLink> sequence) // TODO: May be move to
         ↪  ILinksExtensions or make SequenceDoubletsFrequencyIncrementer
        {
            for (var i = 1; i < sequence.Count; i++)
            {
                Increment(Links.GetOrCreate(sequence[i - 1], sequence[i]));
            }
            return sequence;
        }

        public void Increment(TLink link)
        {
            var previousFrequency = _frequencyPropertyOperator.Get(link);
            var frequency = _frequencyIncrementer.Increment(previousFrequency);
            _frequencyPropertyOperator.Set(link, frequency);
        }
    }
}
```

./Platform.Data.Doublets/Incrementers/UnaryNumberIncrementer.cs

```
using System.Collections.Generic;
using Platform.Interfaces;

namespace Platform.Data.Doublets.Incrementers
{
    public class UnaryNumberIncrementer<TLink> : LinksOperatorBase<TLink>, IIncrementer<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;

        private readonly TLink _unaryOne;

        public UnaryNumberIncrementer(ILinks<TLink> links, TLink unaryOne) : base(links) =>
         ↪  _unaryOne = unaryOne;

        public TLink Increment(TLink unaryNumber)
        {
            if (_equalityComparer.Equals(unaryNumber, _unaryOne))
            {
                return Links.GetOrCreate(_unaryOne, _unaryOne);
            }
            var source = Links.GetSource(unaryNumber);
            var target = Links.GetTarget(unaryNumber);
            if (_equalityComparer.Equals(source, target))
            {
                return Links.GetOrCreate(unaryNumber, _unaryOne);
            }
            else
            {
                    return Links.GetOrCreate(source, Increment(target));
                }
            }
        }
    }
```

./Platform.Data.Doublets/ISynchronizedLinks.cs

```
using Platform.Data.Constants;

namespace Platform.Data.Doublets
{
    public interface ISynchronizedLinks<TLink> : ISynchronizedLinks<TLink, ILinks<TLink>,
     ↪  LinksCombinedConstants<TLink, TLink, int>>, ILinks<TLink>
    {
    }
}
```

./Platform.Data.Doublets/Link.cs

```
using System;
using System.Collections;
using System.Collections.Generic;
using Platform.Exceptions;
using Platform.Ranges;
using Platform.Singletons;
using Platform.Collections.Lists;
using Platform.Data.Constants;

namespace Platform.Data.Doublets
{
    /// <summary>
    /// Структура описывающая уникальную связь.
    /// </summary>
    public struct Link<TLink> : IEquatable<Link<TLink>>, IReadOnlyList<TLink>, IList<TLink>
    {
        public static readonly Link<TLink> Null = new Link<TLink>();

        private static readonly LinksCombinedConstants<bool, TLink, int> _constants =
         ↪  Default<LinksCombinedConstants<bool, TLink, int>>.Instance;
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;

        private const int Length = 3;

        public readonly TLink Index;
        public readonly TLink Source;
        public readonly TLink Target;

        public Link(params TLink[] values)
        {
            Index = values.Length > _constants.IndexPart ? values[_constants.IndexPart] :
             ↪  _constants.Null;
            Source = values.Length > _constants.SourcePart ? values[_constants.SourcePart] :
             ↪  _constants.Null;
            Target = values.Length > _constants.TargetPart ? values[_constants.TargetPart] :
             ↪  _constants.Null;
        }

        public Link(IList<TLink> values)
        {
            Index = values.Count > _constants.IndexPart ? values[_constants.IndexPart] :
             ↪  _constants.Null;
            Source = values.Count > _constants.SourcePart ? values[_constants.SourcePart] :
             ↪  _constants.Null;
            Target = values.Count > _constants.TargetPart ? values[_constants.TargetPart] :
             ↪  _constants.Null;
        }

        public Link(TLink index, TLink source, TLink target)
        {
            Index = index;
            Source = source;
            Target = target;
        }

        public Link(TLink source, TLink target)
            : this(_constants.Null, source, target)
        {
            Source = source;
            Target = target;
        }
        public static Link<TLink> Create(TLink source, TLink target) => new Link<TLink>(source,
        ↪  target);

        public override int GetHashCode() => (Index, Source, Target).GetHashCode();

        public bool IsNull() => _equalityComparer.Equals(Index, _constants.Null)
                             && _equalityComparer.Equals(Source, _constants.Null)
                             && _equalityComparer.Equals(Target, _constants.Null);

        public override bool Equals(object other) => other is Link<TLink> &&
        ↪  Equals((Link<TLink>)other);

        public bool Equals(Link<TLink> other) => _equalityComparer.Equals(Index, other.Index)
                                              && _equalityComparer.Equals(Source, other.Source)
                                              && _equalityComparer.Equals(Target, other.Target);

        public static string ToString(TLink index, TLink source, TLink target) => $"({index}:
        ↪  {source}->{target})";

        public static string ToString(TLink source, TLink target) => $"({source}->{target})";

        public static implicit operator TLink[](Link<TLink> link) => link.ToArray();

        public static implicit operator Link<TLink>(TLink[] linkArray) => new
        ↪  Link<TLink>(linkArray);

        public override string ToString() => _equalityComparer.Equals(Index, _constants.Null) ?
        ↪  ToString(Source, Target) : ToString(Index, Source, Target);

        #region IList

        public int Count => Length;

        public bool IsReadOnly => true;

        public TLink this[int index]
        {
            get
            {
                Ensure.Always.ArgumentInRange(index, new Range<int>(0, Length - 1),
                ↪  nameof(index));
                if (index == _constants.IndexPart)
                {
                    return Index;
                }
                if (index == _constants.SourcePart)
                {
                    return Source;
                }
                if (index == _constants.TargetPart)
                {
                    return Target;
                }
                throw new NotSupportedException(); // Impossible path due to
                ↪  Ensure.ArgumentInRange
            }
            set => throw new NotSupportedException();
        }

        IEnumerator IEnumerable.GetEnumerator() => GetEnumerator();

        public IEnumerator<TLink> GetEnumerator()
        {
            yield return Index;
            yield return Source;
            yield return Target;
        }

        public void Add(TLink item) => throw new NotSupportedException();

        public void Clear() => throw new NotSupportedException();

        public bool Contains(TLink item) => IndexOf(item) >= 0;

        public void CopyTo(TLink[] array, int arrayIndex)
        {
            Ensure.Always.ArgumentNotNull(array, nameof(array));
            Ensure.Always.ArgumentInRange(arrayIndex, new Range<int>(0, array.Length - 1),
            ↪  nameof(arrayIndex));
            if (arrayIndex + Length > array.Length)
            {
                throw new InvalidOperationException();
            }
            array[arrayIndex++] = Index;
            array[arrayIndex++] = Source;
            array[arrayIndex] = Target;
        }

        public bool Remove(TLink item) => Throw.A.NotSupportedExceptionAndReturn<bool>();

        public int IndexOf(TLink item)
        {
            if (_equalityComparer.Equals(Index, item))
            {
                return _constants.IndexPart;
            }
            if (_equalityComparer.Equals(Source, item))
            {
                return _constants.SourcePart;
            }
            if (_equalityComparer.Equals(Target, item))
            {
                return _constants.TargetPart;
            }
            return -1;
        }

        public void Insert(int index, TLink item) => throw new NotSupportedException();

        public void RemoveAt(int index) => throw new NotSupportedException();

        #endregion
    }
}
```

./Platform.Data.Doublets/LinkExtensions.cs

```
namespace Platform.Data.Doublets
{
    public static class LinkExtensions
    {
        public static bool IsFullPoint<TLink>(this Link<TLink> link) =>
         ↪  Point<TLink>.IsFullPoint(link);
        public static bool IsPartialPoint<TLink>(this Link<TLink> link) =>
         ↪  Point<TLink>.IsPartialPoint(link);
    }
}
```

./Platform.Data.Doublets/LinksOperatorBase.cs

```
namespace Platform.Data.Doublets
{
    public abstract class LinksOperatorBase<TLink>
    {
        public ILinks<TLink> Links { get; }
        protected LinksOperatorBase(ILinks<TLink> links) => Links = links;
    }
}
```

./Platform.Data.Doublets/PropertyOperators/PropertiesOperator.cs

```
using System.Linq;
using System.Collections.Generic;
using Platform.Interfaces;

namespace Platform.Data.Doublets.PropertyOperators
{
    public class PropertiesOperator<TLink> : LinksOperatorBase<TLink>,
     ↪  IPropertiesOperator<TLink, TLink, TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;

        public PropertiesOperator(ILinks<TLink> links) : base(links) { }

        public TLink GetValue(TLink @object, TLink property)
        {
            var objectProperty = Links.SearchOrDefault(@object, property);
            if (_equalityComparer.Equals(objectProperty, default))
            {
                return default;
            }
            var valueLink = Links.All(Links.Constants.Any, objectProperty).SingleOrDefault();
            if (valueLink == null)
            {
                return default;
            }
            return Links.GetTarget(valueLink[Links.Constants.IndexPart]);
        }

        public void SetValue(TLink @object, TLink property, TLink value)
        {
            var objectProperty = Links.GetOrCreate(@object, property);
            Links.DeleteMany(Links.AllIndices(Links.Constants.Any, objectProperty));
            Links.GetOrCreate(objectProperty, value);
        }
    }
}
```

./Platform.Data.Doublets/PropertyOperators/PropertyOperator.cs

```
using System.Collections.Generic;
using Platform.Interfaces;

namespace Platform.Data.Doublets.PropertyOperators
{
    public class PropertyOperator<TLink> : LinksOperatorBase<TLink>, IPropertyOperator<TLink,
     ↪  TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;

        private readonly TLink _propertyMarker;
        private readonly TLink _propertyValueMarker;

        public PropertyOperator(ILinks<TLink> links, TLink propertyMarker, TLink
         ↪  propertyValueMarker) : base(links)
        {
            _propertyMarker = propertyMarker;
            _propertyValueMarker = propertyValueMarker;
        }

        public TLink Get(TLink link)
        {
            var property = Links.SearchOrDefault(link, _propertyMarker);
            var container = GetContainer(property);
            var value = GetValue(container);
            return value;
        }

        private TLink GetContainer(TLink property)
        {
            var valueContainer = default(TLink);
            if (_equalityComparer.Equals(property, default))
            {
                return valueContainer;
            }
            var constants = Links.Constants;
            var countinueConstant = constants.Continue;
            var breakConstant = constants.Break;
            var anyConstant = constants.Any;
            var query = new Link<TLink>(anyConstant, property, anyConstant);
            Links.Each(candidate =>
            {
                var candidateTarget = Links.GetTarget(candidate);
                var valueTarget = Links.GetTarget(candidateTarget);
                if (_equalityComparer.Equals(valueTarget, _propertyValueMarker))
                {
                    valueContainer = Links.GetIndex(candidate);
                    return breakConstant;
                }
                return countinueConstant;
            }, query);
            return valueContainer;
        }

        private TLink GetValue(TLink container) => _equalityComparer.Equals(container, default)
         ↪  ? default : Links.GetTarget(container);

        public void Set(TLink link, TLink value)
        {
            var property = Links.GetOrCreate(link, _propertyMarker);
```

```
                var container = GetContainer(property);
                if (_equalityComparer.Equals(container, default))
                {
                    Links.GetOrCreate(property, value);
                }
                else
                {
                    Links.Update(container, property, value);
                }
            }
        }
    }
```

./Platform.Data.Doublets/ResizableDirectMemory/ResizableDirectMemoryLinks.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using System.Runtime.InteropServices;
using Platform.Disposables;
using Platform.Singletons;
using Platform.Collections.Arrays;
using Platform.Numbers;
using Platform.Unsafe;
using Platform.Memory;
using Platform.Data.Exceptions;
using Platform.Data.Constants;
using static Platform.Numbers.Arithmetic;

#pragma warning disable 0649
#pragma warning disable 169
#pragma warning disable 618

// ReSharper disable StaticMemberInGenericType
// ReSharper disable BuiltInTypeReferenceStyle
// ReSharper disable MemberCanBePrivate.Local
// ReSharper disable UnusedMember.Local

namespace Platform.Data.Doublets.ResizableDirectMemory
{
    public partial class ResizableDirectMemoryLinks<TLink> : DisposableBase, ILinks<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;
        private static readonly Comparer<TLink> _comparer = Comparer<TLink>.Default;

        /// <summary>Возвращает размер одной связи в байтах.</summary>
        public static readonly int LinkSizeInBytes = Structure<Link>.Size;

        public static readonly int LinkHeaderSizeInBytes = Structure<LinksHeader>.Size;

        public static readonly long DefaultLinksSizeStep = LinkSizeInBytes * 1024 * 1024;

        private struct Link
        {
            public static readonly int SourceOffset = Marshal.OffsetOf(typeof(Link),
             ↪  nameof(Source)).ToInt32();
            public static readonly int TargetOffset = Marshal.OffsetOf(typeof(Link),
             ↪  nameof(Target)).ToInt32();
            public static readonly int LeftAsSourceOffset = Marshal.OffsetOf(typeof(Link),
             ↪  nameof(LeftAsSource)).ToInt32();
            public static readonly int RightAsSourceOffset = Marshal.OffsetOf(typeof(Link),
             ↪  nameof(RightAsSource)).ToInt32();
            public static readonly int SizeAsSourceOffset = Marshal.OffsetOf(typeof(Link),
             ↪  nameof(SizeAsSource)).ToInt32();
            public static readonly int LeftAsTargetOffset = Marshal.OffsetOf(typeof(Link),
             ↪  nameof(LeftAsTarget)).ToInt32();
            public static readonly int RightAsTargetOffset = Marshal.OffsetOf(typeof(Link),
             ↪  nameof(RightAsTarget)).ToInt32();
            public static readonly int SizeAsTargetOffset = Marshal.OffsetOf(typeof(Link),
             ↪  nameof(SizeAsTarget)).ToInt32();

            public TLink Source;
            public TLink Target;
            public TLink LeftAsSource;
            public TLink RightAsSource;
            public TLink SizeAsSource;
            public TLink LeftAsTarget;
            public TLink RightAsTarget;
            public TLink SizeAsTarget;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static TLink GetSource(IntPtr pointer) => (pointer +
            ↪  SourceOffset).GetValue<TLink>();
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static TLink GetTarget(IntPtr pointer) => (pointer +
            ↪  TargetOffset).GetValue<TLink>();
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static TLink GetLeftAsSource(IntPtr pointer) => (pointer +
            ↪  LeftAsSourceOffset).GetValue<TLink>();
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static TLink GetRightAsSource(IntPtr pointer) => (pointer +
            ↪  RightAsSourceOffset).GetValue<TLink>();
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static TLink GetSizeAsSource(IntPtr pointer) => (pointer +
            ↪  SizeAsSourceOffset).GetValue<TLink>();
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static TLink GetLeftAsTarget(IntPtr pointer) => (pointer +
            ↪  LeftAsTargetOffset).GetValue<TLink>();
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static TLink GetRightAsTarget(IntPtr pointer) => (pointer +
            ↪  RightAsTargetOffset).GetValue<TLink>();
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static TLink GetSizeAsTarget(IntPtr pointer) => (pointer +
            ↪  SizeAsTargetOffset).GetValue<TLink>();

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static void SetSource(IntPtr pointer, TLink value) => (pointer +
            ↪  SourceOffset).SetValue(value);
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static void SetTarget(IntPtr pointer, TLink value) => (pointer +
            ↪  TargetOffset).SetValue(value);
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static void SetLeftAsSource(IntPtr pointer, TLink value) => (pointer +
            ↪  LeftAsSourceOffset).SetValue(value);
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static void SetRightAsSource(IntPtr pointer, TLink value) => (pointer +
            ↪  RightAsSourceOffset).SetValue(value);
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static void SetSizeAsSource(IntPtr pointer, TLink value) => (pointer +
            ↪  SizeAsSourceOffset).SetValue(value);
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static void SetLeftAsTarget(IntPtr pointer, TLink value) => (pointer +
            ↪  LeftAsTargetOffset).SetValue(value);
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static void SetRightAsTarget(IntPtr pointer, TLink value) => (pointer +
            ↪  RightAsTargetOffset).SetValue(value);
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static void SetSizeAsTarget(IntPtr pointer, TLink value) => (pointer +
            ↪  SizeAsTargetOffset).SetValue(value);
        }

        private struct LinksHeader
        {
            public static readonly int AllocatedLinksOffset =
            ↪  Marshal.OffsetOf(typeof(LinksHeader), nameof(AllocatedLinks)).ToInt32();
            public static readonly int ReservedLinksOffset =
            ↪  Marshal.OffsetOf(typeof(LinksHeader), nameof(ReservedLinks)).ToInt32();
            public static readonly int FreeLinksOffset = Marshal.OffsetOf(typeof(LinksHeader),
            ↪  nameof(FreeLinks)).ToInt32();
            public static readonly int FirstFreeLinkOffset =
            ↪  Marshal.OffsetOf(typeof(LinksHeader), nameof(FirstFreeLink)).ToInt32();
            public static readonly int FirstAsSourceOffset =
            ↪  Marshal.OffsetOf(typeof(LinksHeader), nameof(FirstAsSource)).ToInt32();
            public static readonly int FirstAsTargetOffset =
            ↪  Marshal.OffsetOf(typeof(LinksHeader), nameof(FirstAsTarget)).ToInt32();
            public static readonly int LastFreeLinkOffset =
            ↪  Marshal.OffsetOf(typeof(LinksHeader), nameof(LastFreeLink)).ToInt32();

            public TLink AllocatedLinks;
            public TLink ReservedLinks;
            public TLink FreeLinks;
            public TLink FirstFreeLink;
            public TLink FirstAsSource;
            public TLink FirstAsTarget;
            public TLink LastFreeLink;
            public TLink Reserved8;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static TLink GetAllocatedLinks(IntPtr pointer) => (pointer +
            ↪  AllocatedLinksOffset).GetValue<TLink>();
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static TLink GetReservedLinks(IntPtr pointer) => (pointer +
            ↪  ReservedLinksOffset).GetValue<TLink>();
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static TLink GetFreeLinks(IntPtr pointer) => (pointer +
            ↪  FreeLinksOffset).GetValue<TLink>();
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static TLink GetFirstFreeLink(IntPtr pointer) => (pointer +
            ↪  FirstFreeLinkOffset).GetValue<TLink>();
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static TLink GetFirstAsSource(IntPtr pointer) => (pointer +
            ↪  FirstAsSourceOffset).GetValue<TLink>();
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static TLink GetFirstAsTarget(IntPtr pointer) => (pointer +
            ↪  FirstAsTargetOffset).GetValue<TLink>();
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static TLink GetLastFreeLink(IntPtr pointer) => (pointer +
            ↪  LastFreeLinkOffset).GetValue<TLink>();

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static IntPtr GetFirstAsSourcePointer(IntPtr pointer) => pointer +
            ↪  FirstAsSourceOffset;
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static IntPtr GetFirstAsTargetPointer(IntPtr pointer) => pointer +
            ↪  FirstAsTargetOffset;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static void SetAllocatedLinks(IntPtr pointer, TLink value) => (pointer +
            ↪  AllocatedLinksOffset).SetValue(value);
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static void SetReservedLinks(IntPtr pointer, TLink value) => (pointer +
            ↪  ReservedLinksOffset).SetValue(value);
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static void SetFreeLinks(IntPtr pointer, TLink value) => (pointer +
            ↪  FreeLinksOffset).SetValue(value);
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static void SetFirstFreeLink(IntPtr pointer, TLink value) => (pointer +
            ↪  FirstFreeLinkOffset).SetValue(value);
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static void SetFirstAsSource(IntPtr pointer, TLink value) => (pointer +
            ↪  FirstAsSourceOffset).SetValue(value);
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static void SetFirstAsTarget(IntPtr pointer, TLink value) => (pointer +
            ↪  FirstAsTargetOffset).SetValue(value);
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public static void SetLastFreeLink(IntPtr pointer, TLink value) => (pointer +
            ↪  LastFreeLinkOffset).SetValue(value);
        }

        private readonly long _memoryReservationStep;

        private readonly IResizableDirectMemory _memory;
        private IntPtr _header;
        private IntPtr _links;

        private LinksTargetsTreeMethods _targetsTreeMethods;
        private LinksSourcesTreeMethods _sourcesTreeMethods;

        // TODO: Возможно чтобы гарантированно проверять на то, является ли связь удалённой,
        ↪  нужно использовать не список а дерево, так как так можно быстрее проверить на
        ↪  наличие связи внутри
        private UnusedLinksListMethods _unusedLinksListMethods;

        /// <summary>
        /// Возвращает общее число связей находящихся в хранилище.
        /// </summary>
        private TLink Total => Subtract(LinksHeader.GetAllocatedLinks(_header),
        ↪  LinksHeader.GetFreeLinks(_header));

        public LinksCombinedConstants<TLink, TLink, int> Constants { get; }

        public ResizableDirectMemoryLinks(string address)
            : this(address, DefaultLinksSizeStep)
        {
        }

        /// <summary>
        /// Создаёт экземпляр базы данных Links в файле по указанному адресу, с указанным
        ↪  минимальным шагом расширения базы данных.
        /// </summary>
        /// <param name="address">Полный пусть к файлу базы данных.</param>
        /// <param name="memoryReservationStep">Минимальный шаг расширения базы данных в
        ↪  байтах.</param>
        public ResizableDirectMemoryLinks(string address, long memoryReservationStep)
            : this(new FileMappedResizableDirectMemory(address, memoryReservationStep),
            ↪  memoryReservationStep)
        {
        }

        public ResizableDirectMemoryLinks(IResizableDirectMemory memory)
            : this(memory, DefaultLinksSizeStep)
        {
        }

        public ResizableDirectMemoryLinks(IResizableDirectMemory memory, long
        ↪  memoryReservationStep)
        {
            Constants = Default<LinksCombinedConstants<TLink, TLink, int>>.Instance;
            _memory = memory;
            _memoryReservationStep = memoryReservationStep;
            if (memory.ReservedCapacity < memoryReservationStep)
            {
                memory.ReservedCapacity = memoryReservationStep;
            }
            SetPointers(_memory);
            // Гарантия корректности _memory.UsedCapacity относительно _header->AllocatedLinks
            _memory.UsedCapacity = ((long)(Integer<TLink>)LinksHeader.GetAllocatedLinks(_header)
            ↪  * LinkSizeInBytes) + LinkHeaderSizeInBytes;
            // Гарантия корректности _header->ReservedLinks относительно _memory.ReservedCapacity
            LinksHeader.SetReservedLinks(_header, (Integer<TLink>)((_memory.ReservedCapacity -
            ↪  LinkHeaderSizeInBytes) / LinkSizeInBytes));
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public TLink Count(IList<TLink> restrictions)
        {
            // Если нет ограничений, тогда возвращаем общее число связей находящихся в хранилище.
            if (restrictions.Count == 0)
            {
                return Total;
            }
            if (restrictions.Count == 1)
            {
                var index = restrictions[Constants.IndexPart];
                if (_equalityComparer.Equals(index, Constants.Any))
                {
                    return Total;
                }
                return Exists(index) ? Integer<TLink>.One : Integer<TLink>.Zero;
            }
            if (restrictions.Count == 2)
            {
                var index = restrictions[Constants.IndexPart];
                var value = restrictions[1];
                if (_equalityComparer.Equals(index, Constants.Any))
                {
                    if (_equalityComparer.Equals(value, Constants.Any))
                    {
                        return Total; // Any - как отсутствие ограничения
                    }
                    return Add(_sourcesTreeMethods.CountUsages(value),
                    ↪  _targetsTreeMethods.CountUsages(value));
                }
                else
                {
                    if (!Exists(index))
                    {
                        return Integer<TLink>.Zero;
                    }
                    if (_equalityComparer.Equals(value, Constants.Any))
                    {
                        return Integer<TLink>.One;
                    }
                    var storedLinkValue = GetLinkUnsafe(index);
                    if (_equalityComparer.Equals(Link.GetSource(storedLinkValue), value) ||
                        _equalityComparer.Equals(Link.GetTarget(storedLinkValue), value))
                    {
                        return Integer<TLink>.One;
                    }
                    return Integer<TLink>.Zero;
                }
            }
            if (restrictions.Count == 3)
            {
                var index = restrictions[Constants.IndexPart];
                var source = restrictions[Constants.SourcePart];
                var target = restrictions[Constants.TargetPart];

                if (_equalityComparer.Equals(index, Constants.Any))
                {
                    if (_equalityComparer.Equals(source, Constants.Any) &&
                     ↪  _equalityComparer.Equals(target, Constants.Any))
                    {
                        return Total;
                    }
                    else if (_equalityComparer.Equals(source, Constants.Any))
                    {
                        return _targetsTreeMethods.CountUsages(target);
                    }
                    else if (_equalityComparer.Equals(target, Constants.Any))
                    {
                        return _sourcesTreeMethods.CountUsages(source);
                    }
                    else //if(source != Any && target != Any)
                    {
                        // Эквивалент Exists(source, target) => Count(Any, source, target) > 0
                        var link = _sourcesTreeMethods.Search(source, target);
                        return _equalityComparer.Equals(link, Constants.Null) ?
                         ↪  Integer<TLink>.Zero : Integer<TLink>.One;
                    }
                }
                else
                {
                    if (!Exists(index))
                    {
                        return Integer<TLink>.Zero;
                    }
                    if (_equalityComparer.Equals(source, Constants.Any) &&
                     ↪  _equalityComparer.Equals(target, Constants.Any))
                    {
                        return Integer<TLink>.One;
                    }
                    var storedLinkValue = GetLinkUnsafe(index);
                    if (!_equalityComparer.Equals(source, Constants.Any) &&
                     ↪  !_equalityComparer.Equals(target, Constants.Any))
                    {
                        if (_equalityComparer.Equals(Link.GetSource(storedLinkValue), source) &&
                            _equalityComparer.Equals(Link.GetTarget(storedLinkValue), target))
                        {
                            return Integer<TLink>.One;
                        }
                        return Integer<TLink>.Zero;
                    }
                    var value = default(TLink);
                    if (_equalityComparer.Equals(source, Constants.Any))
                    {
                        value = target;
                    }
                    if (_equalityComparer.Equals(target, Constants.Any))
                    {
                        value = source;
                    }
                    if (_equalityComparer.Equals(Link.GetSource(storedLinkValue), value) ||
                        _equalityComparer.Equals(Link.GetTarget(storedLinkValue), value))
                    {
                        return Integer<TLink>.One;
                    }
                    return Integer<TLink>.Zero;
                }
            }
            throw new NotSupportedException("Другие размеры и способы ограничений не
             ↪  поддерживаются.");
```

```
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public TLink Each(Func<IList<TLink>, TLink> handler, IList<TLink> restrictions)
        {
            if (restrictions.Count == 0)
            {
                for (TLink link = Integer<TLink>.One; _comparer.Compare(link,
                ↪  (Integer<TLink>)LinksHeader.GetAllocatedLinks(_header)) <= 0; link =
                ↪  Increment(link))
                {
                    if (Exists(link) && _equalityComparer.Equals(handler(GetLinkStruct(link)),
                    ↪  Constants.Break))
                    {
                        return Constants.Break;
                    }
                }

                return Constants.Continue;
            }
            if (restrictions.Count == 1)
            {
                var index = restrictions[Constants.IndexPart];
                if (_equalityComparer.Equals(index, Constants.Any))
                {
                    return Each(handler, ArrayPool<TLink>.Empty);
                }
                if (!Exists(index))
                {
                    return Constants.Continue;
                }
                return handler(GetLinkStruct(index));
            }
            if (restrictions.Count == 2)
            {
                var index = restrictions[Constants.IndexPart];
                var value = restrictions[1];
                if (_equalityComparer.Equals(index, Constants.Any))
                {
                    if (_equalityComparer.Equals(value, Constants.Any))
                    {
                        return Each(handler, ArrayPool<TLink>.Empty);
                    }
                    if (_equalityComparer.Equals(Each(handler, new[] { index, value,
                    ↪  Constants.Any }), Constants.Break))
                    {
                        return Constants.Break;
                    }
                    return Each(handler, new[] { index, Constants.Any, value });
                }
                else
                {
                    if (!Exists(index))
                    {
                        return Constants.Continue;
                    }
                    if (_equalityComparer.Equals(value, Constants.Any))
                    {
                        return handler(GetLinkStruct(index));
                    }
                    var storedLinkValue = GetLinkUnsafe(index);
                    if (_equalityComparer.Equals(Link.GetSource(storedLinkValue), value) ||
                        _equalityComparer.Equals(Link.GetTarget(storedLinkValue), value))
                    {
                        return handler(GetLinkStruct(index));
                    }
                    return Constants.Continue;
                }
            }
            if (restrictions.Count == 3)
            {
                var index = restrictions[Constants.IndexPart];
                var source = restrictions[Constants.SourcePart];
                var target = restrictions[Constants.TargetPart];
                if (_equalityComparer.Equals(index, Constants.Any))
                {
                    if (_equalityComparer.Equals(source, Constants.Any) &&
                    ↪  _equalityComparer.Equals(target, Constants.Any))
                    {
                        return Each(handler, ArrayPool<TLink>.Empty);
                    }
                    else if (_equalityComparer.Equals(source, Constants.Any))
                    {
                        return _targetsTreeMethods.EachUsage(target, handler);
                    }
                    else if (_equalityComparer.Equals(target, Constants.Any))
                    {
                        return _sourcesTreeMethods.EachUsage(source, handler);
                    }
                    else //if(source != Any && target != Any)
                    {
                        var link = _sourcesTreeMethods.Search(source, target);
                        return _equalityComparer.Equals(link, Constants.Null) ?
                         ↪  Constants.Continue : handler(GetLinkStruct(link));
                    }
                }
                else
                {
                    if (!Exists(index))
                    {
                        return Constants.Continue;
                    }
                    if (_equalityComparer.Equals(source, Constants.Any) &&
                     ↪  _equalityComparer.Equals(target, Constants.Any))
                    {
                        return handler(GetLinkStruct(index));
                    }
                    var storedLinkValue = GetLinkUnsafe(index);
                    if (!_equalityComparer.Equals(source, Constants.Any) &&
                     ↪  !_equalityComparer.Equals(target, Constants.Any))
                    {
                        if (_equalityComparer.Equals(Link.GetSource(storedLinkValue), source) &&
                            _equalityComparer.Equals(Link.GetTarget(storedLinkValue), target))
                        {
                            return handler(GetLinkStruct(index));
                        }
                        return Constants.Continue;
                    }
                    var value = default(TLink);
                    if (_equalityComparer.Equals(source, Constants.Any))
                    {
                        value = target;
                    }
                    if (_equalityComparer.Equals(target, Constants.Any))
                    {
                        value = source;
                    }
                    if (_equalityComparer.Equals(Link.GetSource(storedLinkValue), value) ||
                        _equalityComparer.Equals(Link.GetTarget(storedLinkValue), value))
                    {
                        return handler(GetLinkStruct(index));
                    }
                    return Constants.Continue;
                }
            }
            throw new NotSupportedException("Другие размеры и способы ограничений не
             ↪  поддерживаются.");
        }

        /// <remarks>
        /// TODO: Возможно можно перемещать значения, если указан индекс, но значение существует
        ↪  в другом месте (но не в менеджере памяти, а в логике Links)
        /// </remarks>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public TLink Update(IList<TLink> values)
        {
            var linkIndex = values[Constants.IndexPart];
            var link = GetLinkUnsafe(linkIndex);
            // Будет корректно работать только в том случае, если пространство выделенной связи
             ↪  предварительно заполнено нулями
            if (!_equalityComparer.Equals(Link.GetSource(link), Constants.Null))
            {
                _sourcesTreeMethods.Detach(LinksHeader.GetFirstAsSourcePointer(_header),
                 ↪  linkIndex);
            }
            if (!_equalityComparer.Equals(Link.GetTarget(link), Constants.Null))
            {
                _targetsTreeMethods.Detach(LinksHeader.GetFirstAsTargetPointer(_header),
                 ↪  linkIndex);
            }
            Link.SetSource(link, values[Constants.SourcePart]);
            Link.SetTarget(link, values[Constants.TargetPart]);
            if (!_equalityComparer.Equals(Link.GetSource(link), Constants.Null))
            {
                _sourcesTreeMethods.Attach(LinksHeader.GetFirstAsSourcePointer(_header),
                 ↪  linkIndex);
            }
            if (!_equalityComparer.Equals(Link.GetTarget(link), Constants.Null))
            {
                _targetsTreeMethods.Attach(LinksHeader.GetFirstAsTargetPointer(_header),
                 ↪  linkIndex);
            }
            return linkIndex;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public Link<TLink> GetLinkStruct(TLink linkIndex)
        {
            var link = GetLinkUnsafe(linkIndex);
            return new Link<TLink>(linkIndex, Link.GetSource(link), Link.GetTarget(link));
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private IntPtr GetLinkUnsafe(TLink linkIndex) => _links.GetElement(LinkSizeInBytes,
         ↪  linkIndex);

        /// <remarks>
        /// TODO: Возможно нужно будет заполнение нулями, если внешнее API ими не заполняет
         ↪  пространство
        /// </remarks>
        public TLink Create()
        {
            var freeLink = LinksHeader.GetFirstFreeLink(_header);
            if (!_equalityComparer.Equals(freeLink, Constants.Null))
            {
                _unusedLinksListMethods.Detach(freeLink);
            }
            else
            {
                if (_comparer.Compare(LinksHeader.GetAllocatedLinks(_header),
                 ↪  Constants.MaxPossibleIndex) > 0)
                {
                    throw new
                     ↪  LinksLimitReachedException((Integer<TLink>)Constants.MaxPossibleIndex);
                }
                if (_comparer.Compare(LinksHeader.GetAllocatedLinks(_header),
                 ↪  Decrement(LinksHeader.GetReservedLinks(_header))) >= 0)
                {
                    _memory.ReservedCapacity += _memoryReservationStep;
                    SetPointers(_memory);
                    LinksHeader.SetReservedLinks(_header,
                     ↪  (Integer<TLink>)(_memory.ReservedCapacity / LinkSizeInBytes));
                }
                LinksHeader.SetAllocatedLinks(_header,
                 ↪  Increment(LinksHeader.GetAllocatedLinks(_header)));
                _memory.UsedCapacity += LinkSizeInBytes;
                freeLink = LinksHeader.GetAllocatedLinks(_header);
            }
            return freeLink;
        }

        public void Delete(TLink link)
        {
            if (_comparer.Compare(link, LinksHeader.GetAllocatedLinks(_header)) < 0)
            {
                _unusedLinksListMethods.AttachAsFirst(link);
            }
            else if (_equalityComparer.Equals(link, LinksHeader.GetAllocatedLinks(_header)))
            {
                LinksHeader.SetAllocatedLinks(_header,
                 ↪  Decrement(LinksHeader.GetAllocatedLinks(_header)));
                _memory.UsedCapacity -= LinkSizeInBytes;
                // Убираем все связи, находящиеся в списке свободных в конце файла, до тех пор,
                 ↪  пока не дойдём до первой существующей связи
```

```
                    // Позволяет оптимизировать количество выделенных связей (AllocatedLinks)
                    while ((_comparer.Compare(LinksHeader.GetAllocatedLinks(_header),
                    ↪   Integer<TLink>.Zero) > 0) &&
                    ↪   IsUnusedLink(LinksHeader.GetAllocatedLinks(_header)))
                    {
                        _unusedLinksListMethods.Detach(LinksHeader.GetAllocatedLinks(_header));
                        LinksHeader.SetAllocatedLinks(_header,
                        ↪   Decrement(LinksHeader.GetAllocatedLinks(_header)));
                        _memory.UsedCapacity -= LinkSizeInBytes;
                    }
                }
            }

            /// <remarks>
            /// TODO: Возможно это должно быть событием, вызываемым из IMemory, в том случае, если
            ↪   адрес реально поменялся
            ///
            /// Указатель this.links может быть в том же месте,
            /// так как 0-я связь не используется и имеет такой же размер как Header,
            /// поэтому header размещается в том же месте, что и 0-я связь
            /// </remarks>
            private void SetPointers(IDirectMemory memory)
            {
                if (memory == null)
                {
                    _links = IntPtr.Zero;
                    _header = _links;
                    _unusedLinksListMethods = null;
                    _targetsTreeMethods = null;
                    _unusedLinksListMethods = null;
                }
                else
                {
                    _links = memory.Pointer;
                    _header = _links;
                    _sourcesTreeMethods = new LinksSourcesTreeMethods(this);
                    _targetsTreeMethods = new LinksTargetsTreeMethods(this);
                    _unusedLinksListMethods = new UnusedLinksListMethods(_links, _header);
                }
            }

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            private bool Exists(TLink link)
                => (_comparer.Compare(link, Constants.MinPossibleIndex) >= 0)
                && (_comparer.Compare(link, LinksHeader.GetAllocatedLinks(_header)) <= 0)
                && !IsUnusedLink(link);

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            private bool IsUnusedLink(TLink link)
                => _equalityComparer.Equals(LinksHeader.GetFirstFreeLink(_header), link)
                || (_equalityComparer.Equals(Link.GetSizeAsSource(GetLinkUnsafe(link)),
                ↪   Constants.Null)
                && !_equalityComparer.Equals(Link.GetSource(GetLinkUnsafe(link)), Constants.Null));

            #region DisposableBase

            protected override bool AllowMultipleDisposeCalls => true;

            protected override void Dispose(bool manual, bool wasDisposed)
            {
                if (!wasDisposed)
                {
                    SetPointers(null);
                    _memory.DisposeIfPossible();
                }
            }

            #endregion
        }
    }
```

./Platform.Data.Doublets/ResizableDirectMemory/ResizableDirectMemoryLinks.ListMethods.cs

```
using System;
using Platform.Unsafe;
using Platform.Collections.Methods.Lists;

namespace Platform.Data.Doublets.ResizableDirectMemory
{
    partial class ResizableDirectMemoryLinks<TLink>
    {
        private class UnusedLinksListMethods : CircularDoublyLinkedListMethods<TLink>
        {
            private readonly IntPtr _links;
            private readonly IntPtr _header;

            public UnusedLinksListMethods(IntPtr links, IntPtr header)
            {
                _links = links;
                _header = header;
            }

            protected override TLink GetFirst() => (_header +
             ↪  LinksHeader.FirstFreeLinkOffset).GetValue<TLink>();

            protected override TLink GetLast() => (_header +
             ↪  LinksHeader.LastFreeLinkOffset).GetValue<TLink>();

            protected override TLink GetPrevious(TLink element) =>
             ↪  (_links.GetElement(LinkSizeInBytes, element) +
             ↪  Link.SourceOffset).GetValue<TLink>();

            protected override TLink GetNext(TLink element) =>
             ↪  (_links.GetElement(LinkSizeInBytes, element) +
             ↪  Link.TargetOffset).GetValue<TLink>();

            protected override TLink GetSize() => (_header +
             ↪  LinksHeader.FreeLinksOffset).GetValue<TLink>();

            protected override void SetFirst(TLink element) => (_header +
             ↪  LinksHeader.FirstFreeLinkOffset).SetValue(element);

            protected override void SetLast(TLink element) => (_header +
             ↪  LinksHeader.LastFreeLinkOffset).SetValue(element);

            protected override void SetPrevious(TLink element, TLink previous) =>
             ↪  (_links.GetElement(LinkSizeInBytes, element) +
             ↪  Link.SourceOffset).SetValue(previous);

            protected override void SetNext(TLink element, TLink next) =>
             ↪  (_links.GetElement(LinkSizeInBytes, element) + Link.TargetOffset).SetValue(next);

            protected override void SetSize(TLink size) => (_header +
             ↪  LinksHeader.FreeLinksOffset).SetValue(size);
        }
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/ResizableDirectMemoryLinks.TreeMethods.cs

```
using System;
using System.Text;
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Numbers;
using Platform.Unsafe;
using Platform.Collections.Methods.Trees;
using Platform.Data.Constants;

namespace Platform.Data.Doublets.ResizableDirectMemory
{
    partial class ResizableDirectMemoryLinks<TLink>
    {
        private abstract class LinksTreeMethodsBase :
         ↪  SizedAndThreadedAVLBalancedTreeMethods<TLink>
        {
            private readonly ResizableDirectMemoryLinks<TLink> _memory;
            private readonly LinksCombinedConstants<TLink, TLink, int> _constants;
            protected readonly IntPtr Links;
            protected readonly IntPtr Header;

            protected LinksTreeMethodsBase(ResizableDirectMemoryLinks<TLink> memory)
            {
                Links = memory._links;
                Header = memory._header;
                _memory = memory;
                _constants = memory.Constants;
            }

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected abstract TLink GetTreeRoot();

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected abstract TLink GetBasePartValue(TLink link);

            public TLink this[TLink index]
            {
                get
                {
                    var root = GetTreeRoot();
                    if (GreaterOrEqualThan(index, GetSize(root)))
                    {
                        return GetZero();
                    }
                    while (!EqualToZero(root))
                    {
                        var left = GetLeftOrDefault(root);
                        var leftSize = GetSizeOrZero(left);
                        if (LessThan(index, leftSize))
                        {
                            root = left;
                            continue;
                        }
                        if (IsEquals(index, leftSize))
                        {
                            return root;
                        }
                        root = GetRightOrDefault(root);
                        index = Subtract(index, Increment(leftSize));
                    }
                    return GetZero(); // TODO: Impossible situation exception (only if tree
                    ↪  structure broken)
                }
            }

            // TODO: Return indices range instead of references count
            public TLink CountUsages(TLink link)
            {
                var root = GetTreeRoot();
                var total = GetSize(root);
                var totalRightIgnore = GetZero();
                while (!EqualToZero(root))
                {
                    var @base = GetBasePartValue(root);
                    if (LessOrEqualThan(@base, link))
                    {
                        root = GetRightOrDefault(root);
                    }
                    else
                    {
                        totalRightIgnore = Add(totalRightIgnore, Increment(GetRightSize(root)));
                        root = GetLeftOrDefault(root);
                    }
                }
                root = GetTreeRoot();
                var totalLeftIgnore = GetZero();
                while (!EqualToZero(root))
                {
                    var @base = GetBasePartValue(root);
                    if (GreaterOrEqualThan(@base, link))
                    {
                        root = GetLeftOrDefault(root);
                    }
                    else
                    {
                        totalLeftIgnore = Add(totalLeftIgnore, Increment(GetLeftSize(root)));

                        root = GetRightOrDefault(root);
                    }
                }
                return Subtract(Subtract(total, totalRightIgnore), totalLeftIgnore);
            }

            public TLink EachUsage(TLink link, Func<IList<TLink>, TLink> handler)
            {
                var root = GetTreeRoot();
                if (EqualToZero(root))
                {
                    return _constants.Continue;
                }
                TLink first = GetZero(), current = root;
                while (!EqualToZero(current))
                {
                    var @base = GetBasePartValue(current);
                    if (GreaterOrEqualThan(@base, link))
                    {
                        if (IsEquals(@base, link))
                        {
                            first = current;
                        }
                        current = GetLeftOrDefault(current);
                    }
                    else
                    {
                        current = GetRightOrDefault(current);
                    }
                }
                if (!EqualToZero(first))
                {
                    current = first;
                    while (true)
                    {
                        if (IsEquals(handler(_memory.GetLinkStruct(current)), _constants.Break))
                        {
                            return _constants.Break;
                        }
                        current = GetNext(current);
                        if (EqualToZero(current) || !IsEquals(GetBasePartValue(current), link))
                        {
                            break;
                        }
                    }
                }
                return _constants.Continue;
            }

            protected override void PrintNodeValue(TLink node, StringBuilder sb)
            {
                sb.Append(' ');
                sb.Append((Links.GetElement(LinkSizeInBytes, node) +
                ↪  Link.SourceOffset).GetValue<TLink>());
                sb.Append('-');
                sb.Append('>');
                sb.Append((Links.GetElement(LinkSizeInBytes, node) +
                ↪  Link.TargetOffset).GetValue<TLink>());
            }
        }

        private class LinksSourcesTreeMethods : LinksTreeMethodsBase
        {
            public LinksSourcesTreeMethods(ResizableDirectMemoryLinks<TLink> memory)
                : base(memory)
            {
            }

            protected override IntPtr GetLeftPointer(TLink node) =>
            ↪  Links.GetElement(LinkSizeInBytes, node) + Link.LeftAsSourceOffset;

            protected override IntPtr GetRightPointer(TLink node) =>
            ↪  Links.GetElement(LinkSizeInBytes, node) + Link.RightAsSourceOffset;

            protected override TLink GetLeftValue(TLink node) =>
            ↪  (Links.GetElement(LinkSizeInBytes, node) +
            ↪  Link.LeftAsSourceOffset).GetValue<TLink>();

            protected override TLink GetRightValue(TLink node) =>
            ↪  (Links.GetElement(LinkSizeInBytes, node) +
            ↪  Link.RightAsSourceOffset).GetValue<TLink>();

            protected override TLink GetSize(TLink node)
            {
                var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
                ↪  Link.SizeAsSourceOffset).GetValue<TLink>();
                return Bit.PartialRead(previousValue, 5, -5);
            }

        protected override void SetLeft(TLink node, TLink left) =>
        ↪  (Links.GetElement(LinkSizeInBytes, node) +
        ↪  Link.LeftAsSourceOffset).SetValue(left);

        protected override void SetRight(TLink node, TLink right) =>
        ↪  (Links.GetElement(LinkSizeInBytes, node) +
        ↪  Link.RightAsSourceOffset).SetValue(right);

        protected override void SetSize(TLink node, TLink size)
        {
            var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
            ↪  Link.SizeAsSourceOffset).GetValue<TLink>();
            (Links.GetElement(LinkSizeInBytes, node) +
            ↪  Link.SizeAsSourceOffset).SetValue(Bit.PartialWrite(previousValue, size, 5,
            ↪  -5));
        }

        protected override bool GetLeftIsChild(TLink node)
        {
            var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
            ↪  Link.SizeAsSourceOffset).GetValue<TLink>();
            return (Integer<TLink>)Bit.PartialRead(previousValue, 4, 1);
        }

        protected override void SetLeftIsChild(TLink node, bool value)
        {
            var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
            ↪  Link.SizeAsSourceOffset).GetValue<TLink>();
            var modified = Bit.PartialWrite(previousValue, (TLink)(Integer<TLink>)value, 4,
            ↪  1);
            (Links.GetElement(LinkSizeInBytes, node) +
            ↪  Link.SizeAsSourceOffset).SetValue(modified);
        }

        protected override bool GetRightIsChild(TLink node)
        {
            var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
            ↪  Link.SizeAsSourceOffset).GetValue<TLink>();
            return (Integer<TLink>)Bit.PartialRead(previousValue, 3, 1);
        }

        protected override void SetRightIsChild(TLink node, bool value)
        {
            var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
            ↪  Link.SizeAsSourceOffset).GetValue<TLink>();
            var modified = Bit.PartialWrite(previousValue, (TLink)(Integer<TLink>)value, 3,
            ↪  1);
            (Links.GetElement(LinkSizeInBytes, node) +
            ↪  Link.SizeAsSourceOffset).SetValue(modified);
        }

        protected override sbyte GetBalance(TLink node)
        {
            var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
            ↪  Link.SizeAsSourceOffset).GetValue<TLink>();
            var value = (ulong)(Integer<TLink>)Bit.PartialRead(previousValue, 0, 3);
            var unpackedValue = (sbyte)((value & 4) > 0 ? ((value & 4) << 5) | value & 3 |
            ↪  124 : value & 3);
            return unpackedValue;
        }

        protected override void SetBalance(TLink node, sbyte value)
        {
            var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
            ↪  Link.SizeAsSourceOffset).GetValue<TLink>();
            var packagedValue = (TLink)(Integer<TLink>)((((byte)value >> 5) & 4) | value &
            ↪  3);
            var modified = Bit.PartialWrite(previousValue, packagedValue, 0, 3);
            (Links.GetElement(LinkSizeInBytes, node) +
            ↪  Link.SizeAsSourceOffset).SetValue(modified);
        }

        protected override bool FirstIsToTheLeftOfSecond(TLink first, TLink second)
        {
            var firstSource = (Links.GetElement(LinkSizeInBytes, first) +
            ↪  Link.SourceOffset).GetValue<TLink>();
```

```
                var secondSource = (Links.GetElement(LinkSizeInBytes, second) +
                 ↪  Link.SourceOffset).GetValue<TLink>();
                return LessThan(firstSource, secondSource) ||
                       (IsEquals(firstSource, secondSource) &&
                        ↪  LessThan((Links.GetElement(LinkSizeInBytes, first) +
                        ↪  Link.TargetOffset).GetValue<TLink>(),
                        ↪  (Links.GetElement(LinkSizeInBytes, second) +
                        ↪  Link.TargetOffset).GetValue<TLink>()));
            }

            protected override bool FirstIsToTheRightOfSecond(TLink first, TLink second)
            {
                var firstSource = (Links.GetElement(LinkSizeInBytes, first) +
                 ↪  Link.SourceOffset).GetValue<TLink>();
                var secondSource = (Links.GetElement(LinkSizeInBytes, second) +
                 ↪  Link.SourceOffset).GetValue<TLink>();
                return GreaterThan(firstSource, secondSource) ||
                       (IsEquals(firstSource, secondSource) &&
                        ↪  GreaterThan((Links.GetElement(LinkSizeInBytes, first) +
                        ↪  Link.TargetOffset).GetValue<TLink>(),
                        ↪  (Links.GetElement(LinkSizeInBytes, second) +
                        ↪  Link.TargetOffset).GetValue<TLink>()));
            }

            protected override TLink GetTreeRoot() => (Header +
             ↪  LinksHeader.FirstAsSourceOffset).GetValue<TLink>();

            protected override TLink GetBasePartValue(TLink link) =>
             ↪  (Links.GetElement(LinkSizeInBytes, link) + Link.SourceOffset).GetValue<TLink>();

            /// <summary>
            /// Выполняет поиск и возвращает индекс связи с указанными Source (началом) и Target
             ↪  (концом)
            /// по дереву (индексу) связей, отсортированному по Source, а затем по Target.
            /// </summary>
            /// <param name="source">Индекс связи, которая является началом на искомой
             ↪  связи.</param>
            /// <param name="target">Индекс связи, которая является концом на искомой
             ↪  связи.</param>
            /// <returns>Индекс искомой связи.</returns>
            public TLink Search(TLink source, TLink target)
            {
                var root = GetTreeRoot();
                while (!EqualToZero(root))
                {
                    var rootSource = (Links.GetElement(LinkSizeInBytes, root) +
                     ↪  Link.SourceOffset).GetValue<TLink>();
                    var rootTarget = (Links.GetElement(LinkSizeInBytes, root) +
                     ↪  Link.TargetOffset).GetValue<TLink>();
                    if (FirstIsToTheLeftOfSecond(source, target, rootSource, rootTarget)) //
                     ↪  node.Key < root.Key
                    {
                        root = GetLeftOrDefault(root);
                    }
                    else if (FirstIsToTheRightOfSecond(source, target, rootSource, rootTarget))
                     ↪  // node.Key > root.Key
                    {
                        root = GetRightOrDefault(root);
                    }
                    else // node.Key == root.Key
                    {
                        return root;
                    }
                }
                return GetZero();
            }

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            private bool FirstIsToTheLeftOfSecond(TLink firstSource, TLink firstTarget, TLink
             ↪  secondSource, TLink secondTarget) => LessThan(firstSource, secondSource) ||
             ↪  (IsEquals(firstSource, secondSource) && LessThan(firstTarget, secondTarget));

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            private bool FirstIsToTheRightOfSecond(TLink firstSource, TLink firstTarget, TLink
             ↪  secondSource, TLink secondTarget) => GreaterThan(firstSource, secondSource) ||
             ↪  (IsEquals(firstSource, secondSource) && GreaterThan(firstTarget, secondTarget));
```

```
        }

        private class LinksTargetsTreeMethods : LinksTreeMethodsBase
        {
            public LinksTargetsTreeMethods(ResizableDirectMemoryLinks<TLink> memory)
                : base(memory)
            {
            }

            protected override IntPtr GetLeftPointer(TLink node) =>
             ↪  Links.GetElement(LinkSizeInBytes, node) + Link.LeftAsTargetOffset;

            protected override IntPtr GetRightPointer(TLink node) =>
             ↪  Links.GetElement(LinkSizeInBytes, node) + Link.RightAsTargetOffset;

            protected override TLink GetLeftValue(TLink node) =>
             ↪  (Links.GetElement(LinkSizeInBytes, node) +
             ↪  Link.LeftAsTargetOffset).GetValue<TLink>();

            protected override TLink GetRightValue(TLink node) =>
             ↪  (Links.GetElement(LinkSizeInBytes, node) +
             ↪  Link.RightAsTargetOffset).GetValue<TLink>();

            protected override TLink GetSize(TLink node)
            {
                var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
                 ↪  Link.SizeAsTargetOffset).GetValue<TLink>();
                return Bit.PartialRead(previousValue, 5, -5);
            }

            protected override void SetLeft(TLink node, TLink left) =>
             ↪  (Links.GetElement(LinkSizeInBytes, node) +
             ↪  Link.LeftAsTargetOffset).SetValue(left);

            protected override void SetRight(TLink node, TLink right) =>
             ↪  (Links.GetElement(LinkSizeInBytes, node) +
             ↪  Link.RightAsTargetOffset).SetValue(right);

            protected override void SetSize(TLink node, TLink size)
            {
                var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
                 ↪  Link.SizeAsTargetOffset).GetValue<TLink>();
                (Links.GetElement(LinkSizeInBytes, node) +
                 ↪  Link.SizeAsTargetOffset).SetValue(Bit.PartialWrite(previousValue, size, 5,
                 ↪  -5));
            }

            protected override bool GetLeftIsChild(TLink node)
            {
                var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
                 ↪  Link.SizeAsTargetOffset).GetValue<TLink>();
                return (Integer<TLink>)Bit.PartialRead(previousValue, 4, 1);
            }

            protected override void SetLeftIsChild(TLink node, bool value)
            {
                var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
                 ↪  Link.SizeAsTargetOffset).GetValue<TLink>();
                var modified = Bit.PartialWrite(previousValue, (TLink)(Integer<TLink>)value, 4,
                 ↪  1);
                (Links.GetElement(LinkSizeInBytes, node) +
                 ↪  Link.SizeAsTargetOffset).SetValue(modified);
            }

            protected override bool GetRightIsChild(TLink node)
            {
                var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
                 ↪  Link.SizeAsTargetOffset).GetValue<TLink>();
                return (Integer<TLink>)Bit.PartialRead(previousValue, 3, 1);
            }

            protected override void SetRightIsChild(TLink node, bool value)
            {
                var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
                 ↪  Link.SizeAsTargetOffset).GetValue<TLink>();
                var modified = Bit.PartialWrite(previousValue, (TLink)(Integer<TLink>)value, 3,
                 ↪  1);
                (Links.GetElement(LinkSizeInBytes, node) +
                ↪  Link.SizeAsTargetOffset).SetValue(modified);
            }

            protected override sbyte GetBalance(TLink node)
            {
                var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
                ↪  Link.SizeAsTargetOffset).GetValue<TLink>();
                var value = (ulong)(Integer<TLink>)Bit.PartialRead(previousValue, 0, 3);
                var unpackedValue = (sbyte)((value & 4) > 0 ? ((value & 4) << 5) | value & 3 |
                ↪  124 : value & 3);
                return unpackedValue;
            }

            protected override void SetBalance(TLink node, sbyte value)
            {
                var previousValue = (Links.GetElement(LinkSizeInBytes, node) +
                ↪  Link.SizeAsTargetOffset).GetValue<TLink>();
                var packagedValue = (TLink)(Integer<TLink>)((((byte)value >> 5) & 4) | value &
                ↪  3);
                var modified = Bit.PartialWrite(previousValue, packagedValue, 0, 3);
                (Links.GetElement(LinkSizeInBytes, node) +
                ↪  Link.SizeAsTargetOffset).SetValue(modified);
            }

            protected override bool FirstIsToTheLeftOfSecond(TLink first, TLink second)
            {
                var firstTarget = (Links.GetElement(LinkSizeInBytes, first) +
                ↪  Link.TargetOffset).GetValue<TLink>();
                var secondTarget = (Links.GetElement(LinkSizeInBytes, second) +
                ↪  Link.TargetOffset).GetValue<TLink>();
                return LessThan(firstTarget, secondTarget) ||
                       (IsEquals(firstTarget, secondTarget) &&
                       ↪  LessThan((Links.GetElement(LinkSizeInBytes, first) +
                       ↪  Link.SourceOffset).GetValue<TLink>(),
                       ↪  (Links.GetElement(LinkSizeInBytes, second) +
                       ↪  Link.SourceOffset).GetValue<TLink>()));
            }

            protected override bool FirstIsToTheRightOfSecond(TLink first, TLink second)
            {
                var firstTarget = (Links.GetElement(LinkSizeInBytes, first) +
                ↪  Link.TargetOffset).GetValue<TLink>();
                var secondTarget = (Links.GetElement(LinkSizeInBytes, second) +
                ↪  Link.TargetOffset).GetValue<TLink>();
                return GreaterThan(firstTarget, secondTarget) ||
                       (IsEquals(firstTarget, secondTarget) &&
                       ↪  GreaterThan((Links.GetElement(LinkSizeInBytes, first) +
                       ↪  Link.SourceOffset).GetValue<TLink>(),
                       ↪  (Links.GetElement(LinkSizeInBytes, second) +
                       ↪  Link.SourceOffset).GetValue<TLink>()));
            }

            protected override TLink GetTreeRoot() => (Header +
            ↪  LinksHeader.FirstAsTargetOffset).GetValue<TLink>();

            protected override TLink GetBasePartValue(TLink link) =>
            ↪  (Links.GetElement(LinkSizeInBytes, link) + Link.TargetOffset).GetValue<TLink>();
        }
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/UInt64ResizableDirectMemoryLinks.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Disposables;
using Platform.Collections.Arrays;
using Platform.Singletons;
using Platform.Memory;
using Platform.Data.Exceptions;
using Platform.Data.Constants;

//#define ENABLE_TREE_AUTO_DEBUG_AND_VALIDATION

#pragma warning disable 0649
#pragma warning disable 169

```

```
// ReSharper disable BuiltInTypeReferenceStyle

namespace Platform.Data.Doublets.ResizableDirectMemory
{
    using id = UInt64;

    public unsafe partial class UInt64ResizableDirectMemoryLinks : DisposableBase, ILinks<id>
    {
        /// <summary>Возвращает размер одной связи в байтах.</summary>
        /// <remarks>
        /// Используется только во вне класса, не рекомедуется использовать внутри.
        /// Так как во вне не обязательно будет доступен unsafe C#.
        /// </remarks>
        public static readonly int LinkSizeInBytes = sizeof(Link);

        public static readonly long DefaultLinksSizeStep = LinkSizeInBytes * 1024 * 1024;

        private struct Link
        {
            public id Source;
            public id Target;
            public id LeftAsSource;
            public id RightAsSource;
            public id SizeAsSource;
            public id LeftAsTarget;
            public id RightAsTarget;
            public id SizeAsTarget;
        }

        private struct LinksHeader
        {
            public id AllocatedLinks;
            public id ReservedLinks;
            public id FreeLinks;
            public id FirstFreeLink;
            public id FirstAsSource;
            public id FirstAsTarget;
            public id LastFreeLink;
            public id Reserved8;
        }

        private readonly long _memoryReservationStep;

        private readonly IResizableDirectMemory _memory;
        private LinksHeader* _header;
        private Link* _links;

        private LinksTargetsTreeMethods _targetsTreeMethods;
        private LinksSourcesTreeMethods _sourcesTreeMethods;

        // TODO: Возможно чтобы гарантированно проверять на то, является ли связь удалённой, нужно использовать не список а дерево, так как так можно быстрее проверить на наличие связи внутри
        private UnusedLinksListMethods _unusedLinksListMethods;

        /// <summary>
        /// Возвращает общее число связей находящихся в хранилище.
        /// </summary>
        private id Total => _header->AllocatedLinks - _header->FreeLinks;

        // TODO: Дать возможность переопределять в конструкторе
        public LinksCombinedConstants<id, id, int> Constants { get; }

        public UInt64ResizableDirectMemoryLinks(string address) : this(address, DefaultLinksSizeStep) { }

        /// <summary>
        /// Создаёт экземпляр базы данных Links в файле по указанному адресу, с указанным минимальным шагом расширения базы данных.
        /// </summary>
        /// <param name="address">Полный пусть к файлу базы данных.</param>
        /// <param name="memoryReservationStep">Минимальный шаг расширения базы данных в байтах.</param>
        public UInt64ResizableDirectMemoryLinks(string address, long memoryReservationStep) : this(new FileMappedResizableDirectMemory(address, memoryReservationStep), memoryReservationStep) { }

        public UInt64ResizableDirectMemoryLinks(IResizableDirectMemory memory) : this(memory, DefaultLinksSizeStep) { }

        public UInt64ResizableDirectMemoryLinks(IResizableDirectMemory memory, long
         ↪  memoryReservationStep)
        {
            Constants = Default<LinksCombinedConstants<id, id, int>>.Instance;
            _memory = memory;
            _memoryReservationStep = memoryReservationStep;
            if (memory.ReservedCapacity < memoryReservationStep)
            {
                memory.ReservedCapacity = memoryReservationStep;
            }
            SetPointers(_memory);
            // Гарантия корректности _memory.UsedCapacity относительно _header->AllocatedLinks
            _memory.UsedCapacity = ((long)_header->AllocatedLinks * sizeof(Link)) +
             ↪  sizeof(LinksHeader);
            // Гарантия корректности _header->ReservedLinks относительно _memory.ReservedCapacity
            _header->ReservedLinks = (id)((_memory.ReservedCapacity - sizeof(LinksHeader)) /
             ↪  sizeof(Link));
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public id Count(IList<id> restrictions)
        {
            // Если нет ограничений, тогда возвращаем общее число связей находящихся в хранилище.
            if (restrictions.Count == 0)
            {
                return Total;
            }
            if (restrictions.Count == 1)
            {
                var index = restrictions[Constants.IndexPart];
                if (index == Constants.Any)
                {
                    return Total;
                }
                return Exists(index) ? 1UL : 0UL;
            }
            if (restrictions.Count == 2)
            {
                var index = restrictions[Constants.IndexPart];
                var value = restrictions[1];
                if (index == Constants.Any)
                {
                    if (value == Constants.Any)
                    {
                        return Total; // Any - как отсутствие ограничения
                    }
                    return _sourcesTreeMethods.CountUsages(value)
                         + _targetsTreeMethods.CountUsages(value);
                }
                else
                {
                    if (!Exists(index))
                    {
                        return 0;
                    }
                    if (value == Constants.Any)
                    {
                        return 1;
                    }
                    var storedLinkValue = GetLinkUnsafe(index);
                    if (storedLinkValue->Source == value ||
                        storedLinkValue->Target == value)
                    {
                        return 1;
                    }
                    return 0;
                }
            }
            if (restrictions.Count == 3)
            {
                var index = restrictions[Constants.IndexPart];
                var source = restrictions[Constants.SourcePart];
                var target = restrictions[Constants.TargetPart];
                if (index == Constants.Any)
                {
                    if (source == Constants.Any && target == Constants.Any)
                    {
                        return Total;
                    }
                    else if (source == Constants.Any)
                    {
                        return _targetsTreeMethods.CountUsages(target);
                    }
                    else if (target == Constants.Any)
                    {
                        return _sourcesTreeMethods.CountUsages(source);
                    }
                    else //if(source != Any && target != Any)
                    {
                        // Эквивалент Exists(source, target) => Count(Any, source, target) > 0
                        var link = _sourcesTreeMethods.Search(source, target);
                        return link == Constants.Null ? 0UL : 1UL;
                    }
                }
                else
                {
                    if (!Exists(index))
                    {
                        return 0;
                    }
                    if (source == Constants.Any && target == Constants.Any)
                    {
                        return 1;
                    }
                    var storedLinkValue = GetLinkUnsafe(index);
                    if (source != Constants.Any && target != Constants.Any)
                    {
                        if (storedLinkValue->Source == source &&
                            storedLinkValue->Target == target)
                        {
                            return 1;
                        }
                        return 0;
                    }
                    var value = default(id);
                    if (source == Constants.Any)
                    {
                        value = target;
                    }
                    if (target == Constants.Any)
                    {
                        value = source;
                    }
                    if (storedLinkValue->Source == value ||
                        storedLinkValue->Target == value)
                    {
                        return 1;
                    }
                    return 0;
                }
            }
            throw new NotSupportedException("Другие размеры и способы ограничений не
             ↪  поддерживаются.");
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public id Each(Func<IList<id>, id> handler, IList<id> restrictions)
        {
            if (restrictions.Count == 0)
            {
                for (id link = 1; link <= _header->AllocatedLinks; link++)
                {
                    if (Exists(link))
                    {
                        if (handler(GetLinkStruct(link)) == Constants.Break)
                        {
                            return Constants.Break;
                        }
                    }
                }
                return Constants.Continue;
            }
            if (restrictions.Count == 1)
            {
                var index = restrictions[Constants.IndexPart];
                if (index == Constants.Any)
                {
                    return Each(handler, ArrayPool<ulong>.Empty);
                }
                if (!Exists(index))
                {
                    return Constants.Continue;
                }
                return handler(GetLinkStruct(index));
            }
            if (restrictions.Count == 2)
            {
                var index = restrictions[Constants.IndexPart];
                var value = restrictions[1];
                if (index == Constants.Any)
                {
                    if (value == Constants.Any)
                    {
                        return Each(handler, ArrayPool<ulong>.Empty);
                    }
                    if (Each(handler, new[] { index, value, Constants.Any }) == Constants.Break)
                    {
                        return Constants.Break;
                    }
                    return Each(handler, new[] { index, Constants.Any, value });
                }
                else
                {
                    if (!Exists(index))
                    {
                        return Constants.Continue;
                    }
                    if (value == Constants.Any)
                    {
                        return handler(GetLinkStruct(index));
                    }
                    var storedLinkValue = GetLinkUnsafe(index);
                    if (storedLinkValue->Source == value ||
                        storedLinkValue->Target == value)
                    {
                        return handler(GetLinkStruct(index));
                    }
                    return Constants.Continue;
                }
            }
            if (restrictions.Count == 3)
            {
                var index = restrictions[Constants.IndexPart];
                var source = restrictions[Constants.SourcePart];
                var target = restrictions[Constants.TargetPart];
                if (index == Constants.Any)
                {
                    if (source == Constants.Any && target == Constants.Any)
                    {
                        return Each(handler, ArrayPool<ulong>.Empty);
                    }
                    else if (source == Constants.Any)
                    {
                        return _targetsTreeMethods.EachReference(target, handler);
                    }
                    else if (target == Constants.Any)
                    {
                        return _sourcesTreeMethods.EachReference(source, handler);
                    }
                    else //if(source != Any && target != Any)
                    {
                        var link = _sourcesTreeMethods.Search(source, target);
                        return link == Constants.Null ? Constants.Continue :
                         ↪  handler(GetLinkStruct(link));
                    }
                }
                else
                {
                    if (!Exists(index))
                    {
                        return Constants.Continue;
                    }
                    if (source == Constants.Any && target == Constants.Any)
                    {
                        return handler(GetLinkStruct(index));
                        }
                        var storedLinkValue = GetLinkUnsafe(index);
                        if (source != Constants.Any && target != Constants.Any)
                        {
                            if (storedLinkValue->Source == source &&
                                storedLinkValue->Target == target)
                            {
                                return handler(GetLinkStruct(index));
                            }
                            return Constants.Continue;
                        }
                        var value = default(id);
                        if (source == Constants.Any)
                        {
                            value = target;
                        }
                        if (target == Constants.Any)
                        {
                            value = source;
                        }
                        if (storedLinkValue->Source == value ||
                            storedLinkValue->Target == value)
                        {
                            return handler(GetLinkStruct(index));
                        }
                        return Constants.Continue;
                    }
                }
                throw new NotSupportedException("Другие размеры и способы ограничений не
                 ↪  поддерживаются.");
            }

            /// <remarks>
            /// TODO: Возможно можно перемещать значения, если указан индекс, но значение существует
             ↪  в другом месте (но не в менеджере памяти, а в логике Links)
            /// </remarks>
            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            public id Update(IList<id> values)
            {
                var linkIndex = values[Constants.IndexPart];
                var link = GetLinkUnsafe(linkIndex);
                // Будет корректно работать только в том случае, если пространство выделенной связи
                 ↪  предварительно заполнено нулями
                if (link->Source != Constants.Null)
                {
                    _sourcesTreeMethods.Detach(new IntPtr(&_header->FirstAsSource), linkIndex);
                }
                if (link->Target != Constants.Null)
                {
                    _targetsTreeMethods.Detach(new IntPtr(&_header->FirstAsTarget), linkIndex);
                }
#if ENABLE_TREE_AUTO_DEBUG_AND_VALIDATION
                var leftTreeSize = _sourcesTreeMethods.GetSize(new IntPtr(&_header->FirstAsSource));
                var rightTreeSize = _targetsTreeMethods.GetSize(new IntPtr(&_header->FirstAsTarget));
                if (leftTreeSize != rightTreeSize)
                {
                    throw new Exception("One of the trees is broken.");
                }
#endif
                link->Source = values[Constants.SourcePart];
                link->Target = values[Constants.TargetPart];
                if (link->Source != Constants.Null)
                {
                    _sourcesTreeMethods.Attach(new IntPtr(&_header->FirstAsSource), linkIndex);
                }
                if (link->Target != Constants.Null)
                {
                    _targetsTreeMethods.Attach(new IntPtr(&_header->FirstAsTarget), linkIndex);
                }
#if ENABLE_TREE_AUTO_DEBUG_AND_VALIDATION
                leftTreeSize = _sourcesTreeMethods.GetSize(new IntPtr(&_header->FirstAsSource));
                rightTreeSize = _targetsTreeMethods.GetSize(new IntPtr(&_header->FirstAsTarget));
                if (leftTreeSize != rightTreeSize)
                {
                    throw new Exception("One of the trees is broken.");
                }
#endif
                return linkIndex;
```

```
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private IList<id> GetLinkStruct(id linkIndex)
        {
            var link = GetLinkUnsafe(linkIndex);
            return new UInt64Link(linkIndex, link->Source, link->Target);
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private Link* GetLinkUnsafe(id linkIndex) => &_links[linkIndex];

        /// <remarks>
        /// TODO: Возможно нужно будет заполнение нулями, если внешнее API ими не заполняет
        ↪  пространство
        /// </remarks>
        public id Create()
        {
            var freeLink = _header->FirstFreeLink;
            if (freeLink != Constants.Null)
            {
                _unusedLinksListMethods.Detach(freeLink);
            }
            else
            {
                if (_header->AllocatedLinks > Constants.MaxPossibleIndex)
                {
                    throw new LinksLimitReachedException(Constants.MaxPossibleIndex);
                }
                if (_header->AllocatedLinks >= _header->ReservedLinks - 1)
                {
                    _memory.ReservedCapacity += _memoryReservationStep;
                    SetPointers(_memory);
                    _header->ReservedLinks = (id)(_memory.ReservedCapacity / sizeof(Link));
                }
                _header->AllocatedLinks++;
                _memory.UsedCapacity += sizeof(Link);
                freeLink = _header->AllocatedLinks;
            }
            return freeLink;
        }

        public void Delete(id link)
        {
            if (link < _header->AllocatedLinks)
            {
                _unusedLinksListMethods.AttachAsFirst(link);
            }
            else if (link == _header->AllocatedLinks)
            {
                _header->AllocatedLinks--;
                _memory.UsedCapacity -= sizeof(Link);
                // Убираем все связи, находящиеся в списке свободных в конце файла, до тех пор,
                ↪  пока не дойдём до первой существующей связи
                // Позволяет оптимизировать количество выделенных связей (AllocatedLinks)
                while (_header->AllocatedLinks > 0 && IsUnusedLink(_header->AllocatedLinks))
                {
                    _unusedLinksListMethods.Detach(_header->AllocatedLinks);
                    _header->AllocatedLinks--;
                    _memory.UsedCapacity -= sizeof(Link);
                }
            }
        }

        /// <remarks>
        /// TODO: Возможно это должно быть событием, вызываемым из IMemory, в том случае, если
        ↪  адрес реально поменялся
        ///
        /// Указатель this.links может быть в том же месте,
        /// так как 0-я связь не используется и имеет такой же размер как Header,
        /// поэтому header размещается в том же месте, что и 0-я связь
        /// </remarks>
        private void SetPointers(IResizableDirectMemory memory)
        {
            if (memory == null)
            {
                _header = null;
                _links = null;
                _unusedLinksListMethods = null;
                _targetsTreeMethods = null;
                _unusedLinksListMethods = null;
            }
            else
            {
                _header = (LinksHeader*)(void*)memory.Pointer;
                _links = (Link*)(void*)memory.Pointer;
                _sourcesTreeMethods = new LinksSourcesTreeMethods(this);
                _targetsTreeMethods = new LinksTargetsTreeMethods(this);
                _unusedLinksListMethods = new UnusedLinksListMethods(_links, _header);
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private bool Exists(id link) => link >= Constants.MinPossibleIndex && link <=
         ↪  _header->AllocatedLinks && !IsUnusedLink(link);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private bool IsUnusedLink(id link) => _header->FirstFreeLink == link
                                          || (_links[link].SizeAsSource == Constants.Null &&
                                          ↪  _links[link].Source != Constants.Null);

        #region Disposable

        protected override bool AllowMultipleDisposeCalls => true;

        protected override void Dispose(bool manual, bool wasDisposed)
        {
            if (!wasDisposed)
            {
                SetPointers(null);
                _memory.DisposeIfPossible();
            }
        }

        #endregion
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/UInt64ResizableDirectMemoryLinks.ListMethods.cs

```
using Platform.Collections.Methods.Lists;

namespace Platform.Data.Doublets.ResizableDirectMemory
{
    unsafe partial class UInt64ResizableDirectMemoryLinks
    {
        private class UnusedLinksListMethods : CircularDoublyLinkedListMethods<ulong>
        {
            private readonly Link* _links;
            private readonly LinksHeader* _header;

            public UnusedLinksListMethods(Link* links, LinksHeader* header)
            {
                _links = links;
                _header = header;
            }

            protected override ulong GetFirst() => _header->FirstFreeLink;

            protected override ulong GetLast() => _header->LastFreeLink;

            protected override ulong GetPrevious(ulong element) => _links[element].Source;

            protected override ulong GetNext(ulong element) => _links[element].Target;

            protected override ulong GetSize() => _header->FreeLinks;

            protected override void SetFirst(ulong element) => _header->FirstFreeLink = element;

            protected override void SetLast(ulong element) => _header->LastFreeLink = element;

            protected override void SetPrevious(ulong element, ulong previous) =>
             ↪  _links[element].Source = previous;

            protected override void SetNext(ulong element, ulong next) => _links[element].Target
             ↪  = next;

            protected override void SetSize(ulong size) => _header->FreeLinks = size;
        }
    }
}
```

./Platform.Data.Doublets/ResizableDirectMemory/UInt64ResizableDirectMemoryLinks.TreeMethods.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using System.Text;
using Platform.Collections.Methods.Trees;
using Platform.Data.Constants;

namespace Platform.Data.Doublets.ResizableDirectMemory
{
    unsafe partial class UInt64ResizableDirectMemoryLinks
    {
        private abstract class LinksTreeMethodsBase :
         ↪  SizedAndThreadedAVLBalancedTreeMethods<ulong>
        {
            private readonly UInt64ResizableDirectMemoryLinks _memory;
            private readonly LinksCombinedConstants<ulong, ulong, int> _constants;
            protected readonly Link* Links;
            protected readonly LinksHeader* Header;

            protected LinksTreeMethodsBase(UInt64ResizableDirectMemoryLinks memory)
            {
                Links = memory._links;
                Header = memory._header;
                _memory = memory;
                _constants = memory.Constants;
            }

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected abstract ulong GetTreeRoot();

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected abstract ulong GetBasePartValue(ulong link);

            public ulong this[ulong index]
            {
                get
                {
                    var root = GetTreeRoot();
                    if (index >= GetSize(root))
                    {
                        return 0;
                    }
                    while (root != 0)
                    {
                        var left = GetLeftOrDefault(root);
                        var leftSize = GetSizeOrZero(left);
                        if (index < leftSize)
                        {
                            root = left;
                            continue;
                        }
                        if (index == leftSize)
                        {
                            return root;
                        }
                        root = GetRightOrDefault(root);
                        index -= leftSize + 1;
                    }
                    return 0; // TODO: Impossible situation exception (only if tree structure
                     ↪  broken)
                }
            }

            // TODO: Return indices range instead of references count
            public ulong CountUsages(ulong link)
            {
                var root = GetTreeRoot();
                var total = GetSize(root);
                var totalRightIgnore = 0UL;
                while (root != 0)
                {
                    var @base = GetBasePartValue(root);
                    if (@base <= link)
                    {
                        root = GetRightOrDefault(root);
                    }
                    else
                    {
                        totalRightIgnore += GetRightSize(root) + 1;
                        root = GetLeftOrDefault(root);
                    }
                }
                root = GetTreeRoot();
                var totalLeftIgnore = 0UL;
                while (root != 0)
                {
                    var @base = GetBasePartValue(root);
                    if (@base >= link)
                    {
                        root = GetLeftOrDefault(root);
                    }
                    else
                    {
                        totalLeftIgnore += GetLeftSize(root) + 1;
                        root = GetRightOrDefault(root);
                    }
                }
                return total - totalRightIgnore - totalLeftIgnore;
            }

            public ulong EachReference(ulong link, Func<IList<ulong>, ulong> handler)
            {
                var root = GetTreeRoot();
                if (root == 0)
                {
                    return _constants.Continue;
                }
                ulong first = 0, current = root;
                while (current != 0)
                {
                    var @base = GetBasePartValue(current);
                    if (@base >= link)
                    {
                        if (@base == link)
                        {
                            first = current;
                        }
                        current = GetLeftOrDefault(current);
                    }
                    else
                    {
                        current = GetRightOrDefault(current);
                    }
                }
                if (first != 0)
                {
                    current = first;
                    while (true)
                    {
                        if (handler(_memory.GetLinkStruct(current)) == _constants.Break)
                        {
                            return _constants.Break;
                        }
                        current = GetNext(current);
                        if (current == 0 || GetBasePartValue(current) != link)
                        {
                            break;
                        }
                    }
                }
                return _constants.Continue;
            }

            protected override void PrintNodeValue(ulong node, StringBuilder sb)
            {
                sb.Append(' ');
                sb.Append(Links[node].Source);
                sb.Append('-');
                sb.Append('>');
                sb.Append(Links[node].Target);
            }
        }

        private class LinksSourcesTreeMethods : LinksTreeMethodsBase
        {
            public LinksSourcesTreeMethods(UInt64ResizableDirectMemoryLinks memory)
```

```
                : base(memory)
            {
            }

            protected override IntPtr GetLeftPointer(ulong node) => new IntPtr(&Links[node].LeftAsSource);

            protected override IntPtr GetRightPointer(ulong node) => new IntPtr(&Links[node].RightAsSource);

            protected override ulong GetLeftValue(ulong node) => Links[node].LeftAsSource;

            protected override ulong GetRightValue(ulong node) => Links[node].RightAsSource;

            protected override ulong GetSize(ulong node)
            {
                var previousValue = Links[node].SizeAsSource;
                //return Math.PartialRead(previousValue, 5, -5);
                return (previousValue & 4294967264) >> 5;
            }

            protected override void SetLeft(ulong node, ulong left) => Links[node].LeftAsSource = left;

            protected override void SetRight(ulong node, ulong right) => Links[node].RightAsSource = right;

            protected override void SetSize(ulong node, ulong size)
            {
                var previousValue = Links[node].SizeAsSource;
                //var modified = Math.PartialWrite(previousValue, size, 5, -5);
                var modified = (previousValue & 31) | ((size & 134217727) << 5);
                Links[node].SizeAsSource = modified;
            }

            protected override bool GetLeftIsChild(ulong node)
            {
                var previousValue = Links[node].SizeAsSource;
                //return (Integer)Math.PartialRead(previousValue, 4, 1);
                return (previousValue & 16) >> 4 == 1UL;
            }

            protected override void SetLeftIsChild(ulong node, bool value)
            {
                var previousValue = Links[node].SizeAsSource;
                //var modified = Math.PartialWrite(previousValue, (ulong)(Integer)value, 4, 1);
                var modified = (previousValue & 4294967279) | ((value ? 1UL : 0UL) << 4);
                Links[node].SizeAsSource = modified;
            }

            protected override bool GetRightIsChild(ulong node)
            {
                var previousValue = Links[node].SizeAsSource;
                //return (Integer)Math.PartialRead(previousValue, 3, 1);
                return (previousValue & 8) >> 3 == 1UL;
            }

            protected override void SetRightIsChild(ulong node, bool value)
            {
                var previousValue = Links[node].SizeAsSource;
                //var modified = Math.PartialWrite(previousValue, (ulong)(Integer)value, 3, 1);
                var modified = (previousValue & 4294967287) | ((value ? 1UL : 0UL) << 3);
                Links[node].SizeAsSource = modified;
            }

            protected override sbyte GetBalance(ulong node)
            {
                var previousValue = Links[node].SizeAsSource;
                //var value = Math.PartialRead(previousValue, 0, 3);
                var value = previousValue & 7;
                var unpackedValue = (sbyte)((value & 4) > 0 ? ((value & 4) << 5) | value & 3 | 124 : value & 3);
                return unpackedValue;
            }

            protected override void SetBalance(ulong node, sbyte value)
            {
                var previousValue = Links[node].SizeAsSource;
                var packagedValue = (ulong)((((byte)value >> 5) & 4) | value & 3);
                //var modified = Math.PartialWrite(previousValue, packagedValue, 0, 3);
                var modified = (previousValue & 4294967288) | (packagedValue & 7);
                Links[node].SizeAsSource = modified;
            }

            protected override bool FirstIsToTheLeftOfSecond(ulong first, ulong second)
                => Links[first].Source < Links[second].Source ||
                  (Links[first].Source == Links[second].Source && Links[first].Target <
                  ↪  Links[second].Target);

            protected override bool FirstIsToTheRightOfSecond(ulong first, ulong second)
                => Links[first].Source > Links[second].Source ||
                  (Links[first].Source == Links[second].Source && Links[first].Target >
                  ↪  Links[second].Target);

            protected override ulong GetTreeRoot() => Header->FirstAsSource;

            protected override ulong GetBasePartValue(ulong link) => Links[link].Source;

            /// <summary>
            /// Выполняет поиск и возвращает индекс связи с указанными Source (началом) и Target
            ↪  (концом)
            /// по дереву (индексу) связей, отсортированному по Source, а затем по Target.
            /// </summary>
            /// <param name="source">Индекс связи, которая является началом на искомой
            ↪  связи.</param>
            /// <param name="target">Индекс связи, которая является концом на искомой
            ↪  связи.</param>
            /// <returns>Индекс искомой связи.</returns>
            public ulong Search(ulong source, ulong target)
            {
                var root = Header->FirstAsSource;
                while (root != 0)
                {
                    var rootSource = Links[root].Source;
                    var rootTarget = Links[root].Target;
                    if (FirstIsToTheLeftOfSecond(source, target, rootSource, rootTarget)) //
                    ↪  node.Key < root.Key
                    {
                        root = GetLeftOrDefault(root);
                    }
                    else if (FirstIsToTheRightOfSecond(source, target, rootSource, rootTarget))
                    ↪  // node.Key > root.Key
                    {
                        root = GetRightOrDefault(root);
                    }
                    else // node.Key == root.Key
                    {
                        return root;
                    }
                }
                return 0;
            }

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            private static bool FirstIsToTheLeftOfSecond(ulong firstSource, ulong firstTarget,
            ↪  ulong secondSource, ulong secondTarget)
                => firstSource < secondSource || (firstSource == secondSource && firstTarget <
                ↪  secondTarget);

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            private static bool FirstIsToTheRightOfSecond(ulong firstSource, ulong firstTarget,
            ↪  ulong secondSource, ulong secondTarget)
                => firstSource > secondSource || (firstSource == secondSource && firstTarget >
                ↪  secondTarget);

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override void ClearNode(ulong node)
            {
                Links[node].LeftAsSource = 0UL;
                Links[node].RightAsSource = 0UL;
                Links[node].SizeAsSource = 0UL;
            }

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override ulong GetZero() => 0UL;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override ulong GetOne() => 1UL;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override ulong GetTwo() => 2UL;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override bool ValueEqualToZero(IntPtr pointer) =>
            ↪  *(ulong*)pointer.ToPointer() == 0UL;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override bool EqualToZero(ulong value) => value == 0UL;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override bool IsEquals(ulong first, ulong second) => first == second;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override bool GreaterThanZero(ulong value) => value > 0UL;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override bool GreaterThan(ulong first, ulong second) => first > second;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override bool GreaterOrEqualThan(ulong first, ulong second) => first >=
            ↪  second;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override bool GreaterOrEqualThanZero(ulong value) => true; // value >= 0
            ↪  is always true for ulong

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override bool LessOrEqualThanZero(ulong value) => value == 0; // value is
            ↪  always >= 0 for ulong

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override bool LessOrEqualThan(ulong first, ulong second) => first <=
            ↪  second;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override bool LessThanZero(ulong value) => false; // value < 0 is always
            ↪  false for ulong

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override bool LessThan(ulong first, ulong second) => first < second;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override ulong Increment(ulong value) => ++value;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override ulong Decrement(ulong value) => --value;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override ulong Add(ulong first, ulong second) => first + second;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override ulong Subtract(ulong first, ulong second) => first - second;
        }

        private class LinksTargetsTreeMethods : LinksTreeMethodsBase
        {
            public LinksTargetsTreeMethods(UInt64ResizableDirectMemoryLinks memory)
                : base(memory)
            {
            }

            //protected override IntPtr GetLeft(ulong node) => new
            ↪  IntPtr(&Links[node].LeftAsTarget);

            //protected override IntPtr GetRight(ulong node) => new
            ↪  IntPtr(&Links[node].RightAsTarget);

            //protected override ulong GetSize(ulong node) => Links[node].SizeAsTarget;

            //protected override void SetLeft(ulong node, ulong left) =>
            ↪  Links[node].LeftAsTarget = left;

            //protected override void SetRight(ulong node, ulong right) =>
            ↪  Links[node].RightAsTarget = right;

```

```csharp
            //protected override void SetSize(ulong node, ulong size) =>
            ↪  Links[node].SizeAsTarget = size;

            protected override IntPtr GetLeftPointer(ulong node) => new
            ↪  IntPtr(&Links[node].LeftAsTarget);

            protected override IntPtr GetRightPointer(ulong node) => new
            ↪  IntPtr(&Links[node].RightAsTarget);

            protected override ulong GetLeftValue(ulong node) => Links[node].LeftAsTarget;

            protected override ulong GetRightValue(ulong node) => Links[node].RightAsTarget;

            protected override ulong GetSize(ulong node)
            {
                var previousValue = Links[node].SizeAsTarget;
                //return Math.PartialRead(previousValue, 5, -5);
                return (previousValue & 4294967264) >> 5;
            }

            protected override void SetLeft(ulong node, ulong left) => Links[node].LeftAsTarget
            ↪  = left;

            protected override void SetRight(ulong node, ulong right) =>
            ↪  Links[node].RightAsTarget = right;

            protected override void SetSize(ulong node, ulong size)
            {
                var previousValue = Links[node].SizeAsTarget;
                //var modified = Math.PartialWrite(previousValue, size, 5, -5);
                var modified = (previousValue & 31) | ((size & 134217727) << 5);
                Links[node].SizeAsTarget = modified;
            }

            protected override bool GetLeftIsChild(ulong node)
            {
                var previousValue = Links[node].SizeAsTarget;
                //return (Integer)Math.PartialRead(previousValue, 4, 1);
                return (previousValue & 16) >> 4 == 1UL;
                // TODO: Check if this is possible to use
                //var nodeSize = GetSize(node);
                //var left = GetLeftValue(node);
                //var leftSize = GetSizeOrZero(left);
                //return leftSize > 0 && nodeSize > leftSize;
            }

            protected override void SetLeftIsChild(ulong node, bool value)
            {
                var previousValue = Links[node].SizeAsTarget;
                //var modified = Math.PartialWrite(previousValue, (ulong)(Integer)value, 4, 1);
                var modified = (previousValue & 4294967279) | ((value ? 1UL : 0UL) << 4);
                Links[node].SizeAsTarget = modified;
            }

            protected override bool GetRightIsChild(ulong node)
            {
                var previousValue = Links[node].SizeAsTarget;
                //return (Integer)Math.PartialRead(previousValue, 3, 1);
                return (previousValue & 8) >> 3 == 1UL;
                // TODO: Check if this is possible to use
                //var nodeSize = GetSize(node);
                //var right = GetRightValue(node);
                //var rightSize = GetSizeOrZero(right);
                //return rightSize > 0 && nodeSize > rightSize;
            }

            protected override void SetRightIsChild(ulong node, bool value)
            {
                var previousValue = Links[node].SizeAsTarget;
                //var modified = Math.PartialWrite(previousValue, (ulong)(Integer)value, 3, 1);
                var modified = (previousValue & 4294967287) | ((value ? 1UL : 0UL) << 3);
                Links[node].SizeAsTarget = modified;
            }

            protected override sbyte GetBalance(ulong node)
            {
                var previousValue = Links[node].SizeAsTarget;
                //var value = Math.PartialRead(previousValue, 0, 3);
                var value = previousValue & 7;
                var unpackedValue = (sbyte)((value & 4) > 0 ? ((value & 4) << 5) | value & 3 |
                ↪  124 : value & 3);
                return unpackedValue;
            }

            protected override void SetBalance(ulong node, sbyte value)
            {
                var previousValue = Links[node].SizeAsTarget;
                var packagedValue = (ulong)((((byte)value >> 5) & 4) | value & 3);
                //var modified = Math.PartialWrite(previousValue, packagedValue, 0, 3);
                var modified = (previousValue & 4294967288) | (packagedValue & 7);
                Links[node].SizeAsTarget = modified;
            }

            protected override bool FirstIsToTheLeftOfSecond(ulong first, ulong second)
                => Links[first].Target < Links[second].Target ||
                  (Links[first].Target == Links[second].Target && Links[first].Source <
                  ↪  Links[second].Source);

            protected override bool FirstIsToTheRightOfSecond(ulong first, ulong second)
                => Links[first].Target > Links[second].Target ||
                  (Links[first].Target == Links[second].Target && Links[first].Source >
                  ↪  Links[second].Source);

            protected override ulong GetTreeRoot() => Header->FirstAsTarget;

            protected override ulong GetBasePartValue(ulong link) => Links[link].Target;

            [MethodImpl(MethodImplOptions.AggressiveInlining)]
            protected override void ClearNode(ulong node)
            {
                Links[node].LeftAsTarget = 0UL;
                Links[node].RightAsTarget = 0UL;
                Links[node].SizeAsTarget = 0UL;
            }
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Converters/BalancedVariantConverter.cs

```
using System.Collections.Generic;

namespace Platform.Data.Doublets.Sequences.Converters
{
    public class BalancedVariantConverter<TLink> : LinksListToSequenceConverterBase<TLink>
    {
        public BalancedVariantConverter(ILinks<TLink> links) : base(links) { }

        public override TLink Convert(IList<TLink> sequence)
        {
            var length = sequence.Count;
            if (length < 1)
            {
                return default;
            }
            if (length == 1)
            {
                return sequence[0];
            }
            // Make copy of next layer
            if (length > 2)
            {
                // TODO: Try to use stackalloc (which at the moment is not working with
                ↪  generics) but will be possible with Sigil
                var halvedSequence = new TLink[(length / 2) + (length % 2)];
                HalveSequence(halvedSequence, sequence, length);
                sequence = halvedSequence;
                length = halvedSequence.Length;
            }
            // Keep creating layer after layer
            while (length > 2)
            {
                HalveSequence(sequence, sequence, length);
                length = (length / 2) + (length % 2);
            }
            return Links.GetOrCreate(sequence[0], sequence[1]);
        }

        private void HalveSequence(IList<TLink> destination, IList<TLink> source, int length)
        {
            var loopedLength = length - (length % 2);
            for (var i = 0; i < loopedLength; i += 2)
            {
                destination[i / 2] = Links.GetOrCreate(source[i], source[i + 1]);
            }
            if (length > loopedLength)
            {
                destination[length / 2] = source[length - 1];
            }
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Converters/CompressingConverter.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Interfaces;
using Platform.Collections;
using Platform.Singletons;
using Platform.Numbers;
using Platform.Data.Constants;
using Platform.Data.Doublets.Sequences.Frequencies.Cache;

namespace Platform.Data.Doublets.Sequences.Converters
{
    /// <remarks>
    /// TODO: Возможно будет лучше если алгоритм будет выполняться полностью изолированно от
    ↪  Links на этапе сжатия.
    ///     А именно будет создаваться временный список пар необходимых для выполнения сжатия, в
    ↪  таком случае тип значения элемента массива может быть любым, как char так и ulong.
    ///     Как только список/словарь пар был выявлен можно разом выполнить создание всех этих
    ↪  пар, а так же разом выполнить замену.
    /// </remarks>
    public class CompressingConverter<TLink> : LinksListToSequenceConverterBase<TLink>
    {
        private static readonly LinksCombinedConstants<bool, TLink, long> _constants =
        ↪  Default<LinksCombinedConstants<bool, TLink, long>>.Instance;
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪  EqualityComparer<TLink>.Default;
        private static readonly Comparer<TLink> _comparer = Comparer<TLink>.Default;

        private readonly IConverter<IList<TLink>, TLink> _baseConverter;
        private readonly LinkFrequenciesCache<TLink> _doubletFrequenciesCache;
        private readonly TLink _minFrequencyToCompress;
        private readonly bool _doInitialFrequenciesIncrement;
        private Doublet<TLink> _maxDoublet;
        private LinkFrequency<TLink> _maxDoubletData;

        private struct HalfDoublet
        {
            public TLink Element;
            public LinkFrequency<TLink> DoubletData;

            public HalfDoublet(TLink element, LinkFrequency<TLink> doubletData)
            {
                Element = element;
                DoubletData = doubletData;
            }

            public override string ToString() => $"{Element}: ({DoubletData})";
        }

        public CompressingConverter(ILinks<TLink> links, IConverter<IList<TLink>, TLink>
        ↪  baseConverter, LinkFrequenciesCache<TLink> doubletFrequenciesCache)
            : this(links, baseConverter, doubletFrequenciesCache, Integer<TLink>.One, true)
        {
        }

        public CompressingConverter(ILinks<TLink> links, IConverter<IList<TLink>, TLink>
        ↪  baseConverter, LinkFrequenciesCache<TLink> doubletFrequenciesCache, bool
        ↪  doInitialFrequenciesIncrement)
            : this(links, baseConverter, doubletFrequenciesCache, Integer<TLink>.One,
            ↪  doInitialFrequenciesIncrement)
        {
        }

        public CompressingConverter(ILinks<TLink> links, IConverter<IList<TLink>, TLink>
         ↪  baseConverter, LinkFrequenciesCache<TLink> doubletFrequenciesCache, TLink
         ↪  minFrequencyToCompress, bool doInitialFrequenciesIncrement)
            : base(links)
        {
            _baseConverter = baseConverter;
            _doubletFrequenciesCache = doubletFrequenciesCache;
            if (_comparer.Compare(minFrequencyToCompress, Integer<TLink>.One) < 0)
            {
                minFrequencyToCompress = Integer<TLink>.One;
            }
            _minFrequencyToCompress = minFrequencyToCompress;
            _doInitialFrequenciesIncrement = doInitialFrequenciesIncrement;
            ResetMaxDoublet();
        }

        public override TLink Convert(IList<TLink> source) =>
         ↪  _baseConverter.Convert(Compress(source));

        /// <remarks>
        /// Original algorithm idea: https://en.wikipedia.org/wiki/Byte_pair_encoding .
        /// Faster version (doublets' frequencies dictionary is not recreated).
        /// </remarks>
        private IList<TLink> Compress(IList<TLink> sequence)
        {
            if (sequence.IsNullOrEmpty())
            {
                return null;
            }
            if (sequence.Count == 1)
            {
                return sequence;
            }
            if (sequence.Count == 2)
            {
                return new[] { Links.GetOrCreate(sequence[0], sequence[1]) };
            }
            // TODO: arraypool with min size (to improve cache locality) or stackallow with Sigil
            var copy = new HalfDoublet[sequence.Count];
            Doublet<TLink> doublet = default;
            for (var i = 1; i < sequence.Count; i++)
            {
                doublet.Source = sequence[i - 1];
                doublet.Target = sequence[i];
                LinkFrequency<TLink> data;
                if (_doInitialFrequenciesIncrement)
                {
                    data = _doubletFrequenciesCache.IncrementFrequency(ref doublet);
                }
                else
                {
                    data = _doubletFrequenciesCache.GetFrequency(ref doublet);
                    if (data == null)
                    {
                        throw new NotSupportedException("If you ask not to increment
                         ↪  frequencies, it is expected that all frequencies for the sequence
                         ↪  are prepared.");
                    }
                }
                copy[i - 1].Element = sequence[i - 1];
                copy[i - 1].DoubletData = data;
                UpdateMaxDoublet(ref doublet, data);
            }
            copy[sequence.Count - 1].Element = sequence[sequence.Count - 1];
            copy[sequence.Count - 1].DoubletData = new LinkFrequency<TLink>();
            if (_comparer.Compare(_maxDoubletData.Frequency, default) > 0)
            {
                var newLength = ReplaceDoublets(copy);
                sequence = new TLink[newLength];
                for (int i = 0; i < newLength; i++)
                {
                    sequence[i] = copy[i].Element;
                }
            }
            return sequence;
        }

        /// <remarks>
        /// Original algorithm idea: https://en.wikipedia.org/wiki/Byte_pair_encoding
        /// </remarks>
        private int ReplaceDoublets(HalfDoublet[] copy)
        {
            var oldLength = copy.Length;
            var newLength = copy.Length;
            while (_comparer.Compare(_maxDoubletData.Frequency, default) > 0)
            {
                var maxDoubletSource = _maxDoublet.Source;
                var maxDoubletTarget = _maxDoublet.Target;
                if (_equalityComparer.Equals(_maxDoubletData.Link, _constants.Null))
                {
                    _maxDoubletData.Link = Links.GetOrCreate(maxDoubletSource, maxDoubletTarget);
                }
                var maxDoubletReplacementLink = _maxDoubletData.Link;
                oldLength--;
                var oldLengthMinusTwo = oldLength - 1;
                // Substitute all usages
                int w = 0, r = 0; // (r == read, w == write)
                for (; r < oldLength; r++)
                {
                    if (_equalityComparer.Equals(copy[r].Element, maxDoubletSource) && _equalityComparer.Equals(copy[r + 1].Element, maxDoubletTarget))
                    {
                        if (r > 0)
                        {
                            var previous = copy[w - 1].Element;
                            copy[w - 1].DoubletData.DecrementFrequency();
                            copy[w - 1].DoubletData = _doubletFrequenciesCache.IncrementFrequency(previous, maxDoubletReplacementLink);
                        }
                        if (r < oldLengthMinusTwo)
                        {
                            var next = copy[r + 2].Element;
                            copy[r + 1].DoubletData.DecrementFrequency();
                            copy[w].DoubletData = _doubletFrequenciesCache.IncrementFrequency(maxDoubletReplacementLink, next);
                        }
                        copy[w++].Element = maxDoubletReplacementLink;
                        r++;
                        newLength--;
                    }
                    else
                    {
                        copy[w++] = copy[r];
                    }
                }
                if (w < newLength)
                {
                    copy[w] = copy[r];
                }
                oldLength = newLength;
                ResetMaxDoublet();
                UpdateMaxDoublet(copy, newLength);
            }
            return newLength;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private void ResetMaxDoublet()
        {
            _maxDoublet = new Doublet<TLink>();
            _maxDoubletData = new LinkFrequency<TLink>();
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private void UpdateMaxDoublet(HalfDoublet[] copy, int length)
        {
            Doublet<TLink> doublet = default;
            for (var i = 1; i < length; i++)
            {
                doublet.Source = copy[i - 1].Element;
                doublet.Target = copy[i].Element;
                UpdateMaxDoublet(ref doublet, copy[i - 1].DoubletData);
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private void UpdateMaxDoublet(ref Doublet<TLink> doublet, LinkFrequency<TLink> data)
        {
            var frequency = data.Frequency;
            var maxFrequency = _maxDoubletData.Frequency;
            //if (frequency > _minFrequencyToCompress && (maxFrequency < frequency ||
             ↪  (maxFrequency == frequency && doublet.Source + doublet.Target < /* gives better
             ↪  compression string data (and gives collisions quickly) */ _maxDoublet.Source +
             ↪  _maxDoublet.Target)))
            if (_comparer.Compare(frequency, _minFrequencyToCompress) > 0 &&
               (_comparer.Compare(maxFrequency, frequency) < 0 ||
                ↪  (_equalityComparer.Equals(maxFrequency, frequency) &&
                ↪  _comparer.Compare(Arithmetic.Add(doublet.Source, doublet.Target),
                ↪  Arithmetic.Add(_maxDoublet.Source, _maxDoublet.Target)) > 0))) /* gives
                ↪  better stability and better compression on sequent data and even on rundom
                ↪  numbers data (but gives collisions anyway) */
            {
                _maxDoublet = doublet;
                _maxDoubletData = data;
            }
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Converters/LinksListToSequenceConverterBase.cs

```
using System.Collections.Generic;
using Platform.Interfaces;

namespace Platform.Data.Doublets.Sequences.Converters
{
    public abstract class LinksListToSequenceConverterBase<TLink> : IConverter<IList<TLink>,
     ↪  TLink>
    {
        protected readonly ILinks<TLink> Links;
        public LinksListToSequenceConverterBase(ILinks<TLink> links) => Links = links;
        public abstract TLink Convert(IList<TLink> source);
    }
}
```

./Platform.Data.Doublets/Sequences/Converters/OptimalVariantConverter.cs

```
using System.Collections.Generic;
using System.Linq;
using Platform.Interfaces;

namespace Platform.Data.Doublets.Sequences.Converters
{
    public class OptimalVariantConverter<TLink> : LinksListToSequenceConverterBase<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;
        private static readonly Comparer<TLink> _comparer = Comparer<TLink>.Default;

        private readonly IConverter<IList<TLink>> _sequenceToItsLocalElementLevelsConverter;

        public OptimalVariantConverter(ILinks<TLink> links, IConverter<IList<TLink>>
         ↪  sequenceToItsLocalElementLevelsConverter) : base(links)
            => _sequenceToItsLocalElementLevelsConverter =
             ↪  sequenceToItsLocalElementLevelsConverter;

        public override TLink Convert(IList<TLink> sequence)
        {
            var length = sequence.Count;
            if (length == 1)
            {
                return sequence[0];
            }
            var links = Links;
            if (length == 2)
            {
                return links.GetOrCreate(sequence[0], sequence[1]);
            }
            sequence = sequence.ToArray();
            var levels = _sequenceToItsLocalElementLevelsConverter.Convert(sequence);
            while (length > 2)
            {
                var levelRepeat = 1;
                var currentLevel = levels[0];
                var previousLevel = levels[0];
                var skipOnce = false;
                var w = 0;
                for (var i = 1; i < length; i++)
                {
                    if (_equalityComparer.Equals(currentLevel, levels[i]))
                    {
                        levelRepeat++;
                        skipOnce = false;
                        if (levelRepeat == 2)
                        {
                            sequence[w] = links.GetOrCreate(sequence[i - 1], sequence[i]);
                            var newLevel = i >= length - 1 ?
                                GetPreviousLowerThanCurrentOrCurrent(previousLevel,
                                ↪  currentLevel) :
                                i < 2 ?
                                GetNextLowerThanCurrentOrCurrent(currentLevel, levels[i + 1]) :
                                GetGreatestNeigbourLowerThanCurrentOrCurrent(previousLevel,
                                ↪  currentLevel, levels[i + 1]);
                            levels[w] = newLevel;
                            previousLevel = currentLevel;
                            w++;
                            levelRepeat = 0;
                            skipOnce = true;
                        }
                        else if (i == length - 1)
                        {
                            sequence[w] = sequence[i];
                            levels[w] = levels[i];
                            w++;
                        }
                    }
                    else
                    {
                        currentLevel = levels[i];
                        levelRepeat = 1;
                        if (skipOnce)
                        {
                            skipOnce = false;
                        }
                        else
                        {
                            sequence[w] = sequence[i - 1];
                            levels[w] = levels[i - 1];
                            previousLevel = levels[w];
                            w++;
                        }
                        if (i == length - 1)
                        {
                            sequence[w] = sequence[i];
                            levels[w] = levels[i];
                            w++;
                        }
                    }
                }
                length = w;
            }
            return links.GetOrCreate(sequence[0], sequence[1]);
        }

        private static TLink GetGreatestNeigbourLowerThanCurrentOrCurrent(TLink previous, TLink
        ↪  current, TLink next)
        {
            return _comparer.Compare(previous, next) > 0
                ? _comparer.Compare(previous, current) < 0 ? previous : current
                : _comparer.Compare(next, current) < 0 ? next : current;
        }

        private static TLink GetNextLowerThanCurrentOrCurrent(TLink current, TLink next) =>
        ↪  _comparer.Compare(next, current) < 0 ? next : current;

        private static TLink GetPreviousLowerThanCurrentOrCurrent(TLink previous, TLink current)
        ↪  => _comparer.Compare(previous, current) < 0 ? previous : current;
    }
}
```

./Platform.Data.Doublets/Sequences/Converters/SequenceToItsLocalElementLevelsConverter.cs

```
using System.Collections.Generic;
using Platform.Interfaces;

namespace Platform.Data.Doublets.Sequences.Converters
{
    public class SequenceToItsLocalElementLevelsConverter<TLink> : LinksOperatorBase<TLink>,
     ↪  IConverter<IList<TLink>>
    {
        private static readonly Comparer<TLink> _comparer = Comparer<TLink>.Default;
        private readonly IConverter<Doublet<TLink>, TLink> _linkToItsFrequencyToNumberConveter;
        public SequenceToItsLocalElementLevelsConverter(ILinks<TLink> links,
         ↪  IConverter<Doublet<TLink>, TLink> linkToItsFrequencyToNumberConveter) : base(links)
         ↪  => _linkToItsFrequencyToNumberConveter = linkToItsFrequencyToNumberConveter;
        public IList<TLink> Convert(IList<TLink> sequence)
        {
            var levels = new TLink[sequence.Count];
            levels[0] = GetFrequencyNumber(sequence[0], sequence[1]);
            for (var i = 1; i < sequence.Count - 1; i++)
            {
                var previous = GetFrequencyNumber(sequence[i - 1], sequence[i]);
                var next = GetFrequencyNumber(sequence[i], sequence[i + 1]);
                levels[i] = _comparer.Compare(previous, next) > 0 ? previous : next;
            }
            levels[levels.Length - 1] = GetFrequencyNumber(sequence[sequence.Count - 2],
             ↪  sequence[sequence.Count - 1]);
            return levels;
        }

        public TLink GetFrequencyNumber(TLink source, TLink target) =>
         ↪  _linkToItsFrequencyToNumberConveter.Convert(new Doublet<TLink>(source, target));
    }
}
```

./Platform.Data.Doublets/Sequences/CreteriaMatchers/DefaultSequenceElementCriterionMatcher.cs

```
using Platform.Interfaces;

namespace Platform.Data.Doublets.Sequences.CreteriaMatchers
{
    public class DefaultSequenceElementCriterionMatcher<TLink> : LinksOperatorBase<TLink>,
     ↪  ICriterionMatcher<TLink>
    {
        public DefaultSequenceElementCriterionMatcher(ILinks<TLink> links) : base(links) { }
        public bool IsMatched(TLink argument) => Links.IsPartialPoint(argument);
    }
}
```

./Platform.Data.Doublets/Sequences/CreteriaMatchers/MarkedSequenceCriterionMatcher.cs

```
using System.Collections.Generic;
using Platform.Interfaces;

namespace Platform.Data.Doublets.Sequences.CreteriaMatchers
{
    public class MarkedSequenceCriterionMatcher<TLink> : ICriterionMatcher<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;

        private readonly ILinks<TLink> _links;
        private readonly TLink _sequenceMarkerLink;

        public MarkedSequenceCriterionMatcher(ILinks<TLink> links, TLink sequenceMarkerLink)
        {
            _links = links;
            _sequenceMarkerLink = sequenceMarkerLink;
        }

        public bool IsMatched(TLink sequenceCandidate)
            => _equalityComparer.Equals(_links.GetSource(sequenceCandidate), _sequenceMarkerLink)
            || !_equalityComparer.Equals(_links.SearchOrDefault(_sequenceMarkerLink,
             ↪  sequenceCandidate), _links.Constants.Null);
    }
}
```

./Platform.Data.Doublets/Sequences/DefaultSequenceAppender.cs

```
using System.Collections.Generic;
using Platform.Collections.Stacks;
using Platform.Data.Doublets.Sequences.HeightProviders;
using Platform.Data.Sequences;

namespace Platform.Data.Doublets.Sequences
{
    public class DefaultSequenceAppender<TLink> : LinksOperatorBase<TLink>,
     ↪  ISequenceAppender<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
        ↪  EqualityComparer<TLink>.Default;

        private readonly IStack<TLink> _stack;
        private readonly ISequenceHeightProvider<TLink> _heightProvider;

        public DefaultSequenceAppender(ILinks<TLink> links, IStack<TLink> stack,
        ↪  ISequenceHeightProvider<TLink> heightProvider)
            : base(links)
        {
            _stack = stack;
            _heightProvider = heightProvider;
        }

        public TLink Append(TLink sequence, TLink appendant)
        {
            var cursor = sequence;
            while (!_equalityComparer.Equals(_heightProvider.Get(cursor), default))
            {
                var source = Links.GetSource(cursor);
                var target = Links.GetTarget(cursor);
                if (_equalityComparer.Equals(_heightProvider.Get(source),
                ↪  _heightProvider.Get(target)))
                {
                    break;
                }
                else
                {
                    _stack.Push(source);
                    cursor = target;
                }
            }
            var left = cursor;
            var right = appendant;
            while (!_equalityComparer.Equals(cursor = _stack.Pop(), Links.Constants.Null))
            {
                right = Links.GetOrCreate(left, right);
                left = cursor;
            }
            return Links.GetOrCreate(left, right);
        }
    }
}
```

./Platform.Data.Doublets/Sequences/DuplicateSegmentsCounter.cs

```
using System.Collections.Generic;
using System.Linq;
using Platform.Interfaces;

namespace Platform.Data.Doublets.Sequences
{
    public class DuplicateSegmentsCounter<TLink> : ICounter<int>
    {
        private readonly IProvider<IList<KeyValuePair<IList<TLink>, IList<TLink>>>>
        ↪  _duplicateFragmentsProvider;
        public DuplicateSegmentsCounter(IProvider<IList<KeyValuePair<IList<TLink>,
        ↪  IList<TLink>>>> duplicateFragmentsProvider) => _duplicateFragmentsProvider =
        ↪  duplicateFragmentsProvider;
        public int Count() => _duplicateFragmentsProvider.Get().Sum(x => x.Value.Count);
    }
}
```

./Platform.Data.Doublets/Sequences/DuplicateSegmentsProvider.cs

```
using System;
using System.Linq;
using System.Collections.Generic;
using Platform.Interfaces;
using Platform.Collections;
using Platform.Collections.Lists;
using Platform.Collections.Segments;
using Platform.Collections.Segments.Walkers;
using Platform.Singletons;
using Platform.Numbers;
using Platform.Data.Sequences;

namespace Platform.Data.Doublets.Sequences
{
    public class DuplicateSegmentsProvider<TLink> :
    ↪  DictionaryBasedDuplicateSegmentsWalkerBase<TLink>,
    ↪  IProvider<IList<KeyValuePair<IList<TLink>, IList<TLink>>>>
    {
        private readonly ILinks<TLink> _links;
        private readonly ISequences<TLink> _sequences;
        private HashSet<KeyValuePair<IList<TLink>, IList<TLink>>> _groups;
        private BitString _visited;

        private class ItemEquilityComparer : IEqualityComparer<KeyValuePair<IList<TLink>,
        ↪  IList<TLink>>>
        {
            private readonly IListEqualityComparer<TLink> _listComparer;
            public ItemEquilityComparer() => _listComparer =
            ↪  Default<IListEqualityComparer<TLink>>.Instance;
            public bool Equals(KeyValuePair<IList<TLink>, IList<TLink>> left,
            ↪  KeyValuePair<IList<TLink>, IList<TLink>> right) =>
            ↪  _listComparer.Equals(left.Key, right.Key) && _listComparer.Equals(left.Value,
            ↪  right.Value);
            public int GetHashCode(KeyValuePair<IList<TLink>, IList<TLink>> pair) =>
            ↪  (_listComparer.GetHashCode(pair.Key),
            ↪  _listComparer.GetHashCode(pair.Value)).GetHashCode();
        }

        private class ItemComparer : IComparer<KeyValuePair<IList<TLink>, IList<TLink>>>
        {
            private readonly IListComparer<TLink> _listComparer;

            public ItemComparer() => _listComparer = Default<IListComparer<TLink>>.Instance;

            public int Compare(KeyValuePair<IList<TLink>, IList<TLink>> left,
            ↪  KeyValuePair<IList<TLink>, IList<TLink>> right)
            {
                var intermediateResult = _listComparer.Compare(left.Key, right.Key);
                if (intermediateResult == 0)
                {
                    intermediateResult = _listComparer.Compare(left.Value, right.Value);
                }
                return intermediateResult;
            }
        }

        public DuplicateSegmentsProvider(ILinks<TLink> links, ISequences<TLink> sequences)
            : base(minimumStringSegmentLength: 2)
        {
            _links = links;
            _sequences = sequences;
        }

        public IList<KeyValuePair<IList<TLink>, IList<TLink>>> Get()
        {
            _groups = new HashSet<KeyValuePair<IList<TLink>,
            ↪  IList<TLink>>>(Default<ItemEquilityComparer>.Instance);
            var count = _links.Count();
            _visited = new BitString((long)(Integer<TLink>)count + 1);
            _links.Each(link =>
            {
                var linkIndex = _links.GetIndex(link);
                var linkBitIndex = (long)(Integer<TLink>)linkIndex;
                if (!_visited.Get(linkBitIndex))
                {
                    var sequenceElements = new List<TLink>();
                    _sequences.EachPart(sequenceElements.AddAndReturnTrue, linkIndex);
                    if (sequenceElements.Count > 2)
                    {
                        WalkAll(sequenceElements);
                    }
                }
                return _links.Constants.Continue;
            });
            var resultList = _groups.ToList();
            var comparer = Default<ItemComparer>.Instance;
            resultList.Sort(comparer);
#if DEBUG
            foreach (var item in resultList)
            {
                PrintDuplicates(item);
            }
#endif
            return resultList;
        }

        protected override Segment<TLink> CreateSegment(IList<TLink> elements, int offset, int length) => new Segment<TLink>(elements, offset, length);

        protected override void OnDublicateFound(Segment<TLink> segment)
        {
            var duplicates = CollectDuplicatesForSegment(segment);
            if (duplicates.Count > 1)
            {
                _groups.Add(new KeyValuePair<IList<TLink>, IList<TLink>>(segment.ToArray(), duplicates));
            }
        }

        private List<TLink> CollectDuplicatesForSegment(Segment<TLink> segment)
        {
            var duplicates = new List<TLink>();
            var readAsElement = new HashSet<TLink>();
            _sequences.Each(sequence =>
            {
                duplicates.Add(sequence);
                readAsElement.Add(sequence);
                return true; // Continue
            }, segment);
            if (duplicates.Any(x => _visited.Get((Integer<TLink>)x)))
            {
                return new List<TLink>();
            }
            foreach (var duplicate in duplicates)
            {
                var duplicateBitIndex = (long)(Integer<TLink>)duplicate;
                _visited.Set(duplicateBitIndex);
            }
            if (_sequences is Sequences sequencesExperiments)
            {
                var partiallyMatched = sequencesExperiments.GetAllPartiallyMatchingSequences4((HashSet<ulong>)(object)readAsElement, (IList<ulong>)segment);
                foreach (var partiallyMatchedSequence in partiallyMatched)
                {
                    TLink sequenceIndex = (Integer<TLink>)partiallyMatchedSequence;
                    duplicates.Add(sequenceIndex);
                }
            }
            duplicates.Sort();
            return duplicates;
        }

        private void PrintDuplicates(KeyValuePair<IList<TLink>, IList<TLink>> duplicatesItem)
        {
            if (!(_links is ILinks<ulong> ulongLinks))
            {
                return;
            }
            var duplicatesKey = duplicatesItem.Key;
            var keyString = UnicodeMap.FromLinksToString((IList<ulong>)duplicatesKey);
            Console.WriteLine($"> {keyString} ({string.Join(", ", duplicatesKey)})");
            var duplicatesList = duplicatesItem.Value;
            for (int i = 0; i < duplicatesList.Count; i++)
            {
                ulong sequenceIndex = (Integer<TLink>)duplicatesList[i];
                var formatedSequenceStructure = ulongLinks.FormatStructure(sequenceIndex, x => Point<ulong>.IsPartialPoint(x), (sb, link) => _ = UnicodeMap.IsCharLink(link.Index) ? sb.Append(UnicodeMap.FromLinkToChar(link.Index)) : sb.Append(link.Index));
                Console.WriteLine(formatedSequenceStructure);
                var sequenceString = UnicodeMap.FromSequenceLinkToString(sequenceIndex, ulongLinks);
                Console.WriteLine(sequenceString);
            }
            Console.WriteLine();
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Cache/FrequenciesCacheBasedLinkFrequencyIncrementer.cs

```
using System.Collections.Generic;
using Platform.Interfaces;

```

```
namespace Platform.Data.Doublets.Sequences.Frequencies.Cache
{
    public class FrequenciesCacheBasedLinkFrequencyIncrementer<TLink> :
     ↪  IIncrementer<IList<TLink>>
    {
        private readonly LinkFrequenciesCache<TLink> _cache;

        public FrequenciesCacheBasedLinkFrequencyIncrementer(LinkFrequenciesCache<TLink> cache)
         ↪  => _cache = cache;

        /// <remarks>Sequence itseft is not changed, only frequency of its doublets is
         ↪  incremented.</remarks>
        public IList<TLink> Increment(IList<TLink> sequence)
        {
            _cache.IncrementFrequencies(sequence);
            return sequence;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Cache/LinkFrequenciesCache.cs

```
using System;
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Interfaces;
using Platform.Numbers;

namespace Platform.Data.Doublets.Sequences.Frequencies.Cache
{
    /// <remarks>
    /// Can be used to operate with many CompressingConverters (to keep global frequencies data
     ↪  between them).
    /// TODO: Extract interface to implement frequencies storage inside Links storage
    /// </remarks>
    public class LinkFrequenciesCache<TLink> : LinksOperatorBase<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;
        private static readonly Comparer<TLink> _comparer = Comparer<TLink>.Default;

        private readonly Dictionary<Doublet<TLink>, LinkFrequency<TLink>> _doubletsCache;
        private readonly ICounter<TLink, TLink> _frequencyCounter;

        public LinkFrequenciesCache(ILinks<TLink> links, ICounter<TLink, TLink> frequencyCounter)
            : base(links)
        {
            _doubletsCache = new Dictionary<Doublet<TLink>, LinkFrequency<TLink>>(4096,
             ↪  DoubletComparer<TLink>.Default);
            _frequencyCounter = frequencyCounter;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinkFrequency<TLink> GetFrequency(TLink source, TLink target)
        {
            var doublet = new Doublet<TLink>(source, target);
            return GetFrequency(ref doublet);
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinkFrequency<TLink> GetFrequency(ref Doublet<TLink> doublet)
        {
            _doubletsCache.TryGetValue(doublet, out LinkFrequency<TLink> data);
            return data;
        }

        public void IncrementFrequencies(IList<TLink> sequence)
        {
            for (var i = 1; i < sequence.Count; i++)
            {
                IncrementFrequency(sequence[i - 1], sequence[i]);
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinkFrequency<TLink> IncrementFrequency(TLink source, TLink target)
        {
            var doublet = new Doublet<TLink>(source, target);
            return IncrementFrequency(ref doublet);
        }

        public void PrintFrequencies(IList<TLink> sequence)
        {
            for (var i = 1; i < sequence.Count; i++)
            {
                PrintFrequency(sequence[i - 1], sequence[i]);
            }
        }

        public void PrintFrequency(TLink source, TLink target)
        {
            var number = GetFrequency(source, target).Frequency;
            Console.WriteLine("({0},{1}) - {2}", source, target, number);
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public LinkFrequency<TLink> IncrementFrequency(ref Doublet<TLink> doublet)
        {
            if (_doubletsCache.TryGetValue(doublet, out LinkFrequency<TLink> data))
            {
                data.IncrementFrequency();
            }
            else
            {
                var link = Links.SearchOrDefault(doublet.Source, doublet.Target);
                data = new LinkFrequency<TLink>(Integer<TLink>.One, link);
                if (!_equalityComparer.Equals(link, default))
                {
                    data.Frequency = Arithmetic.Add(data.Frequency,
                     ↪  _frequencyCounter.Count(link));
                }
                _doubletsCache.Add(doublet, data);
            }
            return data;
        }

        public void ValidateFrequencies()
        {
            foreach (var entry in _doubletsCache)
            {
                var value = entry.Value;
                var linkIndex = value.Link;
                if (!_equalityComparer.Equals(linkIndex, default))
                {
                    var frequency = value.Frequency;
                    var count = _frequencyCounter.Count(linkIndex);
                    // TODO: Why `frequency` always greater than `count` by 1?
                    if (((_comparer.Compare(frequency, count) > 0) &&
                     ↪  (_comparer.Compare(Arithmetic.Subtract(frequency, count),
                     ↪  Integer<TLink>.One) > 0))
                     || ((_comparer.Compare(count, frequency) > 0) &&
                      ↪  (_comparer.Compare(Arithmetic.Subtract(count, frequency),
                      ↪  Integer<TLink>.One) > 0)))
                    {
                        throw new InvalidOperationException("Frequencies validation failed.");
                    }
                }
                //else
                //{
                //    if (value.Frequency > 0)
                //    {
                //        var frequency = value.Frequency;
                //        linkIndex = _createLink(entry.Key.Source, entry.Key.Target);
                //        var count = _countLinkFrequency(linkIndex);

                //        if ((frequency > count && frequency - count > 1) || (count > frequency
                 ↪  && count - frequency > 1))
                //            throw new Exception("Frequencies validation failed.");
                //    }
                //}
            }
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Cache/LinkFrequency.cs

```
using System.Runtime.CompilerServices;
using Platform.Numbers;

```

```
namespace Platform.Data.Doublets.Sequences.Frequencies.Cache
{
    public class LinkFrequency<TLink>
    {
        public TLink Frequency { get; set; }
        public TLink Link { get; set; }

        public LinkFrequency(TLink frequency, TLink link)
        {
            Frequency = frequency;
            Link = link;
        }

        public LinkFrequency() { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public void IncrementFrequency() => Frequency = Arithmetic<TLink>.Increment(Frequency);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public void DecrementFrequency() => Frequency = Arithmetic<TLink>.Decrement(Frequency);

        public override string ToString() => $"F: {Frequency}, L: {Link}";
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Cache/LinkToItsFrequencyValueConverter.cs

```
using Platform.Interfaces;

namespace Platform.Data.Doublets.Sequences.Frequencies.Cache
{
    public class FrequenciesCacheBasedLinkToItsFrequencyNumberConverter<TLink> :
     ↪  IConverter<Doublet<TLink>, TLink>
    {
        private readonly LinkFrequenciesCache<TLink> _cache;
        public
         ↪  FrequenciesCacheBasedLinkToItsFrequencyNumberConverter(LinkFrequenciesCache<TLink>
         ↪  cache) => _cache = cache;
        public TLink Convert(Doublet<TLink> source) => _cache.GetFrequency(ref source).Frequency;
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Counters/MarkedSequenceSymbolFrequencyOneOffCounter.cs

```
using Platform.Interfaces;

namespace Platform.Data.Doublets.Sequences.Frequencies.Counters
{
    public class MarkedSequenceSymbolFrequencyOneOffCounter<TLink> :
     ↪  SequenceSymbolFrequencyOneOffCounter<TLink>
    {
        private readonly ICriterionMatcher<TLink> _markedSequenceMatcher;

        public MarkedSequenceSymbolFrequencyOneOffCounter(ILinks<TLink> links,
         ↪  ICriterionMatcher<TLink> markedSequenceMatcher, TLink sequenceLink, TLink symbol)
            : base(links, sequenceLink, symbol)
            => _markedSequenceMatcher = markedSequenceMatcher;

        public override TLink Count()
        {
            if (!_markedSequenceMatcher.IsMatched(_sequenceLink))
            {
                return default;
            }
            return base.Count();
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Counters/SequenceSymbolFrequencyOneOffCounter.cs

```
using System.Collections.Generic;
using Platform.Interfaces;
using Platform.Numbers;
using Platform.Data.Sequences;

namespace Platform.Data.Doublets.Sequences.Frequencies.Counters
{
    public class SequenceSymbolFrequencyOneOffCounter<TLink> : ICounter<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;
        private static readonly Comparer<TLink> _comparer = Comparer<TLink>.Default;

        protected readonly ILinks<TLink> _links;
        protected readonly TLink _sequenceLink;
        protected readonly TLink _symbol;
        protected TLink _total;

        public SequenceSymbolFrequencyOneOffCounter(ILinks<TLink> links, TLink sequenceLink,
         ↪  TLink symbol)
        {
            _links = links;
            _sequenceLink = sequenceLink;
            _symbol = symbol;
            _total = default;
        }

        public virtual TLink Count()
        {
            if (_comparer.Compare(_total, default) > 0)
            {
                return _total;
            }
            StopableSequenceWalker.WalkRight(_sequenceLink, _links.GetSource, _links.GetTarget,
             ↪  IsElement, VisitElement);
            return _total;
        }

        private bool IsElement(TLink x) => _equalityComparer.Equals(x, _symbol) ||
         ↪  _links.IsPartialPoint(x); // TODO: Use SequenceElementCreteriaMatcher instead of
         ↪  IsPartialPoint

        private bool VisitElement(TLink element)
        {
            if (_equalityComparer.Equals(element, _symbol))
            {
                _total = Arithmetic.Increment(_total);
            }
            return true;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Counters/TotalMarkedSequenceSymbolFrequencyCounter.cs

```
using Platform.Interfaces;

namespace Platform.Data.Doublets.Sequences.Frequencies.Counters
{
    public class TotalMarkedSequenceSymbolFrequencyCounter<TLink> : ICounter<TLink, TLink>
    {
        private readonly ILinks<TLink> _links;
        private readonly ICriterionMatcher<TLink> _markedSequenceMatcher;

        public TotalMarkedSequenceSymbolFrequencyCounter(ILinks<TLink> links,
         ↪  ICriterionMatcher<TLink> markedSequenceMatcher)
        {
            _links = links;
            _markedSequenceMatcher = markedSequenceMatcher;
        }

        public TLink Count(TLink argument) => new
         ↪  TotalMarkedSequenceSymbolFrequencyOneOffCounter<TLink>(_links,
         ↪  _markedSequenceMatcher, argument).Count();
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Counters/TotalMarkedSequenceSymbolFrequencyOneOffCounter

```
using Platform.Interfaces;
using Platform.Numbers;

namespace Platform.Data.Doublets.Sequences.Frequencies.Counters
{
    public class TotalMarkedSequenceSymbolFrequencyOneOffCounter<TLink> :
     ↪  TotalSequenceSymbolFrequencyOneOffCounter<TLink>
    {
        private readonly ICriterionMatcher<TLink> _markedSequenceMatcher;

        public TotalMarkedSequenceSymbolFrequencyOneOffCounter(ILinks<TLink> links,
         ↪  ICriterionMatcher<TLink> markedSequenceMatcher, TLink symbol)
            : base(links, symbol)
            => _markedSequenceMatcher = markedSequenceMatcher;
        protected override void CountSequenceSymbolFrequency(TLink link)
        {
            var symbolFrequencyCounter = new
             ↪  MarkedSequenceSymbolFrequencyOneOffCounter<TLink>(_links,
             ↪  _markedSequenceMatcher, link, _symbol);
            _total = Arithmetic.Add(_total, symbolFrequencyCounter.Count());
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Counters/TotalSequenceSymbolFrequencyCounter.cs

```
using Platform.Interfaces;

namespace Platform.Data.Doublets.Sequences.Frequencies.Counters
{
    public class TotalSequenceSymbolFrequencyCounter<TLink> : ICounter<TLink, TLink>
    {
        private readonly ILinks<TLink> _links;
        public TotalSequenceSymbolFrequencyCounter(ILinks<TLink> links) => _links = links;
        public TLink Count(TLink symbol) => new
         ↪  TotalSequenceSymbolFrequencyOneOffCounter<TLink>(_links, symbol).Count();
    }
}
```

./Platform.Data.Doublets/Sequences/Frequencies/Counters/TotalSequenceSymbolFrequencyOneOffCounter.cs

```
using System.Collections.Generic;
using Platform.Interfaces;
using Platform.Numbers;

namespace Platform.Data.Doublets.Sequences.Frequencies.Counters
{
    public class TotalSequenceSymbolFrequencyOneOffCounter<TLink> : ICounter<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;
        private static readonly Comparer<TLink> _comparer = Comparer<TLink>.Default;

        protected readonly ILinks<TLink> _links;
        protected readonly TLink _symbol;
        protected readonly HashSet<TLink> _visits;
        protected TLink _total;

        public TotalSequenceSymbolFrequencyOneOffCounter(ILinks<TLink> links, TLink symbol)
        {
            _links = links;
            _symbol = symbol;
            _visits = new HashSet<TLink>();
            _total = default;
        }

        public TLink Count()
        {
            if (_comparer.Compare(_total, default) > 0 || _visits.Count > 0)
            {
                return _total;
            }
            CountCore(_symbol);
            return _total;
        }

        private void CountCore(TLink link)
        {
            var any = _links.Constants.Any;
            if (_equalityComparer.Equals(_links.Count(any, link), default))
            {
                CountSequenceSymbolFrequency(link);
            }
            else
            {
                _links.Each(EachElementHandler, any, link);
            }
        }

        protected virtual void CountSequenceSymbolFrequency(TLink link)
        {
            var symbolFrequencyCounter = new SequenceSymbolFrequencyOneOffCounter<TLink>(_links,
             ↪  link, _symbol);
            _total = Arithmetic.Add(_total, symbolFrequencyCounter.Count());
        }
        private TLink EachElementHandler(IList<TLink> doublet)
        {
            var constants = _links.Constants;
            var doubletIndex = doublet[constants.IndexPart];
            if (_visits.Add(doubletIndex))
            {
                CountCore(doubletIndex);
            }
            return constants.Continue;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/HeightProviders/CachedSequenceHeightProvider.cs

```
using System.Collections.Generic;
using Platform.Interfaces;

namespace Platform.Data.Doublets.Sequences.HeightProviders
{
    public class CachedSequenceHeightProvider<TLink> : LinksOperatorBase<TLink>,
     ↪  ISequenceHeightProvider<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;

        private readonly TLink _heightPropertyMarker;
        private readonly ISequenceHeightProvider<TLink> _baseHeightProvider;
        private readonly IConverter<TLink> _addressToUnaryNumberConverter;
        private readonly IConverter<TLink> _unaryNumberToAddressConverter;
        private readonly IPropertiesOperator<TLink, TLink, TLink> _propertyOperator;

        public CachedSequenceHeightProvider(
            ILinks<TLink> links,
            ISequenceHeightProvider<TLink> baseHeightProvider,
            IConverter<TLink> addressToUnaryNumberConverter,
            IConverter<TLink> unaryNumberToAddressConverter,
            TLink heightPropertyMarker,
            IPropertiesOperator<TLink, TLink, TLink> propertyOperator)
            : base(links)
        {
            _heightPropertyMarker = heightPropertyMarker;
            _baseHeightProvider = baseHeightProvider;
            _addressToUnaryNumberConverter = addressToUnaryNumberConverter;
            _unaryNumberToAddressConverter = unaryNumberToAddressConverter;
            _propertyOperator = propertyOperator;
        }

        public TLink Get(TLink sequence)
        {
            TLink height;
            var heightValue = _propertyOperator.GetValue(sequence, _heightPropertyMarker);
            if (_equalityComparer.Equals(heightValue, default))
            {
                height = _baseHeightProvider.Get(sequence);
                heightValue = _addressToUnaryNumberConverter.Convert(height);
                _propertyOperator.SetValue(sequence, _heightPropertyMarker, heightValue);
            }
            else
            {
                height = _unaryNumberToAddressConverter.Convert(heightValue);
            }
            return height;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/HeightProviders/DefaultSequenceRightHeightProvider.cs

```
using Platform.Interfaces;
using Platform.Numbers;

namespace Platform.Data.Doublets.Sequences.HeightProviders
{
    public class DefaultSequenceRightHeightProvider<TLink> : LinksOperatorBase<TLink>,
     ↪  ISequenceHeightProvider<TLink>
    {
        private readonly ICriterionMatcher<TLink> _elementMatcher;

        public DefaultSequenceRightHeightProvider(ILinks<TLink> links, ICriterionMatcher<TLink>
         ↪  elementMatcher) : base(links) => _elementMatcher = elementMatcher;
        public TLink Get(TLink sequence)
        {
            var height = default(TLink);
            var pairOrElement = sequence;
            while (!_elementMatcher.IsMatched(pairOrElement))
            {
                pairOrElement = Links.GetTarget(pairOrElement);
                height = Arithmetic.Increment(height);
            }
            return height;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/HeightProviders/ISequenceHeightProvider.cs

```
using Platform.Interfaces;

namespace Platform.Data.Doublets.Sequences.HeightProviders
{
    public interface ISequenceHeightProvider<TLink> : IProvider<TLink, TLink>
    {
    }
}
```

./Platform.Data.Doublets/Sequences/Sequences.cs

```
using System;
using System.Collections.Generic;
using System.Linq;
using System.Runtime.CompilerServices;
using Platform.Collections;
using Platform.Collections.Lists;
using Platform.Threading.Synchronization;
using Platform.Singletons;
using LinkIndex = System.UInt64;
using Platform.Data.Constants;
using Platform.Data.Sequences;
using Platform.Data.Doublets.Sequences.Walkers;
using Platform.Collections.Stacks;

namespace Platform.Data.Doublets.Sequences
{
    /// <summary>
    /// Представляет коллекцию последовательностей связей.
    /// </summary>
    /// <remarks>
    /// Обязательно реализовать атомарность каждого публичного метода.
    ///
    /// TODO:
    ///
    /// !!! Повышение вероятности повторного использования групп (подпоследовательностей),
    /// через естественную группировку по unicode типам, все whitespace вместе, все символы
    ↪  вместе, все числа вместе и т.п.
    /// + использовать ровно сбалансированный вариант, чтобы уменьшать вложенность (глубину
    ↪  графа)
    ///
    /// x*y - найти все связи между, в последовательностях любой формы, если не стоит
    ↪  ограничитель на то, что является последовательностью, а что нет,
    /// то находятся любые структуры связей, которые содержат эти элементы именно в таком
    ↪  порядке.
    ///
    /// Рост последовательности слева и справа.
    /// Поиск со звёздочкой.
    /// URL, PURL - реестр используемых во вне ссылок на ресурсы,
    /// так же проблема может быть решена при реализации дистанционных триггеров.
    /// Нужны ли уникальные указатели вообще?
    /// Что если обращение к информации будет происходить через содержимое всегда?
    ///
    /// Писать тесты.
    ///
    ///
    /// Можно убрать зависимость от конкретной реализации Links,
    /// на зависимость от абстрактного элемента, который может быть представлен несколькими
    ↪  способами.
    ///
    /// Можно ли как-то сделать один общий интерфейс
    ///
    ///
    /// Блокчейн и/или гит для распределённой записи транзакций.
    ///
    /// </remarks>
    public partial class Sequences : ISequences<ulong> // IList<string>, IList<ulong[]> (после
     ↪  завершения реализации Sequences)
    {
        private static readonly LinksCombinedConstants<bool, ulong, long> _constants =
         ↪  Default<LinksCombinedConstants<bool, ulong, long>>.Instance;

        /// <summary>Возвращает значение ulong, обозначающее любое количество связей.</summary>
        public const ulong ZeroOrMany = ulong.MaxValue;

        public SequencesOptions<ulong> Options;
        public readonly SynchronizedLinks<ulong> Links;
        public readonly ISynchronization Sync;

        public Sequences(SynchronizedLinks<ulong> links)
            : this(links, new SequencesOptions<ulong>())
        {
        }

        public Sequences(SynchronizedLinks<ulong> links, SequencesOptions<ulong> options)
        {
            Links = links;
            Sync = links.SyncRoot;
            Options = options;

            Options.ValidateOptions();
            Options.InitOptions(Links);
        }

        public bool IsSequence(ulong sequence)
        {
            return Sync.ExecuteReadOperation(() =>
            {
                if (Options.UseSequenceMarker)
                {
                    return Options.MarkedSequenceMatcher.IsMatched(sequence);
                }
                return !Links.Unsync.IsPartialPoint(sequence);
            });
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private ulong GetSequenceByElements(ulong sequence)
        {
            if (Options.UseSequenceMarker)
            {
                return Links.SearchOrDefault(Options.SequenceMarkerLink, sequence);
            }
            return sequence;
        }

        private ulong GetSequenceElements(ulong sequence)
        {
            if (Options.UseSequenceMarker)
            {
                var linkContents = new UInt64Link(Links.GetLink(sequence));
                if (linkContents.Source == Options.SequenceMarkerLink)
                {
                    return linkContents.Target;
                }
                if (linkContents.Target == Options.SequenceMarkerLink)
                {
                    return linkContents.Source;
                }
            }
            return sequence;
        }

        #region Count

        public ulong Count(params ulong[] sequence)
        {
            if (sequence.Length == 0)
            {
                return Links.Count(_constants.Any, Options.SequenceMarkerLink, _constants.Any);
            }
            if (sequence.Length == 1) // Первая связь это адрес
            {
                if (sequence[0] == _constants.Null)
                {
                    return 0;
                }
                if (sequence[0] == _constants.Any)
                {
                    return Count();
                }
                if (Options.UseSequenceMarker)
                {
                    return Links.Count(_constants.Any, Options.SequenceMarkerLink, sequence[0]);
                }
                return Links.Exists(sequence[0]) ? 1UL : 0;
            }
            throw new NotImplementedException();
        }

        private ulong CountUsages(params ulong[] restrictions)
        {
            if (restrictions.Length == 0)
            {
                return 0;
            }
            if (restrictions.Length == 1) // Первая связь это адрес
            {
                if (restrictions[0] == _constants.Null)
                {
                    return 0;
                }
                if (Options.UseSequenceMarker)
                {
                    var elementsLink = GetSequenceElements(restrictions[0]);
                    var sequenceLink = GetSequenceByElements(elementsLink);
                    if (sequenceLink != _constants.Null)
                    {
                        return Links.Count(sequenceLink) + Links.Count(elementsLink) - 1;
                    }
                    return Links.Count(elementsLink);
                }
                return Links.Count(restrictions[0]);
            }
            throw new NotImplementedException();
        }

        #endregion

        #region Create

        public ulong Create(params ulong[] sequence)
        {
            return Sync.ExecuteWriteOperation(() =>
            {
                if (sequence.IsNullOrEmpty())
                {
                    return _constants.Null;
                }
                Links.EnsureEachLinkExists(sequence);
                return CreateCore(sequence);
            });
        }

        private ulong CreateCore(params ulong[] sequence)
        {
            if (Options.UseIndex)
            {
                Options.Indexer.Index(sequence);
            }
            var sequenceRoot = default(ulong);
            if (Options.EnforceSingleSequenceVersionOnWriteBasedOnExisting)
            {
                var matches = Each(sequence);
                if (matches.Count > 0)
                {
                    sequenceRoot = matches[0];
                }
            }
            else if (Options.EnforceSingleSequenceVersionOnWriteBasedOnNew)
            {
                return CompactCore(sequence);
            }
            if (sequenceRoot == default)
            {
                sequenceRoot = Options.LinksToSequenceConverter.Convert(sequence);
            }
            if (Options.UseSequenceMarker)
            {
                Links.Unsync.CreateAndUpdate(Options.SequenceMarkerLink, sequenceRoot);
            }
            return sequenceRoot; // Возвращаем корень последовательности (т.е. сами элементы)
        }

        #endregion

        #region Each

        public List<ulong> Each(params ulong[] sequence)
        {
            var results = new List<ulong>();
            Each(results.AddAndReturnTrue, sequence);
            return results;
        }

        public bool Each(Func<ulong, bool> handler, IList<ulong> sequence)
        {
            return Sync.ExecuteReadOperation(() =>
            {
                if (sequence.IsNullOrEmpty())
                {
                    return true;
                }
                Links.EnsureEachLinkIsAnyOrExists(sequence);
                if (sequence.Count == 1)
                {
                    var link = sequence[0];
                    if (link == _constants.Any)
                    {
                        return Links.Unsync.Each(_constants.Any, _constants.Any, handler);
                    }
                    return handler(link);
                }
                if (sequence.Count == 2)
                {
                    return Links.Unsync.Each(sequence[0], sequence[1], handler);
                }
                if (Options.UseIndex && !Options.Indexer.CheckIndex(sequence))
                {
                    return false;
                }
                return EachCore(handler, sequence);
            });
        }

        private bool EachCore(Func<ulong, bool> handler, IList<ulong> sequence)
        {
            var matcher = new Matcher(this, sequence, new HashSet<LinkIndex>(), handler);
            // TODO: Find out why matcher.HandleFullMatched executed twice for the same sequence
            ↪  Id.
            Func<ulong, bool> innerHandler = Options.UseSequenceMarker ? (Func<ulong,
            ↪  bool>)matcher.HandleFullMatchedSequence : matcher.HandleFullMatched;
            //if (sequence.Length >= 2)
            if (!StepRight(innerHandler, sequence[0], sequence[1]))
            {
                return false;
            }
            var last = sequence.Count - 2;
            for (var i = 1; i < last; i++)
            {
                if (!PartialStepRight(innerHandler, sequence[i], sequence[i + 1]))
                {
                    return false;
                }
            }
            if (sequence.Count >= 3)
            {
                if (!StepLeft(innerHandler, sequence[sequence.Count - 2],
                ↪  sequence[sequence.Count - 1]))
                {
                    return false;
                }
            }
            return true;
        }

        private bool PartialStepRight(Func<ulong, bool> handler, ulong left, ulong right)
        {
            return Links.Unsync.Each(_constants.Any, left, doublet =>
            {
                if (!StepRight(handler, doublet, right))
                {
                    return false;
                }
                if (left != doublet)
                {
                    return PartialStepRight(handler, doublet, right);
                }
                return true;
            });
        }

        private bool StepRight(Func<ulong, bool> handler, ulong left, ulong right) =>
        ↪  Links.Unsync.Each(left, _constants.Any, rightStep => TryStepRightUp(handler, right,
        ↪  rightStep));

        private bool TryStepRightUp(Func<ulong, bool> handler, ulong right, ulong stepFrom)
        {
            var upStep = stepFrom;
            var firstSource = Links.Unsync.GetTarget(upStep);
            while (firstSource != right && firstSource != upStep)
            {
                upStep = firstSource;
                firstSource = Links.Unsync.GetSource(upStep);
            }
            if (firstSource == right)
            {
                return handler(stepFrom);
            }
            return true;
        }

        private bool StepLeft(Func<ulong, bool> handler, ulong left, ulong right) =>
        ↪  Links.Unsync.Each(_constants.Any, right, leftStep => TryStepLeftUp(handler, left,
        ↪  leftStep));

        private bool TryStepLeftUp(Func<ulong, bool> handler, ulong left, ulong stepFrom)
        {
            var upStep = stepFrom;
            var firstTarget = Links.Unsync.GetSource(upStep);
            while (firstTarget != left && firstTarget != upStep)
            {
                upStep = firstTarget;
                firstTarget = Links.Unsync.GetTarget(upStep);
            }
            if (firstTarget == left)
            {
                return handler(stepFrom);
            }
            return true;
        }

        #endregion

        #region Update

        public ulong Update(ulong[] sequence, ulong[] newSequence)
        {
            if (sequence.IsNullOrEmpty() && newSequence.IsNullOrEmpty())
            {
                return _constants.Null;
            }
            if (sequence.IsNullOrEmpty())
            {
                return Create(newSequence);
            }
            if (newSequence.IsNullOrEmpty())
            {
                Delete(sequence);
                return _constants.Null;
            }
            return Sync.ExecuteWriteOperation(() =>
            {
                Links.EnsureEachLinkIsAnyOrExists(sequence);
                Links.EnsureEachLinkExists(newSequence);
                return UpdateCore(sequence, newSequence);
            });
        }

        private ulong UpdateCore(ulong[] sequence, ulong[] newSequence)
        {
            ulong bestVariant;
            if (Options.EnforceSingleSequenceVersionOnWriteBasedOnNew &&
             ↪  !sequence.EqualTo(newSequence))
            {
                bestVariant = CompactCore(newSequence);
            }
            else
            {
                bestVariant = CreateCore(newSequence);
            }
            // TODO: Check all options only ones before loop execution
            // Возможно нужно две версии Each, возвращающий фактические последовательности и с
             ↪  маркером,
            // или возможно даже возвращать и тот и тот вариант. С другой стороны все варианты
             ↪  можно получить имея только фактические последовательности.
            foreach (var variant in Each(sequence))
            {
                if (variant != bestVariant)
                {
                    UpdateOneCore(variant, bestVariant);
                }
            }
            return bestVariant;
        }

        private void UpdateOneCore(ulong sequence, ulong newSequence)
        {
            if (Options.UseGarbageCollection)
            {
                var sequenceElements = GetSequenceElements(sequence);
                var sequenceElementsContents = new UInt64Link(Links.GetLink(sequenceElements));
                var sequenceLink = GetSequenceByElements(sequenceElements);
                var newSequenceElements = GetSequenceElements(newSequence);
                var newSequenceLink = GetSequenceByElements(newSequenceElements);
                if (Options.UseCascadeUpdate || CountUsages(sequence) == 0)
                {
                    if (sequenceLink != _constants.Null)
                    {
                        Links.Unsync.MergeUsages(sequenceLink, newSequenceLink);
                    }
                    Links.Unsync.MergeUsages(sequenceElements, newSequenceElements);
                }
                ClearGarbage(sequenceElementsContents.Source);
                ClearGarbage(sequenceElementsContents.Target);
            }
            else
            {
                if (Options.UseSequenceMarker)
                {
                    var sequenceElements = GetSequenceElements(sequence);
                    var sequenceLink = GetSequenceByElements(sequenceElements);
                    var newSequenceElements = GetSequenceElements(newSequence);
                    var newSequenceLink = GetSequenceByElements(newSequenceElements);
                    if (Options.UseCascadeUpdate || CountUsages(sequence) == 0)
                    {
                        if (sequenceLink != _constants.Null)
                        {
                            Links.Unsync.MergeUsages(sequenceLink, newSequenceLink);
                        }
                        Links.Unsync.MergeUsages(sequenceElements, newSequenceElements);
                    }
                }
                else
                {
                    if (Options.UseCascadeUpdate || CountUsages(sequence) == 0)
                    {
                        Links.Unsync.MergeUsages(sequence, newSequence);
                }
            }
        }
    }

    #endregion

    #region Delete

    public void Delete(params ulong[] sequence)
    {
        Sync.ExecuteWriteOperation(() =>
        {
            // TODO: Check all options only ones before loop execution
            foreach (var linkToDelete in Each(sequence))
            {
                DeleteOneCore(linkToDelete);
            }
        });
    }

    private void DeleteOneCore(ulong link)
    {
        if (Options.UseGarbageCollection)
        {
            var sequenceElements = GetSequenceElements(link);
            var sequenceElementsContents = new UInt64Link(Links.GetLink(sequenceElements));
            var sequenceLink = GetSequenceByElements(sequenceElements);
            if (Options.UseCascadeDelete || CountUsages(link) == 0)
            {
                if (sequenceLink != _constants.Null)
                {
                    Links.Unsync.Delete(sequenceLink);
                }
                Links.Unsync.Delete(link);
            }
            ClearGarbage(sequenceElementsContents.Source);
            ClearGarbage(sequenceElementsContents.Target);
        }
        else
        {
            if (Options.UseSequenceMarker)
            {
                var sequenceElements = GetSequenceElements(link);
                var sequenceLink = GetSequenceByElements(sequenceElements);
                if (Options.UseCascadeDelete || CountUsages(link) == 0)
                {
                    if (sequenceLink != _constants.Null)
                    {
                        Links.Unsync.Delete(sequenceLink);
                    }
                    Links.Unsync.Delete(link);
                }
            }
            else
            {
                if (Options.UseCascadeDelete || CountUsages(link) == 0)
                {
                    Links.Unsync.Delete(link);
                }
            }
        }
    }

    #endregion

    #region Compactification

    /// <remarks>
    /// bestVariant можно выбирать по максимальному числу использований,
    /// но балансированный позволяет гарантировать уникальность (если есть возможность,
    /// гарантировать его использование в других местах).
    ///
    /// Получается этот метод должен игнорировать Options.EnforceSingleSequenceVersionOnWrite
    /// </remarks>
    public ulong Compact(params ulong[] sequence)
    {
        return Sync.ExecuteWriteOperation(() =>
        {
                if (sequence.IsNullOrEmpty())
                {
                    return _constants.Null;
                }
                Links.EnsureEachLinkExists(sequence);
                return CompactCore(sequence);
            });
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private ulong CompactCore(params ulong[] sequence) => UpdateCore(sequence, sequence);

        #endregion

        #region Garbage Collection

        /// <remarks>
        /// TODO: Добавить дополнительный обработчик / событие CanBeDeleted которое можно
        ↪  определить извне или в унаследованном классе
        /// </remarks>
        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private bool IsGarbage(ulong link) => link != Options.SequenceMarkerLink &&
        ↪  !Links.Unsync.IsPartialPoint(link) && Links.Count(link) == 0;

        private void ClearGarbage(ulong link)
        {
            if (IsGarbage(link))
            {
                var contents = new UInt64Link(Links.GetLink(link));
                Links.Unsync.Delete(link);
                ClearGarbage(contents.Source);
                ClearGarbage(contents.Target);
            }
        }

        #endregion

        #region Walkers

        public bool EachPart(Func<ulong, bool> handler, ulong sequence)
        {
            return Sync.ExecuteReadOperation(() =>
            {
                var links = Links.Unsync;
                var walker = new RightSequenceWalker<ulong>(links, new DefaultStack<ulong>());
                foreach (var part in walker.Walk(sequence))
                {
                    if (!handler(links.GetIndex(part)))
                    {
                        return false;
                    }
                }
                return true;
            });
        }

        public class Matcher : RightSequenceWalker<ulong>
        {
            private readonly Sequences _sequences;
            private readonly IList<LinkIndex> _patternSequence;
            private readonly HashSet<LinkIndex> _linksInSequence;
            private readonly HashSet<LinkIndex> _results;
            private readonly Func<ulong, bool> _stopableHandler;
            private readonly HashSet<ulong> _readAsElements;
            private int _filterPosition;

            public Matcher(Sequences sequences, IList<LinkIndex> patternSequence,
            ↪  HashSet<LinkIndex> results, Func<LinkIndex, bool> stopableHandler,
            ↪  HashSet<LinkIndex> readAsElements = null)
                : base(sequences.Links.Unsync, new DefaultStack<ulong>())
            {
                _sequences = sequences;
                _patternSequence = patternSequence;
                _linksInSequence = new HashSet<LinkIndex>(patternSequence.Where(x => x !=
                ↪  _constants.Any && x != ZeroOrMany));
                _results = results;
                _stopableHandler = stopableHandler;
                _readAsElements = readAsElements;
            }

            protected override bool IsElement(IList<ulong> link) => base.IsElement(link) ||
             ↪   (_readAsElements != null && _readAsElements.Contains(Links.GetIndex(link))) ||
             ↪   _linksInSequence.Contains(Links.GetIndex(link));

            public bool FullMatch(LinkIndex sequenceToMatch)
            {
                _filterPosition = 0;
                foreach (var part in Walk(sequenceToMatch))
                {
                    if (!FullMatchCore(Links.GetIndex(part)))
                    {
                        break;
                    }
                }
                return _filterPosition == _patternSequence.Count;
            }

            private bool FullMatchCore(LinkIndex element)
            {
                if (_filterPosition == _patternSequence.Count)
                {
                    _filterPosition = -2; // Длиннее чем нужно
                    return false;
                }
                if (_patternSequence[_filterPosition] != _constants.Any
                 && element != _patternSequence[_filterPosition])
                {
                    _filterPosition = -1;
                    return false; // Начинается/Продолжается иначе
                }
                _filterPosition++;
                return true;
            }

            public void AddFullMatchedToResults(ulong sequenceToMatch)
            {
                if (FullMatch(sequenceToMatch))
                {
                    _results.Add(sequenceToMatch);
                }
            }

            public bool HandleFullMatched(ulong sequenceToMatch)
            {
                if (FullMatch(sequenceToMatch) && _results.Add(sequenceToMatch))
                {
                    return _stopableHandler(sequenceToMatch);
                }
                return true;
            }

            public bool HandleFullMatchedSequence(ulong sequenceToMatch)
            {
                var sequence = _sequences.GetSequenceByElements(sequenceToMatch);
                if (sequence != _constants.Null && FullMatch(sequenceToMatch) &&
                 ↪   _results.Add(sequenceToMatch))
                {
                    return _stopableHandler(sequence);
                }
                return true;
            }

            /// <remarks>
            /// TODO: Add support for LinksConstants.Any
            /// </remarks>
            public bool PartialMatch(LinkIndex sequenceToMatch)
            {
                _filterPosition = -1;
                foreach (var part in Walk(sequenceToMatch))
                {
                    if (!PartialMatchCore(Links.GetIndex(part)))
                    {
                        break;
                    }
                }
                return _filterPosition == _patternSequence.Count - 1;
            }

            private bool PartialMatchCore(LinkIndex element)
            {
                if (_filterPosition == (_patternSequence.Count - 1))
                {
                    return false; // Нашлось
                }
                if (_filterPosition >= 0)
                {
                    if (element == _patternSequence[_filterPosition + 1])
                    {
                        _filterPosition++;
                    }
                    else
                    {
                        _filterPosition = -1;
                    }
                }
                if (_filterPosition < 0)
                {
                    if (element == _patternSequence[0])
                    {
                        _filterPosition = 0;
                    }
                }
                return true; // Ищем дальше
            }

            public void AddPartialMatchedToResults(ulong sequenceToMatch)
            {
                if (PartialMatch(sequenceToMatch))
                {
                    _results.Add(sequenceToMatch);
                }
            }

            public bool HandlePartialMatched(ulong sequenceToMatch)
            {
                if (PartialMatch(sequenceToMatch))
                {
                    return _stopableHandler(sequenceToMatch);
                }
                return true;
            }

            public void AddAllPartialMatchedToResults(IEnumerable<ulong> sequencesToMatch)
            {
                foreach (var sequenceToMatch in sequencesToMatch)
                {
                    if (PartialMatch(sequenceToMatch))
                    {
                        _results.Add(sequenceToMatch);
                    }
                }
            }

            public void AddAllPartialMatchedToResultsAndReadAsElements(IEnumerable<ulong>
             ↪  sequencesToMatch)
            {
                foreach (var sequenceToMatch in sequencesToMatch)
                {
                    if (PartialMatch(sequenceToMatch))
                    {
                        _readAsElements.Add(sequenceToMatch);
                        _results.Add(sequenceToMatch);
                    }
                }
            }
        }

        #endregion
    }
}
```

./Platform.Data.Doublets/Sequences/Sequences.Experiments.cs

```
using System;
using LinkIndex = System.UInt64;
using System.Collections.Generic;
using Stack = System.Collections.Generic.Stack<ulong>;
using System.Linq;
using System.Text;
using Platform.Collections;
using Platform.Data.Exceptions;
using Platform.Data.Sequences;
using Platform.Data.Doublets.Sequences.Frequencies.Counters;
using Platform.Data.Doublets.Sequences.Walkers;
using Platform.Collections.Stacks;

namespace Platform.Data.Doublets.Sequences
{
    partial class Sequences
    {
        #region Create All Variants (Not Practical)

        /// <remarks>
        /// Number of links that is needed to generate all variants for
        /// sequence of length N corresponds to https://oeis.org/A014143/list sequence.
        /// </remarks>
        public ulong[] CreateAllVariants2(ulong[] sequence)
        {
            return Sync.ExecuteWriteOperation(() =>
            {
                if (sequence.IsNullOrEmpty())
                {
                    return new ulong[0];
                }
                Links.EnsureEachLinkExists(sequence);
                if (sequence.Length == 1)
                {
                    return sequence;
                }
                return CreateAllVariants2Core(sequence, 0, sequence.Length - 1);
            });
        }

        private ulong[] CreateAllVariants2Core(ulong[] sequence, long startAt, long stopAt)
        {
#if DEBUG
            if ((stopAt - startAt) < 0)
            {
                throw new ArgumentOutOfRangeException(nameof(startAt), "startAt должен быть
                 ↪  меньше или равен stopAt");
            }
#endif
            if ((stopAt - startAt) == 0)
            {
                return new[] { sequence[startAt] };
            }
            if ((stopAt - startAt) == 1)
            {
                return new[] { Links.Unsync.CreateAndUpdate(sequence[startAt], sequence[stopAt])
                 ↪  };
            }
            var variants = new ulong[(ulong)Numbers.Math.Catalan(stopAt - startAt)];
            var last = 0;
            for (var splitter = startAt; splitter < stopAt; splitter++)
            {
                var left = CreateAllVariants2Core(sequence, startAt, splitter);
                var right = CreateAllVariants2Core(sequence, splitter + 1, stopAt);
                for (var i = 0; i < left.Length; i++)
                {
                    for (var j = 0; j < right.Length; j++)
                    {
                        var variant = Links.Unsync.CreateAndUpdate(left[i], right[j]);
                        if (variant == _constants.Null)
                        {
                            throw new NotImplementedException("Creation cancellation is not
                             ↪  implemented.");
                        }
                        variants[last++] = variant;
                    }
                }
            }
            return variants;
        }

        public List<ulong> CreateAllVariants1(params ulong[] sequence)
        {
            return Sync.ExecuteWriteOperation(() =>
            {
                if (sequence.IsNullOrEmpty())
                {
                    return new List<ulong>();
                }
                Links.Unsync.EnsureEachLinkExists(sequence);
                if (sequence.Length == 1)
                {
                    return new List<ulong> { sequence[0] };
                }
                var results = new List<ulong>((int)Numbers.Math.Catalan(sequence.Length));
                return CreateAllVariants1Core(sequence, results);
            });
        }

        private List<ulong> CreateAllVariants1Core(ulong[] sequence, List<ulong> results)
        {
            if (sequence.Length == 2)
            {
                var link = Links.Unsync.CreateAndUpdate(sequence[0], sequence[1]);
                if (link == _constants.Null)
                {
                    throw new NotImplementedException("Creation cancellation is not
                     ↪  implemented.");
                }
                results.Add(link);
                return results;
            }
            var innerSequenceLength = sequence.Length - 1;
            var innerSequence = new ulong[innerSequenceLength];
            for (var li = 0; li < innerSequenceLength; li++)
            {
                var link = Links.Unsync.CreateAndUpdate(sequence[li], sequence[li + 1]);
                if (link == _constants.Null)
                {
                    throw new NotImplementedException("Creation cancellation is not
                     ↪  implemented.");
                }
                for (var isi = 0; isi < li; isi++)
                {
                    innerSequence[isi] = sequence[isi];
                }
                innerSequence[li] = link;
                for (var isi = li + 1; isi < innerSequenceLength; isi++)
                {
                    innerSequence[isi] = sequence[isi + 1];
                }
                CreateAllVariants1Core(innerSequence, results);
            }
            return results;
        }

        #endregion

        public HashSet<ulong> Each1(params ulong[] sequence)
        {
            var visitedLinks = new HashSet<ulong>(); // Заменить на bitstring
            Each1(link =>
            {
                if (!visitedLinks.Contains(link))
                {
                    visitedLinks.Add(link); // изучить почему случаются повторы
                }
                return true;
            }, sequence);
            return visitedLinks;
        }

        private void Each1(Func<ulong, bool> handler, params ulong[] sequence)
        {
            if (sequence.Length == 2)
            {
                Links.Unsync.Each(sequence[0], sequence[1], handler);
            }
            else
            {
                var innerSequenceLength = sequence.Length - 1;
                for (var li = 0; li < innerSequenceLength; li++)
                {
                    var left = sequence[li];
                    var right = sequence[li + 1];
                    if (left == 0 && right == 0)
                    {
                        continue;
                    }
                    var linkIndex = li;
                    ulong[] innerSequence = null;
                    Links.Unsync.Each(left, right, doublet =>
                    {
                        if (innerSequence == null)
                        {
                            innerSequence = new ulong[innerSequenceLength];
                            for (var isi = 0; isi < linkIndex; isi++)
                            {
                                innerSequence[isi] = sequence[isi];
                            }
                            for (var isi = linkIndex + 1; isi < innerSequenceLength; isi++)
                            {
                                innerSequence[isi] = sequence[isi + 1];
                            }
                        }
                        innerSequence[linkIndex] = doublet;
                        Each1(handler, innerSequence);
                        return _constants.Continue;
                    });
                }
            }
        }

        public HashSet<ulong> EachPart(params ulong[] sequence)
        {
            var visitedLinks = new HashSet<ulong>(); // Заменить на bitstring
            EachPartCore(link =>
            {
                if (!visitedLinks.Contains(link))
                {
                    visitedLinks.Add(link); // изучить почему случаются повторы
                }
                return true;
            }, sequence);
            return visitedLinks;
        }

        public void EachPart(Func<ulong, bool> handler, params ulong[] sequence)
        {
            var visitedLinks = new HashSet<ulong>(); // Заменить на bitstring
            EachPartCore(link =>
            {
                if (!visitedLinks.Contains(link))
                {
                    visitedLinks.Add(link); // изучить почему случаются повторы
                    return handler(link);
                }
                return true;
            }, sequence);
        }

        private void EachPartCore(Func<ulong, bool> handler, params ulong[] sequence)
        {
            if (sequence.IsNullOrEmpty())
            {
                return;
            }
            Links.EnsureEachLinkIsAnyOrExists(sequence);
            if (sequence.Length == 1)
            {
                var link = sequence[0];
                if (link > 0)
                {
                    handler(link);
                }
                else
                {
                    Links.Each(_constants.Any, _constants.Any, handler);
                }
            }
            else if (sequence.Length == 2)
            {
                //_links.Each(sequence[0], sequence[1], handler);
                //  o_|      x_o ...
                // x_|        |___|
                Links.Each(sequence[1], _constants.Any, doublet =>
                {
                    var match = Links.SearchOrDefault(sequence[0], doublet);
                    if (match != _constants.Null)
                    {
                        handler(match);
                    }
                    return true;
                });
                // |_x      ... x_o
                //  |_o      |___|
                Links.Each(_constants.Any, sequence[0], doublet =>
                {
                    var match = Links.SearchOrDefault(doublet, sequence[1]);
                    if (match != 0)
                    {
                        handler(match);
                    }
                    return true;
                });
                //          ._x o_.
                //           |___|
                PartialStepRight(x => handler(x), sequence[0], sequence[1]);
            }
            else
            {
                // TODO: Implement other variants
                return;
            }
        }

        private void PartialStepRight(Action<ulong> handler, ulong left, ulong right)
        {
            Links.Unsync.Each(_constants.Any, left, doublet =>
            {
                StepRight(handler, doublet, right);
                if (left != doublet)
                {
                    PartialStepRight(handler, doublet, right);
                }
                return true;
            });
        }

        private void StepRight(Action<ulong> handler, ulong left, ulong right)
        {
            Links.Unsync.Each(left, _constants.Any, rightStep =>
            {
                TryStepRightUp(handler, right, rightStep);
                return true;
            });
        }

        private void TryStepRightUp(Action<ulong> handler, ulong right, ulong stepFrom)
        {
            var upStep = stepFrom;
            var firstSource = Links.Unsync.GetTarget(upStep);
            while (firstSource != right && firstSource != upStep)
            {
                upStep = firstSource;
                firstSource = Links.Unsync.GetSource(upStep);
            }
            if (firstSource == right)
            {
                handler(stepFrom);
            }
        }

        // TODO: Test
        private void PartialStepLeft(Action<ulong> handler, ulong left, ulong right)
        {
            Links.Unsync.Each(right, _constants.Any, doublet =>
            {
                StepLeft(handler, left, doublet);
                if (right != doublet)
                {
                    PartialStepLeft(handler, left, doublet);
                }
                return true;
            });
        }

        private void StepLeft(Action<ulong> handler, ulong left, ulong right)
        {
            Links.Unsync.Each(_constants.Any, right, leftStep =>
            {
                TryStepLeftUp(handler, left, leftStep);
                return true;
            });
        }

        private void TryStepLeftUp(Action<ulong> handler, ulong left, ulong stepFrom)
        {
            var upStep = stepFrom;
            var firstTarget = Links.Unsync.GetSource(upStep);
            while (firstTarget != left && firstTarget != upStep)
            {
                upStep = firstTarget;
                firstTarget = Links.Unsync.GetTarget(upStep);
            }
            if (firstTarget == left)
            {
                handler(stepFrom);
            }
        }

        private bool StartsWith(ulong sequence, ulong link)
        {
            var upStep = sequence;
            var firstSource = Links.Unsync.GetSource(upStep);
            while (firstSource != link && firstSource != upStep)
            {
                upStep = firstSource;
                firstSource = Links.Unsync.GetSource(upStep);
            }
            return firstSource == link;
        }

        private bool EndsWith(ulong sequence, ulong link)
        {
            var upStep = sequence;
            var lastTarget = Links.Unsync.GetTarget(upStep);
            while (lastTarget != link && lastTarget != upStep)
            {
                upStep = lastTarget;
                lastTarget = Links.Unsync.GetTarget(upStep);
            }
            return lastTarget == link;
        }

        public List<ulong> GetAllMatchingSequences0(params ulong[] sequence)
        {
            return Sync.ExecuteReadOperation(() =>
            {
                var results = new List<ulong>();
                if (sequence.Length > 0)
                {
                    Links.EnsureEachLinkExists(sequence);
                    var firstElement = sequence[0];
                    if (sequence.Length == 1)
                    {
                        results.Add(firstElement);
                        return results;
                    }
                    if (sequence.Length == 2)
                    {
                        var doublet = Links.SearchOrDefault(firstElement, sequence[1]);
                        if (doublet != _constants.Null)
                        {
                            results.Add(doublet);
                        }
                        return results;
                    }
                    var linksInSequence = new HashSet<ulong>(sequence);
                    void handler(ulong result)
                    {
                        var filterPosition = 0;
                        StopableSequenceWalker.WalkRight(result, Links.Unsync.GetSource,
                         ↪  Links.Unsync.GetTarget,
                            x => linksInSequence.Contains(x) || Links.Unsync.GetTarget(x) == x,
                             ↪  x =>
                            {
                                if (filterPosition == sequence.Length)
                                {
                                    filterPosition = -2; // Длиннее чем нужно
                                    return false;
                                }
                                if (x != sequence[filterPosition])
                                {
                                    filterPosition = -1;
                                    return false; // Начинается иначе
                                }
                                filterPosition++;

                                return true;
                            });
                        if (filterPosition == sequence.Length)
                        {
                            results.Add(result);
                        }
                    }
                    if (sequence.Length >= 2)
                    {
                        StepRight(handler, sequence[0], sequence[1]);
                    }
                    var last = sequence.Length - 2;
                    for (var i = 1; i < last; i++)
                    {
                        PartialStepRight(handler, sequence[i], sequence[i + 1]);
                    }
                    if (sequence.Length >= 3)
                    {
                        StepLeft(handler, sequence[sequence.Length - 2],
                         ↪  sequence[sequence.Length - 1]);
                    }
                }
                return results;
            });
        }

        public HashSet<ulong> GetAllMatchingSequences1(params ulong[] sequence)
        {
            return Sync.ExecuteReadOperation(() =>
            {
                var results = new HashSet<ulong>();
                if (sequence.Length > 0)
                {
                    Links.EnsureEachLinkExists(sequence);
                    var firstElement = sequence[0];
                    if (sequence.Length == 1)
                    {
                        results.Add(firstElement);
                        return results;
                    }
                    if (sequence.Length == 2)
                    {
                        var doublet = Links.SearchOrDefault(firstElement, sequence[1]);
                        if (doublet != _constants.Null)
                        {
                            results.Add(doublet);
                        }
                        return results;
                    }
                    var matcher = new Matcher(this, sequence, results, null);
                    if (sequence.Length >= 2)
                    {
                        StepRight(matcher.AddFullMatchedToResults, sequence[0], sequence[1]);
                    }
                    var last = sequence.Length - 2;
                    for (var i = 1; i < last; i++)
                    {
                        PartialStepRight(matcher.AddFullMatchedToResults, sequence[i],
                         ↪  sequence[i + 1]);
                    }
                    if (sequence.Length >= 3)
                    {
                        StepLeft(matcher.AddFullMatchedToResults, sequence[sequence.Length - 2], sequence[sequence.Length - 1]);
                    }
                }
                return results;
            });
        }

        public const int MaxSequenceFormatSize = 200;

        public string FormatSequence(LinkIndex sequenceLink, params LinkIndex[] knownElements) => FormatSequence(sequenceLink, (sb, x) => sb.Append(x), true, knownElements);

        public string FormatSequence(LinkIndex sequenceLink, Action<StringBuilder, LinkIndex> elementToString, bool insertComma, params LinkIndex[] knownElements) => Links.SyncRoot.ExecuteReadOperation(() => FormatSequence(Links.Unsync, sequenceLink, elementToString, insertComma, knownElements));

        private string FormatSequence(ILinks<LinkIndex> links, LinkIndex sequenceLink, Action<StringBuilder, LinkIndex> elementToString, bool insertComma, params LinkIndex[] knownElements)
        {
            var linksInSequence = new HashSet<ulong>(knownElements);
            //var entered = new HashSet<ulong>();
            var sb = new StringBuilder();
            sb.Append('{');
            if (links.Exists(sequenceLink))
            {
                StopableSequenceWalker.WalkRight(sequenceLink, links.GetSource, links.GetTarget,
                    x => linksInSequence.Contains(x) || links.IsPartialPoint(x), element => // entered.AddAndReturnVoid, x => { }, entered.DoNotContains
                    {
                        if (insertComma && sb.Length > 1)
                        {
                            sb.Append(',');
                        }
                        //if (entered.Contains(element))
                        //{
                        //    sb.Append('{');
                        //    elementToString(sb, element);
                        //    sb.Append('}');
                        //}
                        //else
                        elementToString(sb, element);
                        if (sb.Length < MaxSequenceFormatSize)
                        {
                            return true;
                        }
                        sb.Append(insertComma ? ", ..." : "...");
                        return false;
                    });
            }
            sb.Append('}');
            return sb.ToString();
        }

        public string SafeFormatSequence(LinkIndex sequenceLink, params LinkIndex[] knownElements) => SafeFormatSequence(sequenceLink, (sb, x) => sb.Append(x), true, knownElements);

        public string SafeFormatSequence(LinkIndex sequenceLink, Action<StringBuilder, LinkIndex> elementToString, bool insertComma, params LinkIndex[] knownElements) => Links.SyncRoot.ExecuteReadOperation(() => SafeFormatSequence(Links.Unsync, sequenceLink, elementToString, insertComma, knownElements));

        private string SafeFormatSequence(ILinks<LinkIndex> links, LinkIndex sequenceLink, Action<StringBuilder, LinkIndex> elementToString, bool insertComma, params LinkIndex[] knownElements)
        {
            var linksInSequence = new HashSet<ulong>(knownElements);
            var entered = new HashSet<ulong>();
            var sb = new StringBuilder();
            sb.Append('{');
            if (links.Exists(sequenceLink))
            {
                StopableSequenceWalker.WalkRight(sequenceLink, links.GetSource, links.GetTarget,
                    x => linksInSequence.Contains(x) || links.IsFullPoint(x),
                    ↪  entered.AddAndReturnVoid, x => { }, entered.DoNotContains, element =>
                    {
                        if (insertComma && sb.Length > 1)
                        {
                            sb.Append(',');
                        }
                        if (entered.Contains(element))
                        {
                            sb.Append('{');
                            elementToString(sb, element);
                            sb.Append('}');
                        }
                        else
                        {
                            elementToString(sb, element);
                        }
                        if (sb.Length < MaxSequenceFormatSize)
                        {
                            return true;
                        }
                        sb.Append(insertComma ? ", ..." : "...");
                        return false;
                    });
            }
            sb.Append('}');
            return sb.ToString();
        }

        public List<ulong> GetAllPartiallyMatchingSequences0(params ulong[] sequence)
        {
            return Sync.ExecuteReadOperation(() =>
            {
                if (sequence.Length > 0)
                {
                    Links.EnsureEachLinkExists(sequence);
                    var results = new HashSet<ulong>();
                    for (var i = 0; i < sequence.Length; i++)
                    {
                        AllUsagesCore(sequence[i], results);
                    }
                    var filteredResults = new List<ulong>();
                    var linksInSequence = new HashSet<ulong>(sequence);
                    foreach (var result in results)
                    {
                        var filterPosition = -1;
                        StopableSequenceWalker.WalkRight(result, Links.Unsync.GetSource,
                         ↪  Links.Unsync.GetTarget,
                            x => linksInSequence.Contains(x) || Links.Unsync.GetTarget(x) == x,
                             ↪  x =>
                            {
                                if (filterPosition == (sequence.Length - 1))
                                {
                                    return false;
                                }
                                if (filterPosition >= 0)
                                {
                                    if (x == sequence[filterPosition + 1])
                                    {
                                        filterPosition++;
                                    }
                                    else
                                    {
                                        return false;
                                    }
                                }
                                if (filterPosition < 0)
                                {
                                    if (x == sequence[0])
                                    {
                                        filterPosition = 0;
                                    }
                                }
                                return true;
                            });
                        if (filterPosition == (sequence.Length - 1))
                        {
```

```
                        filteredResults.Add(result);
                    }
                }
                return filteredResults;
            }
            return new List<ulong>();
        });
    }

    public HashSet<ulong> GetAllPartiallyMatchingSequences1(params ulong[] sequence)
    {
        return Sync.ExecuteReadOperation(() =>
        {
            if (sequence.Length > 0)
            {
                Links.EnsureEachLinkExists(sequence);
                var results = new HashSet<ulong>();
                for (var i = 0; i < sequence.Length; i++)
                {
                    AllUsagesCore(sequence[i], results);
                }
                var filteredResults = new HashSet<ulong>();
                var matcher = new Matcher(this, sequence, filteredResults, null);
                matcher.AddAllPartialMatchedToResults(results);
                return filteredResults;
            }
            return new HashSet<ulong>();
        });
    }

    public bool GetAllPartiallyMatchingSequences2(Func<ulong, bool> handler, params ulong[]
     ↪  sequence)
    {
        return Sync.ExecuteReadOperation(() =>
        {
            if (sequence.Length > 0)
            {
                Links.EnsureEachLinkExists(sequence);

                var results = new HashSet<ulong>();
                var filteredResults = new HashSet<ulong>();
                var matcher = new Matcher(this, sequence, filteredResults, handler);
                for (var i = 0; i < sequence.Length; i++)
                {
                    if (!AllUsagesCore1(sequence[i], results, matcher.HandlePartialMatched))
                    {
                        return false;
                    }
                }
                return true;
            }
            return true;
        });
    }

    //public HashSet<ulong> GetAllPartiallyMatchingSequences3(params ulong[] sequence)
    //{
    //    return Sync.ExecuteReadOperation(() =>
    //    {
    //        if (sequence.Length > 0)
    //        {
    //            _links.EnsureEachLinkIsAnyOrExists(sequence);

    //            var firstResults = new HashSet<ulong>();
    //            var lastResults = new HashSet<ulong>();

    //            var first = sequence.First(x => x != LinksConstants.Any);
    //            var last = sequence.Last(x => x != LinksConstants.Any);

    //            AllUsagesCore(first, firstResults);
    //            AllUsagesCore(last, lastResults);

    //            firstResults.IntersectWith(lastResults);

    //            //for (var i = 0; i < sequence.Length; i++)
    //            //    AllUsagesCore(sequence[i], results);

    //            var filteredResults = new HashSet<ulong>();
    //            var matcher = new Matcher(this, sequence, filteredResults, null);
```

```
        //             matcher.AddAllPartialMatchedToResults(firstResults);
        //             return filteredResults;
        //         }

        //         return new HashSet<ulong>();
        //     });
        //}

        public HashSet<ulong> GetAllPartiallyMatchingSequences3(params ulong[] sequence)
        {
            return Sync.ExecuteReadOperation(() =>
            {
                if (sequence.Length > 0)
                {
                    Links.EnsureEachLinkIsAnyOrExists(sequence);
                    var firstResults = new HashSet<ulong>();
                    var lastResults = new HashSet<ulong>();
                    var first = sequence.First(x => x != _constants.Any);
                    var last = sequence.Last(x => x != _constants.Any);
                    AllUsagesCore(first, firstResults);
                    AllUsagesCore(last, lastResults);
                    firstResults.IntersectWith(lastResults);
                    //for (var i = 0; i < sequence.Length; i++)
                    //    AllUsagesCore(sequence[i], results);
                    var filteredResults = new HashSet<ulong>();
                    var matcher = new Matcher(this, sequence, filteredResults, null);
                    matcher.AddAllPartialMatchedToResults(firstResults);
                    return filteredResults;
                }
                return new HashSet<ulong>();
            });
        }

        public HashSet<ulong> GetAllPartiallyMatchingSequences4(HashSet<ulong> readAsElements,
         ↪  IList<ulong> sequence)
        {
            return Sync.ExecuteReadOperation(() =>
            {
                if (sequence.Count > 0)
                {
                    Links.EnsureEachLinkExists(sequence);
                    var results = new HashSet<LinkIndex>();
                    //var nextResults = new HashSet<ulong>();
                    //for (var i = 0; i < sequence.Length; i++)
                    //{
                    //    AllUsagesCore(sequence[i], nextResults);
                    //    if (results.IsNullOrEmpty())
                    //    {
                    //        results = nextResults;
                    //        nextResults = new HashSet<ulong>();
                    //    }
                    //    else
                    //    {
                    //        results.IntersectWith(nextResults);
                    //        nextResults.Clear();
                    //    }
                    //}
                    var collector1 = new AllUsagesCollector1(Links.Unsync, results);
                    collector1.Collect(Links.Unsync.GetLink(sequence[0]));
                    var next = new HashSet<ulong>();
                    for (var i = 1; i < sequence.Count; i++)
                    {
                        var collector = new AllUsagesCollector1(Links.Unsync, next);
                        collector.Collect(Links.Unsync.GetLink(sequence[i]));

                        results.IntersectWith(next);
                        next.Clear();
                    }
                    var filteredResults = new HashSet<ulong>();
                    var matcher = new Matcher(this, sequence, filteredResults, null,
                     ↪  readAsElements);
                    matcher.AddAllPartialMatchedToResultsAndReadAsElements(results.OrderBy(x =>
                     ↪  x)); // OrderBy is a Hack
                    return filteredResults;
                }
                return new HashSet<ulong>();
            });
        }

        // Does not work
        public HashSet<ulong> GetAllPartiallyMatchingSequences5(HashSet<ulong> readAsElements,
         ↪  params ulong[] sequence)
        {
            var visited = new HashSet<ulong>();
            var results = new HashSet<ulong>();
            var matcher = new Matcher(this, sequence, visited, x => { results.Add(x); return
             ↪  true; }, readAsElements);
            var last = sequence.Length - 1;
            for (var i = 0; i < last; i++)
            {
                PartialStepRight(matcher.PartialMatch, sequence[i], sequence[i + 1]);
            }
            return results;
        }

        public List<ulong> GetAllPartiallyMatchingSequences(params ulong[] sequence)
        {
            return Sync.ExecuteReadOperation(() =>
            {
                if (sequence.Length > 0)
                {
                    Links.EnsureEachLinkExists(sequence);
                    //var firstElement = sequence[0];
                    //if (sequence.Length == 1)
                    //{
                    //    //results.Add(firstElement);
                    //    return results;
                    //}
                    //if (sequence.Length == 2)
                    //{
                    //    //var doublet = _links.SearchCore(firstElement, sequence[1]);
                    //    //if (doublet != Doublets.Links.Null)
                    //    //    results.Add(doublet);
                    //    return results;
                    //}
                    //var lastElement = sequence[sequence.Length - 1];
                    //Func<ulong, bool> handler = x =>
                    //{
                    //    if (StartsWith(x, firstElement) && EndsWith(x, lastElement))
                     ↪  results.Add(x);
                    //    return true;
                    //};
                    //if (sequence.Length >= 2)
                    //    StepRight(handler, sequence[0], sequence[1]);
                    //var last = sequence.Length - 2;
                    //for (var i = 1; i < last; i++)
                    //    PartialStepRight(handler, sequence[i], sequence[i + 1]);
                    //if (sequence.Length >= 3)
                    //    StepLeft(handler, sequence[sequence.Length - 2],
                     ↪  sequence[sequence.Length - 1]);
                    //////if (sequence.Length == 1)
                    //////{
                    //////    throw new NotImplementedException(); // all sequences, containing
                     ↪  this element?
                    //////}
                    //////if (sequence.Length == 2)
                    //////{
                    //////    var results = new List<ulong>();
                    //////    PartialStepRight(results.Add, sequence[0], sequence[1]);
                    //////    return results;
                    //////}
                    //////var matches = new List<List<ulong>>();
                    //////var last = sequence.Length - 1;
                    //////for (var i = 0; i < last; i++)
                    //////{
                    //////    var results = new List<ulong>();
                    //////    //StepRight(results.Add, sequence[i], sequence[i + 1]);
                    //////    PartialStepRight(results.Add, sequence[i], sequence[i + 1]);
                    //////    if (results.Count > 0)
                    //////        matches.Add(results);
                    //////    else
                    //////        return results;
                    //////    if (matches.Count == 2)
                    //////    {
                    //////        var merged = new List<ulong>();
                    //////        for (var j = 0; j < matches[0].Count; j++)
                    //////            for (var k = 0; k < matches[1].Count; k++)
                    //////                CloseInnerConnections(merged.Add, matches[0][j], matches[1][k]);
                    //////        if (merged.Count > 0)
                    //////            matches = new List<List<ulong>> { merged };
                    //////        else
                    //////            return new List<ulong>();
                    //////    }
                    //////}
                    //////if (matches.Count > 0)
                    //////{
                    //////    var usages = new HashSet<ulong>();
                    //////    for (int i = 0; i < sequence.Length; i++)
                    //////    {
                    //////        AllUsagesCore(sequence[i], usages);
                    //////    }
                    //////    //for (int i = 0; i < matches[0].Count; i++)
                    //////    //    AllUsagesCore(matches[0][i], usages);
                    //////    //usages.UnionWith(matches[0]);
                    //////    return usages.ToList();
                    //////}
                    var firstLinkUsages = new HashSet<ulong>();
                    AllUsagesCore(sequence[0], firstLinkUsages);
                    firstLinkUsages.Add(sequence[0]);
                    //var previousMatchings = firstLinkUsages.ToList(); //new List<ulong>() { sequence[0] }; // or all sequences, containing this element?
                    //return GetAllPartiallyMatchingSequencesCore(sequence, firstLinkUsages, 1).ToList();
                    var results = new HashSet<ulong>();
                    foreach (var match in GetAllPartiallyMatchingSequencesCore(sequence, firstLinkUsages, 1))
                    {
                        AllUsagesCore(match, results);
                    }
                    return results.ToList();
                }
                return new List<ulong>();
            });
        }

        /// <remarks>
        /// TODO: Может потробоваться ограничение на уровень глубины рекурсии
        /// </remarks>
        public HashSet<ulong> AllUsages(ulong link)
        {
            return Sync.ExecuteReadOperation(() =>
            {
                var usages = new HashSet<ulong>();
                AllUsagesCore(link, usages);
                return usages;
            });
        }

        // При сборе всех использований (последовательностей) можно сохранять обратный путь к той связи с которой начинался поиск (STTTSSSTT),
        // причём достаточно одного бита для хранения перехода влево или вправо
        private void AllUsagesCore(ulong link, HashSet<ulong> usages)
        {
            bool handler(ulong doublet)
            {
                if (usages.Add(doublet))
                {
                    AllUsagesCore(doublet, usages);
                }
                return true;
            }
            Links.Unsync.Each(link, _constants.Any, handler);
            Links.Unsync.Each(_constants.Any, link, handler);
        }

        public HashSet<ulong> AllBottomUsages(ulong link)
        {
            return Sync.ExecuteReadOperation(() =>
            {
                var visits = new HashSet<ulong>();
                var usages = new HashSet<ulong>();
                AllBottomUsagesCore(link, visits, usages);
                return usages;
            });
        }

        private void AllBottomUsagesCore(ulong link, HashSet<ulong> visits, HashSet<ulong>
         ↪  usages)
        {
            bool handler(ulong doublet)
            {
                if (visits.Add(doublet))
                {
                    AllBottomUsagesCore(doublet, visits, usages);
                }
                return true;
            }
            if (Links.Unsync.Count(_constants.Any, link) == 0)
            {
                usages.Add(link);
            }
            else
            {
                Links.Unsync.Each(link, _constants.Any, handler);
                Links.Unsync.Each(_constants.Any, link, handler);
            }
        }

        public ulong CalculateTotalSymbolFrequencyCore(ulong symbol)
        {
            if (Options.UseSequenceMarker)
            {
                var counter = new TotalMarkedSequenceSymbolFrequencyOneOffCounter<ulong>(Links,
                 ↪  Options.MarkedSequenceMatcher, symbol);
                return counter.Count();
            }
            else
            {
                var counter = new TotalSequenceSymbolFrequencyOneOffCounter<ulong>(Links,
                 ↪  symbol);
                return counter.Count();
            }
        }

        private bool AllUsagesCore1(ulong link, HashSet<ulong> usages, Func<ulong, bool>
         ↪  outerHandler)
        {
            bool handler(ulong doublet)
            {
                if (usages.Add(doublet))
                {
                    if (!outerHandler(doublet))
                    {
                        return false;
                    }
                    if (!AllUsagesCore1(doublet, usages, outerHandler))
                    {
                        return false;
                    }
                }
                return true;
            }
            return Links.Unsync.Each(link, _constants.Any, handler)
                && Links.Unsync.Each(_constants.Any, link, handler);
        }

        public void CalculateAllUsages(ulong[] totals)
        {
            var calculator = new AllUsagesCalculator(Links, totals);
            calculator.Calculate();
        }

        public void CalculateAllUsages2(ulong[] totals)
        {
            var calculator = new AllUsagesCalculator2(Links, totals);
            calculator.Calculate();
        }

        private class AllUsagesCalculator
        {
            private readonly SynchronizedLinks<ulong> _links;
            private readonly ulong[] _totals;

            public AllUsagesCalculator(SynchronizedLinks<ulong> links, ulong[] totals)
            {
                _links = links;
                _totals = totals;
            }

            public void Calculate() => _links.Each(_constants.Any, _constants.Any,
             ↪  CalculateCore);

            private bool CalculateCore(ulong link)
            {
                if (_totals[link] == 0)
                {
                    var total = 1UL;
                    _totals[link] = total;
                    var visitedChildren = new HashSet<ulong>();
                    bool linkCalculator(ulong child)
                    {
                        if (link != child && visitedChildren.Add(child))
                        {
                            total += _totals[child] == 0 ? 1 : _totals[child];
                        }
                        return true;
                    }
                    _links.Unsync.Each(link, _constants.Any, linkCalculator);
                    _links.Unsync.Each(_constants.Any, link, linkCalculator);
                    _totals[link] = total;
                }
                return true;
            }
        }

        private class AllUsagesCalculator2
        {
            private readonly SynchronizedLinks<ulong> _links;
            private readonly ulong[] _totals;

            public AllUsagesCalculator2(SynchronizedLinks<ulong> links, ulong[] totals)
            {
                _links = links;
                _totals = totals;
            }

            public void Calculate() => _links.Each(_constants.Any, _constants.Any,
             ↪  CalculateCore);

            private bool IsElement(ulong link)
            {
                //_linksInSequence.Contains(link) ||
                return _links.Unsync.GetTarget(link) == link || _links.Unsync.GetSource(link) ==
                 ↪  link;
            }

            private bool CalculateCore(ulong link)
            {
                // TODO: Проработать защиту от зацикливания
                // Основано на SequenceWalker.WalkLeft
                Func<ulong, ulong> getSource = _links.Unsync.GetSource;
                Func<ulong, ulong> getTarget = _links.Unsync.GetTarget;
                Func<ulong, bool> isElement = IsElement;
                void visitLeaf(ulong parent)
                {
                    if (link != parent)
                    {
                        _totals[parent]++;
                    }
                }
                void visitNode(ulong parent)
                {
                    if (link != parent)
                    {
                        _totals[parent]++;
                    }
                }
                var stack = new Stack();
                var element = link;
                if (isElement(element))
                {
                    visitLeaf(element);
                }
                else
                {
                    while (true)
                    {
                        if (isElement(element))
                        {
                            if (stack.Count == 0)
                            {
                                break;
                            }
                            element = stack.Pop();
                            var source = getSource(element);
                            var target = getTarget(element);
                            // Обработка элемента
                            if (isElement(target))
                            {
                                visitLeaf(target);
                            }
                            if (isElement(source))
                            {
                                visitLeaf(source);
                            }
                            element = source;
                        }
                        else
                        {
                            stack.Push(element);
                            visitNode(element);
                            element = getTarget(element);
                        }
                    }
                }
                _totals[link]++;
                return true;
            }
        }

        private class AllUsagesCollector
        {
            private readonly ILinks<ulong> _links;
            private readonly HashSet<ulong> _usages;

            public AllUsagesCollector(ILinks<ulong> links, HashSet<ulong> usages)
            {
                _links = links;
                _usages = usages;
            }

            public bool Collect(ulong link)
            {
                if (_usages.Add(link))
                {
                    _links.Each(link, _constants.Any, Collect);
                    _links.Each(_constants.Any, link, Collect);
                }
                return true;
            }
        }

        private class AllUsagesCollector1
        {
            private readonly ILinks<ulong> _links;
            private readonly HashSet<ulong> _usages;
            private readonly ulong _continue;

            public AllUsagesCollector1(ILinks<ulong> links, HashSet<ulong> usages)
            {
                _links = links;
                _usages = usages;
                _continue = _links.Constants.Continue;
            }

            public ulong Collect(IList<ulong> link)
            {
                var linkIndex = _links.GetIndex(link);
                if (_usages.Add(linkIndex))
                {
                    _links.Each(Collect, _constants.Any, linkIndex);
                }
                return _continue;
            }
        }

        private class AllUsagesCollector2
        {
            private readonly ILinks<ulong> _links;
            private readonly BitString _usages;

            public AllUsagesCollector2(ILinks<ulong> links, BitString usages)
            {
                _links = links;
                _usages = usages;
            }

            public bool Collect(ulong link)
            {
                if (_usages.Add((long)link))
                {
                    _links.Each(link, _constants.Any, Collect);
                    _links.Each(_constants.Any, link, Collect);
                }
                return true;
            }
        }

        private class AllUsagesIntersectingCollector
        {
            private readonly SynchronizedLinks<ulong> _links;
            private readonly HashSet<ulong> _intersectWith;
            private readonly HashSet<ulong> _usages;
            private readonly HashSet<ulong> _enter;

            public AllUsagesIntersectingCollector(SynchronizedLinks<ulong> links, HashSet<ulong>
            ↪  intersectWith, HashSet<ulong> usages)
            {
                _links = links;
                _intersectWith = intersectWith;
                _usages = usages;
                _enter = new HashSet<ulong>(); // защита от зацикливания
            }

            public bool Collect(ulong link)
            {
                if (_enter.Add(link))
                {
                    if (_intersectWith.Contains(link))
                    {
                        _usages.Add(link);
                    }
                    _links.Unsync.Each(link, _constants.Any, Collect);
                    _links.Unsync.Each(_constants.Any, link, Collect);
                }
                return true;
            }
        }

        private void CloseInnerConnections(Action<ulong> handler, ulong left, ulong right)
        {
            TryStepLeftUp(handler, left, right);
            TryStepRightUp(handler, right, left);
        }

        private void AllCloseConnections(Action<ulong> handler, ulong left, ulong right)
        {
            // Direct
            if (left == right)
            {
                handler(left);
            }
            var doublet = Links.Unsync.SearchOrDefault(left, right);
            if (doublet != _constants.Null)
            {
                handler(doublet);
            }
            // Inner
            CloseInnerConnections(handler, left, right);
            // Outer
            StepLeft(handler, left, right);
            StepRight(handler, left, right);
            PartialStepRight(handler, left, right);
            PartialStepLeft(handler, left, right);
        }

        private HashSet<ulong> GetAllPartiallyMatchingSequencesCore(ulong[] sequence, HashSet<ulong> previousMatchings, long startAt)
        {
            if (startAt >= sequence.Length) // ?
            {
                return previousMatchings;
            }
            var secondLinkUsages = new HashSet<ulong>();
            AllUsagesCore(sequence[startAt], secondLinkUsages);
            secondLinkUsages.Add(sequence[startAt]);
            var matchings = new HashSet<ulong>();
            //for (var i = 0; i < previousMatchings.Count; i++)
            foreach (var secondLinkUsage in secondLinkUsages)
            {
                foreach (var previousMatching in previousMatchings)
                {
                    //AllCloseConnections(matchings.AddAndReturnVoid, previousMatching, secondLinkUsage);
                    StepRight(matchings.AddAndReturnVoid, previousMatching, secondLinkUsage);
                    TryStepRightUp(matchings.AddAndReturnVoid, secondLinkUsage, previousMatching);
                    //PartialStepRight(matchings.AddAndReturnVoid, secondLinkUsage, sequence[startAt]); // почему-то эта ошибочная запись приводит к желаемым результам.
                    PartialStepRight(matchings.AddAndReturnVoid, previousMatching, secondLinkUsage);
                }
            }
            if (matchings.Count == 0)
            {
                return matchings;
            }
            return GetAllPartiallyMatchingSequencesCore(sequence, matchings, startAt + 1); // ??
        }

        private static void EnsureEachLinkIsAnyOrZeroOrManyOrExists(SynchronizedLinks<ulong> links, params ulong[] sequence)
        {
            if (sequence == null)
            {
                return;
            }
            for (var i = 0; i < sequence.Length; i++)
            {
                if (sequence[i] != _constants.Any && sequence[i] != ZeroOrMany && !links.Exists(sequence[i]))
                {
                    throw new ArgumentLinkDoesNotExistsException<ulong>(sequence[i], $"patternSequence[{i}]");
                }
            }
        }

        // Pattern Matching -> Key To Triggers
        public HashSet<ulong> MatchPattern(params ulong[] patternSequence)
        {
            return Sync.ExecuteReadOperation(() =>
            {
                patternSequence = Simplify(patternSequence);
                if (patternSequence.Length > 0)
                {
                    EnsureEachLinkIsAnyOrZeroOrManyOrExists(Links, patternSequence);
                    var uniqueSequenceElements = new HashSet<ulong>();
                    for (var i = 0; i < patternSequence.Length; i++)
                    {
                        if (patternSequence[i] != _constants.Any && patternSequence[i] != ZeroOrMany)
                        {
                            uniqueSequenceElements.Add(patternSequence[i]);
                    }
                }
                var results = new HashSet<ulong>();
                foreach (var uniqueSequenceElement in uniqueSequenceElements)
                {
                    AllUsagesCore(uniqueSequenceElement, results);
                }
                var filteredResults = new HashSet<ulong>();
                var matcher = new PatternMatcher(this, patternSequence, filteredResults);
                matcher.AddAllPatternMatchedToResults(results);
                return filteredResults;
            }
            return new HashSet<ulong>();
        });
    }

    // Найти все возможные связи между указанным списком связей.
    // Находит связи между всеми указанными связями в любом порядке.
    // TODO: решить что делать с повторами (когда одни и те же элементы встречаются
    ↪  несколько раз в последовательности)
    public HashSet<ulong> GetAllConnections(params ulong[] linksToConnect)
    {
        return Sync.ExecuteReadOperation(() =>
        {
            var results = new HashSet<ulong>();
            if (linksToConnect.Length > 0)
            {
                Links.EnsureEachLinkExists(linksToConnect);
                AllUsagesCore(linksToConnect[0], results);
                for (var i = 1; i < linksToConnect.Length; i++)
                {
                    var next = new HashSet<ulong>();
                    AllUsagesCore(linksToConnect[i], next);
                    results.IntersectWith(next);
                }
            }
            return results;
        });
    }

    public HashSet<ulong> GetAllConnections1(params ulong[] linksToConnect)
    {
        return Sync.ExecuteReadOperation(() =>
        {
            var results = new HashSet<ulong>();
            if (linksToConnect.Length > 0)
            {
                Links.EnsureEachLinkExists(linksToConnect);
                var collector1 = new AllUsagesCollector(Links.Unsync, results);
                collector1.Collect(linksToConnect[0]);
                var next = new HashSet<ulong>();
                for (var i = 1; i < linksToConnect.Length; i++)
                {
                    var collector = new AllUsagesCollector(Links.Unsync, next);
                    collector.Collect(linksToConnect[i]);
                    results.IntersectWith(next);
                    next.Clear();
                }
            }
            return results;
        });
    }

    public HashSet<ulong> GetAllConnections2(params ulong[] linksToConnect)
    {
        return Sync.ExecuteReadOperation(() =>
        {
            var results = new HashSet<ulong>();
            if (linksToConnect.Length > 0)
            {
                Links.EnsureEachLinkExists(linksToConnect);
                var collector1 = new AllUsagesCollector(Links, results);
                collector1.Collect(linksToConnect[0]);
                //AllUsagesCore(linksToConnect[0], results);
                for (var i = 1; i < linksToConnect.Length; i++)
                {
                    var next = new HashSet<ulong>();
                    var collector = new AllUsagesIntersectingCollector(Links, results, next);
                    collector.Collect(linksToConnect[i]);
                    //AllUsagesCore(linksToConnect[i], next);
                    //results.IntersectWith(next);
                    results = next;
                }
            }
            return results;
        });
    }

    public List<ulong> GetAllConnections3(params ulong[] linksToConnect)
    {
        return Sync.ExecuteReadOperation(() =>
        {
            var results = new BitString((long)Links.Unsync.Count() + 1); // new
            ↪  BitArray((int)_links.Total + 1);
            if (linksToConnect.Length > 0)
            {
                Links.EnsureEachLinkExists(linksToConnect);
                var collector1 = new AllUsagesCollector2(Links.Unsync, results);
                collector1.Collect(linksToConnect[0]);
                for (var i = 1; i < linksToConnect.Length; i++)
                {
                    var next = new BitString((long)Links.Unsync.Count() + 1); //new
                    ↪  BitArray((int)_links.Total + 1);
                    var collector = new AllUsagesCollector2(Links.Unsync, next);
                    collector.Collect(linksToConnect[i]);
                    results = results.And(next);
                }
            }
            return results.GetSetUInt64Indices();
        });
    }

    private static ulong[] Simplify(ulong[] sequence)
    {
        // Считаем новый размер последовательности
        long newLength = 0;
        var zeroOrManyStepped = false;
        for (var i = 0; i < sequence.Length; i++)
        {
            if (sequence[i] == ZeroOrMany)
            {
                if (zeroOrManyStepped)
                {
                    continue;
                }
                zeroOrManyStepped = true;
            }
            else
            {
                //if (zeroOrManyStepped) Is it efficient?
                zeroOrManyStepped = false;
            }
            newLength++;
        }
        // Строим новую последовательность
        zeroOrManyStepped = false;
        var newSequence = new ulong[newLength];
        long j = 0;
        for (var i = 0; i < sequence.Length; i++)
        {
            //var current = zeroOrManyStepped;
            //zeroOrManyStepped = patternSequence[i] == zeroOrMany;
            //if (current && zeroOrManyStepped)
            //    continue;
            //var newZeroOrManyStepped = patternSequence[i] == zeroOrMany;
            //if (zeroOrManyStepped && newZeroOrManyStepped)
            //    continue;
            //zeroOrManyStepped = newZeroOrManyStepped;
            if (sequence[i] == ZeroOrMany)
            {
                if (zeroOrManyStepped)
                {
                    continue;
                }
                zeroOrManyStepped = true;
            }
            else
```

```
                {
                    //if (zeroOrManyStepped) Is it efficient?
                    zeroOrManyStepped = false;
                }
                newSequence[j++] = sequence[i];
            }
            return newSequence;
        }

        public static void TestSimplify()
        {
            var sequence = new ulong[] { ZeroOrMany, ZeroOrMany, 2, 3, 4, ZeroOrMany,
             ↪  ZeroOrMany, ZeroOrMany, 4, ZeroOrMany, ZeroOrMany, ZeroOrMany };
            var simplifiedSequence = Simplify(sequence);
        }

        public List<ulong> GetSimilarSequences() => new List<ulong>();

        public void Prediction()
        {
            //_links
            //sequences
        }

        #region From Triplets

        //public static void DeleteSequence(Link sequence)
        //{
        //}

        public List<ulong> CollectMatchingSequences(ulong[] links)
        {
            if (links.Length == 1)
            {
                throw new Exception("Подпоследовательности с одним элементом не
                 ↪  поддерживаются.");
            }
            var leftBound = 0;
            var rightBound = links.Length - 1;
            var left = links[leftBound++];
            var right = links[rightBound--];
            var results = new List<ulong>();
            CollectMatchingSequences(left, leftBound, links, right, rightBound, ref results);
            return results;
        }

        private void CollectMatchingSequences(ulong leftLink, int leftBound, ulong[]
        ↪  middleLinks, ulong rightLink, int rightBound, ref List<ulong> results)
        {
            var leftLinkTotalReferers = Links.Unsync.Count(leftLink);
            var rightLinkTotalReferers = Links.Unsync.Count(rightLink);
            if (leftLinkTotalReferers <= rightLinkTotalReferers)
            {
                var nextLeftLink = middleLinks[leftBound];
                var elements = GetRightElements(leftLink, nextLeftLink);
                if (leftBound <= rightBound)
                {
                    for (var i = elements.Length - 1; i >= 0; i--)
                    {
                        var element = elements[i];
                        if (element != 0)
                        {
                            CollectMatchingSequences(element, leftBound + 1, middleLinks,
                             ↪  rightLink, rightBound, ref results);
                        }
                    }
                }
                else
                {
                    for (var i = elements.Length - 1; i >= 0; i--)
                    {
                        var element = elements[i];
                        if (element != 0)
                        {
                            results.Add(element);
                        }
                    }
                }
            }
            else
            {
                var nextRightLink = middleLinks[rightBound];
                var elements = GetLeftElements(rightLink, nextRightLink);
                if (leftBound <= rightBound)
                {
                    for (var i = elements.Length - 1; i >= 0; i--)
                    {
                        var element = elements[i];
                        if (element != 0)
                        {
                            CollectMatchingSequences(leftLink, leftBound, middleLinks,
                             ↪  elements[i], rightBound - 1, ref results);
                        }
                    }
                }
                else
                {
                    for (var i = elements.Length - 1; i >= 0; i--)
                    {
                        var element = elements[i];
                        if (element != 0)
                        {
                            results.Add(element);
                        }
                    }
                }
            }
        }

        public ulong[] GetRightElements(ulong startLink, ulong rightLink)
        {
            var result = new ulong[5];
            TryStepRight(startLink, rightLink, result, 0);
            Links.Each(_constants.Any, startLink, couple =>
            {
                if (couple != startLink)
                {
                    if (TryStepRight(couple, rightLink, result, 2))
                    {
                        return false;
                    }
                }
                return true;
            });
            if (Links.GetTarget(Links.GetTarget(startLink)) == rightLink)
            {
                result[4] = startLink;
            }
            return result;
        }

        public bool TryStepRight(ulong startLink, ulong rightLink, ulong[] result, int offset)
        {
            var added = 0;
            Links.Each(startLink, _constants.Any, couple =>
            {
                if (couple != startLink)
                {
                    var coupleTarget = Links.GetTarget(couple);
                    if (coupleTarget == rightLink)
                    {
                        result[offset] = couple;
                        if (++added == 2)
                        {
                            return false;
                        }
                    }
                    else if (Links.GetSource(coupleTarget) == rightLink) // coupleTarget.Linker
                     ↪  == Net.And &&
                    {
                        result[offset + 1] = couple;
                        if (++added == 2)
                        {
                            return false;
                        }
                    }
                }
                return true;
            });
            return added > 0;
        }

        public ulong[] GetLeftElements(ulong startLink, ulong leftLink)
        {
            var result = new ulong[5];
            TryStepLeft(startLink, leftLink, result, 0);
            Links.Each(startLink, _constants.Any, couple =>
            {
                if (couple != startLink)
                {
                    if (TryStepLeft(couple, leftLink, result, 2))
                    {
                        return false;
                    }
                }
                return true;
            });
            if (Links.GetSource(Links.GetSource(leftLink)) == startLink)
            {
                result[4] = leftLink;
            }
            return result;
        }

        public bool TryStepLeft(ulong startLink, ulong leftLink, ulong[] result, int offset)
        {
            var added = 0;
            Links.Each(_constants.Any, startLink, couple =>
            {
                if (couple != startLink)
                {
                    var coupleSource = Links.GetSource(couple);
                    if (coupleSource == leftLink)
                    {
                        result[offset] = couple;
                        if (++added == 2)
                        {
                            return false;
                        }
                    }
                    else if (Links.GetTarget(coupleSource) == leftLink) // coupleSource.Linker
                     ↪  == Net.And &&
                    {
                        result[offset + 1] = couple;
                        if (++added == 2)
                        {
                            return false;
                        }
                    }
                }
                return true;
            });
            return added > 0;
        }

        #endregion

        #region Walkers

        public class PatternMatcher : RightSequenceWalker<ulong>
        {
            private readonly Sequences _sequences;
            private readonly ulong[] _patternSequence;
            private readonly HashSet<LinkIndex> _linksInSequence;
            private readonly HashSet<LinkIndex> _results;

            #region Pattern Match

            enum PatternBlockType
            {
                Undefined,
                Gap,
                Elements
            }

            struct PatternBlock
            {
                public PatternBlockType Type;
                public long Start;
                public long Stop;
            }

            private readonly List<PatternBlock> _pattern;
            private int _patternPosition;
            private long _sequencePosition;

            #endregion

            public PatternMatcher(Sequences sequences, LinkIndex[] patternSequence,
             ↪  HashSet<LinkIndex> results)
                : base(sequences.Links.Unsync, new DefaultStack<ulong>())
            {
                _sequences = sequences;
                _patternSequence = patternSequence;
                _linksInSequence = new HashSet<LinkIndex>(patternSequence.Where(x => x !=
                 ↪  _constants.Any && x != ZeroOrMany));
                _results = results;
                _pattern = CreateDetailedPattern();
            }

            protected override bool IsElement(IList<ulong> link) =>
             ↪  _linksInSequence.Contains(Links.GetIndex(link)) || base.IsElement(link);

            public bool PatternMatch(LinkIndex sequenceToMatch)
            {
                _patternPosition = 0;
                _sequencePosition = 0;
                foreach (var part in Walk(sequenceToMatch))
                {
                    if (!PatternMatchCore(Links.GetIndex(part)))
                    {
                        break;
                    }
                }
                return _patternPosition == _pattern.Count || (_patternPosition == _pattern.Count
                 ↪  - 1 && _pattern[_patternPosition].Start == 0);
            }

            private List<PatternBlock> CreateDetailedPattern()
            {
                var pattern = new List<PatternBlock>();
                var patternBlock = new PatternBlock();
                for (var i = 0; i < _patternSequence.Length; i++)
                {
                    if (patternBlock.Type == PatternBlockType.Undefined)
                    {
                        if (_patternSequence[i] == _constants.Any)
                        {
                            patternBlock.Type = PatternBlockType.Gap;
                            patternBlock.Start = 1;
                            patternBlock.Stop = 1;
                        }
                        else if (_patternSequence[i] == ZeroOrMany)
                        {
                            patternBlock.Type = PatternBlockType.Gap;
                            patternBlock.Start = 0;
                            patternBlock.Stop = long.MaxValue;
                        }
                        else
                        {
                            patternBlock.Type = PatternBlockType.Elements;
                            patternBlock.Start = i;
                            patternBlock.Stop = i;
                        }
                    }
                    else if (patternBlock.Type == PatternBlockType.Elements)
                    {
                        if (_patternSequence[i] == _constants.Any)
                        {
                            pattern.Add(patternBlock);
                            patternBlock = new PatternBlock
                            {
                                Type = PatternBlockType.Gap,
                                Start = 1,
                                Stop = 1
                            };
                    }
                    else if (_patternSequence[i] == ZeroOrMany)
                    {
                        pattern.Add(patternBlock);
                        patternBlock = new PatternBlock
                        {
                            Type = PatternBlockType.Gap,
                            Start = 0,
                            Stop = long.MaxValue
                        };
                    }
                    else
                    {
                        patternBlock.Stop = i;
                    }
                }
                else // patternBlock.Type == PatternBlockType.Gap
                {
                    if (_patternSequence[i] == _constants.Any)
                    {
                        patternBlock.Start++;
                        if (patternBlock.Stop < patternBlock.Start)
                        {
                            patternBlock.Stop = patternBlock.Start;
                        }
                    }
                    else if (_patternSequence[i] == ZeroOrMany)
                    {
                        patternBlock.Stop = long.MaxValue;
                    }
                    else
                    {
                        pattern.Add(patternBlock);
                        patternBlock = new PatternBlock
                        {
                            Type = PatternBlockType.Elements,
                            Start = i,
                            Stop = i
                        };
                    }
                }
            }
            if (patternBlock.Type != PatternBlockType.Undefined)
            {
                pattern.Add(patternBlock);
            }
            return pattern;
        }

        ///* match: search for regexp anywhere in text */
        //int match(char* regexp, char* text)
        //{
        //    do
        //    {
        //    } while (*text++ != '\0');
        //    return 0;
        //}

        ///* matchhere: search for regexp at beginning of text */
        //int matchhere(char* regexp, char* text)
        //{
        //    if (regexp[0] == '\0')
        //        return 1;
        //    if (regexp[1] == '*')
        //        return matchstar(regexp[0], regexp + 2, text);
        //    if (regexp[0] == '$' && regexp[1] == '\0')
        //        return *text == '\0';
        //    if (*text != '\0' && (regexp[0] == '.' || regexp[0] == *text))
        //        return matchhere(regexp + 1, text + 1);
        //    return 0;
        //}

        ///* matchstar: search for c*regexp at beginning of text */
        //int matchstar(int c, char* regexp, char* text)
        //{
        //    do
        //    {    /* a * matches zero or more instances */
        //        if (matchhere(regexp, text))
        //            return 1;
```

```
            //    } while (*text != '\0' && (*text++ == c || c == '.'));
            //    return 0;
            //}

            //private void GetNextPatternElement(out LinkIndex element, out long mininumGap, out
            ↪  long maximumGap)
            //{
            //    mininumGap = 0;
            //    maximumGap = 0;
            //    element = 0;
            //    for (; _patternPosition < _patternSequence.Length; _patternPosition++)
            //    {
            //        if (_patternSequence[_patternPosition] == Doublets.Links.Null)
            //            mininumGap++;
            //        else if (_patternSequence[_patternPosition] == ZeroOrMany)
            //            maximumGap = long.MaxValue;
            //        else
            //            break;
            //    }

            //    if (maximumGap < mininumGap)
            //        maximumGap = mininumGap;
            //}

            private bool PatternMatchCore(LinkIndex element)
            {
                if (_patternPosition >= _pattern.Count)
                {
                    _patternPosition = -2;
                    return false;
                }
                var currentPatternBlock = _pattern[_patternPosition];
                if (currentPatternBlock.Type == PatternBlockType.Gap)
                {
                    //var currentMatchingBlockLength = (_sequencePosition -
                     ↪  _lastMatchedBlockPosition);
                    if (_sequencePosition < currentPatternBlock.Start)
                    {
                        _sequencePosition++;
                        return true; // Двигаемся дальше
                    }
                    // Это последний блок
                    if (_pattern.Count == _patternPosition + 1)
                    {
                        _patternPosition++;
                        _sequencePosition = 0;
                        return false; // Полное соответствие
                    }
                    else
                    {
                        if (_sequencePosition > currentPatternBlock.Stop)
                        {
                            return false; // Соответствие невозможно
                        }
                        var nextPatternBlock = _pattern[_patternPosition + 1];
                        if (_patternSequence[nextPatternBlock.Start] == element)
                        {
                            if (nextPatternBlock.Start < nextPatternBlock.Stop)
                            {
                                _patternPosition++;
                                _sequencePosition = 1;
                            }
                            else
                            {
                                _patternPosition += 2;
                                _sequencePosition = 0;
                            }
                        }
                    }
                }
                else // currentPatternBlock.Type == PatternBlockType.Elements
                {
                    var patternElementPosition = currentPatternBlock.Start + _sequencePosition;
                    if (_patternSequence[patternElementPosition] != element)
                    {
                        return false; // Соответствие невозможно
                    }
                    if (patternElementPosition == currentPatternBlock.Stop)
                    {
                            _patternPosition++;
                            _sequencePosition = 0;
                        }
                        else
                        {
                            _sequencePosition++;
                        }
                    }
                    return true;
                    //if (_patternSequence[_patternPosition] != element)
                    //    return false;
                    //else
                    //{
                    //    _sequencePosition++;
                    //    _patternPosition++;
                    //    return true;
                    //}
                    ////////
                    //if (_filterPosition == _patternSequence.Length)
                    //{
                    //    _filterPosition = -2; // Длиннее чем нужно
                    //    return false;
                    //}
                    //if (element != _patternSequence[_filterPosition])
                    //{
                    //    _filterPosition = -1;
                    //    return false; // Начинается иначе
                    //}
                    //_filterPosition++;
                    //if (_filterPosition == (_patternSequence.Length - 1))
                    //    return false;
                    //if (_filterPosition >= 0)
                    //{
                    //    if (element == _patternSequence[_filterPosition + 1])
                    //        _filterPosition++;
                    //    else
                    //        return false;
                    //}
                    //if (_filterPosition < 0)
                    //{
                    //    if (element == _patternSequence[0])
                    //        _filterPosition = 0;
                    //}
                }

                public void AddAllPatternMatchedToResults(IEnumerable<ulong> sequencesToMatch)
                {
                    foreach (var sequenceToMatch in sequencesToMatch)
                    {
                        if (PatternMatch(sequenceToMatch))
                        {
                            _results.Add(sequenceToMatch);
                        }
                    }
                }
            }

            #endregion
        }
    }
```

./Platform.Data.Doublets/Sequences/Sequences.Experiments.ReadSequence.cs

```
//#define USEARRAYPOOL
using System;
using System.Runtime.CompilerServices;
#if USEARRAYPOOL
using Platform.Collections;
#endif

namespace Platform.Data.Doublets.Sequences
{
    partial class Sequences
    {
        public ulong[] ReadSequenceCore(ulong sequence, Func<ulong, bool> isElement)
        {
            var links = Links.Unsync;
            var length = 1;
            var array = new ulong[length];
            array[0] = sequence;

            if (isElement(sequence))
            {
                return array;
            }

            bool hasElements;
            do
            {
                length *= 2;
#if USEARRAYPOOL
                var nextArray = ArrayPool.Allocate<ulong>(length);
#else
                var nextArray = new ulong[length];
#endif
                hasElements = false;
                for (var i = 0; i < array.Length; i++)
                {
                    var candidate = array[i];
                    if (candidate == 0)
                    {
                        continue;
                    }
                    var doubletOffset = i * 2;
                    if (isElement(candidate))
                    {
                        nextArray[doubletOffset] = candidate;
                    }
                    else
                    {
                        var link = links.GetLink(candidate);
                        var linkSource = links.GetSource(link);
                        var linkTarget = links.GetTarget(link);
                        nextArray[doubletOffset] = linkSource;
                        nextArray[doubletOffset + 1] = linkTarget;
                        if (!hasElements)
                        {
                            hasElements = !(isElement(linkSource) && isElement(linkTarget));
                        }
                    }
                }
#if USEARRAYPOOL
                if (array.Length > 1)
                {
                    ArrayPool.Free(array);
                }
#endif
                array = nextArray;
            }
            while (hasElements);
            var filledElementsCount = CountFilledElements(array);
            if (filledElementsCount == array.Length)
            {
                return array;
            }
            else
            {
                return CopyFilledElements(array, filledElementsCount);
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private static ulong[] CopyFilledElements(ulong[] array, int filledElementsCount)
        {
            var finalArray = new ulong[filledElementsCount];
            for (int i = 0, j = 0; i < array.Length; i++)
            {
                if (array[i] > 0)
                {
                    finalArray[j] = array[i];
                    j++;
                }
            }
#if USEARRAYPOOL
                ArrayPool.Free(array);
#endif
            return finalArray;
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private static int CountFilledElements(ulong[] array)
        {
            var count = 0;
            for (var i = 0; i < array.Length; i++)
            {
                if (array[i] > 0)
                {
                    count++;
                }
            }
            return count;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/SequencesExtensions.cs

```
using Platform.Data.Sequences;
using System.Collections.Generic;

namespace Platform.Data.Doublets.Sequences
{
    public static class SequencesExtensions
    {
        public static TLink Create<TLink>(this ISequences<TLink> sequences, IList<TLink[]>
         ↪  groupedSequence)
        {
            var finalSequence = new TLink[groupedSequence.Count];
            for (var i = 0; i < finalSequence.Length; i++)
            {
                var part = groupedSequence[i];
                finalSequence[i] = part.Length == 1 ? part[0] : sequences.Create(part);
            }
            return sequences.Create(finalSequence);
        }
    }
}
```

./Platform.Data.Doublets/Sequences/SequencesIndexer.cs

```
using System.Collections.Generic;

namespace Platform.Data.Doublets.Sequences
{
    public class SequencesIndexer<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;

        private readonly ISynchronizedLinks<TLink> _links;
        private readonly TLink _null;

        public SequencesIndexer(ISynchronizedLinks<TLink> links)
        {
            _links = links;
            _null = _links.Constants.Null;
        }

        /// <summary>
        /// Индексирует последовательность глобально, и возвращает значение,
        /// определяющие была ли запрошенная последовательность проиндексирована ранее.
        /// </summary>
        /// <param name="sequence">Последовательность для индексации.</param>
        /// <returns>
        /// True если последовательность уже была проиндексирована ранее и
        /// False если последовательность была проиндексирована только что.
        /// </returns>
        public bool Index(TLink[] sequence)
        {
            var indexed = true;
            var i = sequence.Length;
            while (--i >= 1 && (indexed =
             ↪  !_equalityComparer.Equals(_links.SearchOrDefault(sequence[i - 1], sequence[i]),
             ↪  _null))) { }
            for (; i >= 1; i--)
            {
                _links.GetOrCreate(sequence[i - 1], sequence[i]);
            }
            return indexed;
        }

        public bool BulkIndex(TLink[] sequence)
        {
            var indexed = true;
            var i = sequence.Length;
            var links = _links.Unsync;
            _links.SyncRoot.ExecuteReadOperation(() =>
            {
                while (--i >= 1 && (indexed =
                 ↪  !_equalityComparer.Equals(links.SearchOrDefault(sequence[i - 1],
                 ↪  sequence[i]), _null))) { }
            });
            if (indexed == false)
            {
                _links.SyncRoot.ExecuteWriteOperation(() =>
                {
                    for (; i >= 1; i--)
                    {
                        links.GetOrCreate(sequence[i - 1], sequence[i]);
                    }
                });
            }
            return indexed;
        }

        public bool BulkIndexUnsync(TLink[] sequence)
        {
            var indexed = true;
            var i = sequence.Length;
            var links = _links.Unsync;
            while (--i >= 1 && (indexed =
             ↪  !_equalityComparer.Equals(links.SearchOrDefault(sequence[i - 1], sequence[i]),
             ↪  _null))) { }
            for (; i >= 1; i--)
            {
                links.GetOrCreate(sequence[i - 1], sequence[i]);
            }
            return indexed;
        }

        public bool CheckIndex(IList<TLink> sequence)
        {
            var indexed = true;
            var i = sequence.Count;
            while (--i >= 1 && (indexed =
             ↪  !_equalityComparer.Equals(_links.SearchOrDefault(sequence[i - 1], sequence[i]),
             ↪  _null))) { }
            return indexed;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/SequencesOptions.cs

```
using System;
using System.Collections.Generic;
using Platform.Interfaces;
using Platform.Data.Doublets.Sequences.Frequencies.Cache;
using Platform.Data.Doublets.Sequences.Frequencies.Counters;
using Platform.Data.Doublets.Sequences.Converters;
using Platform.Data.Doublets.Sequences.CreteriaMatchers;

namespace Platform.Data.Doublets.Sequences
{
    public class SequencesOptions<TLink> // TODO: To use type parameter <TLink> the
     ↪  ILinks<TLink> must contain GetConstants function.
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;

        public TLink SequenceMarkerLink { get; set; }
        public bool UseCascadeUpdate { get; set; }
        public bool UseCascadeDelete { get; set; }
        public bool UseIndex { get; set; } // TODO: Update Index on sequence update/delete.
        public bool UseSequenceMarker { get; set; }
        public bool UseCompression { get; set; }
        public bool UseGarbageCollection { get; set; }
        public bool EnforceSingleSequenceVersionOnWriteBasedOnExisting { get; set; }
        public bool EnforceSingleSequenceVersionOnWriteBasedOnNew { get; set; }

        public MarkedSequenceCriterionMatcher<TLink> MarkedSequenceMatcher { get; set; }
        public IConverter<IList<TLink>, TLink> LinksToSequenceConverter { get; set; }
        public SequencesIndexer<TLink> Indexer { get; set; }

        // TODO: Реализовать компактификацию при чтении
        //public bool EnforceSingleSequenceVersionOnRead { get; set; }
        //public bool UseRequestMarker { get; set; }
        //public bool StoreRequestResults { get; set; }

        public void InitOptions(ISynchronizedLinks<TLink> links)
        {
            if (UseSequenceMarker)
            {
                if (_equalityComparer.Equals(SequenceMarkerLink, links.Constants.Null))
                {
                    SequenceMarkerLink = links.CreatePoint();
                }
                else
                {
                    if (!links.Exists(SequenceMarkerLink))
                    {
                        var link = links.CreatePoint();
                        if (!_equalityComparer.Equals(link, SequenceMarkerLink))
                        {
                            throw new InvalidOperationException("Cannot recreate sequence marker
                            ↪  link.");
                        }
                    }
                }
                if (MarkedSequenceMatcher == null)
                {
                    MarkedSequenceMatcher = new MarkedSequenceCriterionMatcher<TLink>(links,
                    ↪  SequenceMarkerLink);
                }
            }
            var balancedVariantConverter = new BalancedVariantConverter<TLink>(links);
            if (UseCompression)
            {
                if (LinksToSequenceConverter == null)
                {
                    ICounter<TLink, TLink> totalSequenceSymbolFrequencyCounter;
                    if (UseSequenceMarker)
                    {
                        totalSequenceSymbolFrequencyCounter = new
                        ↪  TotalMarkedSequenceSymbolFrequencyCounter<TLink>(links,
                        ↪  MarkedSequenceMatcher);
                    }
                    else
                    {
                        totalSequenceSymbolFrequencyCounter = new
                        ↪  TotalSequenceSymbolFrequencyCounter<TLink>(links);
                    }
                    var doubletFrequenciesCache = new LinkFrequenciesCache<TLink>(links,
                    ↪  totalSequenceSymbolFrequencyCounter);
                    var compressingConverter = new CompressingConverter<TLink>(links,
                    ↪  balancedVariantConverter, doubletFrequenciesCache);
                    LinksToSequenceConverter = compressingConverter;
                }
            }
            else
            {
                if (LinksToSequenceConverter == null)
                {
                    LinksToSequenceConverter = balancedVariantConverter;
                }
            }
            if (UseIndex && Indexer == null)
            {
                Indexer = new SequencesIndexer<TLink>(links);
            }
        }

        public void ValidateOptions()
        {
            if (UseGarbageCollection && !UseSequenceMarker)
            {
                throw new NotSupportedException("To use garbage collection UseSequenceMarker
                ↪  option must be on.");
            }
        }
    }
}
```

./Platform.Data.Doublets/Sequences/UnicodeMap.cs

```
using System;
using System.Collections.Generic;
using System.Globalization;
using System.Runtime.CompilerServices;
using System.Text;
using Platform.Data.Sequences;

namespace Platform.Data.Doublets.Sequences
{
    public class UnicodeMap
    {
        public static readonly ulong FirstCharLink = 1;
        public static readonly ulong LastCharLink = FirstCharLink + char.MaxValue;
        public static readonly ulong MapSize = 1 + char.MaxValue;

        private readonly ILinks<ulong> _links;
        private bool _initialized;

        public UnicodeMap(ILinks<ulong> links) => _links = links;

        public static UnicodeMap InitNew(ILinks<ulong> links)
        {
            var map = new UnicodeMap(links);
            map.Init();
            return map;
        }

        public void Init()
        {
            if (_initialized)
            {
                return;
            }
            _initialized = true;
            var firstLink = _links.CreatePoint();
            if (firstLink != FirstCharLink)
            {
                _links.Delete(firstLink);
            }
            else
            {
                for (var i = FirstCharLink + 1; i <= LastCharLink; i++)
                {
                    // From NIL to It (NIL -> Character) transformation meaning, (or infinite
                     ↪  amount of NIL characters before actual Character)
                    var createdLink = _links.CreatePoint();
                    _links.Update(createdLink, firstLink, createdLink);
                    if (createdLink != i)
                    {
                        throw new InvalidOperationException("Unable to initialize UTF 16
                         ↪  table.");
                    }
                }
            }
        }

        // 0 - null link
        // 1 - nil character (0 character)
        // ...
        // 65536 (0(1) + 65535 = 65536 possible values)

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static ulong FromCharToLink(char character) => (ulong)character + 1;

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static char FromLinkToChar(ulong link) => (char)(link - 1);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        public static bool IsCharLink(ulong link) => link <= MapSize;

        public static string FromLinksToString(IList<ulong> linksList)
        {
            var sb = new StringBuilder();
            for (int i = 0; i < linksList.Count; i++)
            {
                sb.Append(FromLinkToChar(linksList[i]));
            }
            return sb.ToString();
        }

        public static string FromSequenceLinkToString(ulong link, ILinks<ulong> links)
        {
            var sb = new StringBuilder();
            if (links.Exists(link))
            {
                StopableSequenceWalker.WalkRight(link, links.GetSource, links.GetTarget,
                    x => x <= MapSize || links.GetSource(x) == x || links.GetTarget(x) == x,
                    ↪  element =>
                    {
                        sb.Append(FromLinkToChar(element));
                        return true;
                    });
            }
            return sb.ToString();
        }

        public static ulong[] FromCharsToLinkArray(char[] chars) => FromCharsToLinkArray(chars,
        ↪  chars.Length);

        public static ulong[] FromCharsToLinkArray(char[] chars, int count)
        {
            // char array to ulong array
            var linksSequence = new ulong[count];
            for (var i = 0; i < count; i++)
            {
                linksSequence[i] = FromCharToLink(chars[i]);
            }
            return linksSequence;
        }

        public static ulong[] FromStringToLinkArray(string sequence)
        {
            // char array to ulong array
            var linksSequence = new ulong[sequence.Length];
            for (var i = 0; i < sequence.Length; i++)
            {
                linksSequence[i] = FromCharToLink(sequence[i]);
            }
            return linksSequence;
        }

        public static List<ulong[]> FromStringToLinkArrayGroups(string sequence)
        {
            var result = new List<ulong[]>();
            var offset = 0;
            while (offset < sequence.Length)
            {
                var currentCategory = CharUnicodeInfo.GetUnicodeCategory(sequence[offset]);
                var relativeLength = 1;
                var absoluteLength = offset + relativeLength;
                while (absoluteLength < sequence.Length &&
                       currentCategory ==
                       ↪  CharUnicodeInfo.GetUnicodeCategory(sequence[absoluteLength]))
                {
                    relativeLength++;
                    absoluteLength++;
                }
                // char array to ulong array
                var innerSequence = new ulong[relativeLength];
                var maxLength = offset + relativeLength;
                for (var i = offset; i < maxLength; i++)
                {
                    innerSequence[i - offset] = FromCharToLink(sequence[i]);
                }
                result.Add(innerSequence);
                offset += relativeLength;
            }
            return result;
        }

        public static List<ulong[]> FromLinkArrayToLinkArrayGroups(ulong[] array)
        {
            var result = new List<ulong[]>();
            var offset = 0;
            while (offset < array.Length)
            {
                var relativeLength = 1;
                if (array[offset] <= LastCharLink)
                {
                    var currentCategory =
                    ↪  CharUnicodeInfo.GetUnicodeCategory(FromLinkToChar(array[offset]));
                    var absoluteLength = offset + relativeLength;
                    while (absoluteLength < array.Length &&
                           array[absoluteLength] <= LastCharLink &&
                           currentCategory == CharUnicodeInfo.GetUnicodeCategory(FromLinkToChar(⌟
                           ↪  array[absoluteLength])))
                    {
                        relativeLength++;
                        absoluteLength++;
                    }
                }
                else
                {
                    var absoluteLength = offset + relativeLength;
                    while (absoluteLength < array.Length && array[absoluteLength] > LastCharLink)
                    {
                        relativeLength++;
                        absoluteLength++;
                    }
                }
                // copy array
                var innerSequence = new ulong[relativeLength];
                var maxLength = offset + relativeLength;
                for (var i = offset; i < maxLength; i++)
                {
                    innerSequence[i - offset] = array[i];
                }
                result.Add(innerSequence);
                offset += relativeLength;
            }
            return result;
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Walkers/LeftSequenceWalker.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Collections.Stacks;

namespace Platform.Data.Doublets.Sequences.Walkers
{
    public class LeftSequenceWalker<TLink> : SequenceWalkerBase<TLink>
    {
        public LeftSequenceWalker(ILinks<TLink> links, IStack<TLink> stack) : base(links, stack)
        ↪  { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetNextElementAfterPop(TLink element) =>
        ↪  Links.GetSource(element);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetNextElementAfterPush(TLink element) =>
        ↪  Links.GetTarget(element);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override IEnumerable<IList<TLink>> WalkContents(IList<TLink> element)
        {
            var start = Links.Constants.IndexPart + 1;
            for (var i = element.Count - 1; i >= start; i--)
            {
                var partLink = Links.GetLink(element[i]);
                if (IsElement(partLink))
                {
                    yield return partLink;
                }
            }
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Walkers/RightSequenceWalker.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Collections.Stacks;

namespace Platform.Data.Doublets.Sequences.Walkers
{
    public class RightSequenceWalker<TLink> : SequenceWalkerBase<TLink>
    {
        public RightSequenceWalker(ILinks<TLink> links, IStack<TLink> stack) : base(links,
        ↪  stack) { }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetNextElementAfterPop(TLink element) =>
        ↪  Links.GetTarget(element);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override TLink GetNextElementAfterPush(TLink element) =>
        ↪  Links.GetSource(element);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected override IEnumerable<IList<TLink>> WalkContents(IList<TLink> element)
        {
            for (var i = Links.Constants.IndexPart + 1; i < element.Count; i++)
            {
                var partLink = Links.GetLink(element[i]);
                if (IsElement(partLink))
                {
                    yield return partLink;
                }
            }
        }
    }
}
```

./Platform.Data.Doublets/Sequences/Walkers/SequenceWalkerBase.cs

```
using System.Collections.Generic;
using System.Runtime.CompilerServices;
using Platform.Collections.Stacks;
using Platform.Data.Sequences;

namespace Platform.Data.Doublets.Sequences.Walkers
{
    public abstract class SequenceWalkerBase<TLink> : LinksOperatorBase<TLink>,
    ↪  ISequenceWalker<TLink>
    {
        private readonly IStack<TLink> _stack;

        protected SequenceWalkerBase(ILinks<TLink> links, IStack<TLink> stack) : base(links) =>
        ↪  _stack = stack;

        public IEnumerable<IList<TLink>> Walk(TLink sequence)
        {
            _stack.Clear();
            var element = sequence;
            var elementValues = Links.GetLink(element);
            if (IsElement(elementValues))
            {
                yield return elementValues;
            }
            else
            {
                while (true)
                {
                    if (IsElement(elementValues))
                    {
                        if (_stack.IsEmpty)
                        {
                            break;
                        }
                        element = _stack.Pop();
                        elementValues = Links.GetLink(element);
                        foreach (var output in WalkContents(elementValues))
                        {
                            yield return output;
                        }
                        element = GetNextElementAfterPop(element);
                        elementValues = Links.GetLink(element);
                    }
                    else
                    {
                        _stack.Push(element);
                        element = GetNextElementAfterPush(element);
                        elementValues = Links.GetLink(element);
                    }
                }
            }
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected virtual bool IsElement(IList<TLink> elementLink) =>
         ↪  Point<TLink>.IsPartialPointUnchecked(elementLink);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected abstract TLink GetNextElementAfterPop(TLink element);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected abstract TLink GetNextElementAfterPush(TLink element);

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        protected abstract IEnumerable<IList<TLink>> WalkContents(IList<TLink> element);
    }
}
```

./Platform.Data.Doublets/Stacks/Stack.cs

```
using System.Collections.Generic;
using Platform.Collections.Stacks;

namespace Platform.Data.Doublets.Stacks
{
    public class Stack<TLink> : IStack<TLink>
    {
        private static readonly EqualityComparer<TLink> _equalityComparer =
         ↪  EqualityComparer<TLink>.Default;

        private readonly ILinks<TLink> _links;
        private readonly TLink _stack;

        public bool IsEmpty => _equalityComparer.Equals(Peek(), _stack);

        public Stack(ILinks<TLink> links, TLink stack)
        {
            _links = links;
            _stack = stack;
        }

        private TLink GetStackMarker() => _links.GetSource(_stack);

        private TLink GetTop() => _links.GetTarget(_stack);

        public TLink Peek() => _links.GetTarget(GetTop());

        public TLink Pop()
        {
            var element = Peek();
            if (!_equalityComparer.Equals(element, _stack))
            {
                var top = GetTop();
                var previousTop = _links.GetSource(top);
                _links.Update(_stack, GetStackMarker(), previousTop);
                _links.Delete(top);
            }
            return element;
        }

        public void Push(TLink element) => _links.Update(_stack, GetStackMarker(),
         ↪  _links.GetOrCreate(GetTop(), element));
    }
}
```

./Platform.Data.Doublets/Stacks/StackExtensions.cs

```
namespace Platform.Data.Doublets.Stacks
{
    public static class StackExtensions
    {
        public static TLink CreateStack<TLink>(this ILinks<TLink> links, TLink stackMarker)
        {
            var stackPoint = links.CreatePoint();
            var stack = links.Update(stackPoint, stackMarker, stackPoint);
            return stack;
        }
    }
}
```

./Platform.Data.Doublets/SynchronizedLinks.cs

```
using System;
using System.Collections.Generic;
using Platform.Data.Constants;
using Platform.Data.Doublets;
using Platform.Threading.Synchronization;

namespace Platform.Data.Doublets
{
    /// <remarks>
    /// TODO: Autogeneration of synchronized wrapper (decorator).
    /// TODO: Try to unfold code of each method using IL generation for performance improvements.
    /// TODO: Or even to unfold multiple layers of implementations.
    /// </remarks>
    public class SynchronizedLinks<T> : ISynchronizedLinks<T>
    {
        public LinksCombinedConstants<T, T, int> Constants { get; }
        public ISynchronization SyncRoot { get; }
        public ILinks<T> Sync { get; }
        public ILinks<T> Unsync { get; }

        public SynchronizedLinks(ILinks<T> links) : this(new ReaderWriterLockSynchronization(),
         ↪  links) { }

        public SynchronizedLinks(ISynchronization synchronization, ILinks<T> links)
        {
            SyncRoot = synchronization;
            Sync = this;
            Unsync = links;
            Constants = links.Constants;
        }

        public T Count(IList<T> restriction) => SyncRoot.ExecuteReadOperation(restriction,
         ↪  Unsync.Count);
        public T Each(Func<IList<T>, T> handler, IList<T> restrictions) =>
         ↪  SyncRoot.ExecuteReadOperation(handler, restrictions, (handler1, restrictions1) =>
         ↪  Unsync.Each(handler1, restrictions1));
        public T Create() => SyncRoot.ExecuteWriteOperation(Unsync.Create);
        public T Update(IList<T> restrictions) => SyncRoot.ExecuteWriteOperation(restrictions,
         ↪  Unsync.Update);
        public void Delete(T link) => SyncRoot.ExecuteWriteOperation(link, Unsync.Delete);

        //public T Trigger(IList<T> restriction, Func<IList<T>, IList<T>, T> matchedHandler,
         ↪  IList<T> substitution, Func<IList<T>, IList<T>, T> substitutedHandler)
        //{
        //    if (restriction != null && substitution != null &&
         ↪  !substitution.EqualTo(restriction))
        //        return SyncRoot.ExecuteWriteOperation(restriction, matchedHandler,
         ↪  substitution, substitutedHandler, Unsync.Trigger);

        //    return SyncRoot.ExecuteReadOperation(restriction, matchedHandler, substitution,
         ↪  substitutedHandler, Unsync.Trigger);
        //}
    }
}
```

./Platform.Data.Doublets/UInt64Link.cs

```
using System;
using System.Collections;
using System.Collections.Generic;
using Platform.Exceptions;
using Platform.Ranges;
using Platform.Singletons;
using Platform.Collections.Lists;
using Platform.Data.Constants;

namespace Platform.Data.Doublets
{
    /// <summary>
    /// Структура описывающая уникальную связь.
    /// </summary>
    public struct UInt64Link : IEquatable<UInt64Link>, IReadOnlyList<ulong>, IList<ulong>
    {
        private static readonly LinksCombinedConstants<bool, ulong, int> _constants =
         ↪  Default<LinksCombinedConstants<bool, ulong, int>>.Instance;

        private const int Length = 3;

        public readonly ulong Index;
        public readonly ulong Source;
        public readonly ulong Target;

        public static readonly UInt64Link Null = new UInt64Link();

        public UInt64Link(params ulong[] values)
        {
            Index = values.Length > _constants.IndexPart ? values[_constants.IndexPart] :
            ↪   _constants.Null;
            Source = values.Length > _constants.SourcePart ? values[_constants.SourcePart] :
            ↪   _constants.Null;
            Target = values.Length > _constants.TargetPart ? values[_constants.TargetPart] :
            ↪   _constants.Null;
        }

        public UInt64Link(IList<ulong> values)
        {
            Index = values.Count > _constants.IndexPart ? values[_constants.IndexPart] :
            ↪   _constants.Null;
            Source = values.Count > _constants.SourcePart ? values[_constants.SourcePart] :
            ↪   _constants.Null;
            Target = values.Count > _constants.TargetPart ? values[_constants.TargetPart] :
            ↪   _constants.Null;
        }

        public UInt64Link(ulong index, ulong source, ulong target)
        {
            Index = index;
            Source = source;
            Target = target;
        }

        public UInt64Link(ulong source, ulong target)
            : this(_constants.Null, source, target)
        {
            Source = source;
            Target = target;
        }

        public static UInt64Link Create(ulong source, ulong target) => new UInt64Link(source,
        ↪   target);

        public override int GetHashCode() => (Index, Source, Target).GetHashCode();

        public bool IsNull() => Index == _constants.Null
                             && Source == _constants.Null
                             && Target == _constants.Null;

        public override bool Equals(object other) => other is UInt64Link &&
        ↪   Equals((UInt64Link)other);

        public bool Equals(UInt64Link other) => Index == other.Index
                                             && Source == other.Source
                                             && Target == other.Target;

        public static string ToString(ulong index, ulong source, ulong target) => $"({index}:
        ↪   {source}->{target})";

        public static string ToString(ulong source, ulong target) => $"({source}->{target})";

        public static implicit operator ulong[](UInt64Link link) => link.ToArray();

        public static implicit operator UInt64Link(ulong[] linkArray) => new
        ↪   UInt64Link(linkArray);

        public override string ToString() => Index == _constants.Null ? ToString(Source, Target)
        ↪   : ToString(Index, Source, Target);

        #region IList

        public ulong this[int index]
        {
            get
            {
                Ensure.Always.ArgumentInRange(index, new Range<int>(0, Length - 1),
                ↪   nameof(index));
                if (index == _constants.IndexPart)
                {
                    return Index;
                }
                if (index == _constants.SourcePart)
                {
                    return Source;
                }
                if (index == _constants.TargetPart)
                {
                    return Target;
                }
                throw new NotSupportedException(); // Impossible path due to
                ↪  Ensure.ArgumentInRange
            }
            set => throw new NotSupportedException();
        }

        public int Count => Length;

        public bool IsReadOnly => true;

        IEnumerator IEnumerable.GetEnumerator() => GetEnumerator();

        public IEnumerator<ulong> GetEnumerator()
        {
            yield return Index;
            yield return Source;
            yield return Target;
        }

        public void Add(ulong item) => throw new NotSupportedException();

        public void Clear() => throw new NotSupportedException();

        public bool Contains(ulong item) => IndexOf(item) >= 0;

        public void CopyTo(ulong[] array, int arrayIndex)
        {
            Ensure.Always.ArgumentNotNull(array, nameof(array));
            Ensure.Always.ArgumentInRange(arrayIndex, new Range<int>(0, array.Length - 1),
            ↪  nameof(arrayIndex));
            if (arrayIndex + Length > array.Length)
            {
                throw new ArgumentException();
            }
            array[arrayIndex++] = Index;
            array[arrayIndex++] = Source;
            array[arrayIndex] = Target;
        }

        public bool Remove(ulong item) => Throw.A.NotSupportedExceptionAndReturn<bool>();

        public int IndexOf(ulong item)
        {
            if (Index == item)
            {
                return _constants.IndexPart;
            }
            if (Source == item)
            {
                return _constants.SourcePart;
            }
            if (Target == item)
            {
                return _constants.TargetPart;
            }

            return -1;
        }

        public void Insert(int index, ulong item) => throw new NotSupportedException();

        public void RemoveAt(int index) => throw new NotSupportedException();

        #endregion
    }
}
```

./Platform.Data.Doublets/UInt64LinkExtensions.cs

```csharp
namespace Platform.Data.Doublets
{
    public static class UInt64LinkExtensions
    {
        public static bool IsFullPoint(this UInt64Link link) => Point<ulong>.IsFullPoint(link);
        public static bool IsPartialPoint(this UInt64Link link) =>
         ↪  Point<ulong>.IsPartialPoint(link);
    }
}
```

./Platform.Data.Doublets/UInt64LinksExtensions.cs

```csharp
using System;
using System.Text;
using System.Collections.Generic;
using Platform.Singletons;
using Platform.Data.Constants;
using Platform.Data.Exceptions;
using Platform.Data.Doublets.Sequences;

namespace Platform.Data.Doublets
{
    public static class UInt64LinksExtensions
    {
        public static readonly LinksCombinedConstants<bool, ulong, int> Constants =
         ↪  Default<LinksCombinedConstants<bool, ulong, int>>.Instance;

        public static void UseUnicode(this ILinks<ulong> links) => UnicodeMap.InitNew(links);

        public static void EnsureEachLinkExists(this ILinks<ulong> links, IList<ulong> sequence)
        {
            if (sequence == null)
            {
                return;
            }
            for (var i = 0; i < sequence.Count; i++)
            {
                if (!links.Exists(sequence[i]))
                {
                    throw new ArgumentLinkDoesNotExistsException<ulong>(sequence[i],
                     ↪  $"sequence[{i}]");
                }
            }
        }

        public static void EnsureEachLinkIsAnyOrExists(this ILinks<ulong> links, IList<ulong>
         ↪  sequence)
        {
            if (sequence == null)
            {
                return;
            }
            for (var i = 0; i < sequence.Count; i++)
            {
                if (sequence[i] != Constants.Any && !links.Exists(sequence[i]))
                {
                    throw new ArgumentLinkDoesNotExistsException<ulong>(sequence[i],
                     ↪  $"sequence[{i}]");
                }
            }
        }

        public static bool AnyLinkIsAny(this ILinks<ulong> links, params ulong[] sequence)
        {
            if (sequence == null)
            {
                return false;
            }
            var constants = links.Constants;
            for (var i = 0; i < sequence.Length; i++)
            {
                if (sequence[i] == constants.Any)
                {
                    return true;
                }
            }
            return false;
        }

        public static string FormatStructure(this ILinks<ulong> links, ulong linkIndex,
         ↪  Func<UInt64Link, bool> isElement, bool renderIndex = false, bool renderDebug = false)
        {
            var sb = new StringBuilder();
            var visited = new HashSet<ulong>();
            links.AppendStructure(sb, visited, linkIndex, isElement, (innerSb, link) =>
             ↪  innerSb.Append(link.Index), renderIndex, renderDebug);
            return sb.ToString();
        }

        public static string FormatStructure(this ILinks<ulong> links, ulong linkIndex,
         ↪  Func<UInt64Link, bool> isElement, Action<StringBuilder, UInt64Link> appendElement,
         ↪  bool renderIndex = false, bool renderDebug = false)
        {
            var sb = new StringBuilder();
            var visited = new HashSet<ulong>();
            links.AppendStructure(sb, visited, linkIndex, isElement, appendElement, renderIndex,
             ↪  renderDebug);
            return sb.ToString();
        }

        public static void AppendStructure(this ILinks<ulong> links, StringBuilder sb,
         ↪  HashSet<ulong> visited, ulong linkIndex, Func<UInt64Link, bool> isElement,
         ↪  Action<StringBuilder, UInt64Link> appendElement, bool renderIndex = false, bool
         ↪  renderDebug = false)
        {
            if (sb == null)
            {
                throw new ArgumentNullException(nameof(sb));
            }
            if (linkIndex == Constants.Null || linkIndex == Constants.Any || linkIndex ==
             ↪  Constants.Itself)
            {
                return;
            }
            if (links.Exists(linkIndex))
            {
                if (visited.Add(linkIndex))
                {
                    sb.Append('(');
                    var link = new UInt64Link(links.GetLink(linkIndex));
                    if (renderIndex)
                    {
                        sb.Append(link.Index);
                        sb.Append(':');
                    }
                    if (link.Source == link.Index)
                    {
                        sb.Append(link.Index);
                    }
                    else
                    {
                        var source = new UInt64Link(links.GetLink(link.Source));
                        if (isElement(source))
                        {
                            appendElement(sb, source);
                        }
                        else
                        {
                            links.AppendStructure(sb, visited, source.Index, isElement,
                             ↪  appendElement, renderIndex);
                        }
                    }
                    sb.Append(' ');
                    if (link.Target == link.Index)
                    {
                        sb.Append(link.Index);
                    }
                    else
                    {
                        var target = new UInt64Link(links.GetLink(link.Target));
                        if (isElement(target))
                        {
                            appendElement(sb, target);
                        }
                        else
                        {
                                links.AppendStructure(sb, visited, target.Index, isElement,
                                 ↪  appendElement, renderIndex);
                            }
                        }
                        sb.Append(')');
                    }
                    else
                    {
                        if (renderDebug)
                        {
                            sb.Append('*');
                        }
                        sb.Append(linkIndex);
                    }
                }
                else
                {
                    if (renderDebug)
                    {
                        sb.Append('~');
                    }
                    sb.Append(linkIndex);
                }
            }
        }
    }
```

./Platform.Data.Doublets/UInt64LinksTransactionsLayer.cs

```
using System;
using System.Linq;
using System.Collections.Generic;
using System.IO;
using System.Runtime.CompilerServices;
using System.Threading;
using System.Threading.Tasks;
using Platform.Disposables;
using Platform.Timestamps;
using Platform.Unsafe;
using Platform.IO;
using Platform.Data.Doublets.Decorators;

namespace Platform.Data.Doublets
{
    public class UInt64LinksTransactionsLayer : LinksDisposableDecoratorBase<ulong> //-V3073
    {
        /// <remarks>
        /// Альтернативные варианты хранения трансформации (элемента транзакции):
        ///
        /// private enum TransitionType
        /// {
        ///     Creation,
        ///     UpdateOf,
        ///     UpdateTo,
        ///     Deletion
        /// }
        ///
        /// private struct Transition
        /// {
        ///     public ulong TransactionId;
        ///     public UniqueTimestamp Timestamp;
        ///     public TransactionItemType Type;
        ///     public Link Source;
        ///     public Link Linker;
        ///     public Link Target;
        /// }
        ///
        /// Или
        ///
        /// public struct TransitionHeader
        /// {
        ///     public ulong TransactionIdCombined;
        ///     public ulong TimestampCombined;
        ///
        ///     public ulong TransactionId
        ///     {
        ///         get
        ///         {
        ///             return (ulong) mask & TransactionIdCombined;
        ///         }
        ///     }
        ///
        ///     public UniqueTimestamp Timestamp
        ///     {
        ///         get
        ///         {
        ///             return (UniqueTimestamp)mask & TransactionIdCombined;
        ///         }
        ///     }
        ///
        ///     public TransactionItemType Type
        ///     {
        ///         get
        ///         {
        ///             // Использовать по одному биту из TransactionId и Timestamp,
        ///             // для значения в 2 бита, которое представляет тип операции
        ///             throw new NotImplementedException();
        ///         }
        ///     }
        /// }
        ///
        /// private struct Transition
        /// {
        ///     public TransitionHeader Header;
        ///     public Link Source;
        ///     public Link Linker;
        ///     public Link Target;
        /// }
        ///
        /// </remarks>
        public struct Transition
        {
            public static readonly long Size = Structure<Transition>.Size;

            public readonly ulong TransactionId;
            public readonly UInt64Link Before;
            public readonly UInt64Link After;
            public readonly Timestamp Timestamp;

            public Transition(UniqueTimestampFactory uniqueTimestampFactory, ulong transactionId, UInt64Link before, UInt64Link after)
            {
                TransactionId = transactionId;
                Before = before;
                After = after;
                Timestamp = uniqueTimestampFactory.Create();
            }

            public Transition(UniqueTimestampFactory uniqueTimestampFactory, ulong transactionId, UInt64Link before)
                : this(uniqueTimestampFactory, transactionId, before, default)
            {
            }

            public Transition(UniqueTimestampFactory uniqueTimestampFactory, ulong transactionId)
                : this(uniqueTimestampFactory, transactionId, default, default)
            {
            }

            public override string ToString() => $"{Timestamp} {TransactionId}: {Before} => {After}";
        }

        /// <remarks>
        /// Другие варианты реализации транзакций (атомарности):
        ///     1. Разделение хранения значения связи ((Source Target) или (Source Linker Target)) и индексов.
        ///     2. Хранение трансформаций/операций в отдельном хранилище Links, но дополнительно потребуется решить вопрос
        ///        со ссылками на внешние идентификаторы, или как-то иначе решить вопрос с пересечениями идентификаторов.
        ///
        /// Где хранить промежуточный список транзакций?
        ///
        /// В оперативной памяти:
        ///  Минусы:
        ///     1. Может усложнить систему, если она будет функционировать самостоятельно,
        ///     так как нужно отдельно выделять память под список трансформаций.
        ///     2. Выделенной оперативной памяти может не хватить, в том случае,
        ///     если транзакция использует слишком много трансформаций.
        ///         -> Можно использовать жёсткий диск для слишком длинных транзакций.
        ///         -> Максимальный размер списка трансформаций можно ограничить / задать
        ↪   константой.
        ///     3. При подтверждении транзакции (Commit) все трансформации записываются разом
        ↪   создавая задержку.
        ///
        /// На жёстком диске:
        ///  Минусы:
        ///     1. Длительный отклик, на запись каждой трансформации.
        ///     2. Лог транзакций дополнительно наполняется отменёнными транзакциями.
        ///         -> Это может решаться упаковкой/исключением дублирующих операций.
        ///         -> Также это может решаться тем, что короткие транзакции вообще
        ///            не будут записываться в случае отката.
        ///     3. Перед тем как выполнять отмену операций транзакции нужно дождаться пока все
        ↪   операции (трансформации)
        ///        будут записаны в лог.
        ///
        /// </remarks>
        public class Transaction : DisposableBase
        {
            private readonly Queue<Transition> _transitions;
            private readonly UInt64LinksTransactionsLayer _layer;
            public bool IsCommitted { get; private set; }
            public bool IsReverted { get; private set; }

            public Transaction(UInt64LinksTransactionsLayer layer)
            {
                _layer = layer;
                if (_layer._currentTransactionId != 0)
                {
                    throw new NotSupportedException("Nested transactions not supported.");
                }
                IsCommitted = false;
                IsReverted = false;
                _transitions = new Queue<Transition>();
                SetCurrentTransaction(layer, this);
            }

            public void Commit()
            {
                EnsureTransactionAllowsWriteOperations(this);
                while (_transitions.Count > 0)
                {
                    var transition = _transitions.Dequeue();
                    _layer._transitions.Enqueue(transition);
                }
                _layer._lastCommitedTransactionId = _layer._currentTransactionId;
                IsCommitted = true;
            }

            private void Revert()
            {
                EnsureTransactionAllowsWriteOperations(this);
                var transitionsToRevert = new Transition[_transitions.Count];
                _transitions.CopyTo(transitionsToRevert, 0);
                for (var i = transitionsToRevert.Length - 1; i >= 0; i--)
                {
                    _layer.RevertTransition(transitionsToRevert[i]);
                }
                IsReverted = true;
            }

            public static void SetCurrentTransaction(UInt64LinksTransactionsLayer layer,
            ↪   Transaction transaction)
            {
                layer._currentTransactionId = layer._lastCommitedTransactionId + 1;
                layer._currentTransactionTransitions = transaction._transitions;
                layer._currentTransaction = transaction;
            }

            public static void EnsureTransactionAllowsWriteOperations(Transaction transaction)
            {
                if (transaction.IsReverted)
                {
                    throw new InvalidOperationException("Transation is reverted.");
                }
                if (transaction.IsCommitted)
                {
                    throw new InvalidOperationException("Transation is commited.");
                }
            }

            protected override void Dispose(bool manual, bool wasDisposed)
            {
                if (!wasDisposed && _layer != null && !_layer.IsDisposed)
                {
                    if (!IsCommitted && !IsReverted)
                    {
                        Revert();
                    }
                    _layer.ResetCurrentTransation();
                }
            }
        }

        public static readonly TimeSpan DefaultPushDelay = TimeSpan.FromSeconds(0.1);

        private readonly string _logAddress;
        private readonly FileStream _log;
        private readonly Queue<Transition> _transitions;
        private readonly UniqueTimestampFactory _uniqueTimestampFactory;
        private Task _transitionsPusher;
        private Transition _lastCommitedTransition;
        private ulong _currentTransactionId;
        private Queue<Transition> _currentTransactionTransitions;
        private Transaction _currentTransaction;
        private ulong _lastCommitedTransactionId;

        public UInt64LinksTransactionsLayer(ILinks<ulong> links, string logAddress)
            : base(links)
        {
            if (string.IsNullOrWhiteSpace(logAddress))
            {
                throw new ArgumentNullException(nameof(logAddress));
            }
            // В первой строке файла хранится последняя закоммиченную транзакцию.
            // При запуске это используется для проверки удачного закрытия файла лога.
            // In the first line of the file the last committed transaction is stored.
            // On startup, this is used to check that the log file is successfully closed.
            var lastCommitedTransition = FileHelpers.ReadFirstOrDefault<Transition>(logAddress);
            var lastWrittenTransition = FileHelpers.ReadLastOrDefault<Transition>(logAddress);
            if (!lastCommitedTransition.Equals(lastWrittenTransition))
            {
                Dispose();
                throw new NotSupportedException("Database is damaged, autorecovery is not
                 ↪  supported yet.");
            }
            if (lastCommitedTransition.Equals(default(Transition)))
            {
                FileHelpers.WriteFirst(logAddress, lastCommitedTransition);
            }
            _lastCommitedTransition = lastCommitedTransition;
            // TODO: Think about a better way to calculate or store this value
            var allTransitions = FileHelpers.ReadAll<Transition>(logAddress);
            _lastCommitedTransactionId = allTransitions.Max(x => x.TransactionId);
            _uniqueTimestampFactory = new UniqueTimestampFactory();
            _logAddress = logAddress;
            _log = FileHelpers.Append(logAddress);
            _transitions = new Queue<Transition>();
            _transitionsPusher = new Task(TransitionsPusher);
            _transitionsPusher.Start();
        }

        public IList<ulong> GetLinkValue(ulong link) => Links.GetLink(link);

        public override ulong Create()
        {
            var createdLinkIndex = Links.Create();
            var createdLink = new UInt64Link(Links.GetLink(createdLinkIndex));
            CommitTransition(new Transition(_uniqueTimestampFactory, _currentTransactionId,
             ↪  default, createdLink));
            return createdLinkIndex;
        }

        public override ulong Update(IList<ulong> parts)
        {
            var linkIndex = parts[Constants.IndexPart];
            var beforeLink = new UInt64Link(Links.GetLink(linkIndex));
            linkIndex = Links.Update(parts);
            var afterLink = new UInt64Link(Links.GetLink(linkIndex));
            CommitTransition(new Transition(_uniqueTimestampFactory, _currentTransactionId,
             ↪  beforeLink, afterLink));
            return linkIndex;
        }

        public override void Delete(ulong link)
        {
            var deletedLink = new UInt64Link(Links.GetLink(link));
            Links.Delete(link);
            CommitTransition(new Transition(_uniqueTimestampFactory, _currentTransactionId,
             ↪  deletedLink, default));
        }

        [MethodImpl(MethodImplOptions.AggressiveInlining)]
        private Queue<Transition> GetCurrentTransitions() => _currentTransactionTransitions ??
         ↪  _transitions;

        private void CommitTransition(Transition transition)
        {
            if (_currentTransaction != null)
            {
                Transaction.EnsureTransactionAllowsWriteOperations(_currentTransaction);
            }
            var transitions = GetCurrentTransitions();
            transitions.Enqueue(transition);
        }

        private void RevertTransition(Transition transition)
        {
            if (transition.After.IsNull()) // Revert Deletion with Creation
            {
                Links.Create();
            }
            else if (transition.Before.IsNull()) // Revert Creation with Deletion
            {
                Links.Delete(transition.After.Index);
            }
            else // Revert Update
            {
                Links.Update(new[] { transition.After.Index, transition.Before.Source,
                 ↪  transition.Before.Target });
            }
        }

        private void ResetCurrentTransation()
        {
            _currentTransactionId = 0;
            _currentTransactionTransitions = null;
            _currentTransaction = null;
        }

        private void PushTransitions()
        {
            if (_log == null || _transitions == null)
            {
                return;
            }
            for (var i = 0; i < _transitions.Count; i++)
            {
                var transition = _transitions.Dequeue();

                _log.Write(transition);
                _lastCommitedTransition = transition;
            }
        }

        private void TransitionsPusher()
        {
            while (!IsDisposed && _transitionsPusher != null)
            {
                Thread.Sleep(DefaultPushDelay);
                PushTransitions();
            }
        }

        public Transaction BeginTransaction() => new Transaction(this);

        private void DisposeTransitions()
        {
            try
            {
                var pusher = _transitionsPusher;
                if (pusher != null)
                {
                    _transitionsPusher = null;
                    pusher.Wait();
                }
                if (_transitions != null)
                {
                    PushTransitions();
                }
                _log.DisposeIfPossible();
                FileHelpers.WriteFirst(_logAddress, _lastCommitedTransition);
            }
            catch
            {
            }
        }

        #region DisposalBase

        protected override void Dispose(bool manual, bool wasDisposed)
        {
            if (!wasDisposed)
            {
                DisposeTransitions();
            }
            base.Dispose(manual, wasDisposed);
        }

        #endregion
    }
}
```

./Platform.Data.Doublets.Tests/ComparisonTests.cs

```
using System;
using System.Collections.Generic;
using Xunit;
using Platform.Diagnostics;

namespace Platform.Data.Doublets.Tests
{
    public static class ComparisonTests
    {
        protected class UInt64Comparer : IComparer<ulong>
        {
            public int Compare(ulong x, ulong y) => x.CompareTo(y);
        }

        private static int Compare(ulong x, ulong y) => x.CompareTo(y);

        [Fact]
        public static void GreaterOrEqualPerfomanceTest()
        {
            const int N = 1000000;

            ulong x = 10;
            ulong y = 500;

            bool result = false;

            var ts1 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = Compare(x, y) >= 0;
                }
            });

            var comparer1 = Comparer<ulong>.Default;

            var ts2 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = comparer1.Compare(x, y) >= 0;
                }
            });

            Func<ulong, ulong, int> compareReference = comparer1.Compare;

            var ts3 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = compareReference(x, y) >= 0;
                }
            });

            var comparer2 = new UInt64Comparer();

            var ts4 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = comparer2.Compare(x, y) >= 0;
                }
            });

            Console.WriteLine($"{ts1} {ts2} {ts3} {ts4} {result}");
        }
    }
}
```

./Platform.Data.Doublets.Tests/DoubletLinksTests.cs

```
using System.Collections.Generic;
using Xunit;
using Platform.Reflection;
using Platform.Numbers;
using Platform.Memory;
using Platform.Scopes;
using Platform.Setters;
using Platform.Data.Doublets.ResizableDirectMemory;

namespace Platform.Data.Doublets.Tests
{
    public static class DoubletLinksTests
    {
        [Fact]
        public static void UInt64CRUDTest()
        {
            using (var scope = new Scope<Types<HeapResizableDirectMemory,
             ↪  ResizableDirectMemoryLinks<ulong>>>())
            {
                scope.Use<ILinks<ulong>>().TestCRUDOperations();
            }
        }

        [Fact]
        public static void UInt32CRUDTest()
        {
            using (var scope = new Scope<Types<HeapResizableDirectMemory,
             ↪  ResizableDirectMemoryLinks<uint>>>())
            {
                scope.Use<ILinks<uint>>().TestCRUDOperations();
            }
        }

        [Fact]
        public static void UInt16CRUDTest()
        {
            using (var scope = new Scope<Types<HeapResizableDirectMemory,
             ↪  ResizableDirectMemoryLinks<ushort>>>())
            {
                scope.Use<ILinks<ushort>>().TestCRUDOperations();
            }
        }

        [Fact]
        public static void UInt8CRUDTest()
        {
            using (var scope = new Scope<Types<HeapResizableDirectMemory,
             ↪  ResizableDirectMemoryLinks<byte>>>())
            {
                scope.Use<ILinks<byte>>().TestCRUDOperations();
            }
        }

        private static void TestCRUDOperations<T>(this ILinks<T> links)
        {
            var constants = links.Constants;

            var equalityComparer = EqualityComparer<T>.Default;

            // Create Link
            Assert.True(equalityComparer.Equals(links.Count(), Integer<T>.Zero));

            var setter = new Setter<T>(constants.Null);
            links.Each(constants.Any, constants.Any, setter.SetAndReturnTrue);

            Assert.True(equalityComparer.Equals(setter.Result, constants.Null));

            var linkAddress = links.Create();

            var link = new Link<T>(links.GetLink(linkAddress));

            Assert.True(link.Count == 3);
            Assert.True(equalityComparer.Equals(link.Index, linkAddress));
            Assert.True(equalityComparer.Equals(link.Source, constants.Null));
            Assert.True(equalityComparer.Equals(link.Target, constants.Null));

            Assert.True(equalityComparer.Equals(links.Count(), Integer<T>.One));

            // Get first link
            setter = new Setter<T>(constants.Null);
            links.Each(constants.Any, constants.Any, setter.SetAndReturnFalse);

            Assert.True(equalityComparer.Equals(setter.Result, linkAddress));

            // Update link to reference itself
            links.Update(linkAddress, linkAddress, linkAddress);

            link = new Link<T>(links.GetLink(linkAddress));

            Assert.True(equalityComparer.Equals(link.Source, linkAddress));
            Assert.True(equalityComparer.Equals(link.Target, linkAddress));

            // Update link to reference null (prepare for delete)
            var updated = links.Update(linkAddress, constants.Null, constants.Null);

            Assert.True(equalityComparer.Equals(updated, linkAddress));

            link = new Link<T>(links.GetLink(linkAddress));

            Assert.True(equalityComparer.Equals(link.Source, constants.Null));
            Assert.True(equalityComparer.Equals(link.Target, constants.Null));

            // Delete link
            links.Delete(linkAddress);

            Assert.True(equalityComparer.Equals(links.Count(), Integer<T>.Zero));

            setter = new Setter<T>(constants.Null);
            links.Each(constants.Any, constants.Any, setter.SetAndReturnTrue);

            Assert.True(equalityComparer.Equals(setter.Result, constants.Null));
        }

        [Fact]
        public static void UInt64RawNumbersCRUDTest()
        {
            using (var scope = new Scope<Types<HeapResizableDirectMemory,
             ↪  ResizableDirectMemoryLinks<ulong>>>())
            {
                scope.Use<ILinks<ulong>>().TestRawNumbersCRUDOperations();
            }
        }

        [Fact]
        public static void UInt32RawNumbersCRUDTest()
        {
            using (var scope = new Scope<Types<HeapResizableDirectMemory,
             ↪  ResizableDirectMemoryLinks<uint>>>())
            {
                scope.Use<ILinks<uint>>().TestRawNumbersCRUDOperations();
            }
        }

        [Fact]
        public static void UInt16RawNumbersCRUDTest()
        {
            using (var scope = new Scope<Types<HeapResizableDirectMemory,
             ↪  ResizableDirectMemoryLinks<ushort>>>())
            {
                scope.Use<ILinks<ushort>>().TestRawNumbersCRUDOperations();
            }
        }

        [Fact]
        public static void UInt8RawNumbersCRUDTest()
        {
            using (var scope = new Scope<Types<HeapResizableDirectMemory,
             ↪  ResizableDirectMemoryLinks<byte>>>())
            {
                scope.Use<ILinks<byte>>().TestRawNumbersCRUDOperations();
            }
        }

        private static void TestRawNumbersCRUDOperations<T>(this ILinks<T> links)
        {
            // Constants
            var constants = links.Constants;
            var equalityComparer = EqualityComparer<T>.Default;

            var h106E = new Hybrid<T>(106L, isExternal: true);
            var h107E = new Hybrid<T>(-char.ConvertFromUtf32(107)[0]);
            var h108E = new Hybrid<T>(-108L);

            Assert.Equal(106L, h106E.AbsoluteValue);
            Assert.Equal(107L, h107E.AbsoluteValue);
            Assert.Equal(108L, h108E.AbsoluteValue);

            // Create Link (External -> External)
            var linkAddress1 = links.Create();

            links.Update(linkAddress1, h106E, h108E);

            var link1 = new Link<T>(links.GetLink(linkAddress1));

            Assert.True(equalityComparer.Equals(link1.Source, h106E));
            Assert.True(equalityComparer.Equals(link1.Target, h108E));

            // Create Link (Internal -> External)
            var linkAddress2 = links.Create();

            links.Update(linkAddress2, linkAddress1, h108E);

            var link2 = new Link<T>(links.GetLink(linkAddress2));

            Assert.True(equalityComparer.Equals(link2.Source, linkAddress1));
            Assert.True(equalityComparer.Equals(link2.Target, h108E));

            // Create Link (Internal -> Internal)
            var linkAddress3 = links.Create();

            links.Update(linkAddress3, linkAddress1, linkAddress2);

            var link3 = new Link<T>(links.GetLink(linkAddress3));

            Assert.True(equalityComparer.Equals(link3.Source, linkAddress1));
            Assert.True(equalityComparer.Equals(link3.Target, linkAddress2));

            // Search for created link
            var setter1 = new Setter<T>(constants.Null);
            links.Each(h106E, h108E, setter1.SetAndReturnFalse);

            Assert.True(equalityComparer.Equals(setter1.Result, linkAddress1));

            // Search for nonexistent link
            var setter2 = new Setter<T>(constants.Null);
            links.Each(h106E, h107E, setter2.SetAndReturnFalse);

            Assert.True(equalityComparer.Equals(setter2.Result, constants.Null));

            // Update link to reference null (prepare for delete)
            var updated = links.Update(linkAddress3, constants.Null, constants.Null);

            Assert.True(equalityComparer.Equals(updated, linkAddress3));

            link3 = new Link<T>(links.GetLink(linkAddress3));

            Assert.True(equalityComparer.Equals(link3.Source, constants.Null));
            Assert.True(equalityComparer.Equals(link3.Target, constants.Null));

            // Delete link
            links.Delete(linkAddress3);

            Assert.True(equalityComparer.Equals(links.Count(), Integer<T>.Two));

            var setter3 = new Setter<T>(constants.Null);
            links.Each(constants.Any, constants.Any, setter3.SetAndReturnTrue);

            Assert.True(equalityComparer.Equals(setter3.Result, linkAddress2));
        }

        // TODO: Test layers
    }
}
```

./Platform.Data.Doublets.Tests/EqualityTests.cs

```
using System;
using System.Collections.Generic;
using Xunit;
using Platform.Diagnostics;

namespace Platform.Data.Doublets.Tests
{
    public static class EqualityTests
    {
        protected class UInt64EqualityComparer : IEqualityComparer<ulong>
        {
            public bool Equals(ulong x, ulong y) => x == y;

            public int GetHashCode(ulong obj) => obj.GetHashCode();
        }

        private static bool Equals1<T>(T x, T y) => Equals(x, y);

        private static bool Equals2<T>(T x, T y) => x.Equals(y);

        private static bool Equals3(ulong x, ulong y) => x == y;

        [Fact]
        public static void EqualsPerfomanceTest()
        {
            const int N = 1000000;

            ulong x = 10;
            ulong y = 500;

            bool result = false;

            var ts1 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = Equals1(x, y);
                }
            });

            var ts2 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = Equals2(x, y);
                }
            });

            var ts3 = Performance.Measure(() =>
            {
                for (int i = 0; i < N; i++)
                {
                    result = Equals3(x, y);
                    }
                });

                var equalityComparer1 = EqualityComparer<ulong>.Default;

                var ts4 = Performance.Measure(() =>
                {
                    for (int i = 0; i < N; i++)
                    {
                        result = equalityComparer1.Equals(x, y);
                    }
                });

                var equalityComparer2 = new UInt64EqualityComparer();

                var ts5 = Performance.Measure(() =>
                {
                    for (int i = 0; i < N; i++)
                    {
                        result = equalityComparer2.Equals(x, y);
                    }
                });

                Func<ulong, ulong, bool> equalityComparer3 = equalityComparer2.Equals;

                var ts6 = Performance.Measure(() =>
                {
                    for (int i = 0; i < N; i++)
                    {
                        result = equalityComparer3(x, y);
                    }
                });

                var comparer = Comparer<ulong>.Default;

                var ts7 = Performance.Measure(() =>
                {
                    for (int i = 0; i < N; i++)
                    {
                        result = comparer.Compare(x, y) == 0;
                    }
                });

                Assert.True(ts2 < ts1);
                Assert.True(ts3 < ts2);
                Assert.True(ts5 < ts4);
                Assert.True(ts5 < ts6);

                Console.WriteLine($"{ts1} {ts2} {ts3} {ts4} {ts5} {ts6} {ts7} {result}");
            }
        }
    }
```

./Platform.Data.Doublets.Tests/LinksTests.cs

```
using System;
using System.Collections.Generic;
using System.Diagnostics;
using System.IO;
using System.Text;
using System.Threading;
using System.Threading.Tasks;
using Xunit;
using Platform.Disposables;
using Platform.IO;
using Platform.Ranges;
using Platform.Random;
using Platform.Timestamps;
using Platform.Singletons;
using Platform.Counters;
using Platform.Diagnostics;
using Platform.Data.Constants;
using Platform.Data.Doublets.ResizableDirectMemory;
using Platform.Data.Doublets.Decorators;

namespace Platform.Data.Doublets.Tests
{
    public static class LinksTests
    {
        private static readonly LinksCombinedConstants<bool, ulong, int> _constants =
         ↪  Default<LinksCombinedConstants<bool, ulong, int>>.Instance;

        private const long Iterations = 10 * 1024;

        #region Concept

        [Fact]
        public static void MultipleCreateAndDeleteTest()
        {
            //const int N = 21;

            using (var scope = new TempLinksTestScope())
            {
                var links = scope.Links;

                for (var N = 0; N < 100; N++)
                {
                    var random = new System.Random(N);

                    var created = 0;
                    var deleted = 0;

                    for (var i = 0; i < N; i++)
                    {
                        var linksCount = links.Count();

                        var createPoint = random.NextBoolean();

                        if (linksCount > 2 && createPoint)
                        {
                            var linksAddressRange = new Range<ulong>(1, linksCount);
                            var source = random.NextUInt64(linksAddressRange);
                            var target = random.NextUInt64(linksAddressRange); //-V3086

                            var resultLink = links.CreateAndUpdate(source, target);
                            if (resultLink > linksCount)
                            {
                                created++;
                            }
                        }
                        else
                        {
                            links.Create();
                            created++;
                        }
                    }

                    Assert.True(created == (int)links.Count());

                    for (var i = 0; i < N; i++)
                    {
                        var link = (ulong)i + 1;
                        if (links.Exists(link))
                        {
                            links.Delete(link);
                            deleted++;
                        }
                    }

                    Assert.True(links.Count() == 0);
                }
            }
        }

        [Fact]
        public static void CascadeUpdateTest()
        {
            var itself = _constants.Itself;

            using (var scope = new TempLinksTestScope(useLog: true))
            {
                var links = scope.Links;

                var l1 = links.Create();
                var l2 = links.Create();

                l2 = links.Update(l2, l2, l1, l2);

                links.CreateAndUpdate(l2, itself);
                links.CreateAndUpdate(l2, itself);

                l2 = links.Update(l2, l1);
                links.Delete(l2);

                Global.Trash = links.Count();

                links.Unsync.DisposeIfPossible(); // Close links to access log

                Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(scope.TempTransactionLogFilename);
            }
        }

        [Fact]
        public static void BasicTransactionLogTest()
        {
            using (var scope = new TempLinksTestScope(useLog: true))
            {
                var links = scope.Links;
                var l1 = links.Create();
                var l2 = links.Create();

                Global.Trash = links.Update(l2, l2, l1, l2);

                links.Delete(l1);

                links.Unsync.DisposeIfPossible(); // Close links to access log

                Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(scope.TempTransactionLogFilename);
            }
        }

        [Fact]
        public static void TransactionAutoRevertedTest()
        {
            // Auto Reverted (Because no commit at transaction)
            using (var scope = new TempLinksTestScope(useLog: true))
            {
                var links = scope.Links;
                var transactionsLayer = (UInt64LinksTransactionsLayer)scope.MemoryAdapter;
                using (var transaction = transactionsLayer.BeginTransaction())
                {
                    var l1 = links.Create();
                    var l2 = links.Create();

                    links.Update(l2, l2, l1, l2);
                }

                Assert.Equal(0UL, links.Count());

                links.Unsync.DisposeIfPossible();

                var transitions = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(scope.TempTransactionLogFilename);
                Assert.Single(transitions);
            }
        }

        [Fact]
        public static void TransactionUserCodeErrorNoDataSavedTest()
        {
            // User Code Error (Autoreverted), no data saved
            var itself = _constants.Itself;

            TempLinksTestScope lastScope = null;
            try
            {
                using (var scope = lastScope = new TempLinksTestScope(deleteFiles: false, useLog: true))
                {
                    var links = scope.Links;
                    var transactionsLayer = (UInt64LinksTransactionsLayer)((LinksDisposableDecoratorBase<ulong>)links.Unsync).Links;
                    using (var transaction = transactionsLayer.BeginTransaction())
                    {
                        var l1 = links.CreateAndUpdate(itself, itself);
                        var l2 = links.CreateAndUpdate(itself, itself);

                        l2 = links.Update(l2, l2, l1, l2);
                    links.CreateAndUpdate(l2, itself);
                    links.CreateAndUpdate(l2, itself);

                    //Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(scope.TempTransactionLogFilename);

                    l2 = links.Update(l2, l1);

                    links.Delete(l2);

                    ExceptionThrower();

                    transaction.Commit();
                }

                Global.Trash = links.Count();
            }
        }
        catch
        {
            Assert.False(lastScope == null);

            var transitions = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(lastScope.TempTransactionLogFilename);

            Assert.True(transitions.Length == 1 && transitions[0].Before.IsNull() &&
                transitions[0].After.IsNull());

            lastScope.DeleteFiles();
        }
    }

    [Fact]
    public static void TransactionUserCodeErrorSomeDataSavedTest()
    {
        // User Code Error (Autoreverted), some data saved
        var itself = _constants.Itself;

        TempLinksTestScope lastScope = null;
        try
        {
            ulong l1;
            ulong l2;

            using (var scope = new TempLinksTestScope(useLog: true))
            {
                var links = scope.Links;
                l1 = links.CreateAndUpdate(itself, itself);
                l2 = links.CreateAndUpdate(itself, itself);

                l2 = links.Update(l2, l2, l1, l2);

                links.CreateAndUpdate(l2, itself);
                links.CreateAndUpdate(l2, itself);

                links.Unsync.DisposeIfPossible();

                Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(
                    scope.TempTransactionLogFilename);
            }

            using (var scope = lastScope = new TempLinksTestScope(deleteFiles: false,
                useLog: true))
            {
                var links = scope.Links;
                var transactionsLayer = (UInt64LinksTransactionsLayer)links.Unsync;
                using (var transaction = transactionsLayer.BeginTransaction())
                {
                    l2 = links.Update(l2, l1);

                    links.Delete(l2);

                    ExceptionThrower();

                    transaction.Commit();
                }

                Global.Trash = links.Count();
            }
            }
            catch
            {
                Assert.False(lastScope == null);

                Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(last
                 ↪  Scope.TempTransactionLogFilename);

                lastScope.DeleteFiles();
            }
        }

        [Fact]
        public static void TransactionCommit()
        {
            var itself = _constants.Itself;

            var tempDatabaseFilename = Path.GetTempFileName();
            var tempTransactionLogFilename = Path.GetTempFileName();

            // Commit
            using (var memoryAdapter = new UInt64LinksTransactionsLayer(new
             ↪  UInt64ResizableDirectMemoryLinks(tempDatabaseFilename),
             ↪  tempTransactionLogFilename))
            using (var links = new UInt64Links(memoryAdapter))
            {
                using (var transaction = memoryAdapter.BeginTransaction())
                {
                    var l1 = links.CreateAndUpdate(itself, itself);
                    var l2 = links.CreateAndUpdate(itself, itself);

                    Global.Trash = links.Update(l2, l2, l1, l2);

                    links.Delete(l1);

                    transaction.Commit();
                }

                Global.Trash = links.Count();
            }

            Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(tempTran
             ↪  sactionLogFilename);
        }

        [Fact]
        public static void TransactionDamage()
        {
            var itself = _constants.Itself;

            var tempDatabaseFilename = Path.GetTempFileName();
            var tempTransactionLogFilename = Path.GetTempFileName();

            // Commit
            using (var memoryAdapter = new UInt64LinksTransactionsLayer(new
             ↪  UInt64ResizableDirectMemoryLinks(tempDatabaseFilename),
             ↪  tempTransactionLogFilename))
            using (var links = new UInt64Links(memoryAdapter))
            {
                using (var transaction = memoryAdapter.BeginTransaction())
                {
                    var l1 = links.CreateAndUpdate(itself, itself);
                    var l2 = links.CreateAndUpdate(itself, itself);

                    Global.Trash = links.Update(l2, l2, l1, l2);

                    links.Delete(l1);

                    transaction.Commit();
                }

                Global.Trash = links.Count();
            }

            Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(tempTran
             ↪  sactionLogFilename);

            // Damage database

            FileHelpers.WriteFirst(tempTransactionLogFilename, new UInt64LinksTransactionsLayer.Transition(new UniqueTimestampFactory(), 555));

            // Try load damaged database
            try
            {
                // TODO: Fix
                using (var memoryAdapter = new UInt64LinksTransactionsLayer(new UInt64ResizableDirectMemoryLinks(tempDatabaseFilename), tempTransactionLogFilename))
                using (var links = new UInt64Links(memoryAdapter))
                {
                    Global.Trash = links.Count();
                }
            }
            catch (NotSupportedException ex)
            {
                Assert.True(ex.Message == "Database is damaged, autorecovery is not supported yet.");
            }

            Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(tempTransactionLogFilename);

            File.Delete(tempDatabaseFilename);
            File.Delete(tempTransactionLogFilename);
        }

        [Fact]
        public static void Bug1Test()
        {
            var tempDatabaseFilename = Path.GetTempFileName();
            var tempTransactionLogFilename = Path.GetTempFileName();

            var itself = _constants.Itself;

            // User Code Error (Autoreverted), some data saved
            try
            {
                ulong l1;
                ulong l2;

                using (var memoryAdapter = new UInt64LinksTransactionsLayer(new UInt64ResizableDirectMemoryLinks(tempDatabaseFilename), tempTransactionLogFilename))
                using (var links = new UInt64Links(memoryAdapter))
                {
                    l1 = links.CreateAndUpdate(itself, itself);
                    l2 = links.CreateAndUpdate(itself, itself);

                    l2 = links.Update(l2, l2, l1, l2);

                    links.CreateAndUpdate(l2, itself);
                    links.CreateAndUpdate(l2, itself);
                }

                Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(tempTransactionLogFilename);

                using (var memoryAdapter = new UInt64LinksTransactionsLayer(new UInt64ResizableDirectMemoryLinks(tempDatabaseFilename), tempTransactionLogFilename))
                using (var links = new UInt64Links(memoryAdapter))
                {
                    using (var transaction = memoryAdapter.BeginTransaction())
                    {
                        l2 = links.Update(l2, l1);

                        links.Delete(l2);

                        ExceptionThrower();

                        transaction.Commit();
                    }

                    Global.Trash = links.Count();
                }
            }
            catch
```

```csharp
            {
                Global.Trash = FileHelpers.ReadAll<UInt64LinksTransactionsLayer.Transition>(tempTransactionLogFilename);
            }

            File.Delete(tempDatabaseFilename);
            File.Delete(tempTransactionLogFilename);
        }

        private static void ExceptionThrower()
        {
            throw new Exception();
        }

        [Fact]
        public static void PathsTest()
        {
            var source = _constants.SourcePart;
            var target = _constants.TargetPart;

            using (var scope = new TempLinksTestScope())
            {
                var links = scope.Links;
                var l1 = links.CreatePoint();
                var l2 = links.CreatePoint();

                var r1 = links.GetByKeys(l1, source, target, source);
                var r2 = links.CheckPathExistance(l2, l2, l2, l2);
            }
        }

        [Fact]
        public static void RecursiveStringFormattingTest()
        {
            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences; // TODO: Auto use sequences on Sequences getter.

                var a = links.CreatePoint();
                var b = links.CreatePoint();
                var c = links.CreatePoint();

                var ab = links.CreateAndUpdate(a, b);
                var cb = links.CreateAndUpdate(c, b);
                var ac = links.CreateAndUpdate(a, c);

                a = links.Update(a, c, b);
                b = links.Update(b, a, c);
                c = links.Update(c, a, b);

                Debug.WriteLine(links.FormatStructure(ab, link => link.IsFullPoint(), true));
                Debug.WriteLine(links.FormatStructure(cb, link => link.IsFullPoint(), true));
                Debug.WriteLine(links.FormatStructure(ac, link => link.IsFullPoint(), true));

                Assert.True(links.FormatStructure(cb, link => link.IsFullPoint(), true) ==
                    "(5:(4:5 (6:5 4)) 6)");
                Assert.True(links.FormatStructure(ac, link => link.IsFullPoint(), true) ==
                    "(6:(5:(4:5 6) 6) 4)");
                Assert.True(links.FormatStructure(ab, link => link.IsFullPoint(), true) ==
                    "(4:(5:4 (6:5 4)) 6)");

                // TODO: Think how to build balanced syntax tree while formatting structure (eg.
                    "(4:(5:4 6) (6:5 4)") instead of "(4:(5:4 (6:5 4)) 6)"

                Assert.True(sequences.SafeFormatSequence(cb, DefaultFormatter, false) ==
                    "{{5}{5}{4}{6}}");
                Assert.True(sequences.SafeFormatSequence(ac, DefaultFormatter, false) ==
                    "{{5}{6}{6}{4}}");
                Assert.True(sequences.SafeFormatSequence(ab, DefaultFormatter, false) ==
                    "{{4}{5}{4}{6}}");
            }
        }

        private static void DefaultFormatter(StringBuilder sb, ulong link)
        {
            sb.Append(link.ToString());
        }

        #endregion

        #region Performance

        /*
       public static void RunAllPerformanceTests()
       {
           try
           {
               links.TestLinksInSteps();
           }
           catch (Exception ex)
           {
               ex.WriteToConsole();
           }

           return;

           try
           {
               //ThreadPool.SetMaxThreads(2, 2);

               // Запускаем все тесты дважды, чтобы первоначальная инициализация не повлияла на результат
               // Также это дополнительно помогает в отладке
               // Увеличивает вероятность попадания информации в кэши
               for (var i = 0; i < 10; i++)
               {
                   //0 - 10 ГБ
                   //Каждые 100 МБ срез цифр

                   //links.TestGetSourceFunction();
                   //links.TestGetSourceFunctionInParallel();
                   //links.TestGetTargetFunction();
                   //links.TestGetTargetFunctionInParallel();
                   links.Create64BillionLinks();

                   links.TestRandomSearchFixed();
                   //links.Create64BillionLinksInParallel();
                   links.TestEachFunction();
                   //links.TestForeach();
                   //links.TestParallelForeach();
               }

               links.TestDeletionOfAllLinks();

           }
           catch (Exception ex)
           {
               ex.WriteToConsole();
           }
       }*/

        /*
       public static void TestLinksInSteps()
       {
           const long gibibyte = 1024 * 1024 * 1024;
           const long mebibyte = 1024 * 1024;

           var totalLinksToCreate = gibibyte / Platform.Links.Data.Core.Doublets.Links.LinkSizeInBytes;
           var linksStep = 102 * mebibyte / Platform.Links.Data.Core.Doublets.Links.LinkSizeInBytes;

           var creationMeasurements = new List<TimeSpan>();
           var searchMeasuremets = new List<TimeSpan>();
           var deletionMeasurements = new List<TimeSpan>();

           GetBaseRandomLoopOverhead(linksStep);
           GetBaseRandomLoopOverhead(linksStep);

           var stepLoopOverhead = GetBaseRandomLoopOverhead(linksStep);

           ConsoleHelpers.Debug("Step loop overhead: {0}.", stepLoopOverhead);

           var loops = totalLinksToCreate / linksStep;

           for (int i = 0; i < loops; i++)
           {
                creationMeasurements.Add(Measure(() => links.RunRandomCreations(linksStep)));
                searchMeasuremets.Add(Measure(() => links.RunRandomSearches(linksStep)));

                Console.Write("\rC + S {0}/{1}", i + 1, loops);
            }

            ConsoleHelpers.Debug();

            for (int i = 0; i < loops; i++)
            {
                deletionMeasurements.Add(Measure(() => links.RunRandomDeletions(linksStep)));

                Console.Write("\rD {0}/{1}", i + 1, loops);
            }

            ConsoleHelpers.Debug();

            ConsoleHelpers.Debug("C S D");

            for (int i = 0; i < loops; i++)
            {
                ConsoleHelpers.Debug("{0} {1} {2}", creationMeasurements[i],
↪   searchMeasuremets[i], deletionMeasurements[i]);
            }

            ConsoleHelpers.Debug("C S D (no overhead)");

            for (int i = 0; i < loops; i++)
            {
                ConsoleHelpers.Debug("{0} {1} {2}", creationMeasurements[i] - stepLoopOverhead,
↪   searchMeasuremets[i] - stepLoopOverhead, deletionMeasurements[i] - stepLoopOverhead);
            }

            ConsoleHelpers.Debug("All tests done. Total links left in database: {0}.",
↪   links.Total);
        }

        private static void CreatePoints(this Platform.Links.Data.Core.Doublets.Links links, long
↪   amountToCreate)
        {
            for (long i = 0; i < amountToCreate; i++)
                links.Create(0, 0);
        }

         private static TimeSpan GetBaseRandomLoopOverhead(long loops)
         {
             return Measure(() =>
             {
                 ulong maxValue = RandomHelpers.DefaultFactory.NextUInt64();
                 ulong result = 0;
                 for (long i = 0; i < loops; i++)
                 {
                     var source = RandomHelpers.DefaultFactory.NextUInt64(maxValue);
                     var target = RandomHelpers.DefaultFactory.NextUInt64(maxValue);

                     result += maxValue + source + target;
                 }
                 Global.Trash = result;
             });
         }
          */

         [Fact(Skip = "performance test")]
         public static void GetSourceTest()
         {
             using (var scope = new TempLinksTestScope())
             {
                 var links = scope.Links;
                 ConsoleHelpers.Debug("Testing GetSource function with {0} Iterations.",
                  ↪  Iterations);

                 ulong counter = 0;

                 //var firstLink = links.First();
                 // Создаём одну связь, из которой будет производить считывание
                 var firstLink = links.Create();

                 var sw = Stopwatch.StartNew();

                // Тестируем саму функцию
                for (ulong i = 0; i < Iterations; i++)
                {
                    counter += links.GetSource(firstLink);
                }

                var elapsedTime = sw.Elapsed;

                var iterationsPerSecond = Iterations / elapsedTime.TotalSeconds;

                // Удаляем связь, из которой производилось считывание
                links.Delete(firstLink);

                ConsoleHelpers.Debug(
                    "{0} Iterations of GetSource function done in {1} ({2} Iterations per
                    ↪  second), counter result: {3}",
                    Iterations, elapsedTime, (long)iterationsPerSecond, counter);
            }
        }

        [Fact(Skip = "performance test")]
        public static void GetSourceInParallel()
        {
            using (var scope = new TempLinksTestScope())
            {
                var links = scope.Links;
                ConsoleHelpers.Debug("Testing GetSource function with {0} Iterations in
                ↪  parallel.", Iterations);

                long counter = 0;

                //var firstLink = links.First();
                var firstLink = links.Create();

                var sw = Stopwatch.StartNew();

                // Тестируем саму функцию
                Parallel.For(0, Iterations, x =>
                {
                    Interlocked.Add(ref counter, (long)links.GetSource(firstLink));
                    //Interlocked.Increment(ref counter);
                });

                var elapsedTime = sw.Elapsed;

                var iterationsPerSecond = Iterations / elapsedTime.TotalSeconds;

                links.Delete(firstLink);

                ConsoleHelpers.Debug(
                    "{0} Iterations of GetSource function done in {1} ({2} Iterations per
                    ↪  second), counter result: {3}",
                    Iterations, elapsedTime, (long)iterationsPerSecond, counter);
            }
        }

        [Fact(Skip = "performance test")]
        public static void TestGetTarget()
        {
            using (var scope = new TempLinksTestScope())
            {
                var links = scope.Links;
                ConsoleHelpers.Debug("Testing GetTarget function with {0} Iterations.",
                ↪  Iterations);

                ulong counter = 0;

                //var firstLink = links.First();
                var firstLink = links.Create();

                var sw = Stopwatch.StartNew();

                for (ulong i = 0; i < Iterations; i++)
                {
                    counter += links.GetTarget(firstLink);
                }

                var elapsedTime = sw.Elapsed;

                var iterationsPerSecond = Iterations / elapsedTime.TotalSeconds;

            links.Delete(firstLink);

            ConsoleHelpers.Debug(
                "{0} Iterations of GetTarget function done in {1} ({2} Iterations per second), counter result: {3}",
                Iterations, elapsedTime, (long)iterationsPerSecond, counter);
        }
    }

    [Fact(Skip = "performance test")]
    public static void TestGetTargetInParallel()
    {
        using (var scope = new TempLinksTestScope())
        {
            var links = scope.Links;
            ConsoleHelpers.Debug("Testing GetTarget function with {0} Iterations in parallel.", Iterations);

            long counter = 0;

            //var firstLink = links.First();
            var firstLink = links.Create();

            var sw = Stopwatch.StartNew();

            Parallel.For(0, Iterations, x =>
            {
                Interlocked.Add(ref counter, (long)links.GetTarget(firstLink));
                //Interlocked.Increment(ref counter);
            });

            var elapsedTime = sw.Elapsed;

            var iterationsPerSecond = Iterations / elapsedTime.TotalSeconds;

            links.Delete(firstLink);

            ConsoleHelpers.Debug(
                "{0} Iterations of GetTarget function done in {1} ({2} Iterations per second), counter result: {3}",
                Iterations, elapsedTime, (long)iterationsPerSecond, counter);
        }
    }

    // TODO: Заполнить базу данных перед тестом
    /*
    [Fact]
    public void TestRandomSearchFixed()
    {
        var tempFilename = Path.GetTempFileName();

        using (var links = new Platform.Links.Data.Core.Doublets.Links(tempFilename, DefaultLinksSizeStep))
        {
            long iterations = 64 * 1024 * 1024 / Platform.Links.Data.Core.Doublets.Links.LinkSizeInBytes;

            ulong counter = 0;
            var maxLink = links.Total;

            ConsoleHelpers.Debug("Testing Random Search with {0} Iterations.", iterations);

            var sw = Stopwatch.StartNew();

            for (var i = iterations; i > 0; i--)
            {
                var source = RandomHelpers.DefaultFactory.NextUInt64(LinksConstants.MinPossibleIndex, maxLink);
                var target = RandomHelpers.DefaultFactory.NextUInt64(LinksConstants.MinPossibleIndex, maxLink);

                counter += links.Search(source, target);
            }

            var elapsedTime = sw.Elapsed;

            var iterationsPerSecond = iterations / elapsedTime.TotalSeconds;

```

```
                ConsoleHelpers.Debug("{0} Iterations of Random Search done in {1} ({2}
↪   Iterations per second), c: {3}", iterations, elapsedTime, (long)iterationsPerSecond,
↪   counter);
            }

            File.Delete(tempFilename);
        }*/

        [Fact(Skip = "useless: O(0), was dependent on creation tests")]
        public static void TestRandomSearchAll()
        {
            using (var scope = new TempLinksTestScope())
            {
                var links = scope.Links;
                ulong counter = 0;

                var maxLink = links.Count();

                var iterations = links.Count();

                ConsoleHelpers.Debug("Testing Random Search with {0} Iterations.",
                ↪  links.Count());

                var sw = Stopwatch.StartNew();

                for (var i = iterations; i > 0; i--)
                {
                    var linksAddressRange = new Range<ulong>(_constants.MinPossibleIndex,
                    ↪  maxLink);

                    var source = RandomHelpers.Default.NextUInt64(linksAddressRange);
                    var target = RandomHelpers.Default.NextUInt64(linksAddressRange);

                    counter += links.SearchOrDefault(source, target);
                }

                var elapsedTime = sw.Elapsed;

                var iterationsPerSecond = iterations / elapsedTime.TotalSeconds;

                ConsoleHelpers.Debug("{0} Iterations of Random Search done in {1} ({2}
                ↪  Iterations per second), c: {3}",
                     iterations, elapsedTime, (long)iterationsPerSecond, counter);
            }
        }

        [Fact(Skip = "useless: O(0), was dependent on creation tests")]
        public static void TestEach()
        {
            using (var scope = new TempLinksTestScope())
            {
                var links = scope.Links;

                var counter = new Counter<IList<ulong>, ulong>(links.Constants.Continue);

                ConsoleHelpers.Debug("Testing Each function.");

                var sw = Stopwatch.StartNew();

                links.Each(counter.IncrementAndReturnTrue);

                var elapsedTime = sw.Elapsed;

                var linksPerSecond = counter.Count / elapsedTime.TotalSeconds;

                ConsoleHelpers.Debug("{0} Iterations of Each's handler function done in {1} ({2}
                ↪  links per second)",
                    counter, elapsedTime, (long)linksPerSecond);
            }
        }

        /*
        [Fact]
        public static void TestForeach()
        {
            var tempFilename = Path.GetTempFileName();

            using (var links = new Platform.Links.Data.Core.Doublets.Links(tempFilename,
↪   DefaultLinksSizeStep))
```

```
            {
                ulong counter = 0;

                ConsoleHelpers.Debug("Testing foreach through links.");

                var sw = Stopwatch.StartNew();

                //foreach (var link in links)
                //{
                //    counter++;
                //}

                var elapsedTime = sw.Elapsed;

                var linksPerSecond = (double)counter / elapsedTime.TotalSeconds;

                ConsoleHelpers.Debug("{0} Iterations of Foreach's handler block done in {1} ({2}
↪   links per second)", counter, elapsedTime, (long)linksPerSecond);
            }

            File.Delete(tempFilename);
        }
        */

        /*
        [Fact]
        public static void TestParallelForeach()
        {
            var tempFilename = Path.GetTempFileName();

            using (var links = new Platform.Links.Data.Core.Doublets.Links(tempFilename,
↪   DefaultLinksSizeStep))
            {

                long counter = 0;

                ConsoleHelpers.Debug("Testing parallel foreach through links.");

                var sw = Stopwatch.StartNew();

                //Parallel.ForEach((IEnumerable<ulong>)links, x =>
                //{
                //    Interlocked.Increment(ref counter);
                //});

                var elapsedTime = sw.Elapsed;

                var linksPerSecond = (double)counter / elapsedTime.TotalSeconds;

                ConsoleHelpers.Debug("{0} Iterations of Parallel Foreach's handler block done in
↪   {1} ({2} links per second)", counter, elapsedTime, (long)linksPerSecond);
            }

            File.Delete(tempFilename);
        }
        */

        [Fact(Skip = "performance test")]
        public static void Create64BillionLinks()
        {
            using (var scope = new TempLinksTestScope())
            {
                var links = scope.Links;
                var linksBeforeTest = links.Count();

                long linksToCreate = 64 * 1024 * 1024 /
                 ↪  UInt64ResizableDirectMemoryLinks.LinkSizeInBytes;

                ConsoleHelpers.Debug("Creating {0} links.", linksToCreate);

                var elapsedTime = Performance.Measure(() =>
                {
                    for (long i = 0; i < linksToCreate; i++)
                    {
                        links.Create();
                    }
                });

                var linksCreated = links.Count() - linksBeforeTest;
                var linksPerSecond = linksCreated / elapsedTime.TotalSeconds;

                ConsoleHelpers.Debug("Current links count: {0}.", links.Count());

                ConsoleHelpers.Debug("{0} links created in {1} ({2} links per second)",
                 ↪  linksCreated, elapsedTime,
                    (long)linksPerSecond);
            }
        }

        [Fact(Skip = "performance test")]
        public static void Create64BillionLinksInParallel()
        {
            using (var scope = new TempLinksTestScope())
            {
                var links = scope.Links;
                var linksBeforeTest = links.Count();

                var sw = Stopwatch.StartNew();

                long linksToCreate = 64 * 1024 * 1024 /
                 ↪  UInt64ResizableDirectMemoryLinks.LinkSizeInBytes;

                ConsoleHelpers.Debug("Creating {0} links in parallel.", linksToCreate);

                Parallel.For(0, linksToCreate, x => links.Create());

                var elapsedTime = sw.Elapsed;

                var linksCreated = links.Count() - linksBeforeTest;
                var linksPerSecond = linksCreated / elapsedTime.TotalSeconds;

                ConsoleHelpers.Debug("{0} links created in {1} ({2} links per second)",
                 ↪  linksCreated, elapsedTime,
                    (long)linksPerSecond);
            }
        }

        [Fact(Skip = "useless: O(0), was dependent on creation tests")]
        public static void TestDeletionOfAllLinks()
        {
            using (var scope = new TempLinksTestScope())
            {
                var links = scope.Links;
                var linksBeforeTest = links.Count();

                ConsoleHelpers.Debug("Deleting all links");

                var elapsedTime = Performance.Measure(links.DeleteAll);

                var linksDeleted = linksBeforeTest - links.Count();
                var linksPerSecond = linksDeleted / elapsedTime.TotalSeconds;

                ConsoleHelpers.Debug("{0} links deleted in {1} ({2} links per second)",
                 ↪  linksDeleted, elapsedTime,
                    (long)linksPerSecond);
            }
        }

        #endregion
    }
}
```

./Platform.Data.Doublets.Tests/OptimalVariantSequenceTests.cs

```
using System;
using System.Linq;
using System.Collections.Generic;
using Xunit;
using Platform.Interfaces;
using Platform.Data.Doublets.Sequences;
using Platform.Data.Doublets.Sequences.Frequencies.Cache;
using Platform.Data.Doublets.Sequences.Frequencies.Counters;
using Platform.Data.Doublets.Sequences.Converters;
using Platform.Data.Doublets.PropertyOperators;
using Platform.Data.Doublets.Incrementers;
using Platform.Data.Doublets.Converters;

namespace Platform.Data.Doublets.Tests
{
    public static class OptimalVariantSequenceTests
    {
        private const string SequenceExample = "зеленела зелёная зелень";

        [Fact]
        public static void LinksBasedFrequencyStoredOptimalVariantSequenceTest()
        {
            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;
                var constants = links.Constants;

                links.UseUnicode();

                var sequence = UnicodeMap.FromStringToLinkArray(SequenceExample);

                var meaningRoot = links.CreatePoint();
                var unaryOne = links.CreateAndUpdate(meaningRoot, constants.Itself);
                var frequencyMarker = links.CreateAndUpdate(meaningRoot, constants.Itself);
                var frequencyPropertyMarker = links.CreateAndUpdate(meaningRoot,
                ↪  constants.Itself);

                var unaryNumberToAddressConveter = new
                ↪  UnaryNumberToAddressAddOperationConverter<ulong>(links, unaryOne);
                var unaryNumberIncrementer = new UnaryNumberIncrementer<ulong>(links, unaryOne);
                var frequencyIncrementer = new FrequencyIncrementer<ulong>(links,
                ↪  frequencyMarker, unaryOne, unaryNumberIncrementer);
                var frequencyPropertyOperator = new PropertyOperator<ulong>(links,
                ↪  frequencyPropertyMarker, frequencyMarker);
                var linkFrequencyIncrementer = new LinkFrequencyIncrementer<ulong>(links,
                ↪  frequencyPropertyOperator, frequencyIncrementer);
                var linkToItsFrequencyNumberConverter = new
                ↪  LinkToItsFrequencyNumberConveter<ulong>(links, frequencyPropertyOperator,
                ↪  unaryNumberToAddressConveter);
                var sequenceToItsLocalElementLevelsConverter = new
                ↪  SequenceToItsLocalElementLevelsConverter<ulong>(links,
                ↪  linkToItsFrequencyNumberConverter);
                var optimalVariantConverter = new OptimalVariantConverter<ulong>(links,
                ↪  sequenceToItsLocalElementLevelsConverter);

                ExecuteTest(links, sequences, sequence,
                ↪  sequenceToItsLocalElementLevelsConverter, linkFrequencyIncrementer,
                ↪  optimalVariantConverter);
            }
        }

        [Fact]
        public static void DictionaryBasedFrequencyStoredOptimalVariantSequenceTest()
        {
            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                links.UseUnicode();

                var sequence = UnicodeMap.FromStringToLinkArray(SequenceExample);

                var linksToFrequencies = new Dictionary<ulong, ulong>();

                var totalSequenceSymbolFrequencyCounter = new
                ↪  TotalSequenceSymbolFrequencyCounter<ulong>(links);

                var linkFrequenciesCache = new LinkFrequenciesCache<ulong>(links,
                ↪  totalSequenceSymbolFrequencyCounter);

                var linkFrequencyIncrementer = new
                ↪  FrequenciesCacheBasedLinkFrequencyIncrementer<ulong>(linkFrequenciesCache);
                var linkToItsFrequencyNumberConverter = new FrequenciesCacheBasedLinkToItsFreque⌋
                ↪  ncyNumberConverter<ulong>(linkFrequenciesCache);

                var sequenceToItsLocalElementLevelsConverter = new
                ↪  SequenceToItsLocalElementLevelsConverter<ulong>(links,
                ↪  linkToItsFrequencyNumberConverter);
                var optimalVariantConverter = new OptimalVariantConverter<ulong>(links,
                ↪  sequenceToItsLocalElementLevelsConverter);

                ExecuteTest(links, sequences, sequence,
                ↪  sequenceToItsLocalElementLevelsConverter, linkFrequencyIncrementer,
                ↪  optimalVariantConverter);
            }
        }

        private static void ExecuteTest(SynchronizedLinks<ulong> links, Sequences.Sequences
        ↪  sequences, ulong[] sequence, SequenceToItsLocalElementLevelsConverter<ulong>
        ↪  sequenceToItsLocalElementLevelsConverter, IIncrementer<IList<ulong>>
        ↪  linkFrequencyIncrementer, OptimalVariantConverter<ulong> optimalVariantConverter)
        {
            linkFrequencyIncrementer.Increment(sequence);

            var levels = sequenceToItsLocalElementLevelsConverter.Convert(sequence);

            var optimalVariant = optimalVariantConverter.Convert(sequence);

            var readSequence1 = sequences.ReadSequenceCore(optimalVariant, links.IsPartialPoint);

            Assert.True(sequence.SequenceEqual(readSequence1));
        }
    }
}
```

./Platform.Data.Doublets.Tests/ReadSequenceTests.cs

```
using System;
using System.Collections.Generic;
using System.Diagnostics;
using System.Linq;
using Xunit;
using Platform.Data.Sequences;
using Platform.Data.Doublets.Sequences.Converters;

namespace Platform.Data.Doublets.Tests
{
    public static class ReadSequenceTests
    {
        [Fact]
        public static void ReadSequenceTest()
        {
            const long sequenceLength = 2000;

            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var sequence = new ulong[sequenceLength];
                for (var i = 0; i < sequenceLength; i++)
                {
                    sequence[i] = links.Create();
                }

                var balancedVariantConverter = new BalancedVariantConverter<ulong>(links);

                var sw1 = Stopwatch.StartNew();
                var balancedVariant = balancedVariantConverter.Convert(sequence); sw1.Stop();

                var sw2 = Stopwatch.StartNew();
                var readSequence1 = sequences.ReadSequenceCore(balancedVariant,
                ↪  links.IsPartialPoint); sw2.Stop();

                var sw3 = Stopwatch.StartNew();
                var readSequence2 = new List<ulong>();
                SequenceWalker.WalkRight(balancedVariant,
                                         links.GetSource,
                                         links.GetTarget,
                                         links.IsPartialPoint,
                                         readSequence2.Add);
                sw3.Stop();

                Assert.True(sequence.SequenceEqual(readSequence1));

                Assert.True(sequence.SequenceEqual(readSequence2));

                // Assert.True(sw2.Elapsed < sw3.Elapsed);

                Console.WriteLine($"Stack-based walker: {sw3.Elapsed}, Level-based reader:
                ↪  {sw2.Elapsed}");

                for (var i = 0; i < sequenceLength; i++)
                {
                    links.Delete(sequence[i]);
                    }
                }
            }
        }
    }
```

./Platform.Data.Doublets.Tests/ResizableDirectMemoryLinksTests.cs

```
using System.IO;
using Xunit;
using Platform.Singletons;
using Platform.Memory;
using Platform.Data.Constants;
using Platform.Data.Doublets.ResizableDirectMemory;

namespace Platform.Data.Doublets.Tests
{
    public static class ResizableDirectMemoryLinksTests
    {
        private static readonly LinksCombinedConstants<ulong, ulong, int> _constants =
         ↪  Default<LinksCombinedConstants<ulong, ulong, int>>.Instance;

        [Fact]
        public static void BasicFileMappedMemoryTest()
        {
            var tempFilename = Path.GetTempFileName();
            using (var memoryAdapter = new UInt64ResizableDirectMemoryLinks(tempFilename))
            {
                memoryAdapter.TestBasicMemoryOperations();
            }
            File.Delete(tempFilename);
        }

        [Fact]
        public static void BasicHeapMemoryTest()
        {
            using (var memory = new
             ↪  HeapResizableDirectMemory(UInt64ResizableDirectMemoryLinks.DefaultLinksSizeStep))
            using (var memoryAdapter = new UInt64ResizableDirectMemoryLinks(memory,
             ↪  UInt64ResizableDirectMemoryLinks.DefaultLinksSizeStep))
            {
                memoryAdapter.TestBasicMemoryOperations();
            }
        }

        private static void TestBasicMemoryOperations(this ILinks<ulong> memoryAdapter)
        {
            var link = memoryAdapter.Create();
            memoryAdapter.Delete(link);
        }

        [Fact]
        public static void NonexistentReferencesHeapMemoryTest()
        {
            using (var memory = new
             ↪  HeapResizableDirectMemory(UInt64ResizableDirectMemoryLinks.DefaultLinksSizeStep))
            using (var memoryAdapter = new UInt64ResizableDirectMemoryLinks(memory,
             ↪  UInt64ResizableDirectMemoryLinks.DefaultLinksSizeStep))
            {
                memoryAdapter.TestNonexistentReferences();
            }
        }

        private static void TestNonexistentReferences(this ILinks<ulong> memoryAdapter)
        {
            var link = memoryAdapter.Create();
            memoryAdapter.Update(link, ulong.MaxValue, ulong.MaxValue);
            var resultLink = _constants.Null;
            memoryAdapter.Each(foundLink =>
            {
                resultLink = foundLink[_constants.IndexPart];
                return _constants.Break;
            }, _constants.Any, ulong.MaxValue, ulong.MaxValue);
            Assert.True(resultLink == link);
            Assert.True(memoryAdapter.Count(ulong.MaxValue) == 0);
            memoryAdapter.Delete(link);
        }
    }
}
```

./Platform.Data.Doublets.Tests/ScopeTests.cs

```
using Xunit;
using Platform.Scopes;
using Platform.Memory;
using Platform.Data.Doublets.ResizableDirectMemory;
using Platform.Data.Doublets.Decorators;

namespace Platform.Data.Doublets.Tests
{
    public static class ScopeTests
    {
        [Fact]
        public static void SingleDependencyTest()
        {
            using (var scope = new Scope())
            {
                scope.IncludeAssemblyOf<IMemory>();
                var instance = scope.Use<IDirectMemory>();
                Assert.IsType<HeapResizableDirectMemory>(instance);
            }
        }

        [Fact]
        public static void CascadeDependencyTest()
        {
            using (var scope = new Scope())
            {
                scope.Include<TemporaryFileMappedResizableDirectMemory>();
                scope.Include<UInt64ResizableDirectMemoryLinks>();
                var instance = scope.Use<ILinks<ulong>>();
                Assert.IsType<UInt64ResizableDirectMemoryLinks>(instance);
            }
        }

        [Fact]
        public static void FullAutoResolutionTest()
        {
            using (var scope = new Scope(autoInclude: true, autoExplore: true))
            {
                var instance = scope.Use<UInt64Links>();
                Assert.IsType<UInt64Links>(instance);
            }
        }
    }
}
```

./Platform.Data.Doublets.Tests/SequencesTests.cs

```
using System;
using System.Collections.Generic;
using System.Diagnostics;
using System.Linq;
using Xunit;
using Platform.Collections;
using Platform.Random;
using Platform.IO;
using Platform.Singletons;
using Platform.Data.Constants;
using Platform.Data.Doublets.Sequences;
using Platform.Data.Doublets.Sequences.Frequencies.Cache;
using Platform.Data.Doublets.Sequences.Frequencies.Counters;
using Platform.Data.Doublets.Sequences.Converters;

namespace Platform.Data.Doublets.Tests
{
    public static class SequencesTests
    {
        private static readonly LinksCombinedConstants<bool, ulong, int> _constants =
        ↪  Default<LinksCombinedConstants<bool, ulong, int>>.Instance;

        static SequencesTests()
        {
            // Trigger static constructor to not mess with perfomance measurements
            _ = BitString.GetBitMaskFromIndex(1);
        }

        [Fact]
        public static void CreateAllVariantsTest()
        {
            const long sequenceLength = 8;

            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var sequence = new ulong[sequenceLength];
                for (var i = 0; i < sequenceLength; i++)
                {
                    sequence[i] = links.Create();
                }

                var sw1 = Stopwatch.StartNew();
                var results1 = sequences.CreateAllVariants1(sequence); sw1.Stop();

                var sw2 = Stopwatch.StartNew();
                var results2 = sequences.CreateAllVariants2(sequence); sw2.Stop();

                Assert.True(results1.Count > results2.Length);
                Assert.True(sw1.Elapsed > sw2.Elapsed);

                for (var i = 0; i < sequenceLength; i++)
                {
                    links.Delete(sequence[i]);
                }

                Assert.True(links.Count() == 0);
            }
        }

        //[Fact]
        //public void CUDTest()
        //{
        //    var tempFilename = Path.GetTempFileName();

        //    const long sequenceLength = 8;

        //    const ulong itself = LinksConstants.Itself;

        //    using (var memoryAdapter = new ResizableDirectMemoryLinks(tempFilename,
        ↪   DefaultLinksSizeStep))
        //    using (var links = new Links(memoryAdapter))
        //    {
        //        var sequence = new ulong[sequenceLength];
        //        for (var i = 0; i < sequenceLength; i++)
        //            sequence[i] = links.Create(itself, itself);


        //        SequencesOptions o = new SequencesOptions();

        // TODO: Из числа в bool значения o.UseSequenceMarker = ((value & 1) != 0)
        //        o.


        //        var sequences = new Sequences(links);

        //        var sw1 = Stopwatch.StartNew();
        //        var results1 = sequences.CreateAllVariants1(sequence); sw1.Stop();

        //        var sw2 = Stopwatch.StartNew();
        //        var results2 = sequences.CreateAllVariants2(sequence); sw2.Stop();

        //        Assert.True(results1.Count > results2.Length);
        //        Assert.True(sw1.Elapsed > sw2.Elapsed);

        //        for (var i = 0; i < sequenceLength; i++)
        //            links.Delete(sequence[i]);
        //    }

        //    File.Delete(tempFilename);
        //}

        [Fact]
        public static void AllVariantsSearchTest()
        {
            const long sequenceLength = 8;

            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var sequence = new ulong[sequenceLength];
                for (var i = 0; i < sequenceLength; i++)
                {
                    sequence[i] = links.Create();
                }

                var createResults = sequences.CreateAllVariants2(sequence).Distinct().ToArray();

                //for (int i = 0; i < createResults.Length; i++)
                //    sequences.Create(createResults[i]);

                var sw0 = Stopwatch.StartNew();
                var searchResults0 = sequences.GetAllMatchingSequences0(sequence); sw0.Stop();

                var sw1 = Stopwatch.StartNew();
                var searchResults1 = sequences.GetAllMatchingSequences1(sequence); sw1.Stop();

                var sw2 = Stopwatch.StartNew();
                var searchResults2 = sequences.Each1(sequence); sw2.Stop();

                var sw3 = Stopwatch.StartNew();
                var searchResults3 = sequences.Each(sequence); sw3.Stop();

                var intersection0 = createResults.Intersect(searchResults0).ToList();
                Assert.True(intersection0.Count == searchResults0.Count);
                Assert.True(intersection0.Count == createResults.Length);

                var intersection1 = createResults.Intersect(searchResults1).ToList();
                Assert.True(intersection1.Count == searchResults1.Count);
                Assert.True(intersection1.Count == createResults.Length);

                var intersection2 = createResults.Intersect(searchResults2).ToList();
                Assert.True(intersection2.Count == searchResults2.Count);
                Assert.True(intersection2.Count == createResults.Length);

                var intersection3 = createResults.Intersect(searchResults3).ToList();
                Assert.True(intersection3.Count == searchResults3.Count);
                Assert.True(intersection3.Count == createResults.Length);

                for (var i = 0; i < sequenceLength; i++)
                {
                    links.Delete(sequence[i]);
                }
            }
        }

        [Fact]
        public static void BalancedVariantSearchTest()
        {
            const long sequenceLength = 200;

            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var sequence = new ulong[sequenceLength];
                for (var i = 0; i < sequenceLength; i++)
                {
                    sequence[i] = links.Create();
                }

                var balancedVariantConverter = new BalancedVariantConverter<ulong>(links);

                var sw1 = Stopwatch.StartNew();
                var balancedVariant = balancedVariantConverter.Convert(sequence); sw1.Stop();

                var sw2 = Stopwatch.StartNew();
                var searchResults2 = sequences.GetAllMatchingSequences0(sequence); sw2.Stop();

                var sw3 = Stopwatch.StartNew();
                var searchResults3 = sequences.GetAllMatchingSequences1(sequence); sw3.Stop();

                // На количестве в 200 элементов это будет занимать вечность
                //var sw4 = Stopwatch.StartNew();
                //var searchResults4 = sequences.Each(sequence); sw4.Stop();

                Assert.True(searchResults2.Count == 1 && balancedVariant == searchResults2[0]);

                Assert.True(searchResults3.Count == 1 && balancedVariant ==
                ↪  searchResults3.First());

                //Assert.True(sw1.Elapsed < sw2.Elapsed);

                for (var i = 0; i < sequenceLength; i++)
                {
                    links.Delete(sequence[i]);
                }
            }
        }

        [Fact]
        public static void AllPartialVariantsSearchTest()
        {
            const long sequenceLength = 8;

            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var sequence = new ulong[sequenceLength];
                for (var i = 0; i < sequenceLength; i++)
                {
                    sequence[i] = links.Create();
                }

                var createResults = sequences.CreateAllVariants2(sequence);

                //var createResultsStrings = createResults.Select(x => x + ": " +
                ↪  sequences.FormatSequence(x)).ToList();
                //Global.Trash = createResultsStrings;

                var partialSequence = new ulong[sequenceLength - 2];

                Array.Copy(sequence, 1, partialSequence, 0, (int)sequenceLength - 2);

                var sw1 = Stopwatch.StartNew();
                var searchResults1 =
                ↪  sequences.GetAllPartiallyMatchingSequences0(partialSequence); sw1.Stop();

                var sw2 = Stopwatch.StartNew();
                var searchResults2 =
                ↪  sequences.GetAllPartiallyMatchingSequences1(partialSequence); sw2.Stop();

                //var sw3 = Stopwatch.StartNew();
                //var searchResults3 =
                ↪  sequences.GetAllPartiallyMatchingSequences2(partialSequence); sw3.Stop();

                var sw4 = Stopwatch.StartNew();
                var searchResults4 =
                ↪  sequences.GetAllPartiallyMatchingSequences3(partialSequence); sw4.Stop();

                //Global.Trash = searchResults3;

                //var searchResults1Strings = searchResults1.Select(x => x + ": " +
                ↪  sequences.FormatSequence(x)).ToList();
                //Global.Trash = searchResults1Strings;

                var intersection1 = createResults.Intersect(searchResults1).ToList();
                Assert.True(intersection1.Count == createResults.Length);

                var intersection2 = createResults.Intersect(searchResults2).ToList();
                Assert.True(intersection2.Count == createResults.Length);

                var intersection4 = createResults.Intersect(searchResults4).ToList();
                Assert.True(intersection4.Count == createResults.Length);

                for (var i = 0; i < sequenceLength; i++)
                {
                    links.Delete(sequence[i]);
                }
            }
        }

        [Fact]
        public static void BalancedPartialVariantsSearchTest()
        {
            const long sequenceLength = 200;

            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var sequence = new ulong[sequenceLength];
                for (var i = 0; i < sequenceLength; i++)
                {
                    sequence[i] = links.Create();
                }

                var balancedVariantConverter = new BalancedVariantConverter<ulong>(links);

                var balancedVariant = balancedVariantConverter.Convert(sequence);

                var partialSequence = new ulong[sequenceLength - 2];

                Array.Copy(sequence, 1, partialSequence, 0, (int)sequenceLength - 2);

                var sw1 = Stopwatch.StartNew();
                var searchResults1 =
                 ↪  sequences.GetAllPartiallyMatchingSequences0(partialSequence); sw1.Stop();

                var sw2 = Stopwatch.StartNew();
                var searchResults2 =
                 ↪  sequences.GetAllPartiallyMatchingSequences1(partialSequence); sw2.Stop();

                Assert.True(searchResults1.Count == 1 && balancedVariant == searchResults1[0]);

                Assert.True(searchResults2.Count == 1 && balancedVariant ==
                 ↪  searchResults2.First());

                for (var i = 0; i < sequenceLength; i++)
                {
                    links.Delete(sequence[i]);
                }
            }
        }

        [Fact(Skip = "Correct implementation is pending")]
        public static void PatternMatchTest()
        {
            var zeroOrMany = Sequences.Sequences.ZeroOrMany;

            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var e1 = links.Create();
                var e2 = links.Create();

                var sequence = new[]
                {
                    e1, e2, e1, e2 // mama / papa
                };

                var balancedVariantConverter = new BalancedVariantConverter<ulong>(links);

                var balancedVariant = balancedVariantConverter.Convert(sequence);

                // 1: [1]
                // 2: [2]
                // 3: [1,2]
                // 4: [1,2,1,2]

                var doublet = links.GetSource(balancedVariant);

                var matchedSequences1 = sequences.MatchPattern(e2, e1, zeroOrMany);

                Assert.True(matchedSequences1.Count == 0);

                var matchedSequences2 = sequences.MatchPattern(zeroOrMany, e2, e1);

                Assert.True(matchedSequences2.Count == 0);

                var matchedSequences3 = sequences.MatchPattern(e1, zeroOrMany, e1);

                Assert.True(matchedSequences3.Count == 0);

                var matchedSequences4 = sequences.MatchPattern(e1, zeroOrMany, e2);

                Assert.Contains(doublet, matchedSequences4);
                Assert.Contains(balancedVariant, matchedSequences4);

                for (var i = 0; i < sequence.Length; i++)
                {
                    links.Delete(sequence[i]);
                }
            }
        }

        [Fact]
        public static void IndexTest()
        {
            using (var scope = new TempLinksTestScope(new SequencesOptions<ulong> { UseIndex = true }, useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;
                var indexer = sequences.Options.Indexer;

                var e1 = links.Create();
                var e2 = links.Create();

                var sequence = new[]
                {
                    e1, e2, e1, e2 // mama / papa
                };

                Assert.False(indexer.Index(sequence));

                Assert.True(indexer.Index(sequence));
            }
        }

        /// <summary>Imported from https://raw.githubusercontent.com/wiki/Konard/LinksPlatform/%D0%9E-%D1%82%D0%BE%D0%BC%2C-%D0%BA%D0%B0%D0%BA-%D0%B2%D1%81%D1%91-%D0%BD%D0%B0%D1%87%D0%B8%D0%BD%D0%B0%D0%BB%D0%BE%D1%81%D1%8C.md</summary>
        private static readonly string _exampleText =
            @"([english version](https://github.com/Konard/LinksPlatform/wiki/About-the-beginning))

Обозначение пустоты, какое оно? Темнота ли это? Там где отсутствие света, отсутствие фотонов (носителей света)? Или это то, что полностью отражает свет? Пустой белый лист бумаги? Там где есть место для нового начала? Разве пустота это не характеристика пространства? Пространство это то, что можно чем-то наполнить?

[![чёрное пространство, белое пространство](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/1.png ""чёрное пространство, белое пространство"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/1.png)

Что может быть минимальным рисунком, образом, графикой? Может быть это точка? Это ли простейшая форма? Но есть ли у точки размер? Цвет? Масса? Координаты? Время существования?

[![чёрное пространство, чёрная точка](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/2.png ""чёрное пространство, чёрная точка"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/2.png)

А что если повторить? Сделать копию? Создать дубликат? Из одного сделать два? Может это быть так? Инверсия? Отражение? Сумма?

[![белая точка, чёрная точка](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/3.png ""белая точка, чёрная точка"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/3.png)

А что если мы вообразим движение? Нужно ли время? Каким самым коротким будет путь? Что будет если этот путь зафиксировать? Запомнить след? Как две точки становятся линией? Чертой? Гранью? Разделителем? Единицей?

[![две белые точки, чёрная вертикальная линия](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/4.png ""две белые точки, чёрная вертикальная линия"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/4.png)
```

```

Можно ли замкнуть движение? Может ли это быть кругом? Можно ли замкнуть время? Или остаётся только спираль? Но что если замкнуть предел? Создать ограничение, разделение? Получится замкнутая область? Полностью отделённая от всего остального? Но что это всё остальное? Что можно делить? В каком направлении? Ничего или всё? Пустота или полнота? Начало или конец? Или может быть это единица и ноль? Дуальность? Противоположность? А что будет с кругом если у него нет размера? Будет ли круг точкой? Точка состоящая из точек?

[![белая вертикальная линия, чёрный круг](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/5.png ""белая вертикальная линия, чёрный круг"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/5.png)

Как ещё можно использовать грань, черту, линию? А что если она может что-то соединять, может тогда её нужно повернуть? Почему то, что перпендикулярно вертикальному горизонтально? Горизонт? Инвертирует ли это смысл? Что такое смысл? Из чего состоит смысл? Существует ли элементарная единица смысла?

[![белый круг, чёрная горизонтальная линия](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/6.png ""белый круг, чёрная горизонтальная линия"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/6.png)

Соединять, допустим, а какой смысл в этом есть ещё? Что если помимо смысла ""соединить, связать"", есть ещё и смысл направления ""от начала к концу""? От предка к потомку? От родителя к ребёнку? От общего к частному?

[![белая горизонтальная линия, чёрная горизонтальная стрелка](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/7.png ""белая горизонтальная линия, чёрная горизонтальная стрелка"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/7.png)

Шаг назад. Возьмём опять отделённую область, которая лишь та же замкнутая линия, что ещё она может представлять собой? Объект? Но в чём его суть? Разве не в том, что у него есть граница, разделяющая внутреннее и внешнее? Допустим связь, стрелка, линия соединяет два объекта, как бы это выглядело?

[![белая связь, чёрная направленная связь](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/8.png ""белая связь, чёрная направленная связь"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/8.png)

Допустим у нас есть смысл ""связать"" и смысл ""направления"", много ли это нам даёт? Много ли вариантов интерпретации? А что если уточнить, каким именно образом выполнена связь? Что если можно задать ей чёткий, конкретный смысл? Что это будет? Тип? Глагол? Связка? Действие? Трансформация? Переход из состояния в состояние? Или всё это и есть объект, суть которого в его конечном состоянии, если конечно конец определён направлением?

[![белая обычная и направленная связи, чёрная типизированная связь](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/9.png ""белая обычная и направленная связи, чёрная типизированная связь"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/9.png)

А что если всё это время, мы смотрели на суть как бы снаружи? Можно ли взглянуть на это изнутри? Что будет внутри объектов? Объекты ли это? Или это связи? Может ли эта структура описать сама себя? Но что тогда получится, разве это не рекурсия? Может это фрактал?

[![белая обычная и направленная связи с рекурсивной внутренней структурой, чёрная типизированная связь с рекурсивной внутренней структурой](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/10.png ""белая обычная и направленная связи с рекурсивной внутренней структурой, чёрная типизированная связь с рекурсивной внутренней структурой"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/10.png)

На один уровень внутрь (вниз)? Или на один уровень во вне (вверх)? Или это можно назвать шагом рекурсии или фрактала?

[![белая обычная и направленная связи с двойной рекурсивной внутренней структурой, чёрная типизированная связь с двойной рекурсивной внутренней структурой](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/11.png ""белая обычная и направленная связи с двойной рекурсивной внутренней структурой, чёрная типизированная связь с двойной рекурсивной внутренней структурой"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/11.png)

Последовательность? Массив? Список? Множество? Объект? Таблица? Элементы? Цвета? Символы? Буквы? Слово? Цифры? Число? Алфавит? Дерево? Сеть? Граф? Гиперграф?

```

```
[![белая обычная и направленная связи со структурой из 8 цветных элементов последовательности, чёрная типизированная связь со структурой из 8 цветных элементов последовательности](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/12.png ""белая обычная и направленная связи со структурой из 8 цветных элементов последовательности, чёрная типизированная связь со структурой из 8 цветных элементов последовательности"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/12.png)

...

[![анимация](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/intro-animation-500.gif ""анимация"")](https://raw.githubusercontent.com/Konard/LinksPlatform/master/doc/Intro/intro-animation-500.gif)";


        private static readonly string _exampleLoremIpsumText =
            @"Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua.
Ut enim ad minim veniam, quis nostrud exercitation ullamco laboris nisi ut aliquip ex ea commodo consequat.";

        [Fact]
        public static void CompressionTest()
        {
            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var e1 = links.Create();
                var e2 = links.Create();

                var sequence = new[]
                {
                    e1, e2, e1, e2 // mama / papa / template [(m/p), a] { [1] [2] [1] [2] }
                };

                var balancedVariantConverter = new BalancedVariantConverter<ulong>(links.Unsync);
                var totalSequenceSymbolFrequencyCounter = new TotalSequenceSymbolFrequencyCounter<ulong>(links.Unsync);
                var doubletFrequenciesCache = new LinkFrequenciesCache<ulong>(links.Unsync, totalSequenceSymbolFrequencyCounter);
                var compressingConverter = new CompressingConverter<ulong>(links.Unsync, balancedVariantConverter, doubletFrequenciesCache);

                var compressedVariant = compressingConverter.Convert(sequence);

                // 1: [1]       (1->1) point
                // 2: [2]       (2->2) point
                // 3: [1,2]     (1->2) doublet
                // 4: [1,2,1,2] (3->3) doublet

                Assert.True(links.GetSource(links.GetSource(compressedVariant)) == sequence[0]);
                Assert.True(links.GetTarget(links.GetSource(compressedVariant)) == sequence[1]);
                Assert.True(links.GetSource(links.GetTarget(compressedVariant)) == sequence[2]);
                Assert.True(links.GetTarget(links.GetTarget(compressedVariant)) == sequence[3]);

                var source = _constants.SourcePart;
                var target = _constants.TargetPart;

                Assert.True(links.GetByKeys(compressedVariant, source, source) == sequence[0]);
                Assert.True(links.GetByKeys(compressedVariant, source, target) == sequence[1]);
                Assert.True(links.GetByKeys(compressedVariant, target, source) == sequence[2]);
                Assert.True(links.GetByKeys(compressedVariant, target, target) == sequence[3]);

                // 4 - length of sequence
                Assert.True(links.GetSquareMatrixSequenceElementByIndex(compressedVariant, 4, 0) == sequence[0]);
                Assert.True(links.GetSquareMatrixSequenceElementByIndex(compressedVariant, 4, 1) == sequence[1]);
                Assert.True(links.GetSquareMatrixSequenceElementByIndex(compressedVariant, 4, 2) == sequence[2]);
                Assert.True(links.GetSquareMatrixSequenceElementByIndex(compressedVariant, 4, 3) == sequence[3]);
            }
        }

        [Fact]
        public static void CompressionEfficiencyTest()
        {
            var strings = _exampleLoremIpsumText.Split(new[] { '\n', '\r' },
             ↪  StringSplitOptions.RemoveEmptyEntries);
            var arrays = strings.Select(UnicodeMap.FromStringToLinkArray).ToArray();
            var totalCharacters = arrays.Select(x => x.Length).Sum();

            using (var scope1 = new TempLinksTestScope(useSequences: true))
            using (var scope2 = new TempLinksTestScope(useSequences: true))
            using (var scope3 = new TempLinksTestScope(useSequences: true))
            {
                scope1.Links.Unsync.UseUnicode();
                scope2.Links.Unsync.UseUnicode();
                scope3.Links.Unsync.UseUnicode();

                var balancedVariantConverter1 = new
                 ↪  BalancedVariantConverter<ulong>(scope1.Links.Unsync);
                var totalSequenceSymbolFrequencyCounter = new
                 ↪  TotalSequenceSymbolFrequencyCounter<ulong>(scope1.Links.Unsync);
                var linkFrequenciesCache1 = new LinkFrequenciesCache<ulong>(scope1.Links.Unsync,
                 ↪  totalSequenceSymbolFrequencyCounter);
                var compressor1 = new CompressingConverter<ulong>(scope1.Links.Unsync,
                 ↪  balancedVariantConverter1, linkFrequenciesCache1,
                 ↪  doInitialFrequenciesIncrement: false);

                var compressor2 = scope2.Sequences;
                var compressor3 = scope3.Sequences;

                var constants = Default<LinksCombinedConstants<bool, ulong, int>>.Instance;

                var sequences = compressor3;
                //var meaningRoot = links.CreatePoint();
                //var unaryOne = links.CreateAndUpdate(meaningRoot, constants.Itself);
                //var frequencyMarker = links.CreateAndUpdate(meaningRoot, constants.Itself);
                //var frequencyPropertyMarker = links.CreateAndUpdate(meaningRoot,
                 ↪  constants.Itself);

                //var unaryNumberToAddressConveter = new
                 ↪  UnaryNumberToAddressAddOperationConverter<ulong>(links, unaryOne);
                //var unaryNumberIncrementer = new UnaryNumberIncrementer<ulong>(links,
                 ↪  unaryOne);
                //var frequencyIncrementer = new FrequencyIncrementer<ulong>(links,
                 ↪  frequencyMarker, unaryOne, unaryNumberIncrementer);
                //var frequencyPropertyOperator = new FrequencyPropertyOperator<ulong>(links,
                 ↪  frequencyPropertyMarker, frequencyMarker);
                //var linkFrequencyIncrementer = new LinkFrequencyIncrementer<ulong>(links,
                 ↪  frequencyPropertyOperator, frequencyIncrementer);
                //var linkToItsFrequencyNumberConverter = new
                 ↪  LinkToItsFrequencyNumberConveter<ulong>(links, frequencyPropertyOperator,
                 ↪  unaryNumberToAddressConveter);

                var linkFrequenciesCache3 = new LinkFrequenciesCache<ulong>(scope3.Links.Unsync,
                 ↪  totalSequenceSymbolFrequencyCounter);

                var linkToItsFrequencyNumberConverter = new FrequenciesCacheBasedLinkToItsFreque⌟
                 ↪  ncyNumberConverter<ulong>(linkFrequenciesCache3);

                var sequenceToItsLocalElementLevelsConverter = new
                 ↪  SequenceToItsLocalElementLevelsConverter<ulong>(scope3.Links.Unsync,
                 ↪  linkToItsFrequencyNumberConverter);
                var optimalVariantConverter = new
                 ↪  OptimalVariantConverter<ulong>(scope3.Links.Unsync,
                 ↪  sequenceToItsLocalElementLevelsConverter);

                var compressed1 = new ulong[arrays.Length];
                var compressed2 = new ulong[arrays.Length];
                var compressed3 = new ulong[arrays.Length];

                var START = 0;
                var END = arrays.Length;

                //for (int i = START; i < END; i++)
                //    linkFrequenciesCache1.IncrementFrequencies(arrays[i]);

                var initialCount1 = scope2.Links.Unsync.Count();

                var sw1 = Stopwatch.StartNew();

                for (int i = START; i < END; i++)
                {
                    linkFrequenciesCache1.IncrementFrequencies(arrays[i]);
                    compressed1[i] = compressor1.Convert(arrays[i]);
                }

                var elapsed1 = sw1.Elapsed;

                var balancedVariantConverter2 = new
                ↪  BalancedVariantConverter<ulong>(scope2.Links.Unsync);

                var initialCount2 = scope2.Links.Unsync.Count();

                var sw2 = Stopwatch.StartNew();

                for (int i = START; i < END; i++)
                {
                    compressed2[i] = balancedVariantConverter2.Convert(arrays[i]);
                }

                var elapsed2 = sw2.Elapsed;

                for (int i = START; i < END; i++)
                {
                    linkFrequenciesCache3.IncrementFrequencies(arrays[i]);
                }

                var initialCount3 = scope3.Links.Unsync.Count();

                var sw3 = Stopwatch.StartNew();

                for (int i = START; i < END; i++)
                {
                    //linkFrequenciesCache3.IncrementFrequencies(arrays[i]);
                    compressed3[i] = optimalVariantConverter.Convert(arrays[i]);
                }

                var elapsed3 = sw3.Elapsed;

                Console.WriteLine($"Compressor: {elapsed1}, Balanced variant: {elapsed2},
                ↪  Optimal variant: {elapsed3}");

                // Assert.True(elapsed1 > elapsed2);

                // Checks
                for (int i = START; i < END; i++)
                {
                    var sequence1 = compressed1[i];
                    var sequence2 = compressed2[i];
                    var sequence3 = compressed3[i];

                    var decompress1 = UnicodeMap.FromSequenceLinkToString(sequence1,
                    ↪  scope1.Links.Unsync);

                    var decompress2 = UnicodeMap.FromSequenceLinkToString(sequence2,
                    ↪  scope2.Links.Unsync);

                    var decompress3 = UnicodeMap.FromSequenceLinkToString(sequence3,
                    ↪  scope3.Links.Unsync);

                    var structure1 = scope1.Links.Unsync.FormatStructure(sequence1, link =>
                    ↪  link.IsPartialPoint());
                    var structure2 = scope2.Links.Unsync.FormatStructure(sequence2, link =>
                    ↪  link.IsPartialPoint());
                    var structure3 = scope3.Links.Unsync.FormatStructure(sequence3, link =>
                    ↪  link.IsPartialPoint());

                    //if (sequence1 != Constants.Null && sequence2 != Constants.Null &&
                    ↪  arrays[i].Length > 3)
                    //    Assert.False(structure1 == structure2);
                    //if (sequence3 != Constants.Null && sequence2 != Constants.Null &&
                    ↪  arrays[i].Length > 3)
                    //    Assert.False(structure3 == structure2);

                    Assert.True(strings[i] == decompress1 && decompress1 == decompress2);
                    Assert.True(strings[i] == decompress3 && decompress3 == decompress2);
                }

                Assert.True((int)(scope1.Links.Unsync.Count() - initialCount1) <
                ↪  totalCharacters);
                Assert.True((int)(scope2.Links.Unsync.Count() - initialCount2) <
                ↪  totalCharacters);
                Assert.True((int)(scope3.Links.Unsync.Count() - initialCount3) <
                ↪  totalCharacters);

                Console.WriteLine($"{(double)(scope1.Links.Unsync.Count() - initialCount1) /
                ↪  totalCharacters} | {(double)(scope2.Links.Unsync.Count() - initialCount2) /
                ↪  totalCharacters} | {(double)(scope3.Links.Unsync.Count() - initialCount3) /
                ↪  totalCharacters}");

                Assert.True(scope1.Links.Unsync.Count() - initialCount1 <
                ↪  scope2.Links.Unsync.Count() - initialCount2);
                Assert.True(scope3.Links.Unsync.Count() - initialCount3 <
                ↪  scope2.Links.Unsync.Count() - initialCount2);

                var duplicateProvider1 = new
                ↪  DuplicateSegmentsProvider<ulong>(scope1.Links.Unsync, scope1.Sequences);
                var duplicateProvider2 = new
                ↪  DuplicateSegmentsProvider<ulong>(scope2.Links.Unsync, scope2.Sequences);
                var duplicateProvider3 = new
                ↪  DuplicateSegmentsProvider<ulong>(scope3.Links.Unsync, scope3.Sequences);

                var duplicateCounter1 = new DuplicateSegmentsCounter<ulong>(duplicateProvider1);
                var duplicateCounter2 = new DuplicateSegmentsCounter<ulong>(duplicateProvider2);
                var duplicateCounter3 = new DuplicateSegmentsCounter<ulong>(duplicateProvider3);

                var duplicates1 = duplicateCounter1.Count();

                ConsoleHelpers.Debug("------");

                var duplicates2 = duplicateCounter2.Count();

                ConsoleHelpers.Debug("------");

                var duplicates3 = duplicateCounter3.Count();

                Console.WriteLine($"{duplicates1} | {duplicates2} | {duplicates3}");

                linkFrequenciesCache1.ValidateFrequencies();
                linkFrequenciesCache3.ValidateFrequencies();
            }
        }

        [Fact]
        public static void CompressionStabilityTest()
        {
            // TODO: Fix bug (do a separate test)
            //const ulong minNumbers = 0;
            //const ulong maxNumbers = 1000;

            const ulong minNumbers = 10000;
            const ulong maxNumbers = 12500;

            var strings = new List<string>();

            for (ulong i = minNumbers; i < maxNumbers; i++)
            {
                strings.Add(i.ToString());
            }

            var arrays = strings.Select(UnicodeMap.FromStringToLinkArray).ToArray();
            var totalCharacters = arrays.Select(x => x.Length).Sum();

            using (var scope1 = new TempLinksTestScope(useSequences: true, sequencesOptions: new
            ↪  SequencesOptions<ulong> { UseCompression = true,
            ↪  EnforceSingleSequenceVersionOnWriteBasedOnExisting = true }))
            using (var scope2 = new TempLinksTestScope(useSequences: true))
            {
                scope1.Links.UseUnicode();
                scope2.Links.UseUnicode();

                //var compressor1 = new Compressor(scope1.Links.Unsync, scope1.Sequences);
                var compressor1 = scope1.Sequences;
                var compressor2 = scope2.Sequences;

                var compressed1 = new ulong[arrays.Length];
                var compressed2 = new ulong[arrays.Length];

                var sw1 = Stopwatch.StartNew();
            var START = 0;
            var END = arrays.Length;

            // Collisions proved (cannot be solved by max doublet comparison, no stable rule)
            // Stability issue starts at 10001 or 11000
            //for (int i = START; i < END; i++)
            //{
            //    var first = compressor1.Compress(arrays[i]);
            //    var second = compressor1.Compress(arrays[i]);

            //    if (first == second)
            //        compressed1[i] = first;
            //    else
            //    {
            //        // TODO: Find a solution for this case
            //    }
            //}

            for (int i = START; i < END; i++)
            {
                var first = compressor1.Create(arrays[i]);
                var second = compressor1.Create(arrays[i]);

                if (first == second)
                {
                    compressed1[i] = first;
                }
                else
                {
                    // TODO: Find a solution for this case
                }
            }

            var elapsed1 = sw1.Elapsed;

            var balancedVariantConverter = new BalancedVariantConverter<ulong>(scope2.Links);

            var sw2 = Stopwatch.StartNew();

            for (int i = START; i < END; i++)
            {
                var first = balancedVariantConverter.Convert(arrays[i]);
                var second = balancedVariantConverter.Convert(arrays[i]);

                if (first == second)
                {
                    compressed2[i] = first;
                }
            }

            var elapsed2 = sw2.Elapsed;

            Debug.WriteLine($"Compressor: {elapsed1}, Balanced sequence creator:
            ↪  {elapsed2}");

            Assert.True(elapsed1 > elapsed2);

            // Checks
            for (int i = START; i < END; i++)
            {
                var sequence1 = compressed1[i];
                var sequence2 = compressed2[i];

                if (sequence1 != _constants.Null && sequence2 != _constants.Null)
                {
                    var decompress1 = UnicodeMap.FromSequenceLinkToString(sequence1,
                    ↪  scope1.Links);

                    var decompress2 = UnicodeMap.FromSequenceLinkToString(sequence2,
                    ↪  scope2.Links);

                    //var structure1 = scope1.Links.FormatStructure(sequence1, link =>
                    ↪  link.IsPartialPoint());
                    //var structure2 = scope2.Links.FormatStructure(sequence2, link =>
                    ↪  link.IsPartialPoint());

                    //if (sequence1 != Constants.Null && sequence2 != Constants.Null &&
                    ↪  arrays[i].Length > 3)
```

```csharp
                        //    Assert.False(structure1 == structure2);

                        Assert.True(strings[i] == decompress1 && decompress1 == decompress2);
                    }
                }

                Assert.True((int)(scope1.Links.Count() - UnicodeMap.MapSize) < totalCharacters);
                Assert.True((int)(scope2.Links.Count() - UnicodeMap.MapSize) < totalCharacters);

                Debug.WriteLine($"{(double)(scope1.Links.Count() - UnicodeMap.MapSize) /
                ↪  totalCharacters} | {(double)(scope2.Links.Count() - UnicodeMap.MapSize) /
                ↪  totalCharacters}");

                Assert.True(scope1.Links.Count() <= scope2.Links.Count());

                //compressor1.ValidateFrequencies();
            }
        }

        [Fact]
        public static void RundomNumbersCompressionQualityTest()
        {
            const ulong N = 500;

            //const ulong minNumbers = 10000;
            //const ulong maxNumbers = 20000;

            //var strings = new List<string>();

            //for (ulong i = 0; i < N; i++)
            //    strings.Add(RandomHelpers.DefaultFactory.NextUInt64(minNumbers,
            ↪  maxNumbers).ToString());

            var strings = new List<string>();

            for (ulong i = 0; i < N; i++)
            {
                strings.Add(RandomHelpers.Default.NextUInt64().ToString());
            }

            strings = strings.Distinct().ToList();

            var arrays = strings.Select(UnicodeMap.FromStringToLinkArray).ToArray();
            var totalCharacters = arrays.Select(x => x.Length).Sum();

            using (var scope1 = new TempLinksTestScope(useSequences: true, sequencesOptions: new
            ↪  SequencesOptions<ulong> { UseCompression = true,
            ↪  EnforceSingleSequenceVersionOnWriteBasedOnExisting = true }))
            using (var scope2 = new TempLinksTestScope(useSequences: true))
            {
                scope1.Links.UseUnicode();
                scope2.Links.UseUnicode();

                var compressor1 = scope1.Sequences;
                var compressor2 = scope2.Sequences;

                var compressed1 = new ulong[arrays.Length];
                var compressed2 = new ulong[arrays.Length];

                var sw1 = Stopwatch.StartNew();

                var START = 0;
                var END = arrays.Length;

                for (int i = START; i < END; i++)
                {
                    compressed1[i] = compressor1.Create(arrays[i]);
                }

                var elapsed1 = sw1.Elapsed;

                var balancedVariantConverter = new BalancedVariantConverter<ulong>(scope2.Links);

                var sw2 = Stopwatch.StartNew();

                for (int i = START; i < END; i++)
                {
                    compressed2[i] = balancedVariantConverter.Convert(arrays[i]);
                }

                var elapsed2 = sw2.Elapsed;

                Debug.WriteLine($"Compressor: {elapsed1}, Balanced sequence creator:
                ↪  {elapsed2}");

                Assert.True(elapsed1 > elapsed2);

                // Checks
                for (int i = START; i < END; i++)
                {
                    var sequence1 = compressed1[i];
                    var sequence2 = compressed2[i];

                    if (sequence1 != _constants.Null && sequence2 != _constants.Null)
                    {
                        var decompress1 = UnicodeMap.FromSequenceLinkToString(sequence1,
                        ↪  scope1.Links);

                        var decompress2 = UnicodeMap.FromSequenceLinkToString(sequence2,
                        ↪  scope2.Links);

                        Assert.True(strings[i] == decompress1 && decompress1 == decompress2);
                    }
                }

                Assert.True((int)(scope1.Links.Count() - UnicodeMap.MapSize) < totalCharacters);
                Assert.True((int)(scope2.Links.Count() - UnicodeMap.MapSize) < totalCharacters);

                Debug.WriteLine($"{(double)(scope1.Links.Count() - UnicodeMap.MapSize) /
                ↪  totalCharacters} | {(double)(scope2.Links.Count() - UnicodeMap.MapSize) /
                ↪  totalCharacters}");

                // Can be worse than balanced variant
                //Assert.True(scope1.Links.Count() <= scope2.Links.Count());

                //compressor1.ValidateFrequencies();
            }
        }

        [Fact]
        public static void AllTreeBreakDownAtSequencesCreationBugTest()
        {
            // Made out of AllPossibleConnectionsTest test.

            //const long sequenceLength = 5; //100% bug
            const long sequenceLength = 4; //100% bug
            //const long sequenceLength = 3; //100% _no_bug (ok)

            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var sequence = new ulong[sequenceLength];
                for (var i = 0; i < sequenceLength; i++)
                {
                    sequence[i] = links.Create();
                }

                var createResults = sequences.CreateAllVariants2(sequence);

                Global.Trash = createResults;

                for (var i = 0; i < sequenceLength; i++)
                {
                    links.Delete(sequence[i]);
                }
            }
        }

        [Fact]
        public static void AllPossibleConnectionsTest()
        {
            const long sequenceLength = 5;

            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;
```

```csharp

                var sequence = new ulong[sequenceLength];
                for (var i = 0; i < sequenceLength; i++)
                {
                    sequence[i] = links.Create();
                }

                var createResults = sequences.CreateAllVariants2(sequence);
                var reverseResults = sequences.CreateAllVariants2(sequence.Reverse().ToArray());

                for (var i = 0; i < 1; i++)
                {
                    var sw1 = Stopwatch.StartNew();
                    var searchResults1 = sequences.GetAllConnections(sequence); sw1.Stop();

                    var sw2 = Stopwatch.StartNew();
                    var searchResults2 = sequences.GetAllConnections1(sequence); sw2.Stop();

                    var sw3 = Stopwatch.StartNew();
                    var searchResults3 = sequences.GetAllConnections2(sequence); sw3.Stop();

                    var sw4 = Stopwatch.StartNew();
                    var searchResults4 = sequences.GetAllConnections3(sequence); sw4.Stop();

                    Global.Trash = searchResults3;
                    Global.Trash = searchResults4; //-V3008

                    var intersection1 = createResults.Intersect(searchResults1).ToList();
                    Assert.True(intersection1.Count == createResults.Length);

                    var intersection2 = reverseResults.Intersect(searchResults1).ToList();
                    Assert.True(intersection2.Count == reverseResults.Length);

                    var intersection0 = searchResults1.Intersect(searchResults2).ToList();
                    Assert.True(intersection0.Count == searchResults2.Count);

                    var intersection3 = searchResults2.Intersect(searchResults3).ToList();
                    Assert.True(intersection3.Count == searchResults3.Count);

                    var intersection4 = searchResults3.Intersect(searchResults4).ToList();
                    Assert.True(intersection4.Count == searchResults4.Count);
                }

                for (var i = 0; i < sequenceLength; i++)
                {
                    links.Delete(sequence[i]);
                }
            }
        }

        [Fact(Skip = "Correct implementation is pending")]
        public static void CalculateAllUsagesTest()
        {
            const long sequenceLength = 3;

            using (var scope = new TempLinksTestScope(useSequences: true))
            {
                var links = scope.Links;
                var sequences = scope.Sequences;

                var sequence = new ulong[sequenceLength];
                for (var i = 0; i < sequenceLength; i++)
                {
                    sequence[i] = links.Create();
                }

                var createResults = sequences.CreateAllVariants2(sequence);

                //var reverseResults =
                 ↪  sequences.CreateAllVariants2(sequence.Reverse().ToArray());

                for (var i = 0; i < 1; i++)
                {
                    var linksTotalUsages1 = new ulong[links.Count() + 1];

                    sequences.CalculateAllUsages(linksTotalUsages1);

                    var linksTotalUsages2 = new ulong[links.Count() + 1];

                    sequences.CalculateAllUsages2(linksTotalUsages2);
                    var intersection1 = linksTotalUsages1.Intersect(linksTotalUsages2).ToList();
                    Assert.True(intersection1.Count == linksTotalUsages2.Length);
                }

                for (var i = 0; i < sequenceLength; i++)
                {
                    links.Delete(sequence[i]);
                }
            }
        }
    }
}
```

./Platform.Data.Doublets.Tests/TempLinksTestScope.cs

```
using System.IO;
using Platform.Disposables;
using Platform.Data.Doublets.ResizableDirectMemory;
using Platform.Data.Doublets.Sequences;
using Platform.Data.Doublets.Decorators;

namespace Platform.Data.Doublets.Tests
{
    public class TempLinksTestScope : DisposableBase
    {
        public readonly ILinks<ulong> MemoryAdapter;
        public readonly SynchronizedLinks<ulong> Links;
        public readonly Sequences.Sequences Sequences;
        public readonly string TempFilename;
        public readonly string TempTransactionLogFilename;
        private readonly bool _deleteFiles;

        public TempLinksTestScope(bool deleteFiles = true, bool useSequences = false, bool
         ↪  useLog = false)
            : this(new SequencesOptions<ulong>(), deleteFiles, useSequences, useLog)
        {
        }

        public TempLinksTestScope(SequencesOptions<ulong> sequencesOptions, bool deleteFiles =
         ↪  true, bool useSequences = false, bool useLog = false)
        {
            _deleteFiles = deleteFiles;
            TempFilename = Path.GetTempFileName();
            TempTransactionLogFilename = Path.GetTempFileName();

            var coreMemoryAdapter = new UInt64ResizableDirectMemoryLinks(TempFilename);

            MemoryAdapter = useLog ? (ILinks<ulong>)new
             ↪  UInt64LinksTransactionsLayer(coreMemoryAdapter, TempTransactionLogFilename) :
             ↪  coreMemoryAdapter;

            Links = new SynchronizedLinks<ulong>(new UInt64Links(MemoryAdapter));
            if (useSequences)
            {
                Sequences = new Sequences.Sequences(Links, sequencesOptions);
            }
        }

        protected override void Dispose(bool manual, bool wasDisposed)
        {
            if (!wasDisposed)
            {
                Links.Unsync.DisposeIfPossible();
                if (_deleteFiles)
                {
                    DeleteFiles();
                }
            }
        }

        public void DeleteFiles()
        {
            File.Delete(TempFilename);
            File.Delete(TempTransactionLogFilename);
        }
    }
}
```

./Platform.Data.Doublets.Tests/UnaryNumberConvertersTests.cs

```csharp
using Xunit;
using Platform.Random;
using Platform.Data.Doublets.Converters;

namespace Platform.Data.Doublets.Tests
{
    public static class UnaryNumberConvertersTests
    {
        [Fact]
        public static void ConvertersTest()
        {
            using (var scope = new TempLinksTestScope())
            {
                const int N = 10;
                var links = scope.Links;
                var meaningRoot = links.CreatePoint();
                var one = links.CreateAndUpdate(meaningRoot, links.Constants.Itself);
                var powerOf2ToUnaryNumberConverter = new
                ↪  PowerOf2ToUnaryNumberConverter<ulong>(links, one);
                var toUnaryNumberConverter = new AddressToUnaryNumberConverter<ulong>(links,
                ↪  powerOf2ToUnaryNumberConverter);
                var random = new System.Random(0);
                ulong[] numbers = new ulong[N];
                ulong[] unaryNumbers = new ulong[N];
                for (int i = 0; i < N; i++)
                {
                    numbers[i] = random.NextUInt64();
                    unaryNumbers[i] = toUnaryNumberConverter.Convert(numbers[i]);
                }
                var fromUnaryNumberConverterUsingOrOperation = new
                ↪  UnaryNumberToAddressOrOperationConverter<ulong>(links,
                ↪  powerOf2ToUnaryNumberConverter);
                var fromUnaryNumberConverterUsingAddOperation = new
                ↪  UnaryNumberToAddressAddOperationConverter<ulong>(links, one);
                for (int i = 0; i < N; i++)
                {
                    Assert.Equal(numbers[i],
                    ↪  fromUnaryNumberConverterUsingOrOperation.Convert(unaryNumbers[i]));
                    Assert.Equal(numbers[i],
                    ↪  fromUnaryNumberConverterUsingAddOperation.Convert(unaryNumbers[i]));
                }
            }
        }
    }
}
```

Index