```xml
<?xml version="1.0" encoding="UTF-8" ?>
<!DOCTYPE mapper
    PUBLIC "-//mybatis.org//DTD Mapper 3.0//EN"
    "http://mybatis.org/dtd/mybatis-3-mapper.dtd">

<mapper namespace="com.resultmap2.mapper.TeacherMap">
  <resultMap id="mymap1" type="com.resultmap2.pojo.Teacher">
    <id column="id" property="id"/>
    <result column="name" property="name"/>
    <collection property="list" ofType="com.resultmap2.pojo.Student"
select="com.resultmap2.mapper.StudentMapper.selByTid" column="id">
</collection>
  </resultMap>


  <select id="selAll" resultMap="mymap1" >
    select  * from TEACHER
  </select>

  <resultMap id="mymap2" type="com.resultmap2.pojo.Teacher">
    <id column="id" property="id"/>
    <result column="name" property="name"/>
    <collection property="list" ofType="com.resultmap2.pojo.Student">
      <id column="sid" property="id"/>
      <result column="sname" property="name"/>
      <result column="age" property="age"/>
      <result column="tid" property="tid"/>
    </collection>
  </resultMap>

  <select id="selAll1" resultMap="mymap2">
    select t.ID,t.NAME,s.ID sid,s.NAME sname,s.AGE,s.TID from TEACHER t left join
STUDENT s on s.TID=t.ID
  </select>
</mapper>
```