

```

<?xml version="1.0" encoding="UTF-8" ?>
<beans xmlns="http://www.springframework.org/schema/beans"
       xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
       xsi:schemaLocation="
           http://www.springframework.org/schema/beans
           http://www.springframework.org/schema/beans/spring-beans.xsd">

    <bean id="peo" class="com.Spring2.Pojo.People">
<!--      <property name="id" value="222"></property>-->
<!--      <property name="name" value="张三"></property>-->
        <property name="id">
            <value>123</value>
        </property>
        <property name="name">
            <value>张三</value>
        </property>

        <!--属性是Set-->
        <property name="sets">
            <set>
                <value>1</value>
                <value>2</value>
                <value>3</value>
                <value>4</value>
                <value>5</value>
            </set>
        </property>

        <!--如果属性是List-->
        <!--如果list中只有一个-->
<!--      <property name="list" value="1"></property>-->

        <property name="list">
            <list>
                <value>1</value>
                <value>2</value>
                <value>3</value>
                <value>4</value>
            </list>
        </property>

        <!--如果属性是数组-->
        <!--如果数组只有一个值-->
<!--      <property name="strs" value="1"></property>-->

        <property name="strs">

```

```
<array>
  <value>1</value>
  <value>2</value>
  <value>3</value>
</array>
</property>
```

```
<!--如果属性是Map-->
<property name="map">
  <map>
    <entry key="1" value="张三"></entry>
  </map>
</property>
```

```
<!--如果属性是properties-->
<property name="demo">
  <props>
    <prop key="key" >value1</prop>
    <prop key="key1" >value2</prop>
  </props>
</property>
```

```
<property name="desk" ref="desk"></property>
```

```
</bean>
```

```
<bean class="com.Spring2.Pojo.Desk" id="desk">
  <property name="id" value="1"></property>
  <property name="price" value="200"></property>
</bean>
```

```
</beans>
```