

```

<%@ page import="com.jiang.Entity.Student" %> <%--
Created by IntelliJ IDEA.
User: DELL
Date: 2019/9/8
Time: 11:21
To change this template use File | Settings | File Templates.
--%>
<%@ page contentType="text/html;charset=UTF-8" language="java" %>
<html>
<head>
    <title>EL</title>
</head>
<body>
    <%
        Student student1 = (Student) request.getAttribute("student");
        out.print(student1);
        out.print(student1.getSno());
        out.print(student1.getSname());
        out.print(student1.getAddress().getHomeAddress());
        out.print(student1.getAddress().getSchoolAddress());

    %>

    <!--EL代码-->
    ${requestScope.student }<br/>
    ${requestScope.student.sno}<br/>
    ${requestScope.student.sname}<br/>
    ${requestScope.student.address.homeAddress}<br/>
    ${requestScope.student.address.schoolAddress}<br/>

    ${requestScope.student["address"]['schoolAddress']}<br/>

    --特殊符号--
    点操作符:${requestScope.my-name}
    中括号操作符:${requestScope['my-name']}

    --获取变量值--
    ${requestScope['my']};

    --获取数组--
    ${requestScope.hobbies[0]}
    ${requestScope.hobbies[1]}

    --map--
    ${requestScope.map.cn}

```

```
${requestScope.map['cn']}
```

```
--运算--
```

```
${3>2} ${3 get 2}
```

```
${3>2||3<2} ${3>2 or 3<2}
```

```
--Empty运算--
```

```
${empty requestScope["my-name"]}
```

```
${empty requestScope["hello"]} <!--不存在的值或者为null, 返回true-->
```

```
--session--
```

```
${sessionScope.sessionId}
```

```
--参数对象--
```

```
${param.uname}
```

```
${paramValues.hobbies[0]}
```

```
${paramValues.hobbies[1]}
```

```
${paramValues.hobbies[2]}
```

```
--jsp获取隐式对象--
```

```
${pageContext.response}
```

```
${pageContext.request.ServletPort}
```

```
</body>
```

```
</html>
```