

Bài 1

Sach

(abstract

- tên Sach : String
- Giá Bán : double
- + tính Chi Phi () : double
- + Xuat () : void

Sach Van Ban

- chi Phi Thut Ke : double
- + tính Chi Phi () : double
- + Xuat () : void

Sach

- Chat Luu Bid : String
- + tính Chi Phi () : double
- + Xuat () : void

cao cap

Void

String

" + "

}

ab

double

return

get

T

}

class S

int hinh : b

double ch

return n

}

}

class Sach

double

double C

Void Nhap

Scanner

Scanner (Sg

ma = S

+g = S

trang =

{

Void

String

" + "

}

ab

double

return

get

T

}

class S

int hinh : b

double ch

return n

}

}

class Sach

double

double C

import java.util.*;

abstract class Sach {

String ma, ten, +g;

int trang;

double gia;

Static final double THUE = 0,03;

public Sach {

ma = "Sach"; ten = "HDT"; +g

= "Nguyen"; trang = 100; gia = 1000

}

ing
double

void Nhap () {

Scanner Sc = new
Scanner (System.in);
ma = Sc.nextLine();
tg = Sc.nextLine();
trang = Sc.nextDouble();
}

void xuat () {

System.out.println("ma" +
" + ten + " + tg + " + trang + " + gia");
}

Sach
- Chat Locu
+ tinh Elu
+ xuat

cao cap

Biid : String

Phi () : double

() : void

abstract double chi Phi ();
double loi nhan ();

return gia - chi Phi () -
gia * Thue & gia * 0,2;
}

}

class SachPattern extends Sach {

int hinh : boolean mau;

double chi phi () {

return mau ? hinh 2000 : hinh * 1200;
}

}

class SachVanBei extends Sach {

double cp Bin

double Chi Phi () {

"HDT"; tg
gia = 9000