```
public class Main {
    public static void main(String[] args){

        HinhHoc h1 = new HinhTron (5);
        HinhHoc h2 = new HinhChuNhat (4,6);

        h1.tinhDienTich();
        h2.tinhDienTich();
    }
}
```

ví dụ: lớp cha là Animal, có pthức makeSound() (tiếng kêu của động vật). Giả sử có 4 lớp con là Pig, Cat, Dog, Bird.

```
class Animal{
    public void makeSound (){
        System.out.println("Động vật tạo ra âm thanh");
    }
}

class Pig extends Animal (){
    @Override
    public void makeSound(){
        System.out.println("ụt ụt");
    }
}
```

```
class Dog exten
    @Override
    public void
        System.ou
    }
}

class Cat e
    @Override
    public void
        System.
    }
}

class Bird
    @Overri
    public
        Syste
    }
}

public c
    public
        A
        A
        A
        A
```

```
class Dog extends Animal {
    @Override
    public void makeSound() {
        System.out.println("gâu gâu");
    }
}

class Cat extends Animal {
    @Override
    ~~out.println("Cat sound: meow meow")~~;
    public void makeSound() {
        System.out.println("meow meow");
    }
}

class Bird extends Animal {
    @Override
    public void makeSound() {
        System.out.println("chip chip");
    }
}

public class Main {
    public static void main(String[] args) {
        Animal myPig = new Pig();
        Animal myDog = new Dog();
        Animal myCat = new Cat();
        Animal ~~Bay~~ myBird = new Bird();
```

```
        my Pig . makeSound();
        my Dog . makeSound();
        my Cat . makeSound();
        my Bird . makeSound();
    }
}
```

ví dụ 3:

```
class XeDap {
    public void run() {
        System.out.println(" Xe dap dang chay..");
    }
}

class XeDapDien extends XeDap {
    @Override
    public void run() {
        System.out.println(" Xe dap dien dang chay
                                bang dien");
    }
}

public class Main {
    public static void main( String [] args) {
        XeDap myXeDap = new XeDapDien();
        myXe . run();
    }
}
```

ví dụ 4:

```
class Person {
    protected
    protected

    public
        this.nam
    }
    public
        this.b
    }

    public
        retu
    }
}

class Emp
    protec

    public
        th
    }

    @Ove
    pub
        r

    }
}
```

ví dụ 4:

```
class Person {
    protected String name;
    protected Date birthday;

    public void setName (String name) {
        this.name = name;
    }
    public void setBirthday (Date birthday) {
        this.birthday = birthday;
    }

    public String getDetails() {
        return "Name : " + name + ", Birthday :"
                                + birthday;
    }
}


class Employee extends Person {
    protected double salary;

    public void setSalary (double salary) {
        this.salary = salary;
    }

    @Override
    public String getDetails() {
        return super.getDetails() + ", Salary : " +
                                salary;
    }
}
```

```
class Manager extends Employee {
    private Employee assistant;

    public void setAssistant(Employee assistant){
        this.assistant = assistant;
    }

    @Override
    public String getDetails(){
        return super.getDetails() + ", Assistant: " +
(assistant != null ? assistant.name: "None");
    }
}


public class Main {
    public static void main(String[] args){
        Manager mng = new Manager();
        mng.setName("Nguyen Thi C");
        mng.setSalary(2000000);

        Employee staff = new Employee();
        staff.setName("Tran Van A");
        mng.setAssistant(staff);

        System.out.println(mng.getDetails());
    }
}
```

ví dụ 5:

```
class bank {
    public float
        return 0;
    }
}

class SBI ext
    @Override
    public flo
        return 8
    }
}

class ICICI
    @Override
    public fl
        return
    }
}

class AXIS
    @Overr
    public
        retu
    }
}
```

ví dụ 5:

```
class Bank {
    public float getRateOfInterest() {
        return 0;
    }
}

class SBI extends Bank {
    @Override
    public float getRateOfInterest() {
        return 8;
    }
}

class ICICI extends Bank {
    @Override
    public float getRateOfInterest() {
        return 7;
    }
}

class AXIS extends Bank {
    @Override
    public float getRateOfInterest() {
        return 9;
    }
}
```

```
public class Main {
    public static void main (String[] args) {
        Bank b1 = new SBI();
        Bank b2 = new ICICI();
        Bank b3 = new AXIS();

        System.out.println("SBI Rate of Interest:"
                + b1.getRateOfInterest() +
                "%");
        System.out.println("ICICI Rate of Interest:" +
                b2.getRateOfInterest() + "%")
        System.out.println("AXIS Rate of Interest:" + b3.
                getRateOfInterest() + "%");
    }
}
```

~~ví dụ 5~~

~~class Bank {~~

~~public void float get~~

Các bước xây dựng chương trình có tính đa hình:

- Xây dựng lớp cơ sở
- " dẫn xuất
- Ghi đè phương thức
- Đa hình đối tượng