

Bài tập 1:

Chúng ta có interface mail chứa các method sendMail(), log()
Class MailImpl sẽ implements mail và triển khai các method
mà method mà mail khai báo.

```
interface mail {  
    void sendMail();  
    void log();  
}  
class MailImpl implements mail {  
    @Override  
    public void sendMail() {  
        S.o.pln ("Đang gửi Mail ...");  
    }  
    @Override  
    public void log() {  
        S.o.pln ("Đang ghi log ...");  
    }  
}  
class Main {  
    public static void main (String [] args) {  
        mail myMail = new MailImpl();  
        myMail.sendMail();  
        myMail.log();  
    }  
}
```


Bài tập 2:

```
Interface Shape {  
    double get Area ();  
    double get Perimeter ();  
    void draw ();  
}  
class Rectangle implements Shape {  
    @Override  
    public double getArea (int width, int height) {  
        System.out.println ("The area of the rectangle is " +  
            (width * height));  
    }  
    @Override  
    public double getPerimeter (int width, int height) {  
        System.out.println ("The perimeter of the rectangle is  
" + (2 * (width + height)));  
    }  
    @Override  
    public void draw () {  
        System.out.println ("Drawing a Rectangle ...");  
    }  
    public boolean isSquare () {  
        return width == height;  
    }  
}  
class Circle implements Shape {  
    @Override  
    public double getArea () {  
        return Math.PI * radius * radius;  
    }  
    @Override  
    public double getPerimeter () {  
        return 2 * Math.PI * radius;  
    }  
    @Override  
    public void draw () {  
        System.out.println ("Drawing a Circle ...");  
    }  
}
```



```

class Main {
    public static void main (String [] args) {
        Rectangle r1 = new Rectangle (5, 10),
        Circle c1 = new Circle (3.5)
        Shape [] shape = new Shape [2],
        Shape [0] = r1,
        Shape [1] = c1,
        System.out.println ("Diện tích : + s.getArea ());
        System.out.println ("Chu vi : + s.getPerimeter ());
    }
}

```



```

class Main {
    public static void main (String [] args) {
        Rectangle r1 = new Rectangle (5, 10);
        Circle c1 = new Circle (3.5);
        Shape [] shape = new Shape [2];
        shape [0] = r1;
        shape [1] = c1;
        System.out.println ("Diện tích : + s.getArea ());
        System.out.println ("Chu vi : + s.getPerimeter ());
    }
}

```

Bài tập 3:

```

interface Car {
    String getColor ();
    double getSpeed ();
    void accelerate ();
}

class BMW implements Car {
    @Override
    public void accelerate () {
        this.speed += 20;
        System.out.println ("BMW");
    }
    @Override
    public String getColor () {
        return this.color;
    }
    @Override
    public double getSpeed () {
        return this.speed;
    }
    @Override
    public String toString () {
        return "BMW [màu: " + color + " tốc độ : speed + " ]"
    }
}

```



```

class Civic implements Car {
    private String color;
    private double Speed;
    public Civic (String color, double Speed) {
        this.color = color;
        this.Speed = Speed;
    }
    @Override
    public void accelerate () {
        this.Speed += 15;
        System.out.println ("Civic");
    }
    @Override
    public String getColor () {
        return this.color;
    }
    @Override
    public double getSpeed () {
        return this.Speed;
    }
    @Override
    public String toString () {
        return "Civic [Mau: " + color + ", tốc độ: " + Speed
        + "]";
    }
}

```